Lwarp

LaTeX HTML5

The lwarp package

LaTeX to HTML

v0.72 — 2019/06/08

© 2016–2019 Brian Dunn
bd@BDTechConcepts.com

Abstract

The lwarp package converts LaTeX to HTML by using LaTeX to process the user's document and directly generate HTML tags. External utility programs are only used for the final conversion of text and images. Math may be represented by SVG images or MathJax. Hundreds of LaTeX packages are supported.

Documents may be produced by DVI or PDF LaTeX, LuaLaTeX, XeLaTeX; by several CJK engines, classes, and packages; or by customized systems such as perltex and pythontex. A *texlua* script automates compilation, index, glossary, and batch image processing, and also supports *latexmk*. Configuration is semi-automatic at the first manual compile. Support files are self-generated. Print and HTML versions of each document may coexist.

Assistance is provided for HTML import into EPUB conversion software and word processors.

Requirements include the commonly-available Poppler utilities (included with MiKTeX) and Perl. Detailed installation instructions are included for each of the major operating systems and TeX distributions.

A quick-start tutorial is provided, as well as extensive documentation for special cases, a general index, and a troubleshooting index. Automatic error testing is provided for configuration files, package load order, and image generation.

SVG math and many other generated images include LaTeX expressions in the `alt` tags. MathJax may be used with advanced equation numbering under the direct control of lwarp.

Complicated tables are supported, which copy/paste well into LibreOffice Writer.

Supported classes and packages include memoir and koma-script, cleveref, caption, mdframed, siunitx, and many popular packages for tabulars, floats, graphics, theorems, the title page, bibliography, indexing, footnotes, and editorial work.

TeX is a self-modifying tokenized macro-expansion language. Since lwarp is written directly in LaTeX, it is able to interpret the document's meaning at a deeper level than external conversions which merely approximate TeX. HTML5 and CSS3 are leveraged to provide advanced features such as booktabs trim, multicolumns, side-by-side minipages, and JavaScript-free navigation.

For a list of supported features, see table 2: Supported packages and features.

To update existing projects, see section 1: Updates.

Lwarp is still in development. Changes are likely.

License:

This work may be distributed and/or modified under the conditions of the LaTeX Project Public License, either version 1.3 of this license or (at your option) any later version. The latest version of this license is in http://www.latex-project.org/lppl.txt and version 1.3 or later is part of all distributions of LaTeX version 2005/12/01 or later.

Support TEX development

TEX and related projects:

- are mostly open-sourced and a volunteer effort;
- benefit students, academics, scientists, engineers, and businesses;
- help drive education, public and private research, and commercial activity;
- are used in the fields of mathematics, science, engineering, and humanities;
- are international in reach;
- span decades of development;
- are enduring — many older packages are still actively used and maintained;
- are largely backwards compatible;
- are portable across all the major computing platforms;
- are usable even on older computers and away from internet access;
- are continuing to maintain relevance with modern improvements;
- require no yearly subscription fees;
- and are supported by an active community of knowledgeable volunteers.

Please consider helping by joining and/or contributing to the TEX Users Group, a United States 501(c)(3) tax-exempt charitable organization. Contributions are accepted by credit card, check, or Pay Pal, via the United Way, or by USA or European bank transfer. Membership in TUG supports the development of TEXLive, the major TEX distribution.

Donations may be directed towards individual projects:

TUG Bursary Fund: Assistance for attending annual TUG meetings.
CTAN: The Comprehensive TEX Archive Network — Central storage for TEX.
TeX Development Fund: Support for specific projects.
EduTeX: Teaching and using TEX in schools and universities.
GUST e-foundry fonts: Enhanced for math and additional language groups.
LaTeX Project: Modernizing the LATEX core.
Libre Font Fund: Fonts, tools (FontForge), and distribution (the Open Font Library).
LuaTeX: Combining the pdfTEX engine and the Lua language.
MetaPost: Postscript graphics.
MacTeX: TEX for Mac.
PDF Accessibility: Modern PDF standards.
Other: Additional projects may be specified.

To make a contribution: https://www.tug.org/donate.html

For country-specific TEX users groups: http://tug.org/usergroups.html

For users of MiKTEX: https://miktex.org/donations.html

Contents

Support TEX development **2**

List of Figures **38**

List of Tables **38**

1 Updates **39**

2 Introduction **60**

2.1 Typesetting conventions 62

2.2 Supported packages and features 63

3 Alternatives **69**

3.1 internet class 69

3.2 TEX4HT 69

3.3 Translators 69

3.4 AsciiDoc and Asciidoctor 70

3.4.1 Asciidoctor-LATEX 70

3.5 Pandoc 70

3.6 Word processors 70

3.7 Commercial systems 70

3.8 Comparisons 70

4 Installation **72**

4.1 Installing the lwarp package 74

4.2 Installing the *lwarpmk* utility 75

4.2.1 Using a local copy of *lwarpmk* 77

4.3 Installing additional utilities 77

5 Tutorial **79**

5.1 Starting a new project 79

5.2 Compiling the print version with *lwarpmk* 83

5.3 Compiling the HTML version with *lwarpmk* 84

5.4 Generating the SVG images 85

5.5 Using MathJax for math 86

5.6 Changing the CSS style . . . 87
5.7 Customizing the HTML output . . . 87
5.8 Using *latexmk* . . . 88
5.9 Using XeLaTeX or LuaLaTeX . . . 89
5.10 Using DVI LaTeX . . . 89
5.11 Using a glossary . . . 90
5.11.1 gloss package . . . 90
5.11.2 glossaries package . . . 90
5.12 Cleaning auxiliary files . . . 91
5.13 Cleaning auxiliary and output files . . . 91
5.14 Cleaning the images from the `<project>-images` directory . . . 91
5.15 Converting PDF or EPS images to SVG . . . 91
5.16 Creating HTML from an incomplete compile . . . 91
5.17 Processing multiple projects in the same directory . . . 91
5.18 Using the *make* utility . . . 92
6 Converting an existing document . . . 93
7 Additional details . . . 94
7.1 Shell escape . . . 94
7.2 Font and UTF-8 support . . . 94
7.2.1 Indexes, glossaries, and encoding . . . 95
7.3 lwarp package loading and options . . . 96
7.4 Customizing the HTML output . . . 100
7.4.1 Example HTML file naming . . . 105
7.5 Customizing the CSS . . . 106
7.6 Selecting the operating system . . . 107
7.7 Selecting actions for print or HTML output . . . 108
7.8 Commands to be placed into the `warpprint` environment . . . 109
7.9 Title page . . . 109
7.10 HTML page meta descriptions . . . 110

7.11 HTML homepage meta title . . . 110
7.12 HTML page meta author . . . 111
8 Special cases and limitations . . . 111
8.1 Things to avoid . . . 111
8.1.1 Invalid HTML . . . 112
8.2 Formatting . . . 112
8.2.1 Text formatting . . . 112
8.2.2 Horizontal space . . . 112
8.2.3 Text alignment . . . 112
8.2.4 Accents . . . 113
8.2.5 textcomp package . . . 113
8.2.6 Superscripts and other non-math uses of math mode . . . 113
8.2.7 Empty \item followed by a new line of text or a nested list: . . . 113
8.2.8 Filenames and URLs in lists or footnotes . . . 113
8.2.9 relsize package . . . 113
8.3 Boxes and minipages . . . 114
8.3.1 Marginpars . . . 114
8.3.2 Save Boxes . . . 114
8.3.3 Minipages . . . 114
8.3.4 Side-by-side minipages . . . 115
8.3.5 Framed minipages and other environments . . . 115
8.3.6 fancybox package . . . 116
8.3.7 mdframed package . . . 117
8.4 Section names . . . 118
8.5 Cross-references . . . 119
8.5.1 Page references . . . 119
8.5.2 cleveref and varioref packages . . . 119
8.5.3 Hyperlinks, hyperref, and url . . . 120
8.5.4 Footnotes and page notes . . . 120

8.6 Front and back matter . . . 121
8.6.1 Custom classes with multiple authors and affiliations . . . 121
8.6.2 Starred chapters and sections . . . 122
8.6.3 abstract package . . . 122
8.6.4 titling and authblk . . . 122
8.6.5 tocloft package . . . 123
8.6.6 appendix package . . . 123
8.6.7 pagenote package . . . 123
8.6.8 endnotes package . . . 123
8.6.9 BibTeX . . . 123
8.6.10 gloss package . . . 124
8.6.11 glossaries package . . . 124
8.6.12 nomencl package . . . 125
8.6.13 Indexing overview . . . 125
8.6.14 Indexing with basic LaTeX and makeidx . . . 125
8.6.15 Indexing with index . . . 126
8.6.16 Indexing with splitidx . . . 127
8.6.17 Indexing with imakeidx . . . 129
8.6.18 Indexes with memoir . . . 132
8.6.19 Using a custom *makeindex* style file . . . 134
8.6.20 Using a custom *xindy* style file . . . 135
8.6.21 Additional indexing limitations . . . 135
8.6.22 Index positions, TOC, tocbibind . . . 136
8.7 Math . . . 137
8.7.1 Math in section names . . . 137
8.7.2 Rendering tradeoffs . . . 137
8.7.3 SVG option . . . 138
8.7.4 MathJax option . . . 138
8.7.5 Customizing MathJax . . . 139

8.7.6 MathJax limitations . . . 139
8.7.7 Catcode changes . . . 140
8.7.8 Complicated inline math objects . . . 140
8.7.9 Complicated display math objects . . . 140
8.7.10 ntheorem package . . . 141
8.7.11 siunitx package . . . 141
8.7.12 units and nicefrac packages . . . 141
8.7.13 newtxmath package . . . 141
8.8 Graphics . . . 141
8.8.1 tikz package . . . 143
8.8.2 grffile package . . . 143
8.8.3 color package . . . 143
8.8.4 xcolor package . . . 143
8.8.5 epstopdf package . . . 144
8.8.6 pstricks package . . . 144
8.8.7 pdftricks package . . . 144
8.8.8 psfrag package . . . 144
8.8.9 pstool package . . . 145
8.8.10 asymptote package . . . 145
8.8.11 overpic package . . . 145
8.8.12 Multimedia packages . . . 145
8.9 Tabbing . . . 146
8.10 Tabular . . . 146
8.10.1 tabular environment . . . 146
8.10.2 multirow package . . . 148
8.10.3 longtable package . . . 149
8.10.4 threeparttablex package . . . 150
8.10.5 supertabular and xtab packages . . . 150
8.10.6 colortbl package . . . 150

8.10.7 ctable package . . . 151
8.10.8 bigdelim package . . . 151
8.11 Floats . . . 151
8.11.1 Float contents alignment . . . 151
8.11.2 float, trivfloat, and/or algorithmicx together . . . 151
8.11.3 caption and subcaption packages . . . 151
8.11.4 subfig package . . . 152
8.11.5 floatrow package . . . 152
8.11.6 keyfloat package . . . 153
8.12 KOMA-SCRIPT classes. . . . 153
8.13 MEMOIR class . . . 153
8.14 International languages . . . 154
8.15 Miscellaneous packages . . . 154
8.15.1 verse and memoir. . . . 154
8.15.2 newclude package. . . . 155
8.15.3 babel package . . . 155
8.15.4 polyglossia package . . . 155
8.15.5 todonotes and luatodonotes packages . . . 155
8.15.6 fixme . . . 156
8.15.7 chemfig package . . . 156
8.15.8 chemformula package . . . 156
8.15.9 mhchem package . . . 156
8.15.10 xparse package. . . . 156
8.15.11 kotex package . . . 157
9 Compiling using custom shell commands . . . 158
9.1 Command options . . . 158
9.2 Literal character macros . . . 158
9.3 *latexmk* . . . 159
9.4 perltex package . . . 160

9.5 pythontex package 160
9.6 Other packages 160
9.7 *make* program 161
9.8 UTF-8 locale 161
10 EPUB conversion 162
11 Word-processor conversion 164
11.1 Activating word-processor conversion 164
11.2 Additional modifications 165
11.3 Recommendations 167
11.4 Limitations 168
12 Modifying lwarp 170
12.1 Creating a development system 170
12.2 Modifying a package for lwarp 171
12.2.1 Adding a package to the lwarp.dtx file 172
12.3 Modifying a class for lwarp 173
12.4 Testing lwarp 173
12.5 Modifying *lwarpmk* 173
13 Troubleshooting 175
13.1 lwarp package error conditions and warnings 175
13.1.1 Configuration file `lwarpmk.conf` 175
13.1.2 Image generation with **`lwarpmk limages`** 175
13.1.3 Default bitmapped font 176
13.1.4 Packages 176
13.1.5 Compiling 176
13.2 Using the lwarp package 177
13.2.1 Debug tracing output 180
13.3 Compiling the `lwarp.dtx` file 181
14 Trademarks 182

1 lwarp.sty 183

15 Implementation. 183

16 Section depths and HTML headings. 184

17 Source code 185

18 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex* 186

19 Early package requirements 186

20 Package load order 186

20.1 Tests of package load order 187

20.2 Error for disallowed packages and classes loaded before lwarp . . 189

20.3 Enforcing package loading after lwarp 190

21 MD5 hashing. 199

22 pdfLATEX T1 and UTF-8 encoding. 199

23 Unicode input characters 200

24 Avoid a bitmapped font 200

25 Upright quotes 201

26 Miscellaneous tools 201

27 Operating-System portability. 203

27.1 Literal characters 203

27.2 Common portability code. 204

27.3 UNIX, LINUX, and MAC OS. 204

27.4 MS-WINDOWS 204

28 Package options. 205

28.1 Additional options support 209

28.2 Conditional compilation 211

29 Required packages. 212

30 Loading packages 216

31 Additional required packages. 221

32 File handles 221

33 Include a file 222

34 Copying a file. 223

35 Debugging messages 223

36 Defining print and HTML versions of macros and environments . . . 224

37 HTML-conversion output modifications 229

37.1 User-level controls 229

37.2 Heading adjustments 231

38 Remembering original formatting macros 232

39 Accents 234

40 Configuration files 235

40.1 Decide whether to generate configuration files 235

40.2 <project>_html.tex 236

40.3 *lwarpmk* configuration files 236

40.3.1 Helper macros 236

40.3.2 lwarpmk.conf 242

40.3.3 <project>.lwarpmkconf. 242

40.4 lwarp.css 243

40.5 lwarp_sagebrush.css 272

40.6 lwarp_formal.css 276

40.7 sample_project.css 280

40.8 lwarp.ist 281

40.9 lwarp.xdy 281

40.10 lwarp_one_limage.cmd. 282

40.11 lwarp_mathjax.txt 283

40.12 lwarpmk.lua — lwarpmk option. 285

41 Stacks 302

41.1 Assigning depths 302

41.2 Closing actions 303

41.3 Closing depths. 303

41.4 Pushing and popping the stack 304

42 Data arrays . . . 305
43 Localizing catcodes . . . 306
44 Localizing dynamic math . . . 307
45 HTML entities. . . . 308
46 HTML filename generation . . . 308
47 Homepage link . . . 311
48 \LWRPrintStack diagnostic tool . . . 312
49 Closing stack levels . . . 313
50 PDF pages and styles . . . 314
51 HTML tags, spans, divs, elements. . . . 315
51.1 Mapping LaTeX sections to HTML sections . . . 315
51.2 Babel-French tag modifications . . . 315
51.3 HTML output formatting . . . 316
51.4 HTML tags . . . 317
51.5 Block tags and comments . . . 318
51.6 Div class and element class . . . 319
51.7 Single-line elements . . . 321
51.8 HTML5 semantic elements . . . 321
51.9 High-level block and inline classes . . . 321
51.10 Closing HTML tags . . . 323
52 Paragraph handling . . . 324
53 Paragraph start/stop handling . . . 328
54 Indentfirst . . . 330
55 Page headers and footers . . . 331
56 CSS . . . 331
57 MathJax script . . . 332
58 Title, HTML meta author, HTML meta description. . . . 332
59 Footnotes . . . 333
59.1 Regular page footnotes . . . 334

59.2 Minipage footnotes . . . 335
59.3 Titlepage thanks . . . 335
59.4 Regular page footnote implementation . . . 335
59.5 Minipage footnote implementation . . . 337
59.6 Printing pending footnotes . . . 338
60 Marginpars . . . 340
61 Splitting HTML files . . . 341
61.1 Customizing MathJax . . . 346
62 Sectioning . . . 351
62.1 User-level starred section commands . . . 351
62.2 Book class commands . . . 352
62.3 Sectioning support macros . . . 352
62.4 Pre- and post- sectioning names . . . 359
62.5 \section and friends . . . 360
63 Starting a new file . . . 361
64 Starting HTML output . . . 365
65 Ending HTML output . . . 368
66 Title page . . . 370
66.1 Setting the title, etc. . . . 370
66.2 \if@titlepage . . . 371
66.3 Changes for \affiliation . . . 372
66.4 Printing the thanks . . . 373
66.5 Printing the title, etc. in HTML . . . 373
66.6 Printing the title, etc. in print form . . . 374
66.7 \maketitle for HTML output . . . 375
66.8 \published and \subtitle . . . 378
67 Abstract . . . 379
68 Quote and verse . . . 379
68.1 Attributions . . . 379

68.2 Quotes, quotations 380
68.3 Verse 380
68.3.1 LaTeX core verse environment 381
68.3.2 verse and memoir 381
69 Verbatim and tabbing 382
70 Theorems 384
71 Lists 385
71.1 List environment 386
71.2 Itemize 389
71.3 Enumerate 390
71.4 Description 390
71.5 Patching the lists 391
72 Tabular 392
72.1 Limitations 392
72.2 Temporary package-related macros 394
72.2.1 arydshln 394
72.3 Token lookahead 394
72.4 Tabular variables 395
72.5 Handling &, @, !, and bar 398
72.5.1 Handling & 400
72.5.2 Filling an unfinished row 401
72.6 Handling \\ 402
72.7 Looking ahead in the column specifications 403
72.8 Parsing @, >, <, !, bar columns 404
72.9 Parsing 'l', 'c', or 'r' columns 408
72.10 Parsing 'p', 'm', or 'b' columns 408
72.11 Parsing 'w' columns 408
72.12 Parsing '*' columns 409
72.13 Parsing 'D' columns 409

72.14 Expanding the star column specifiations . . . 409
72.15 Parsing the column specifications . . . 411
72.16 colortbl and xparse tabular color support . . . 416
72.17 Starting a new row . . . 417
72.18 Printing vertical bar tags . . . 418
72.19 Printing at or bang tags . . . 418
72.20 Data opening tag . . . 419
72.21 Midrules . . . 421
72.22 Cell colors . . . 427
72.23 Multicolumns . . . 431
72.23.1 Parsing multicolumns . . . 431
72.23.2 Multicolumn factored code . . . 434
72.23.3 Multicolumn . . . 437
72.23.4 Longtable captions . . . 438
72.23.5 Counting HTML tabular columns . . . 440
72.24 Multirow if not loaded . . . 441
72.25 Multicolumnrow . . . 442
72.26 Utility macros inside a table . . . 443
72.27 Special-case tabular markers . . . 443
72.28 Checking for a new table cell . . . 444
72.29 \mrowcell . . . 447
72.30 \mcolrowcell . . . 447
72.31 HTML tabular environment . . . 448
73 Cross-references . . . 454
73.1 Setup . . . 455
73.2 New lwarp labels. . . . 455
73.3 Labels . . . 458
73.4 References . . . 459
73.5 Hyper-references . . . 461

74 Floats 465
74.1 Float environment 465
74.2 Float tracking 467
74.3 Caption inside a float environment 469
74.4 Caption and LOF linking and tracking 469
75 Table of Contents, LOF, LOT 472
75.1 Reading and printing the TOC 473
75.2 High-level TOC commands 475
75.3 Side TOC 476
75.4 Low-level TOC line formatting 477
76 Index and glossary 481
77 Bibliography presentation 484
78 Restoring original formatting 485
79 Math 486
79.1 Limitations 486
79.1.1 Math in section names 486
79.1.2 Rendering tradeoffs 487
79.1.3 SVG option 487
79.1.4 MathJax option 488
79.1.5 Customizing MathJax 488
79.1.6 MathJax limitations 488
79.1.7 Catcode changes 489
79.1.8 Complicated inline math objects 489
79.1.9 Complicated display math objects 490
79.2 HTML `alt` tag names 490
79.3 Inline and display math 490
79.4 MathJax support 501
79.5 Equation environment 503
79.6 `\displaymathnormal` and `\displaymathother` 506

79.7 AMS Math environments . . . 507
79.7.1 Support macros . . . 507
79.7.2 Environment patches . . . 509
80 Lateximages . . . 511
80.1 Description . . . 511
80.2 Support counters and macros . . . 512
80.3 Font size . . . 513
80.4 Sanitizing math expressions for HTML . . . 513
80.5 Equation numbers . . . 515
80.6 HTML alt tags . . . 516
80.7 lateximage environment . . . 517
81 center, flushleft, flushright . . . 522
82 Preloaded packages . . . 524
83 siunitx . . . 525
84 Graphics print-mode modifications . . . 526
84.1 General limitations . . . 526
84.2 Print-mode modifications . . . 528
85 xcolor boxes . . . 528
86 chemmacros environments . . . 531
87 cleveref . . . 532
88 picture environment . . . 535
89 Minipages and Boxes . . . 535
89.1 Counters and lengths . . . 536
89.2 Footnote handling . . . 537
89.3 Minipage handling . . . 537
89.4 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox . . . 541
90 Direct formatting . . . 546
91 Skips, spaces, font sizes . . . 559
92 \phantomsection . . . 566

93 \LaTeX and other logos . . . 567
94 \AtBeginDocument, \AtEndDocument . . . 570
95 Loading KOMA-SCRIPT class patches . . . 570
96 Loading MEMOIR class patches . . . 571
97 ut* class patches . . . 571
98 CTEX patches . . . 572
99 kotexutf patches . . . 573

2 lwarp-2in1.sty . . . 574
3 lwarp-2up.sty . . . 574
4 lwarp-a4.sty . . . 574
5 lwarp-a4wide.sty . . . 575
6 lwarp-a5comb.sty . . . 575
7 lwarp-abstract.sty . . . 575
8 lwarp-academicons.sty . . . 577
9 lwarp-accsupp.sty . . . 578
10 lwarp-acro.sty . . . 578
11 lwarp-acronym.sty . . . 580
12 lwarp-adjmulticol.sty . . . 581
13 lwarp-addlines.sty . . . 582
14 lwarp-afterpage.sty . . . 582
15 lwarp-algorithm2e.sty . . . 582
16 lwarp-algorithmicx.sty . . . 586
17 lwarp-alltt.sty . . . 587
18 lwarp-amsmath.sty . . . 587
19 lwarp-amsthm.sty . . . 590
20 lwarp-anonchap.sty . . . 594
21 lwarp-anysize.sty . . . 595

22 lwarp-appendix.sty 595
23 lwarp-ar.sty 595
24 lwarp-arabicfront.sty 597
25 lwarp-array.sty 597
26 lwarp-arydshln.sty 598
27 lwarp-asymptote.sty 600
28 lwarp-atbegshi.sty 600
29 lwarp-attachfile.sty 601
30 lwarp-attachfile2.sty 602
31 lwarp-authblk.sty 604
32 lwarp-autonum.sty 605
33 lwarp-axessibility.sty 606
34 lwarp-axodraw2.sty 606
35 lwarp-backnaur.sty 607
36 lwarp-backref.sty 608
37 lwarp-balance.sty 608
38 lwarp-bbding.sty 608
39 lwarp-biblatex.sty 613
40 lwarp-bibunits.sty 614
41 lwarp-bigdelim.sty 614
42 lwarp-bigfoot.sty 615
43 lwarp-bigstrut.sty 616
44 lwarp-bitpattern.sty 616
45 lwarp-blowup.sty 616
46 lwarp-booklet.sty 617
47 lwarp-bookmark.sty 617
48 lwarp-booktabs.sty 618

49 lwarp-bophook.sty 619
50 lwarp-bounddvi.sty 619
51 lwarp-boxedminipage2e.sty 620
52 lwarp-breakurl.sty 620
53 lwarp-breqn.sty 621
54 lwarp-bsheaders.sty 622
55 lwarp-bxpapersize.sty 622
56 lwarp-bytefield.sty 623
57 lwarp-cancel.sty 623
58 lwarp-canoniclayout.sty 624
59 lwarp-caption.sty 624
60 lwarp-cases.sty 627
61 lwarp-changebar.sty 628
62 lwarp-changelayout.sty 628
63 lwarp-changepage.sty 629
64 lwarp-changes.sty 630
65 lwarp-chappg.sty 632
66 lwarp-chapterbib.sty 632
67 lwarp-chemfig.sty 633
68 lwarp-chemformula.sty 634
69 lwarp-chemgreek.sty 639
70 lwarp-chemmacros.sty 640
168 chemmacros 640
168.1 Changes to the user's document 640
168.2 Code 640
168.3 Loading modules 640
168.4 New environments 641

168.5 Acid-base . . . 641
168.6 Charges . . . 643
168.7 Nomenclature . . . 643
168.8 Particles . . . 645
168.9 Phases . . . 646
168.10 Mechanisms . . . 647
168.11 Newman . . . 649
168.12 Orbital . . . 649
168.13 Reactions . . . 650
168.14 Redox . . . 650
168.15 Scheme . . . 651
168.16 Spectroscopy . . . 651
168.17 Thermodynamics . . . 655

71 lwarp-chemnum.sty . . . 657
72 lwarp-chkfloat.sty . . . 658
73 lwarp-chngpage.sty . . . 658
74 lwarp-cite.sty . . . 659
75 lwarp-CJK.sty . . . 659
76 lwarp-CJKutf8.sty . . . 659
77 lwarp-clrdblpg.sty . . . 660
78 lwarp-cmdtrack.sty . . . 660
79 lwarp-color.sty . . . 660
80 lwarp-colortbl.sty . . . 660
81 lwarp-continue.sty . . . 662
82 lwarp-copyrightbox.sty . . . 662
83 lwarp-crop.sty . . . 663
84 lwarp-ctable.sty . . . 663
85 lwarp-cuted.sty . . . 666

86 lwarp-cutwin.sty 666
87 lwarp-dblfloatfix.sty 667
88 lwarp-dblfnote.sty 667
89 lwarp-dcolumn.sty 668
90 lwarp-diagbox.sty 668
91 lwarp-dingbat.sty 669
92 lwarp-dprogress.sty 670
93 lwarp-draftcopy.sty 671
94 lwarp-draftfigure.sty 671
95 lwarp-draftwatermark.sty 671
96 lwarp-easy-todo.sty 672
97 lwarp-ebook.sty 673
98 lwarp-ed.sty 673
99 lwarp-ellipsis.sty 674
100 lwarp-embrac.sty 674
101 lwarp-emptypage.sty 675
102 lwarp-endfloat.sty 675
103 lwarp-endheads.sty 676
104 lwarp-endnotes.sty 676
105 lwarp-enumerate.sty 677
106 lwarp-enumitem.sty 677
107 lwarp-epigraph.sty 678
108 lwarp-epsfig.sty 679
109 lwarp-epstopdf.sty 680
110 lwarp-epstopdf-base.sty 680
111 lwarp-eqlist.sty 681
112 lwarp-eqparbox.sty 681

113 lwarp-errata.sty 682
114 lwarp-eso-pic.sty 684
115 lwarp-eurosym.sty 684
116 lwarp-everypage.sty 685
117 lwarp-everyshi.sty 685
118 lwarp-extramarks.sty 685
119 lwarp-fancybox.sty 686
120 lwarp-fancyhdr.sty 691
121 lwarp-fancyref.sty 692
122 lwarp-fancytabs.sty 693
123 lwarp-fancyvrb.sty 693
124 lwarp-figcaps.sty 699
125 lwarp-figsize.sty 699
126 lwarp-fitbox.sty 700
127 lwarp-fix2col.sty 700
128 lwarp-fixme.sty 700
129 lwarp-fixmetodonotes.sty 702
130 lwarp-flafter.sty 702
131 lwarp-flippdf.sty 702
132 lwarp-float.sty 703
133 lwarp-floatflt.sty 704
134 lwarp-floatpag.sty 705
135 lwarp-floatrow.sty 705
136 lwarp-fltrace.sty 710
137 lwarp-flushend.sty 711
138 lwarp-fnbreak.sty 711
139 lwarp-fncychap.sty 711

140 lwarp-fnlineno.sty 712
141 lwarp-fnpara.sty 712
142 lwarp-fnpos.sty 712
143 lwarp-fontawesome.sty 713
144 lwarp-fontawesome5.sty 714
145 lwarp-fontaxes.sty 715
146 lwarp-fontenc.sty 716
147 lwarp-footmisc.sty 716
148 lwarp-footnote.sty 717
149 lwarp-footnotebackref.sty 718
150 lwarp-footnotehyper.sty 718
151 lwarp-footnoterange.sty 718
152 lwarp-footnpag.sty 719
153 lwarp-foreign.sty 719
154 lwarp-forest.sty 719
155 lwarp-framed.sty 720
156 lwarp-ftcap.sty 722
157 lwarp-ftnright.sty 722
158 lwarp-fullminipage.sty 723
159 lwarp-fullpage.sty 723
160 lwarp-fullwidth.sty 723
161 lwarp-fwlw.sty 724
162 lwarp-gentombow.sty 724
163 lwarp-geometry.sty 724
164 lwarp-gloss.sty 725
165 lwarp-glossaries.sty 725
166 lwarp-gmeometric.sty 727

167 lwarp-graphics.sty 728

265 graphics 728

265.1 Graphics extensions 728

265.2 Length conversions and graphics options 729

265.3 Printing HTML styles 731

265.4 \includegraphics 732

265.5 Boxes 737

168 lwarp-graphicx.sty 740

169 lwarp-grffile.sty 740

170 lwarp-grid.sty 741

171 lwarp-grid-system.sty 741

172 lwarp-gridset.sty 741

173 lwarp-hang.sty 742

174 lwarp-hanging.sty 743

175 lwarp-hypbmsec.sty 744

176 lwarp-hypcap.sty 744

177 lwarp-hypdestopt.sty 745

178 lwarp-hypernat.sty 745

179 lwarp-hyperref.sty 745

180 lwarp-hyperxmp.sty 750

181 lwarp-hyphenat.sty 751

182 lwarp-idxlayout.sty 751

183 lwarp-ifoddpage.sty 752

184 lwarp-imakeidx.sty 753

185 lwarp-index.sty 757

186 lwarp-inputtrc.sty 758

187 lwarp-intopdf.sty 759

188 lwarp-karnaugh-map.sty 759
189 lwarp-keyfloat.sty 762
190 lwarp-layaureo.sty 768
191 lwarp-layout.sty 768
192 lwarp-layouts.sty 768
193 lwarp-leading.sty 771
194 lwarp-letterspace.sty 771
195 lwarp-lettrine.sty 771
196 lwarp-lineno.sty 772
197 lwarp-lips.sty 775
198 lwarp-listings.sty 775
199 lwarp-listliketab.sty 779
200 lwarp-lltjext.sty 779
201 lwarp-longtable.sty 780
202 lwarp-lscape.sty 783
203 lwarp-ltablex.sty 784
204 lwarp-ltcaption.sty 784
205 lwarp-ltxgrid.sty 785
206 lwarp-ltxtable.sty 785
207 lwarp-lua-check-hyphen.sty 785
208 lwarp-lua-visual-debug.sty 786
209 lwarp-luacolor.sty 786
210 lwarp-luatodonotes.sty 786
211 lwarp-magaz.sty 788
212 lwarp-makeidx.sty 788
213 lwarp-manyfoot.sty 789
214 lwarp-marginal.sty 791

215 lwarp-marginfit.sty 791
216 lwarp-marginfix.sty 791
217 lwarp-marginnote.sty 792
218 lwarp-marvosym.sty 792
219 lwarp-mathtools.sty 793
220 lwarp-mcaption.sty 793
221 lwarp-mdframed.sty 794
319 mdframed 794
319.1 Limitations 794
319.2 Package loading 795
319.3 Patches 795
319.4 Initial setup 795
319.5 Color and length HTML conversion 796
319.6 Environment encapsulation 796
319.7 Mdframed environment 797
319.8 Titles and subtitles 798
319.9 New environments 800
222 lwarp-media9.sty 803
223 lwarp-memhfixc.sty 805
224 lwarp-metalogo.sty 805
225 lwarp-metalogox.sty 806
226 lwarp-mhchem.sty 806
227 lwarp-microtype.sty 809
228 lwarp-midfloat.sty 809
229 lwarp-midpage.sty 810
230 lwarp-minibox.sty 810
231 lwarp-minitoc.sty 811
232 lwarp-morefloats.sty 811

233 lwarp-moreverb.sty 811
234 lwarp-movie15.sty 813
235 lwarp-mparhack.sty 814
236 lwarp-multicap.sty 814
237 lwarp-multicol.sty 815
238 lwarp-multicolrule.sty 816
239 lwarp-multimedia.sty 816
240 lwarp-multirow.sty 817
241 lwarp-multitoc.sty 821
242 lwarp-musicography.sty 821
243 lwarp-nameauth.sty 823
244 lwarp-nameref.sty 824
245 lwarp-natbib.sty 824
246 lwarp-nccfancyhdr.sty 825
247 lwarp-needspace.sty 826
248 lwarp-nextpage.sty 826
249 lwarp-nfssext-cfr.sty 827
250 lwarp-nicefrac.sty 835
251 lwarp-niceframe.sty 836
252 lwarp-nomencl.sty 836
253 lwarp-nonfloat.sty 837
254 lwarp-nonumonpart.sty 837
255 lwarp-nopageno.sty 837
256 lwarp-notes.sty 838
257 lwarp-notespages.sty 838
258 lwarp-nowidow.sty 839

259 lwarp-ntheorem.sty 839

357 ntheorem 839

357.1 Limitations 840

357.2 Options 840

357.3 Remembering the theorem style 841

357.4 HTML cross-referencing 843

357.5 \newtheoremstyle 844

357.6 Standard styles 844

357.7 Additional objects 845

357.8 Renewed standard configuration 846

357.9 amsthm option 847

357.10 Ending a theorem 849

357.11 \NoEndMark 850

357.12 List-of 850

357.13 Symbols 850

357.14 Cross-referencing 851

260 lwarp-octave.sty 851

261 lwarp-overpic.sty 852

262 lwarp-pagegrid.sty 853

263 lwarp-pagenote.sty 853

264 lwarp-pagesel.sty 853

265 lwarp-paralist.sty 853

266 lwarp-parnotes.sty 854

267 lwarp-parskip.sty 855

268 lwarp-pbox.sty 855

269 lwarp-pdfcomment.sty 856

270 lwarp-pdfcrypt.sty 856

271 lwarp-pdflscape.sty 856

272 lwarp-pdfmarginpar.sty 857
273 lwarp-pdfpages.sty 857
274 lwarp-pdfprivacy.sty 859
275 lwarp-pdfrender.sty 860
276 lwarp-pdfsync.sty 860
277 lwarp-pdftricks.sty 860
278 lwarp-pdfx.sty 861
279 lwarp-perpage.sty 861
280 lwarp-pfnote.sty 862
281 lwarp-phfqit.sty 863
282 lwarp-pifont.sty 863
283 lwarp-placeins.sty 864
284 lwarp-plarydshln.sty 864
285 lwarp-plext.sty 864
286 lwarp-plextarydshln.sty 865
287 lwarp-plextcolortbl.sty 865
288 lwarp-prelim2e.sty 866
289 lwarp-prettyref.sty 866
290 lwarp-preview.sty 866
291 lwarp-psfrag.sty 867
292 lwarp-psfragx.sty 867
293 lwarp-pst-eps.sty 868
294 lwarp-pstool.sty 868
295 lwarp-pstricks.sty 869
296 lwarp-pxatbegshi.sty 869
297 lwarp-pxeveryshi.sty 869
298 lwarp-pxftnright.sty 870

299 lwarp-pxjahyper.sty 870
300 lwarp-quotchap.sty 870
301 lwarp-quoting.sty 871
302 lwarp-ragged2e.sty 872
303 lwarp-realscripts.sty 872
304 lwarp-refcheck.sty 873
305 lwarp-register.sty 874
306 lwarp-relsize.sty 874
307 lwarp-repeatindex.sty 876
308 lwarp-resizegather.sty 877
309 lwarp-rmpage.sty 877
310 lwarp-romanbar.sty 877
311 lwarp-romanbarpagenumber.sty 877
312 lwarp-rotating.sty 878
313 lwarp-rotfloat.sty 878
314 lwarp-rviewport.sty 879
315 lwarp-savetrees.sty 879
316 lwarp-scalefnt.sty 880
317 lwarp-schemata.sty 880
318 lwarp-scrextend.sty 880
319 lwarp-scrhack.sty 883
320 lwarp-scrlayer.sty 883
321 lwarp-scrlayer-notecolumn.sty 885
322 lwarp-scrlayer-scrpage.sty 885
323 lwarp-scrpage2.sty 886
324 lwarp-section.sty 887
325 lwarp-sectionbreak.sty 888

326 lwarp-sectsty.sty 889
327 lwarp-semantic-markup.sty 889
328 lwarp-setspace.sty 890
329 lwarp-shadow.sty 891
330 lwarp-shapepar.sty 892
331 lwarp-showidx.sty 892
332 lwarp-showkeys.sty 892
333 lwarp-showtags.sty 893
334 lwarp-sidecap.sty 893
335 lwarp-sidenotes.sty 894
336 lwarp-SIunits.sty 895
337 lwarp-siunitx.sty 896
338 lwarp-slantsc.sty 901
339 lwarp-soul.sty 901
340 lwarp-soulpos.sty 903
341 lwarp-soulutf8.sty 903
342 lwarp-splitidx.sty 904
343 lwarp-srcltx.sty 905
344 lwarp-srctex.sty 906
345 lwarp-stabular.sty 906
346 lwarp-stfloats.sty 906
347 lwarp-struktex.sty 907
348 lwarp-subcaption.sty 907
349 lwarp-subfig.sty 908
350 lwarp-subfigure.sty 913
351 lwarp-supertabular.sty 913
352 lwarp-syntonly.sty 915

353 lwarp-tabfigures.sty 915
354 lwarp-tablefootnote.sty 915
355 lwarp-tabls.sty 916
356 lwarp-tabularx.sty 916
357 lwarp-tabulary.sty 916
358 lwarp-tascmac.sty 917
359 lwarp-textarea.sty 919
360 lwarp-textcomp.sty 919
361 lwarp-textfit.sty 922
362 lwarp-textpos.sty 923
363 lwarp-theorem.sty 924
364 lwarp-thinsp.sty 927
365 lwarp-threadcol.sty 928
366 lwarp-threeparttable.sty 928
367 lwarp-threeparttablex.sty 929
368 lwarp-thumb.sty 930
369 lwarp-thumbs.sty 930
370 lwarp-tikz.sty 930
371 lwarp-titleps.sty 932
372 lwarp-titleref.sty 935
373 lwarp-titlesec.sty 935
374 lwarp-titletoc.sty 937
375 lwarp-titling.sty 938
376 lwarp-tocbasic.sty 943
377 lwarp-tocbibind.sty 943
378 lwarp-tocdata.sty 945
379 lwarp-tocenter.sty 947

380 lwarp-tocloft.sty 947
381 lwarp-tocstyle.sty 953
382 lwarp-todo.sty 953
383 lwarp-todonotes.sty 954
384 lwarp-topcapt.sty 956
385 lwarp-tram.sty 956
386 lwarp-transparent.sty 957
387 lwarp-trimclip.sty 957
388 lwarp-trivfloat.sty 958
389 lwarp-truncate.sty 959
390 lwarp-turnthepage.sty 959
391 lwarp-twoup.sty 959
392 lwarp-typearea.sty 959
393 lwarp-typicons.sty 960
394 lwarp-ulem.sty 961
395 lwarp-umoline.sty 962
396 lwarp-underscore.sty 963
397 lwarp-units.sty 963
398 lwarp-unitsdef.sty 964
399 lwarp-upref.sty 965
400 lwarp-url.sty 965
401 lwarp-uspace.sty 965
402 lwarp-verse.sty 966
403 lwarp-versonotes.sty 967
404 lwarp-vertbars.sty 968
405 lwarp-vmargin.sty 968
406 lwarp-vowel.sty 969

407 lwarp-vpe.sty 969

408 lwarp-vwcol.sty 969

409 lwarp-wallpaper.sty 971

410 lwarp-watermark.sty 972

411 lwarp-widows-and-orphans.sty 972

412 lwarp-wrapfig.sty 973

413 lwarp-xbmks.sty 974

414 lwarp-xcolor.sty 974

512 xcolor 974

512.1 Limitations 974

512.2 xcolor definitions: location and timing 975

512.3 Package loading 977

512.4 Remembering and restoring original definitions 977

512.5 HTML color style 977

512.6 HTML border 978

512.7 High-level macros 978

512.8 Row colors 983

415 lwarp-xechangebar.sty 984

416 lwarp-xellipsis.sty 984

417 lwarp-xetexko-vertical.sty 985

418 lwarp-xfakebold.sty 986

419 lwarp-xfrac.sty 986

420 lwarp-xltabular.sty 988

421 lwarp-xltxtra.sty 989

422 lwarp-xmpincl.sty 989

423 lwarp-xpiano.sty 990

424 lwarp-xpinyin.sty 990

425 lwarp-xr.sty 991

426 lwarp-xr-hyper.sty 991

427 lwarp-xtab.sty 991

428 lwarp-xunicode.sty 993

429 lwarp-xurl.sty 994

430 lwarp-xy.sty 994

431 lwarp-zhlineskip.sty 995

432 lwarp-zwpagelayout.sty 995

433 lwarp-patch-komascript.sty 997

434 lwarp-patch-memoir.sty 999

532 patch-memoir 999

532.1 Packages 1000

532.2 Preliminary setup 1001

532.3 Laying out the page 1001

532.4 Text and fonts 1003

532.5 Titles 1004

532.6 Abstracts 1004

532.7 Docment divisions 1004

532.8 Pagination and headers 1007

532.9 Paragraphs and lists 1008

532.10 Contents lists 1009

532.11 Floats and captions 1013

532.12 Page notes 1016

532.13 Decorative text 1017

532.14 Poetry 1017

532.15 Boxes, verbatims and files 1018

532.16 Cross referencing 1019

532.17 Back matter 1019

532.18 Miscellaneous 1021
532.19 ccaption emulation 1021
532.20 Final patchwork 1023
435 lwarp-common-multimedia.sty 1023
Change History 1029
534 Chg Hist 1029
Index of Objects 1057
General Index 1077
Troubleshooting Index 1081
Index of Indexes 1086

List of Figures

1 tutorial.tex listing 80

List of Tables

1 Typesetting conventions 62
2 LaTeX lwarp package — Supported features 63
3 Required software programs 73
4 Configuration files created by print version 82
5 lwarp package options 97
6 HTML settings 101
7 Literal character macros 159
8 Section HTML headings for word-processor conversion 167
9 Section depths and HTML headings 184
10 Tabular baseline 411
11 Tabular HTML column conversions 412
12 Cross-referencing data structures 456
13 Float data structures 465
14 amsthm package — CSS styling of theorems and proofs 591
15 Ntheorem package — CSS styling of theorems and proofs 839
16 Theorem package — CSS styling of theorems and proofs 924

1 Updates

The following is a summary of updates to lwarp, highlighting new features and any special changes which must be made due to improvements or modifications in lwarp itself.

For a detailed list of the most recent changes, see the end of the Change History on page 1056.

v0.72: Font control, `\multicolumn`, xr and xr-hyper.

⚠ images

- Due to internal changes, images for inline SVG math and `lateximages` will have new hash values, and will have to be regenerated using

  Enter ⇒ **`lwarpmk cleanlimages`**

  and

  Enter ⇒ **`lwarpmk limages`**

- Docs: Color-codes package names in the table of supported packages and features, table 2, according to each package's level of support by lwarp.
- `\multicolumn`: Fix for paragraph columns.

packages

- xr, xr-hyper: Fixes for references, `\externaldocument`.
- soulutf8: Fix: Loads soul for emulation.
- boxedminipage2e: Added support for `lateximages`.
- zhlineskip: Updated to v1.0e.
- Added fontaxes, slantsc, tabfigures.
- Added nfssext-cfr, thus supporting cfr-lm and several other font packages.
- Added backnaur, hypbmsec, minibox, pdfcrypt, shapepar.

v0.71: Error handling, multimedia, `tabular`.

- `tabular`: Added support for '`*`' columns. Fix for paragraph tags.
- `quotation`: Fix for HTML tag.
- Docs: Added a section about error conditions tested by lwarp. See section 13.1.
- *lwarpmk*: If file `lwarpmk.conf` is an older version, or the incorrect operating system, displays the print command to use to recompile.

packages

- chemfig: Updated for v1.4.
- endfloat: Updated for v2.7.
- textpos: Updated for v1.9.1.

multimedia

- Added media9, movie15, multimedia.

v0.70: Error handling, MathJax, mathtools.

- Error handling for "Label(s) changed." Refuses to **`lwarpmk limages`** until recompile first.
- Fix: If Computer Modern font is used, ensures cm-super or lmodern is used.
- Fixes for `\makebox`.
- Fixes for `\parbox` inside a `<span>`.
- MathJax: Updated to v2.7.5. Loads the `autoload-all.js` extension. Added `\MathJaxFilename` to select custom scripts.

packages

- textcomp, xunicode: Fix for `\textinterrobang`.
- mhchem: Works with MathJax. See section 324.
- changes: Updated to v3.1.2.
- Added autonum, changelayout, inputtrc, mathtools, metalogox.

v0.69: Error handling, many fixes, improved keyfloat / tocdata.

- Fix for HTML corruption of `lateximage` displays.
- `\makebox`, `\framebox`: Fix for (⟨*width,height*⟩) arguments.
- `fminipage`: Honors `\minipagefullwidth`.

packages

- array, longtable: Fix for `\tabularnewline`.
- tabularx, tabulary: Fix to require the array package.
- supertabular, xtab: Fix to clear caption after use.
- graphics: Added a warning if used the `\includegraphics scale` option.
- multirow: Added an error if didn't use `\mrowcell` or `\mcolrowcell` when using `\multirow` or `\multicolumnrow`.
- keyfloat: Updated for v2.00, additional improvements.
- Added ctable, eqlist, eqparbox, ftcap, listliketab, minitoc, tocdata, topcapt.

v0.68: Error handling, tabulars, footnotes.

lwarpmk

- *lwarpmk*: Improved error handling for image generation if compile was incomplete.
- `tabular`: Fix for `\warpprintonly`.

packages

- longtable: Improved flexibility for `\endhead`, etc. Improved error reporting if `\endhead`, etc. incorrect for lwarp.
- threeparttable: Fix for caption type.
- hyperref: Fix for options with braces.
- morefloats: Fix to be loaded early for print output.
- listings: Updated for v1.7.
- Added bigfoot, fnpara, footnotebackref, manyfoot, tablefootnote, threeparttablex.
- Added layouts, niceframe, perpage, showtags.
- Prevented alg, algorithmic, pdfcprot, fncylab.

v0.67: Filename generation, symbol fonts.

docs
- Documentation fix for `<project>-images`, `<project>-images.txt`.
- Added discussion regarding section names. See section 8.4.

filenames
- Added `\FilenameNullify` and `\FilenameSimplify` for filename generation. See section 8.4.
- Core, textcomp, xunicode: Nullified additional symbols during filename generation.

packages
- color: Fix for version number warnings.
- Added academicons, bbding, dingbat, eurosym, fontawesome, fontawesome5, marvosym, pifont, typicons.
- Added changes, easyReview, fitbox, foreign, gloss, karnaugh-map, multicap, nomencl, notes, struktex, umoline, xfakebold.
- Tested to work as-is with askmaps, curves, euro, karnaughmap, tikz-karnaugh.

v0.66: xr, multiple projects, image names/directory, HTML formatting

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

`lateximage`
- Adds options `ImagesDirectory` and `ImagesName` to assign directory and name prefixes for `lateximage` images. The new defaults include the jobname, allowing the image directories for multiple projects to coexist.

⚠ existing projects
- To reuse existing `lateximage` directories, add lwarp options

```
\usepackage[
  ImagesDirectory={lateximages},
  ImagesName={lateximage-}
]{lwarp}
```

  If not reused, the existing `lateximages` directory and `lateximages.txt` file may be removed.

filenames
- Added `\FilenameLimit` to control the maximum length of the filenames generated by lwarp.

⚠ Possible filename changes
- Improved filename generation when special characters or macros are used in section names.

Windows
- Fix for **`lwarpmk cleanlimages`** with WINDOWS.

floats
- Fixes for floats in the home page.

lists, table notes
- Improved css for definition lists, table notes.

`tabular`
- `tabular`: Fixes for `\par` in column specifier, minipage inside `tabular`.

indexing
- Indexing: Fix for a long line of multiple entries.

`minipage`
- `\minipagefullwidth`: Fix for global changes.
- Added `\UseMinipageWidths` and `\IgnoreMinipageWidths`. See section 8.3.3.

colors
- Improved `\fbox`, `\fboxBlock`, `\fminipage` to use current text color.

html
- Improved HTML output formatting.

docs
- Added discussion regarding invalid HTML. See section 8.1.1.

- Added discussion regarding math in section names, `\imagegraphics` `scale` option. See section 6.
- Added discussion regarding international languages in section names. See section 8.14.

packages
- caption: Fix for options clash.
- xr, xr-hyper: Now compatible.
- subcaption: Improved horizontal spacing.
- multicol: Fix for minipage inside `multicols`.
- multicolrule: Updated for v1.2.
- tocbasic: Minor update.
- acronym: Fix for acronym in float caption.
- kotexutf: Patch with *pdflatex* and new lwarp labels.
- extramarks, fancyhdr: Updated for v3.10.
- memoir: Added docs regarding version numbers. See section 8.13.
- zref: No longer required.
- Added ar, ed, indentfirst, nameauth, truncate.
- Verified to work as-is with changelog.
- Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs.

v0.65: css layout, `alt` tags, Japanese.

page layout
- Moved the sideTOC to the left side, allowing improved CSS for margin notes.
- Improved page layout CSS.

image `alt` tags
- graphicx `\includegraphics`: Added the `alt` key to assign an `alt` tag to an image. Default is "`(image)`", assigned to pass validation.

duplicate html files
- Detects and causes an error if duplicate HTML file names are generated, caused by identical or similar sectioning names.

fixes
- Fix for `tabular*`.
- Fix for tabular border colors.
- Fixes `\quad`, `\enskip`, and figure captions to pass validation.

Japanese
- Added ltj* classes, bounddvi, gentombow, lltjext, plarydshln, plext, plextarydshln, plextcolortbl, pxatbegshi, pxeveryshi, pxftnright, pxjahyper, tascmac.
- Verified to work with plarray, plautopatch, plextarray, plextdelarray, pxgentombow, plsiunitx, pxpdfpages, pxpgfrcs, pxpgfmark.

packages
- Added support for fontspec `\textsi` and `\sishape`.
- Added multicol's `\docolaction`.
- Added embrac, footnoterange, multicolrule, versonotes.

v0.64: Koma-Script, Japanese, Chinese.

Japanese
- Added utarticle and related classes.
- Improved ujarticle and related classes.

Chinese
- Fix for biblatex with CTEX and other classes.

Koma-Script
- Fixes for scrlayer, scrlayer-scrpage.

packages
- addlines: Updated to v0.3.
- Added bsheaders, gmeometric, marginal, rmpage, scrpage2.

v0.63: mdframed, Chinese, Japanese, Korean

localization
- Added `\linkhomename`: A user-definable name for the **Home** link.
- Documented `\sidetocname`: A user-definable name for the sideTOC.

fixes
- Fix: `\LinkHome` for print output.

optimizations
- Moved package load checks to the lwarp core to reduce the number of `lwarp-*` files.

packages
- mdframed: Fix with amsthm, improved titles and font control. Improved rule widths.

Chinese
- Fixes for xeCJK.
- Added xpinyin, zhlineskip.
- Verified to work with cjkpunct, upzhkinsoku, zhspacing.

Japanese
- Verified to work with zxjatype, luatexja, luatexja-fontspec.
- Added bxjsarticle and related classes.
- Added ltjsarticle and related classes.
- Added pLATEX, upLATEX, ujarticle and related classes.
- Prevented utarticle and related classes.
- Prevented bxcjkatype.

Korean
- Verified to work with kotex, xetexko, luatexko.

v0.62: MiKTEX docs, HTML title, CTEX, xeCJK, bitpattern.

docs
- Docs: Setting a UTF-8 locale. See section 9.8.

MiKTEX
- MiKTEX: Docs for *MiKTeX Console* and miktex-poppler-bin.

html `<title>`
- HTML subpage titles: Added `\HTMLTitleBeforeSection` and `\HTMLTitleAfterSection` to select whether the HTML `<title>` displays the website name before or after the section name. See section 7.4.

fixes
- Fix for package options handling.
- Fixes for horizontal white space between `fminipage`, `fcolorminipage`, `colorboxBlock`, `fcolorboxBlock`.
- Logos: Fix for XƎTEX logo, improved css, made robust, improved search-engine optimization.
- `\\[$1]`: Additional HTML `<br>` if $1 > 0 pt.
- Fixes for `\includgraphics` filename, and with `FormatWP`.
- Fix: css for `\textup`.

- Fix: Added `\slshape`.

Chinese
- Added ctex package and related classes, xeCJK.
- Prevented CJK, CJKutf8 unless xeCJK, ctex are used.

packages
- chemfig: Docs for new macro `\polymerdelim`.
- asymptote: Docs for compilation.
- chngpage: Fix to load lwarp-changepage.
- algorithm2e: Fix with non-book classes.
- register: Updated to v1.8.
- nicefrac: Improved font control and css, honors `nice` and `ugly`.
- units: Improved font control and css, honors `tight` and `loose`.
- xfrac: Improved css.
- textcomp and xunicode: Fix conflicts with `\textcircled`.
- ulem: Improved compatibility with CJKulem, `lateximage`.
- MathJax and siunitx: Removed inoperable extension.
- Added bitpattern, pdfcomment, pdfmarginpar, tram, unitsdef, xechangebar.
- Added musicography, octave, semantic-markup.
- Added 2in1, flippdf, notespages, rviewport, twoup.

v0.61: Custom compilation, EPS-related packages, documentation, indexes.

docs
- Split index into multiple indexes. See page 1086.
- Improved documentation regarding font selection. See section 7.2.
- Added documentation regarding debugging options. See section 35.
- Added documentation regarding HTML entities inside program listings. See section 8.2.1.

custom compiling
- Added options to specify the shell commands to execute for **`lwarpmk print`** and **`lwarpmk html`**, allowing the use of lwarp with perltex, pythontex, etc. If not specified, these are set automatically depending on the LaTeX engine, `--shell-escape`, and lwarp options. See section 9.

⚠ changed names
- Changed macro names to match `\displaymathother`, `\displaymathnormal`:

Old	New
`\StartDynamicMath`	`\inlinemathother`
`\StopDynamicMath`	`\inlinemathnormal`

fixes
- Fix: Paragraph tags in a `tabular`.
- Fix: supertabular and xtab captions.
- Fix: DVI LaTeX `\includegraphics` EPS images.
- Fix: newfloat lists.
- Fix: css footnotes text align, minipage tabular and footnote margins.

packages
- Added epsfig, psfrag, psfragx, pstool.
- Added copyrightbox, pdfprivacy, thinsp, threadcol, uspace.
- Added chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.

v0.60: Fixes for longtable, listings.

fixes
- longtable, etc.: Fixes for slowdown and memory management for very long tables.
- listings: Fix for HTML entities, and also when used inside a list.
- diagbox: Fix for incorrect HTML par tags.

packages
- Added 2up, booklet.
- Added bophook, draftfigure, fullminipage, grid-system, layaureo.
- Added leading, widows-and-orphans.
- Added fancytabs, thumb, thumbs.

v0.59: DVI *latex*, MathJax, asymptote, pdftricks and pstricks, epstopdf, brqen.

⚠ Reset the configuration
- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk
- Added an error if `lwarpmk.conf`'s format has changed and the document must be recompiled.
- Added a warning if the `lwarpmk.conf` configuration file appears to be for the wrong operating system, in case files are transferred between systems.
- Added
  ```
  lwarpmk epstopdf <list-of-EPS-files>
  ```
  to quickly convert a document's EPS images to PDF or SVG. See section 8.8.

dvi *latex*
- Added support for DVI *latex*. See section 7.3.

latexmk
- Fix for `--shell-escape` with *latexmk*.

math
- Updated MathJax script to v2.7.4.
- Fix: Mathjax chapter number removed from non-numeric tagged equations.
- Added MathJax support for nicefrac, units.
- Fix for `\[` and `\]` with `\displaymathnormal`.

images
- Fix for `\includegraphics` filename expansion.
- `\includegraphics` now works with `.pdf` and `.eps` filename extensions.

packages
- Moved amsmath out of the lwarp core.
- Fix for chemformula `\NMR`.
- Added asymptote, pdftricks, pstricks, pst-eps.
- Added breqn, Slunits.
- Added bxpapersize, canoniclayout, draftcopy, fnbreak, nccfancyhdr.
- Added accsupp, axessibility.
- Added xunicode.
- Improved and now supports epstopdf.
- Tested to work as-is: eepic, sepfootnotes.

docs
- Added information about setting up a development version of lwarp.

v0.58: Extensive improvements in indexing, glossaries. Adds PDF-inclusion packages.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- *lwarpmk*: Added the `-p` option to specify the project name.

glossaries

- *lwarpmk*: Now uses *makeglossaries* for glossary generation, allowing the processing of multiple glossaries at once.
- Added lwarp option `GlossaryCmd` to specify the shell command used by **`lwarpmk printglossary`** and **`lwarpmk htmlglossary`**. Defaults to **`makeglossaries`**.

index and glossary

- Docs: Extra indexing options. See section 8.6.13.
- Added support for *makeindex*. (Previously supported only *xindy*.) Also added indexing packages listed below.
- Added lwarp options `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to specify shell commands used by **`lwarpmk printindex`**, **`lwarpmk htmlindex`**, and *latexmk*. May be preset with the `makeindex` or `xindy` lwarp options. See section 7.3.
- Added lwarp options `makeindex` and `xindy` to set `PrintIndexCmd`, `HTMLIndexCmd`, and `LatexmkIndexCmd` to sensible values for a typical single index. See section 7.3.
- Added lwarp option `makeindexStyle` to tell *lwarpmk* to use a custom style instead of `lwarp.ist`. See section 8.6.19.
- Fix for index entries with `\see`, `\seealso`, `\emph`, `\textbf`, etc.

misc. fixes

- Replaced each `\csuse` with `\@nameuse` for improved error detection.
- Additional internal print/HTML macro selection improvements.
- Fix: `\printindex` finishes pending `\index` writes first.

packages

- Fixes for memoir: makeidx, ccaption, multiple indexes, `\specialindex`.
- Fixes for komascript: Indexing improvements.
- Added imakeidx, index, repeatindex, splitidx.
- Added attachfile, attachfile2, intopdf, pdfpages, pdfx.
- Added cases.
- Tested to work as-is: notes2bib, hvindex.

v0.57: algorithm2e, float styles, tabular packages, internal improvements.

MathJax

- Added support for MathJax equations with `\footnote`, `\footnotemark`.

math macros

- Added `\StartDefiningMath` and `\StopDefiningMath` for use when defining macros in the preamble which contain $. See section 8.7.7.

dynamic math

- Added `\inlinemathother` and `\inlinemathnormal` to delimit math expressions which depend on a variable condition such as a counter. Such expressions will not be hashed for reuse, and will be converted to SVG math images even when MathJax is enabled. See section 8.7.8.

⚠ new name

- Renamed `\EndDefiningTabulars` to `\StopDefiningTabulars`.

lateximage alt tags
- Improved localization for lateximage HTML alt tags. For SVG math images, the alt tag under some conditions will be set to \mathimagename, which defaults to "math image". For packages, the alt tag is set using the package name followed by \packagediagramname, which defaults to "diagram". Ex:

  ```
  (-xy- diagram)
  ```

  See section 7.4.

- Fix: Improved print/HTML macro selection.

misc. fixes
- Fix: \href text catcodes.
- Fix: \subref text.
- Fixes: Colored \rule and \boxframe.

packages
- float, rotfloat: Adds support for float styles ruled and boxed.
- float: Fix: Do not create \l@<type> until \listof is used.
- marginnote: Fix: Long optional argument.
- ellipsis: Adds \midwordellipsis.
- breakurl: Fix for text catcodes.
- Added algorithm2e, register, ltablex, xltabular, xellipsis, trimclip, errata, vowel, xpiano.
- Prevents glossary.
- Tested to work as-is with gauss, phonrule, piano, SIunits, tikzcodeblocks.

v0.56: Shell escape, tabular packages.

lwarpmk
- Added

  ```
  lwarpmk pdftosvg <list-of-PDF-files>
  ```

  to quickly convert a document's PDF images to SVG, for use with HTML. See section 8.8.

- Added support for --shell-escape. See section 7.1.

tabular
- Added support for array w and W columns.
- Fix: \multicolumn parameter handling.
- Added support for double \hlines, \midrules, and vertical rules.
- Added support for arydshln dashed lines with HTML tabular, but reverts to plain rules for lateximage and SVG math array.

misc. fixes
- Fix: \thinspace.
- Fix: paralist compact environments.

packages
- Added parnotes, quoting, lua-check-hyphen, tocenter, underscore.
- Added bibunits.
- Tested to work as-is with babelbib, bodegraph, fast-diagram, nicematrix, structmech.

v0.55: Various fixes.

misc fixes

- Fix: Extraneous space in file links, which also prevented *Calibre* EPUB conversions.
- Fix: Float optional argument regression.
- Fix: `\ForceHTMLTOC` with `\phantomsection`.
- Fix: Overfull boxes in `lateximages`.
- Fix: QED symbols in `lateximage`.

packages

- koma-script: Fix: Figure with `\centering`, etc.
- Added clrdblpg.

v0.54: Float `\centering`, improved image checks.

⚠ Reset the configuration

- Due to changes in *lwarpmk*, recompile any existing project a single time using **`pdflatex filename.tex`** or similar, after which *lwarpmk* may then be used with the new configuration files.

lwarpmk

- `lwarpmk limages` checks for the presence of the HTML version of the document and valid image references before attempting to create the `lateximages`.
- *lwarpmk*: Improved error message if configuration file does not exist.

BibTeX

- Added documentation for avoiding error with BibTeX and `\etalchar`. See section 8.6.9.

polyglossia

- Added documentation regarding polyglossia. See section 8.15.4.

macros in section names

- Added documentation regarding the use of macros in section names. See section 8.1.

document encoding

⚠ New and revised encoding options

- Renamed and added package options:

Old Package Option	New Package Option
`xdyFilename`	`xindyStyle`
`IndexLanguage`	`xindyLanguage`
–	`xindyCodepage`
–	`pdftotextEnc`

Use these options along with inputenc or inputenx to process documents in an encoding other than UTF-8. See section 7.2.

floats with `\centering`, etc.

- Floats now honor `\centering`, `\raggedright`, `\raggedleft`, and their ragged2e equivalents, when placed directly after:

```
\begin{floattype}
\centering
```

misc. fixes

- tikz: `\pgfpicture`, fit, align, font.
- ragged2e: `\centering` etc.
- hyperref: `\hypertarget` was creating duplicate of `\label`.
- hyperref: Active chars inside `\hyperref`, `\hyperlink`.
- hyperref: `\ref` inside `\hyperlink` caused a nested HTML link.
- glossaries: Fix when not using babel or polyglossia.

- textcomp: `\textperthousand`.
- LaTeX core `verse` environment: line spacing.

⚠ packages

- Removed `\citetitle`, adjusted `\attribution`.
- memoir: Minor update for v3.7g.
- Added inputenx, bibunits, chngpage, forest, magaz, gridset.
- Prevents loading ae, aecc, t1enc, and wasysym.

v0.53: Improved image checks.

lwarpmk

- *lwarpmk*: Added a warning about corrupted images due to the need to recompile the document one more time.
- *lwarpmk*: Added the **`lwarpmk cleanlimages`** command.
- Added documentation for **`lwarpmk cleanlimages`** and **`lwarpmk pdftohtml`**.

v0.52: Improved footnotes, SVG math.

documentation

- Improved install instructions regarding `lwarp_baseline_marker.png`.
- Added documentation regarding footnotes in section headings, and footnotes with `\VerbatimFootnotes` from fancybox, fancyvrb. See section 8.5.4.
- Added documentation regarding font selection when using XeLaTeX or LuaLaTeX with fontspec and traditional font packages. See section 7.2.

SVG math

- Fix: Limit the number of background tasks when generating `lateximages`.
- Added user-adjustable SVG math font scaling. See section 80.3.
- Added warnings if `lwarp_baseline_marker.png` is not present, or if graphicx or graphics is not loaded.
- Improved `\ensuremath` hashing expansion.
- Fix: `equation*` with `split`.
- `tabbing` now works inside a `lateximage`. Use for math in `tabbing`.

MathJax

- Fix: MathJax script was not executing in some conditions.
- Added `\CustomizeMathJax` to add custom functions. See section 8.7.

footnotes

- Fix: Footnote numbering when using `HTMLDebugComments`.
- Fix: Footnote paragraph tags.
- Fix: `FootnoteDepth` defaults to `\subsubsection`.

misc. fixes

- Fix: `\kill` in a `lateximage`.
- Fix: `\FileDepth`, misc. others, when input encoding is not `utf8`.
- Fix: `\texorpdfstring` in a section name.

packages

- hyperref emulation: Fix for `#`, `%`, `&`, `~`, `_` characters in URLs.
- fancybox, fancyvrb: Initial support for `\VerbatimFootnotes`.
- nicefrac: Added with fix for `\ensuremath`.
- graphicx: Fix for option defaults. Added v1.1a/b options.
- endfloat: Updated for v2.6.
- url: Fixes for active characters.

v0.51: Improved SVG math, added numerous chemistry packages.

documentation
- Docs: Added Things to avoid.
- Docs: Added to Converting an existing document.
- Docs: Multiple authors and affiliations with custom classes. See section 8.6.1.
- Docs: tikz with matrices. See section 8.8.1.

SVG math
- Improved SVG math baseline.
- Improved SVG math font and color.
- Faster SVG math rendering.
- Improved support for display math containing complicated math objects, such as tikz-cd. See section 8.7.9.
- Fix: `\addcontentsline` inside SVG math.
- Fix: SVG math containing an embedded `lateximage`.

MathJax
- MathJax now handles `\ensuremath` in expressions.

misc. fixes
- Fix: Added `alignat` environment.
- Fix: afterpackage no longer required, which conflicted with scrlfile.
- Fix: titling `\thanks` mark.
- Fix: fancybox improvements.
- Fix: tikz `\tikz` macro. (Previously only the `tikzpicture` environment worked.)
- Fix: tikz with optional argument.

packages
- Added mhchem, chemfig, chemformula, chemmacros, chemnum, chemgreek, epstopdf-base, grid, ltxgrid.

v0.50: Improved SVG math.

svg math
- SVG math and other `lateximages` now are converted to SVG using parallel background tasks, utilizing all available CPU cores.
- Inline SVG math image file names now are MD5 hashes made from their source LaTeX code. Identical inline math expressions, such as multiple instance of x, now share a single image file. This reduces the number of images to store, transmit, process, and display. Each image file is only converted to SVG a single time, and reused if it already exists. Display math and other forms of SVG image such as `picture` and Ti*k*z still use individual image files which are recreated each time **`lwarpmk limages`** is run.
- Fixes: SVG math and/or `\underline` in a sectioning file name.
- Improved SVG display math and tags.
- Improved SVG math and siunitx `alt` tags.
- Improved siunitx units.
- Fix: `\ensuremath` with MathJax now creates a `lateximage`.
- Fix: `\centering`, etc. in SVG math, `lateximage`, Ti*k*z.

misc. fixes
- Fix: Made various macros robust, additionally fixing authblk.

- Fix: ntheorem if neither `standard` nor `amsthm` selected.
- Fix: listings: Improved column alignment.
- Fix: Load fontspec if necessary.

packages
- Added xy, epstopdf, diagbox, pbox, bytefield, axodraw2, phfqit, schemata, dblfloatfix, nonfloat, morefloats.

v0.49:

tabular
- Added xcolor `\rowcolors`.
- Fix: `\noalign` inside a `tabular`.

math
- Fix: `\eqref` in a caption.

misc fixes
- Fix: Incorrect PDF font size changes caused occasional HTML corruption.
- Fix: printlen changes are now grouped for HTML output.

packages
- Added vwcol, vertbars, hyphenat, lineno, fnlineno, figsize, hypdestopt, pagegrid, pdfrender, luacolor, resizegather.

v0.48:

documentation
- Added some documentation regarding converting an existing document. See section 6.

cleveref
- Updated compatibility for new cleveref v0.21.

tabular
- Fix: Ignores optional tabular column arguments.

minor updates
- Added `\leftline`, `\centerline`, `\rightline`.
- Lists have improved font control via `\makelabel`.
- Print-mode `lateximage` now boxed to the natural width of its multiline contents.
- `abstract` now allows an optional name, as required by some classes.

math
- Fix: Improved spacing, `\mbox`, and font sizes with SVG math, Ti*k*z.
- siunitx: Improved SVG math, fraction compatibility, color output.

misc. fixes
- Fix: LOF/LOT links.
- Fix: Virtual page size grouping caused excessive PDF page breaks.
- Fix: Parsing similar package names in a single `\usepackage`.
- Fix: Adapts to classes without `\part`.
- Fix: `\newline` in `\title` was causing `<br>` in window title.
- Fix: `\maketitle` with `\cr`, `\crcr`, `\noalign`, for IEEEtran class.
- Fix: xfrac neutralized `BlockClass` and others.
- Fix: todonotes and luatodonotes: Improved `\todototoc`.

packages
- Added colortbl, chapterbib, acro, acronym, hypernat, hypcap, stfloats, vmargin, fancyheadings.
- fancyref: Now directly supported.

v0.47:

math
- Improved SVG math baseline and sizing.
- Fixes: SVGmath in captions, subcaptions, `\nameref`.
- Fixes: Line wrap at hyphen in HTML output.

packages
- Added endheads, multitoc, sectionbreak, blowup, xurl.

v0.46:

⚠ name change
- `\PrintStack` changed to `\LWRPrintStack`.

misc. fixes
- Fix: Empty lines between `tabular` rows.
- Fix: Stack unnesting.
- Fix: SVG math and `lateximages` in numerous situations.
- Fix: Spaces in `\usepackage`.
- Fix: Now allows MathJax inside `verse`.

v0.45:

documentation
- Improved *MiKTeX* install instructions.
- Improved graphics and epstopdf instructions.
- Updates to the Introduction.

memoir
- Added memoir, memhfixc. See section 8.13.

cross-references
- Fix: Now allows underscores in labels.
- Fix: `\_` and `\<blank>` in section/file names.

math
- Fix: Now allows MathJax inside `tabbing`.

bibliography
- Fix: Bibliography `\em` names.
- Added cite, natbib, backref. (Also works as-is with biblatex.)

misc. fixes
- Fix: Empty lines between `tabular` rows.
- Fix: "Improper `\prevdepth`" with minipages, lists.
- Fix: Incorrect SVG math and `lateximages` with subfig.
- Fix: Lateximages from incorrect pages with Mathjax.
- Fix: Missing sidetoc if using listings.
- Fix: Added an array emulation package.

packages
- Added subfigure, prettyref, hanging, midpage, flafter, fltrace, changebar, endfloat, continue, fwlw, turnthepage, footnpag, pagesel, textfit, titleref.

v0.44:

koma-script
- Added koma-script classes (except scrlttr2, scrjura).
- Added scrextend, scrlayer, scrlayer-notecolumn, scrlayer-scrpage, scrhack, tocstyle, tocbasic.

html title and author
- Added `\HTMLTitle`. Fixed web page title if `\HTMLTitle` empty and no `\title` given and not using titling package.
- Fixed web page author if `\HTMLauthor` is empty and `\author` is not given.

encodings
- If using *pdflatex*, automatically loads T1 and UTF-8 encodings. (Additional fontenc encodings may be loaded after lwarp.)

lists
- Added `list` and `trivlist` environments, hang.

tabular
- Fix: `\multicolumn` alignment if formatting for a word processor.
- Added ltxtable.

math
- Fix: MathJax combined with `lateximages`.
- algorithmicx: Improved comment symbol and floating.

packages
- Completed todonotes and luatodonotes.
- Added todo, easy-todo, fixmetodonotes, fixme.
- Added soulutf8, soulpos, cancel.
- Added section, fancyref, ifoddpage.
- Added preview, atbegshi, watermark.
- Improved tocloft `\newlistof` and `\newlistentry`.

v0.43:

- Docs: Reorganized HTML customization, added an HTML settings table. See section 7.4.

footnotes
- Added `FootnoteDepth` to control the placement of pending footnotes before section breaks. By default, pending footnotes are printed before each `\subparagraph` or higher.

sectioning
- Fix: Expansion in section name.

tabular
- Fix: Ignore spaces in tabular column specification.
- Fix: Tabular rules at bottom or when finishing incomplete rows.
- Fix: `\multicolumn` at/bang/before/after specifications, trim, and vertical rules.
- Fix: supertabular and xtab column misalignment.

math
- Fix: `equation*`.
- Fix: SVG math in a section name.
- Fix: `\ref` and `\eqref` in SVG math.

packages
- Added todonotes and luatodonotes (but only `disabled`).
- Added breakurl.
- hyperref: Fix: Several macros were made robust, `\Gauge` added.

v0.42:

Support TeX!
- Added TeX development support page. (See page 2.)

word-processor conversion
- Improved assitance for word-processor conversions when boolean `FormatWP` is set `true`. See section 11.

⚠ name change
  - The boolean `FormatWordProcessor` has been renamed `FormatWP`.

⚠ name change
  - The boolean `HTMLMarkFloats` has been renamed `WPMarkFloats`.
  - New booleans control whether to place additional marks around minipages, at the table of contents, at the LOF and LOT, and whether to print math as LaTeX source for copy/paste into the *LibreOffice Writer TeXMaths* extension.

  - Improved formatting for numerous objects. See section 11.

tabbing
- Add: tabbing environment.

overpic
- Add: overpic package. See section 359.

math
- Fix: Text copy/paste of $\mathcal{AMS}$ math environment numbers and names.
- Improved \ensuremath.
- MathJax with siunitx: Updated script and documentation.

symbols
- textcomp: Improved \textinterrobangdown.
- realscripts: Fix for subscripts in a lateximage.

load order
- morewrites: Enforces loading before lwarp.

v0.41:

tabular
- Added tabular vertical rules, subject to some limitations. See the rules section of section 8.10.1.
- Improved booktabs: Width and trim are honored.

⚠ new syntax
- Added \mcolrowcell for empty cells inside a \multicolumnrow. Use \mcolrowcell instead of \mrowcell for two-dimensional cells created by \multicolumnrow. Continue to use \mrowcell for empty cells in a \multirow. See section 338.2 on page 820.
- Fix: Unfinished tabular rows are automatically filled.
- Fix for tabular column specifiers while using babel-french. (\NoAutoSpacing is activated then nullified inside the tabular, due to a conflict with the tabular column parsing code.)

v0.40:

graphics, graphicx
- graphics and graphicx have been moved from the lwarp core, and are only loaded if requested with \usepackage.

\includegraphics path
⚠ image file extensions
- Improved graphics \graphicspath support. Multiple image directories may now be used. Refer to .pdf files without a file extension to allow the HTML version to use a .svg, .png, .jpg, or .gif version instead. See section 8.8.
- grffile is now directly supported instead of emulated.

bigdelim
- Fix for bigdelim, and improved documentation. See section 139.

symbols
- Improved LaTeX and textcomp symbols.

fixes
- Fix for LaTeX logos and \InlineClass, etc. inside a lateximage.
- Fix for xltxtra with XeLaTeX.
- Fixes for tocbibind with \simplechapter, etc.
- Fixes for \multicolumnrow and \nullfonts with older versions of multirow and xparse.
- Added \underline.

margins
- Added adjmulticol.

columns
- Added cuted, midfloat.

footnotes
- Added pfnote, fnpos, dblfnote.

tabular
- Added stabular, tabls.

sectioning
- Added sectsty, anonchap, quotchap.

v0.39:

title pages
- Improved the titlepage HTML code, `\thanks` notes, and `\maketitle`. titling is no longer required, but is still supported. The `\published` and `\subtitle` fields are no longer provided, but `\AddSubtitlePublished` replicates them using titling. See section 66.8. authblk is added, and should be loaded before titling. See section 66.

⚠ `\published` and `\subtitle` load order

tabular
- `\multirow` now supports the new optional `vpos` argument.

multi column/row cell
- Added `\multicolumnrow` for combined `\multicolumn` and `\multirow`. See section 338.2.
- Tabular special cases:
  - Added `\TabularMacro` to mark custom macros inside tabular data cells, avoiding row corruption. See section 8.10.1.
  - Added `\ResumeTabular` for use when a `tabular` environment is defined inside another environment. See section 8.10.1.

⚠ macros inside tabular

⚠ tabular defined inside another environment

tabular
- Added supertabular, xtab, bigstrut, bigdelim.

margins
- Added fullwidth.

page layout
- Added addlines, anysize, a4, a4wide, a5comb, textarea, zwpagelayout, typearea, ebook.

v0.38:

forced single-pass compile
- Added **`lwarpmk print1`** and **`lwarpmk html1`** actions to force a compile of the project a single time. Useful when multiple passes are not needed, or changes were not detected.

starred sections
- Added `\ForceHTMLPage` and `\ForceHTMLTOC` to force a starred sectional unit onto its own HTML page and with its own TOC entry. See section 8.6.2.

updated tutorial
- Modified the tutorial to use the new `\ForceHTMLPage` and `\ForceHTMLTOC` macros.

packages
- Added appendix, tocbibind, fncychap, fix2col.

font size
- Added relsize, scalefnt.
- Added realscripts, metalogo, xltxtra.
- Added grffile, romanbar.

page numbering
- Added arabicfront, chappg, nonumonpart, nopageno, romanbarpagenumber.

front & back matter
- Docs: Improved description of the use of front/back matter. See section 8.6.
- Fix: color requests xcolor.
- Fix: `\part` for article class.

v0.37:

`\include` for html
- `\include` now maintains independent `.aux` files for HTML versions.

latexmk
- comment, used by lwarp, now maintains independent cut files for print and HTML versions, helping *latexmk* to better know whether to recompile.

accents and symbols
- Improved support for LaTeX accents, textcomp, siunitx symbols.

babel-french
- Improved babel-french handling for load order and ~ tilde.

v0.36:

- Recorganized the documentation section regarding special cases and limitations. (Section 8)
- Improved source formatting.

boxes and frames

- `\fbox` and related now use `\fboxsep` and `\fboxrule`.
- `\makebox` and `\framebox` now use width and position.
- `\fcolorbox` and related now work inside a `lateximage`.

babel-french

- babel-french: Improvements for French variants, load order, footnotes, ellipses.

footnotes

- Improved footnote numbering. `lateximage` footnotes now appear as regular footnotes to match the numbering of the print version. Also fixed a regression with MathJax.

siunitx

- Improved siunitx units.
- Fix for filenames while using MathJax.
- Fix for `\rule` when xcolor is not loaded.
- Added transparent, upref.

v0.35: Fix: `\textbf` and related.

v0.34:

⚠ Optional arguments

- `BlockClass`'s optional argument has been moved in front of the mandatory argument:

  `BlockClass[style]{class}` (NEW)

  instead of:

  `BlockClass{class}[style]` (OLD)

  This change makes it more consistent with LaTeX standards, and avoids problems with space between arguments.

⚠ Optional arguments

- Likewise, `\InlineClass`'s optional argument now comes before the mandatory arguments:

  `\InlineClass[style]{class}{text}`

spans with minipages

framing minipages

- Improved compatibility between spans, minipages, lists, frames, and math. Handles minipages and lists inside an HTML span, such as an `\fbox` containing a minipage, although with minimal HTML fomatting. See section 8.3.3. `\fboxBlock` is added to frame minipages, tables, and lists with full HTML formatting but no longer inline, and behaves as `\fbox` for print output. The `fminipage` environment is added for framed minipages, as an environment with full HTML formatting, and draws a framed minipage in print output. See section 8.3.5. `\fbox` and minipages now often work in SVG math and `lateximages`. MathJax supports `\fbox`, but not `\fboxBlock` nor `fminipage`.

lateximage, svg math, tabular

- Improved compatibility between `lateximage` and `minipage`, `\parbox`, `\makebox`, `\fbox`, `\framebox`, `\raisebox`, `\scalebox`, `\reflectbox`, `tabular`, booktabs.
- Improved font control for `lateximagees` and SVG math.

eqnarray

- Added the `eqnarray` environments.

verbatim packages

- fancyvrb is no longer required (preloaded), but is still supported.
- Added verbatim and moreverb.

framing packages

- Added fancybox, boxedminipage2e and shadow.

list packages

- enumitem is no longer required, but is still supported.
- Added enumerate and paralist.
- titleps is no longer required, but is still supported.
- Added crop.
- Added rotfloat, marginfit, and several minor packages; see the change log.

babel-french

- Adds fixed-width HTML spaces around punctuation when using babel-french. LuaTEX does not yet use the extra punctuation spacing.

v0.33:

- Tabular `@` and `!` columns now havetheir own HTML columns.
- `&` catcode changes are localized, perhaps causing errors about the tab alignment character `&`, so any definitions of macros or environments which themselves contain `tabular` and `&` must be enclosed within `\StartDefiningTabulars` and `\StopDefiningTabulars` (previously called `\EndDefiningTabulars`. See section 43. This change is not required for the routine use of tables, but only when a table is defined inside another macro or environment, and while also using the `&` character inside the definition. This may include the use inside conditional expressions.
- Several math environments were incorrectly placed inline. Also, for amsmath with SVG math, the `fleqn` option has been removed, resulting in improved spacing for aligned equations.
- Bug fixes; see the changelog.

v0.32: Bug fixes; no source changes needed:

- *lwarpmk* has been adjusted to work with the latest *luatex*.
- Spaces in the `\usepackage` and `\RequirePackage` package lists are now accepted and ignored.
- Fix for the glossaries package and `\glo@name`.

v0.31: Bug fix; no source changes needed:

- Improved compatibility with keyfloat, including the new `keywrap` environment.

v0.30:

⚠ lwarp-newproject

- lwarp-newproject has been removed, and its functions have been combined with lwarp.

  To modify existing documents, remove from the document source:

  ```
  \usepackage{lwarp-newproject}
  ```

  The lwarp package now produces the configuration files during print output, and also accepts the option `lwarpmk` if desired.

⚠ HTML setup changes.

- A number of macros related to HTML settings have been converted to options, and other macros and options have been renamed to create a consistent syntax:

Old Macro	New Package Option
\HomeHTMLFileName	HomeHTMLFilename
\HTMLFileName	HTMLFilename
\useLatexmk	latexmk
\warpOSwindows	OSWindows

Old Package Option	New Package Option
lwarpmklang	xindyLanguage
(new)	xindyStyle

Old Macro	New Macro
\MetaLanguage	\HTMLLanguage
\HTMLauthor	\HTMLAuthor
\NewHTMLdescription	\HTMLDescription
\SetFirstPageTop	\HTMLFirstPageTop
\SetPageTop	\HTMLPageTop
\SetPageBottom	\HTMLPageBottom
\NewCSS	\CSSFilename

- Per the above changes, in existing documents, modify the package load of lwarp, such as:

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={},
    xindyLanguage=english
]{lwarp}
```

- The file lwarp_html.xdy has been renamed lwarp.xdy. To update each document's project:
  1. Make the changes shown above.
  2. Recompile the document in print mode. This updates the project's configuration files, and also generates the new file lwarp.xdy.
  3. The old file lwarp_html.xdy may be deleted.
- The new lwarp package option xindyStyle may be used to tell *lwarpmk* to use a custom .xdy file instead of lwarp.xdy. See section 8.6.20.
- Improvements in index processing:
  - *xindy*'s language is now used for index processing as well as glossary.
  - Print mode without *latexmk* now uses *xindy* instead of *makeindex*.
  - *texindy*/*xindy* usage depends on *pdflatex* vs *xelatex*, *lualatex*.
  - For *pdflatex* and *texindy*, the -C utf8 option is used. This is supported in modern distributions, but a customized lwarpmk.lua may need to be created for use with older distributions.

v0.29:

- Add: `lwarpmklang` option for lwarp-newproject and lwarp. Sets the language to use while processing the glossary. (As of v0.30, this has been changed to the `IndexLanguage` option.) (As of v0.54, this has been changed to the `xindyLanguage` option.)
- Fix: `\includegraphics` when no optional arguments.

v0.28:

- `\HTMLAuthor {`⟨*name*⟩`}` assigns HTML meta author if non-empty. Defaults to `\theauthor`.
- Booean `HTMLDebugComments` controls whether HTML comments are added for closing `<div>`s, opening and closing sections, etc.
- Boolean `FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.
- Boolean `FormatWordProcessor` changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Name changed to `FormatWP` as of v0.42.
- Boolean `HTMLMarkFloats` adds text marks around floats only if the boolean `FormatWordProcessor` is `true`. These make it easier to identify float boundaries, which are to be manually converted to word-processor frames. Name changed to `WPMarkFloats` as of v0.42.
- Updated for the new MathJax CDN repository.
- Adds tabulary.
- Supports the options syntax for graphics.
- Improved index references, now pointing exactly to their target.
- Adds glossaries. *lwarpmk* is modified to add `printglosssary` and `htmlglossary` actions.

2 Introduction

The lwarp project aims to allow a rich LaTeX document to be converted to a reasonable HTML5 interpretation, with only minor intervention on the user's part. No attempt has been made to force LaTeX to provide for every HTML-related possibility, and HTML cannot exactly render every possible LaTeX concept. Where compromise is necessary, it is desirable to allow the print output to remain typographically rich, and compromise only in the HTML conversion.

Several "modern" features of HTML5, CSS3, and SVG are employed to allow a fairly feature-rich document without relying on the use of JavaScript. Limited testing on older browsers shows that these new features degrade gracefully.

---

lwarp is a native LaTeX package, and operates by either patching or emulating various functions. Source-level compatibility is a major goal, but occasional user intervention is required in certain cases.

As a package running directly in LaTeX, lwarp has some advantages over other methods of HTML conversion. TeX itself is still used, allowing a wider range of TeX trickery to be understood. Lua expressions are still available with LuaTeX. Entire categories of LaTeX packages work as-is when used with lwarp: definitions, file handling, utilities, internal data structures and calculations, specialized math-mode typesetting for various fields of science and engineering, and anything generating plain-text output. Blocks of PDF output may be automatically converted to SVG images while using the same font and spacing as the original print document, directly supporting Ti*k*z and `picture`. Numerous packages are easily adapted for HTML versions, either by loading and patching the originals, or by creating nullified or emulated replacements, and all without resorting to external programming. As a result, several hundred packages have already been adapted (table 2), and an uncounted number more work as-is.

Packages have been selected according to several criteria: perceived importance, popularity lists, recent CTAN updates, CTAN topics, mention in other packages, support by other HTML conversion methods, and from sample documents taken from public archives. These include some "obsolete" packages as well.[1]

Assistance is also provided for modifying the HTML output to suit the creation of EPUB documents, and for modifying the HTML output to ease import into a word processor.

---

[1] An amazing number of decades-old packages are still in use today.

pdflatex, *xelatex*, or *lualatex* may be used, allowing lwarp to process the usual image formats. While generating HTML output, SVG files are used in place of PDF. Other formats such as PNG and JPG are used as-is.

SVG images may be used for math, and are also used for `picture`, Ti*k*Z, and similar environments. The SVG format has better browser and e-book support than MathML (as of this writing), while still allowing for high-quality display and printing of images (again, subject to potentially bug-ridden[2] browser support).

Furthermore, SVG images allow math to be presented with the same precise formatting as in the print version. Math is accompanied by `<alt>` tags holding the LaTeX source for the expression, allowing it to be copy/pasted into other documents.[3] Custom LaTeX macros may be used as-is in math expressions, since the math is evaluated entirely inside LaTeX. An MD5 hash is used to combine multiple instances of the same inline math expression into a single image file, which then needs to be converted to SVG only a single time.

The MathJax JavaScript display engine may be selected for math display instead of using SVG images. Subject to browser support and Internet access, MathJax allows an HTML page to display math without relying on a large number of external image files.[4] lwarp maintains LaTeX control for cross-referencing and equation numbering, and attempts to force MathJax to tag equations accordingly.

A *texlua* program called *lwarpmk* is used to process either the print or HTML version of the document. A few external utility programs are used to finish the conversion from a LaTeX-generated PDF file which happens to have HTML5 tags, to a number of HTML5 plain-text files and accompanying images.

lwarp automatically generates the extra files necessary for the HTML conversion, such as CSS and `.xdy` files, and configuration files for the utility *lwarpmk*. Also included is a parallel version of the user's source document, `<sourcename>-html.tex`, which selects HTML output and then inputs the user's own source. This process allows both the printed and HTML versions to co-exist side-by-side, each with their own auxiliary files.

When requesting packages during HTML conversion, lwarp first looks to see if it has its own modified version to use instead of the standard LaTeX version. These `lwarp-packagename.sty` files contain code used to emulate or replace functions for HTML output.

---

[2] Firefox has had an on-again/off-again bug for quite some time regareding printing svgs at high resolution.

[3] There seems to be some debate as to whether Mathml is actually an improvement over LaTeX for sharing math. The author has no particular opinion on the matter, except to say that in this case LaTeX is much easier to implement!

[4] One svg image file per math expression, except that duplicate inline math expressions are combined into a single file according to the MD5 hash function of its contents. A common scientific paper can easily include several thousand files, and in one case the MD5 hash cut the number of files in half and the rendering time by 30%.

2.1 Typesetting conventions

Font weight, family, and style are used to indicate various objects:

Table 1: Typesetting conventions

package	LaTeX package.
program	Program's executable name.
`option`	Program or package option.
`filename`	File name in the operating system.
Brand Name	Proper name for a program, operating system, etc.
`commands`	Commands to be entered by the user.
`code`	Program code.
`\macroname`	LaTeX macro.
`environment`	LaTeX environment.
`counter`	LaTeX counter.
`boolean`	LaTeX boolean.
`<element>`	html element.
`attribute`	html attribute.
User Interface	A user-interface item.
acro	Acronym.

2.2 Supported packages and features

Table 2 lists some of the various LaTeX features and packages which may be used.

Package names are colored according to their support level:

name: Supported as-is.

name: Modifed to work with HTML output, and also as print output in SVG math or `latexmage` environments.

name: Emulated for HTML output.

name: Ignored for HTML output, but provides source-level compatibility.

Table 2: LaTeX lwarp package — Supported features

Category	Status and supported features.
Engines:	DVI LaTeX, pdfLaTeX, XeLaTeX, LuaLaTeX, upLaTeX
Compiling:	*latexmk*, *perltex*, *pythontex*, *make*, etc.
Classes:	article, book, report, scrartcl, scrbook, scrreprt, memoir, CJK-related as listed below.
Koma-script:	scrextend, scrhack, scrlayer. Others as listed below.
Memoir:	memhfixc
Languages:	babel, polyglossia. cjkpunct, xeCJK.
Chinese:	CTeX, ctex, upzhkinsoku, xpinyin, zhlineskip, zhspacing.
Japanese:	upLaTeX, LuaTeX-ja, gentombow, lltjext, plarray, plarydshln, plautopatch, plext, plextarray, plextarydshln, plextcolortbl, plextdelarray, pxatbegshi, pxeveryshi, pxftnright, pxgentombow, pxjahyper, pxpdfpages, pxpgfrcs, pxpgfmark, tascmac, zxjatype. bxjsarticle and related, ltjsarticle and related, luatexja, luatexja-fontspec, ujarticle and related, utarticle and related.
Korean:	kotex, luatexko, xetexko.

lwarp Supported Functions — continued

Category	Status
Page layout:	2in1, 2up, a4, a4wide, a5comb, addlines, anysize, atbegshi, blowup, booklet, bophook, bounddvi, bxpapersize, canoniclayout, changelayout, changepage, chngpage, clrdblpg, continue, draftcopy, draftfigure, draftwatermark, ebook, everyshi, fancyhdr, fancytabs, flippdf, fullminipage, fullpage, fwlw, geometry, gmeometric, grid, grid-system, gridset, layaureo, layout, layouts, leading, ltxgrid, nccfancyhdr, notespages, nowidow, pagegrid, pagesel, pdfcrypt, pdfprivacy, preview, ragged2e, rmpage, scrlayer-scrpage, scrpage2, setspace, textarea, threadcol, thumb, thumbs, titleps, tocenter, turnthepage, twoup, typearea, underlin, vmargin, watermark, widows-and-orphans, zwpagelayout.
Sectioning:	Adds `FileDepth` for splitting the HTML output. Files may be numbered sequentially or named according to section name. Common short words and punctuation are removed from the filenames. anonchap, bsheaders, fncychap, hypbmsec, indentfirst, quotchap, section, sectionbreak, secdot, sectsty, titlesec.
Table of contents, figures, tables:	Supported, with hyperlinks. minitoc, multitoc, shorttoc, titletoc, tocbasic, tocbibind, tocdata, tocloft, tocstyle.
Title page:	`\maketitle`, `titlepage`, authblk, titling.
Front & back matter:	abstract, appendix.
Indexing:	*makeindex* and *xindy* are supported, with hyperlinks. hvindex, idxlayout, imakeidx, index, makeidx, repeatindex, splitidx.
Glossary:	gloss, glossaries and *xindy*, nomencl.
Bibliography:	babelbib, backref, biblatex, bibunits, chapterbib, cite, hypernat, natbib, notes2bib, showtags.
Cross-references:	bookmark, breakurl, cleveref, fancyref, hypdestopt, hyperref, perpage, prettyref, titleref, url, varioref, xr, xr-hyper, xurl.
Margin notes:	marginal, marginfit, marginfix, scrlayer-notecolumn, versonotes.

lwarp Supported Functions — continued

Category	Status
Footnotes:	Adds `FootnoteDepth` to print footnotes at section breaks. bigfoot, dblfnote, endheads, endnotes, fixfoot, fnbreak, fnpara, fnpos, footmisc, footnote, footnotebackref, footnoterange, footnpag, manyfoot, marginnote, nccfoots, pagenote, parnotes, pfnote, sepfootnotes, sidenotes, tablefootnote.
Math:	Converted to SVG images with HTML `<alt>` tags containing the LaTeX source for the math expression. MathJax supported as an alternative. amsmath: $\mathcal{AMS}$ environments are supported. User-defined macros are available during conversion, due to native LaTeX processing.
Theorems:	Native LaTeX theorems, amsthm, ntheorem, theorem.
Additional math:	Math fonts via SVG images, amscd, autonum, backnaur, bm, braket, breqn, cases, delarray, guass, jkmath, mathtools, nicematrix, pb-diagram, resizegather, xfakebold, xy. Many others work as-is.
Display math with `\displaymathother`:	Complicated math objects in display math, such as tikz-cd, etc.
Units and fractions:	nicefrac, SIunits, siunitx, units, unitsdef, xfrac.
Floats:	Appear where declared. capt-of, caption, cutwin, dblfloatfix, endfloat, fix2col, flafter, float, floatflt, floatrow, fltrace, ftcap, hypcap, keyfloat, morefloats, multicap, newfloat, nonfloat, placeins, rotfloat, stfloats, subcaption, subfig, subfigure, subfloat, topcapt, trivfloat, wrapfig.
Tabular:	`tabular` environment, array, arydshln, bigdelim, booktabs, colortbl, ctable, diagbox, longtable, ltablex, ltxtable, multirow, supertabular, tabularx, tabulary, threeparttable, threeparttablex, xltabular, xtab.

lwarp Supported Functions — continued

Category	Status
Graphics:	graphics and graphicx. `\includegraphics` supports `width`, `height`, `origin`, `angle`, and `scale` tags, and adds `class`. References to PDF files are changed to SVG, other image types are accepted as well. `\rotatebox` and `\scalebox` are supported as well as HTML can handle. rotating is emulated but all objects are unrotated. `picture`, tikz, and xy are converted to an SVG image. asymptote, curves, eepic, epsfig, epstopdf, figsize, fitbox, grffile, media9, movie15, multimedia, overpic, psfrag, psfragx, pst-eps, pstool, pstricks, rviewport, tikz-3dplot.
xcolor:	Full package color names, any color models, and mixing. `\textcolor`, `\colorbox`, `\fcolorbox`. Enhanced for HTML compatibility.
Lists:	Standard LaTeX environments, enumerate, enumitem, eqlist, hang, listliketab, paralist.
Environments:	Standard LaTeX environments.
`minipage`, `\parbox`:	Some HTML5-imposed limitations. Nested minipages are supported. eqparbox, minibox, pbox, shapepar.
Quotations:	copyrightbox, csquotes, epigraph, quoting, verse.
Verbatim:	fancyvrb, moreverb, shortvrb, verbatim.
Frames:	boxedminipage2e, fancybox, framed, mdframed, niceframe, shadow, vertbars.
Multi-columns:	adjmulticol, multicol, multicolrule, vwcol.
Margins:	fullwidth, hanging, midpage.
Line numbering:	fnlineno, lineno.
Direct formatting:	`\emph`, `\textsuperscript`, `\textbf`, etc are supported. `\bfseries`, etc. are only supported in some cases. cancel, ellipsis, embrac, enparen, hyphenat, lettrine, lips, lua-check-hyphen, luacolor, magaz, pdfrender, realscripts, relsize, scalefnt, soul, soulpos, soulutf8, textfit, thinsp, trimclip, truncate, ulem, umoline, underscore, uspace, xellipsis.
Acronyms:	acro, acronym.
Ordinals:	engord, fmtcount, nth.

lwarp Supported Functions — continued

Category	Status
Text ligatures:	Ligatures for symbols are supported. Ligatures for f, q, t are intentionally turned off because many simpler browsers do not display them correctly. Modern full-featured browsers re-create these ligatures on-the-fly.
Horizontal space:	HTML output for thin-unbreakable, unbreakable, `\enskip`, `\quad`, `\qquad`, `\hspace`.
Rules:	`\rule` with width, height, raise, text color.
HTML reserved characters:	`\&`, `\textless`, and `\textgreater` are converted to HTML entities.
Fonts:	Used as-is. Appear in SVG math expressions or embedded image environments. fontaxes, nfssext-cfr, slantsc, tabfigures. Tested to work as-is: Special font macros in cfr-lm and others which use nfssext-cfr.
Symbols:	Native LaTeX diacriticals, academicons, bbding, chemgreek, dingbat, euro, eurosym, fontawesome, fontawesome5, gensymb, marvosym, metalogo, metalogox, pifont, textalpha, textcomp, textgreek, typicons, xunicode.
Files:	attachfile, attachfile2, hyperxmp, inputtrc, intopdf, pdfpages, pdfx, xmpincl.
Science and engineering:	algorithm2e, algorithmicx, ar, askmaps, axodraw2, bitpattern, blochsphere, bodegraph, bohr, bytefield, chemfig, chemformula, chemgreek, chemmacros, chemnum, circuitikz, elements, engtlc, fast-diagram, hepnicenames, heppennames, karnaughmap, karnaugh-map, listings, linop, mhchem, pgfgantt, phfqit, physics, register, simpler-wick, slashed, structmech, struktex. tikz-karnaugh, tikzcodeblocks
Arts and humanities:	foreign, forest, musicography, nameauth, octave, phonrule, piano, schemata, semantic-markup, tikz-dependency, vowel, xpiano
Admonitions:	notes.
Editorial:	changebar, changelog, changes, easy-todo, easyReview, ed, errata, fixme, fixmetodonotes, pdfcomment, pdfmarginpar, todo, todonotes, tram, xechangebar.

lwarp Supported Functions — continued

Category	Status
Accessibility:	accsupp, axessibility.
Debug:	chkfloat, cmdtrack, dprogress, lua-visual-debug, refcheck, srcltx, srctex, vpe, xbmks.
Working as-is:	Various utility, calculation, file, and text-only packages, such as calc, fileerr, somedefs, trace, xspace. Also, most math-only packages, including specialized typesetting for various fields of science and engineering.

3 Alternatives

Summarized below are several other ways to convert a LaTeX or other document to HTML. Where an existing LaTeX document is to be converted to HTML, lwarp may be a good choice. For new projects with a large number of documents, it may be worth investigating the alternatives before decided which path to take.

3.1 internet class

Cls internet The closest to lwarp in design principle is the `internet` class by Andrew Stacey — an interesting project which directly produces several versions of markdown, and also HTML and EPUB. https://github.com/loopspace/latex-to-internet

3.2 TeX4ht

Prog TeX4ht http://tug.org/tex4ht/

Prog htlatex

This system uses native LaTeX processing to produce a DVI file containing special commands, and then uses additional post-processing for the HTML conversion by way of numerous configuration files. In some cases lwarp provides a better HTML conversion, and it supports a different set of packages. TeX4ht produces several other forms of output beyond HTML, including ODT and a direct path to EPUB, and is still being developed.

3.3 Translators

These systems use external programs to translate a subset of LaTeX syntax into HTML. Search for each on CTAN (http:\ctan.org).

Prog Hevea **HeVeA:** http://hevea.inria.fr/ (not on CTAN)

Prog TtH **TtH:** http://hutchinson.belmont.ma.us/tth/

Prog GELLMU **GELLMU:** http://www.albany.edu/~hammond/gellmu/

Prog LaTeXML **LaTeXML:** http://dlmf.nist.gov/LaTeXML/

Prog Plastex **PlasTeX:** https://github.com/tiarno/plastex

Prog LaTeX2HTML **LaTeX2HTML:** http://www.latex2html.org/
and http://ctan.org/pkg/latex2html.

Prog TeX2page **TeX2page:** http://ds26gte.github.io/tex2page/index.html

Finally, GladTeX may used to directly insert LaTeX math into HTML:

Prog GladTeX **GladTeX:** http://humenda.github.io/GladTeX/

3.4 AsciiDoc and Asciidoctor

AsciiDoc is one of the most capable markup languages, providing enough features to produce the typical technical-writing document with cross-references, and it writes LaTeX and HTML.

Prog AsciiDoc **Asciidoctor:** http://asciidoctor.org/ (More active.)

Prog AsciiDoctor **AsciiDoc:** http://asciidoc.org/ (The original project.)

3.4.1 Asciidoctor-LaTeX

The Asciidoctor-LaTeX project is developing additional LaTeX-related features.

Asciidoctor-LateX:
http://www.noteshare.io/book/asciidoctor-latex-manual
Prog Asciidoctor-LaTeX https://github.com/asciidoctor/asciidoctor-latex

3.5 Pandoc

Prog Pandoc A markup system which also reads and writes LaTeX and HTML.

Pandoc: http://pandoc.org/

(Watch for improvements in cross-references to figures and tables.)

3.6 Word processors

Prog Word
Prog LibreOffice
Prog OpenOffice

It should be noted that the popular word processors have advanced through the years in their abilities to represent math with a LaTeX-ish input syntax, unicode math fonts, and high-quality output, and also generate HTML with varying success. See recent developments in Microsoft® *Word*® and LibreOffice™ *Writer*.

3.7 Commercial systems

Prog Adobe
Prog FrameMaker
Prog InDesign
Prog Flare
Prog Madcap

Likewise, several professional systems exist whose abilities have been advancing in the areas of typesetting, cross-referencing, and HTML generation. See Adobe® *FrameMaker*®, Adobe *InDesign*®, and Madcap *Flare*™.

3.8 Comparisons

AsciiDoc, Pandoc, and various other markup languages typically have a syntax which tries to be natural and human-readable, but the use of advanced features tends to

require many combinations of special characters, resulting in a complicated mess of syntax. By contrast, LaTeX spells things out in readable words but takes longer to type, although integrated editors exist which can provide faster entry and a graphic user interface. For those functions which are covered by the typical markup language it is arguable that LaTeX is comparably easy to learn, while LaTeX provides many more advanced features where needed, along with a large number of pre-existing packages which provide solutions to numerous common tasks.

Text-based document-markup systems share some of the advantages of LaTeX vs. a typical word processor. Documents formats are stable. The documents themselves are portable, work well with revision control, do not crash or become corrupted, and are easily generated under program control. Formatting commands are visible, cross-referencing is automatic, and editing is responsive. Search/replace with regular expressions provides a powerful tool for the manipulation of both document contents and structure. Markup systems and some commercial systems allow printed output through a LaTeX back end, yielding high-quality results especially when the LaTeX template is adjusted, but they lose the ability to use LaTeX macros and other LaTeX source-document features.

The effort required to customize the output of each markup system varies. For print output, LaTeX configuration files are usually used. For HTML output, a CSS file will be available, but additional configuration may require editing some form of control file with a different syntax, such as XML. In the case of lwarp, CSS is used, and much HTML output is adjusted through the usual LaTeX optional macro parameters, but further customization may require patching LaTeX code.

The popular word processors and professional document systems each has a large base of after-market support including pre-designed styles and templates, and often include content-management systems for topic reuse.

4 Installation

Table 3 shows the tools which are used for the LaTeX to HTML conversion. In most cases, these will be available via the standard package-installation tools.

Detailed installation instructions follow.

Table 3: Required software programs

Provided by your LaTeX distribution:

From TeXLive: http://tug.org/texlive/.

LaTeX: *pdflatex*, *xelatex*, or *lualatex*.

The lwarp package: This package.

The *lwarpmk* utility: Provided along with this package. This should be an operating-system executable in the same way that *pdflatex* or *latexmk* is. It is possible to have the lwarp package generate a local copy of *lwarpmk* called `lwarpmk.lua`. See table 4.

***luatex*:** Used by the *lwarpmk* program to simplify and automate document generation.

***xindy*:** The *xindy* program is used by lwarp to create indexes. On a MiKTeX system this may have to be acquired separately, but it is part of the regular installer as of mid 2015.

***latexmk*:** Optionally used by *lwarpmk* to compile LaTeX code. On a MiKTeX system, *Perl* may need to be installed first.

***pdfcrop*:** Used to pull images out of the LaTeX pdf.

Poppler pdf utilities:

***pdftotext*:** Used to convert pdf to text.

***pdfseparate*:** Used to pull images out of the LaTeX pdf.

***pdftocairo*:** Used to convert images to svg.

These might be provided by your operating-system package manager, and MiKTeX provides miktex-poppler-bin-* packages.

From Poppler: poppler.freedesktop.org.

For MacOS®, see https://brew.sh/, install *Homebrew*, then

Enter ⇒ **`brew install poppler`**

For Windows, see MikTeX miktex-poppler-bin-*, or:
https://sourceforge.net/projects/poppler-win32/ and:
http://blog.alivate.com.au/poppler-windows/

***Perl*:**

This may be provided by your operating-system package manager, and may be required for some of the Poppler pdf utilities.

strawberryperl.com (recommended), perl.org

Automatically downloaded from the internet as required:

MathJax: Optionally used to display math. From: mathjax.org

4.1 Installing the lwarp package

There are several ways to install lwarp. These are listed here with the preferred methods listed first:

Pre-installed: Try entering into a command line:

Enter ⇒ **`kpsewhich lwarp.sty`**

If a path to `lwarp.sty` is shown, then lwarp is already installed and you may skip to the next section.

TEX Live: If using a TEX Live distribution, try installing via *tlmgr*:

Enter ⇒ **`tlmgr install lwarp`**

MiKTEX:

1. For newer versions of MiKTEX, install or update lwarp using the *MiKTeX Console* program.
2. For older versions of MiKTEX, to install lwarp the first time, use the *MiKTeX Package Manager (Admin)*. To update lwarp, use *MiKTeX Update (Admin)*.
3. Either way, also update the package miktex-misc, which will install and update the *lwarpmk* executable.

Operating-system package: The operating-system package manager may already have lwarp, perhaps as part of a set of TEX-related packages.

CTAN TDS archive: lwarp may be downloaded from the Comprehensive TEX Archive:

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the TDS archive: `lwarp.tds.zip`
3. Find the TEX `local` directory:

   TEX Live:

   Enter ⇒ **`kpsewhich -var-value TEXMFLOCAL`**

   MiKTEX:

   In the **Settings** window, **Roots** tab, look for a local TDS root.

   This should be something like:

   ```
   /usr/local/texlive/texmf-local/
   ```

4. Unpack the archive in the TDS local directory.
5. Renew the cache:

   Enter ⇒ **`mktexlsr`**

   — or —

   Enter ⇒ **`texhash`**

   Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.

CTAN `.dtx` and `.ins` files: Another form of TEX package is `.dtx` and `.ins` source files. These files are used to create the documentation and `.sty` files.

1. See http://ctan.org/pkg/lwarp for the lwarp package.
2. Download the zip archive `lwarp.zip` into your own `lwarp` directory.
3. Unpack `lwarp.zip`.
4. Locate the contents `lwarp.dtx` and `lwarp.ins`
5. Create the `.sty` files:
   Enter ⇒ **`pdflatex lwarp.ins`**
6. Create the documentation:

```
pdflatex lwarp.dtx  (several times)
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
makeindex -s gind.ist lwarp.idx
pdflatex lwarp.dtx  (several times)
```

7. Copy the `.sty` files somewhere such as the TEX Live local tree found in the previous CTAN TDS section, under the subdirectory:
   `<texlocal>/tex/latex/local/lwarp`
8. Copy `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` to the same place as the `.sty` files.
9. Copy the documentation `lwarp.pdf` to a `source` directory in the local tree, such as:
   `<texlocal>/doc/local/lwarp`
10. Renew the cache:
    Enter ⇒ **`mktexlsr`**
    — or —
    Enter ⇒ **`texhash`**
    Or, for WINDOWS MiKTEX, start the program called *MiKTeX Settings (Admin)* and click on the button called **Refresh FNDB**.
11. See section 4.2.1 to generate your local copy of *lwarpmk*.
12. Once the local version of `lwarpmk.lua` is installed, it may be made available system-wide as per section 4.2.

Project-local CTAN `.dtx` and `.ins` files: The `.dtx` and `.ins` files may be downloaded to a project directory, then compiled right there, alongside the document source files. The resultant `*.sty` and `lwarpmk.lua` files may be used as-is, so long as they are in the same directory as the document source. The files `lwarp_baseline_marker.png` and `lwarp_baseline_marker.eps` must also be copied as well. This approach is especially useful if you would like to temporarily test lwarp before deciding whether to permanently install it.

Just testing!

4.2 Installing the *lwarpmk* utility

(Note: If *lwarpmk* is not already installed, it is easiest to use a local copy instead of installing it system-wide. See section 4.2.1.)

After the lwarp package is installed, you may need to setup the *lwarpmk* utility:

1. At a command line, try executing **lwarpmk**. If the *lwarpmk* help message appears, then *lwarpmk* is already set up. If not, it is easiest to generate and use a local copy. See section 4.2.1.

2. For MiKTEX, try updating the miktex-misc package. This may install the *lwarpmk* executable for you.

   Otherwise, continue with the following:

3. Locate the file `lwarpmk.lua`, which should be in the `scripts` directory of the TDS tree. On a TEX Live or MiKTEX system you may use

   Enter ⇒ **kpsewhich lwarpmk.lua**

   (If the file is not found, you may also generate a local copy and use it instead. See section 4.2.1.)

4. Create *lwarpmk*:

   Unix: Create a symbolic link and make it executable:

   (a) Locate the TEX Live binaries:

   Enter ⇒ **kpsewhich -var-value TEXMFROOT**

   This will be something like:

   `/usr/local/texlive/<year>`

   The binaries are then located in the `bin/<arch>` directory under the root:

   `/usr/local/texlive/<year>/bin/<architecture>/`

   In this directory you will find programs such as *pdflatex* and *makeindex*.

   (b) In the binaries directory, create a new symbolic link from the binaries directory to `lwarpmk.lua`:

   Enter ⇒ **ln -s <pathtolwarpmk.lua> lwarpmk**

   (c) Make the link executable:

   Enter ⇒ **chmod 0755 lwarpmk**

   WINDOWS TEX Live: Create a new `lwarpmk.exe` file:

   (a) Locate the TEX Live binaries as shown above for UNIX.

   (b) In the binaries directory, make a *copy* of `runscript.exe` and call it `lwarpmk.exe` This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

   WINDOWS MiKTEX: Create a new `lwarpmk.bat` file:

   (a) Locate the MiKTEX binaries. These will be in a directory such as:

   `C:\Program Files\MiKTeX 2.9\miktex\bin\x64`

   In this directory you will find programs such as `pdflatex.exe` and `makeindex.exe`.

   (b) Create a new file named `lwarpmk.bat` containing:

   ```
   texlua "C:\Program Files\MiKTeX 2.9\scripts\lwarp\lwarp.texlua" %*
   ```

   This will call the copy of `lwarpmk.lua` which is in the `scripts` directory of the distribution.

4.2.1 Using a local copy of *lwarpmk*

It is also possible to use a local version of *lwarpmk*:

1. When compiling the tutorial in section 5, use the `lwarpmk` option for the lwarp package:

   ```
   \usepackage[lwarpmk]{lwarp}
   ```

2. When the tutorial is compiled with *pdflatex*, the file `lwarpmk.lua` will be generated along with the other configuration files.

3. `lwarpmk.lua` may be used for this project:

   Unix:

   (a) Make `lwarpmk.lua` executable:

   Enter ⇒ **`chmod 0755 lwarpmk.lua`**

   (b) Compile documents with

   Enter ⇒ **`./lwarpmk.lua html`**

   Enter ⇒ **`./lwarpmk.lua print`**

   etc.

   (c) It may be useful to rename or link to a version without the `.lua` suffix.

   WINDOWS:

   Compile documents with either of the following, depending on which command shell is being used:

   Enter ⇒ **`texlua lwarpmk.lua html`**

   Enter ⇒ **`texlua lwarpmk.lua print`**

   etc.

   Or:

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk print`**

   etc.

4.3 Installing additional utilities

To test for the existence of the additional utilities:

Enter the following in a command line. If each programs' version is displayed, then that utility is already installed. See table 3 on page 73.

Enter ⇒ **`luatex --version`**

Enter ⇒ **`xindy --version`**

Enter ⇒ **`latexmk --version`**

Enter ⇒ **`perl --version`**

Enter ⇒ **`pdfcrop --version`**

Enter ⇒ **`pdftotext -v`**

Enter ⇒ **`pdfseparate --version`**

Enter ⇒ **`pdftocairo -v`**

To install *xindy*, *latexmk*, and *pdfcrop*:

The TEX utilities *xindy*, *latexmk*, and *pdfcrop* may be installed in *TexLive* with *tlmgr*, installed by *MiKTeX*, provided by your operating system's package manager, or downloaded from the *CTAN* archive:

http://ctan.org/pkg/xindy
http://ctan.org/pkg/latexmk
http://ctan.org/pkg/pdfcrop

Prog [requirement] pdftotext
Prog [requirement] pdfseparate
Prog [requirement] pdftocairo

To install the POPPLER utilities to a UNIX/LINUX system:

The tools from the POPPLER project should be provided by your operating system's package manager.

To install the POPPLER utilities to a MACOS machine:

1. Install *Homebrew* from https://brew.sh/:

```
/usr/bin/ruby -e "$(curl -fsSL https://raw.githubusercontent.com/Homebrew/install/master/install)"
```

2. Install the POPPLER utilities:

```
Enter ⇒  brew install poppler
```

To install the POPPLER utilities to a WINDOWS machine:

If using MikTEX, install a miktex-poppler-bin-* package. Otherwise:

1. See table 3 on page 73.
2. Download and extract the POPPLER utilities *pdftotext*, *pdfseparate*, and *pdfseparate* to a directory, such as `Poppler`.
3. In the **Start** window, type "Path" to search for results related to Path. Or, open the control panel and search for "Path".
4. Choose **Edit the system environment variables** in the control panel.
5. Choose the **Environment Variables** button.
6. Choose the **Path** variable, then the **Edit** button.
7. Choose the **New** button to make an additional entry.
8. Enter the `bin` directory of the POPPLER utilities, such as:

   `C:\Users\<myname>\Desktop\Poppler\poppler-0.5_x86\poppler-0.5\bin`

   Be sure to include `\bin`.
9. Click **Ok** when done.

Prog [requirement] perl

To install PERL to a WINDOWS machine:

1. Download and install a version of PERL, such as STRAWBERRY PERL, to a directory without a space in its name, such as `C:\Strawberry`.
2. Edit the **Path** as seen above for the POPPLER utilities.
3. Enter the `bin` directory of the *perl* utility, such as:

   `C:\Strawberry\perl\bin`

   Be sure to include `\bin`.
4. Click **Ok** when done.

Any utilities installed by hand must be added to the PATH.

5 Tutorial

This section shows an example of how to create an lwarp document.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

5.1 Starting a new project

1. Create a new project directory called `tutorial`.

File `tutorial.tex`

2. Inside the `tutorial` directory, create a new file called `tutorial.tex`. This may be done several ways:

   Copy from the documentation PDF:

   A listing is in fig. 1, which may be copied/pasted from the figure directly into your own editor, depending on the quality of the PDF viewer and editor, or:

   Copy from the lwarp documentation directory:

File `lwarp_tutorial.txt`

   Another copy may be found by entering into a command line:

   Enter ⇒ **`texdoc -l lwarp_tutorial.txt`**

⚠ Note: `.txt` suffix!

   This should be in the `doc/latex/lwarp/` directory along with this PDF documentation. Copy `lwarp_tutorial.txt` directly into your `tutorial` directory, renamed as `tutorial.tex`.

⚠ Bad formatting!

   When using WINDOWS, use an editor other than NOTEPAD, since NOTEPAD does not accept the end-of-line from a UNIX text file.

3. Compile the project:

   Enter ⇒ **`pdflatex tutorial.tex`**

   (several times)

   (*xelatex* or *lualatex* may be used as well. lwarp also supports DVI *latex* for use with `.eps` images.)

4. View the resulting `tutorial.pdf` with a PDF viewer.

A number of new files are created when `tutorial.tex` is compiled, as shown in table 4. These files are created by the `lwarp` package.

(Two of the new files are configuration files for the helper program *lwarpmk*. Whenever a print version of the document is created, the configuration files for *lwarpmk* are updated to record the operating system, LaTeX engine (*latex*, *pdflatex*, *xelatex*, or *lualatex*), the filenames of the source code and HTML output, and whether the additional helper program *latexmk* will be used to compile the document.)

Figure 1: tutorial.tex listing

Note: There are two pages!

```
% Save this as tutorial.tex for the lwarp package tutorial.

\documentclass{book}

\usepackage{iftex}

% --- LOAD FONT SELECTION AND ENCODING BEFORE LOADING LWARP ---

\ifPDFTeX
\usepackage{lmodern}            % pdflatex or dvi latex
\usepackage[T1]{fontenc}
\usepackage[utf8]{inputenc}
\else
\usepackage{fontspec}           % XeLaTeX or LuaLaTeX
\fi

% --- LWARP IS LOADED NEXT ---
\usepackage[
%   HomeHTMLFilename=index,     % Filename of the homepage.
%   HTMLFilename={node-},       % Filename prefix of other pages.
%   IndexLanguage=english,      % Language for xindy index, glossary.
%   latexmk,                    % Use latexmk to compile.
%   OSWindows,                  % Force Windows. (Usually automatic.)
%   mathjax,                    % Use MathJax to display math.
]{lwarp}
% \boolfalse{FileSectionNames}  % If false, numbers the files.

% --- LOAD PDFLATEX MATH FONTS HERE ---

% --- OTHER PACKAGES ARE LOADED AFTER LWARP ---
\usepackage{makeidx} \makeindex
\usepackage{xcolor}             % (Demonstration purposes only.)
\usepackage{hyperref,cleveref}  % LOAD THESE LAST!

% --- LATEX AND HTML CUSTOMIZATION ---
\title{The Lwarp Tutorial}
\author{Some Author}
\setcounter{tocdepth}{2}        % Include subsections in the \TOC.
\setcounter{secnumdepth}{2}     % Number down to subsections.
\setcounter{FileDepth}{1}       % Split \HTML\ files at sections
\booltrue{CombineHigherDepths}  % Combine parts/chapters/sections
\setcounter{SideTOCDepth}{1}    % Include subsections in the side\TOC
\HTMLTitle{Webpage Title}       % Overrides \title for the web page.
\HTMLAuthor{Some Author}        % Sets the HTML meta author tag.
\HTMLLanguage{en-US}            % Sets the HTML meta language.
\HTMLDescription{A description.}% Sets the HTML meta description.
\HTMLFirstPageTop{Name and \fbox{HOMEPAGE LOGO}}
\HTMLPageTop{\fbox{LOGO}}
\HTMLPageBottom{Contact Information and Copyright}
\CSSFilename{lwarp_sagebrush.css}
```

```
\begin{document}

\maketitle                      % Or titlepage/titlingpage environment.

% An article abstract would go here.

\tableofcontents                % MUST BE BEFORE THE FIRST SECTION BREAK!
\listoffigures

\chapter{First chapter}

\section{A section}

This is some text which is indexed.\index{Some text.}

\subsection{A subsection}

See \cref{fig:withtext}.

\begin{figure}\begin{center}
\fbox{\textcolor{blue!50!green}{Text in a figure.}}
\caption{A figure with text\label{fig:withtext}}
\end{center}\end{figure}

\section{Some math}

Inline math: $r = r_0 + vt - \frac{1}{2}at^2$
followed by display math:
\begin{equation}
a^2 + b^2 = c^2
\end{equation}


\begin{warpprint}   % For print output ...
\cleardoublepage    % ... a common method to place index entry into TOC.
\phantomsection
\addcontentsline{toc}{chapter}{\indexname}
\end{warpprint}
\ForceHTMLPage      % HTML index will be on its own page.
\ForceHTMLTOC       % HTML index will have its own toc entry.
\printindex

\end{document}
```

Table 4: Configuration files created by print version

tutorial.pdf: The pdf output from LaTeX. The print version of the document.

tutorial_html.tex: A small `.tex` file used to create a parallel html version of the document, which co-exists with usual the pdf version, and which will have its own auxiliary files. In this way, both pdf and html documents may co-exist side-by-side.

Auxiliary files: The usual LaTeX files `.aux`, `.log`, `.out`, `.toc`, `.lof`, `.idx`. When an html version of the document is created, `_html` versions of the auxiliary files will also be generated.

lwarpmk.conf: A configuration file for *lwarpmk*, which is used to automate the compilation of pdf or html versions of the document.

tutorial.lwarpmkconf: Another configuration file used by *lwarpmk*, which is only useful if you wish to have several projects residing in the same directory.

.css files: `lwarp.css`, `lwarp_formal.css`, `lwarp_sagebrush.css` These files are standard for lwarp, and are not meant to be modified by the user.

sample_project.css: An example of a user-customized css file, which may be used for project-specific changes to the lwarp defaults.

lwarp.ist: Used by lwarp while creating an index using *makeindex*. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarp.xdy: Used by lwarp while creating an index using *xindy*. This file should not be modified by the user. A custom file may be used instead, if necessary.

lwarp_one_limage.txt: For Windows only. Used to process svg images in the background. Copied to `lwarp_one_limage.cmd` when images are generated.

lwarp_mathjax.txt: Inserted into the html files when MathJax is used to display math. This file should not be modified by the user.

comment.cut: A temporary file used by lwarp to conditionally process blocks of text. This file may be ignored.

When the `lwarpmk` option is given to the lwarp package:

lwarpmk.lua: A local copy of the *lwarpmk* utility.

On Unix-related operating systems this file must be made executable:

```
chmod u+x lwarpmk.lua
```

This may be useful to have to archive with a project for future use.

5.2 Compiling the print version with *lwarpmk*

The *lwarpmk* utility program is used to compile either the printed or the HTML version of the document.

`lwarpmk print` is used to recompile a printed version of the document.

1. Re-compile the print version:

   Enter ⇒ **`lwarpmk print`**

   lwarpmk prints an introduction then checks to see if the document must be recompiled. If it seems that the files are up-to-date, then *lwarpmk* informs you of that fact and then exits.

2. Make a small change in the original document, such as adding a space character.

3. Recompile again.

   Enter ⇒ **`lwarpmk print`**

   The document is recompiled when a change is seen in the source. Several compilations may be necessary to resolve cross-references.

4. Force a recompile to occur.

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk print`**

   `lwarpmk again` updates the date code for the file, triggering a recompile the next time the document is made.[5]

5. Process the index.[6] [7]

   Enter ⇒ **`lwarpmk printindex`**

6. Recompile again to include the index.

   Enter ⇒ **`lwarpmk print`**

7. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk print1`**

Note that the HTML customization commands are ignored while making the print version.

[5] Although, when using the utility *latexmk* (introduced later), the changed date is ignored and an actual change in contents must occur to cause a recompile.

[6] The command **`lwarpmk printglossary`** is also available to process a glossary produced with the glossaries package. See section 8.6.11.

[7] Also see section 8.6.14 for index options.

5.3 Compiling the HTML version with *lwarpmk*

`lwarpmk html` is used to recompile an HTML version of the document.

1. Compile the HTML version:

   Enter ⇒ **`lwarpmk html`**

   (a) *lwarpmk* uses LaTeX to process `tutorial_html.tex` to create `tutorial_html.pdf`.

   (b) *pdftotext* is then used to convert to the file `tutorial_html.html`. This file is a plain-text file containing HTML tags and content for the entire document.

   (c) *lwarpmk* manually splits `tutorial_html.html` into individual HTML files according to the HTML settings. For this tutorial, the result is `tutorial.html` (the home page), along with `First-chapter.html`[8], `Some-math.html`, and the document's index in `_Index.html`.[9]

2. View the HTML page in a web browser.

   Open the file `tutorial.html` in a web browser.

   math Note that math is still displayed as its `alt` tag, which is the plain-text LaTeX source, until the images of the math expressions have been generated. Math may be displayed as SVG images or by a MathJax script, as seen in sections 5.4 and 5.5.

3. Force a recompile:

   Enter ⇒ **`lwarpmk again`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk print`**

4. Process the HTML index and recompile:[10][11]

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   `_Index.html` is updated for the new LaTeX index.

5. Reload the web page to see the added index.

6. To force a single recompile when needed, even if no changes were detected:

   Enter ⇒ **`lwarpmk html1`**

[8] `First-chapter.html` also contains the first section, even though the second section is its own html page. This behavior is controlled by the boolean `CombineHigherDepths`.

[9] `index.html` is commonly used as a homepage, so the document index is in `_Index.html`.

[10] The command **`lwarpmk htmlglossary`** is also available to process a glossary produced with the glossaries package. See section 8.6.11.

[11] Also see section 8.6.14 for index options.

5.4 Generating the SVG images

math as svg images

By default lwarp represents math as SVG images, with the LaTeX source included in `alt` attributes. In this way, the math is displayed as it was drawn by LaTeX, and the LaTeX source may be copied and pasted into other documents.

`picture` and Tikz

lwarp uses the same mechanism for `picture` and Ti*k*z environments.

1. Create the SVG images:

   Enter ⇒ **`lwarpmk limages`**

   Enter ⇒ **`lwarpmk html`**

2. Move to the tutorial's HTML math page and reload the document in the browser.
3. The math images are displayed using the same font and formatting as the printed version.
4. Copy/paste a math expression into a text editor to see the LaTeX source.

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[12] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ html instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

⚠ page counter

Incorrect SVG images will also occur if the document changes the page counter:

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

⚠ Lots of files!

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 5.5 to use MathJax instead.

[12] This becomes important when dealing with a document containing thousands of images.

5.5 Using MathJax for math

math with MathJax

Math may also be represented using the MathJax JavaScript project.

1. In the tutorial's source code, uncomment the `mathjax` package option for lwarp:

   ```
   mathjax, % Use MathJax to display math.
   ```

2. Recompile

   Enter ⇒ **`lwarpmk html`**

3. Reload the math page.

⚠ MathJax requirements

MathJax requires web access unless a local copy of MathJax is available, and it also requires that JavaScript is enabled for the web page. The math is rendered by MathJax. Right-click on math to see several options for rendering, and for copying the LaTeX source.

While using MathJax has many advantages, it may not be able to represent complex expressions or spacing adjustments as well as LaTeX, and it may not support some math-related packages.

5.6 Changing the css style

For a formal css style, add to the preamble:

```
\usepackage{lwarp}
. . .
\CSSFilename{lwarp_formal.css}
. . .
\begin{document}
```

For a modern css style, `lwarp_sagebrush.css` is also provided:

```
\CSSFilename{lwarp_sagebrush.css}
```

See section 7.5 for more information about modifying the css styling of the document.

5.7 Customizing the HTML output

A number of settings may be made to control the HTML output, including filename generation, automatic compilation, math output, document splitting, meta data, and page headers and footers.

See section 7.4 for more information.

5.8 Using *latexmk*

latexmk is a LaTeX utility used to monitor changes in source files and recompile as needed.

1. In the tutorial's source code uncomment the `latexmk` option for the lwarp package:

   ```
   latexmk, % Use latexmk to compile.
   ```

2. Recompile the printed version of the document.

   Enter ⇒ **`lwarpmk print`**

   lwarp updates its own configuration files (`lwarpmk.conf` and `tutorial.lwarpmkconf`) whenever the printed version of the document is compiled. These configuration files remember that *lwarpmk* should use *latexmk* to compile the document.

3. Recompile the document.

   Enter ⇒ **`lwarpmk print`**

   and/or

   Enter ⇒ **`lwarpmk html`**

Changes are detected by comparing checksums rather than modification times, so `lwarpmk again` will not trigger a recompile, but *latexmk* has a much better awareness of changes than the *lwarpmk* utility does and it is likely to correctly know when to recompile. A recompile may be forced by making a small change to the source, and a single recompile may be forced with:

forced single-pass recompile

Enter ⇒ **`lwarpmk print1`**

and/or

Enter ⇒ **`lwarpmk html1`**

5.9 Using XeLaTeX or LuaLaTeX

XeLaTeX or LuaLaTeX may be used instead of LaTeX.

1. Remove the auxiliary files for the project:

   Enter ⇒ **`lwarpmk cleanall`**

2. Use *xelatex* or *lualatex* to compile the printed version a single time.

   Enter ⇒ **`xelatex tutorial.tex`**

   -or-

   Enter ⇒ **`lualatex tutorial.tex`**

   When the compile occurs, the configuration files for *lwarpmk* are modified to remember which TeX engine was used. XeLaTeX or LuaLaTeX will be used for future runs of *lwarpmk*.

3. To recompile the document:

   Enter ⇒ **`lwarpmk print`**

   -and-

   Enter ⇒ **`lwarpmk html`**

4. Also remember to update the indexes and recompile again:

   Enter ⇒ **`lwarpmk htmlindex`**

   Enter ⇒ **`lwarpmk html`**

   Enter ⇒ **`lwarpmk printindex`**

   Enter ⇒ **`lwarpmk print`**

5.10 Using DVI LaTeX

Traditional DVI LaTeX may also be used along with `.eps` image files. An SVG version of each image must also be provided. *lwarpmk* may be used to convert image formats.

To convert EPS files to PDF:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

To convert PDF files to SVG:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

⚠ bitmapped fonts See section 7.2 regarding font selection to avoid the use of bitmapped fonts.

5.11 Using a glossary

lwarp supports the gloss and glossaries packages, although this tutorial does not supply an example.

5.11.1 gloss package

See section 8.6.10.

5.11.2 glossaries package

To process the glossary for the print version:

Enter ⇒ **`lwarpmk printglossary`**

⚠ (If **`makeglossaries`** is not found, see section 8.6.11.)

To process the glossary for the HTML version:

Enter ⇒ **`lwarpmk htmlglossary`**

In each case, the document will have to be recompiled afterwards:

Enter ⇒ **`lwarpmk html1`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk print1`**

Enter ⇒ **`lwarpmk print`**

See section 8.6.11 to set options for processing glossaries.

5.12 Cleaning auxiliary files

To remove the auxiliary files `.aux`, `.toc`, `.lof`, `.lot`, `.idx`, `.ind`, `.log`, and `.gl*`:

Enter ⇒ **`lwarpmk clean`**

5.13 Cleaning auxiliary and output files

To remove the auxiliary files, and also remove the `.pdf` and `.html` files:

Enter ⇒ **`lwarpmk cleanall`**

5.14 Cleaning the images from the `<project>-images` directory

The `<project>-images` directory contains SVG images automatically generated for inline and display math, tikz, etc. To remove all the images from the `lateximages` directory:

Enter ⇒ **`lwarpmk cleanlimages`**

5.15 Converting PDF or EPS images to SVG

HTML cannot display PDF or EPS images, so any external PDF graphics images must be converted to SVG format. *pdftocairo* and *epstopdf* may be used one image at a time, but *lwarpmk* also provides a way to convert PDF or EPS images in bulk:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of files)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of files)**

Be sure to always provide SVG files for HTML output.

5.16 Creating HTML from an incomplete compile

During testing it may be useful to finish the HTML conversion even when the document had errors and did not compile successfully. To attempt an HTML conversion of an incomplete document:

Enter ⇒ **`lwarpmk pdftohtml [-p project]`**

5.17 Processing multiple projects in the same directory

It is possible to have several projects in the same directory. *lwarpmk* has an optional parameter which is the document to compile.

To create each project:

Enter ⇒ **pdflatex project_a**

Enter ⇒ **pdflatex project_b**

Each project is given its own configuration file:

`project_a.lwarpmkconf, project_b.lwarpmkconf`

To compile each project with `lwarkmk`:

Enter ⇒ **lwarpmk print -p project_a**

Enter ⇒ **lwarpmk html -p project_b**

5.18 Using the *make* utility

lwarpmk has an action which may be useful for integration with the common *make* utility:

```
lwarpmk pdftohtml [-p project]
```

make may be used to compile the code to PDF with HTML tags (`project_html.pdf`), then *lwarpmk* may be used to convert each target to HTML files.

6 Converting an existing document

To convert an existing document for use with lwarp:

1. Arrange the document in the following order:
   (a) Declare the `\documentclass`.
   (b) Load text fonts.
   (c) Load inputenc or inputenx, fontenc, and/or fontspec.
   (d) Load lwarp.
   (e) Load remaining packages.
2. Modify the document:

⚠ math in section names

   (a) If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

⚠ scale

   (b) Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

   to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

   (c) Possible changes to `tabular` environments include: `*` columns, multirow, longtable, supertabular, xtab, bigdelim. See section 8.10.1.
   (d) Possible option clashes with memoir. See section 8.13.
   (e) If using indexes, see section 8.6.14.
   (f) If using many indexes, glossaries, `.aux` files, etc., see section 8.6.14 regarding morewrites. If morewrites is already used, be sure to add the setup with `allocate=10`.
   (g) Other changes as per Special cases and limitations, section 8.
3. Convert any PDF images to SVG. See section 8.8.
4. Manually compile the print version with *latex*, *pdflatex*, *lualatex*, or *xelatex*.
5. `lwarpmk print` to finish the print version.
6. `lwarpmk html` to create the HTML version.
7. `lwarpmk limages` to create the SVG images of any SVG math, `lateximage`, Ti*k*z, etc.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

7 Additional details

7.1 Shell escape

Opt --shell-escape

Some documents require the use of an external program, which is allowed when using the `--shell-escape` command-line option. When the document is first compiled manually, and also whenever the print version is recompiled, lwarp detects and remembers whether shell escape is enabled. If so, it will also be enabled when the document is recompiled with *lwarpmk*.

7.2 Font and UTF-8 support

⚠ type 3 bitmapped fonts

lwarp uses *pdftotext* to convert PDF output into UTF-8-encoded text. This process requires that UTF-8 information be embedded in the PDF file, which may prevent the use of older "type 3" bit-mapped fonts, and of older packages such as ae. The lwarp option `pdftotextEnc` may be useful in some situations. See section 7.3.

vector fonts

Computer Modern

⚠ *pdflatex*

⚠ DVI *latex*

Pkg cm-super

While using DVI *latex* or PDF *pdflatex*, if no font-related package is specified then the default Computer Modern font is used, which may be a "type 3" bit-mapped font which may not convert well to plain text. A "type 1" vector font is required.

To use the updated cm-super's type 1 fonts instead of Computer Modern, install the cm-super font package.

Pkg lmodern

To use Latin Modern instead, add

```
usepackage{lmodern}
```

to the preamble.

Pkg dejavu

Another useful option is the Deja Vu series of fonts, which have an increased coverage of language and glyphs:

```
\usepackage{dejavu}
```

latex, *pdflatex*, T1, UTF8

While using DVI *latex* or PDF *pdflatex*, lwarp automatically loads fontenc with T1 encoding. fontenc may be loaded with an additional encoding after lwarp. inputenc is automatically loaded with UTF8 encoding if if has not yet been loaded, but may also be specified with another encoding such as `latin1`. See the next section regarding index encoding.

⚠ *xelatex* and *lualatex*

XeLaTeX and LuaLaTeX users must use the fontspec package. Do NOT use fontenc!

Place fontspec or fontenc, xunicode, and other font and UTF-8 related commands after the `\documentclass` command and before `\usepackage{lwarp}`.

⚠ package conflicts

In some cases, a package conflict may require that a font package be loaded after lwarp, which should work as well:

1. `documentclass{article/book/report}` comes first, followed by any of:

2. Font and UTF-8 related commands:

   - For XeLaTeX or LuaLaTeX:

     – fontspec and font choices

     Pkg fontspec

     ligatures

     lwarp sets the following to turn off TeX ligatures during the generation of HTML tags, and turn off common ligatures in regular text, since older browsers may not display them correctly and newer browsers can automatically re-create them.

     ```
     \defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
     \defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
     \defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
     ```

   - For *pdflatex*:

     (a) `\usepackage{lmodern}`, or other font-related packages

     Pkg lmodern

     (b) `\usepackage[T1]{fontenc}`

     Pkg fontenc

     (c) `\usepackage[utf8]{inputenc}`, or `latin1`, etc. Or use inputenx.

     Pkg inputenc

     (d) `\usepackage{newunicodechar}` along with related definitions.

     Pkg inputenx

     Pkg newunicodechar

     (e) To assist with the PDF-HTML conversion:

     File glyphtounicode.tex

     i. `\input glyphtounicode.tex`

     ii. `\input glyphtounicode-cmr.tex% from the pdfx package`

     iii. `\pdfgentounicode=1`

     (f) Another option to assist with the PDF-HTML conversion:

     – `\usepackage{cmap}`

     Pkg cmap

     (g) `\usepackage{textcomp}`

     Pkg textcomp

3. `\usepackage{lwarp}` (section 7.3) goes after any of the above, followed by:

4. `\usepackage{newtxmath}` or other math-related font packages. Many of these load amsmath, which must be loaded after lwarp, so they must also be loaded after lwarp.

⚠ fontspec with traditional font packages

5. `\setmonofont{TeX Gyre Cursor}` or similar may be required if using XeLaTeX or LuaLaTeX and fontspec along with traditional font packages such as txfonts, newtxtext, etc. This is required to turn off the monospaced font's ligatures with fontspec after loading the traditional font packages. Monospaced output ligatures must be turned off to produce the correct HTML characters.

6. … the rest of the preamble and the main document.

⚠ UTF-8 locale In some cases, an external program may require a UTF-8 "locale". See section 9.8.

7.2.1 Indexes, glossaries, and encoding

lwarp uses the *xindy* program to processes indexes. *xelatex* and *lualatex* use *xindy* and *pdflatex* uses *texindy*.

The lwarp option `xindyLanguage` may be used to set the language option for xindy, and the `xindyCodepage` option may be used to set the codepage option for xindy. These are used for index generation.

7.3 lwarp package loading and options

lwarp supports book, report, and article classes, as well as the equivalent Koma-script classes and memoir, and various CJK-related classes and packages.

Load the lwarp package immediately after the font and UTF-8 setup commands.

Package options may be set while loading lwarp, or later with

```
\lwarpsetup{⟨key=value, . . . ⟩}
```

Pkg lwarp

lwarp package options are as follows:

Opt mathsvg
Opt mathjax

mathsvg, mathjax: For math display, select mathsvg (default) or mathjax. For more information about the math options, see section 8.7.

Opt latexmk
Default: false

latexmk: Tells *lwarpmk* to use *latexmk* to recompile the document several times if necessary. Otherwise, *lwarpmk* attempts to determing for itself whether to recompile. See section 7.4.

Opt dvips
Default: false

dvips: Tells *lwarpmk* to use *dvips* and *ps2pdf* to convert DVI output to PDF.

Opt dvipdfm
Default: false

dvipdfm: Tells *lwarpmk* to use *dvipdfm* to convert DVI output to PDF.

Opt dvipdfmx
Default: false

dvipdfmx: Tells *lwarpmk* to use *dvipdfmx* to convert DVI output to PDF.

Opt HomeHTMLFilename
Default: {}

HomeHTMLFilename: See section 7.4.

Opt HTMLFilename
Default: {}

HTMLFilename: See section 7.4.

Opt PrintLatexCmd
Default: <automatic>

PrintLatexCmd: Sets the shell commands executed by **lwarpmk print**. If not specified, will automatically be set according to the detected LaTeX engine and the use of --shell-escape.

Opt HTMLLatexCmd
Default: <automatic>

HTMLLatexCmd: Sets the shell commands executed by **lwarpmk html**. If not specified, will automatically be set according to the detected LaTeX engine and the use of --shell-escape.

Opt makeindex
Default: makeindex

makeindex: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use *makeindex* when generating indexes with **lwarpmk printindex**, **lwarpmk htmlindex**, or *latexmk*. If neither makeindex nor xindy is used, makeindex is assumed.

Opt xindy
Default: makeindex

xindy: Sets PrintIndexCmd, HTMLIndexCmd, and LatexmkImageCmd to use *xindy* when generating indexes with **lwarpmk printindex**, **lwarpmk htmlindex**, or *latexmk*.

Opt makeindexStyle
Default: lwarp.ist

makeindexStyle: If you wish to use a custom .ist file for index generation, see section 28.

Opt xindyStyle
Default: lwarp.xdy

xindyStyle: If you wish to use a custom .xdy file for index generation, see section 28.

Opt xindyLanguage
Default: english

xindyLanguage: If using an index or glossary, see section 28.

Opt xindyCodepage
Default: utf8

xindyCodepage: If using an index, see section 28.

Opt PrintIndexCmd
Default: <automatic>

PrintIndexCmd: Sets the shell commands executed by **lwarpmk printindex**. If not specified, will be set by the selection of makeindex or xindy. May be used to specify the creation of multiple indexes. See section 8.6.14.

Table 5: lwarp package options

Option	Description
mathsvg	Show math using svg images.
mathjax	Show math using MathJax.
latexmk	Use *latexmk* for compiling documents.
dvips	Use *dvips* and *ps2pdf* to convert dvi documents.
dvipdfm	Use *dvipdfm* to convert dvi documents.
dvipdfmx	Use *dvipdfmx* to convert dvi documents.
HomeHTMLFilename	The filename of the home page.
HTMLFilename	A prefix for the filenames of the remaining web pages.
PrintLatexCmd	The shell commands for **lwarpmk print**.
HTMLLatexCmd	The shell commands for **lwarpmk html**.
For indexing (section 8.6.14) and glossaries (section 8.6.11):	
makeindex	Use *makeindex* to generate indices.
xindy	Use *xindy* to generate indices.
makeindexStyle	Set a custom style for *makeindex*.
xindyStyle	Set a custom style for *xindy*.
xindyLanguage	The *xindy* language option used for index generation.
xindyCodepage	The *xindy* codepage option used for index generation.
PrintIndexCmd	Shell commands executed by **lwarpmk printindex**.
HTMLIndexCmd	Shell commands executed by **lwarpmk htmlindex**.
LatexmkIndexCmd	Shell commands executed by *latexmk*.
GlossaryCmd	Shell command executed by **lwarpmk printglossary** and **lwarpmk htmlglossary**.
Seldom necessary:	
OSWindows	Force compatibility with MS-Windows.
pdftotextEnc	Set the encoding for *pdftotext*.
lwarpmk	Generate a local copy of lwarpmk.lua.
Used internally by lwarp:	
warpprint	Generate print output, and also generate configuration files.
warpHTML	Generate html output.
BaseJobname	The \jobname to use. Set to the \jobname of the printed version even while generating html.

Examples:

```
makeindex -s lwarp.ist projectname.idx                (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname.idx      (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `PrintIndexCmd` to sensible values for each of those programs while compiling a single index. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `PrintIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C` *xindy* options, as the lwarp `xindyLanguage` and `xindyCodepage` options are not used for the `PrintIndexCmd` option when it is set manually.

This option is stored in the configuration files `lwarpmk.conf` and `*.lwarpmkconf`, and is then passed by the **`lwarpmk printindex`** command to the operating system to compile the print indexes. Since the command string is parsed by TEX, written to a file, read from the file by LuaTEX, and finally passed to the operating system, any attempt at quoting will be problematic. For complicated commands, it would be best to create a shell script, and simply refer to the script with the lwarp `PrintIndexCmd` option.

Opt `HTMLIndexCmd`
Default: `<automatic>`

`HTMLIndexCmd:` Sets the shell commands executed by **`lwarpmk htmlindex`**. If not specified, will be set by the selection of `makeindex` or `xindy`. May be used to specify the creation of multiple indexes. See section 8.6.14.

⚠ filenames

Example settings are similar to `PrintIndexCmd`, but append `_html` to the filenames:

```
makeindex -s lwarp.ist projectname_html.idx           (makeindex)
xindy -M lwarp.xdy -L english -C utf8 projectname_html.idx  (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `HTMLIndexCmd` to sensible values for each of those programs while compiling a single index. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified.

⚠ xindy

If specifying `HTMLIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C` *xindy* options, as the lwarp `xindyLanguage` and `xindyCodepage` options are not used for the `HTMLIndexCmd` option when it is set manually.

As with `PrintIndexCmd`, to generate complicated indexes it may be worthwhile to use a shell script, then refer to that script with `HTMLIndexCmd`.

Opt `LatexmkIndexCmd`
Default: `<automatic>`

`LatexmkIndexCmd:` Sets the shell commands executed by *latexmk*. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, `LatexmkIndexCmd` does not include any filenames, which will be provided instead by *latexmk*. See section 8.6.14.

Example settings are similar to `PrintIndexCmd`, but without a filename:

```
makeindex -s lwarp.ist                                (makeindex)
xindy -M lwarp.xdy -L english -C utf8                      (xindy)
```

automatic setting

The use of the `makeindex` or `xindy` options sets `LatexmkIndexCmd` to either of the two settings show above. lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanuage`, and `xindyCodepage` options will be used if specified. Unlike `PrintIndexCmd` and `HTMLIndexCmd`, *latexmk* uses either of the single-line settings of `LatexmkIndexCmd` shown above to compile each of multiple indexes if necessary.

⚠ xindy

If specifying `LatexmkIndexCmd` manually, be sure to assign an *xindy* language and codepage with the `-L` and `-C` *xindy* options, as the lwarp `xindyLanguage` and `xindyCodepage` options are not used for the `LatexmkIndexCmd` option when it is set manually.

Opt `GlossaryCmd`
Default: **`makeglossaries`**

GlossaryCmd: Sets the shell command executed by **`lwarpmk printglossary`** and **`lwarpmk htmlglossary`**. The print or HTML glossary filename is appended to this command. See section 8.6.11.

Opt `OSWindows`

OSWindows: lwarp attempts to automatically sense WINDOWS, but it may be forced with this option. See section 7.6.

Opt `pdftotextEnc`
Default: `UTF-8`

pdftotextEnc: Used to specify the encoding used by *pdftotext* during the PDF-HTML conversion. In most situations, the default is the correct choice.

Opt `lwarpmk`

lwarpmk: If you wish to have lwarp generate a local copy of `lwarpmk.lua` for archival or local-installation purposes, compile the print version with the `lwarpmk` option set. See section 28.

The following options are used internally by lwarp, and usually are not used in the user's document:

Opt `warpprint`
Opt `warpHTML`

warpprint and warpHTML: Usually controlled by *lwarpmk*, and not set in the document. Select the `warpprint` option to generate print output (default), or the `warpHTML` option to generate HTML5 output. The default is print output, so the print version may be compiled with the usual *pdflatex*, etc. When lwarp is loaded in print mode, it creates `<project>_html.tex`, which sets the `warpHTML` option before calling the user's source code `<project>.tex`. In this way, `<project>.tex` can `\usepackage{lwarp}` without any options to create a printed version, while `<project>_html.tex` will create an HTML version.

Opt `BaseJobname`
Default: `\jobname`

BaseJobname: Not intended for the user. Used internally by lwarp when creating the `*_html.tex` file used to compile the HTML version. See section 28.

7.4 Customizing the HTML output

Table 6 shows several settings may be used to customize the HTML output. Watch for the correct placement of each!

⚠ Placement!

⚠ Changes! Note that if changes are made, it is best to first:

1. Clear all the HTML, PDF, and auxiliary files:
   Enter ⇒ **`lwarpmk clearall`**
2. Recompile the print version in order to recreate the configuration files for *lwarpmk*:
   Enter ⇒ **`lwarpmk print`**
3. Finally, recompile the HTML version with the new settings:
   Enter ⇒ **`lwarpmk html`**

Options for the lwarp package:

Use the following as options for `\usepackage[<options>]{lwarp}`:

Opt HomeHTMLFilename
Default: \BaseJobname

HomeHTMLFilename: Filename of the homepage, without the "`.html`" suffix. Defaults to the `\BaseJobname`. A common setting is:

```
HomeHTMLFilename=index
```

causing the homepage to be the file `index.html`. Underscores are allowed in `HomeHTMLFilename` and `HTMLFilename` options, but may need to be escaped elsewhere, such as when appearing in a list:

filename underscores

```
\item [\href{file\_name.pdf}{text}] \
```

See section 7.4.1 for examples of naming and numbering HTML files.

Opt HTMLFilename
Default: <empty>

HTMLFilename: A filename prefix for the rest of the HTML web pages. Useful for numbered web pages with a common prefix. May be empty. See section 7.4.1 for examples of naming and numbering HTML files.

Opt latexmk
Default: false

latexmk: Controls whether lwarp uses *latexmk* to compile the document. This setting is written to *lwarpmk*'s configuration files.

Opt mathsvg
Default: true

mathsvg: Selects SVG display for math output. (The default.)

Opt mathjax
Default: false

mathjax: Selects MathJax for math output.

Opt makeindex
Default: makeindex

makeindex: Selects *makeindex* for index generation by *lwarpmk*.

Opt xindy
Default: makeindex

xindy: Selects *xindy* for index generation by *lwarpmk*.

Placed in the preamble before `\begin{document}`:

`\linkhomename`
Default: Home

`\linkhomename`: Name of the link to the home page. Paragraphs are allowed. Redefine with `\renewcommand`.

Table 6: html settings

Macro/Cntr/Bool	Description
\linkhomename	Name of the link to the homepage.
SideTOCDepth	Sectioning depth of the sidetoc.
\sidetocname	Name of the sidetoc.
FileDepth	Sectioning depth of the file splits.
CombineHigherDepths	Combine higher section levels.
FileSectionNames	Use section names for file names, else use numbers.
\FilenameLimit	Maximum length of the generated filenames.
FootnoteDepth	Sectioning depth of footnotes.
\abstractname	The name of the abstract.
\mathimagename	The svg math image lateximage alt tag.
\packagediagramname	The suffix for a package's lateximage alt tags.
\CSSFilename	The css for the following files.
\MathJaxFilename	The MathJax script for the following files.
\HTMLLanguage	The html lang tag.
\HTMLTitle	The homepage's <title>, overriding \title.
\HTMLTitleBeforeSection	Set subpage <title>s to \HTMLTitle - sectionname
\HTMLTitleAfterSection	Set subpage <title>s to sectioname - \HTMLTitle
\HTMLAuthor	The html author meta tag, overriding \author.
\HTMLDescription	The html description meta tag.
\HTMLFirstPageTop	Heading for the home page.
\HTMLPageTop	Heading for the other pages.
\HTMLPageBottom	Footing for all pages.
HTMLDebugComments	Boolean to generate html comments.

Ctr tocdepth

tocdepth: Sectioning depth of the table of contents. See section 16 for a list of LaTeX stack depths.

Ctr SideTOCDepth
Default: 1

SideTOCDepth: Sectioning depth of the sideTOC. Defaults to 1, causing the sideTOC to show sections but not subsections.

sidetoc

Each subpage of the website has its own small table of contents on the side (the "sideTOC"). Its depth is set by SideTOCDepth. This sideTOC is only shown if the web page is wide enough. When using a narrow web browser window, "responsive web design" is used to show the sideTOC at the top of the page and a link back to **Home** at the bottom.

It is recommended to set:

```
SideTOCDepth=FileDepth
```

or

```
SideTOCDepth=FileDepth+1
```

⚠ inaccessible pages

If SideTOCDepth<FileDepth, web pages will be inaccessible via the sideTOC.

\sidetocname
Default: Contents

\sidetocname: Name of the sideTOC. Paragraphs are allowed. Redefine with \renewcommand.

Ctr FileDepth
Default: -5

FileDepth: Sectioning depth of file splits. Defaults to -5, causing the entire HTML website to be one single file.

- To place the entire file into one HTML page, use:
  `\setcounter{FileDepth}{-5}`
- To split the HTML file at \section depth, use:
  `\setcounter{FileDepth}{1}`

⚠

- To ensure that the HTML pages/files are accessible:
  Place a \tableofcontents somewhere before the first section break (therefore in the "home page"), and set
  `tocdepth>=FileDepth`

Bool CombineHigherDepths
Default: true

CombineHigherDepths: Combine a higher section with its first lower subsections, down to the FileDepth. Defaults to true. Set to false to simulate the concept of a chapter opening on its own page, for example.

The file splits are controlled by the counter FileDepth and the boolean CombineHigherDepths. Setting FileDepth to 0 splits the file at chapters, 1 at sections, etc. CombineHigherDepths controls whether to combine pages at levels higher than the chosen FileDepth, such as in this tutorial where the page which opens the chapter also contains the first section. Be careful to set tocdepth and SideTOCDepth to allow access to each page of the website. Set tocdepth and SideTOCDepth to be greater than or equal to FileDepth.

⚠ Inaccesible pages!

⚠ Lost in an old page!

When making changes to the file structure, it is possible to end up with the web browser pointing to an old file which is no longer in use. When this occurs, changes to the web site will not appear in the browser, even if reloading the page, because that page is no longer in use. It is best to return to the home page, clean the files (`lwarpmk cleanall`), change

FileDepth and/or CombineHigherDepths, then finally recompile and re-navigate to the desired page using the new file structure.

Bool FileSectionNames
Default: true

FileSectionNames: If true, web page filenames are derived from a sanitized version of the section names. If false, web pages are numbered. Either way, the HTMLFilename option is used as a prefix. See section 7.4.1 for examples of naming and numbering HTML files. The user must ensure that filenames are unique after begin sanitized. For example, math in the section name is removed before creating the filename, so the rest of the filename must be sufficiently unique to avoid name collisions.

⚠ Unique filename!

\FilenameLimit
Default: 80

\FilenameLimit: The maximum length of the filenames generated by lwarp. ".html" is added to this length. Redefine with \renewcommand.

Ctr FootnoteDepth
Default: 3

FootnoteDepth: Determines where to place pending footnotes. 3 places footnotes before each break down to the \subsubsection level. 1 places footnotes before each \section break. Any pending footnotes are also placed at the bottom of each page before each file break.

Bool HTMLDebugComments
Default: false

HTMLDebugComments: Set true to generate HTML comments, such as which section or is being opened or closed.

\abstractname
Default: Abstract

\abstractname: The name of the abstract. This may also be over-written by the babel package. Defaults to "Abstract". Redefine with \renewcommand.

Placed before \begin{document}, or before any sectioning command which causes a file break:

\CSSFilename
Default: lwarp.css

\CSSFilename: {⟨*filename.css*⟩} Sets the css file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The css styles of the web pages are set by the \CSSFilename command. If \CSSFilename is not used, a default plain style is used to mimic printed LaTeX output. lwarp_sagebrush.css is a semi-fancy colored style as shown in this tutorial. Change it to lwarp_formal.css for a more formal look, or comment out the \CSSFilename command to see the default. \CSSFilename may be used before each file break to set the css for individual pagess of the website.

\MathJaxFilename
Default: lwarp_mathjax.txt

\MathJaxFilename: {⟨*filename*⟩} Sets the MathJax script file to use for the following files. May be changed before each each sectioning command which would cause a file split.

The MathJax script file is copied into the head of each HTML file. This may be used to point to a local repository, add extensions, or change the script somewhere in the middle of the document. \MathJaxFilename may be used before each file break to set the script file for individual pages of the website.

\HTMLLanguage
Default: en-US

\HTMLLanguage: {⟨*langauge*⟩} The HTML file's HTML lang meta tag. Defaults to en-US.

\HTMLTitle
Default: \thetitle

\HTMLTitle: {⟨*title*⟩} Overrides \title for the HTML header's meta title. De-

faults to \thetitle, which is set by \title, or empty otherwise. Unlike the author, \thetitle is set by \title even if not using the titling package.

\HTMLTitleBeforeSection
Default: \HTMLTitleBeforeSection

\HTMLTitleBeforeSection: Sets subpage <title> tags to show the website title followed by the section name.

\HTMLTitleAfterSection

\HTMLTitleAfterSection: Sets subpage <title> tags to show the section name followed by the website title.

custom <title>

To customize subpage <title>s, redefine \theHTMLTitleSection, which defaults to:

```
\def\theHTMLTitleSection{%
  \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
}
```

\HTMLAuthor
Default: \theauthor

\HTMLAuthor: {⟨*author*⟩} The HTML header's meta author. Defaults to \theauthor, which is set by \author if using the titling package, but is empty otherwise. There are several ways to represent the author and affiliations, especially if using the authblk package, most of which do not result in a sensible \theauthor, so \HTMLAuthor is useful to create a list of authors without their affiliations.

\HTMLDescription
Default: <empty>

\HTMLDescription: {⟨*description*⟩} Sets the HTML description tag for the following files. May be changed before each each sectioning command which would cause a file split.

\HTMLFirstPageTop
Default: <empty>

\HTMLFirstPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of the home page. Useful for logos, etc. Defaults empty. Ignored in print output.

\HTMLPageTop
Default: <empty>

\HTMLPageTop: {⟨*contents*⟩} A user-definable custom action applied to the top of pages other than the home page. Useful for logos, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

\HTMLPageBottom
Default: <empty>

\HTMLPageBottom: {⟨*contents*⟩} A user-definable custom action applied to the bottom of each web page. Useful for authors, copyright notices, contact information, etc. Defaults empty. \LinkHome may be used to place a link back to the homepage. Ignored in print output.

Placed in the home page before the first sectioning command which causes a file break:

\tableofcontents
⚠ TOC on the homepage!

\tableofcontents: Used to place a table of contents on the home page. This command must be used before the first file split, so that a way is available to navigate to other files from the homepage.

Links to each chapter/section are provided, as selected by tocdepth.

Placed in the document wherever necessary:

\mathimagename
Default: math image

\mathimagename: Redefine with \renewcommand. When creating an SVG math

image, its alt tag may be set to the math expression, which may be hashed for image reuse. In the case of \ensuremath or after \inlinemathother, where the contents require a unique image for each instance of the same expression, the alt tag is set to \mathimagename, and the image is not reused.

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "math image", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

\packagediagramname
Default: diagram

\packagediagramname: Redefine with \renewcommand. For many packages, the output is placed inside a lateximage with an HTML alt tag set to the package name followed by \packagediagramname. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following lateximages.

Env warpprint

warpprint: An environment which is only used while generating print output. Place inside anything which does not apply to HTML and which may cause problems with lwarp. If lwarp knows about and emulates or supports a package then its related macros, lengths, counters, etc. probably won't have to be placed inside a warpprint environment, but unknown packages may cause problems which may be isolated from lwarp using this environment.

⚠ *Do not place anything else on the same line as* \end{warpprint}.

Env warpHTML

warpHTML: An environment which is only used while generating HTML output. This is useful for website logos and other items which have no purpose in printed output.

⚠ *Do not place anything else on the same line as* \end{warpHTML}.

\warpprintonly

\warpprintonly: {⟨*contents*⟩} A macro version of the warpprint environment.

\warpHTMLonly

\warpHTMLonly: {⟨*contents*⟩} A macro version of the warpHTML environment.

7.4.1 Example HTML file naming

Examples of ways to name or number HTML files:

Numbered HTML nodes:

Example: Homepage index.html, and node-1, node-2. [13]

[13] See \SetHTMLFileNumber to number in groups by chapter, for example.

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={node-}
]{lwarp}
\boolfalse{FileSectionNames}
```

Named HTML sections, no prefix:

Example: `index.html`, and `About.html`, `Products.html`

```
\usepackage[
    HomeHTMLFilename=index,
    HTMLFilename={}
]{lwarp}
\booltrue{FileSectionNames}
```

Named HTML sections, with prefix:

Example: Homepage `mywebsite.html`, and additional pages such as `mywebsite-About.html`, `mywebsite-Products`, etc.

```
\usepackage[
    HomeHTMLFilename=mywebsite,
    HTMLFilename={mywebsite-}
]{lwarp}
\booltrue{FileSectionNames}
```

7.5 Customizing the css

`\CSSFilename` {⟨*filename*⟩}
Default: `lwarp.css`

`\CSSFilename` may be used to choose which `.css` file is used to display each page of the web site. Use `\CSSFilename` before `\begin{document}` to assign the style of the home page. If different parts of the website should have different styles, call `\CSSFilename` again before each section heading which creates a new file. This may be changed numerous times throughout the file, resulting in different HTML pages having different CSS files assigned:

```
...
\CSSFilename{myCSS.css}
\chapter{Another Chapter}
...
```

The styles provided by lwarp include:

`lwarp.css`: A default style if `\CSSFilename` is not used. This style is comparable to a plain LaTeX document. To set this style, you may use `\CSSFilename{lwarp.css}`, or no `\CSSFilename` call at all.

lwarp_formal.css: A formal style with a serif fonts and a traditional look.

lwarp_sagebrush.css: A style with muted colors, gradient backgrounds, additional borders, and rounded corners.

To see each style in use, change the `\CSSFilename` entry in the tutorial, `lwarpmk html` again, and then reload the tutorial webpage.

Custom css

A customized style may also be created. For each new project a file called `sample_project.css` is generated. This may be renamed to `<project>.css` then used by assigning `\CSSFilename{<project>.css}`.

⚠ Rename it!

Note that `sample_project.css` is overwritten whenever lwarp is loaded in print mode. It is therefore important to rename the file to something like `<project>.css` before using it, so that your own changes are not overwritten.

`<project>.css` has an entry which loads `lwarp.css`, and this entry may be changed to load `lwarp_formal.css` or `lwarp_sagebrush.css` if desired. Additional changes to the css may be made by making entries later in the `<project>.css` file.

File lwarp.css
File project.css
File sample_project.css

It is best to make a local project-specific css file such as `project.css`, containing only things which are different from `lwarp.css`. The file `project.css` should refer to `lwarp.css` as follows:

```
/* ( --- Start of project.css --- ) */
/* ( --- A sample project-specific CSS file for lwarp --- ) */

/* Uncomment one of the following: */
@import url("lwarp.css") ;
/* @import url("lwarp_formal.css") ; */
/* @import url("lwarp_sagebrush.css") ; */

/* Project-specific CSS setting follow here. */
/* . . . */

/* ( --- End of project.css --- ) */
```

Finally use `\CSSFilename{<project>.css}` in the document to activate the custom css.

7.6 Selecting the operating system

Prog Unix
Prog Mac OS
Prog Linux

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

Prog MS-Windows

If MS-WINDOWS is not correctly detected, use the lwarp option `OSWindows`.

Prog Windows
Opt OSWindows

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set `true`. This boolean may be tested by the user for later use.

7.7 Selecting actions for print or HTML output

The following environments and macros are used to select actions which only apply to either traditional LaTeX print-formatted PDF generation, or to HTML generation.

For most of built-in LaTeX and many additional packages there is user-level source code support or emulation, so no special handling will be required. For those cases which lwarp does not handle by itself, the following environments and macros may be used to isolate sections of code for print-only or HTML-only.

These environments are also useful for creating a special version of the titlepage for print and another for HTML.

Env warpHTML Anything which is to be done only for HTML5 output is surrounded by a warpHTML environment:

```
\begin{warpHTML}
 ... something to be done only during \HTML\ generation
\end{warpHTML}
```

⚠ \end{warpHTML} Do *not* place anything else on the same line as \end{warpHTML}. The exact phrase is used to mark the end of the environment.

Env warpprint Anything which is to be done only for print output is surrounded by a warpprint environment:

```
\begin{warpprint}
 ... something to be done only during traditional \PDF\ generation
\end{warpprint}
```

⚠ \end{warpprint} As above, do not place anything else on the line with \end{warpprint}.

Env warpall Anything which is to be done for any output may be surrounded by a warpall environment. Doing so is optional.

```
\begin{warpall}
 ... something to be done during print \PDF\ or \HTML\ output
\end{warpall}
```

As above, do not place anything else on the line with \end{warpall}.

Macros are also provided for print-only or HTML-only code:

\warpprintonly {⟨*actions*⟩}

Performs the given actions only when print output is being generated.

\warpHTMLonly {⟨*actions*⟩}

Performs the given actions only when HTML output is being generated.

7.8 Commands to be placed into the warpprint environment

Certain print-related commands should always be placed inside a warpprint environment, or may need other special handling. These are unrelated to HTML output, but are hard to isolate automatically. For example:

- Paragraph formatting: \parindent \parskip
- Manual page positions such as the textpos package, which is emulated but only in a limited way.
- Anything changing the page counter. lwarp requires that the page counter not be adjusted during HTML output.

Some packages require additional setup commands. Where these packages are emulated for HTML, setup commands may work for the emulated HTML output as well as for print output. See the details for each package in this document for more information.

Also see section 13: Troubleshooting.

7.9 Title page

In the preamble, place an additional block of code to set the following:

```
\title{Document Title} % One line only
\author{Author One\affiliation{Affiliation One} \and
    Author Two\affiliation{Affiliation Two} }
\date{Optional date}
```

The title is used in the meta tags in the HTML files, unless overridden by \HTMLTitle, and the rest are used in \maketitle. To use a \subtitle or \published field, see section 66.8.

\maketitle Use \maketitle just after the \begin{document}, as this will establish the title of the homepage. Optionally, use a titlepage environment instead.

Env titlepage The titlepage environment may be used to hold a custom title page. The titlepage will be set in a class titlepage, and \printtitle, etc. may be used inside this environment.

Env titlingpage Another form of custom title page, where \maketitle is allowed, and additional information may be included as well.

\title {⟨*title*⟩}

⚠ newlines

Avoid newlines in the \title; these will interfere with the file break and css detection. Use a \subtitle command instead (section 66.8). The title will appear in the document \maketitle as a heading <h1>. The HTML meta title tag will also have this title, unless \HTMLTitle is used to set the meta title to something else instead.

\author {⟨*author*⟩}

In \author, \protect may be needed before some formatting commands. In HTML, the author will appear in a of class author in the \maketitle. If the titling package is used, the author will also appear in a HTML meta tag, but \HTMLAuthor may be necessary to create a plain list of names if \author had affiliations added. \affiliation is a new addition to lwarp.

\date {⟨*date*⟩}

\date works as expected. In HTML, this will appear in a class titledate.

\thanks {⟨*text*⟩}

\thanks are allowed in the titlepage fields, and will be rendered as HTML notes at the bottom of the title page.

7.10 HTML page meta descriptions

\HTMLDescription {⟨*A description of the web page.*⟩}
Default: (none)

limitations

Each page of HTML output should have its own HTML meta description, which usually shows up in web search results, is limited to around 150 characters in length, and should not include the ASCII double quote character (").

placement

Use \HTMLDescription just before \begin{document} to set the description of the home page, and also just before each sectioning command such as \chapter or \section where a new file will be generated, depending on FileDepth. For example, if FileDepth is 1, use \HTMLDescription just before each \section command, and that description will be placed inside the HTML page for that \section. The same descrition will be used for all following HTML files as well, until reset by a new \HTMLDescription. It is best to use a unique description for each HTML file.

disabling

To disable the generation of HTML description meta tags, use:

```
\HTMLDescription{}
```

7.11 HTML homepage meta title

\HTMLTitle {⟨*title*⟩}
Default: \HTMLtitle{\thetitle}

Sets the contents of the web page <meta name="title"> element. May be set empty to cancel the meta title tag.

See section 7.4 for \HTMLTitleBeforeSection and \HTMLTitleAfterSection, used to set the title for HTML subpages.

7.12 HTML page meta author

\HTMLAuthor {⟨*author*⟩}
Default: \HTMLAuthor{\theauthor}

Sets the contents of the web page <meta name="author"> element. May be set empty to cancel the meta author tag.

\author may be used to create a list of authors and their affiliations, in several formats if using authblk, and these may not successfully parse properly into a sensible list for \theauthor. \HTMLAuthor may be used to set the meta tag to a simple list of names.

8 Special cases and limitations

Some commonly-used LaTeX expressions should be modified as follows to allow for a smooth conversion to both HTML and print-formatted outputs.

Need help?

See the General Index for "how-to", and the Troubleshooting Index if something doesn't work. The Index of Objects contains automated entries for each package, macro, environment, counter, boolean, and other objects; individually and also sorted by category. A Troubleshooting section is also available.

8.1 Things to avoid

In the document, avoid the following:

page counter: Do not adjust the page counter. If doing so is required for the print version, place the adjustment inside a warpprint environment.

Custom math environment macros: Do not use expressions such as \beq as a replacement for \begin{equation}.

Custom macros in section, figure, table names: Custom macros which appear in sectioning commands or float captions then appear in the .toc, .lof, and .lot lists, and should be made robust using \newrobustcmd or \robustify from etoolbox, xparse, etc.

When setting FileSectionNames to true to name the HTML files from the section names, the file names are created from sanitized versions of the chapter or section names, but the section names must be plain text or something which expands into plain text. Robust macros will not work at the sectioning level which is used for file names, but a robust macro or other complicated name may be used for the manditory argument of \chapter, \section, etc., if a plain-text version is also included in the optional argument:

```
\chapter[Plain Name]{\ARobustMacro{Fancy Name}}
```

8.1.1 Invalid HTML

Additionally, some objects are valid LaTeX, but invalid HTML. An example is a tabular inside `\textbf`, since HTML does not allow a table inside a span. lwarp will create the table, and the browser may support it, but the result is technically invalid.

8.2 Formatting

8.2.1 Text formatting

⚠ `\bfseries`, etc. `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ HTML special chars &, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the listings package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

verbatim The various `verbatim`-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

8.2.2 Horizontal space

`\hspace` `\hspace` is converted to an inline HTML span of the given width, except that `0` width is ignored, a width of `.16667em` is converted to an HTML thin breakable space (`U+2009`), and a `\fill` is converted to a `\qquad`.

`\,` ~ and `\,` are converted to HTML entities.

`\kern` `\hskip` `\kern` and `\hskip` are entered into the HTML PDF output as-is, then interpreted by *pdftotext*, and thus usually appear as a single space.

8.2.3 Text alignment

Use the environments `center`, `flushright`, `flushleft` instead of the macros `\centering`, `\raggedright`, `\raggedleft`.

⚠ `figure` & `table` alignment `\centering`, etc. are honored in a `figure` or `table` if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

8.2.4 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX.

8.2.5 textcomp package

Pkg textcomp

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols

Many textcomp symbols are not supported by many system / browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

8.2.6 Superscripts and other non-math uses of math mode

Use `\textsuperscript{x}` instead of `$^{x}$`

8.2.7 Empty `\item` followed by a new line of text or a nested list:

lists

Use a trailing backslash: `\item[label] \`

8.2.8 Filenames and URLs in lists or footnotes

filename underscore

Escape underscores in the filenames:

```
\item[\href{file\_name.pdf}{text}]
```

8.2.9 relsize package

Pkg relsize

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small

The HTML browser's setting for minumum font size may limit how small the output will be displayed.

8.3 Boxes and minipages

8.3.1 Marginpars

`\marginpar` `[⟨left⟩] {⟨right⟩}` `\marginpar` may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the `\marginpar`. Paragraph breaks are converted to `<br />` tags.

`\marginparBlock` `[⟨left⟩] {⟨right⟩}` To include block-related macros, use `\marginparBlock`, which takes the same arguments but creates a `<div>` instead of a `<span>`. A line break will occur in the text where the `\marginBlock` occurs.

8.3.2 Save Boxes

⚠ boxes TEX boxes are placed inline and do not allow line breaks, so boxes with long contents may overflow the line during HTML conversion. lwarp uses methods which help avoid this problem.

⚠ `minipage, \parbox` `\savebox` and related do not (yet) support `minipage` or `\parbox`.

8.3.3 Minipages

⚠ inline A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement `minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side Side-by-side `minipages` may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span There is limited support for `minipages` inside an HTML `<span>`. An HTML `<div>` cannot appear inside a `<span>`. While in a `<span>`, `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an “inline” format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ minipage size When using `\linewidth`, `\textwidth`, and `\textheight`, widths and heights in HTML are scaled proportionally to a 6×9 inch text area, and inside a `multicols` `\linewidth` is divided by the specified number of columns.

if width is `\linewidth` If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if html A new macro `\minipagefullwidth` requests that, during HTML output, the next single `minipage` or `\parbox` be generated without an HTML `width` attribute, allowing it to

be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ tabular, multicols

\UseMinipageWidths
\IgnoreMinipageWidths

Inside a tabular or multicols environment, where the width depends on the browser window, \minipagefullwidth is effectively used by default for every minipage or \parbox inside the environment. \UseMinipageWidths may be used to tell lwarp to honor the specified widths of all following minipages and \parboxes until the end of the local scope, and \IgnoreMinipageWidths may be used to tell lwarp to ignore the specified widths.

⚠ text alignment

Nested minipages adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a flushleft or similar environment in the child minipage to force a text alignment.

8.3.4 Side-by-side minipages

Place side-by-side minipages inside a center environment, with horizontal space between them, such as \quad, \qquad, \hspace, or \hfill. The result is similar in print and HTML. Do not use space commands at the start or end of the line.

8.3.5 Framed minipages and other environments

\fbox can only be used around inline items during HTML output, but HTML cannot place a block element such as a for a minipage or a list inside of a . Several options are provided for framing an object, depending on which kind of object and which packages are loaded:

\fbox
\fboxBlock
Env fminipage

For a framed object, options include:

To remove the frame in HTML output: Place the \fbox command and its closing brace inside warpprint environments. This will nullify the frame for HTML output.

For inline text:

To frame the contents inline with some formatting losses in HTML: This is the default action of \fbox when enclosing a minipage. During HTML output, \fbox nullifies the HTML tags for minipage, \parbox, and lists. The contents are included as inline text inside the \fbox's of class framebox. For lists, line breaks are converted to HTML breaks. The result is a plain-text inline version of the contents, framed inline with the surrounding text, but lacking any extra HTML markup.

For inline minipage and lists:

To frame the contents on their own line with improved formatting in HTML: A new command \fboxBlock is included, intended to be a direct replacement for \fbox for cases where the \fbox surrounds a minipage, table, or list. For print output, this behaves as \fbox. For HTML output, the contents are placed inside an HTML with the class framed, resulting in the contents being placed on their own line with a frame surrounding them. The contents preserve their HTML formatting, so lists and minipages look nicer, and valid HTML is created for a tabular. While an \fbox containing a tabular is valid LaTeX code,

the result in HTML is problematic since a table is a not a , so use \fboxBlock around a tabular, or else place the tabular inside a minipage, or use fminipage, described next. Also see below regarding the "Misplaced alignment tab character &." error.

For display tabular, minipages, and lists:

To create a framed minipage in both print and HTML: A new environment fminipage is included. For print output, this is identical to minipage, except that it is also framed. For HTML output, this forms a of class framed, the contents preserve their HTML formatting, and valid HTML is created for a tabular. Also see section 85 for a new environment fcolorminipage. Also see below regarding the "Misplaced alignment tab character &." error.

colored boxes and frames:

To create colored frames and boxes: See section 512 for xcolor's \colorbox and \fcolorbox, and lwarp's additional \colorboxBlock and \fcolorboxBlock.

⚠ Misplaced alignment tab character &

To frame tables or verbatim environments: Place the contents inside a fminipage, or perhaps a \fboxBlock for a tabular. Also, if using \fboxblock with tabular, you will have to use \StartDefiningTabulars before the start of the macro which uses \fboxBlock and the tabular, and \StopDefiningTabulars afterwards. Also see the lwarp documentation for the fancybox package.

To frame equations: See section 217 for the fancybox package.

For fancy framed minipages: See packages boxedminipage2e, shadow, fancybox, framed, mdframed.

Custom environments: Use a custom environment to create a sidebar, containing a BlockClass environment with custom css formatting, and \warpprintonly{\hrule} command:

```
\begin{BlockClass}{frameminipage}% ignored in print output
  % use \CSS\ to format div class ``framedminipage''
\warpprintonly{\hrule} % only appears in print output
Contents
\warpprintonly{\hrule} % only appears in print output
\end{BlockClass}
```

8.3.6 fancybox package

Pkg fancybox

framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

`\fbox` works with fancybox. Also see lwarp's `\fboxBlock` macro and `fminipage` environment for alternatives to `\fbox` for framing environments.

framed table example

The fancybox documentation's example framed table using an `\fbox` containing a `tabular` does not work with lwarp, but the `FramedTable` environment does work if `\fbox` is replaced by `\fboxBlock`. This method loses HTML formatting. A better method is to enclose the table's contents inside a `fminipage` environment. The caption may be placed either inside or outside the `fminipage`:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the `verbatim` environment inside a span, box, or fancybox's `\Sbox`, but a `verbatim` may be placed inside a `fminipage`. The fancybox documentation's example `FramedVerb` may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}
```

framed `\VerbBox`

fancybox's `\VerbBox` may be used inside `\fbox`.

indented alignment

`LVerbatim`, `\LVerbatimInput`, and `\LUseVerbatim` indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

8.3.7 mdframed package

Pkg mdframed support

Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading

When used, lwarp loads mdframed in HTML with `framemethod=none`.

font

For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont

`theoremtitlefont` is not supported, since the following text is not in braces in the mdframed source.

ignored options

`userdefinedwidth` and `align` are currently ignored.

css classes

Environments created or encapsulated by mdframed are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class |mdframedtitle|. Subtitles are in a `<div>` of class |mdframedsubtitle|, and likewise for subsubtitles.

8.4 Section names

If using named HTML files, by selecting `\booltrue{FileSectionNames}`, the generated filenames may be simplified by using `\FilenameSimplify` and `\FilenameNullify`:

`\FilenameSimplify` `{`⟨*text*⟩`}`

To remove common short words from the automatically-generated filenames, replacing each with a single hyphen "-", use `\FilenameSimplify`:

```
\FilenameSimplify*{-in-}
\FilenameSimplify*{A-}
```

The first example removes the word "in" in the middle of a filename, and the second example removes "A" at the start of the filename. The star forces the arguments to be detokenized, which is required for a plain-text comparison. (The unstarred form is used for a token-sensitive comparison, which is seldom required by the user.) After simplfication, repeated hyphen characters will be further simplified to a single hyphen "-". Finally, single hyphens at the start or end of the filename are removed.

`\FilenameNullify` `{`⟨*macros*⟩`}`

⚠ macros in section names

Macro names may appear in the automatically-generated file names. To remove these, create *non-robust* nullified versions of the macros, ensuring that each line ends with a percent character `%` as shown below. These are placed inside `\FilenameNullify`, which adds them to the list of macros which are nullfiied during filename generation. Low-level macros such as `\begingroup` will cause problems when nullfied. Many macros such as `\textbf` are already nullfied. lwarp also already nullifies built-in symbol and textcomp macros, including if defined by xunicode, but not all xunicode macros. See the definition of `\LWR@nullfonts` for a complete list.

```
\FilenameNullify{%
  \renewcommand*{\macroname}[1]{#1}%
  \renewcommand*{\anothermacro}{}%
}
```

⚠ duplicate filename

Avoid duplicate file names. Section names at levels which result in HTML file splits must be unique. lwarp will generate an error if a duplicate HTML filename is generated. Use the optional TOC caption entry parameter for formatting. Remember to `\protect` LaTeX commands which appear in section names and TOC captions.

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

8.5 Cross-references

labels

⚠ label characters

Labels with special characters may be a problem. It is best to stick with alphanumeric, hyphen, underscore, and perhaps the colon (if not French).

`\nameref`

⚠ empty link

`\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

8.5.1 Page references

⚠ LaTeX page numbers

The printed page does not translate to the HTML page, so `\pageref` references are converted to parentheses containing `\pagerefPageFor`, which defaults to "see ", followed by a hyperlink to the appropriate object.

Ex:

```
\ref{sec:name} on page \pageref{sec:name}
```

in HTML becomes:

"Sec. 1.23 on page (**see** sec. 1.23)".

`\pagerefPageFor` may be redefined to "page for ", empty, etc. See page 461.

8.5.2 cleveref and varioref packages

Pkg cleveref

Pkg varioref

⚠ cleveref page numbers

cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

Ex:

```
\cpageref{tab:first,tab:second}
```

in html becomes:

"pages **for** table 4.1 and **for** table 4.2"

See \cpagerefFor at page 534 to redefine the message which is printed for page number references.

8.5.3 Hyperlinks, hyperref, and url

Pkg hyperref
Pkg url

lwarp emulates hyperref, including the creation of active hyperlinks, but does not require that hyperref be loaded by the document.

⚠ comments between arguments

Do not place a comment with a % character between arguments for \hyperref, etc., as it is neutralized for inclusion in HTML URLs.

lwarp can also load url, but url should not be used at the same time as hyperref, since they both define the \url command. lwarp does not (yet) attempt to convert url links into hyperlinks during HTML output, nor does the print version of url create hyperlinks.

⚠ backref

When generating HTML, lwarp's emulation of hyperref does not automatically load backref, so backref must be loaded explicitly.

8.5.4 Footnotes and page notes

lwarp uses native LaTeX footnote code, although with its own \box to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for \alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

footmisc

The footmisc stable option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the stable option, provide a short TOC entry, and \protect the \footnote:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc
⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the stable option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust \secnumdepth instead.

fancybox, fancyvrb
⚠ \VerbatimFootnotes
⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

pfnote
⚠ pfnote numbers

While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

bigfoot, manyfoot
⚠ verbatim

Verbatim footnotes are not yet supported.

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

8.6 Front and back matter

8.6.1 Custom classes with multiple authors and affiliations

Some classes allow multiple authors and affiliations. Often it is possible to emulate these using a standard class along with authblk:

```
%\documentclass{customclass} % for print document
\documentclass{article} % for html document

\usepackage{lwarp}
\begin{warpHTML}
\usepackage{authblk}
\let\affiliation\affil % maybe required
\end{warpHTML}
```

8.6.2 Starred chapters and sections

The following describes \ForceHTMLPage and \ForceHTMLTOC, which may be used for endnotes, glossaries, tocbibind, bibliographies, and the index. See the following sections where applicable. Continue here if interested in the reason for adding these commands to lwarp.

Some packages use \chapter* or \section* to introduce reference material such as notes or lists, often to be placed in the back matter of a book. These starred sections are placed inline instead of on their own HTML pages, and they are not given TOC entries.

lwarp provides a method to cause a starred section to be on its own HTML page, subject to FileDepth, and also a method to cause the starred section to have its own TOC entry during HTML output.

\ForceHTMLPage

To place a starred section on its own HTML page, use \ForceHTMLPage just before the \chapter* or \section*. lwarp will create a new page for the starred sectional unit.

A starred sectional unit does not have a TOC entry unless one is placed manually. The typical method using \phantomsection and \addcontentsline works for inline text but fails when the new starred section is given its own webpage after the TOC entry is created, or when creating an EPUB where the TOC entry will point to the page before the starred section. If the starred section has its own HTML page but no correct TOC entry pointing to that page, the page will be inaccessible unless some other link is created.

⚠ inaccessible html page

\ForceHTMLTOC

To automatically force the HTML version of the document to have a TOC entry for a starred section, use \ForceHTMLTOC just before the \chapter* or \section*, and place \phantomsection and \addcontentsline inside a warpprint environment.

For print output, \ForceHTMLTOC and \ForceHTMLPage have no effect.

8.6.3 abstract package

Pkg abstract

If using the number option with file splits, be sure to place the table of contents before the abstract. The number option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

⚠ missing toc

8.6.4 titling and authblk

Pkg titling

Pkg authblk

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

package support

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

⚠ load order

\published and \subtitle

8.6.5 tocloft package

Opt [tocloft] titles
Pkg tocloft
Pkg tocloft
⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

8.6.6 appendix package

Pkg appendix
⚠ incorrect toc link

During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

8.6.7 pagenote package

Pkg pagenote

pagenote works as-is, but the `page` option is disabled.

8.6.8 endnotes package

Pkg endnotes
table of contents

To place the endnotes in the TOC, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

html page

To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

8.6.9 BibTeX

\etalchar

Displays a superscript "+" to indicate "and others".

⚠ Modify *.bib

When enough authors are cited for a source, BibTeX may use the `\etalchar` command to display a math superscript with a + character to indicate "and others". Without modification, this will result in an "Improper `\prevdepth`" error. At present, lwarp requires that `\etalchar` be replaced by a text superscript. To do so, add to the start of the `.bib` file the following:

```
@PREAMBLE{"\let\etalchar\relax \newcommand{\etalchar}[1]{\textsuperscript{#1}}"}
```

8.6.10 gloss package

Pkg gloss

⚠ compiling

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

8.6.11 glossaries package

Pkg glossaries

processing glossaries

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

lwarpmk has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

The shell command to execute is set by the lwarp option `GlossaryCmd`, which defaults to **`makeglossaries`**. The print or HTML glossary filename is appended to this command.

⚠ *makeglossaries* not found

In some situations it may be required to modify the default command, such as to add the **`perl`** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and toc options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style

The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/html versions The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

8.6.12 nomencl package

Pkg nomencl To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

8.6.13 Indexing overview

There are many ways to process indexes for a LaTeX document, including native LaTeX capabilities, a number of packages and classes, the possible availability of shell escape and *latexmk*, and the need to process print and HTML versions. lwarp attempts to provide easy recompilation of indexes along with the rest of the document, but the various indexing options must be set correctly. Numerous examples are given below. Some differ in minor details, so the important parts are highlighted in red, and options are in green.

Once set up properly, the entire document may be recompiled with **`lwarpmk print`** and **`lwarpmk html`**. In some cases, it will also be necessary to compile the indexes with **`lwarpmk printindex`** and **`lwarpmk htmlindex`**. A recompile may then be forced with **`lwarpmk print1`** and **`lwarpmk html1`**.

manual processing The user may continue to process indexes manually or by shell script without the use of *lwarpmk*, but adjustments will be required to process HTML indexes as well. In general, `*.idx` and `*.ind` files will be accompanied by `*_html.idx` and `*_html.ind` files.

custom index style If using a custom indexing style file, see sections 8.6.19 and 8.6.20.

source code See section 76 for lwarp's core index and glossary code, section 283 for index, section 440 for splitidx, section 282 for imakeidx, section 475 for tocbibind, and section 532.17 for memoir's indexing patches.

8.6.14 Indexing with basic LaTeX and makeidx

lwarpmk processing The following allow the user to process indexes automatically, or using *lwarpmk*'s commands:

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

For a single index using *makeindex*:

```
\usepackage[makeindex,latexmk] {lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.ist` style file. When creating the HTML index, "`_html`" is automatically appended to each of the names.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index using *xindy*:

```
\usepackage[
    xindy,
    xindyLanguage=english,                  <optional>
    xindyCodepage=utf8,                     <optional>
    latexmk                                 <optional>
]{lwarp}
```

The usual `.idx` and `.ind` files will be used, along with the new `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

8.6.15 Indexing with index

lwarp is told how to use *makeindex* using the `PrintIndexCmd` and `HTMLIndexCmd` options. The file `lwarp.ist` is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

For multiple indexes using *makeindex* and index:

(Assuming that the second index has file extensions .sist and .sind)

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist
      -o <projectname>.sind <projectname>.sidx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist
      -o <projectname>_html.sind <projectname>_html.sidx
  }
]{lwarp}
\usepackage{index}
. . .
\makeindex
\newindex{secondname}{sidx}{sind}{Second Index}
```

⚠ Windows *For WINDOWS, replace the two ";" characters with "&".*

When creating the HTML index, "_html" is automatically appended to the index filenames.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

8.6.16 Indexing with splitidx

lwarp is told how to use *splitindex* using the PrintIndexCmd and HTMLIndexCmd options. The file lwarp.ist is specified, which generates index letter heads for print output and also allows special HTML formatting for HTML output.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

⚠ \thepage When using \AtWriteToIndex or \AtNextWriteToIndex, the user must not refer to \thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 532.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

For multiple indexes using *makeindex* and splitidx:

```
\usepackage[
  makeindex, latexmk,
  PrintIndexCmd={
    splitindex <projectname> -- -s lwarp.ist
  },
  HTMLIndexCmd={
    splitindex <projectname>_html -- -s lwarp.ist
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "_html" is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

For multiple indexes using *xindy* and splitidx:

```
\usepackage[
  xindy, latexmk,
  PrintIndexCmd={
    splitindex -m xindy <projectname> -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  },
  HTMLIndexCmd={
    splitindex -m xindy <projectname>_html -- -M lwarp.xdy
      -L english -C utf8                          <optional>
  }
]{lwarp}
\usepackage{splitidx}
. . .
\makeindex
\newindex[Second Index]{secondname}
```

When creating the HTML index, "_html" is automatically appended to each of the names.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.17 Indexing with imakeidx

Due to the number of methods which may be used to process multiple indexes, the options for style file and *xindy* language and codepage must be specified in one of several different ways. These are described in detail later in this section, but are summarized here.

If shell escape is used, imakeidx will automatically compile the indexes by itself. Options specifying a custom style file and *xindy* language and codepage must be specified for each `\makeindex` command using its `options=` option, which must include lwarp's special `lwarp.ist` or `lwarp.xdy` file, or a file based on them. If using a custom indexing style file, see sections 8.6.19 and 8.6.20. The `splitindex` option is also available of shell escape is used, in which case the splitidx package and *splitindex* program will also be used.

If shell escape is not possible, *latexmk* may be used to automatically compile the indexes. The style, language, and codepage options are specified with lwarp's `makeindexStyle`, `xindyStyle`, `xindyLanguage`, and `xindyCodepage` options. These are passed to *latexmk* by *lwarpmk*'s **lwarpmk printindex** and **lwarpmk htmlindex** commands.

Where shell escape and *latexmk* are not possible, *lwarpmk* may be used to manually compile the indexes. lwarp's `PrintIndexCmd` and `HTMLIndexCmd` options are used.

For a single or multiple indexes using *makeindex* and imakeidx:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

imakeidx will automatically compile the indexes. Shell escape is not required while using *makeindex*. `latexmk` may be specified, and if so it will be used for **lwarpmk print** and **lwarpmk html**, but *imakeidx* will actually create the indexes.

For a single or multiple indexes using *makeindex* and *splitindex* with imakeidx:

The index style `lwarp.ist` is automatically used for HTML output. This file turns on letter headings, so it may be desirable to specify it as an option, in which case it will also be used for print output, which will help match the print and HTML output.

```
\usepackage[makeindex,latexmk] {lwarp}
\usepackage[makeindex,splitindex]{imakeidx}
. . .
\makeindex[options={-s lwarp.ist}]
\makeindex[name=secondname,options={-s lwarp.ist}]
```

⚠ enable shell escape

Shell escape is required while using *splitindex*. For the first compile, use

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex*, and will also use *makeindex* to compile the indexes.

`latexmk` may be specified, and if so it will be used for **`lwarpmk print`** and **`lwarpmk html`**, but *imakeidx* will actually create the indexes.

For multiple indexes using *xindy* and imakeidx, using shell escape:

Options may be given to imakeidx's `\makeindex` command. The style file `lwarp.xdy` is automatically used for HTML output, and is not necessary for print output since the output will be similar. If language or codepage must be set, they should be specified as options for `\makeindex`, since imakeidx will process the indexes.

```
\usepackage[xindy,latexmk] {lwarp}
\usepackage[xindy,splitindex]{imakeidx}
. . .
\makeindex[
  options={ -M lwarp.xdy -L english -c utf8 }
]
\makeindex[
  name=secondname,
  options={ -M lwarp.xdy -L english -c utf8 }
]
```

⚠ enable shell escape

For the first compile, use

Enter ⇒ **pdflatex --shell-escape projectname.tex**

Enter ⇒ **pdflatex --enable-write18 projectname.tex** **(MiKTeX)**

or similar with *xelatex* or *lualatex*. lwarp will remember that shell escape was used.

imakeidx will automatically execute *splitindex* if selected, and will also use *xindy* to compile the indexes.

If selected, *latexmk* will automatically recompile the entire document as necessary.

For indexes using *xindy* and *imakeidx*, without shell escape, but *with* *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\usepackage[
  xindy,
  xindyLanguage=english,                    <optional>
  xindyCodepage=utf8,                       <optional>
  latexmk,
]{lwarp}
\usepackage[xindy]{imakeidx}
...
\makeindex
\makeindex[name=secondname]
```

latexmk will create the indexes automatically when **`lwarpmk print`** and **`lwarpmk html`** are executed.

For indexes using *xindy* and *imakeidx*, without shell escape, and *without* *latexmk*:

lwarpmk must be told how to create the indexes:

```
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
\usepackage[xindy]{imakeidx}
...
\makeindex
\makeindex[name=secondname]
```

⚠ Windows

For WINDOWS, replace the two ";" characters with "&".

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

8.6.18 Indexes with memoir

For a single index with memoir and makeindex:

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.ist` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and makeindex, using *latexmk*:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[makeindex,latexmk]{lwarp}
. . .
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically when the user executes **`lwarpmk print`** and **`lwarpmk html`**.

For multiple indexes with memoir and makeindex, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  makeindex,
  PrintIndexCmd={
    makeindex -s lwarp.ist <projectname>.idx ;
    makeindex -s lwarp.ist secondname.idx
  },
  HTMLIndexCmd={
    makeindex -s lwarp.ist <projectname>_html.idx ;
    makeindex -s lwarp.ist secondname_html.idx
  }
]{lwarp}
. . .
\makeindex
\makeindex[secondname]
```

⚠ Windows

For WINDOWS, replace the two ";" characters with "&".

`<projectname>` is the `\jobname`: if compiling "`name.tex`", use the filenames `name.idx` and `name_html.idx`.

Use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For a single index with memoir and xindy:

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk                                   <optional>
]{lwarp}
...
\xindyindex
\makeindex
```

The usual `.idx` and `.ind` files will be used, along with the `lwarp.xdy` style file.

lwarpmk will use *latexmk* if specified, in which case *latexmk* will create the index automatically. Otherwise, use

Enter ⇒ **`lwarpmk printindex`**

Enter ⇒ **`lwarpmk htmlindex`**

to compile the indexes.

For multiple indexes with memoir and xindy, using latexmk:

lwarp's options are used, and are passed to *latexmk*.

```
\documentclass{memoir}
\usepackage[
    xindy,
    xindyLanguage=english,                    <optional>
    xindyCodepage=utf8,                       <optional>
    latexmk
]{lwarp}
...
\xindyindex
\makeindex
\makeindex[secondname]
```

lwarpmk will use *latexmk* to create the indexes automatically.

For multiple indexes with memoir and xindy, *without* latexmk:

lwarpmk must be told how to create the indexes:

```
\documentclass{memoir}
\usepackage[
  xindy,
  PrintIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname.idx
  },
  HTMLIndexCmd={
    xindy -M lwarp.xdy -L english -C utf8
      <projectname>_html.idx ;
    xindy -M lwarp.xdy -L english -C utf8
      secondname_html.idx
  }
]{lwarp}
...
\xindyindex
\makeindex
\makeindex[secondname]
```

⚠ Windows

For WINDOWS, replace the four ";" characters with "&".

<projectname> is the \jobname: if compiling "name.tex", use the filenames name.idx and name_html.idx.

Use

Enter ⇒ **lwarpmk printindex**

Enter ⇒ **lwarpmk htmlindex**

to compile the indexes.

8.6.19 Using a custom *makeindex* style file

Prog makeindex
File lwarp.ist

When using *makeindex*, *lwarpmk* uses the file lwarp.ist to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *makeindex* style file:

1. Copy lwarp.ist to a new filename such as projectname.ist
2. Make changes to projectname.ist. Keep the lines which refer to \hyperindexref. These lines creates the hyperlinks for the HTML index. During print output \hyperindexref becomes a null function.

Opt makeindexStyle

3. In the document source use the makeindexStyle option for lwarp:

```
\usepackage[
    ... other options ...
```

```
    \textred{makeindexStyle=projectname.ist},
]{lwarp}
```

Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

4. Recompile the print version, which causes lwarp to rewrite the `lwarpmk.conf` configuration file. This tells *lwarpmk* to use the custom `projectname.ist` file instead of `lwarp.ist`.

8.6.20 Using a custom *xindy* style file

Prog xindy
File lwarp.xdy

When using *xindy*, *lwarpmk* uses the file `lwarp.xdy` to process the index. This file is over-written by lwarp whenever a print version of the document is processed.

To use a custom *xindy* style file:

1. Copy `lwarp.xdy` to a new filename such as `projectname.xdy`
2. Make changes to `projectname.xdy`.

   Keep the lines which refer to `\hyperindexref`:

   ```
   (define-attributes (("hyperindexref")))
   (markup-locref :open "\hyperindexref{" :close "}")
   ...
   (markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
   ```

   These lines create the hyperlinks for the HTML index. During print output `\hyperindexref` becomes a null function.

   To create custom styles, refer to the lines for `\textbf` and `\textit`.

Opt xindyStyle

3. In the document source use the `xindyStyle` option for lwarp:

   ```
   \usepackage[
       ... other options ...
       \textred{xindyStyle=projectname.xdy},
   ]{lwarp}
   ```

   Likewise, refer to the custom style file if using `\PrintIndexCmd`, `\HTMLIndexCmd`, or `\LatexmkIndexCmd`.

4. Recompile the print version, which causes lwarp to rewrite the `lwarpmk.conf` configuration file. This tells *lwarpmk* to use the custom `projectname.xdy` file instead of `lwarp.xdy`.

8.6.21 Additional indexing limitations

⚠ xindy with hyperref

xindy and hyperref may not work well together for print output with “see”, “see also”, reference ranges, or stylized index references. It may be necessary to turn off hyper-referencing for indexes:

```
\usepackage[hyperindex=false]{hyperref}
```

⚠ empty index

If an HTML index is empty, it may be necessary to add the following before lwarp is loaded:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
. . .
\usepackage{lwarp}
```

makeindex custom display styles

When using *makeindex*, custom display styles are possible:

```
\begin{warpprint}
\newcommand{\notesstyle}[1]{#1nn}
\end{warpprint}

\begin{warpHTML}
\makeatletter
\newcommand{\notesstyle}[1]{\LWR@doindexentry{#1} notes }
\makeatother
\end{warpHTML}
. . .
A sentence.\index{key|notesstyle}
```

xindy custom display styles

For custom styles with *xindy*, see `lwarp.xdy` for `\textbf` and `\textit` as examples.

8.6.22 Index positions, TOC, tocbibind

placement and toc options

An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex
numbered index section

Use the tocbibind `numindex` option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

Pkg tocloft
⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

8.7 Math

8.7.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

8.7.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MathJax JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially

speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 10 regarding EPUB output with MathJax.

8.7.3 SVG option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[14], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For $\mathcal{AMS}$ environments with multiple numbers in the same environment, only the first and last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{AMS}$ environment, although the `\tag` macro will still appear inside the LaTeX math expression.

⚠ SVG math in TeX boxes

SVG math does not work inside TeX boxes, since a `\newpage` is required before and after each image.

8.7.4 MathJax option

MathJax math option

Prog MathJax

The popular MathJax alternative (`mathjax.org`) may be used to display math.

When MathJax is enabled, math is rendered twice:

[14] See section 517 regarding fonts and fractions.

1. As regular LaTeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LaTeX, and

2. As detokenized printed LaTeX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LaTeX values, and the MathJax cross-referencing system is ignored in favor of the LaTeX internal system, seamlessly integrating with the rest of the LaTeX code.

8.7.5 Customizing MathJax

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

8.7.6 MathJax limitations

MathJax limitations

Prog MathJax

Limitations when using MathJax include:

subequations

- MathJax itself does not support subequations. This may be improved by parsing the LaTeX math expression to manually insert tags, but this has not yet been done.

footnotes in math

- Footnotes inside equations are not yet supported while using MathJax.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

⚠ siunitx inside an equation

https://github.com/burnpanck/MathJax-siunitx

Also see section 8.7.11.

tabbing

- A `tabbing` environment is emulated using an HTML <pre>.While MathJax is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

⚠ other macros and packages

- Other math-related macros and packages are not supported by MathJax, including \ensuremath and bigdelim, along with occasionally-used macros such as \relax. lwarp emulates footnotes, units, and nicefrac for MathJax.

8.7.7 Catcode changes

preamble macros with math

The math shift character $ is not set for HTML output until after the preamble. Macros defined in the preamble which contain $ must be enclosed between \StartDefiningMath and \StopDefiningMath to temporarily change to the HTML meaning of $:

```
\StartDefiningMath
\newcommand{. . . }
\StopDefiningMath
```

As an alternative, use \(and \) instead of $, in which case \StartDefiningMath and \StopDefiningMath are not necessary.

If a package defines macros using $, it may be nessary to use \StartDefiningMath and \StopDefiningMath before and after loading the package.

8.7.8 Complicated inline math objects

\inlinemathnormal
\inlinemathother

changing contents
complicated alt tag

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as $x+1$, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an alt tag. The macro \inlinemathother may be used before a dynamic math expression, and \inlinemathnormal after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.

8.7.9 Complicated display math objects

\displaymathnormal

By default, or when selecting \displaymathnormal, MathJax math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother
MathJax unsupported
complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML alt tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

8.7.10 ntheorem package

Pkg ntheorem

⚠ Font control

This conversion is not total. Font control is via CSS, and the custom LaTeX font settings are ignored.

⚠ Equation numbering

ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environmentswhen the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's `thref` option.

8.7.11 siunitx package

Pkg siunitx

fractions

Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required

Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script.

⚠ tabular

Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

8.7.12 units and nicefrac packages

Pkg units

Pkg nicefrac

units and nicefrac work with lwarp, but MathJax does not have an extension for units or nicefrac. These packages do work with lwarp's option `svgmath`.

8.7.13 newtxmath package

Pkg newtxmath

⚠ loading sequence

The proper load order is:

```
...
\usepackage{lwarp}
...
\usepackage{amsthm}
\usepackage{newtxmath}
...
```

8.8 Graphics

Pkg graphics

Pkg graphicx

⚠ scale

Avoid using the `\includegraphics` `scale` option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

\includegraphics file formats

For \includegraphics with .pdf or .eps files, the user must provide a .pdf or .eps image file for use in print mode, and also a .svg, .png, or .jpg version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the .pdf or .eps format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a .pdf or .eps image is referred to with its file extension, the extension will be changed to .svg for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo

PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **pdftocairo -svg filename.pdf**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

Prog lwarpmk epstopdf

Prog epstopdf

epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **lwarpmk pdftosvg *.PDF**

to convert to SVG images.

DVI latex

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **lwarpmk epstopdf *.eps** **(or a list of filenames)**

Enter ⇒ **lwarpmk pdftosvg *.pdf** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx

⚠ viewport

⚠ viewport units

If using the older graphics syntax, use both optional arguments for \includegraphics. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

For \includegraphics, avoid px and % units for width and height, or enclose them inside warpHTML environments. For font-proportional image sizes, use ex or em. For

fixed-sized images, use cm, mm, in, pt, or pc. Use the keys width=.5\linewidth, or similar for \textwidth or \textheight to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the scale option, since it is not well supported by HTML browsers.

options — \includegraphics accepts width and height, origin, rotate and scale, plus new class and alt keys.

html class — With HTML output, \includegraphics accepts an optional class=xyz keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

html alt tags — Likewise, the \includegraphics alt key adds an HTML alt tag to an image, and is ignored for print output. If not assigned, each image is given an alt tag of "(image)".

\rotatebox — \rotatebox accepts the optional origin key.

⚠ browser support — \rotatebox, \scalebox, and \reflectbox depend on modern browser support. The CSS3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

8.8.1 tikz package

Pkg tikz

⚠ displaymath and matrices — If using display math with tikzpicture or \tikz, along with matrices with the & character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of & in the tikz expression must be replaced with \&.

8.8.2 grffile package

Pkg grffile

⚠ matching pdf and svg — grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

8.8.3 color package

Pkg color

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

8.8.4 xcolor package

Pkg xcolor

\colorboxBlock and \fcolorboxBlock — \colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML

mode they place their contents into a instead of a . These s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none — \fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support — Color definitions, models, and mixing are fully supported without any changes required.

colored tables — \rowcolors is supported, except that the optional argument is ignored so far.

colored text and boxes — \textcolor, \colorbox, and \fcolorbox are supported.

\color and \pagecolor — \color and \pagecolor are ignored. Use CSS or \textcolor where possible.

8.8.5 epstopdf package

Pkg epstopdf

⚠ convert to .svg

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

8.8.6 pstricks package

Pkg pstricks

⚠ use pspicture

All pstricks content should be contained inside a pspicture environment.

8.8.7 pdftricks package

Pkg pdftricks

⚠ convert image files

The pdftricks image files <jobname>-fig*.pdf must be converted to .svg, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **lwarpmk pdftosvg <jobname>-fig*.pdf**

8.8.8 psfrag package

Pkg psfrag

⚠ use psfrags

The psfrags environment is modified to use lateximage to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the EPS file.

8.8.9 pstool package

Pkg pstool

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename

The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

8.8.10 asymptote package

Pkg asymptote

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

8.8.11 overpic package

Pkg overpic

⚠ scaling

The macros \overpicfontsize and \overpicfontskip are used during HTML generation. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

8.8.12 Multimedia packages

Pkg multimedia

Pkg movie15

Pkg media9

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

8.9 Tabbing

The tabbing environment works, except that SVG math and lateximages do not yet work inside the environment.

⚠ math in tabbing

If math is used inside tabbing, place tabbing inside a lateximage environment, which will render the entire environment as a single SVG image.

8.10 Tabular

8.10.1 tabular environment

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, siunitx S columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include `tabular` and instances of the `&` character, it may be necessary to make `&` active before the environment or macro is defined, then restore `&` to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow

This includes before and after defining any macro which used `\ttabbox` from floatrow.

⚠ `tabular` inside another environment

- When creating a new environment which contains a `tabular` environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use `\ResumeTabular` as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use `\TabularMacro` just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

`@` and `!`

- Only one each of `@` and `!` is used at each column, and they are used in that order.

`\multirow`

- In `\multirow` cells, the print version may have extra instances of `<`, `>`, `@`, and `!` cells on the second and later rows in the `\multirow` which do not appear in the HTML version.

⚠ `\newcolumntype`

- `\newcolumntype` is ignored; unknown column types are set to `l`.

Rules:

- Doubled `\hlines`, `\midrules`, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an `@` or `!` column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with `@` or `!` columns, and full-width rules ignore trim.

full-width rules

- `\toprule`, `\midrule`, `\bottomrule`, and `\hline` ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use `\cmidrule` followed by `\bottomrule`, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional `-2ex` is ignored in HTML, but improves the visual formatting in the print output.

⚠ `\warpprintonly`
⚠ Misplaced `\noalign`

- For `\toprule` and `\bottomrule`, when combined with a `warpprint` or `warpHTML` environment, if a "Misplaced `\noalign`" error occurs, change

```
This & That \endhead
```

to

```
\warpprintonly{This & That \endhead}
```

and likewise with the other `\end` headings. Keep the `\endfirsthead` row unchanged, as it is still relevent to HTML output.

Other:

- tabularx ignores the width, but `X` columns do produce paragraph columns or multicolumns.

longtable headings

- For longtable, place headings and footings which do not apply to HTML inside `\warpprintonly{}`.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as `\multirow`. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

```
\warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
\warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
```

8.10.2 multirow package

vposn

- Note that recent versions of multirow include a new optional `vposn` argument.

multirow cells

- For multirow, insert `\mrowcell` into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
. . . &  \multirow{2}{.5in}{text}  & . . .
. . . &  \mrowcell                 & . . .
```

colored cells

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.

with \multicolumn

- See section 338.2 for \multicolumrow.

⚠ \multicolumn & \multirow

lwarp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

⚠ skipped cells

⚠ empty cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
. . . &  \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}  & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
. . . &  \mcolrowcell          &          \mcolrowcell   & . . .
```

8.10.3 longtable package

Pkg longtable

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 8.10.4 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . . table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign

Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill

\kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ leximage

longtable is not supported inside a \leximage.

8.10.4 threeparttablex package

Pkg threeparttablex

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width

The table notes are created using a `\multicolumn`. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use `\UseMinipageWidths` before `\insertTableNotes`. The width is then specified, and in many cases the result is an improvement in overall table layout.

8.10.5 supertabular and xtab packages

Pkg supertabular

Pkg xtab

⚠ Misplaced alignment tab character &

For `\tablefirsthead`, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage

supertabular and xtab are not supported inside a `lateximage`.

8.10.6 colortbl package

Pkg colortbl

⚠ row/cell color

Only use `\rowcolor` and `\cellcolor` at the start of a row, in that order.

colortbl ignores the overhang arguments.

8.10.7 ctable package

⚠ Misplaced alignment tab character &

Use \StartDefiningTabulars before one or more \ctables, and \StopDefiningTabulars after. These change the meaning of the ampersand & character.

8.10.8 bigdelim package

Pkg bigdelim

⚠ use \mrowcell

\ldelim and \rdelim use \multirow, so \mrowcell must be used in the proper number of empty cells in the same column below \ldelim or \rdelim, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

<-> a b

left { c d
e f
g h

<-> i j

8.11 Floats

8.11.1 Float contents alignment

⚠ figure & table alignment

\centering, etc. are honored in a figure or table if they are the first command inside the float:

```
\begin{table*}
\centering
\caption{A Table}
. . .
```

8.11.2 float, trivfloat, and/or algorithmicx together

Pkg float
Pkg trivfloat
Pkg algorithmicx

If using \newfloat, trivfloat, and/or algorithmicx together, see section 486.1.

8.11.3 caption and subcaption packages

⚠ package conflicts

Pkg caption
Pkg subcaption

⚠ options

To pass options to caption, select the options before loading lwarp:

```
\documentclass{article}
. . .
\PassOptionsToPackage{options_list}{caption}
. . .
\usepackage{lwarp}
. . .
\usepackage{caption}
```

⚠ numbering To ensure proper float numbering, set caption positions such as:

```
\captionsetup[figure]{position=bottom}
\captionsetup[subfigure]{position=bottom}
\captionsetup[table]{position=top}
\captionsetup[subtable]{position=top}
```

Similarly for longtable. These positions depend on where the user places the `\caption` command inside each float.

8.11.4 subfig package

Pkg subfig

⚠ lof/lotdepth At present, the package options for `lofdepth` and `lotdepth` are not working. These counters must be set separately after the package has been loaded.

In the document source, use `\hfill` and `\hspace*` subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

8.11.5 floatrow package

Pkg floatrow Use `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros using `\ttabbox` with a tabular inside. See section 8.10.1.

⚠ Misplaced alignment tab character &
⚠ subfig package When combined with the subfig package, while inside a `subfloatrow` `\ffigbox` and `\ttabbox` must have the caption in the first of the two of the mandatory arguments.

⚠ `\FBwidth, \FBheight` The emulation of floatrow does not support `\FBwidth` or `\FBheight`. These values are pre-set to `.3\linewidth` and `2in`. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use `warpprint` and `warpHTML` environments to select appropriate values for each case.
- Inside a `warpHTML` environment, manually change `\FBwidth` or `\FBheight` before the `\ffigbox` or `\ttabbox`. Use `\FBwidth` or `\FBheight` normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

8.11.6 keyfloat package

Pkg keyfloat
⚠ keywrap

If placing a `\keyfig[H]` inside a `keywrap`, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

8.12 KOMA-SCRIPT classes

Cls komascript

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

`\titlehead`, `\subject`, `\captionformat`, `\figureformat`, and `\tableformat` are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

8.13 MEMOIR class

Cls memoir
⚠ options clash

While emulating memoir, lwarp pre-loads a number of packages (section 532.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in `\pagenotesubhead` and related macros.

Poem numbering is not supported.

The verbatim environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

8.14 International languages

⚠ section and file names

If using *pdflatex* with the setting \booltrue{FileSectionNames}, non-ASCII text in section names can result in corrupted HTML file names. *pdflatex* may be used if setting \boolfalse{FileSectionNames}, in which case HTML file numbers will be generated.

For correct HTML file names, use *xelatex*, *lualatex*, or dedicated document classes / engines.

(As of this writing, this warning is only relevent to the kotex package.)

8.15 Miscellaneous packages

8.15.1 verse and memoir

Pkg verse
Cls memoir
\attrib

When using verse or memoir, always place a \\ after each line.

The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing

Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

8.15.2 newclude package

Pkg newclude
⚠ loading

newclude modifies \label in a non-adaptive way, so newclude must be loaded before lwarp is loaded:

```
\documentclass{article}
. . . <font setup>
\usepackage{newclude}
\usepackage[warpHTML]{lwarp}
. . .
```

8.15.3 babel package

Pkg babel
⚠ \CaptionSeparator

When French is used, the caption separator is changed to a dash. The following may be used to restore it to a colon:

```
\renewcommand*{\CaptionSeparator}{:~}
```

punctuation spaces
⚠ customized spacing

Also when French is used, lwarp creates fixed-width space around punctuation by patching \FBcolonspace, \FBthinspace, \FBguillspace, \FBmedkern, \FBthickkern, \FBtextellipsis, and the tilde. If the user's document also changes these parameters, the user's changes should be placed inside a warpprint environment so that the user's changes do not affect the HTML output.

8.15.4 polyglossia package

Pkg polyglossia

lwarp uses cleveref, which has some limitations when using polyglossia, possibly resulting in the error

```
! Undefined control sequence. . . . \@begindocumenthook
```

To test compatibility, add

```
\usepackage{cleveref}
```

near the end of the preamble (as the last package to be loaded), and try to compile the print version. It may be necessary to set

```
\setdefaultlanguage{english}
```

or some other language supported by cleveref, then select other languages using \setotherlanguages.

Once the print version works with cleveref and polyglossia, the HTML version should work as well using lwarp.

8.15.5 todonotes and luatodonotes packages

Pkg todonotes
Pkg luatodonotes

The documentation for todonotes and luatodonotes have an example with a todo

inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

8.15.6 fixme

Pkg fixme

External layouts (\fxloadlayouts) are not supported.

⚠ external layouts

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

8.15.7 chemfig package

If using \polymerdelim to add delimiters to a \chemfig, wrap both inside a single lateximage:

```
\begin{lateximage}[(-chemfig-~\packagediagramname)]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

8.15.8 chemformula package

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, \displaymathother must be used before array, and then \displaymathnormal may be used after. (The chemformula package adapts to array, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, \displaymathother may also be used for other forms of display and inline math which contain chemformula expressions.

8.15.9 mhchem package

See section 324.

8.15.10 xparse package

Pkg xparse

To remove from the log any warnings about redeclaring objects, place the following before lwarp is loaded:

```
\usepackage[log-declarations=false]{xparse}
```

8.15.11 kotex package

Pkg kotex See section 8.14 regarding *pdflatex* and Korean section names.

⚠ Korean section names

9 Compiling using custom shell commands

lwarp and *lwarpmk* try to make it easy to process print and HTML compilation tasks in most situations. Depending on the operating system, command-line options, TEX engine, and lwarp options, the commands **`lwarpmk print`** and **`lwarpmk html`** are automatically set up to correctly recompile the project. These actions may be overridden using lwarp options, thus allowing the use of packages such as perltex and pythontex.

9.1 Command options

Opt PrintLatexCmd
Opt HTMLLatexCmd

The lwarp options `PrintLatexCmd` and `HTMLLatexCmd` are used to set customized commands to be executed by **`lwarpmk print`** and **`lwarpmk html`**.

`PrintLatexCmd` should be set to shell commands which take `project.tex` and generate `project.pdf`.

`HTMLLatexCmd` should be set to take `project_html.tex` and generate `project_html.pdf`. *lwarpmk* will then take `project_html.pdf` and automatically convert it and generate `project.html`.

9.2 Literal character macros

The lwarp package options are parsed by TEX, and so some characters require the use of a special macro to represent them. See table 7. `\LWRopquote` and `\LWRopseq` may be used to increase operating-system portability. `\jobname` must have `_html` appended for processing HTML. `\space` may be necessary between other macros.

⚠ macro not found

To use these macros, either kvoptions-patch must be loaded before lwarp:

```
\usepackage{kvoptions-patch}
\usepackage[
    PrintLatexCmd={ ... } ,
    HTMLLatexCmd={ ... }
]{lwarp}
```

Table 7: Literal character macros

Character	Macro	Comment
%	\LWRpercent	
$	\LWRdollar	
&	\LWRamp	
%	\LWRhash	
\	\LWRbackslash	
' or "	\LWRopquote	Depends on the operating system.
& or &&	\LWRopseq	Depends on the operating system.
(space)	\space	Forces an extra space.
(jobname)	\jobname	Without file extension.

or \lwarpsetup must be used to set PrintLatexCmd and HTMLLatexCmd:

```
\usepackage[...]{lwarp}
\lwarpsetup{
  PrintLatexCmd=
      {
          latex tm \LWRopseq
          dvips -o tm-pics.ps tm.dvi \LWRopseq
          ps2pdf tm-pics.ps \LWRopseq
          pdflatex tm.tex
      } ,
  HTMLLatexCmd=
      {
          latex tm_html \LWRopseq
          dvips -o tm_html-pics.ps tm_html.dvi \LWRopseq
          ps2pdf tm_html-pics.ps \LWRopseq
          pdflatex tm_html.tex
      }
}
```

9.3 *latexmk*

Prog latexmk If *latexmk* is used for a project, it may be easiest to continue using it.

latexmk project.tex would create project.pdf as normal.

latexmk project_html.tex would create project_html.pdf, then

lwarpmk pdftohtml project_html.pdf would take project_html.pdf and convert it to project.html.

Pkg sagetex *latexmk* may simplify the use of packages such as sagetex.

9.4 perltex package

Pkg perltex The lwarp package option settings to use perltex would be similar to:

```
\usepackage[
  . . .
  PrintLatexCmd={perltex -latex=pdflatex project.tex} ,
  HTMLLatexCmd={perltex -latex=pdflatex project_html.tex} ,
  . . .
]{lwarp}
```

⚠ "impure" math Place perltex math expressions between `\displaymathother` and `\displaymathnormal`, or `\inlinemathother` and `\inlinemathnormal`. See section 8.7.9.

9.5 pythontex package

Pkg pythontex An example using pythontex:

```
\usepackage[
  . . .
  PrintLatexCmd={
    pdflatex project.tex \LWRopseq
    pythontex project \LWRopseq
    pdflatex project.tex
  } ,
  HTMLLatexCmd={
    pdflatex project_html.tex \LWRopseq
    pythontex project_html \LWRopseq
    pdflatex project_html.tex
  } ,
  . . .
]{lwarp}
```

Another possibility is to use *latexmk*, placing the **`latexmk . . .`** commands in the `PrintLatexCmd` and `HTMLLatexCmd` options. While using these options, the lwarp option `latexmk` would not be used.

⚠ "impure" math
⚠ HTML look-alike

No attempt has yet been made to make pythontex robust with HTML output. Some math objects must be surrounded by `\displaymathother` ...`\displaymathnormal`, or `\inlinemathother` ...`\inlinemathnormal`. Displays of code may have to be enclosed inside a `lateximage` environment to prevent <, > and similar from being interpreted by the browser as HTML entities.

9.6 Other packages

Pkg sympytex Other packages such as sympytex and rterface would be set up similar to pythontex,

Pkg rterface

and the same warnings would apply.

9.7 *make* program

Prog make

To use lwarp with the *make* program, have the `makefile` take `project.tex` and generate the print version `project.pdf`, as normal. `\usepackage{lwarp}` must be used, and it generates `lwarpmk.conf` when the print version is created.

To generate HTML, first have `project_html.tex` be compiled to generate `project_html.pdf`. This must be in PDF format. Finally, have `project_html.pdf` be converted to HTML using **`lwarpmk pdftohtml project_html.pdf`**, and convert SVG math with **`lwarpmk limages`**.

9.8 UTF-8 locale

⚠ UTF-8 locale

lwarpmk uses the *texlua* program, which sets the "locale" to "`C`", including for external operating-system calls such as when executing **`lwarpmk html`**. In some cases, an external program called from the user's document may require the use of a UTF-8 "locale". For UNIX-related operating systems, it may be required to use lwarp's custom compilation options to add a locale change:

```
\usepackage{lwarp}[
  PrintLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex -shell-escape project.tex
  }
  HTMLLatexCmd={
    env LC_CTYPE=en_US.UTF-8
      xelatex -shell-escape project_html.tex
  }
]
```

Pkg ditaa

The only example seen so far where this is required is the ditaa package, where the locale change allows the use of UTF-8 with XeLaTeX and ditaa. To use LuaLaTeX instead, the locale change would have to be made inside the ditaa package where its calls the *ditaa* program.

10 EPUB conversion

lwarp does not produce EPUB documents, but it may be told to modify its HTML output to greatly assist in the conversion. An external program may then be used to finish the conversion to EPUB.

<meta> author

To assign the author's name for regular lwarp HTML files, and also for the EPUB, use `\HTMLAuthor {⟨name⟩}`. This assigns the name to the `<meta>` author element. It may be set empty, and it defaults to `\theauthor`.

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatEPUB`

Bool `FormatEPUB`
Default: `false`

`FormatEPUB` changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

To help convert lwarp HTML output to EPUB, add

```
\booltrue{FormatEPUB}
```

to the project's source preamble after `\usepackage{lwarp}`. The EPUB version of the document cannot co-exist with the regular HTML version, so

Enter ⇒ **`lwarpmk cleanall`**

Enter ⇒ **`lwarpmk html`**

Enter ⇒ **`lwarpmk limages`**

to recompile with the `FormatEPUB` boolean turned on. Several changes are then made to the HTML output:

- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.

Calibre

The resulting files will be ready to be loaded into an EPUB conversion program, such as the open-source program *Calibre* (`https://calibre-ebook.com/`).

⚠ search order

The EPUB conversion program must know what order the files are included. For lwarp projects, set the EPUB conversion software to do a breadth-first search of the files. For *Calibre*, this option is found in

Preferences → Plugins → File type plugins → HTML to Zip

⚠ encoding

Check the box Add linked files in breadth first order. Set the document encoding as `utf-8`, which is what lwarp generates for HTML, even if the original printed document uses some other encoding.

⚠ section breaks

The EPUB-conversion program must also know where the section breaks are located. For a list of lwarp's section headings, see table 9. For example, an `article` class document would break at `\section`, which is mapped to HTML heading level `<h4>`, whereas a `book` class document would break at `\chapter`, which is HTML heading level `<h3>`. For *Calibre*, this option is found in

Preferences → Conversion (Common Options) → Structure Detection → Detect chapters at (XPath expression)

Select the "magic wand" to the right of this entry box, and set the first entry

Match HTML tags with tag name:

to "h4". (Or "h3" for document classes with `\chapters`.) The Detect chapters at field should then show

//h:h4 — or — **//h:h3**

This option is also available on the main tool bar at the Convert books button.

Once these settings have been made, the lwarp-generated HTML files may be loaded by *Calibre*, and then converted to an EPUB.

MathJax support

MathJax may be used in EPUB documents. Some e-readers include MathJax, but any given reader may or may not have a recent version, and may or may not include extensions such as support for siunitx.

lwarp adds some modifications to MathML to support equations numbered by chapter. These modifications may not be compatible with the e-reader's version of MathJax, so lwarp requests that a known version be loaded instead. In some cases chapter numbering of equations still doesn't work.

Until math support in EPUB documents is improved, it is recommended to use SVG images instead of MathJax, especially for equations numbered by chapter, or where siunitx support is important.

11 Word-processor conversion

lwarp may be told to modify its HTML output to make it easier to import the HTML document into a word processor. At the time of this writing, it seems that LibreOffice works best at preserving table layout, but it still has some limitations, such as an inability to automatically assign figure and table frames and captions according to user-selected HTML classes. lwarp provides some assistance in locating these frame boundaries, as shown below.

11.1 Activating word-processor conversion

A special boolean is provided to simplify the process of converting lwarp HTML output to EPUB:

`FormatWP`

Bool `FormatWP`
Default: `false`

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments. Additionally, honors the booleans `WPMarkFloats`, `WPMarkMinipages`, `WPMarkTOC`, and `WPMarkLOFT`.

To help modify lwarp HTML output for easier import to a word processor, add

```
\booltrue{FormatWP}
```

to the project's source preamble after lwarp is loaded. The following changes are then made to the HTML output:

formatting adjustments

- If using a class without chapters, `\section` and lower are shifted up in level for the HTML heading tags. The CSS has not been changed, so the section heading formats will not match the normal HTML output, but when imported to *LibreOffice Writer* the higher section headings will import as **Heading 1** for the title, **Heading 2** for `\section`, etc.
- Headers, footers, and navigation are removed at file splits.
- Any accumulated footnotes are printed at the bottom of each section.
- Forces single-file output.
- Turns off HTML debugging comments. These are comments appearing inside the HTML code, marking the opening/closing of sections and `<div>`s, but they are no longer useful when the document has been imported into a word processor.
- An additional `<div>` with an `id` encapsulates each float and minipage, which on import into *LibreOffice Writer* causes a thin frame to appear around the text block for each.

- Float captions are given an explicit italic formatting.
- Tabular rule borders are made explicit for *LibreOffice Writer*. LibreOffice displays a light border around each cell while editing, even those which have no border when printed, and lwarp also uses a light border for thin rules, so it will be best to judge the results using the print preview instead of while editing in LibreOffice.
- `\includegraphics` and SVG math width and height are made explicit for LibreOffice.
- `\hspace` is approximated by a number of `\quad`s, and rules are approximated by a number of underscores.
- Explicit HTML styles are given to:
  - `\textsc`, etc.
  - `\underline`, soul and ulem markup.
  - `center`, `flushleft`, `flushright`.
  - `\marginpar`, keyfloat, sidenotes, floatflt, and wrapfig.
  - fancybox `\shadowbox`, etc.
  - The LaTeX and TeX logos.
- Honors several booleans:

  WPMarkFloats: Marks the begin and end of floats.

  WPMarkMinipages: Marks the begin and end of minipages.

  WPMarkTOC: Marks the location of the Table of Contents.

  WPMarkLOFT: Marks the locations of the List of Figures/Tables.

  WPMarkMath: Prints LaTeX math instead of using images.

  WPTitleHeading: Adjusts title and section headings.

  Several of these may be used to add markers to the HTML text which help determine where to adjust the word processor document after import.

11.2 Additional modifications

`WPMarkFloats`

Bool `WPMarkFloats`
Default: `false`

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions.

`WPMarkMinipages`

Bool `WPMarkMinipages`
Default: `false`

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

`WPMarkTOC`

Bool `WPMarkTOC`
Default: `true`

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual TOC is printed instead.*

`WPMarkLOFT`

Bool `WPMarkLOFT`
Default: `false`

While formatting for word processors, adds

```
=== list of figures ===    and/or
=== list of tables ===
```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

`WPMarkMath`

---

siunitx
Bool `WPMarkMath`
Default: `false`
Prog `TeXMaths`

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

When using the siunitx package, enter

Table 8: Section html headings for word-processor conversion

	html headings*			
	With \chapter		Without \chapter	
	WPTitleHeading		WPTitleHeading	
Section	true	false	true	false
Title	<h1>	plain	<h1>	plain
\part	<h2>	<h1>	<h2>	<h1>
\chapter	<h3>	<h2>	—	—
\section	<h4>	<h3>	<h3>	<h2>
\subsection	<h5>	<h4>	<h4>	<h3>
\paragraph	<h6>	<h5>	<h5>	<h4>
\subparagraph	span	<h6>	<h6>	<h5>

* For default depths when not FormatWP, see table 9 on page 184.

```
\usepackage{siunitx}
```

in the *TeXMaths* preamble. Equation numbering is problematic for $\mathcal{AMS}$ math environments.

WPTitleHeading

Bool WPTitleHeading
Default: false
section headings

While formatting for word processors, true sets the document title to <h1>, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to false to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 167.

11.3 Recommendations

TOC, LOF, LOT

For use with *LibreOffice Writer*, it is recommended to:

1. Set \booltrue{FormatWP}
2. Set \booltrue{WPMarkTOC} and \boolfalse{WPMarkLOFT}
3. Use lwarp to generate the HTML document.

4. Copy/paste from the HTML document into an empty *LibreOffice Writer* document.
5. Manually insert a LibreOffice TOC in the LibreOffice document.
6. Manually add frames around each float, adding a caption which is cut/pasted from each float's simulated caption.
7. Manually create cross references.

This process yields a document with an actual LibreOffice Table of Contents, but a simulated List of Figures and List of Tables.

siunitx

For siunitx, remember to adjust the preamble as mentioned above.

LO view border options

LibreOffice has options in the **View** menu to turn on/off the display of thin borders around table cells and text objects.

11.4 Limitations

Floats and captions are not explicitly converted to LibreOffice floats with their own captions. Floats are surrounded by a thin frame in the LibreOffice editor, and may be marked with `WPMarkFloats`, but are not given a proper LibreOffice object frame. Captions are given an explicit italic formatting, but not a proper LibreOffice paragraph style.

Cross references are not actual LibreOffice linked cross references.

The List of Figures and List of Tables are not linked. The pasted pseudo LOF and LOT match the numbering of the LaTeX and HTML versions.

Equation numbering is not automatic, but the equation numbers in SVG math will match the LaTeX and HTML output. SVG math is recommended when using the $\mathcal{AMS}$ environments, which may have multiple numbered equations per object.

As of when last checked, LibreOffice ignores the following:

- Minipage alignment.
- Tabular cell vertical alignment.
- Image rotation and scaling.
- Rounded border corners, which are also used by:
  - `\textcircled`
  - booktabs trim
- `\hspace` and rules, also used by algorithmic.
- Coloring of text decorations, used by soul and ulem.
- Overline text decoration, used by romanbar.

LibreOffice also has limitations with frames and backgrounds:

- Multiple lines in an object are framed individually instead of as a whole.
- Nested frames are not handled correctly.
- Images inside boxes are not framed correctly.
- Spans with background colors and frames are not displayed correctly.

12 Modifying lwarp

locating something

To quickly find the source for a package in `lwarp.dtx`, search for `*packagename`, such as `*siunitx`.

Likewise, to quickly find the source for a file in `lwarp.dtx`, search for `*filename`, such as `*lwarp.css`.

Purely text-based packages probably will work as-is when generating HTML.

Look to existing code for ideas on how to expand into new code.

image of TEX output

An environment may be converted to a `lateximage` then displayed with an image of the resulting LATEX output. See section 88 for an example of the `picture` environment.

css classes

To create a custom HTML block or inline CSS class, see section 51.9.

print/HTML macros

To create print and HTML versions of the same macro or environment, see section 36.

⚠ TEX boxes

Any TEX boxes must be undone, as SVG math or `lateximages` require `\newpage`, which will not work in a TEX box.

index recreation

To recreate the index for the lwarp documentation:

```
makeindex -s gglo.ist -o lwarp.gls lwarp.glo
splitindex lwarp.idx -- -s gind.ist
```

12.1 Creating a development system

The following creates a local development system for lwarp on a TeXLive system in a UNIX-like environment. Doing so allows anything requesting lwarp to use the development version instead of whichever version is installed in TeXLive.

Create a development directory:

Place into this directory `lwarp.dtx` and `lwarp.ins`.

To create `lwarp.sty`, execute

Enter ⇒ **`pdflatex lwarp.ins`**

which creates `lwarp.sty` and several hundred additional `lwarp-*.sty` files for the various packages which are supported.

To create the documentation `lwarp.pdf`, execute

Enter ⇒ **`pdflatex lwarp.dtx`**

To make the development files visible to other projects:

Create the directory

```
/usr/local/texlive/texmf-local/tex/latex/local/lwarp
```

Inside this directory, create the file `update`, containing:

```
ln -s /path_to_dev_directory/lwarp*.sty .
ln -s /path_to_dev_directory/lwarp_baseline_marker.png .
ln -s /path_to_dev_directory/lwarp_baseline_marker.eps .
mktexlsr
```

Run ./update now, and whenever a new lwarp-* package is added.

To make the development version of *lwarpmk* visible to other projects:

```
cd /opt
ln -s /usr/local/texlive/texmf-local/bin/x86_64-linux texbin_local
cd texbin_local
ln -s ../../scripts/lwarp/lwarpmk.lua lwarpmk
cd /usr/local/texlive/texmf-local/scripts/
mkdir lwarp
cd lwarp
ln -s /path_to_dev_directory/lwarpmk.lua lwarpmk
```

Verify that the correct version is found with

Enter ⇒ **`which lwarpmk`**

To make the local versions visible to the shell:

Paths must be set by the shell startup, such as in `.bashrc` and `.cshrc`:

In `.bashrc`:

```
PATH=/opt/texbin_local:/opt/texbin:$PATH
```

In `.cshrc`:

```
setenv PATH ${HOME}/bin:/opt/texbin_local:/opt/texbin:${PATH}
```

12.2 Modifying a package for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

When creating HTML, lwarp redefines the `\usepackage` and `\RequirePackage` macros such that it first looks to see if a `lwarp-<packagename>.sty` version exists. If so, the lwarp version is used instead. This modular system allows users to create their own

versions of packages for lwarp to use for HTML, simply by creating a new package with a `lwarp-` prefix. If placed in the local directory along with the source code, it will be seen by that project alone. If placed alongside the other `lwarp-` packages where TEX can see it, then the user's new package will be seen by any documents using lwarp. (Remember `mktexlsr` or `texhash`.)

An `lwarp-<packagename>.sty` package is only used during HTML generation. Its purpose is to pretend to be the original package, while modify anything necessary to create a successful HTML conversion. For many packages it is sufficient to simply provide nullified macros, lengths, counters, etc. for anything which the original package does, while passing the raw text on to be typeset. See the pre-existing `lwarp-` packages for examples.

Anything the user might expect of the original package must be replaced or emulated by the new `lwarp-` package, including package options, user-adjustable counters, lengths, and booleans, and conditional behaviors. In many of these packages, most of the new definitions have a "local" prefix according to the package name, and `@` characters inside the name, which hides these names from the user. In most cases these macros will not need to be emulated for HTML output. Only the "user-facing" macros need to be nullified or emulated.

Each `lwarp-*` package should first call either of:

```
\LWR@ProvidesPackageDrop
  -or-
\LWR@ProvidesPackagePass
```

If "`Drop`"ped, the original print-version package is ignored, and only the `lwarp-` version is used. Use this where the original print version is useless for HTML. If "`Pass`"ed, the original package is loaded first, with the user-supplied options, then the `lwarp-` version continues loading as well. See section 357 (ntheorem) for an example of selectively disabling user options for a package. Use this when HTML output only requires some modifications of the original package. For a case where the original package is usable without changes, there is no need to create a `lwarp-` version.

12.2.1 Adding a package to the lwarp.dtx file

When adding a package to `lwarp.dtx` for permanent inclusing in lwarp, provide the `lwarp-<packagename>` code in `lwarp.dtx`, add its entry into `lwarp.ins`, and also remember to add

```
\LWR@loadafter{<packagename>}
```

to `lwarp.dtx` in section 20.1. This causes lwarp to stop with an error if packagename is loaded before lwarp. Finally, add an entry in table 2, Supported packages and features, and also the Updates section.

12.3 Modifying a class for lwarp

If a class loads additional packages, it will be required to modify the class for lwarp, since lwarp must be loaded before most other packages.

To work with lwarp, a class must first set up anything which replicates the functions of the basic LaTeX classes, load any required fonts, then load lwarp, then finally load and adjust any other required packages.

12.4 Testing lwarp

When changes have been made, test the print output before testing the HTML. The print output compiles faster, and any errors in the printed version will be easier to figure out than the HTML version.

Remember that the configuration files are only rewritten when compiling the printed version of the document.

When changing the source to *lwarpmk* or a CSS file in `lwarp.dtx`:

1. Change the source in `lwarp.dtx`.
2. `pdflatex lwarp.ins`
3. `pdflatex lwarp.dtx`
4. If modifying *lwarpmk* the new version should now be active.
5. If modifying CSS files:
   (a) For the document, `lwarpmk print` to update the CSS files in the project.
   (b) Reload the HTML document to see the effect of the new CSS files.

Sometimes it is worth checking the `<project>_html.pdf` file, which is the PDF containing HTML tags. Also, `<project>_html.html` has the text conversion of these tags, before the file is split into individual HTML files.

It is also worth checking the browser's tools for verifying the correctness of HTML and CSS code.

12.5 Modifying *lwarpmk*

Prog `lwarpmk`
File `lwarpmk.lua`

In most installations, `lwarpmk.lua` is an executable file located somewhere the operating system knows about, and it is called by typing **`lwarpmk`** into a terminal.

A project-local copy of `lwarpmk.lua` may be generated, modified, and then used to compile documents:

1. Add the `lwarpmk` option to the lwarp package.

2. Recompile the printed version of the document. The `lwarpmk` option causes lwarp to create a local copy of `lwarpmk.lua`
3. The `lwarpmk` option may now be removed from the lwarp package.
4. Copy and rename `lwarpmk.lua` to a new file such as `mymake.lua`.
5. Modify `mymake.lua` as desired.
6. If necessary, make `mymake.lua` executable.
7. Use `mymake.lua` instead of `lwarpmk.lua`.

13 Troubleshooting

13.1 lwarp package error conditions and warnings

lwarp tests for a number of error conditions and prints appropriate warnings. The following is a summary of these conditions.

13.1.1 Configuration file `lwarpmk.conf`

File does not exist: The configuration file must exist for lwarpmk.

Incorrect `Unix` /`Windows` selection: The operating system which was detected by lwarp. So far only `Unix` and `Windows` are supported.

Incorrect delimiter characters. Older versions of *lwarpmk* used a different delimiter.

Source name is set to `lwarp`: lwarp has recently been recompiled in this directory, which overwrote the project's configuration files. This also occurs if *lwarpmk* is executed in lwarp's source directory.

Incorrect operating system: The configuratio file was set for a different operating system, perhaps due to sharing in a collaborative project.

Outdated configuration files: lwarp has been updated since this projects was last compiled. If there appears to be a valid print command in the file, lwarpmk displays this to instruct the user how to recompile the print version, which then updates the configuration files.

The designated source file does not exist: For whatever reason…

Unknown engine: lwarp cannot determing which engine is being used. Supported are DVI LaTeX, PDF LaTeX, XeLaTeX, LuaLaTeX, and upLaTeX.

13.1.2 Image generation with `lwarpmk limages`

"Wait a moment for the images to complete before reloading page.":

Images are generated by background tasks. If the document is reloaded before these tasks are complete, some images may not yet be generated. *lwarpmk* tries to wait for background tasks to complete before exiting.

HTML version does not exist: Images are extracted from the HTML version, which must be compiled before images are generated.

`*-images.txt` does not exist: This file tells which images to extract from the HTML file. If the file does not exist, it may be that no SVG math or `lateximages` were used. If so, **`lwarpmk limages`** is not necessary.

Cross references are not correct: The document must have up-to-date cross references to locate the images to extract. A number of conditions may cause incorrect cross references.

"WARNING: Images will be incorrect.": An image reference was not found. Recompile.

`lwarpmk epstopdf *` or `lwarpmk pdftosvg *`: Errors if filenames are not found.

13.1.3 Default bitmapped font

lwarp requires the use of a vector font. If lwarp detects that the document uses the default Computer Modern font, and the cm-super package is not installed, it is assumed that the font is bitmapped. An error is generated, along with the recommendation to install cm-super or use lmodern.

13.1.4 Packages

Loaded before lwarp: Some packages and classes must be loaded before lwarp. These include input and font encoding, morewrites and newclude, and a number of CJK-related packages and classes.

Loaded after lwarp: Most packages which are modified by lwarp must be loaded after lwarp.

Loaded never: Some packages do not work with lwarp. An error is generated, along with a list of alternatives to consider.

Specific packages: Some packages enforce a specific load order vs. certain other packages.

Patching error: lwarp tries to patch some packages using xpatch. If the original package has been updated more recently than lwarp, a patch may not work. It may be necessary to use an older version of the package until lwarp is updated.

longtable: lwarp's longtable package issues detailed error messages regarding the use of the table headers and footers.

13.1.5 Compiling

Duplicate filenames: lwarp may generate file names from section names. While doing so, the filenames are simplified and special characters are removed. If this process generates a duplicate filename, and error is generated, describing the filename and which section name generated it.

Multirow: When `\multirow` or `\multicolrow` are used, `\mrowcell` or `\mcolrowcell` must be placed in the appropriate cells to avoid corrupted HTML output.

(width,height) missing a comma: `\makebox` and `\framebox` can accept a parenthesis-delimited width and height, which must be separated by a comma.

"Load graphicx or graphics for improved SVG math baselines.": SVG math baselines are improved if either of these packages are used.

"Load graphicx or graphics for improved XeTeX logo.": If these packages are loaded, the XeLaTeX logo can use the reversed "E".

"It is recommended to use `[width=xx\linewidth]` instead of `[scale=yy]` ": Browser support of `scale` is not the same effect as LaTeX.

13.2 Using the lwarp package

The following address problems which may occur, and possible solutions to each.

Also see:
Section 7.8: Commands to be placed into the `warpprint` environment
Section 8: Special cases and limitations

Text is not converting correctly / corrupted HTML tags:

- Font-related UTF-8 information must be embedded in the PDF file. See section 7.2 regarding bitmapped vs. vector fonts.
- See section 8.2.1 regarding HTML entities and the characters &, <, and >.

Undefined HTML settings:

- See the warning regarding the placement of the HTML settings at section 7.4.

Tabular problems: See section 8.10.1.

Obscure error messages:

Print first: Be sure that a print version of the document compiles and that your document's LaTeX code is correct, before attempting to generate an HTML version.

`\end{warpHTML}, \end{warpprint}, \end{warpall}`: Each of these must be without any other characters on the same line.

Options clash: If using memoir, see section 8.13.

"No room for a new `\write`.": Before `\usepackage{lwarp}`, add:

```
\usepackage{morewrites}
\morewritessetup{allocate=10}
```

"Missing $ inserted.": If using a filename or URL in a footnote or `\item`, escape underscores with `\_`.

"Label(s) may have changed. Rerun to get cross-references right.":

This warning may repeat endlessly if a math expression is used in a caption. Simple math expressions such as $X=1$ may be replaced with

```
\textit{X}\,=\,1
```

"Leaders not followed by proper glue": This can be caused by a missing `l@<floattype>` or `l@<sectiontype>` definition. See lwarp's definitions for examples.

"Improper \prevdepth": `lateximages` and SVG math require `\newpage`, which cannot work inside TEX boxes or `\ensuremath`. Anything using `\newsavebox`, `\newbox`, `lrbox`, `\savebox`, `\hbox`, `\vbox`, `\usebox`, `\sbox`, etc., must be modified to work without box commands.

If you find something using `\ensuremath`, have it temporarily set:

```
\LetLtxMacro\@ensuredmath\LWR@origensuredmath
```

inside a group first.

⚠ macros in section,table,figure names

Also, custom macros which appear inside a section, figure, or table name should be made robust since they appear inside the `.toc`, `.lof`, or `.lot` files. Use `\newrobustcmd` or `\robustify` from etoolbox, xparse, etc.

⚠ BibTeX

If using BibTeX, see section 8.6.9.

⚠ polyglossia

"! Undefined control sequence. . . . \@begindocumenthook": See section 8.15.4 if using polyglossia.

⚠ custom macros for environments

"\begin{equation} ended by \end{document}": Do not use custom macros such as `\beq` and `\eeq` to replace

```
\begin{equation}
. . .
\end{equation}
```

⚠ `\LWR@formatted`

"Misplaced \omit": If using `\LWR@formatted` to define new macros for print and HTML modes, see section 36 regarding `\LWR@expandableformatted`.

⚠ "impure" math objects

Complicated objects inside math: Some objects, such as Ti*k*z, may not compile in lwarp's normal math emulation. Insert

```
\displaymathother -or- \inlinemathother
```

before the math, and then

```
\displaymathnormal -or- \inlinemathnormal
```

when displaying "normal" math. See section 8.7.9.

Slow compliation of math objects: Complicated math objects can also cause problems with `alt` tags, resulting in very slow compilation, large `alt` tags, and possible crashes. Use `\inlinemathother` ...`\inlinemathnormal` or `\displaymathother` ...`\displaymathnormal` around the math expression.

⚠ MathJax

⚠ MathJax

Incorrect MATHJAX: Some objects do not convert to MATHJAX. Use `\displaymathother` before these objects, then `\displaymathnormal` to return to "normal" display math. See section 8.7.9.

Missing sections: See section 7.4 regarding the `FileDepth` and `SideTOCDepth` counters, and the use of `\tableofcontents` in the home page.

Misnumbered footnotes from section headings: See section 8.5.4.

Missing HTML files:

- See the warning regarding changes to the HTML settings at section 7.4.
- Ensure that the filenames are unique after math and short words are removed. See `FileSectionNames` at section 7.4.

Missing / incorrect cross-references:

- Use `lwarpmk again` followed by `lwarpmk html` or `lwarpmk print` to compile the document one more time.

labels
⚠ label characters

- Labels with special characters may be a problem. It is best to stick with alpha-numeric, hyphen, underscore, and perhaps the colon (if not French).

\nameref
⚠ empty link

  `\nameref` refers to the most recently-used section where the `\label` was defined. If no section has been defined before the `\label`, the link will be empty. Index entries also use `\nameref` and have the same limitation.

⚠ cleveref page numbers

- cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

  Ex:

  ```
      \cpageref{tab:first,tab:second}
   in html becomes:
  ```

  "pages **for** table 4.1 and **for** table 4.2"

  See `\cpagerefFor` at page 534 to redefine the message which is printed for page number references.

BibTeX errors with `\etalchar`: See section 8.6.9.

Malformed URLs: Do not use the `%` character between arguments of `\hyperref`, etc., as this character is among those which is neutralized for inclusion in HTML URLs.

Em-dashes or En-dashes in listing captions and titles:

Use XeLaTeX or LuaLaTeX.

Floats out of sequence:

Mixed "Here" and floating: Floats [H]ere and regular floats may become out of order. `\clearpage` if necessary.

Caption setup: With `\captionsetup` set the positions for the captions `above` or `below` to match their use in the source code.

Images are appearing in strange places:

- Enter **`lwarpmk limages`** to refresh the `lateximage` images.

SVG images:

⚠ adding/removing

When a math expression, `picture`, or Ti*k*z environment is added or removed, the SVG images must be re-created by entering **`lwarpmk limages`** to maintain the proper image-file associations. Inline SVG math may be hashed and thus not need to be recreated, but display math and objects such as Ti*k*z may move to new image numbers when the document is changed.

recompile first

Before attempting to create the SVG image files, *lwarpmk* verifies that the HTML version of the document exists and has correct internal image references.[15] If it is necessary to recompile the document's HTML version one more time, *lwarpmk* usually will inform the user with an error message, but there are some conditions which cannot be detected, so the user should watch for the LaTeX recompile warnings.

⚠ html instead of images

If HTML appears where an SVG image should be, recompile the document one more time to get the page numbers back in sync, then remake the images one more time.

Incorrect SVG images will also occur if the document changes the page counter:

⚠ page counter

```
\setcounter{page}{<value>}
```

The page counter must *not* be adjusted by the user.

Expressing math as SVG images has the advantage of representing the math exactly as LaTeX would, but has the disadvantage of requiring an individual file for each math expression. For inline math, and some other objects, lwarp uses an MD5 hash on its LaTeX source to combine multiple instances of identical inline expressions into a single image file, but display math and other environments such as `picture` and Ti*k*z require one image file each. For a document with a large amount of math, see section 5.5 to use MathJax instead.

⚠ Lots of files!

Plain-looking document:

- The document's CSS stylesheet may not be available, or may be linked incorrectly. Verify any `\CSSFilename` statements point to a valid CSS file.

Broken fragments of HTML:

- Check the PDF file used to create HTML to see if the tags overflowed the margin. (This is why such large page size and margins are used.)

Changes do not seem to be taking effect:

- Be sure to `lwarpmk clean`, recompile, then start by reloading the home page. You may have been looking at an older version of the document. If you changed a section name, you may have been looking at the file for the old name.
- See the warning regarding changes to the HTML settings at section 7.4.
- Verify that the proper CSS is actually being used.
- The browser may compensate for some subtle changes, such as automatically generating ligatures, reflowing text, etc.

Un-matched conditional compiles:

- Verify the proper `begin/end` of `warpprint`, `warpHTML`, and `warpall` environments.

13.2.1 Debug tracing output

`\tracinglwarp`

When `\tracinglwarp` is used, lwarp will add extra tracing messages to the `.log` file. The last several messages may help track down errors.

Place `\tracinglwarp` just after `\usepackage{lwarp}` to activate tracing.

[15] This becomes important when dealing with a document containing thousands of images.

13.3 Compiling the `lwarp.dtx` file

`lwarp_tutorial.tex`: Copy or link `lwarp_tutorial.txt` from the TDS `doc` directory to the `source` directory, or wherever you wish to compile the documentation. This file is included verbatim in the documentation, but is in the `doc` directory so that it may be found by *texdoc* and copied by the user.

Illogical error messages caused by an out-of-sync `lwarp.sty` file:

1. Delete the `lwarp.sty` file.
2. Enter **`pdflatex lwarp.ins`** to generate a new `lwarp.sty` file.
3. Enter **`pdflatex lwarp.dtx`** to recompile the `lwarp.pdf` documentation.

Un-nested environments:

Be sure to properly nest:

- `\begin{macrocode}` and `\end{macrocode}`
- `\begin{macro}` and `\end{macro}`
- `\begin{environment}` and `\end{environment}`

14 Trademarks

- TEX is a trademark of American Mathematical Society.
- ADOBE® and ADOBE *Framemaker*® are either registered trademarks or trademarks of ADOBE SYSTEMS INCORPORATED in the United States and/or other countries.
- LINUX® is the registered trademark of Linus Torvalds in the U.S. and other countries.
- MAC OS® is a trademark of APPLE INC.
- MADCAP FLARE™ is the property of MADCAP SOFTWARE, INC.
- MATHJAX is copyright 2009 and later. The MATHJAX CONSORTIUM is a joint venture of the AMERICAN MATHEMATICAL SOCIETY (AMS) and the SOCIETY FOR INDUSTRIAL AND APPLIED MATHEMATICS (SIAM) to advance mathematical and scientific content on the web.
- MICROSOFT®, ENCARTA, MSN, and WINDOWS® are either registered trademarks or trademarks of MICROSOFT CORPORATION in the United States and/or other countries.
- UNIX® is a registered trademark of THE OPEN GROUP.
- YOUTUBE™ is trademark of GOOGLE LLC.

File 1 **lwarp.sty**

15 Implementation

This package is perhaps best described as a large collection of smaller individual technical challenges, in many cases solved through a number of ~~crude hacks~~ clever tricks. Reference sources are given for many of the solutions, and a quick internet search will provide additional possibilities.

Judgement calls were made, and are often commented. Improvements are possible. The author is open to ideas and suggestions.

Packages were patched for re-use where they provided significant functionality. Examples include xcolor with its color models and conversion to HTML color output, and siunitx which provides many number and unit-formatting options, almost all of which are available in pure-text form, and thus easily used by *pdftotext*.

Packages were emulated where their primary purpose was visual formatting which is not relevent to HTML output. For example, packages related to sectioning are already patched by numerous other packages, creating a difficult number of combinations to try to support, and yet in HTML output all of the formatting is thrown away, so these packages are merely emulated.

Packages with graphical output are allowed as-is, but must be nested inside a `lateximage` environment to preserve the graphics.

Testing has primarily been done with the Iceweasel/Firefox browser.

Table 9: Section depths and html headings

Section	LaTeX depth	html headings *
title of the entire website		`<h1>`
none	-5	new for this package
book	-2	**not yet used**
part	-1	`<h2>`
chapter	0	`<h3>`
section	1	`<h4>`
subsection	2	`<h5>`
subsubsection	3	`<h6>`
paragraph	4	`<span class = "paragraph">`
subparagraph	5	`<span class = "subparagraph">`
listitem	7	new for this package, used for list items

* If `FormatWP` is true, section headings may be adjusted, depending on `WPTitleHeading`. See table 8 on page 167.

16 Section depths and HTML headings

Stacks are created to track depth inside the LaTeX document structure. This depth is translated to HTML headings as shown in table 9. "Depth" here is not depth in the traditional computer-science stack-usage sense, but rather a representation of the nesting depth inside the LaTeX document structure.

When starting a new section, the program first must close out any existing sections and lists of a deeper level to keep the HTML tags nested correctly.

Support for the memoir package will require the addition of a book level, which may push the HTML headings down a step, and also cause `subsubsection` to become a `<div>` due to a limit of six HTML headings.

It is possible to use HTML5 `<section>` and `<h1>` for all levels, but this may not be well-recognized by older browsers.

Fixed levels for parts and chapters allow the CSS to remain fixed as well.

17 Source code

This is where the documented source code for lwarp begins, continuing through the following sections all the way to the change log and index at the end of this document.

The following sections document the actual implementation of the lwarp package.

line numbers — The small numbers at the left end of a line refer to line numbers in the `lwarp.sty` file.

subjects — Blue-colored tags in the left margin aid in quickly identifying the subject of each paragraph.

objects — Black-colored tags in the left marign are used to identify programming objects such as files, packages, environments, booleans, and counters. Items without a tag are command macros. Each of these also appears in the index as individual entries, and are also listed together under "files", "packages", "environments", "booleans", and "counters".

index entries

⚠ warnings — Special warnings are marked with a warning icon.

for HTML output:
for PRINT output:
for HTML & PRINT: — Green-colored tags in the left margin show which sections of source code apply to the generation of HTML, print, or both forms of output.

— lwarp source code begins on the following page —

18 Detecting the TEX engine — *pdflatex*, *lualatex*, *xelatex*

See: http://tex.stackexchange.com/a/47579.

Detects XETEX and LUALATEX:

```
\RequirePackage{iftex}
\newif\ifxetexorluatex
\ifXeTeX
    \xetexorluatextrue
\else
    \ifLuaTeX
        \xetexorluatextrue
    \else
        \xetexorluatexfalse
    \fi
\fi

\ifLuaTeX
\RequirePackage{luatex85}% until the geometry package is updated
\fi

\RequirePackage{ifpdf}


\RequirePackage{ifptex}
```

19 Early package requirements

Pkg etoolbox Provides \ifbool and other functions.

Pkg xpatch Patches macros with optional arguments.

```
\RequirePackage{etoolbox}[2011/01/03]% v2.6 for \BeforeBeginEnvironment, etc.
\RequirePackage{xpatch}
```

Pkg ifplatform Provides \ifwindows to try to automatically detect WINDOWS OS.

```
\RequirePackage{ifplatform}% sense op-system platform
```

Pkg letltxmacro

```
\RequirePackage{letltxmacro}
```

20 Package load order

Several packages must never be used with lwarp, others should only be loaded before lwarp, and others should only be loaded after. The lwarp core checks most of these

cases. In some lwarp-* packages, \LWR@loadbefore is used to trigger an error if they are loaded after lwarp, while additional code provides necessary patches for when they are loaded before.

Packages which must be loaded after lwarp are enfoced by a large number of \LWR@loadafter statements, below. Some packages are emulated by memoir, and so these are tested by \LWR@notmemoirloadafter, which does not cause an error if memoir is used.

\LWR@checkloadfilename is used to check each filename to see if it must never be loaded, or must always be loaded before lwarp.

20.1 Tests of package load order

\LWR@loadafter {⟨*packagename*⟩} Error if this package was loaded before lwarp.

```
\newcommand*{\LWR@loadafter}[1]{%
\@ifpackageloaded{#1}
{
    \PackageError{lwarp}
        {%
            Package #1,\MessageBreak
            or one which uses #1,\MessageBreak
            must be loaded after lwarp
        }
        {Move \detokenize{\usepackage}{#1} after
        \detokenize{\usepackage}{lwarp}.\MessageBreak
        Package #1 may also be loaded by something else,\MessageBreak
        which must also be moved after lwarp.}
}
{}
}
```

\LWR@notmemoirloadafter {⟨*packagename*⟩} Error if not memoir class and this package was loaded before lwarp.

memoir emulates many packages, and pretends that they have already been loaded.

```
\@ifclassloaded{memoir}
{\newcommand*{\LWR@notmemoirloadafter}[1]{}}
{\LetLtxMacro\LWR@notmemoirloadafter\LWR@loadafter}
```

\LWR@notltjloadafter {⟨*packagename*⟩} Error if not a ltjs* class and this package was loaded before lwarp.

```
\LetLtxMacro\LWR@notltjloadafter\LWR@loadafter

\@ifclassloaded{ltjarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

```
\@ifclassloaded{ltjsbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjsreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjspf}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjskiyou}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtarticle}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtbook}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
\@ifclassloaded{ltjtreport}{\renewcommand*{\LWR@notltjloadafter}[1]{}}{}
```

`\LWR@loadbefore` {⟨*packagename*⟩} Error if this package is loaded after lwarp.

```
\newcommand*{\LWR@loadbefore}[1]{%
\@ifpackageloaded{#1}
{}
{
\PackageError{lwarp}
{Package #1 must be loaded before lwarp}
{Move \detokenize{\usepackage}{#1} before \detokenize{\usepackage}{lwarp}.}
}
}
```

`\LWR@checkloadbefore` {⟨*thispackagename*⟩} {⟨*packagename*⟩}

If package names match, error if it is loaded after lwarp.

```
\newcommand*{\LWR@checkloadbefore}[2]{%
    \edef\LWR@tempone{#1}%
    \ifdefstring{\LWR@tempone}{#2}{%
        \LWR@loadbefore{#1}%
    }{}%
}
```

`\LWR@loadnever` {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

The first packages is not supported, so tell the user to use the second instead.

```
\newcommand*{\LWR@loadnever}[2]{%
\PackageError{lwarp}
{%
    Package #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Package(s) #2 may be useful instead
}
{%
    Package #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another package.\MessageBreak
    For a possible alternative, see package(s) #2.
}
}
```

`\LWR@checkloadnever` {⟨*thispackagename*⟩} {⟨*badpackagename*⟩} {⟨*replacementpkgnames*⟩}

If this package name is the bad packagename, suggest the replacements instead.

```
\newcommand*{\LWR@checkloadnever}[3]{%
    \edef\LWR@tempone{#1}%
    \ifdefstring{\LWR@tempone}{#2}{%
        \LWR@loadnever{#2}{#3}%
    }{}%
}
```

\LWR@earlyloadnever {⟨*badpackagename*⟩} {⟨*replacementpkgname*⟩}

The first package is not supported, so tell the user to use the second instead. This version checks immediately for packages which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyloadnever}[2]{%
\@ifpackageloaded{#1}{%
\PackageError{lwarp}
{%
    Package #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Package(s) #2 may be useful instead
}
{%
    Package #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another package.\MessageBreak
    For a possible alternative, see package(s) #2.
}
}{}%
}
```

\LWR@earlyclassloadnever {⟨*badclassname*⟩} {⟨*replacementclassname*⟩}

The first class is not supported, so tell the user to use the second instead. This version checks immediately for classes which may have been loaded before lwarp.

```
\newcommand*{\LWR@earlyclassloadnever}[2]{%
\@ifclassloaded{#1}{%
\PackageError{lwarp}
{%
    Class #1 is not supported\MessageBreak
    by lwarp's HTML conversion.\MessageBreak
    Class(es) #2 may be useful instead
}
{%
    Class #1 might conflict with lwarp in some way,\MessageBreak
    or is superceded by another class.\MessageBreak
    For a possible alternative, see class(es) #2.
}
}{}%
}
```

20.2 Error for disallowed packages and classes loaded before lwarp

```
\LWR@earlyclassloadnever{jarticle}{ujarticle}
\LWR@earlyclassloadnever{jbook}{ujbook}
\LWR@earlyclassloadnever{jreport}{ujreport}
\LWR@earlyclassloadnever{tarticle}{utarticle}
\LWR@earlyclassloadnever{tbook}{utbook}
\LWR@earlyclassloadnever{treport}{utreport}
\LWR@earlyloadnever{ae}{cm-super, lmodern}
\LWR@earlyloadnever{aecompl}{cm-super, lmodern}
\LWR@earlyloadnever{aecc}{cm-super, lmodern}
\LWR@earlyloadnever{alg}{algorithm2e, algorithmicx}
\LWR@earlyloadnever{algorithmic}{algorithm2e, algorithmicx}
\LWR@earlyloadnever{boxedminipage}{boxedminipage2e}
\LWR@earlyloadnever{caption2}{caption}
% \LWR@earlyloadnever{ccaption}{caption}% might be preloaded by memoir
```

The older CJK and CJKutf8 only work with xeCJK:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@earlyloadnever{CJK}{ctex, xeCJK}
    \LWR@earlyloadnever{CJKutf8}{ctex, xeCJK}
}
```

bxcjkatype is based on CJK:

```
\LWR@earlyloadnever{bxcjkjatype}{upLaTeX, bxjsarticle, ujarticle, utarticle}
```

hangul is not in TeXLive, and is not tested:

```
\LWR@earlyloadnever{hangul}{kotex, xetexko, luatexko}
```

Others:

```
\LWR@earlyloadnever{colortab}{colortbl}
\LWR@earlyloadnever{epsf}{graphicx}
\LWR@earlyloadnever{fancyheadings}{fancyhdr}
\LWR@earlyloadnever{fncylab}{cleveref}
\LWR@earlyloadnever{glossary}{glossaries}
\LWR@earlyloadnever{hyper}{hyperref}
\LWR@earlyloadnever{pdfcprot}{microtype}
\LWR@earlyloadnever{picinpar}{floatflt, wrapfig}
\LWR@earlyloadnever{picins}{floatflt, wrapfig}
\LWR@earlyloadnever{sistyle}{siunitx}
\LWR@earlyloadnever{t1enc}{fontenc, inputenc, inputenx}
\LWR@earlyloadnever{ucs}{inputenc, inputencx}
\LWR@earlyloadnever{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

20.3 Enforcing package loading after lwarp

Packages which should only be loaded after lwarp are tested here to trip an error of they have already been loaded.

The following packages must be loaded after lwarp:

```
\LWR@loadafter{2in1}
```

```
\LWR@loadafter{2up}
\LWR@loadafter{a4}
\LWR@loadafter{a4wide}
\LWR@loadafter{a5comb}
\LWR@notmemoirloadafter{abstract}
\LWR@loadafter{academicons}
\LWR@loadafter{accsupp}
\LWR@loadafter{acro}
\LWR@loadafter{acronym}
\LWR@loadafter{adjmulticol}
\LWR@loadafter{addlines}
\LWR@loadafter{ae}
\LWR@loadafter{aecc}
\LWR@loadafter{afterpage}
\LWR@loadafter{algorithm2e}
\LWR@loadafter{algorithmicx}
\LWR@loadafter{alltt}
\LWR@loadafter{amsmath}
\LWR@loadafter{amsthm}
\LWR@loadafter{anonchap}
\LWR@loadafter{anysize}
\LWR@notmemoirloadafter{appendix}
\LWR@loadafter{ar}
\LWR@loadafter{arabicfront}
\LWR@notmemoirloadafter{array}
\LWR@loadafter{arydshln}
\LWR@loadafter{asymptote}
% \LWR@loadafter{atbegshi}% used by morewrites
\LWR@loadafter{attachfile}
\LWR@loadafter{attachfile2}
\LWR@loadafter{authblk}
\LWR@loadafter{autonum}
\LWR@loadafter{axessibility}
\LWR@loadafter{axodraw2}
\LWR@loadafter{backnaur}
\LWR@loadafter{backref}
\LWR@loadafter{balance}
\LWR@loadafter{bbding}
\LWR@loadafter{bigdelim}
\LWR@loadafter{bigfoot}
\LWR@loadafter{bigstrut}
\LWR@loadafter{bitpattern}
\LWR@loadafter{blowup}
\LWR@loadafter{booklet}
\LWR@loadafter{bookmark}
\LWR@notmemoirloadafter{booktabs}
\LWR@loadafter{bophook}
\LWR@loadafter{bounddvi}
\LWR@loadafter{boxedminipage}
\LWR@loadafter{boxedminipage2e}
\LWR@loadafter{breakurl}
\LWR@loadafter{breqn}
\LWR@loadafter{bsheaders}
\LWR@loadafter{bxpapersize}
\LWR@loadafter{bytefield}
```

```
\LWR@loadafter{cancel}
\LWR@loadafter{canoniclayout}
\LWR@loadafter{caption}
\LWR@loadafter{caption2}
\LWR@loadafter{cases}
% \LWR@loadafter{ccaption}% may be preloaded by memoir
\LWR@loadafter{changebar}
\LWR@loadafter{changelayout}
\LWR@notmemoirloadafter{changepage}
\LWR@loadafter{changes}
\LWR@loadafter{chappg}
\LWR@loadafter{chapterbib}
\LWR@loadafter{chemfig}
\LWR@loadafter{chemformula}
\LWR@loadafter{chemgreek}
\LWR@loadafter{chemmacros}
\LWR@loadafter{chemnum}
\LWR@loadafter{chkfloat}
\LWR@notmemoirloadafter{chngpage}
\LWR@loadafter{cite}
\LWR@loadafter{cmdtrack}
\LWR@loadafter{color}
\LWR@loadafter{colortbl}
\LWR@loadafter{continue}
\LWR@loadafter{copyrightbox}
\LWR@notmemoirloadafter{crop}
% ctex must be loaded before lwarp
\LWR@loadafter{ctable}
\LWR@loadafter{cuted}
\LWR@loadafter{cutwin}
\LWR@loadafter{dblfloatfix}
\LWR@loadafter{dblfnote}
\LWR@notmemoirloadafter{dcolumn}
\LWR@loadafter{diagbox}
\LWR@loadafter{dingbat}
\LWR@loadafter{dprogress}
\LWR@loadafter{draftcopy}
\LWR@loadafter{draftfigure}
\LWR@loadafter{draftwatermark}
\LWR@loadafter{easy-todo}
\LWR@loadafter{ebook}
\LWR@loadafter{ed}
\LWR@loadafter{ellipsis}
\LWR@loadafter{embrac}
\LWR@loadafter{emptypage}
\LWR@loadafter{endfloat}
\LWR@loadafter{endheads}
\LWR@loadafter{endnotes}
\LWR@notmemoirloadafter{enumerate}
\LWR@loadafter{enumitem}
\LWR@notmemoirloadafter{epigraph}
\LWR@loadafter{epsfig}
\LWR@loadafter{epstopdf}
\LWR@loadafter{epstopdf-base}
\LWR@loadafter{eqlist}
```

```
\LWR@loadafter{eqparbox}
\LWR@loadafter{errata}
\LWR@loadafter{eso-pic}
\LWR@loadafter{eurosym}
\LWR@loadafter{everypage}
\LWR@loadafter{everyshi}
\LWR@loadafter{extramarks}
\LWR@loadafter{fancybox}
\LWR@loadafter{fancyhdr}
\LWR@loadafter{fancyheadings}
\LWR@loadafter{fancyref}
\LWR@loadafter{fancytabs}
\LWR@loadafter{fancyvrb}
\LWR@loadafter{figcaps}
\LWR@loadafter{figsize}
\LWR@loadafter{fitbox}
\LWR@loadafter{fix2col}
\LWR@loadafter{fixme}
\LWR@loadafter{fixmetodonotes}
\LWR@loadafter{flafter}
\LWR@loadafter{flippdf}
\LWR@loadafter{float}
\LWR@loadafter{floatflt}
\LWR@loadafter{floatpag}
\LWR@loadafter{floatrow}
\LWR@loadafter{fltrace}
\LWR@loadafter{flushend}
\LWR@loadafter{fnbreak}
\LWR@loadafter{fncychap}
\LWR@loadafter{fnlineno}
\LWR@loadafter{fnpara}
\LWR@loadafter{fnpos}
\LWR@loadafter{fontawesome}
\LWR@loadafter{fontawesome5}
% fontenc must be loaded before lwarp
% fontspec must be loaded before lwarp
\LWR@loadafter{footmisc}
\LWR@loadafter{footnote}
\LWR@loadafter{footnotebackref}
\LWR@loadafter{footnotehyper}
\LWR@loadafter{footnoterange}
\LWR@loadafter{footnpag}
\LWR@loadafter{foreign}
\LWR@loadafter{forest}
\LWR@loadafter{framed}
\LWR@loadafter{ftcap}
\LWR@loadafter{ftnright}
\LWR@loadafter{fullminipage}
\LWR@loadafter{fullpage}
\LWR@loadafter{fullwidth}
\LWR@loadafter{fwlw}
\LWR@loadafter{gentombow}
% geometry is always loaded by lwarp, and lwarp-geometry is AtBeginDocument
\LWR@loadafter{gmeometric}
\LWR@loadafter{glossaries}
```

```
% \LWR@loadafter{graphics}% pre-loaded by xunicode
% \LWR@loadafter{graphicx}% pre-loaded by xunicode
\LWR@loadafter{gloss}
\LWR@loadafter{glossary}
\LWR@loadafter{grffile}
\LWR@loadafter{grid}
\LWR@loadafter{grid-system}
\LWR@loadafter{gridset}
\LWR@loadafter{hang}
\LWR@loadafter{hanging}
\LWR@loadafter{hypbmsec}
\LWR@loadafter{hypcap}
\LWR@loadafter{hypdestopt}
\LWR@loadafter{hypernat}
\LWR@loadafter{hyperref}
\LWR@loadafter{hyperxmp}
\LWR@loadafter{hyphenat}
\LWR@loadafter{idxlayout}
\LWR@loadafter{ifoddpage}
\LWR@loadafter{imakeidx}
\LWR@notmemoirloadafter{index}
% inputenc must be loaded before lwarp
% inputenx must be loaded before lwarp
% inputtrc may be loaded before lwarp
\LWR@loadafter{intopdf}
\LWR@loadafter{karnaugh-map}
\LWR@loadafter{keyfloat}
\LWR@loadafter{layaureo}
\LWR@loadafter{layout}
\LWR@loadafter{layouts}
\LWR@loadafter{leading}
\LWR@loadafter{letterspace}
\LWR@loadafter{lettrine}
\LWR@loadafter{lineno}
\LWR@loadafter{lips}
\LWR@loadafter{listings}
\LWR@loadafter{listliketab}
\LWR@loadafter{longtable}
\LWR@loadafter{lscape}
\LWR@loadafter{ltablex}
\LWR@loadafter{ltcaption}
\LWR@loadafter{ltxgrid}
\LWR@loadafter{ltxtable}
\LWR@loadafter{lua-check-hyphen}
\LWR@loadafter{lua-visual-debug}
\LWR@loadafter{luacolor}
\LWR@loadafter{luatodonotes}
\LWR@loadafter{magaz}
\LWR@notmemoirloadafter{makeidx}
\LWR@loadafter{manyfoot}
\LWR@loadafter{marginfit}
\LWR@loadafter{marginfix}
\LWR@loadafter{marginnote}
\LWR@loadafter{marvosym}
\LWR@loadafter{mathtools}
```

```
\LWR@loadafter{mcaption}
\LWR@loadafter{mdframed}
\LWR@loadafter{media9}
\LWR@loadafter{memhfixc}
\LWR@loadafter{metalogo}
\LWR@loadafter{metalogox}
\LWR@loadafter{mhchem}
\LWR@loadafter{microtype}
\LWR@loadafter{midfloat}
\LWR@loadafter{midpage}
\LWR@loadafter{minibox}
\LWR@loadafter{minitoc}
% morefloats must be allowed early for print mode
\LWR@notmemoirloadafter{moreverb}
% morewrites must be loaded before lwarp
\LWR@notmemoirloadafter{movie15}
\LWR@notmemoirloadafter{mparhack}
\LWR@loadafter{multicap}
%\LWR@loadafter{multicol}% loaded by ltxdoc
\LWR@loadafter{multicolrule}
\LWR@loadafter{multimedia}
\LWR@loadafter{multirow}
\LWR@loadafter{multitoc}
\LWR@loadafter{musicography}
\LWR@loadafter{nameauth}
\LWR@loadafter{nameref}
\LWR@loadafter{natbib}
\LWR@notmemoirloadafter{nccfancyhdr}
\LWR@notmemoirloadafter{needspace}
% newclude must be loaded before lwarp
\LWR@loadafter{newtxmath}
% newunicodechar must be loaded before lwarp
\LWR@notmemoirloadafter{nextpage}
\LWR@loadafter{nicefrac}
\LWR@loadafter{niceframe}
\LWR@loadafter{nomencl}
\LWR@loadafter{nonfloat}
\LWR@loadafter{nonumonpart}
\LWR@loadafter{nopageno}
\LWR@loadafter{notes}
\LWR@loadafter{notespages}
\LWR@loadafter{nowidow}
\LWR@loadafter{ntheorem}
\LWR@loadafter{octave}
\LWR@loadafter{overpic}
\LWR@loadafter{pagegrid}
\LWR@notmemoirloadafter{pagenote}
\LWR@loadafter{pagesel}
\LWR@loadafter{paralist}
\LWR@loadafter{parnotes}
\LWR@notmemoirloadafter{parskip}
\LWR@loadafter{pbox}
\LWR@loadafter{pdfcomment}
\LWR@loadafter{pdfcrypt}
\LWR@loadafter{pdflscape}
```

```
\LWR@loadafter{pdfmarginpar}
\LWR@loadafter{pdfpages}
\LWR@loadafter{pdfprivacy}
\LWR@loadafter{pdfrender}
\LWR@loadafter{pdfsync}
\LWR@loadafter{pdftricks}
\LWR@loadafter{pdfx}
\LWR@loadafter{perpage}
\LWR@loadafter{pfnote}
\LWR@loadafter{phfqit}
\LWR@loadafter{pifont}
\LWR@loadafter{placeins}
\LWR@loadafter{plarray}
\LWR@loadafter{plarydshln}
\LWR@loadafter{plextarray}
\LWR@loadafter{plextarydshln}
\LWR@loadafter{plcolortbl}
\LWR@loadafter{plextdelarray}
\LWR@loadafter{prelim2e}
\LWR@loadafter{prettyref}
\LWR@loadafter{preview}
\LWR@loadafter{psfrag}
\LWR@loadafter{psfragx}
\LWR@loadafter{pst-eps}
\LWR@loadafter{pstool}
\LWR@loadafter{pstricks}
% \LWR@loadafter{pxatbegshi}% may be used by morewrites
\LWR@loadafter{pxeveryshi}
\LWR@loadafter{pxftnright}
\LWR@loadafter{pxjahyper}
\LWR@loadafter{quotchap}
\LWR@loadafter{quoting}
\LWR@loadafter{ragged2e}
\LWR@loadafter{realscripts}
\LWR@loadafter{refcheck}
\LWR@loadafter{register}
\LWR@loadafter{relsize}
\LWR@loadafter{repeatindex}
\LWR@loadafter{resizegather}
\LWR@loadafter{rmpage}
\LWR@loadafter{romanbar}
\LWR@loadafter{romanbarpagenumber}
\LWR@loadafter{rotating}
\LWR@loadafter{rotfloat}
\LWR@loadafter{rviewport}
\LWR@loadafter{savetrees}
% scalefnt is loaded by babel-french
\LWR@loadafter{schemata}
\LWR@loadafter{scrextend}
\LWR@loadafter{scrhack}
\LWR@loadafter{scrlayer}
\LWR@loadafter{scrlayer-notecolumn}
\LWR@loadafter{scrlayer-scrpage}
\LWR@loadafter{scrpage2}
\LWR@loadafter{section}
```

```
\LWR@loadafter{sectionbreak}
\LWR@loadafter{sectsty}
\LWR@loadafter{semantic-markup}
\LWR@notmemoirloadafter{setspace}
\LWR@loadafter{shadow}
\LWR@loadafter{shapepar}
\LWR@notmemoirloadafter{showidx}
\LWR@loadafter{showkeys}
\LWR@loadafter{showtags}
\LWR@loadafter{sidecap}
\LWR@loadafter{sidenotes}
\LWR@loadafter{SIunits}
\LWR@loadafter{siunitx}
\LWR@loadafter{slantsc}
\LWR@loadafter{soul}
\LWR@loadafter{soulpos}
\LWR@loadafter{soulutf8}
\LWR@loadafter{splitidx}
\LWR@loadafter{srcltx}
\LWR@loadafter{srctex}
\LWR@loadafter{stabular}
\LWR@notltjloadafter{stfloats}
\LWR@loadafter{struktex}
\LWR@loadafter{subcaption}
\LWR@loadafter{subfig}
\LWR@loadafter{subfigure}
\LWR@loadafter{supertabular}
\LWR@loadafter{t1inc}
\LWR@loadafter{tabfigures}
\LWR@loadafter{tabls}
\LWR@loadafter{tablefootnote}
\LWR@notmemoirloadafter{tabularx}
\LWR@loadafter{tabulary}
\LWR@loadafter{tascmac}
\LWR@loadafter{textarea}
% \LWR@loadafter{textcomp}% maybe before lwarp with font packages
\LWR@loadafter{textfit}
\LWR@loadafter{textpos}
\LWR@loadafter{theorem}
\LWR@loadafter{thinsp}
\LWR@loadafter{threadcol}
\LWR@loadafter{threeparttable}
\LWR@loadafter{threeparttablex}
\LWR@loadafter{thumb}
\LWR@loadafter{thumbs}
\LWR@loadafter{tikz}
\LWR@loadafter{titleps}
\LWR@loadafter{titlesec}
\LWR@loadafter{titletoc}
\LWR@notmemoirloadafter{titling}
% \LWR@loadafter{tocbasic}% preloaded by koma-script classes
\LWR@notmemoirloadafter{tocbibind}
\LWR@loadafter{tocdata}
\LWR@loadafter{tocenter}
\LWR@notmemoirloadafter{tocloft}
```

```
\LWR@loadafter{tocstyle}
\LWR@loadafter{todo}
\LWR@loadafter{todonotes}
\LWR@loadafter{topcapt}
\LWR@loadafter{tram}
\LWR@loadafter{transparent}
\LWR@loadafter{trimclip}
\LWR@loadafter{trivfloat}
\LWR@loadafter{truncate}
\LWR@loadafter{turnthepage}
\LWR@loadafter{twoup}

% \LWR@loadafter{typearea}% preloaded by koma-script classes
\LWR@loadafter{typicons}
% \LWR@loadafter{ulem}% preloaded by ctexart and related classes
\LWR@loadafter{umoline}
\LWR@loadafter{underscore}
\LWR@loadafter{units}
\LWR@loadafter{unitsdef}
\LWR@loadafter{upref}
\LWR@loadafter{url}
\LWR@loadafter{uspace}
\LWR@loadafter{varioref}% no lwarp package provided
\LWR@notmemoirloadafter{verse}
\LWR@loadafter{versonotes}
\LWR@loadafter{vertbars}
\LWR@loadafter{vmargin}
\LWR@loadafter{vowel}
\LWR@loadafter{vpe}
\LWR@loadafter{vwcol}
\LWR@loadafter{wallpaper}
\LWR@loadafter{watermark}
\LWR@loadafter{widows-and-orphans}
\LWR@loadafter{wrapfig}
\LWR@loadafter{xbmks}
\LWR@loadafter{xcolor}
\LWR@loadafter{xechangebar}
\LWR@loadafter{xellipsis}
% xetexko-vertical must be loaded before lwarp
\LWR@loadafter{xfakebold}
\LWR@loadafter{xfrac}
\LWR@loadafter{xltabular}
\LWR@loadafter{xltxtra}
\LWR@loadafter{xmpincl}
\LWR@loadafter{xpiano}
\LWR@loadafter{xpinyin}
\LWR@loadafter{xr}
\LWR@loadafter{xr-hyper}
\LWR@loadafter{xtab}
% xunicode must be loaded before lwarp
\LWR@loadafter{xurl}
\LWR@loadafter{xy}
\LWR@loadafter{zwpagelayout}
```

21 MD5 hashing

The MD5 hash is used for `lateximage` filenames for SVG math.

```
\newcommand{\LWR@mdfive}[1]{%
\PackageError{lwarp}
{No MD5 macro was found}
{Lwarp must find the macros pdfmdfivesum or mdfivesum.}
}
```

The default for pdfLaTeX, DVILaTeX, upLaTeX, etc:

```
\let\LWR@mdfive\pdfmdfivesum
```

For LuaLaTeX:

```
\ifLuaTeX
\RequirePackage{pdftexcmds}
\let\LWR@mdfive\pdf@mdfivesum
\fi
```

For XeLaTeX:

```
\ifXeTeX
\@ifundefined{pdffivesum}{}
    {\let\LWR@mdfive\pdfmdfivesum}
\@ifundefined{mdfivesum}{}
    {\let\LWR@mdfive\mdfivesum}
\fi
```

22 pdfLaTeX T1 and UTF-8 encoding

When using pdfLaTeX, lwarp requires T1 encoding, and recommends UTF-8 encoding.

If some other input encoding is already defined, lwarp will try to use it instead, and hope for the best.

XeLaTeX and LuaLaTeX are both UTF-8 by nature.

`\LWR@pdfencoding` Sets `T1`, and also `utf8` if not already set.

```
\newcommand*{\LWR@pdfencoding}{%
    \RequirePackage[T1]{fontenc}

    \@ifpackageloaded{inputenc}{}{
        \@ifpackageloaded{inputenx}{}{
            \RequirePackage[utf8]{inputenc}
        }
    }
}
```

```
\ifPDFTeX% pdflatex or dvi latex
    \LWR@pdfencoding
\fi

\ifpTeX
    \LWR@pdfencoding
\fi
```

23 Unicode input characters

for HTML & PRINT:

If using *pdflatex*, convert a minimal set of Unicode characters. Additional characters may be defined by the user, as needed.

A commonly-used multiply symbol is declared to be `\texttimes`.

The first arguments of `\newunicodechar` below are text ligatures in the source code, even though they are not printed in the following listing.

```
\ifpTeX
\else
\RequirePackage{newunicodechar}

\newunicodechar{×}{\texttimes}

\ifPDFTeX% pdflatex or dvi latex
\newunicodechar{ff}{ff}% the first arguments are ligatures
\newunicodechar{fi}{fi}
\newunicodechar{fl}{fl}
\newunicodechar{ffi}{ffi}
\newunicodechar{ffl}{ffl}
\newunicodechar{–}{---}
\newunicodechar{–}{--}
\fi

\fi
```

24 Avoid a bitmapped font

If DVI or PDF LaTeX, and if the default Computer Modern is the selected font family, ensure that cm-super or lmodern is used to provide a vector font.

```
\ifxetexorluatex
\else
    \ifdefstring{\f@family}{cmr}{
        \IfFileExists{type1ec.sty}% found in cm-super
        {}
        {% cm-super not installed
            \IfFileExists{lmodern.sty}{
                \PackageInfo{lwarp}{cm-super not installed, loading lmodern}
```

```
                \RequirePackage{lmodern}
            }{
                \PackageError{lwarp}
                {%
                    Lwarp requires a vector font.\MessageBreak
                   Install and load cm-super, lmodern, or another\MessageBreak
                    Type-1 vector font before loading lwarp%
                }
                {%
                    Install cm-super or lmodern.\MessageBreak
                    If lmodern, load it before lwarp:\MessageBreak
                        \space\space\protect\usepackage{lmodern}\MessageBreak
                        \space\space\protect\usepackage{lwarp}%
                }
            }
        }% cm-super not installed
    }{}% f@family
\fi
```

25 Upright quotes

In PDFTEX, preserve upright quotes in verbatim text. upquote also loads textcomp.

```
\ifPDFTeX
\RequirePackage{upquote}
\fi

\ifpTeX
    \RequirePackage{upquote}
\fi
```

26 Miscellaneous tools

`\LWR@providelength` {⟨\lengthname⟩} Provides the length if it isn't defined yet.

Used to provide source compatibility for lengths which will be ignored, but might or might not be already provided by other packages.

```
\newcommand*\LWR@providelength[1]{%
    \ifdeflength{#1}{}{\newlength{#1}}%
}
```

`\LWR@convertto` {⟨*dest unit*⟩} {⟨*length*⟩}

Prints a length in the given units, without printing the unit itself.

```
\newcommand*{\LWR@convertto}[2]{\strip@pt\dimexpr #2*65536/\number\dimexpr 1#1}
```

\LWR@printpercentlength {⟨*smaller*⟩} {⟨*larger*⟩}

Prints a percent ratio of the two lengths.

```
\newcommand*{\LWR@printpercentlength}[2]{%
    \setcounter{LWR@tempcountone}{100*\ratio{#1}{#2}}%
    \arabic{LWR@tempcountone}%
}
```

\LWR@patcherror {⟨*packagename*⟩} {⟨*macroname*⟩}

Prints an error if could not patch a macro.

```
\newcommand*{\LWR@patcherror}[2]{%
\PackageError{lwarp}
{Unable to patch package #1, macro #2}
{Please contact the author of the lwarp package.}
}
```

\LWR@isolate {⟨*text*⟩} Isolates Chinese characters from the surrounding text. This is required to avoid extra spaces on either side of the Chinese characters, especially when written to a file.

```
\newcommand{\LWR@isolate}[1]{#1}%

\@ifpackageloaded{ctexpatch}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}

\@ifpackageloaded{xeCJK}{
    \renewcommand{\LWR@isolate}[1]{\null#1\null}%
}{}
```

\LWR@firstoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@secondoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@thirdoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

\LWR@fourthoffour {⟨*first*⟩} {⟨*second*⟩} {⟨*third*⟩} {⟨*fourth*⟩}

Expands to the nth of the four arguments. Used for extra cross referencing.

```
\long\def\LWR@firstoffour#1#2#3#4{#1}
\long\def\LWR@secondoffour#1#2#3#4{#2}
\long\def\LWR@thirdoffour#1#2#3#4{#3}
\long\def\LWR@fourthoffour#1#2#3#4{#4}
```

27 Operating-System portability

Prog Unix
Prog Mac OS
Prog Linux
Prog MS-Windows
Prog Windows
Opt OSWindows

lwarp tries to detect which operating system is being used. UNIX / MAC OS / LINUX is the default (collectively referred to as "UNIX" in the configuration files), and MS-WINDOWS is supported as well.

If MS-WINDOWS is not correctly detected, use the lwarp option `OSWindows`.

When detected or specified, the operating-system path separator used by lwarp is modified, and the boolean `usingOSWindows` is set `true`. This boolean may be tested by the user for later use.

27.1 Literal characters

Literal characters to be used in `PrintLatexCmd` and `HTMLLatexCmd`. These are defined without `@` to easily allow their inclusion in the user's document.

The literal `%` character:

```
\let\LWRpercent\@percentchar
```

The literal `$` character:

```
\catcode`\$=12
\def\LWRdollar{$}
\catcode`\$=3
```

The literal `&` character:

```
\catcode`\&=12
\def\LWRamp{&}
\catcode`\&=4
```

The literal `\` character. The ampersand is temporarily set to the escape character during the definition of the backslash macro.

```
\catcode`\&=0
&catcode`&\=12
&def&LWRbackslash{\}
&catcode`&\=0
\catcode`\&=4
```

The literal `{` character. The ampersand is temporarily set to the begin group character during the definition of the leftbrace macro.

```
\catcode`\&=1
\catcode`\{=12
\def\LWRleftbrace&{}
\catcode`\{=1
\catcode`\&=4
```

The literal } character. The ampersand is temporarily set to the end group character during the definition of the leftbrace macro.

```
\catcode`\&=2
\catcode`\}=12
\def\LWRrightbrace{}&
\catcode`\}=2
\catcode`\&=4
```

The literal # character:

```
\catcode`\#=12
\def\LWRhash{#}
\catcode`\#=6
```

`\LWRopquote` The operating system's quote mark, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
\def\LWRopquote{'}
```

`\LWRopseq` The operating system's sequential execution command, UNIX default. For WINDOWS, see `\LWR@setOSWindows`, below.

```
\def\LWRopseq{\space\LWRamp\LWRamp\space\space}
```

27.2 Common portability code

`Bool usingOSWindows` Set if the `OSWindows` option is used, or if WINDOWS is automatically detected.

```
\newbool{usingOSWindows}
\boolfalse{usingOSWindows}
```

27.3 UNIX, LINUX, and MAC OS

`\OSPathSymbol` Symbol used to separate directories in a path.

```
\newcommand*{\OSPathSymbol}{/}
```

27.4 MS-WINDOWS

For MS-WINDOWS:

`\LWR@setOSWindows` Set defaults for the MS-WINDOWS operating system. lwarp attempts to auto-detect the operatings system, and the `OSWindows` option may also be used to force MS-WINDOWS compatibility.

```
\newcommand*{\LWR@setOSWindows}
{
\booltrue{usingOSWindows}
\renewcommand*{\OSPathSymbol}{\@backslashchar}
\def\LWRopquote{"}
\def\LWRopseq{\space\LWRamp\space\space}
}
```

Test for windows during compile. The user may also specify `OSWindows` package option in case this test fails.

```
\ifwindows
\LWR@setOSWindows
\fi
```

28 Package options

Pkg kvoptions — Allows key/value package options.

```
\RequirePackage{kvoptions}
\SetupKeyvalOptions{family=LWR,prefix=LWR@}
```

\lwarpsetup — A user interface to set the keys:

```
\newcommand{\lwarpsetup}[1]{\setkeys{LWR}{#1}}
```

Bool warpingprint
Bool warpingHTML
Bool mathjax
Bool LWR@origmathjax

Set to true/false depending on the package option selections for print/HTML/EPUB output and mathsvg/mathjax.

`LWR@origmathjax` remembers the original setting to be restored by `\displaymathnormal`.

```
\newbool{warpingprint}
\newbool{warpingHTML}
\newbool{mathjax}
\newbool{LWR@origmathjax}
```

defaults — The default is print output, and SVG math if the user chose HTML output.

```
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
\boolfalse{mathjax}%
```

Opt warpprint — If the `warpprint` option is given, boolean `warpingprint` is true and boolean `warpingHTML` is false, and may be used for `\ifbool` tests.

```
\DeclareVoidOption{warpprint}{%
\PackageInfo{lwarp}{Using option 'warpprint'}
```

```
\booltrue{warpingprint}%
\boolfalse{warpingHTML}%
}
```

Opt warpHTML Anything in the warpHTML environment will be generated for HTML output only.

Opt warpHTML If the warpHTML option is given, boolean warpingHTML is true and boolean warpingprint is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{warpHTML}{%
\PackageInfo{lwarp}{Using option 'warpHTML'}%
\booltrue{warpingHTML}%
\boolfalse{warpingprint}%
}
```

Opt mathsvg Option mathsvg selects SVG math display: If the mathsvg option is given, boolean mathjax is false, and may be used for \ifbool tests.

```
\DeclareVoidOption{mathsvg}{%
\PackageInfo{lwarp}{Using option 'mathsvg'}
\boolfalse{mathjax}%
\boolfalse{LWR@origmathjax}%

}
```

Opt mathjax Option mathjax selects MathJax math display: If the mathjax option is given, boolean mathjax is true, may be used for \ifbool tests.

```
\DeclareVoidOption{mathjax}{%
\PackageInfo{lwarp}{Using option 'mathjax'}
\booltrue{mathjax}%
\booltrue{LWR@origmathjax}%

}
```

Opt BaseJobname Option BaseJobname sets the \BaseJobname for this document.
Default: \jobname

This is the \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without _html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```
\DeclareStringOption[\jobname]{BaseJobname}
```

Opt ImagesDirectory Option ImagesDirectory sets the name of the directory to use for the lateximage images.
Default: \jobname-images

```
\DeclareStringOption[\BaseJobname-images]{ImagesDirectory}
```

Opt ImagesName Option ImagesName sets the prefix to use for the lateximage images.
Default: image-

```
\DeclareStringOption[image-]{ImagesName}
```

Opt makeindexStyle
Default: lwarp.ist

Selects a custom .ist file. A customized file should be based on lwarp.ist, and must retain the lines related to \hyperindexref.

```
\DeclareStringOption[lwarp.ist]{makeindexStyle}
```

Opt xindyStyle
Default: lwarp.xdy

Selects a custom .xdy file. A customized file should be based on lwarp.xdy, and must retain the line

```
(markup-locref :open "\hyperindexref{" :close "}")
```

```
\DeclareStringOption[lwarp.xdy]{xindyStyle}
```

Opt xindyLanguage
Default: english

Sets the xindy language to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index and glossary.

```
\DeclareStringOption[english]{xindyLanguage}
```

Opt xindyCodepage
Default: utf8

Sets the xindy codepage to be assigned in *lwarpmk*'s configuration files. This is then used by *lwarpmk* while processing the index.

```
\DeclareStringOption[utf8]{xindyCodepage}
```

Opt pdftotextEnc
Default: UTF-8

The option pdftotextEnc sets the encoding used by *pdftotext*. This is passed to *pdftotext* using its -enc option, and is used when converting LaTeX PDF output with HTML tags into a plain-text file with HTML tags.

```
\DeclareStringOption[UTF-8]{pdftotextEnc}
```

Opt lwarpmk

Tells lwarp to generate a local copy of *lwarpmk* called lwarpmk.lua. Useful for archiving for future use. This file may be made executable and acts just like *lwarpmk*.

If lwarpmk option, creates a local copy of lwarpmk.lua:

```
\newbool{LWR@creatinglwarpmk}
\boolfalse{LWR@creatinglwarpmk}

\DeclareVoidOption{lwarpmk}{
\PackageInfo{lwarp}{Using option 'lwarpmk'}
\booltrue{LWR@creatinglwarpmk}
}
```

Opt OSWindows

Tells lwarp to use MS-Windows compatibility. Auto-detection of the operating system is attempted, and this option is only necessary if the auto-detection fails. See the automatically-generated lwarpmk.conf file to find out whether the operating system was detected correctly.

```
\DeclareVoidOption{OSWindows}{
\PackageInfo{lwarp}{Using option 'OSWindows'}
\LWR@setOSWindows
}
```

Opt HomeHTMLFilename
Default: \BaseJobname

The filename of the homepage. The default is the jobname. This option is stored into \LWR@HomeHTMLFilename, and later transferred into \HomeHTMLFilename for internal use.

```
787 \DeclareStringOption[]{HomeHTMLFilename}
```

Opt HTMLFilename
Default: <empty>

The filename prefix of web pages after the homepage. The default is empty, no prefix. This option is stored into \LWR@HTMLFilename, and later transferred into \HTMLFilename for internal use.

```
788 \DeclareStringOption[]{HTMLFilename}
```

Opt PrintLatexCmd
Default: <automatic>

The shell commands to use to compile the print document.

```
789 \DeclareStringOption[]{PrintLatexCmd}
```

Opt HTMLLatexCmd
Default: <automatic>

The shell commands to use to compile the HTML document.

```
790 \DeclareStringOption[]{HTMLLatexCmd}
```

Opt PrintIndexCmd
Default: <empty>

The shell commands to use to compile the print indexes.

```
791 \DeclareStringOption[]{PrintIndexCmd}
```

Opt HTMLIndexCmd
Default: <empty>

The shell commands to use to compile the HTML indexes.

```
792 \DeclareStringOption[]{HTMLIndexCmd}
```

Opt LatexmkIndexCmd
Default: <empty>

The shell commands to by used by *latexmk* to compile the print indexes. Unlike PrintIndexCmd and HTMLIndexCmd, LatexmkIndexCmd does not include the filename, which will be provided by *latexmk*.

```
793 \DeclareStringOption[]{LatexmkIndexCmd}
```

Opt makeindex

Tells lwarp to use makeindex for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *makeindex* with a single index file.

```
794 \DeclareBoolOption[false]{makeindex}
```

Opt xindy

Tells lwarp to use xindy for index generation. When lwarpmk.conf and *.lwarpmkconf are generated, PrintIndexCmd and HTMLIndexCmd will be set for *xindy* with a single index file.

```
795 \DeclareBoolOption[false]{xindy}
```

Opt GlossaryCmd
Default: makeglossaries

The shell command to use to compile the glossary. The print or HTML version of the glossary filename will be appended to this command.

```
796 \DeclareStringOption[makeglossaries]{GlossaryCmd}
```

Opt latexmk Option latexmk tells *lwarpmk* to use *latexmk* when compiling documents.

```
\DeclareBoolOption[false]{latexmk}
```

Opt dvips Option dvips tells *lwarpmk* to use *dvips* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvips}
```

Opt dvipdfm Option dvipdfm tells *lwarpmk* to use *dvipdfm* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvipdfm}
```

Opt dvipdfmx Option dvipdfmx tells *lwarpmk* to use *dvipdfmx* when compiling DVI *latex* documents.

```
\DeclareBoolOption[false]{dvipdfmx}
```

Execute options Execute the package options, with the defaults which have been set just above:

```
\ProcessKeyvalOptions*\relax
```

28.1 Additional options support

Assign the \BaseJobname if the user hasn't provided one:

```
\providecommand*{\BaseJobname}{\LWR@BaseJobname}
```

Defaults unless already over-ridden by the user:

```
\ifcsempty{LWR@HomeHTMLFilename}{
    \newcommand*{\HomeHTMLFilename}{\BaseJobname}
}{
    \csedef{HomeHTMLFilename}{\LWR@HomeHTMLFilename}
}

\csedef{HTMLFilename}{\LWR@HTMLFilename}
```

Special handling for underscores in labels and filenames.

\LWR@sanitized The sanitized version of what was given to \LWR@sanitize. Characters are set to their detokenized versions. Required for underscores in labels and filenames.

```
\newcommand*{\LWR@sanitized}{}
```

\LWR@sanitize {⟨*text*⟩}

Sanitizes the text and returns the result in \LWR@sanitized.

```
\newcommand*{\LWR@sanitize}[1]{%
\edef\LWR@sanitized{#1}%
\edef\LWR@sanitized{\detokenize\expandafter{\LWR@sanitized}}%
}
```

Sanitize some string options to neutralize underscores.

```
\LWR@sanitize{\LWR@BaseJobname}
\edef\LWR@BaseJobname{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesDirectory}
\edef\LWR@ImagesDirectory{\LWR@sanitized}

\LWR@sanitize{\LWR@ImagesName}
\edef\LWR@ImagesName{\LWR@sanitized}
```

`\LWR@PrintIndexCmd` and `\LWR@HTMLIndexCmd` are tested to see if they are empty. If so, they are set to a reasonable defaults for a single index using *makeindex*, then possibly set to defaults for *xindy* if the lwarp `xindy` option was selected.

```
\ifdefempty{\LWR@PrintIndexCmd}{
    \renewcommand{\LWR@PrintIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@PrintIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname.idx%
        }
    }{}
}{}

\ifdefempty{\LWR@HTMLIndexCmd}{
    \renewcommand{\LWR@HTMLIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle \space  \jobname_html.idx%
    }
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@HTMLIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage \space
            \jobname_html.idx%
        }
    }{}
}{}

\ifdefempty{\LWR@LatexmkIndexCmd}{
    \renewcommand{\LWR@LatexmkIndexCmd}{%
        makeindex  -s \LWR@makeindexStyle%
    }
```

```
    \ifbool{LWR@xindy}{
        \renewcommand{\LWR@LatexmkIndexCmd}{%
            xindy
            -M \LWR@xindyStyle \space
            -L \LWR@xindyLanguage \space
            -C \LWR@xindyCodepage%
        }
    }{}
}{}
```

28.2 Conditional compilation

\warpprintonly {⟨*contents*⟩}

Only process the contents if producing printed output.

```
\newcommand{\warpprintonly}[1]{\ifbool{warpingprint}{#1}{}}
```

\warpHTMLonly {⟨*contents*⟩}

Only process the contents if producing HTML output.

```
\newcommand{\warpHTMLonly}[1]{\ifbool{warpingHTML}{#1}{}}
```

Pkg comment Provides conditional code blocks.

Attempts to use versions or verbatim fail in some cases, and do not provide much of a speed benefit even when they do work.

```
\RequirePackage{comment}
```

Use `comment_print.cut` for print mode, and `comment_html.cut` for HTML mode. This helps *latexmk* to more reliably know whether to recompile.

```
\ifbool{warpingHTML}{
\def\DefaultCutFileName{\def\CommentCutFile{comment_html.cut}}
}{}

\ifbool{warpingprint}{
\def\DefaultCutFileName{\def\CommentCutFile{comment_print.cut}}
}{}
```

Env warpall Anything in the `warpall` environment will be generated for print or HTML outputs.

```
\includecomment{warpall}
```

Env warpprint Anything in the `warpprint` environment will be generated for print output only.

Env warpHTML

For HTML output:

```
\ifbool{warpingHTML}
{\includecomment{warpHTML}}
{\excludecomment{warpHTML}}%

\ifbool{warpingprint}
{\includecomment{warpprint}}
{\excludecomment{warpprint}}
```

Optionally generate a local copy of *lwarpmk*. Default to no.

```
\ifbool{LWR@creatinglwarpmk}
{\includecomment{LWR@createlwarpmk}}
{\excludecomment{LWR@createlwarpmk}}
```

29 Required packages

These packages are automatically loaded by lwarp when generating HTML output. Some of them are also automatically loaded when generating print output, but some are not.

for HTML output:

```
\begin{warpHTML}
```

Load fontspec if necessary:

```
\ifxetexorluatex
\@ifpackageloaded{fontspec}{}{
    \usepackage[no-math]{fontspec}
}
```

The monospaced font is used for HTML tags, so turn off its TeX ligatures and common ligatures:

```
\defaultfontfeatures[\rmfamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\sffamily]{Ligatures={NoCommon,TeX}}
\defaultfontfeatures[\ttfamily]{Ligatures=NoCommon}
\else
```

pdflatex only: Only pre-loaded if *pdflatex* is being used.

Pkg microtype

ligatures Older browsers don't display ligatures. Turn off letter ligatures, keeping LaTeX dash and quote ligatures, which may fail on older browers but at least won't corrupt written words.

```
\RequirePackage {microtype}

\microtypesetup{
    protrusion=false,
    expansion=false,
```

```
    tracking=false,
    kerning=false,
    spacing=false}

\DisableLigatures[f,q,t,T,Q]{encoding = *,family = *}

\fi

\end{warpHTML}
```

Pkg geometry Tactics to avoid unwanted page breaks and margin overflow:

- Uses a very long and wide page to minimize page breaks and margin overflow.
- Uses a scriptsize font.
- Uses extra space at the margin to avoid HTML tag overflow off the page.
- Forces a new PDF page before some environments.
- Forces line break between major pieces of long tags.

for HTML output:

```
\begin{warpHTML}

\RequirePackage{geometry}
```

Avoid class and option conflict by changing settings after package load:

```
\geometry{
    paperheight=190in,%
    paperwidth=20in,%
    left=2in,right=6in,%
    top=1in,bottom=1in,%
}
```

ltjtarticle and other classes may require these to be reset by lwarp:

```
\setlength{\textheight}{0.8\paperheight}
\setlength{\textwidth}{0.7\paperwidth}

\@twosidefalse
\@mparswitchfalse

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xparse

LaTeX3 command argument parsing

```
\RequirePackage{xparse}
```

Pkg calc

```
\RequirePackage{calc}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg expl3

LaTeX3 programming

```
\RequirePackage{expl3}
```

Pkg gettitlestring

Used to emulate \nameref.

```
\RequirePackage{gettitlestring}
```

Pkg everyhook

everyhook is used to patch paragraph handling.

```
\@ifundefined{bxjs@everypar}{}{\let\everypar\bxjs@everypar}

\RequirePackage{everyhook}
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg filecontents

Used to write helper files, done in print mode.

Patched to work with morewrites, per https://tex.stackexchange.com/questions/312830/does-morewrites-not-support-filecontents-and-can-i-write-body-of-environment-us/312910

```
\RequirePackage{filecontents}

\@ifpackagelater{filecontents}{2011/10/09}%
{}
{
\newwrite\fcwrite
\let\LWR@origfilec@ntents\filec@ntents
\def\filec@ntents{\def\chardef##1\write{\let\reserved@c\fcwrite}\LWR@origfilec@ntents}
}

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg xifthen

```
\RequirePackage{xifthen}
```

Pkg verbatim

```
\RequirePackage{verbatim}
```

Pkg refcount

Provides \setcounterref, \setcounterpageref, etc.

```
\RequirePackage{refcount}
```

Pkg newfloat

```
\RequirePackage{newfloat}
```

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Pkg xstring

⚠ index

There was a short-term bug in xstring regarding \IfInteger which affected lwarp's index generation. The updated version is requested here.

```
\RequirePackage{xstring}[2019/02/01]
```

Pkg environ

Used to encapsulate math environments for re-use in HTML <alt> text.

```
\RequirePackage{environ}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Pkg printlen

Used to convert lengths for image width/height options.

```
\RequirePackage{printlen}
```

\LWR@printlength {⟨*length*⟩}

Prints a length using a locally-controlled unit and space. Rounding is used unless the length is small.

```
\newrobustcmd*{\LWR@printlength}[1]{%
\begingroup%
\uselengthunit{PT}%
\renewcommand*{\unitspace}{}%
\ifdimless{#1}{10pt}{%
    \printlength{#1}%
}{%
```

```
    \rndprintlength{#1}%
}%
\endgroup%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Pkg varwidth Used for print-mode lateximage.

```
\RequirePackage{varwidth}

\end{warpprint}
```

30 Loading packages

for HTML & PRINT:

```
\begin{warpall}
```

Remember the original \RequirePackage:

```
\LetLtxMacro\LWR@origRequirePackage\RequirePackage
```

\LWR@requirepackagenames Stores the list of required package names.

```
\newcommand*{\LWR@requirepackagenames}{}
```

\LWR@parsedrequirepackagenames Stores the parsed list of required package names after spaces are removed and lwarp- is prepended.

```
\newcommand*{\LWR@parsedrequirepackagenames}{}
```

\LWR@nullifycomment Remove the preexisting comment environment. Certain packages define it for their own use.

```
\newcommand*{\LWR@nullifycomment}{%
    \PackageInfo{lwarp}%
        {Nullifying the comment environment before loading \LWR@strresulttwo,}%
    \let\comment\relax%
    \let\endcomment\relax%
}
```

\LWR@findword [⟨*1: separator*⟩] {⟨*2: list*⟩} {⟨*3: index*⟩} [⟨*4: destination*⟩]

Note that argument 4 is passed directly to \StrBetween.

```
\newcommand*\LWR@findword[3][,]{%
    \StrBetween[#3,\numexpr#3+1]{#1#2#1}{#1}{#1}%
}
```

`\LWR@checkloadfilename` {⟨*filename*⟩} Checks if this filename should be loaded after lwarp, or never at all.

The following should never be loaded:

```
\newcommand*{\LWR@checkloadfilename}[1]{%
\LWR@checkloadnever{#1}{ae}{latinmodern}
\LWR@checkloadnever{#1}{aecc}{latinmodern}
\LWR@checkloadnever{#1}{alg}{algorithm2e, algorithmicx}
\LWR@checkloadnever{#1}{algorithmic}{algorithm2e, algorithmicx}
\LWR@checkloadnever{#1}{bitfield}{bytefield}
\LWR@checkloadnever{#1}{boxedminipage}{boxedminipage2e}
\LWR@checkloadnever{#1}{caption2}{caption}
\LWR@checkloadnever{#1}{ccaption}{caption}
\LWR@checkloadnever{#1}{colortab}{colortbl}
\LWR@checkloadnever{#1}{doublespace}{setspace}
\LWR@checkloadnever{#1}{epsf}{graphicx}
\LWR@checkloadnever{#1}{fancyheadings}{fancyhdr}
\LWR@checkloadnever{#1}{fncylab}{cleveref}
\LWR@checkloadnever{#1}{glossary}{glossaries}
\LWR@checkloadnever{#1}{hyper}{hyperref}
\LWR@checkloadnever{#1}{newthm}{ntheorem}
\LWR@checkloadnever{#1}{pdfcprot}{microtype}
\LWR@checkloadnever{#1}{picinpar}{floatflt, wrapfig}
\LWR@checkloadnever{#1}{picins}{floatflt, wrapfig}
\LWR@checkloadnever{#1}{rplain}{fancyhdr}
\LWR@checkloadnever{#1}{si}{siunitx}
\LWR@checkloadnever{#1}{sistyle}{siunitx}
\LWR@checkloadnever{#1}{t1enc}{fontenc, inputenc, inputenx}
\LWR@checkloadnever{#1}{ucs}{inputenc, inputencx}
\LWR@checkloadnever{#1}{wasysym}{textcomp, amssymb, amsfonts, mnsymbol, fdsymbol}
```

The following should only be loaded before lwarp:

```
\LWR@checkloadbefore{#1}{ctex}
\LWR@checkloadbefore{#1}{fontspec}
\LWR@checkloadbefore{#1}{inputenc}
\LWR@checkloadbefore{#1}{inputenx}
\LWR@checkloadbefore{#1}{nfssext-cfr}
\LWR@checkloadbefore{#1}{fontaxes}
\LWR@checkloadbefore{#1}{kotex}
\LWR@checkloadbefore{#1}{luatexja}
\LWR@checkloadbefore{#1}{luatexja-fontspec}
\LWR@checkloadbefore{#1}{luatexko}
\LWR@checkloadbefore{#1}{morewrites}
\LWR@checkloadbefore{#1}{newclude}
\LWR@checkloadbefore{#1}{newunicodechar}
\LWR@checkloadbefore{#1}{plext}
\LWR@checkloadbefore{#1}{xeCJK}
\LWR@checkloadbefore{#1}{xetexko}
\LWR@checkloadbefore{#1}{zxjatype}
}
```

`\LWR@lookforpackagename` {⟨*index*⟩}

If HTML, and if this is an lwarp-supported package name, re-direct it to the lwarp version by renaming it `lwarp-` followed by the original name.

Looks `index` deep into the list of package names, `\LWR@requirepackagenames`, and builds `\LWR@parsedrequirepackagenames` which is the modified list of names.

```
\newcommand*{\LWR@lookforpackagename}[1]{%
```

Find the `index`'th package name from the list:

```
\LWR@findword{\LWR@requirepackagenames}{#1}[\LWR@strresult]%
```

Remove blanks. The original name with blanks is in `LWR@strresult` and the final name with no blanks goes into `LWR@strresulttwo`.

```
\StrSubstitute[100]{\LWR@strresult}{ }{}[\LWR@strresulttwo]%
```

See if the package name was found:

```
\IfStrEq{\LWR@strresulttwo}{}%
{}% no filename
{% yes filename was found
```

Possible adjustments before loading the package. Maybe nullify the `comment` environment if the new package will be redefining it for a new purpose.

```
    \ifdefstring{\LWR@strresulttwo}{easyReview}{\LWR@nullifycomment}{}%
    \ifdefstring{\LWR@strresulttwo}{changes}{\LWR@nullifycomment}{}%
```

If HTML, check if the package should be loaded before lwarp, or never at all:

```
    \ifbool{warpingHTML}{\LWR@checkloadfilename{\LWR@strresulttwo}}{}%
```

If HTML, and if found, and if an lwarp-equivalent name exists, use `lwarp-*` instead.

```
    \ifboolexpr{
        bool{warpingHTML} and
        test{\IfFileExists{lwarp-\LWR@strresulttwo.sty}}
    }%
    {% lwarp-* file found
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
            \edef\LWR@parsedrequirepackagenames{lwarp-\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,lwarp-\LWR@strresulttwo%
            }%
        }%
    }%
    {%
```

Otherwise, use the current package name.

```
        \ifdefvoid{\LWR@parsedrequirepackagenames}{%
```

```
            \edef\LWR@parsedrequirepackagenames{\LWR@strresulttwo}%
        }{%
            \edef\LWR@parsedrequirepackagenames{%
                \LWR@parsedrequirepackagenames,\LWR@strresulttwo%
            }%
        }%
    }% no lwarp-* file
}% yes filename
}
```

\RequirePackage [⟨*1: options*⟩] {⟨*2: package names*⟩} [⟨*3: version*⟩]

For each of many package names in a comma-separated list, if an lwarp version of a package exists, select it instead of the LaTeX version.

```
\RenewDocumentCommand{\RequirePackage}{o m o}{%
```

Redirect up to twenty names:[16]

```
\renewcommand*{\LWR@requirepackagenames}{#2}%
\renewcommand*{\LWR@parsedrequirepackagenames}{}%
\LWR@lookforpackagename{1}%
\LWR@lookforpackagename{2}%
\LWR@lookforpackagename{3}%
\LWR@lookforpackagename{4}%
\LWR@lookforpackagename{5}%
\LWR@lookforpackagename{6}%
\LWR@lookforpackagename{7}%
\LWR@lookforpackagename{8}%
\LWR@lookforpackagename{9}%
\LWR@lookforpackagename{10}%
\LWR@lookforpackagename{11}%
\LWR@lookforpackagename{12}%
\LWR@lookforpackagename{13}%
\LWR@lookforpackagename{14}%
\LWR@lookforpackagename{15}%
\LWR@lookforpackagename{16}%
\LWR@lookforpackagename{17}%
\LWR@lookforpackagename{18}%
\LWR@lookforpackagename{19}%
\LWR@lookforpackagename{20}%
```

\RequirePackage depending on the options and version:

```
\IfValueTF{#1}%
{% options given
    \IfValueTF{#3}% version given?
    {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}[#3]}%
    {\LWR@origRequirePackage[#1]{\LWR@parsedrequirepackagenames}}%
}%
{% no options given
    \IfValueTF{#3}% version given?
```

[16] This was originally nine names, but then I came across a package which used twelve...

```
    {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}[#3]}%
    {\LWR@origRequirePackage{\LWR@parsedrequirepackagenames}}%
}%
}
\LetLtxMacro\usepackage\RequirePackage

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@ProvidesPackagePass {⟨*pkgname*⟩} [⟨*version*⟩]

Uses the original package, including options.

```
\NewDocumentCommand{\LWR@ProvidesPackagePass}{m o}{
\PackageInfo{lwarp}{%
    Using package ‘#1’ and adding lwarp modifications,\MessageBreak
    including options,}%
\IfValueTF{#2}
{\ProvidesPackage{lwarp-#1}[#2]}
{\ProvidesPackage{lwarp-#1}}
\DeclareOption*{\PassOptionsToPackage{\CurrentOption}{#1}}
\ProcessOptions\relax
\IfValueTF{#2}
{\LWR@origRequirePackage{#1}[#2]}
{\LWR@origRequirePackage{#1}}
```

In some cases, the following seems to be required to avoid an “unknown option” error, such as when loading xcolor with options.

```
\DeclareOption*{}%
\ProcessOptions\relax
}
```

\LWR@ProvidesPackageDrop {⟨*pkgname*⟩} [⟨*version*⟩]

Ignores the original package and uses lwarp’s version instead. Drops/discards all options.

```
\NewDocumentCommand{\LWR@ProvidesPackageDrop}{m o}{
\PackageInfo{lwarp}{%
    Replacing package ‘#1’ with the lwarp version,\MessageBreak
    and discarding options,%
}%
\IfValueTF{#2}
{\ProvidesPackage{lwarp-#1}[#2]}
{\ProvidesPackage{lwarp-#1}}
```

Ignore all options.

```
\DeclareOption*{}
```

Nullifies then processes the options. Seems to be required when options contain curly braces, which were causing "Missing \begin{document}".

```
% \ProcessOptions\relax% original LaTeX code
\let\ds@\@empty%         from the original \ProcessOptions
\edef\@curroptions{}%    lwarp modification to \ProcessOptions
\@process@ptions\relax%  from the original \ProcessOptions
}

\end{warpHTML}
```

31 Additional required packages

for HTML output:

```
\begin{warpHTML}
```

Pkg caption

```
\LWR@origRequirePackage{caption}
\AtBeginDocument{\RequirePackage{lwarp-caption}}%

\end{warpHTML}
```

32 File handles

Defines file handles for writes.

for HTML & PRINT:

```
\begin{warpall}
```

\LWR@quickfile For quick temporary use only. This is reused in several places.

```
\newwrite\LWR@quickfile%

\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@lateximagesfile For <project>-images.txt:

```
\newwrite\LWR@lateximagesfile

\end{warpHTML}
```

33 Include a file

During HTML output, \include{<filename>} causes the following to occur:

1. lwarp creates <filename>_html_inc.tex whose contents are:
   \input <filename>.tex
2. <filename>_html_inc.tex is then \included instead of <filename>.tex.
3. <filename>_html_inc.aux is automatically generated and used by LaTeX.

for HTML output:

```
\begin{warpHTML}
```

\include {⟨*filename*⟩}

\@include {⟨*filename*⟩} Modified to load _html_inc files.

```
\def\@include#1 {%
\immediate\openout\LWR@quickfile #1_html_inc.tex% lwarp
\immediate\write\LWR@quickfile{\string\input{#1.tex}}% lwarp
\immediate\closeout\LWR@quickfile% lwarp
\LWR@origclearpage% \changed
\if@filesw
    \immediate\write\@mainaux{\string\@input{#1_html_inc.aux}}% changed
\fi
\@tempswatrue
\if@partsw
    \@tempswafalse
    \edef\reserved@b{#1}%
    \@for\reserved@a:=\@partlist\do
    {\ifx\reserved@a\reserved@b\@tempswatrue\fi}%
\fi
\if@tempswa
    \let\@auxout\@partaux
    \if@filesw
        \immediate\openout\@partaux #1_html_inc.aux % changed
        \immediate\write\@partaux{\relax}%
    \fi
    \@input@{#1_html_inc.tex}% changed
    \LWR@origclearpage% changed
    \@writeckpt{#1}%
    \if@filesw
        \immediate\closeout\@partaux
    \fi
\else
    \deadcycles\z@
    \@nameuse{cp@#1}%
\fi
\let\@auxout\@mainaux%
}

\end{warpHTML}
```

34 Copying a file

for HTML output:
```
\begin{warpHTML}
```

`\LWR@copyfile` {⟨*source filename*⟩} {⟨*destination filename*⟩}

Used to copy the `.toc` file to `.sidetoc` to re-print the TOC in the sideTOC navigation pane.

```
\newwrite\LWR@copyoutfile  % open the file to write to
\newread\LWR@copyinfile      % open the file to read from

\newcommand*{\LWR@copyfile}[2]{%
\LWR@traceinfo{LWR@copyfile: copying #1 to #2}

\immediate\openout\LWR@copyoutfile=#2
\openin\LWR@copyinfile=#1
\begingroup\endlinechar=-1
\makeatletter

\LWR@traceinfo{LWR@copyfile: about to loop}

\loop\unless\ifeof\LWR@copyinfile
  \LWR@traceinfo{LWR@copyfile: one line}
  \read\LWR@copyinfile to\LWR@fileline % Read one line and store it into \LWR@fileline
%   \LWR@fileline\par                  % print the content into the pdf
% print the content:
  \immediate\write\LWR@copyoutfile{\unexpanded\expandafter{\LWR@fileline}}%
\repeat
\immediate\closeout\LWR@copyoutfile
\LWR@traceinfo{LWR@copyfile: done}
\endgroup
}
```

```
\end{warpHTML}
```

35 Debugging messages

html comments

To have the HTML output include additional HTML comments, such as which `<div>` is closing, use

```
\booltrue{HTMLDebugComments}
```

debugging information

To have debug information written to the log, use

```
\tracinglwarp
```

for HTML & PRINT:
```
\begin{warpall}
```

Bool `LWR@tracinglwarp` True if tracing is turned on.

```
\newbool{LWR@tracinglwarp}
```

`\tracinglwarp` Turns on the debug tracing messages.

```
\newcommand{\tracinglwarp}{\booltrue{LWR@tracinglwarp}}
```

`\LWR@traceinfo` {⟨*text*⟩} If tracing is turned on, writes the text to the `.log` file.

```
\newcommand{\LWR@traceinfo}[1]{%
\ifbool{LWR@tracinglwarp}%
{%
    \typeout{*** lwarp: #1}%
}%
{}%
}
```

Bool `HTMLDebugComments` Add comments in HTML about closing `<div>`s, sections, etc.
Default: `false`

```
\newbool{HTMLDebugComments}
\boolfalse{HTMLDebugComments}
```

If `\tracinglwarp`, show where preamble hooks occur:

```
\AfterEndPreamble{
\LWR@traceinfo{AfterEndPreamble}
}

\AtBeginDocument{
\LWR@traceinfo{AtBeginDocument}
}
```

```
\end{warpall}
```

36 Defining print and HTML versions of macros and environments

The following refers to defining objects inside lwarp, and is not for the user's document.

Many macros and environments must be provided as both print and HTML versions.

While generating the print version of a document, the original macros as defined by LaTeX and its packages are used as-is.

While generating the HTML version of a document, the original macro or environment is redefined to call a new HTML version or a copy of the original print version. The new HTML versions of macros and environments are used most of the time. Copies of the print versions are used inside a `latexmage` environment, which draws and

remembers an image of the printed output, and also several other places. The copies of the print versions may also be used by the HTML versions, such as when the HTML version merely encloses the print version inside HTML tags.

The general structure for providing print and HTML versions of a macro or environment is as follows:

For a preexisting macro, not defined with xparse: An HTML version is provided with a special name, inside a warpHTML environment, then \LWR@formatted is used to redefine and patch various macros:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may also use xparse

\LWR@formatted{name}
\end{warpHTML}
```

\LWR@formatted{name} copies the original print version, then redefines \name to use either the print or HTML version depending on which mode lwarp is using. xparse may be used to define the new HTML version, even if the original did not use xparse.

For a preexisiting environment, not defined with xparse: The process is similar. Note the use of \LWR@formattedenv instead of \LWR@formatted.

```
\begin{warpHTML}
\newenvironment{LWR@HTML@name}{...}% may also use xparse

\LWR@formattedenv{name}
\end{warpHTML}
```

If the original used xparse: A copy must be made using a new name:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@name}{..}{..}% copy the original

\NewDocumentCommand{\LWR@HTML@name}{..}{..}% or use \newcommand

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment, using \LWR@formattedenv. (\LWR@formatted and \LWR@formattedenv use \LetLtxMacro to copy the original print definiton, which may not work with macros and environments created by xparse, so the print version must be manually recreated in the lwarp source.)

For a new macro or environment, not using xparse for the print version:

```
\begin{warpall}
\newcommand{\name}{...}% NOT xparse!
```

```
\end{warpall}

\begin{warpHTML}
\newcommand{\LWR@HTML@name}{...}% may use xparse for HTML

\LWR@formatted{name}
\end{warpHTML}
```

Similar for an environment. The plain `\name` or environment `name` is used for the printed version, and is placed inside `warpall`. xparse may be used for the `\LWR@HTML@<name>` version.

For a new macro or environment, using xparse: It is possible to use xparse for an entirely new macro or environment by defining the `\LWR@print@<name>` version with xparse, along with `\name` defined without xparse to refer directly to the `\LWR@print` version:

```
\begin{warpall}
\NewDocumentCommand{\LWR@print@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@print@name}{...} {...} {...}

% Simply a call to \LWR@print@name:
\newcommand{\name}{\LWR@print@name}%        -or-
\newenvironment{name}{\LWR@print@name}{\endLWR@print@name}
\end{warpall}

\begin{warpHTML}
\NewDocumentCommand{\LWR@HTML@name}{...} {...}%      -or-
\NewDocumentEnvironment{\LWR@HTML@name}{...} {...} {...}

\LWR@formatted{name}%    -or-
\LWR@formattedenv{name}
\end{warpHTML}
```

In general, `\LWR@formatted` or `\LWR@formattedenv` are placed inside a `warpHTML` environment, and while producing an HTML document they do the following:

- Macros are modified:
  1. The pre-existing print version `\name` is saved as `\LWR@print@<name>`, unless `\LWR@print@<name>` is already defined.
  2. The original `\name` is redefined to call either the print or HTML version depending on which format is in use at the moment, as set by `\LWR@formatting`, which is defined as either "`print`" or "`HTML`".
- When lwarp is producing a print document, the original definitions are used, as well as any new definitions defined in `warpall` above.
- When lwarp is generating HTML output, `\LWR@formatting` is set to "`HTML`", and `\name` is directed to `\LWR@HTML@<name>`.

- When lwarp is generating HTML output but enters a lateximage environment, or for some other reason needs to draw images using the original print definitions, \LWR@formatting is changed to "print" and \name is then redirected to \LWR@print@<name>, which was the original \name.

Since arguments are not handled by the new \name, any star and other arguments are processed by the print or HTML version.

Expandable versions are also provided as well. These usually are necessary for anything which could appear inside a tabular, without which a "Misplaced \omit" error may occur.

⚠ Misplaced \omit error

\LWR@expandableformatted
\LWR@expandableformattedenv

(Older versions of lwarp used \LetLtxMacro for everything, but this could fail when using macros defined by xparse. This older system is still in use for many definitions.)

for HTML output:

```
\begin{warpHTML}
```

\LWR@formatting Remembers if selected print/HTML formatting.

Used while \LWR@restoreorigformatting, such as in an lateximage. May be set to either "print" or "HTML".

```
\newcommand*{\LWR@formatting}{HTML}
```

\LWR@formatted {⟨*macroname*⟩} No backslash in the macro name.

If not yet defined, defines \LWR@print@<name> as the original print-mode \<name>. Also redefines \<name> to use \LWR@<format>@<name>, where <format> is set by \LWR@formatting, and is print or HTML.

```
\newcommand*{\LWR@formatted}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewrobustcmd\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }%
}
```

\LWR@expandableformatted {⟨*macroname*⟩} No backslash in the macro name.

An expandable version of \LWR@formatted.

```
\newcommand*{\LWR@expandableformatted}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
    }{}%
    \ifcsundef{#1}{%
        \expandafter\newcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }{%
        \expandafter\renewcommand\csname #1\endcsname{%
            \@nameuse{LWR@\LWR@formatting @#1}%
        }%
    }%
}
```

\LWR@formattedenv {⟨*environmentname*⟩}

If not yet defined, defines the environment LWR@print@<name> as the original print-mode <name>. Also redefines the environment <name> to use environment LWR@<format>@<name>, where <format> is set by \LWR@formatting, and is print or HTML.

```
\newcommand*{\LWR@formattedenv}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareDocumentEnvironment{#1}{}%
    {%
        \@nameuse{LWR@\LWR@formatting @#1}%
    }%
    {%
        \@nameuse{endLWR@\LWR@formatting @#1}%
    }%
}
```

\LWR@expandableformattedenv {⟨*environmentname*⟩}

An expandable version of LWR@formattedenv.

```
\newcommand*{\LWR@expandableformattedenv}[1]{%
    \ifcsundef{LWR@print@#1}{%
        \expandafter\LetLtxMacro\csname LWR@print@#1\expandafter\endcsname%
            \csname#1\endcsname%
        \csletcs{endLWR@print@#1}{end#1}%
    }{}%
    \DeclareExpandableDocumentEnvironment{#1}{}%
    {%
        \@nameuse{LWR@\LWR@formatting @#1}%
```

```
    }%
    {%
        \@nameuse{endLWR@\LWR@formatting @#1}%
    }%
}
```

```
\end{warpHTML}
```

37 HTML-conversion output modifications

These booleans modify the HTML output in various ways to improve conversion to EPUB or word processor imports.

for HTML & PRINT:

```
\begin{warpall}
```

37.1 User-level controls

Bool FormatEPUB
Default: false

Changes HTML output for easy EPUB conversion via an external program. Removes per-file headers, footers, and nav. Adds footnotes per chapter/section.

```
\newbool{FormatEPUB}
\boolfalse{FormatEPUB}
```

Bool FormatWP
Default: false

Changes HTML output for easier conversion by a word processor. Removes headers and nav, prints footnotes per section, and also forces single-file output and turns off HTML debug comments.

```
\newbool{FormatWP}
\boolfalse{FormatWP}
```

Bool WPMarkFloats
Default: false

Adds

```
=== begin table ===
. . .
=== end ===
```

or

```
=== begin figure ===
. . .
=== end ===
```

around floats while formatting for word processors. This helps identify boundaries of floats to be manually converted to word-processor frames and captions. [17]

```
\newbool{WPMarkFloats}
\boolfalse{WPMarkFloats}
```

[17] Perhaps some day word processors will have html import options for identifying <figure> and caption tags for figures and tables.

Bool WPMarkMinipages
Default: false

Adds

```
=== begin minipage ===
. . .
=== end minipage ===
```

around minipages while formatting for word processors. This helps identify boundaries of minipages to be manually converted to word-processor frames.

```
\newbool{WPMarkMinipages}
\boolfalse{WPMarkMinipages}
```

Bool WPMarkTOC
Default: true

While formatting for word processors, adds

```
=== table of contents ===
```

where the Table of Contents would have been. This helps identify where to insert the actual TOC.

If set `false`*, the actual TOC is printed instead.*

```
\newbool{WPMarkTOC}
\booltrue{WPMarkTOC}
```

Bool WPMarkLOFT
Default: false

While formatting for word processors, adds

```
=== list of figures ===    and/or
=== list of tables ===
```

where each of these lists would have been. This helps identify where to insert the actual lists.

If set `false`*, the actual lists are printed instead.*

```
\newbool{WPMarkLOFT}
\boolfalse{WPMarkLOFT}
```

Bool WPMarkMath
Default: false

While formatting for word processors, prints math as LaTeX code instead of creating SVG images or MathJax. This is useful for cut/paste into the *LibreOffice Writer TeXMaths* extension.

```
\newbool{WPMarkMath}
\boolfalse{WPMarkMath}
```

Bool WPTitleHeading
Default: false

While formatting for word processors, `true` sets the document title to `<h1>`, which is expected for HTML documents, but also causes the lower-level section headings to start at **Heading 2** when imported into LibreOffice. Set to `false` to cause the title to be plain text, and the section headings to begin at **Heading 1**.

See table 8 on page 167.

```
\newbool{WPTitleHeading}
\boolfalse{WPTitleHeading}
```

```
\end{warpall}
```

37.2 Heading adjustments

If formatting the HTML for a word processor, adjust heading levels.

If `WPTitleHeading` is true, adjust so that `part` is **Heading 1**.

If `WPTitleHeading` is false, use `<h1>` for the title, and set `part` to **Heading 2**.

for HTML output:

```
\begin{warpHTML}

\AtBeginDocument{
\ifbool{FormatWP}{
\@ifundefined{chapter}{
\ifbool{WPTitleHeading}{% part and section starting at h2
\renewcommand*{\LWR@tagtitle}{h1}
\renewcommand*{\LWR@tagtitleend}{/h1}
\renewcommand*{\LWR@tagpart}{h2}
\renewcommand*{\LWR@tagpartend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% WPTitleHeading
{% not WPTitleHeading, part and section starting at h1
\renewcommand*{\LWR@tagtitle}{div class="title"}
\renewcommand*{\LWR@tagtitleend}{/div}
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagsection}{h2}
\renewcommand*{\LWR@tagsectionend}{/h2}
\renewcommand*{\LWR@tagsubsection}{h3}
\renewcommand*{\LWR@tagsubsectionend}{/h3}
\renewcommand*{\LWR@tagsubsubsection}{h4}
\renewcommand*{\LWR@tagsubsubsectionend}{/h4}
\renewcommand*{\LWR@tagparagraph}{h5}
\renewcommand*{\LWR@tagparagraphend}{/h5}
\renewcommand*{\LWR@tagsubparagraph}{h6}
\renewcommand*{\LWR@tagsubparagraphend}{/h6}
}% not WPTitleHeading
}% chapter undefined
{% chapter defined
\ifbool{WPTitleHeading}{}
{% not WPTitleHeading, part and chapter starting at h1
\renewcommand*{\LWR@tagtitle}{div class="title"}
\renewcommand*{\LWR@tagtitleend}{/div}
```

```
\renewcommand*{\LWR@tagpart}{h1}
\renewcommand*{\LWR@tagpartend}{/h1}
\renewcommand*{\LWR@tagchapter}{h2}
\renewcommand*{\LWR@tagchapterend}{/h2}
\renewcommand*{\LWR@tagsection}{h3}
\renewcommand*{\LWR@tagsectionend}{/h3}
\renewcommand*{\LWR@tagsubsection}{h4}
\renewcommand*{\LWR@tagsubsectionend}{/h4}
\renewcommand*{\LWR@tagsubsubsection}{h5}
\renewcommand*{\LWR@tagsubsubsectionend}{/h5}
\renewcommand*{\LWR@tagparagraph}{h6}
\renewcommand*{\LWR@tagparagraphend}{/h6}
\renewcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\renewcommand*{\LWR@tagsubparagraphend}{/span}
}% not WPTitleHeading
}% chapter defined
}{}% FormatWP
}% AtBeginDocument

\end{warpHTML}
```

38 Remembering original formatting macros

for HTML output:

```
\begin{warpHTML}
```

Remember original definitions of formatting commands. Will be changed to HTML commands for most uses. Will be temporarily restored to original meaning inside any lateximage environment. Also nullify unused commands.

Some packages redefine \#, which is used to generate HTML, so the original must be remembered here.

```
\chardef\LWR@origpound=`\#

\let\LWR@origcomma\,
\let\LWR@origthinspace\thinspace
\let\LWR@orignegthinspace\negthinspace
\let\LWR@origtilde~
\let\LWR@origenskip\enskip
\let\LWR@origquad\quad
\let\LWR@origqquad\qquad
\let\LWR@orighfil\hfil
\let\LWR@orighss\hss
\let\LWR@origllap\llap
\let\LWR@origrlap\rlap
\let\LWR@orighfilneg\hfilneg
\let\LWR@orighspace\hspace

\let\LWR@origrule\rule

\let\LWR@origmedskip\medskip
\let\LWR@origbigskip\bigskip
```

```
1380
1381 \let\LWR@origtextellipsis\textellipsis
1382 \let\LWR@orig@textquotedbl\textquotedbl
1383
1384 \LetLtxMacro\LWR@origttfamily\ttfamily
1385
1386 \LetLtxMacro\LWR@origem\em
1387 \LetLtxMacro\LWR@orignormalfont\normalfont
1388
1389 \let\LWR@origonecolumn\onecolumn
1390
1391 \let\LWR@origsp\sp
1392 \let\LWR@origsb\sb
1393 \LetLtxMacro\LWR@origtextsuperscript\textsuperscript
1394 \LetLtxMacro\LWR@orig@textsuperscript\@textsuperscript
1395
1396 \AtBeginDocument{
1397 \LetLtxMacro\LWR@origtextsubscript\textsubscript
1398 \LetLtxMacro\LWR@orig@textsubscript\@textsubscript
1399 }
1400
1401 \LetLtxMacro\LWR@origunderline\underline

1402 \let\LWR@orignewpage\newpage
1403
1404 \let\LWR@origpagestyle\pagestyle
1405 \let\LWR@origthispagestyle\thispagestyle
1406 \LetLtxMacro\LWR@origpagenumbering\pagenumbering
1407
1408 \let\LWR@orignewline\newline
1409
1410
1411 \AtBeginDocument{% in case packages change definition
1412 \let\LWR@orig@trivlist\@trivlist
1413 \let\LWR@origtrivlist\trivlist
1414 \let\LWR@origendtrivlist\endtrivlist
1415 \LetLtxMacro\LWR@origitem\item
1416 \LetLtxMacro\LWR@origitemize\itemize
1417 \LetLtxMacro\LWR@endorigitemize\enditemize
1418 \LetLtxMacro\LWR@origenumerate\enumerate
1419 \LetLtxMacro\LWR@endorigenumerate\endenumerate
1420 \LetLtxMacro\LWR@origdescription\description
1421 \LetLtxMacro\LWR@endorigdescription\enddescription
1422 \let\LWR@orig@mklab\@mklab
1423 \let\LWR@origmakelabel\makelabel
1424 \let\LWR@orig@donoparitem\@donoparitem
1425 \LetLtxMacro\LWR@orig@item\@item
1426 \let\LWR@orig@nbitem\@nbitem
1427 }
1428
1429 \let\LWR@origpar\par
1430
1431 \LetLtxMacro\LWR@origfootnote\footnote
1432 \let\LWR@orig@mpfootnotetext\@mpfootnotetext
1433
```

```
\let\LWR@origclearpage\clearpage


\AtBeginDocument{% in case packages change definition
\LetLtxMacro\LWR@orighline\hline%
\LetLtxMacro\LWR@origcline\cline%
}

\end{warpHTML}
```

39 Accents

Native LaTeX accents such as \" will work, but many more kinds of accents are available when using Unicode-aware XeLaTeX and LuaLaTeX.

for HTML output:

```
\begin{warpHTML}
```

Without `\AtBeginDocument`, `\t` was being re-defined somewhere.

```
\AtBeginDocument{
```

The following are restored for print when inside a `lateximage`.

For Unicode engines, only `\t` needs to be redefined:

```
\LetLtxMacro\LWR@origt\t
```

For pdfLaTeX, additional work is required:

```
\ifPDFTeX% pdflatex or dvi latex
\LetLtxMacro\LWR@origequalaccent\=
\LetLtxMacro\LWR@origdotaccent\.
\LetLtxMacro\LWR@origu\u
\LetLtxMacro\LWR@origv\v
\LetLtxMacro\LWR@origc\c
\LetLtxMacro\LWR@origd\d
\LetLtxMacro\LWR@origb\b
```

The HTML redefinitions follow.

For pdfLaTeX, Unicode diacritical marks are used:

```
\renewcommand*{\=}[1]{#1\HTMLunicode{0305}}
\renewcommand*{\.}[1]{#1\HTMLunicode{0307}}
\renewcommand*{\u}[1]{#1\HTMLunicode{0306}}
\renewcommand*{\v}[1]{#1\HTMLunicode{030C}}
\renewcommand*{\c}[1]{#1\HTMLunicode{0327}}
\renewcommand*{\d}[1]{#1\HTMLunicode{0323}}
\renewcommand*{\b}[1]{#1\HTMLunicode{0331}}
\fi
```

For all engines, a Unicode diacritical tie is used:

```
\def\LWR@t#1#2{#1\HTMLunicode{0361}#2}
\renewcommand*{\t}[1]{\LWR@t#1}
```

`\LWR@restoreorigaccents` Called from `\restoreoriginalformatting` when a `lateximage` is begun.

```
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@restoreorigaccents}{%
\LetLtxMacro\=\LWR@origequalaccent%
\LetLtxMacro\.\LWR@origdotaccent%
\LetLtxMacro\u\LWR@origu%
\LetLtxMacro\v\LWR@origu%
\LetLtxMacro\t\LWR@origt%
\LetLtxMacro\c\LWR@origc%
\LetLtxMacro\d\LWR@origd%
\LetLtxMacro\b\LWR@origb%
}%
\else% XeLaTeX, LuaLaTeX:
\newcommand*{\LWR@restoreorigaccents}{%
\LetLtxMacro\t\LWR@origt%
}%
\fi%
}% AtBeginDocument

\end{warpHTML}
```

40 Configuration files

40.1 Decide whether to generate configuration files

Configuration files are only written if processing the print version of the document, and not processing a pstool image. pstool uses an additional compile for each image using the original document's preamble, which includes lwarp, so the lwarp configuration files are turned off if `-pstool` is part of the `\jobname`.

Default to no configuration files:

```
\excludecomment{LWRwriteconf}
```

Generate configuration files if print mode and not `-pstool`:

for PRINT output:

```
\begin{warpprint}
\fullexpandarg%
\IfSubStr*{\jobname}{-pstool}
    {
        \PackageInfo{lwarp}{%
            Jobname with -pstool is found.\MessageBreak
            Not generating lwarp configuration files,%
        }
```

```
    }
    {
        \PackageInfo{lwarp}{Generating lwarp configuration files,}%
        \includecomment{LWRwriteconf}
    }
\end{warpprint}
```

40.2 <project>_html.tex

File *_html.tex Used to allow an HTML version of the document to exist alongside the print version.

Config file:

```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=\jobname_html.tex
\immediate\write\LWR@quickfile{%
\detokenize{\PassOptionsToPackage}%
{warpHTML,BaseJobname=\jobname}{lwarp}%
}
\immediate\write\LWR@quickfile{%
\detokenize{\input}\string{\jobname.tex\string }%
}
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.3 *lwarpmk* configuration files

Config file:

```
\begin{LWRwriteconf}
```

\LWR@lwarpconfversion The version number of the configuration file, allowing *lwarpmk* to detect an obsolete configuration file format. Incremented by one each time the configuration file format changes. (This is NOT the same as the lwarp version number.)

```
\newcommand*{\LWR@lwarpconfversion}{2}% also in lwarpmk.lua
```

40.3.1 Helper macros

\LWR@shellescapecmd The LaTeX compile option for shell escape, if used.

```
\ifshellescape
    \def\LWR@shellescapecmd{--shell-escape }
\else
    \def\LWR@shellescapecmd{}
\fi
```

\LWR@compilecmd {⟨*engine*⟩} {⟨*suffix*⟩}

Used to form the basic compilation command for a document, adding the optional shell escape.

Engine is *pdflatex*, etc. Suffix is empty or `_html`

```
\newcommand*{\LWR@compilecmd}[2]{%
    #1 \LWR@shellescapecmd \jobname#2%
}
```

`\LWR@addcompilecmd` {⟨*cmd*⟩} {⟨*suffix*⟩}

Adds to the compilation command.

Cmd is *dvipdfmx*, etc. Suffix is empty or `_html`

```
\newcommand*{\LWR@addcompilecmd}[2]{%
    \LWRopseq
    #1 \jobname#2%
}
```

`\LWR@unknownengine` Error message if not sure which LaTeX engine is being used.

```
\newcommand*{\LWR@unknownengine}{%
    \PackageError{lwarp}
    {Unknown LaTeX engine.}
   {Lwarp only knows about pdflatex, dvi latex, xelatex, lualatex, and upLateX.}
}
```

`\LWR@latexmkvar` {⟨*varname*⟩} {⟨*value*⟩}

Adds a *latexmk* variable assignment.

```
\newcommand*{\LWR@latexmkvar}[2]{%
    -e
    \LWRopquote%
    \LWRdollar #1=q/#2/%
    \LWRopquote
}
```

`\LWR@latexmkcmd` {⟨*latexmk options*⟩}

Sets a call to *latexmk* with the given options, possibly adding `--shell-escape`, and also adding the indexing program.

```
\newcommand*{\LWR@latexmkcmd}[1]{%
    latexmk  \space \LWR@shellescapecmd \space  #1 \space
    -recorder \space
    \LWR@latexmkvar{makeindex}{\LWR@LatexmkIndexCmd}
}
```

`\LWR@latexmkdvipdfm` {⟨*dvipdfm or dvipdfmx*⟩}

Adds the options settings for *dvipdfm* or *dvipdfmx*.

```
\newcommand*{\LWR@latexmkdvipdfm}[1]{%
```

```
    -pdfdvi \space
    \LWR@latexmkvar{dvipdf}{%
        #1
        \@percentchar O
        -o \@percentchar D
        \@percentchar S%
    }
}
```

\LWR@compileuplatex Sets compile options for upLaTeX with ujarticle or related classes.

```
\newcommand*{\LWR@compileuplatex}{
    \def\LWR@tempprintlatexcmd{%
        \LWR@compilecmd{uplatex}{}
        \LWR@addcompilecmd{dvipdfmx}{}
    }
    \def\LWR@tempHTMLlatexcmd{%
        \LWR@compilecmd{uplatex}{_html}
        \LWR@addcompilecmd{dvipdfmx}{_html}
    }
}
```

\LWR@PrintLatexCmd
\LWR@HTMLLatexCmd

If not set by the user, the following sets the command to use to compile the source to PDF form.

If using *latexmk*, a complicated string is created, eventually resulting in something such as:

For *xelatex* with `--shell-escape`:

```
[[latexmk   -xelatex   --shell-escape  -recorder
    -e '$makeindex = q/makeindex -s lwarp.ist/'  <jobname>_html]]
```

For *dvipdfmx*:

```
[[latexmk   -pdfdvi  -e '$dvipdf=q/dvipdfmx %O -o %D %S/'
    -recorder
    -e '$makeindex=q/makeindex -s lwarp.ist/'   <jobname>_html]]
```

For the following, temporary values are computed, but the permanent values are only set if the originals were not assigned by the user.

```
\ifbool{LWR@latexmk}{
```

For *latexmk* with *pdflatex* or *lualatex*:

```
    \ifpdf
```

For *latexmk* with *pdflatex*:

```
        \ifPDFTeX
            \def\LWR@latexcmd{\LWR@latexmkcmd{-pdf -dvi- -ps-}}
        \else
```

For *latexmk* with *lualatex*:

```
            \ifLuaTeX
                \def\LWR@latexcmd{\LWR@latexmkcmd{-lualatex}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For *latexmk* with *xelatex* or DVI *latex*:

```
        \ifXeTeX
```

For *latexmk* with *xelatex*:

```
            \def\LWR@latexcmd{\LWR@latexmkcmd{-xelatex}}
        \else% \ifXeTeX
```

For *latexmk* with DVI *latex*:

```
            \ifbool{LWR@dvipdfm}{
                \def\LWR@latexcmd{%
                    \LWR@latexmkcmd{%
                        \LWR@latexmkdvipdfm{dvipdfm}%
                    }
                }
            }{
                \ifbool{LWR@dvipdfmx}{
                    \def\LWR@latexcmd{%
                        \LWR@latexmkcmd{%
                            \LWR@latexmkdvipdfm{dvipdfmx}%
                        }
                    }
                }{
                    \def\LWR@latexcmd{\LWR@latexmkcmd{-pdfps}}
                }
            }
        \fi
    \fi% \ifpdf
```

The final assignment if *latexmk*:

```
    \def\LWR@tempprintlatexcmd{\LWR@latexcmd \space \jobname}
    \def\LWR@tempHTMLlatexcmd{\LWR@latexcmd \space \jobname_html}
}% latexmk
```

Without *latexmk*, the compiling command is simply the compiler name and the optional shell escape:

```
{% not latexmk
    \ifpdf
```

For *pdflatex* or *lualatex*:

```
        \ifPDFTeX
```

For *pdflatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{pdflatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{pdflatex}{_html}}
        \else
            \ifLuaTeX
```

For *lualatex*:

```
                \def\LWR@tempprintlatexcmd{\LWR@compilecmd{lualatex}{}}
                \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{lualatex}{_html}}
            \else
                \LWR@unknownengine
            \fi
        \fi
    \else% \ifpdf
```

For DVI *latex* or *xelatex*:

```
        \ifXeTeX
```

For *xelatex*:

```
            \def\LWR@tempprintlatexcmd{\LWR@compilecmd{xelatex}{}}
            \def\LWR@tempHTMLlatexcmd{\LWR@compilecmd{xelatex}{_html}}
        \else
```

For DVI *latex*. Default to *dvips*, unless told to use *dvipdfm* or *dvipdfmx*:

```
            \ifbool{LWR@dvipdfm}{
```

For DVI *latex* with *dvipdfm*:

```
                \def\LWR@tempprintlatexcmd{%
                    \LWR@compilecmd{latex}{}
                    \LWR@addcompilecmd{dvipdfm}{}
                }
                \def\LWR@tempHTMLlatexcmd{%
                    \LWR@compilecmd{latex}{_html}
                    \LWR@addcompilecmd{dvipdfm}{_html}
                }
            }{
                \ifbool{LWR@dvipdfmx}{
```

For DVI *latex* with *dvipdfmx*:

```
                    \def\LWR@tempprintlatexcmd{%
                        \LWR@compilecmd{latex}{}
                        \LWR@addcompilecmd{dvipdfmx}{}
                    }
                    \def\LWR@tempHTMLlatexcmd{%
                        \LWR@compilecmd{latex}{_html}
                        \LWR@addcompilecmd{dvipdfmx}{_html}
                    }
                }{% dvips
```

For DVI *latex* with *dvips* and *ps2pdf*:

```
                    \def\LWR@tempprintlatexcmd{%
                        \LWR@compilecmd{latex}{}
                        \LWR@addcompilecmd{dvips}{}
                        \LWR@addcompilecmd{ps2pdf}{}.ps
                    }
                    \def\LWR@tempHTMLlatexcmd{%
                        \LWR@compilecmd{latex}{_html}
                        \LWR@addcompilecmd{dvips}{_html}
                        \LWR@addcompilecmd{ps2pdf}{_html}.ps
                    }
                }
            }
        \fi% \ifXeTeX
    \fi% \ifpdf
}% latexmk
```

For ujarticle, utarticle, and related, using upLaTeX and *dvipdfmx*:

```
\@ifclassloaded{ujarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{ujbook}{\LWR@compileuplatex}{}
\@ifclassloaded{ujreport}{\LWR@compileuplatex}{}
\@ifclassloaded{utarticle}{\LWR@compileuplatex}{}
\@ifclassloaded{utbook}{\LWR@compileuplatex}{}
\@ifclassloaded{utreport}{\LWR@compileuplatex}{}
```

Only make the setting permanent if the original was empty:

```
\ifdefempty{\LWR@PrintLatexCmd}{
    \def\LWR@PrintLatexCmd{\LWR@tempprintlatexcmd}
}{}
\ifdefempty{\LWR@HTMLLatexCmd}{
    \def\LWR@HTMLLatexCmd{\LWR@tempHTMLlatexcmd}
}{}
```

`\LWR@writeconf` {⟨*filename*⟩}

Common code for each of `lwarpmk.conf` and `<project>.lwarpmkconf`. Each entry is a variable name, the equal sign, and a quoted string inside `[[` and `]]`, which are *lua*'s long quote characters, allowing the use of single and double quotes inside.

```
\newcommand{\LWR@writeconf}[1]{
\ifcsdef{LWR@quickfile}{}{\newwrite{\LWR@quickfile}}
\immediate\openout\LWR@quickfile=#1
\immediate\write\LWR@quickfile{confversion = [[\LWR@lwarpconfversion]]}
\ifbool{usingOSWindows}{
    \immediate\write\LWR@quickfile{opsystem = [[Windows]]}
}{
    \immediate\write\LWR@quickfile{opsystem = [[Unix]]}
}
\immediate\write\LWR@quickfile{sourcename = [[\jobname]]}
\immediate\write\LWR@quickfile{homehtmlfilename = [[\HomeHTMLFilename]]}
\immediate\write\LWR@quickfile{htmlfilename = [[\HTMLFilename]]}
\immediate\write\LWR@quickfile{imagesdirectory = [[\LWR@ImagesDirectory]]}
\immediate\write\LWR@quickfile{imagesname = [[\LWR@ImagesName]]}
\immediate\write\LWR@quickfile{latexmk = [[\ifbool{LWR@latexmk}{true}{false}]]}
\immediate\write\LWR@quickfile{printlatexcmd = [[\LWR@PrintLatexCmd]]}
\immediate\write\LWR@quickfile{HTMLlatexcmd = [[\LWR@HTMLLatexCmd]]}
\immediate\write\LWR@quickfile{printindexcmd = [[\LWR@PrintIndexCmd]]}
\immediate\write\LWR@quickfile{HTMLindexcmd = [[\LWR@HTMLIndexCmd]]}
\immediate\write\LWR@quickfile{latexmkindexcmd = [[\LWR@LatexmkIndexCmd]]}
\immediate\write\LWR@quickfile{glossarycmd = [[\LWR@GlossaryCmd]]}
\immediate\write\LWR@quickfile{pdftotextenc = [[\LWR@pdftotextEnc]]}
\immediate\closeout\LWR@quickfile
}


\end{LWRwriteconf}
```

40.3.2 lwarpmk.conf

File lwarpmk.conf

lwarpmk.conf is automatically (re-)created by the lwarp package when executing
pdflatex <project.tex>,
or similar for *xelatex* or *lualatex*, in print-document generation mode, which is the default unless the warpHTML option is given. lwarpmk.conf is then used by the utility *lwarpmk*.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{lwarpmk.conf}}

\end{LWRwriteconf}
```

40.3.3 <project>.lwarpmkconf

File project.lwarpmkconf

A project-specific configuration file for *lwarpmk*.

The makeindex and xindy options have already been handled for lwarp.conf.

Config file:

```
\begin{LWRwriteconf}

\AtBeginDocument{\LWR@writeconf{\jobname.lwarpmkconf}}

```

```
\end{LWRwriteconf}
```

40.4 lwarp.css

File lwarp.css This is the base CSS layer used by lwarp.

This must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.css}
/*
  CSS stylesheet for the LaTeX lwarp package
  Copyright 2016-2019 Brian Dunn — BD Tech Concepts LLC
*/


/* a fix for older browsers: */
header, section, footer, aside, nav, main,
    article, figure { display: block; }


A:link {color:#000080 ; text-decoration: none ; }
A:visited {color:#800000 ; }
A:hover {color:#000080 ; text-decoration: underline ;}
A:active {color:#800000 ; }

a.tocpart {display: inline-block ; margin-left: 0em ;
    font-weight: bold ;}
a.tocchapter {display: inline-block ; margin-left: 0em ;
    font-weight: bold ;}
a.tocsection {display: inline-block ; margin-left: 1em ;
    text-indent: -.5em ; font-weight: bold ; }
a.tocsubsection {display: inline-block ; margin-left: 2em ;
    text-indent: -.5em ; }
a.tocsubsubsection {display: inline-block ; margin-left: 3em ;
    text-indent: -.5em ; }
a.tocparagraph {display: inline-block ; margin-left: 4em ;
    text-indent: -.5em ; }
a.tocsubparagraph {display: inline-block ; margin-left: 5em ;
    text-indent: -.5em ; }
a.tocfigure {margin-left: 0em}
a.tocsubfigure {margin-left: 2em}
a.toctable {margin-left: 0em}
a.tocsubtable {margin-left: 2em}
a.toctheorem {margin-left: 0em}
a.toclstlisting {margin-left: 0em}

body {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
        "Lucida Bright", Georgia, serif;
    background: #FAF7F4 ;
    color: black ;
    margin:0em ;
```

```
    padding:0em ;
    font-size: 100% ;
    line-height: 1.2 ;
}

p {margin: 1.5ex 0em 1.5ex 0em ;}
table p {margin: .5ex 0em .5ex 0em ;}

/* Holds a section number */
span.sectionnumber { margin-right: 0em }

/* Inserted in front of index lines */
span.indexitem {margin-left: 0em}
span.indexsubitem {margin-left: 2em}
span.indexsubsubitem {margin-left: 4em}

div.hidden, span.hidden { display: none ; }

kbd, span.texttt {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
    font-size: 100% ;
}

pre { padding: 3pt ; }

span.strong, span.textbf, div.strong, div.textbf { font-weight: bold; }

span.textit, div.textit { font-style: italic; }

span.textmd, div.textmd { font-weight: normal; }

span.texteb { font-weight: bolder; }

span.textlg { font-weight: lighter; }

span.textsc, div.textsc {
    font-variant: small-caps;
    font-variant-numeric: oldstyle-nums ;
}

span.textulc, div.textulc {
    font-variant: normal ;
    font-variant-numeric: normal ;
}

span.textsl, div.textsl { font-style: oblique; }

span.textup, div.textup {
    font-style: normal;
    font-variant: normal;
    font-variant-numeric: normal ;
}

```

```
span.textrm, div.textrm {
    font-family: "DejaVu Serif", "Bitstream Vera Serif",
    "Lucida Bright", Georgia, serif;
}

span.textsf, div.textsf {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
}

span.textcircled { border: 1px solid black ; border-radius: 1ex ; }

span.underline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
}

span.overline {
    text-decoration: overline ;
    text-decoration-skip: auto ;
}


/* for vertical text: */
div.verticalrl { writing-mode: vertical-rl }
div.horizontaltb { writing-mode: horizontal-tb }


/* for diagbox */
div.diagboxtitleN { border-bottom: 1px solid gray }
div.diagboxtitleS { border-top: 1px solid gray }

div.diagboxE {
    padding-left: 2em ;
    text-align: right ;
}

div.diagboxW {
    padding-right: 2em ;
    text-align: left ;
}



/* For realscripts */
.supsubscript {
    display: inline-block;
    text-align:left ;
}

.supsubscript sup,
.supsubscript sub {
    position: relative;
    display: block;
    font-size: .5em;
```

```
    line-height: 1;
}

.supsubscript sup {
    top: .5em;
}

.supsubscript sub {
    top: .5em;
}

div.attribution p {
    text-align: right ;
    font-size: 80%
}

span.poemtitle {
  font-size: 120% ; font-weight: bold;
}

pre.tabbing {
    font-family: "Linux Libertine Mono O", "Lucida Console",
        "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
        "Liberation Mono", "FreeMono", "Andale Mono",
        "Nimbus Mono L", "Courier New", monospace;
}

blockquote {
    display: block ;
    margin-left: 2em ;
    margin-right: 2em ;
}

/* quotchap is for the quotchap package */
div.quotchap {
    display: block ;
    font-style: oblique ;
    overflow-x: auto ;
    margin-left: 2em ;
    margin-right: 2em ;
}

blockquote p, div.quotchap p {
    line-height: 1.5;
    text-align: left ;
    font-size: .85em ;
}

/* qauthor is for the quotchap package */
div.qauthor {
  display: block ;
  text-align: right ;
  margin-left: auto ;
  margin-right: 2em ;
  font-size: 80% ;
```

```
  font-variant: small-caps;
}

div.qauthor p {
  text-align: right ;
}

div.epigraph, div.dictum {
  line-height: 1.2;
    text-align: left ;
    padding: 3ex 1em 0ex 1em ;
/*     margin: 3ex auto 3ex auto ; */ /* Epigraph centered */
    margin: 3ex 1em 3ex auto ; /* Epigraph to the right */
/*    margin: 3ex 1em 3ex 1em ; */ /* Epigraph to the left */
    font-size: .85em ;
    max-width: 27em ;
}

div.epigraphsource, div.dictumauthor {
    text-align:right ;
    margin-left:auto ;
/*     max-width: 50% ; */
    border-top: 1px solid #A0A0A0 ;
    padding-bottom: 3ex ;
    line-height: 1.2;
}

div.epigraph p, div.dictum p { padding: .5ex ; margin: 0ex ;}
div.epigraphsource p, div.dictumauthor p { padding: .5ex 0ex 0ex 0ex ; margin: 0ex ;}
div.dictumauthor { font-style:italic }


/* copyrightbox package */
div.copyrightbox { margin: .5ex .5em }
div.copyrightbox p {margin: 0px .5em ; padding: 0px}
div.copyrightboxnote {text-align: left ; font-size: 60%}


/* lettrine package: */
span.lettrine { font-size: 4ex ; float: left ; }
span.lettrinetext { font-variant: small-caps ; }

/* ulem, soul, umoline packages: */
span.uline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
}

span.uuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: double ;
}

span.uwave {
```

```
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: wavy ;
}

span.sout {
    text-decoration: line-through ;
}

span.oline {
    text-decoration: overline ;
    text-decoration-skip: auto ;
}

span.xout {
    text-decoration: line-through ;
}

span.dashuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: dashed ;
}

span.dotuline {
    text-decoration: underline ;
    text-decoration-skip: auto ;
    text-decoration-style: dotted ;
}

span.letterspacing { letter-spacing: .2ex ; }

span.capsspacing {
    font-variant: small-caps ;
    letter-spacing: .1ex ;
}

span.highlight { background: #F8E800 ; }




html body {
  margin: 0 ;
  line-height: 1.2;
}


body div {
  margin: 0ex;
}


h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
```

```
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {    /* title of the entire website, used on each page */
    text-align: center ;
    font-size: 2.5em ;
    padding: .4ex 0em 0ex 0em ;
}
h2 { font-size: 2.25em }
h3 { font-size: 2em }
h4 { font-size: 1.75em }
h5 { font-size: 1.5em }
h6 { font-size: 1.25em }
span.paragraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ; }
span.subparagraph {font-size: 1em ; font-variant: normal ;
    margin-right: 1em ;  }

div.minisec {
    font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    font-style: normal ;
    font-weight: bold ;
    text-align: left ;
}

h1 {
  margin: 0ex 0em 0ex 0em ;
  line-height: 1.3;
  text-align: center ;
}

h2 {
  margin: 1ex 0em 1ex 0em ;
  line-height: 1.3;
  text-align: center ;
}

h3 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h4 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h5 {
```

```
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}

h6 {
  margin: 3ex 0em 1ex 0em ;
  line-height: 1.3;
}


div.titlepage {
  text-align: center ;
}

.footnotes {
    text-align: left ;
    font-size: .85em ;
    margin: 3ex 2em 0ex 2em ;
    border-top: 1px solid silver ;
}

.marginpar, .marginparblock {
    max-width: 50%;
    float: right ;
    clear: both ;
    text-align: left ;
    margin: 1ex 0.5em 1ex 1em ;
    padding: 1ex 0.5em 1ex 0.5em ;
    font-size: 85% ;
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
    overflow-x: auto ;
}

.marginpar br { margin-bottom: 2ex ; }

div.marginblock, div.marginparblock {
    max-width:50%;
    min-width: 10em; /* room for caption */
    float:right;
    text-align:left;
    margin: 1ex 0.5em 1ex 1em ;
    padding: 1ex 0.5em 1ex 0.5em ;
    overflow-x: auto;
}

div.marginblock div.minipage,
div.marginparblock div.minipage {
    display: block ;
    margin: 0pt auto 0pt auto ;
}

div.marginblock div.minipage p ,
div.marginparblock div.minipage p
    { font-size: 85%}
```

```
2124
2125 div.marginblock br ,
2126 div.marginparblock br
2127     { margin-bottom: 2ex ; }
2128
2129 div.bodycontainer {
2130     float: left ;
2131     width: 80% ;
2132 }
2133
2134 div.bodywithoutsidetoc div.bodycontainer {
2135     float: none ;
2136     width: 100% ;
2137 }
2138
2139 section.textbody div.footnotes{
2140     margin: 3ex 2em 0ex 2em ;
2141     border-bottom: 2px solid silver ;
2142 }
2143
2144 .footnoteheader {
2145     border-top: 2px solid silver ;
2146     margin-top: 3ex ;
2147     padding-top: 1ex ;
2148     font-weight: bold ;
2149 }
2150
2151 .mpfootnotes {
2152     text-align: left ;
2153     font-size: .85em ;
2154     margin-left: 1em ;
2155     border-top: 1px solid silver ;
2156 }
2157
2158 /* Remove footnote top border in the title page. */
2159 div.titlepage div.mpfootnotes {
2160     border-top: none ;
2161 }
2162
2163
2164
2165 ul, ol {
2166   margin: 1ex 1em 1ex 0em;
2167   line-height: 1.2;
2168 }
2169
2170 body dir, body menu {
2171   margin: 3ex 1em 3ex 0em;
2172   line-height: 1.2;
2173 }
2174
2175 li { margin: 0ex 0em 1ex 0em; }
2176
2177 html {
2178   margin: 0;
```

```
  padding: 0;
}

.programlisting {
  font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
  margin: 1ex 0ex 1ex 0ex ;
  padding: .5ex 0pt .5ex 0pt ;
  overflow-x: auto;
}

section.textbody>pre.programlisting {
border-top: 1px solid silver ;
border-bottom: 1px solid silver ;
}


div.displaymath {
    text-align: center ;
}

div.displaymathnumbered {
    text-align: right ;
    margin-left: 5% ;
    margin-right: 5% ;
    min-width: 2.5in ;
}

@media all and (min-width: 400px) {
    div.displaymathnumbered {
        margin-left: 10% ;
        margin-right: 10% ;
    }
}

@media all and (min-width: 800px) {
    div.displaymathnumbered {
        margin-right: 20% ;
    }
}

@media all and (min-width: 1200px) {
    div.displaymathnumbered {
        margin-right: 30% ;
    }
}


.inlineprogramlisting {
  font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
  overflow-x: auto;
}
```

```
2234
2235 span.listinglabel {
2236     display: inline-block ;
2237     font-size: 70% ;
2238     width: 4em ;
2239     text-align: right ;
2240     margin-right: 2em ;
2241 }
2242
2243 div.abstract {
2244   margin: 2em 5% 2em 5% ;
2245   padding: 1ex 1em 1ex 1em ;
2246 /*  font-weight: bold ; */
2247   font-size: 90% ;
2248     text-align: left ;
2249 }
2250
2251 div.abstract dl {line-height:1.5;}
2252 div.abstract dt {color:#304070;}
2253
2254 div.abstracttitle{
2255     font-family: "URW Classico", Optima, "Linux Biolinum O",
2256         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2257         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2258     font-weight:bold;
2259     font-size:1.25em;
2260     text-align: center ;
2261 }
2262
2263 span.abstractrunintitle{
2264     font-family: "URW Classico", Optima, "Linux Biolinum O",
2265         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
2266         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
2267     font-weight:bold;
2268 }
2269
2270
2271 .verbatim {
2272     overflow-x: auto ;
2273 }
2274
2275 .alltt {
2276     overflow-x: auto ;
2277 }
2278
2279
2280 .bverbatim {
2281     margin: 1ex 0pt 1ex 0pt ;
2282     padding: .5ex 0pt .5ex 0pt ;
2283     overflow-x: auto ;
2284 }
2285
2286 .lverbatim {
2287     margin: 1ex 0pt 1ex 0pt ;
2288     padding: .5ex 0pt .5ex 0pt ;
```

```
    overflow-x: auto ;
}

.fancyvrb {
    font-size:.85em ;
    margin: 3ex 0pt 3ex 0pt
}

.fancyvrblabel {
    font-weight:bold;
    text-align: center ;
}


.verse {
    font-family: "Linux Libertine Mono O", "Lucida Console",
        "Droid Sans Mono", "DejaVu Mono", "Bitstream Vera Mono",
        "Liberation Mono", "FreeMono", "Andale Mono",
        "Nimbus Mono L", "Courier New", monospace;
    margin-left: 1em ;
}


div.singlespace { line-height: 1.2 ; }
div.onehalfspace { line-height: 1.5 ; }
div.doublespace { line-height: 2 ; }


/* Word processor format output: */
div.wpfigure { border: 1px solid red ; margin: .5ex ; padding: .5ex ; }
div.wptable { border: 1px solid blue ; margin: .5ex ; padding: .5ex ; }
div.wpminipage { border: 1px solid green ; margin: .5ex ; padding: .5ex ;}



/* Minipage environments, vertically aligned to top, center, bottom: */
.minipage, .fminipage, .fcolorminipage {
    /* display: inline-block ; */
        /* Mini pages which follow each other will be tiled. */
    margin: .25em .25em .25em .25em;
    padding: .25em .25em .25em .25em;
    display: inline-flex;
    flex-direction: column ;
    overflow: auto;
}

.inlineminipage {
    display: inline-block ;
    text-align: left
}

/* Paragraphs in the flexbox did not collapse their margins. */
/* Have not yet researched this. */
.minipage p {margin: .75ex 0em .75ex 0em ;}
```

```
2344
2345 .fboxBlock .minipage, .colorbox .minipage, .colorboxBlock .minipage,
2346 .fcolorbox .minipage, .fcolorboxBlock .minipage
2347     {border: none ; background: none;}
2348
2349 .fbox, .fboxBlock { border: 1px solid black ; }
2350
2351 .fbox, .fboxBlock, .fcolorbox, .fcolorboxBlock, .colorbox, .colorboxBlock,
2352 .fminipage, .fcolorminipage
2353     {display: inline-block}
2354
2355 .shadowbox, .shabox {
2356    border: 1px solid black;
2357     box-shadow: 3px 3px 3px #808080 ;
2358      border-radius: 0px ;
2359     padding: .4ex .3em .4ex .3em ;
2360     margin: 0pt .3ex 0pt .3ex ;
2361   display: inline-block ;
2362 }
2363
2364 .doublebox {
2365    border: 3px double black;
2366      border-radius: 0px ;
2367     padding: .4ex .3em .4ex .3em ;
2368     margin: 0pt .3ex 0pt .3ex ;
2369   display: inline-block ;
2370 }
2371
2372 .ovalbox, .Ovalbox {
2373    border: 1px solid black;
2374      border-radius: 1ex ;
2375     padding: .4ex .3em .4ex .3em ;
2376     margin: 0pt .3ex 0pt .3ex ;
2377   display: inline-block ;
2378 }
2379
2380 .Ovalbox { border-width: 2px ; }
2381
2382 .framebox {
2383    border: 1px solid black;
2384      border-radius: 0px ;
2385     padding: .3ex .2em 0ex .2em ;
2386     margin: 0pt .1ex 0pt .1ex ;
2387   display: inline-block ;
2388 }
2389
2390
2391 .mdframed {
2392     padding: 0ex ;
2393     margin: 2ex 0em 2ex 0em ;
2394 }
2395
2396 .mdframed p { padding: 0ex .5em 0ex .5em ; }
2397
2398 .mdframed dl { padding: 1ex .5em 0ex .5em ; }
```

```
2399
2400 .mdframedtitle {
2401     padding: .5ex 0pt 0pt 0pt ;
2402     border-radius: 10pt 10pt 0pt 0pt ;
2403     display: block ;
2404     margin-bottom: 1ex ;
2405 }
2406
2407 .mdframedsubtitle {
2408     display: block ;
2409 }
2410
2411 .mdframedsubsubtitle {
2412     display: block ;
2413 }
2414
2415 .mdtheorem {
2416     padding: 0ex .5em 0ex .5em ;
2417     margin: 3ex 5% 3ex 5% ;
2418 }
2419
2420
2421 /* framed package */
2422 .framed, pre.boxedverbatim, fcolorbox {
2423     margin: 3ex 0em 3ex 0em ;
2424    border: 1px solid black;
2425      border-radius: 0px ;
2426     padding: .3ex 1em 0ex 1em ;
2427   display: block ;
2428 }
2429
2430 .shaded {
2431     margin: 3ex 0em 3ex 0em ;
2432     padding: .3ex 1em .3ex 1em ;
2433     display: block ;
2434 }
2435
2436 .snugframed {
2437     margin: 3ex 0em 3ex 0em ;
2438    border: 1px solid black;
2439      border-radius: 0px ;
2440   display: block ;
2441 }
2442
2443 .framedleftbar {
2444     margin: 3ex 0em 3ex 0em ;
2445    border-left: 3pt solid black;
2446      border-radius: 0px ;
2447     padding: .3ex .2em .3ex 1em ;
2448   display: block ;
2449 }
2450
2451 .framedtitle {
2452     margin: 0em ;
2453     padding: 0em ;
```

```
    font-size: 130%
}

.framedtitle p { padding: .3em }


/* For the niceframe package: */

div.niceframe, div.curlyframe, div.artdecoframe, div.generalframe {
    padding: 1ex ;
    margin: 2ex auto ;
    border-radius: 2ex ;
}

div.niceframe {
    border: 6px groove black ;
}

div.curlyframe {
    border-left: 3px dotted black ;
    border-right: 3px dotted black ;
    border-radius: 6ex ;
}

div.artdecoframe {
    border-left: 10px double black ;
    border-right: 10px double black ;
    border-radius: 6ex ;
}

div.generalframe {
    border: 6px groove black ;
}



dl {
  margin: 1ex 2em 1ex 0em;
  line-height: 1.3;
}

dl dt {
    display: block ;
    float:left ;
    font-weight: bold;
    padding-right: 1em ;
}

dl dd { display: block ; }

dl dd:after { content: "" ; display: block ; clear: both }

dl dd p { margin-top: 0em; }

dd ul, dd ol, dd dl { clear: both ; padding-top: 1ex }
```

```
2509
2510
2511 nav {
2512     font-family: "URW Classico", Optima, "Linux Biolinum O",
2513         "DejaVu Sans", "Bitstream Vera Sans",
2514         Geneva, Verdana, sans-serif ;
2515     margin-bottom: 4ex ;
2516 }
2517
2518 nav p {
2519     line-height: 1.2 ;
2520     margin-top:.5ex ;
2521     margin-bottom:.5ex;
2522     font-size: .9em ;
2523 }
2524
2525
2526
2527 img, img.hyperimage, img.borderimage {
2528     max-width: 600px;
2529     border: 1px solid silver;
2530     box-shadow: 3px 3px 3px #808080 ;
2531     padding: .5% ;
2532     margin: .5% ;
2533     background: none ;
2534 }
2535
2536 img.inlineimage{
2537     padding: 0px ;
2538     box-shadow: none ;
2539     border: none ;
2540     background: none ;
2541     margin: 0px ;
2542     display: inline-block ;
2543     border-radius: 0px ;
2544 }
2545
2546 img.logoimage{
2547     max-width: 300px ;
2548     box-shadow: 3px 3px 3px #808080 ;
2549     border: 1px solid black ;
2550     background:none ;
2551     padding:0 ;
2552     margin:.5ex ;
2553     border-radius: 10px ;
2554 }
2555
2556
2557 .section {
2558 /*
2559     To have each section float relative to each other:
2560 */
2561 /*
2562     display: block ;
2563     float: left ;
```

```
2564     position: relative ;
2565     background: white ;
2566     border: 1px solid silver ;
2567     padding: .5em ;
2568 */
2569     margin: 0ex .5em 0ex .5em ;
2570     padding: 0 ;
2571 }
2572
2573
2574 figure {
2575     margin: 5ex auto 5ex auto ;
2576     padding: 1ex 1em 1ex 1em ;
2577     overflow-x: auto ;
2578 }
2579
2580
2581 /* To automatically center images in figures: */
2582 /*
2583 figure img.inlineimage {
2584     margin: 0ex auto 0ex auto ;
2585     display: block ;
2586 }
2587 */
2588
2589 /* To automatically center minipages in figures: */
2590 /*
2591 figure div.minipage, figure div.minipage div.minipage {
2592     margin: 1ex auto 1ex auto ;
2593     display: block ;
2594 }
2595 */
2596
2597 figure figure { margin: 0pt }
2598
2599 figure div.minipage p { font-size: 85% ; }
2600
2601 figure.subfigure, figure.subtable  {
2602     display: inline-block ; margin: 3ex 1em 3ex 1em ;
2603 }
2604
2605 div.figurecaption .minipage { margin:0 ; padding: 0 }
2606
2607 div.minipage figure { border: none ; box-shadow: none ; }
2608 div.minipage figure.table { margin: 0ex }
2609 div.minipage div.footnotes { margin: 1ex 2em 0ex 2em }
2610
2611 div.floatrow { text-align: center; }
2612
2613 div.floatrow figure { display: inline-block ; margin: 1ex 2% ; }
2614
2615 div.floatfoot { font-size: .85em ;
2616     border-top: 1px solid silver ; line-height: 1.2 ; }
2617
2618 div.figurecaption , .lstlistingtitle {
```

```
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
    margin-top: 1ex ;
    margin-bottom: 1ex ;
}

figure.subfigure div.figurecaption, figure.subtable div.figurecaption  {
    border-bottom: none ; background: none ;
}

div.nonfloatcaption {
    margin: 1ex auto 1ex auto ;
    font-size: .85em ;
    text-align: center ;
    font-weight: bold ;
}

/* For a \RawCaption inside a minipage inside a figure's floatrow: */
figure div.floatrow div.minipage div.figurecaption {
    border: none ;
    background: none ;
}


/* For packages such as float, rotfloat, and algorithm2e: */

figure.boxed, figure.boxruled {
    border: 1px solid black ;
}

figure.ruled {
    border-top: 1px solid black ;
    border-bottom: 1px solid black ;
    border-left: 0px ;
    border-right: 0px ;
    border-radius: 0px ;
    background: none ;
    box-shadow: none ;
}

figure.ruled div.figurecaption, figure.boxruled div.figurecaption {
    border-top: 1px solid silver ;
    border-bottom: 1px solid silver ;
}


table {
    margin: 1ex auto 1ex auto ;
    border-collapse: separate ;
    border-spacing: 0px ;
    line-height: 1.3 ;
    }

tr.hline td {border-top: 1px solid #808080 ; margin-top: 0ex ;
```

```
    margin-bottom: 0ex ; } /* for \hline */

tr.tbrule td {border-top: 1px solid black ; margin-top: 0ex ;
    margin-bottom: 0ex ; } /* for \toprule, \bottomrule */

td {padding: .5ex .5em .5ex .5em ;}

table td.tdl { text-align: left ; vertical-align: middle ; }
table td.tdc { text-align: center ; vertical-align: middle ; }
table td.tdat { text-align: center ; vertical-align: middle ; padding: 0px ; margin: 0px ; }
table td.tdbang { text-align: center ; vertical-align: middle ; }
table td.tdr { text-align: right ; vertical-align: middle ; }
table td.tdp { text-align: left ; vertical-align: bottom ; }
table td.tdm { text-align: left ; vertical-align: middle ; }
table td.tdb { text-align: left ; vertical-align: top ; }
table td.tdP { text-align: center ; vertical-align: bottom ; }
table td.tdM { text-align: center ; vertical-align: middle ; }
table td.tdB { text-align: center ; vertical-align: top ; }

table td.tvertbarl { border-left: 1px solid black }
table td.tvertbarldouble { border-left: 4px double black }
table td.tvertbarr { border-right: 1px solid black }
table td.tvertbarrdouble { border-right: 4px double black }

table td.tvertbarldash { border-left: 1px dashed black }
table td.tvertbarldoubledash { border-left: 2px dashed black }
table td.tvertbarrdash { border-right: 1px dashed black }
table td.tvertbarrdoubledash { border-right: 2px dashed black }


/* for cmidrules: */
table td.tdrule {
    border-top: 1px solid #A0A0A0 ;
}

table td.tdrulel {
    border-top-left-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}

table td.tdruler {
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}

table td.tdrulelr {
    border-top-left-radius:.5em ;
    border-top-right-radius:.5em ;
    border-top: 1px solid #A0A0A0 ;
}


/* Margins of paragraphs inside table cells: */
td.tdp p , td.tdprule p , td.tdP p , td.tdPrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }
```

```
td.tdm p , td.tmbrule p , td.tdM p , td.tdMrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }
td.tdb p , td.tdbrule p , td.tdB p , td.tdBrule p { padding-top: 1ex ;
    padding-bottom: 1ex ; margin: 0ex ; }

td.tdp , td.tdprule , td.tdP , td.tdPrule
    { padding: 0ex .5em 0ex .5em ; }
td.tdm , td.tdmrule , td.tdM , td.tdMrule
    { padding: 0ex .5em 0ex .5em ; }
td.tdb , td.tdbrule , td.tdB , td.tdBrule
    { padding: 0ex .5em 0ex .5em ; }


/* table notes: */
.tnotes {
    margin: 0ex 5% 1ex 5% ;
    padding: 0.5ex 1em 0.5ex 1em;
    font-size:.80em;
    text-align: left ;
}

.minipage .tnotes {
    margin: 0pt ;
    padding: 0pt ;
}

.tnotes dl dt p {margin-bottom:0px;}

.tnoteitemheader {margin-right: 1em;}


/* for colortbl and cell color */
div.cellcolor {
    width: 100% ;
    padding: .5ex .5em .5ex .5em ;
    margin: -.5ex -.5em -.5ex -.5em ;
}


/* for bigdelim */
.ldelim, .rdelim { font-size: 200% }


/* center, flushleft, flushright environments */
div.center{text-align:center;}
div.center table {margin-left:auto;margin-right:auto;}
div.flushleft{text-align:left;}
div.flushleft table {margin-left:0em ; margin-right:auto;}
div.flushright{text-align:right;}
div.flushright table {margin-left:auto ; margin-right: 0em ;}


/* Fancybox */
div.Btrivlist table tr td {
    padding: .2ex 0em ;
```

```
}


/* program listing callouts: */
span.callout {
     font-family: "DejaVu Sans", "Bitstream Vera Sans",
        Geneva, Verdana, sans-serif ;
    border-radius: .5em;
    background-color:black;
    color:white;
    padding:0px .25em 0px .25em;
    margin: 0 ;
    font-weight: bold;
    font-size:.72em ;
}

div.programlisting pre.verbatim span.callout{
    font-size: .85em ;
}

span.verbatim {
    font-family: "DejaVu Mono", "Bitstream Vera Mono", "Lucida Console",
        "Nimbus Mono L", "Liberation Mono", "FreeMono", "Andale Mono",
        "Courier New", monospace;
}




div.published
{
    text-align: center ;
    font-variant: normal ;
    font-style: italic ;
    font-size: 1em ;
    margin: 1ex 0em 1ex 0em ;
}

div.subtitle
{
    text-align: center ;
    font-variant: normal ;
    font-style: italic ;
    font-size: 1.25em ;
    margin: 1ex 0em 1ex 0em ;
}

div.subtitle p { margin: 1ex ; }

div.author
{
    font-variant: normal ;
    font-style: normal ;
    font-size: 1em ;
    margin: 1ex 0em 1ex 0em ;
}
```

```
2839
2840 div.oneauthor {
2841     display: inline-block ;
2842     margin: 0ex 1em 0ex 1em ;
2843 }
2844
2845 /*
2846 div.author table {
2847     margin: 1ex auto 0ex auto ;
2848     background: none ;
2849 }
2850
2851 div.author table tbody tr td { padding: .25ex ; }
2852 */
2853
2854 span.affiliation {font-size: .85em ; font-variant: small-caps; }
2855
2856 div.titledate {
2857     text-align: center ;
2858     font-size: .85em ;
2859     font-style: italic;
2860     margin: 1ex 0em 1ex 0em ;
2861 }
2862
2863
2864 nav.topnavigation{
2865     text-align: left ;
2866     padding: 0.5ex 1em 0.5ex 1em ;
2867 /*     margin: 2ex 0em 3ex 0em ; */
2868     margin: 0 ;
2869     border-bottom: 1px solid silver ;
2870     border-top: 1px solid silver ;
2871     clear:both ;
2872 }
2873
2874 nav.botnavigation{
2875     text-align: left ;
2876     padding: 0.5ex 1em 0.5ex 1em ;
2877 /*     margin: 3ex 0em 2ex 0em ; */
2878     margin: 0 ;
2879     border-top: 1px solid silver ;
2880     border-bottom: 1px solid silver ;
2881     clear:both ;
2882 }
2883
2884
2885 header {
2886     line-height: 1.2 ;
2887     font-size: 1em ;
2888     border-bottom: 1px solid silver ;
2889     margin: 0px ;
2890     padding: 2ex 1em 2ex 1em ;
2891     text-align:left ;
2892 }
2893
```

```
2894
2895 footer {
2896     font-size: .85em ;
2897     line-height: 1.2 ;
2898     margin-top: 1ex ;
2899     border-top: 1px solid silver ;
2900     padding: 2ex 1em 2ex 1em ;
2901     clear:both ;
2902     text-align:left ;
2903 }
2904
2905
2906 a.linkhome { font-weight:bold ; font-size: 1em ;}
2907
2908
2909 div.lateximagesource { padding: 0px ; margin: 0px ; display: none; }
2910
2911 img.lateximage{
2912     padding: 0pt ;
2913     margin: 0pt ;
2914     box-shadow: none ;
2915     border: none ;
2916     background: none ;
2917     max-width: 100% ;
2918     border-radius: 0ex ;
2919     border: none ;
2920 }
2921
2922
2923 /* The -1px right margin compensates for the 1px right border. */
2924 /* Without this -1px margin, the body container appears below instead */
2925 /* of floating to the side. */
2926 div.sidetoccontainer {
2927     font-family: "DejaVu Serif", "Bitstream Vera Serif",
2928         "Lucida Bright", Georgia, serif;
2929     float: left ;
2930     width: 20%;
2931     margin: 0pt -1px 3ex 0pt ;
2932     border-right: 1px solid silver;
2933     border-bottom: 1px solid silver;
2934     background: #FAF7F4 ;
2935     font-size:.9em ;
2936     border-radius: 0px 0px 20px 0px ;
2937 }
2938
2939 div.sidetoccontents {
2940     overflow-y: auto ;
2941     width: 100% ;
2942     text-align: left ;
2943 }
2944
2945
2946 nav.sidetoc p {line-height:1.2 ; margin: 1ex .5em 1ex .5em ;
2947     text-indent: 0 ; }
2948
```

```
nav.sidetoc p a {color:black ; font-size: .7em ;}

div.sidetoctitle {font-size: 1.2em; font-weight:bold; text-align:center;
    border-bottom: 1px solid silver ;    }

nav.sidetoc a:hover {text-decoration: underline ; }



section.textbody { margin: 0ex 1em 0ex 1em ;}


div.multicolsheading { -webkit-column-span: all;
    -moz-column-span: all; column-span: all; }
div.multicols { -webkit-columns: 3 380px ;
    -moz-columns: 3 380px ; columns: 3 380px ; }
div.multicols p {margin-top: 0ex}


/* Used for xfrac and nicefrac: */
span.numerator {
    font-size: 60% ;
    vertical-align: .4em ;
}

span.denominator {
    font-size: 60%
}


/* Used for algorithm2e: */
div.alg2evline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
    border-radius: 0px 0px 0px 1ex ;
}

div.alg2evsline{
    margin-left: 1em ;
    padding-left: 1em ;
    border-left: 1px solid black ;
}

div.alg2enoline{
    margin-left: 1em ;
    padding-left: 1em ;
}

span.alg2elinenumber{
    margin-right: .5em ;
    font-size: 50% ;
    color: red ;
}

```

```
3004
3005 /* Used for algorithmicx: */
3006 span.floatright { float: right ; }
3007
3008
3009 /* keyfloat and tocdata: */
3010 .floatnotes {
3011     margin: 0ex 5% 0ex 5% ;
3012     padding: 0ex 1em 0ex 1em ;
3013     font-size:.80em ;
3014     text-align: left ;
3015 }
3016
3017 .authorartist{
3018     font-size:.70em ;
3019     font-style: italic;
3020 }
3021
3022
3023
3024 /* Native LaTeX theorems: */
3025
3026 .theoremcontents { font-style: italic; margin-top: 3ex ; margin-bottom: 3ex ; }
3027 .theoremlabel { font-style: normal; font-weight: bold ; margin-right: .5em ; }
3028
3029
3030 /* theorem, amsthm, and ntheorem packages */
3031
3032 span.theoremheader,
3033 span.theoremheaderplain,
3034 span.theoremheaderdefinition,
3035 span.theoremheaderbreak,
3036 span.theoremheadermarginbreak,
3037 span.theoremheaderchangebreak,
3038 span.theoremheaderchange,
3039 span.theoremheadermargin
3040 {
3041     font-style:normal ; font-weight: bold ; margin-right: 1em ;
3042 }
3043
3044 span.amsthmnameplain,
3045 span.amsthmnamedefinition,
3046 span.amsthmnumberplain,
3047 span.amsthmnumberdefinition
3048 {
3049     font-style:normal ; font-weight: bold ;
3050 }
3051
3052
3053 span.amsthmnameremark,
3054 span.amsthmnumberremark
3055 {font-style:italic ; font-weight: normal ; }
3056
3057
3058 span.amsthmnoteplain,
```

```
span.amsthmnotedefinition
{font-style:normal ;}


span.theoremheaderremark,
span.theoremheaderproof,
span.amsthmproofname
{font-style:italic ; font-weight: normal ; margin-right: 1em ; }

span.theoremheadersc
{
    font-style:normal ;
    font-variant: small-caps ;
    font-weight: normal ;
    margin-right: 1em ;
}

.theoremendmark {float:right}

div.amsthmbodyplain, div.theorembodyplain, div.theorembodynonumberplain,
div.theorembodybreak, div.theorembodynonumberbreak,
div.theorembodymarginbreak,
div.theorembodychangebreak,
div.theorembodychange,
div.theorembodymargin
{
    font-style:italic;
    margin-top: 3ex ; margin-bottom: 3ex ;
}

div.theorembodydefinition, div.theorembodyremark, div.theorembodyproof,
div.theorembodyplainupright, nonumberplainuprightsc,
div.amsthmbodydefinition, div.amsthmbodyremark,
div.amsthmproof
{
    font-style: normal ;
    margin-top: 3ex ; margin-bottom: 3ex ;
}

span.amsthmnoteremark {}


/* For the backnaur package: */
div.backnaur {
    display: block ;
    margin: 2ex 2em 2ex 2em ;
}

div.backnaur p {
    margin: .25ex 0ex .25ex 0ex ;
}

div.backnaurprod {
    display: inline-block ;
    min-width: 8em ;
```

```
3114     text-align:right ;
3115 }
3116
3117 div.backnaurdesc {
3118     display: inline-block ;
3119 }
3120
3121
3122 /* For the notes package: */
3123 div.notesimportantnote, div.noteswarningnote, div.notesinformationnote {
3124     clear: both ;
3125     margin: 2ex 2em 2ex 2em ;
3126     border: 1px solid silver ;
3127 }
3128
3129 div.notesicon {
3130     float:left ;
3131     display: inline-block ;
3132     background: gold ;
3133     padding: 0ex 1em 0ex 1em ;
3134     margin-right: 1em ;
3135     font-weight: bold ;
3136 }
3137
3138 div.notescontents { font-style: italic }
3139
3140
3141 /*
3142 For CSS LaTeX and related logos:
3143 Based on spacing demonstrated by the metafont package.
3144 */
3145
3146 .latexlogofont {
3147     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3148         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3149     font-variant: normal ;
3150 }
3151
3152 .latexlogo {
3153     font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
3154         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3155     font-size: 1.1em;
3156 }
3157
3158 .latexlogosup {
3159   text-transform: uppercase;
3160   letter-spacing: .03em ;
3161   font-size: 0.7em;
3162   vertical-align: 0.25em;
3163   margin-left: -0.4em;
3164   margin-right: -0.15em;
3165 }
3166
3167 .latexlogosub {
3168   text-transform: uppercase;
```

```
  vertical-align: -0.27ex;
  margin-left: -0.08em;
  margin-right: -0.07em;
  font-size: 1em;
}

.latexlogotwoe {
  text-transform: none ;
  font-variant-numeric: oldstyle-nums ;
}

.latexlogotwoesub {
  font-style:italic ;
  vertical-align: -0.27ex;
  margin-left: -0.11em;
  margin-right: -0.1em;
  font-size: 1em;
}

.xelatexlogo {
    font-family: "Linux Libertine O", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    letter-spacing: .03em ;
    font-size: 1.1em;
}

.xelatexlogosub {
  vertical-align: -0.27ex;
  margin-left: -0.0667em;
  margin-right: -.05em;
  font-size: 1em;
  letter-spacing: .03em ;
}

.amslogo {
    font-family: "TeXGyreChorus","URW Chancery L",
        "Apple Chancery","ITC Zapf Chancery","Monotype Corsiva",
        "Linux Libertine O", "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif ;
    font-style: italic ;
}

.lyxlogo {
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "DejaVu Sans", "Bitstream Vera Sans", Geneva,
        Verdana, sans-serif ;
}


/* Only display top and bottom navigation if a small screen: */
/* Hide the sidetoc if a small screen: */
nav.topnavigation { display:none; }
nav.botnavigation { display:none; }

/* Only display the sidetoc's webpage title if a small screen */
```

```
span.sidetocthetitle { display: none }

@media screen and (max-width: 50em) {
    div.sidetoccontainer {
        float: none ;
        width: 100% ;
        padding: 0 ;
        border-radius: 0 ;
        border-bottom: 1px solid black ;
        border-top: 1px solid black ;
        box-shadow: none ;
    }
    span.sidetocthetitle { display: inline }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
    .marginpar {
        max-width: 100%;
        float: none;
        display:block ;
        margin: 1ex 1em 1ex 1em ;
    }
}

@media print {
    body {
        font-family: "Linux Libertine O",
        "DejaVu Serif", "Bitstream Vera Serif",
        "Liberation Serif", "Nimbus Roman No 9 L",
        "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
    }
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display: none; }
    nav.botnavigation { display: none; }
    div.bodycontainer { width: 100% }
}

@media handheld {
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
}

@media projection {
    div.sidetoccontainer { display:none; }
    nav.topnavigation { display:block }
    nav.botnavigation { display:block }
    div.bodycontainer { width: 100% }
}
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.5 lwarp_sagebrush.css

File lwarp_sagebrush.css An optional css which may be used for a semi-modern appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_sagebrush.css}
@import url("lwarp.css") ;


A:link {color:#105030 ; text-decoration: none ; }
A:visited {color:#705030 ; text-shadow:1px 1px 2px #a0a0a0;}
A:hover {color:#006000 ; text-decoration: underline ; text-shadow:0px 0px 2px #a0a0a0;}
A:active {color:#00C000 ; text-shadow:1px 1px 2px #a0a0a0;}



h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
{
    font-family: "URW Classico", Optima, "Linux Biolinum O",
        "Linux Libertine O", "Liberation Serif",
        "Nimbus Roman No 9 L",  "FreeSerif",
        "Hoefler Text", Times, "Times New Roman", serif;
    font-variant: small-caps ;
    font-weight: normal ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
}

h1 {    /* title of the entire website, used on each page */
    font-variant: small-caps ;
    color: #304070 ;
    text-shadow: 2px 2px 3px #808080;
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C4);
}

h1 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
}

h2 {
  border-bottom: 1px solid #304070;
/*  border-top: 2px solid #304070; */
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #DAD0C0);
}



div.abstract {
    background: #f5f5eb ;
```

```
3324     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3325
3326   border: 1px solid silver;
3327     border-radius: 1em ;
3328 }
3329
3330 div.abstract dl {line-height:1.5;}
3331 div.abstract dt {color:#304070;}
3332
3333 div.abstracttitle{
3334     font-family: "URW Classico", Optima, "Linux Biolinum O",
3335         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3336         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3337     font-weight:bold;
3338     font-variant: small-caps ;
3339     font-size:1.5em;
3340     border-bottom: 1px solid silver ;
3341     color: #304070 ;
3342     text-align: center ;
3343     text-shadow: 1px 1px 2px #808080;
3344 }
3345
3346 span.abstractrunintitle{
3347     font-family: "URW Classico", Optima, "Linux Biolinum O",
3348         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3349         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3350     font-weight:bold;
3351 }
3352
3353
3354 div.epigraph, div.dictum {
3355     background: #f5f5eb ;
3356     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3357
3358     border: 1px solid silver ;
3359     border-radius: 1ex ;
3360     box-shadow: 3px 3px 3px #808080 ;
3361 }
3362
3363
3364 .example {
3365     background-color: #f5f5eb ;
3366     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3367
3368 }
3369
3370 div.exampletitle{
3371     font-family: "URW Classico", Optima, "Linux Biolinum O",
3372         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3373         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3374     font-weight:bold;
3375     font-variant: small-caps ;
3376     border-bottom: 1px solid silver ;
3377     color: #304070 ;
3378     text-align: center ;
```

```
3379     text-shadow: 1px 1px 2px #808080;
3380 }
3381
3382
3383 .sidebar {
3384     background-color: #f5f5eb ;
3385     background-image: linear-gradient(to bottom, #f5f5eb, #C8C8B8);
3386
3387 }
3388
3389 div.sidebartitle{
3390     font-family: "URW Classico", Optima, "Linux Biolinum O",
3391         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3392         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3393     font-weight:bold;
3394     font-variant: small-caps ;
3395     border-bottom: 1px solid silver ;
3396     color: #304070 ;
3397     text-align: center ;
3398     text-shadow: 1px 1px 2px #808080;
3399 }
3400
3401
3402 .fancyvrblabel {
3403     font-family: "URW Classico", Optima, "Linux Biolinum O",
3404         "Linux Libertine O", "Liberation Serif", "Nimbus Roman No 9 L",
3405         "FreeSerif", "Hoefler Text", Times, "Times New Roman", serif;
3406     font-weight:bold;
3407     font-variant: small-caps ;
3408     font-size: 1.5em ;
3409     color: #304070 ;
3410     text-align: center ;
3411     text-shadow: 1px 1px 2px #808080;
3412 }
3413
3414 div.minipage {
3415     background-color: #eeeee7 ;
3416     border: 1px solid silver ;
3417     border-radius: 1ex ;
3418 }
3419
3420 table div.minipage { background: none ; border: none ; }
3421
3422 div.framebox div.minipage {border:none ; background:none}
3423
3424 section.textbody > div.minipage {
3425     box-shadow: 3px 3px 3px #808080 ;
3426 }
3427
3428 div.fboxBlock div.minipage { box-shadow: none ; }
3429
3430 .framed .minipage , .framedleftbar .minipage {
3431     border: none ;
3432     background: none ;
3433     padding: 0ex ;
```

```
3434     margin: 0ex ;
3435 }
3436
3437 figure.figure .minipage, div.figurecaption .minipage { border: none; }
3438
3439 div.marginblock div.minipage ,
3440 div.marginparblock div.minipage
3441     { border: none; }
3442
3443 figure , div.marginblock {
3444     background-color: #eeeee7 ;
3445     border: 1px solid silver ;
3446     border-radius: 1ex ;
3447     box-shadow: 3px 3px 3px #808080 ;
3448 }
3449
3450 figure figure {
3451     border: 1px solid silver ;
3452     margin: 0em ;
3453     box-shadow: none ;
3454 }
3455
3456 /*
3457 div.figurecaption {
3458     border-top: 1px solid silver ;
3459     border-bottom: 1px solid silver ;
3460     background-color: #e8e8e8 ;
3461 }
3462 */
3463
3464
3465 div.table {
3466     box-shadow: 3px 3px 3px #808080 ;
3467 }
3468
3469 /*
3470 .tnotes {
3471     background: #e8e8e8;
3472     border: 1px solid silver;
3473 }
3474 */
3475
3476
3477 nav.topnavigation{
3478     background-color: #b0b8b0 ;
3479     background-image: linear-gradient(to bottom,#e0e0e0,#b0b8b0) ;
3480 }
3481
3482 nav.botnavigation{
3483     background-color: #b0b8b0 ;
3484     background-image: linear-gradient(to top,#e0e0e0,#b0b8b0) ;
3485 }
3486
3487
3488
```

```
header{
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to top, #F7F7F0, #b0b8b0);
}

footer{
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #b0b8b0);
}



div.sidetoccontainer {
    background-color: #F7F7F0 ;
    background-image: linear-gradient(to bottom, #F7F7F0, #C0C0C0);
    box-shadow: 3px 3px 3px #808080 ;
    }

div.sidetoctitle {color: #304070 ; }

nav.sidetoc a:hover {
    color:#006000 ;
    text-decoration: none ;
    text-shadow:0px 0px 2px #a0a0a0;
}


@media screen and (max-width: 45em) {
    div.sidetoccontainer { border-radius: 0 ; }
}


\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.6 lwarp_formal.css

File `lwarp_formal.css` An optional css which may be used for a more formal appearance.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_formal.css}
@import url("lwarp.css") ;



A:link {color:#802020 ; text-decoration:none; }
A:visited {color:#802020 ; text-shadow:none ;}
A:hover {color:#400000 ; text-shadow:none ;}
A:active {color:#C00000 ; text-shadow:none ;}

```

```
3535
3536 body {
3537     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3538         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3539         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3540         "Times New Roman", serif;
3541     background: #fffcf5;
3542 }
3543
3544 span.textrm {
3545     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3546         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3547         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3548         "Times New Roman", serif;
3549 }
3550
3551 span.textsf {
3552      font-family: "DejaVu Sans", "Bitstream Vera Sans",
3553         Geneva, Verdana, sans-serif ;
3554 }
3555
3556
3557
3558 h1, h2, h3, h4, h5, h6, span.paragraph, span.subparagraph
3559 {
3560     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3561         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3562         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3563         "Times New Roman", serif;
3564     color: #800000 ;
3565     text-shadow: none ;
3566 }
3567
3568 h1, h2 {
3569     background-color: #fffcf5 ;
3570     background-image: none ;
3571     border-bottom: 1px solid #808080;
3572 /*    border-top: 2px solid #808080; */
3573 }
3574
3575 div.abstracttitle {
3576     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3577         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3578         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3579         "Times New Roman", serif;
3580     color: black ;
3581     text-shadow: none ;
3582 }
3583
3584 span.abstractrunintitle {
3585     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3586         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3587         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3588         "Times New Roman", serif;
3589     color: black ;
```

```
    text-shadow: none ;
}

div.abstract { font-size: 100% }

.sidebar {
    background: #fffcf5;
    background-image: none ;
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
  font-size: 90% ;
}

div.sidebartitle{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}

.example {
    background: #fffcf5;
    background-image: none ;
  margin: 2em 5% 2em 5%;
  padding: 0.5em 1em;
  border: none ;
  border-top : 1px solid silver;
  border-bottom : 1px solid silver;
}

div.exampletitle{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}

div.fancyvrblabel{
    font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
        "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
        "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
        "Times New Roman", serif;
    color: #800000 ;
    text-shadow: none ;
    border: none ;
}
```

```
3645
3646
3647
3648 figure {
3649     margin: 5ex 5% 5ex 5% ;
3650     padding: 1ex 1em 1ex 1em ;
3651     background-color: #fffcf5 ;
3652     overflow-x: auto ;
3653     border: none ;
3654 /*     border-top: 1px solid silver; */
3655 /*     border-bottom: 1px solid silver; */
3656 }
3657
3658
3659 div.figurecaption , .lstlisting {
3660     border: none ;
3661 /*     border-top: 1px solid silver ; */
3662 /*     border-bottom: 1px solid silver ; */
3663     background-color: #fffcf5 ;
3664 }
3665
3666 .tnotes {
3667     background: #fffcf5 ;
3668     border-top: 1px solid silver ;
3669     border-bottom: 1px solid silver ;
3670 }
3671
3672 .theorem {
3673         background: none ;
3674 }
3675
3676 .minipage {
3677     background-color: #fffcf5 ;
3678     border: none ;
3679 }
3680
3681 div.floatrow figure { border: none ; }
3682
3683 figure figure { border: none ; }
3684
3685
3686 nav.toc, nav.lof, nav.lot, nav.lol {
3687     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3688         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3689         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3690         "Times New Roman", serif;
3691 }
3692
3693 div.sidetoccontainer {
3694     font-family: "Linux Libertine O", "Hoefler Text", "Garamond",
3695         "Bembo", "Janson", "TeX Gyre Pagella", "Palatino",
3696         "Liberation Serif", "Nimbus Roman No 9 L",  "FreeSerif", Times,
3697         "Times New Roman", serif;
3698     background-image: linear-gradient(to bottom, #fffcf5, #C0C0C0);
3699 }
```

```
3700
3701 div.sidetoctitle{
3702     color: #800000 ;
3703 }
3704
3705 header{
3706     background-color: #e0e0e0 ;
3707     background-image: linear-gradient(to top, #fffcf5, #b0b0b0);
3708     text-align:center ;
3709 }
3710
3711 footer{
3712     background-color: #e0e0e0 ;
3713     background-image: linear-gradient(to bottom, #fffcf5, #b0b0b0);
3714     padding: 2ex 1em 2ex 1em ;
3715     text-align:left ;
3716 }
3717
3718 nav.botnavigation {
3719     background: #dedcd5 ;
3720     border-top: 1px solid black ;
3721 }
3722 \end{filecontents*}
3723 % \end{Verbatim}% for syntax highlighting
3724 \end{LWRwriteconf}
```

40.7 sample_project.css

File sample_project.css The project-specific CSS file. Use with \CSSFilename.

If used, this must be present both when compiling the project and also when distributing the HTML files.

Config file:

```
3725 \begin{LWRwriteconf}
3726 \begin{filecontents*}{sample_project.css}
3727 /* ( --- Start of project.css --- ) */
3728 /* ( --- A sample project-specific CSS file for lwarp --- ) */
3729
3730 /* Uncomment one of the following: */
3731 @import url("lwarp.css") ;
3732 /* @import url("lwarp_formal.css") ; */
3733 /* @import url("lwarp_sagebrush.css") ; */
3734
3735 /* Project-specific CSS setting follow here. */
3736 /* . . . */
3737
3738 /* ( --- End of project.css --- ) */
3739 \end{filecontents*}
3740 % \end{Verbatim}% for syntax highlighting
3741 \end{LWRwriteconf}
```

40.8 lwarp.ist

File `lwarp.ist` Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The page compositor line is for memoir's `\specialindex`.

Config file:
```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.ist}
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 ", \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"
page_compositor "."
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.9 lwarp.xdy

File `lwarp.xdy` Used to modify the index for lwarp.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

See:
https://tex.stackexchange.com/questions/80300/how-can-i-convince-hyperref-and-xindy-to-play-together-nicely

Config file:
```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp.xdy}
(require "tex/inputenc/latin.xdy")
(merge-rule "\\PS *" "Postscript")
(require "texindy.xdy")
(require "page-ranges.xdy")
(require "book-order.xdy")
(define-location-class "arabic-page-numbers"
```

```
    ("arabic-numbers") :min-range-length 1)
(require "makeindex.xdy")
(define-attributes (("hyperindexref")))
(markup-locref :open "\hyperindexref{" :close "}")
(markup-locref :open "\hyperindexref{" :close "}" :attr "hyperpage")
(markup-locref :open "\textbf{\hyperindexref{" :close "}}" :attr "textbf")
(markup-locref :open "\textit{\hyperindexref{" :close "}}" :attr "textit")
(define-location-class-order ("roman-page-numbers"
                  "arabic-page-numbers"
                  "alpha-page-numbers"
                  "Roman-page-numbers"
                  "Alpha-page-numbers"
                  "see"
                  "seealso"))
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.10 lwarp_one_limage.cmd

File lwarp_one_limage.cmd

Used by lwarp to help make lateximages when using Windows.

This must be present when compiling the project, but does not need to be present when distributing the resulting HTML files.

The arguments are each of the three fields from <project>-images.txt, and also the base name of the source file.

MiKTeX does not allow file lwarp_one_limage.cmd to be created directly by *lwarpmk*, so lwarp_one_limage.txt is created instead, then copied to lwarp_one_limage.cmd by *lwarpmk*. This occurs each time *lwarpmk* used to create lateximages.

Config file:

```
\begin{LWRwriteconf}
\immediate\openout\LWR@quickfile=lwarp_one_limage.txt
\immediate\write\LWR@quickfile{%
    pdfseparate -f \LWRpercent 1 -l \LWRpercent 1 \LWRpercent 4_html.pdf %
   \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent\LWRpercent d.pdf%
}
\immediate\write\LWR@quickfile{%
   pdfcrop --hires  \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
   pdftocairo -svg -noshrink  \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf %
    \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.svg%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol\LWRpercent 3.pdf%
}
\immediate\write\LWR@quickfile{%
    del \LWR@ImagesDirectory\OSPathSymbol lateximagetemp-\LWRpercent 1.pdf%
}
\immediate\write\LWR@quickfile{exit}
```

```
\immediate\closeout\LWR@quickfile
\end{LWRwriteconf}
```

40.11 lwarp_mathjax.txt

File lwarp_mathjax.txt

The default MathJax script used by lwarp when using MathJax. A recent version of MathJax is used, as served by the recommended repository. Adjustments are made to allow LaTeX to control the equation tags.

\MathJaxFilename determines which script file is copied into the HTML pages, and defaults to lwarp_mathjax.txt. The script files must be present when compiling the project, but do not need to be present when distributing the resulting HTML files.

custom script

To generate a custom script, such as to use a local repository, copy lwarp_mathjax.txt to a new file, make changes while keeping lwarp's adjustments for equation numbering, and use \MathJaxFilename to select new filename.

Config file:

```
\begin{LWRwriteconf}
\begin{filecontents*}{lwarp_mathjax.txt}
<!-- https://groups.google.com/forum/#!topic/
                                  mathjax-users/jUtewUcE2bY -->
<script type="text/x-mathjax-config">
MathJax.Hub.Register.StartupHook("TeX AMSmath Ready",function () {
    var seteqsectionDefault = {name: "", num: 0};
    var seteqsections = {}, seteqsection = seteqsectionDefault;
    var TEX = MathJax.InputJax.TeX, PARSE = TEX.Parse;
    var AMS = MathJax.Extension["TeX/AMSmath"];
    TEX.Definitions.Add({
    macros: {
        seteqsection: "mySection",
        seteqnumber: "mySetEqNumber"
    }
    });

    PARSE.Augment({
    mySection: function (name) {
        seteqsection.num = AMS.number;
        var n = this.GetArgument(name);
        if (n === "") {
            seteqsection = seteqsectionDefault;
        } else {
            if (!seteqsections["_"+n])
                seteqsections["_"+n] = {name:n, num:0};
            seteqsection = seteqsections["_"+n];
        }
        AMS.number = seteqsection.num;
    },
    mySetEqNumber: function (name) {
        var n = this.GetArgument(name);
        if (!n || !n.match(/^ *[0-9]+ *$/))
            n = "";
        else
            n = parseInt(n)-1;
```

```
        <!-- $ syntax highlighting -->
        if (n === "" || n < 1)
            TEX.Error
            ("Argument to "+name+" should be a positive integer");
        AMS.number = n;
    }
    });
    MathJax.Hub.Config({
    TeX: {
        equationNumbers: {
            formatTag: function (n) {
                <!-- if not numeric, don't include the chapter -->
                if (!n.match(/^ *[0-9]+ *$/ ))
                <!-- $ syntax highlighting -->
                    return "("+(n).replace(/^\./,"")+")" ;
                else
                  return "("+(seteqsection.name+"."+n).replace(/^\./,"")+")" ;
            },
            formatID: function (n) {
                n = (seteqsection.name+'.'+n).replace
                    (/[:"'<>&]/g,"").replace(/^\./,"");
                return 'mjx-eqn-' + n;
            }
        }
    }
    });
});
</script>

<!-- http://docs.mathjax.org/en/latest/options/ThirdParty.html -->
<script type="text/x-mathjax-config">
  MathJax.Ajax.config.path["Contrib"] =
    "https://cdn.mathjax.org/mathjax/contrib";
</script>

<script type="text/x-mathjax-config">
MathJax.Hub.Config({
    TeX: {
        extensions: ["autoload-all.js"] ,
        equationNumbers: {
            autoNumber: "AMS"
        }
    }
});
</script>

<!-- Alternative CDN provider: -->
<script type="text/javascript" async
src="https://cdnjs.cloudflare.com/ajax/libs/mathjax/2.7.5/MathJax.js?config=TeX-AMS_HTML-full">
</script>

<!-- No longer supported after April 30, 2017: -->
<!--
<script
 src="https://cdn.mathjax.org/mathjax/latest/MathJax.js?config=TeX-AMS_HTML-full">
```

```
</script>
-->

\end{filecontents*}
% \end{Verbatim}% for syntax highlighting
\end{LWRwriteconf}
```

40.12 `lwarpmk.lua` — `lwarpmk` option

Opt `lwarpmk` Creates a local copy of *lwarpmk*.

Prog `lwarpmk` Command-line utility to process lwarp files and images.

parallel processing `latex`images and SVG math images are generated using multiple processes in parallel. For UNIX and LINUX, every 32 images the `wait` command is issued to wait for the previous batch of images to finish processing before starting a new batch. For WINDOWS, every 32 images one task is dispatched with

```
START /B /WAIT /BELOWNORMAL
```

which causes the operating system to wait until this lesser-priority tasks finishes, hopefully also waiting for the normal priority tasks which were already in progress to also complete. Afterwards, the next batch of images is started.

The following is only generated if the `lwarpmk` option was given to lwarp.

```
\begin{LWR@createlwarpmk}

\begin{filecontents*}{lwarpmk.lua}
#!/usr/bin/env texlua

-- Copyright 2016-2019 Brian Dunn


printversion = "v0.72"
requiredconfversion = "2" -- also at *lwarpmk.conf

function printhelp ()
print ("lwarpmk: Use lwarpmk -h or lwarpmk --help for help.") ;
end


function printusage ()
--
-- Print the usage of the lwarpmk command:
--
print ( [[

lwarpmk print [-p project]: Compile the print version if necessary.
lwarpmk print1 [-p project]: Forced single compile of the print version.
lwarpmk printindex [-p project]: Process print indexes.
lwarpmk printglossary [-p project]: Process the glossary for the print version.
lwarpmk html [-p project]: Compile the HTML version if necessary.
```

```
lwarpmk html1 [-p project]: Forced single compile of the HTML version.
lwarpmk htmlindex [-p project]: Process HTML indexes.
lwarpmk htmlglossary [-p project]: Process the glossary for the html version.
lwarpmk again [-p project]: Touch the source code to trigger recompiles.
lwarpmk limages [-p project]: Process the "lateximages" created by lwarp.sty.
lwarpmk pdftohtml [-p project]:
    For use with latexmk or a Makefile:
    Converts project_html.pdf to project_html.html and individual HTML files.
    Finishes the HTML conversion even if there was a compile error.
lwarpmk pdftosvg <list of file names>: Converts each PDF file to SVG.
lwarpmk epstopdf <list of file names>: Converts each EPS file to PDF.
lwarpmk clean [-p project]: Remove *.aux, *.toc, *.lof/t,
    *.idx, *.ind, *.log, *_html_inc.*, .gl*
lwarpmk cleanall [-p project]: Remove auxiliary files, project.pdf, *.html
lwarpmk cleanlimages: Removes all images from the "lateximages" directory.
lwarpmk -h: Print this help message.
lwarpmk --help: Print this help message.

]] )
-- printconf ()
end


function splitfile (destfile,sourcefile)
--
-- Split one large sourcefile into a number of files,
-- starting with destfile.
-- The file is split at each occurance of <!--|Start file|newfilename|*
--
print ("lwarpmk: Splitting " .. sourcefile .. " into " .. destfile) ;
local sfile = io.open(sourcefile)
io.output(destfile)
for line in sfile:lines() do
i,j,copen,cstart,newfilename = string.find (line,"(.*)|(.*)|(.*)|") ;
if ( (i~= nil) and (copen == "<!--") and (cstart == "Start file")) then
    -- split the file
    io.output(newfilename) ;
else
    -- not a splitpoint
    io.write (line .. "\n") ;
end
end -- do
io.close(sfile)
end -- function


function cvalueerror ( line, linenum , cvalue )
--
-- Incorrect value, so print an error and exit.
--
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. linenum .. " : " .. line ) ;
    print (
        "lwarpmk: incorrect variable value \"" .. cvalue ..
        "\" in lwarpmk.conf.\n"
```

```
3992     ) ;
3993     print ("lwarpmk: ===")
3994 --    printconf () ;
3995     os.exit(1) ;
3996 end
3997
3998
3999 function printhowtorecompile ()
4000 -- Tells the user how to recompile to regenerate the configuration files.
4001    print ("lwarpmk: The configuration files lwarpmk.conf and "..sourcename..".lwarpmkconf" )
4002     print ("lwarpmk:   must be updated.  To do so, recompile" )
4003     print ("lwarpmk:   " , sourcename..".tex" )
4004     if ( printlatexcmd == "" ) then
4005         print ("lwarpmk:   using xe/lua/pdflatex," )
4006     else
4007         print ("lwarpmk:   using the command:")
4008         print ("lwarpmk:   " , printlatexcmd )
4009     end
4010     print ("lwarpmk:   then use lwarpmk again.")
4011 end -- printhowtorecompile
4012
4013
4014 function ignoreconf ()
4015 -- Global argument index
4016 argindex = 2
4017 end
4018
4019 function loadconf ()
4020 --
4021 -- Load settings from the project's "lwarpmk.conf" file:
4022 --
4023 -- Default configuration filename:
4024 local conffile = "lwarpmk.conf"
4025 local confroot = "lwarpmk"
4026 -- Global argument index
4027 argindex = 2
4028 -- Optional configuration filename:
4029 if ( arg[argindex] == "-p" ) then
4030     argindex = argindex + 1
4031     confroot = arg[argindex]
4032     conffile = confroot..".lwarpmkconf"
4033     argindex = argindex + 1
4034 end
4035 -- Additional defaults:
4036 confversion = "0"
4037 opsystem = "Unix"
4038 imagesdirectory = "lateximages"
4039 imagesname = "image-"
4040 latexmk = "false"
4041 printlatexcmd = ""
4042 HTMLlatexcmd = ""
4043 printindexcmd = ""
4044 HTMLindexcmd = ""
4045 latexmkindexcmd = ""
4046 -- to be removed:
```

```
-- indexprog = "makeindex"
-- makeindexstyle = "lwarp.ist"
-- xindylanguage = "english"
-- xindycodepage = "utf8"
-- xindystyle = "lwarp.xdy"
-- pdftotextenc = "UTF-8"
glossarycmd = "makeglossaries"
-- Verify the file exists:
if (lfs.attributes(conffile,"mode")==nil) then
    -- file not exists
    print ("lwarpmk: ===")
    print ("lwarpmk: File \"" .. conffile .."\" does not exist.")
    print ("lwarpmk: Move to the project's source directory,")
    print ("lwarpmk: recompile using pdflatex, xelatex, or lualatex,")
    print ("lwarpmk: then try using lwarpmk again.")
    if ( arg[argindex] ~= nil ) then
        print (
            "lwarpmk: (\"" .. confroot ..
            "\" does not appear to be a project name.)"
        )
    end
    print ("lwarpmk: ===")
    printhelp () ;
    os.exit(1) -- exit the entire lwarpmk script
else -- file exists
-- Read the file:
print ("lwarpmk: Reading " .. conffile ..".")
local cfile = io.open(conffile)
-- Scan each line, parsing each line as: name = [[string]]
local linenum = 0
for line in cfile:lines() do -- scan lines
linenum = linenum + 1
i,j,cvarname,cvalue = string.find (line,"([%w-_]*)%s*=%s*%[%[([^%]]*)%]%]") ;
-- Error if incorrect enclosing characters:
if ( i == nil ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " ..  linenum .. " : " .. line ) ;
    print ("lwarpmk: Incorrect entry in " .. conffile ..".\n" ) ;
    print ("lwarpmk: ===")
--    printconf () ;
    os.exit(1) ;
end -- nil
if ( cvarname == "confversion" ) then
    confversion = cvalue
elseif ( cvarname == "opsystem" ) then
    -- Verify choice of opsystem:
    if ( (cvalue == "Unix") or (cvalue == "Windows") ) then
        opsystem = cvalue
    else
        cvalueerror ( line, linenum , cvalue )
    end
elseif ( cvarname == "sourcename" ) then sourcename = cvalue
elseif ( cvarname == "homehtmlfilename" ) then homehtmlfilename = cvalue
elseif ( cvarname == "htmlfilename" ) then htmlfilename = cvalue
elseif ( cvarname == "imagesdirectory" ) then imagesdirectory = cvalue
```

```
elseif ( cvarname == "imagesname" ) then imagesname = cvalue
elseif ( cvarname == "latexmk" ) then latexmk = cvalue
elseif ( cvarname == "printlatexcmd" ) then printlatexcmd = cvalue
elseif ( cvarname == "HTMLlatexcmd" ) then HTMLlatexcmd = cvalue
elseif ( cvarname == "printindexcmd" ) then printindexcmd = cvalue
elseif ( cvarname == "HTMLindexcmd" ) then HTMLindexcmd = cvalue
elseif ( cvarname == "latexmkindexcmd" ) then latexmkindexcmd = cvalue
elseif ( cvarname == "glossarycmd" ) then glossarycmd = cvalue
elseif ( cvarname == "pdftotextenc" ) then pdftotextenc = cvalue
else
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. linenum .. " : " .. line ) ;
    print (
        "lwarpmk: Incorrect variable name \"" .. cvarname .. "\" in " ..
        conffile ..".\n"
    ) ;
    print ("lwarpmk: ===")
--    printconf () ;
os.exit(1) ;
end -- cvarname
end -- do scan lines
io.close(cfile)
end -- file exists
-- Error if sourcename is "lwarp".
-- This could happen if a local copy of lwarp has recently been recompiled.
if sourcename=="lwarp" then
    print ("lwarpmk: ===")
   print ("lwarpmk: lwarp.sty has recently been recompiled in this directory,")
   print ("lwarpmk: and \"lwarpmk.conf\" is no longer set for your own project.")
  print ("lwarpmk: Recompile your own project using pdf/lua/xelatex <projectname>.")
  print ("lwarpmk: After a recompile, \"lwarpmk.conf\" will be set for your project,")
    print ("lwarpmk: and you may again use lwarpmk.")
    print ("lwarpmk: ===")
    os.exit(1)
end -- sourcename of "lwarp"
-- Select some operating-system commands:
if opsystem=="Unix" then  -- For Unix / Linux / Mac OS:
    rmname = "rm"
    mvname = "mv"
    cpname = "cp"
    touchnamepre = "touch"
    touchnamepost = ""
    newtouchname = "touch"
    dirslash = "/"
    opquote= "\'"
    cmdgroupopenname = " ( "
    cmdgroupclosename = " ) "
    seqname = " && "
    bgname = " &"
elseif opsystem=="Windows" then -- For Windows
    rmname = "DEL"
    mvname = "MOVE"
    cpname = "COPY"
    touchnamepre = "COPY /b"
    touchnamepost = "+,,"
```

```
4157     newtouchname = "echo empty >"
4158     dirslash = "\\"
4159     opquote= "\""
4160     cmdgroupopenname = ""
4161     cmdgroupclosename = ""
4162     seqname = " & "
4163     bgname = ""
4164 else
4165     print ("lwarpmk: ===")
4166     print ("lwarpmk: Select Unix or Windows for opsystem." )
4167     print ("lwarpmk: ===")
4168     os.exit(1)
4169 end --- for Windows
4170 -- Warning if the operating system does not appear to be correct,
4171 -- in case files were transferred to another system.
4172 if ( (package.config:sub(1,1)) ~= dirslash ) then
4173     print ("lwarpmk: ===")
4174    print ("lwarpmk: It appears that lwarpmk.conf is for a different operating system." )
4175     printhowtorecompile ()
4176     print ("lwarpmk: ===")
4177     os.exit(1)
4178 end
4179 -- Error if the configuration file's version is not current:
4180 if ( confversion ~= requiredconfversion ) then
4181     print ("lwarpmk: ===")
4182     printhowtorecompile ()
4183     print ("lwarpmk: ===")
4184     os.exit(1)
4185 end
4186 end -- loadconf
4187
4188
4189 function executecheckerror ( executecommands , errormessage )
4190 --
4191 -- Execute an operating system call,
4192 -- and maybe exit with an error message.
4193 --
4194 local err
4195 err = os.execute ( executecommands )
4196 if ( err ~= 0 ) then
4197     print ("lwarpmk: ===")
4198     print ("lwarpmk: " .. errormessage )
4199     print ("lwarpmk: ===")
4200     os.exit(1)
4201 end
4202 end -- executecheckerror
4203
4204
4205 function refreshdate ()
4206 os.execute(touchnamepre .. " " .. sourcename .. ".tex " .. touchnamepost)
4207 end
4208
4209
4210
4211 function reruntoget (filesource)
```

```
--
-- Scan the LaTeX log file for the phrase "Rerun to get",
-- indicating that the file should be compiled again.
-- Return true if found.
--
local fsource = io.open(filesource)
for line in fsource:lines() do
if ( string.find(line,"Rerun to get") ~= nil ) then
    io.close(fsource)
    return true
end -- if
end -- do
io.close(fsource)
return false
end



function onetime (latexcmd, fsuffix)
--
-- Compile one time, return true if should compile again.
-- fsuffix is "" for print, "_html" for HTML output.
--
print("lwarpmk: Compiling with: " .. latexcmd)
executecheckerror (
    latexcmd ,
    "Compile error."
)
return (reruntoget(sourcename .. fsuffix .. ".log") ) ;
end


function manytimes (latexcmd, fsuffix)
--
-- Compile up to five times.
-- fsuffix is "" for print, "_html" for HTML output
--
if onetime(latexcmd, fsuffix) == true then
if onetime(latexcmd, fsuffix) == true then
if onetime(latexcmd, fsuffix) == true then
if onetime(latexcmd, fsuffix) == true then
if onetime(latexcmd, fsuffix) == true then
end end end end end
end


function verifyfileexists (filename)
--
-- Exit if the given file does not exist.
--
if (lfs.attributes ( filename , "modification" ) == nil ) then
    print ("lwarpmk: ===")
    print ("lwarpmk: " .. filename .. " not found." ) ;
    print ("lwarpmk: ===")
    os.exit (1) ;
```

```
4267 end
4268 end
4269
4270
4271
4272 function pdftohtml ()
4273 --
4274 -- Convert <project>_html.pdf into HTML files:
4275 --
4276 -- Convert to text:
4277 print ("lwarpmk: Converting " .. sourcename
4278     .."_html.pdf to " .. sourcename .. "_html.html")
4279 os.execute("pdftotext  -enc " .. pdftotextenc .. "  -nopgbrk  -layout "
4280     .. sourcename .. "_html.pdf " .. sourcename .. "_html.html")
4281 -- Split the result into individual HTML files:
4282 splitfile (homehtmlfilename .. ".html" , sourcename .. "_html.html")
4283 end
4284
4285
4286 function removeaux ()
4287 --
4288 -- Remove auxiliary files:
4289 -- All .aux files are removed since there may be many bbl*.aux files.
4290 --
4291 os.execute ( rmname .. " *.aux " ..
4292     sourcename ..".toc " .. sourcename .. "_html.toc " ..
4293     sourcename ..".lof " .. sourcename .. "_html.lof " ..
4294     sourcename ..".lot " .. sourcename .. "_html.lot " ..
4295     " *.idx " ..
4296     " *.ind " ..
4297     sourcename ..".ps " .. sourcename .."_html.ps " ..
4298     sourcename ..".log " .. sourcename .. "_html.log " ..
4299     sourcename ..".gl* " .. sourcename .. "_html.gl* " ..
4300     " *_html_inc.* "
4301     )
4302 end
4303
4304 function checkhtmlpdfexists ()
4305 --
4306 -- Error if the HTML document does not exist.
4307 -- The lateximages are drawn from the HTML PDF version of the document,
4308 -- so "lwarpmk html" must be done before "lwarpmk limages".
4309 --
4310 local htmlpdffile = io.open(sourcename .. "_html.pdf", "r")
4311 if ( htmlpdffile == nil ) then
4312     print ("")
4313     print ("lwarpmk: ===")
4314     print ("lwarpmk: The HTML version of the document does not exist.")
4315     print ("lwarpmk: Enter \"lwarpmk html\" to compile the HTML version.")
4316     print ("lwarpmk: ===")
4317     os.exit(1)
4318 end
4319 io.close (htmlpdffile)
4320 end -- checkhtmlpdfexists
4321
```

```
4322
4323 function warnlimages ()
4324 --
4325 -- Warning of a missing <sourcename>-images.txt file:
4326     print ("lwarpmk: ===")
4327     print ("lwarpmk: \"" .. sourcename .. "-images.txt\" does not exist.")
4328     print ("lwarpmk: Your project does not use SVG math or other lateximages,")
4329     print ("lwarpmk: or the file has been deleted somehow.")
4330     print ("lwarpmk: Use \"lwarpmk html1\" to recompile your project")
4331     print ("lwarpmk: and recreate \"" .. sourcename .. "-images.txt\".")
4332    print ("lwarpmk: If your project does not use SVG math or other lateximages,")
4333    print ("lwarpmk: then \"" .. sourcename .. "-images.txt\" will never exist, and")
4334     print ("lwarpmk: \"lwarpmk limages\" will not be necessary.")
4335     print ("lwarpmk: ===")
4336 end -- warnlimages
4337
4338
4339 function warnlimagesrecompile ()
4340 -- Warning if must recompile before creating limages:
4341     print ("")
4342     print ("lwarpmk: ===")
4343     print ("lwarpmk: Cross-references are not yet correct.")
4344    print ("lwarpmk: The document must be recompiled before creating the lateximages.")
4345    print ("lwarpmk: Enter \"lwarpmk html1\" again, then try \"lwarpmk limages\" again.")
4346     print ("lwarpmk: ===")
4347 end --warnlimagesrecompile
4348
4349
4350 function checklimages ()
4351 --
4352 -- Check <sourcename>.txt to see if need to recompile first.
4353 -- If any entry has a page number of zero, then there were incorrect images.
4354 --
4355 print ("lwarpmk: Checking for a valid " .. sourcename .. "-images.txt file.")
4356 local limagesfile = io.open(sourcename .. "-images.txt", "r")
4357 if ( limagesfile == nil ) then
4358     warnlimages ()
4359     os.exit(1)
4360 end
4361 -- Track warning to recompile if find a page 0
4362 local pagezerowarning = false
4363 -- Scan <sourcename>.txt
4364 for line in limagesfile:lines() do
4365     -- lwimgpage is the page number in the PDF which has the image
4366     -- lwimghash is true if this filename is a hash
4367     -- lwimgname is the lateximage filename root to assign for the image
4368     i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
4369     -- For each entry:
4370     if ( (i~=nil) ) then
4371         -- If the page number is 0, image references are incorrect
4372         --  and must recompile the soure document:
4373         if ( lwimgpage == "0" ) then
4374             pagezerowarning = true
4375         end
4376     end -- if i~=nil
```

```
end -- do
-- The last line should be |end|end|end|.
-- If not, the compile must have aborted, and the images are incomplete.
if ( lwimgpage ~= "end" ) then
    warnlimagesrecompile()
    os.exit(1) ;
end
if ( pagezerowarning ) then
    warnlimagesrecompile()
    os.exit(1) ;
end -- pagezerowarning
end -- checklimages


function createuniximage ( lwimgfullname )
--
-- Create one lateximage for Unix / Linux / Mac OS.
--
executecheckerror (
    cmdgroupopenname ..
    "pdfseparate -f " .. lwimgpage .. " -l " .. lwimgpage .. " " ..
        sourcename .."_html.pdf " ..
        imagesdirectory .. dirslash .."lateximagetemp-%d" .. ".pdf" ..
        seqname ..
    -- Crop the image:
    "pdfcrop  --hires  " .. imagesdirectory .. dirslash .. "lateximagetemp-" ..
        lwimgpage .. ".pdf " ..
        imagesdirectory .. dirslash .. lwimgname .. ".pdf" ..
        seqname ..
    -- Convert the image to svg:
   "pdftocairo -svg  -noshrink  " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf " ..
        imagesdirectory .. dirslash .. lwimgname ..".svg" ..
        seqname ..
    -- Remove the temporary files:
   rmname .. " " .. imagesdirectory .. dirslash .. lwimgname .. ".pdf" .. seqname ..
   rmname .. " " .. imagesdirectory .. dirslash .. "lateximagetemp-" .. lwimgpage .. ".pdf" ..
    cmdgroupclosename .. " >/dev/null " .. bgname
    ,
    "File error trying to convert " .. lwimgfullname
)
-- Every 32 images, wait for completion at below normal priority,
--  allowing other image tasks to catch up.
numimageprocesses = numimageprocesses + 1
if ( numimageprocesses > 32 ) then
    numimageprocesses = 0
    print ( "lwarpmk: waiting" )
    executecheckerror ( "wait" , "File error trying to wait.")
end
end -- createuniximage


function createwindowsimage ( lwimgfullname )
--
-- Create one lateximage for Windows.
--
```

```
4432 -- Every 32 images, wait for completion at below normal priority,
4433 --  allowing other image tasks to catch up.
4434 numimageprocesses = numimageprocesses + 1
4435 if ( numimageprocesses > 32 ) then
4436     numimageprocesses = 0
4437     thiswaitcommand = "/WAIT /BELOWNORMAL"
4438     print ( "lwarpmk: waiting" )
4439 else
4440     thiswaitcommand = ""
4441 end
4442 -- Execute the image generation command
4443 executecheckerror (
4444     "start /B " .. thiswaitcommand .. " \"\" lwarp_one_limage " ..
4445     lwimgpage .. " " ..
4446     lwimghash .. " " ..
4447     lwimgname .. " " ..
4448     sourcename .. " <nul >nul"
4449     ,
4450     "File error trying to create image."
4451 )
4452 end -- createwindowsimage
4453
4454
4455 function createonelateximage ( line )
4456 --
4457 -- Given the next line of <sourcename>.txt, convert a single image.
4458 --
4459 -- lwimgpage is the page number in the PDF which has the image
4460 -- lwimghash is true if this filename is a hash
4461 -- lwimgname is the lateximage filename root to assign for the image
4462 i,j,lwimgpage,lwimghash,lwimgname = string.find (line,"|(.*)|(.*)|(.*)|")
4463 -- For each entry:
4464 if ( (i~=nil) ) then
4465     -- Skip if the page number is 0:
4466     if ( lwimgpage == "0" ) then
4467         pagezerowarning = true
4468     -- Skip if the page number is "end":
4469     else if ( lwimgpage == "end" ) then
4470     else
4471         -- Skip is this image is hashed and already exists:
4472        local lwimgfullname = imagesdirectory .. dirslash .. lwimgname .. ".svg"
4473         if (
4474             (lwimghash ~= "true") or
4475             (lfs.attributes(lwimgfullname,"mode")==nil) -- file not exists
4476         )
4477         then -- not hashed or not exists:
4478             -- Print the name of the file being generated:
4479             print ( "lwarpmk: " .. lwimgname )
4480           -- Touch/create the dest so that only once instance tries to build it:
4481             executecheckerror (
4482                 newtouchname .. " " .. lwimgfullname ,
4483                 "File error trying to touch " .. lwimgfullname
4484             )
4485             -- Separate out the image into its own single-page pdf:
4486             if opsystem=="Unix" then
```

```
4487                createeuniximage (lwimgfullname)
4488            elseif opsystem=="Windows" then
4489                createwindowsimage (lwimgfullname)
4490            end
4491        end -- not hashed or not exists
4492    end -- not page "end"
4493    end -- not page 0
4494 end -- not nil
4495 end -- createonelateximage
4496
4497
4498 function createlateximages ()
4499 --
4500 -- Create lateximages based on <sourcename>-images.txt:
4501 --
4502 -- See if the document must be recompiled first:
4503 checklimages ()
4504 -- See if the HTML version exists:
4505 checkhtmlpdfexists ()
4506 -- Attempt to create the lateximages:
4507 print ("lwarpmk: Creating lateximages.")
4508 local limagesfile = io.open(sourcename .. "-images.txt", "r")
4509 if ( limagesfile == nil ) then
4510    warnlimages ()
4511    os.exit(1)
4512 end
4513 -- Create the lateximages directory, ignore error if already exists
4514 err = os.execute("mkdir " .. imagesdirectory)
4515 -- For Windows, create lwarp_one_limage.cmd from lwarp_one_limage.txt:
4516 if opsystem=="Windows" then
4517    executecheckerror (
4518        cpname .. " lwarp_one_limage.txt lwarp_one_limage.cmd" ,
4519       "File error trying to copy lwarp_one_limage.txt to lwarp_one_limage.cmd"
4520    )
4521 end -- create lwarp_one_limage.cmd
4522 -- Track the number of parallel processes
4523 numimageprocesses = 0
4524 -- Track warning to recompile if find a page 0
4525 pagezerowarning = false
4526 -- Scan <sourcename>.txt
4527 for line in limagesfile:lines() do
4528    createonelateximage ( line )
4529 end -- do
4530 io.close(limagesfile)
4531 print ( "lwarpmk limages: ===")
4532 print ( "lwarpmk limages: Wait a moment for the images to complete" )
4533 print ( "lwarpmk limages:   before reloading the page." )
4534 print ( "lwarpmk limages: ===")
4535 print ( "lwarpmk limages: Done." )
4536 if ( pagezerowarning == true ) then
4537    print ( "lwarpmk limages: WARNING: Images will be incorrect." )
4538    print ( "lwarpmk limages:   Enter \"lwarpmk cleanlimages\", then" )
4539    print ( "lwarpmk limages:   recompile the document one more time, then" )
4540    print ( "lwarpmk limages:   repeat \"lwarpmk images\" again." )
4541 end -- pagezerowarning
```

```
end -- function


function convertepstopdf ()
--
-- Converts EPS files to PDF files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "pdftosvg".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        os.execute ( "epstopdf " .. arg[i] )
    end -- if
end -- do
end --function


function convertpdftosvg ()
--
-- Converts PDF files to SVG files.
-- The filenames are arg[argindex] and up.
-- arg[1] is the command "pdftosvg".
--
ignoreconf ()
for i = argindex , #arg do
    if (lfs.attributes(arg[i],"mode")==nil) then
        print ("lwarpmk: File \"" .. arg[i] .. "\" does not exist.")
    else
        print ("lwarpmk: Converting \"" .. arg[i] .. "\"")
        os.execute ( "pdftocairo -svg " .. arg[i] )
    end -- if
end -- do
end --function


-- Force an update and conclude processing:
function updateanddone ()
print ("lwarpmk: Forcing an update of " .. sourcename ..".tex.")
refreshdate ()
print ("lwarpmk: " .. sourcename ..".tex is ready to be recompiled.")
print ("lwarpmk: Done.")
end -- function


-- Start of the main code: --


-- lwarpmk --version :

if (arg[1] == "--version") then
print ( "lwarpmk: " .. printversion )
```

```
4597
4598 else -- not --version
4599
4600
4601 -- print intro:
4602
4603 print ("lwarpmk: " .. printversion .. "  Automated make for the LaTeX lwarp package.")
4604
4605
4606 -- lwarpmk print:
4607
4608 if arg[1] == "print" then
4609 loadconf ()
4610 if ( latexmk == "true" ) then
4611     print ("lwarpmk: Compiling with: " .. printlatexcmd)
4612     executecheckerror (
4613         printlatexcmd ,
4614         "Compile error."
4615     )
4616     print ("lwarpmk: Done.")
4617 else -- not latexmk
4618     verifyfileexists (sourcename .. ".tex") ;
4619     -- See if up to date:
4620     if (
4621         ( lfs.attributes ( sourcename .. ".pdf" , "modification" ) == nil ) or
4622         (
4623             lfs.attributes ( sourcename .. ".tex" , "modification" ) >
4624             lfs.attributes ( sourcename .. ".pdf" , "modification" )
4625         )
4626     ) then
4627         -- Recompile if not yet up to date:
4628         manytimes(printlatexcmd, "")
4629         print ("lwarpmk: Done.") ;
4630     else
4631         print ("lwarpmk: " .. sourcename .. ".pdf is up to date.") ;
4632     end
4633 end -- not latexmk
4634
4635
4636 -- lwarpmk print1:
4637
4638 elseif arg[1] == "print1" then
4639     loadconf ()
4640     verifyfileexists (sourcename .. ".tex") ;
4641     onetime(printlatexcmd, "")
4642     print ("lwarpmk: Done.") ;
4643
4644
4645 -- lwarpmk printindex:
4646 -- Compile the index then touch the source
4647 -- to trigger a recompile of the document:
4648
4649 elseif arg[1] == "printindex" then
4650 loadconf ()
4651 os.execute ( printindexcmd )
```

```
print ("lwarpmk: -------")
updateanddone ()


-- lwarpmk printglossary:
-- Compile the glossary then touch the source
-- to trigger a recompile of the document:

elseif arg[1] == "printglossary" then
loadconf ()
print ("lwarpmk: Processing the glossary.")

os.execute(glossarycmd .. " " .. sourcename)
updateanddone ()


-- lwarpmk html:

elseif arg[1] == "html" then
loadconf ()
if ( latexmk == "true" ) then
    print ("lwarpmk: Compiling with: " .. HTMLlatexcmd)
    executecheckerror (
        HTMLlatexcmd ,
        "Compile error."
    )
    pdftohtml ()
    print ("lwarpmk: Done.")
else -- not latexmk
    verifyfileexists ( sourcename .. ".tex" ) ;
    -- See if exists and is up to date:
    if (
      ( lfs.attributes ( homehtmlfilename .. ".html" , "modification" ) == nil ) or
        (
            lfs.attributes ( sourcename .. ".tex" , "modification" ) >
            lfs.attributes ( homehtmlfilename .. ".html" , "modification" )
        )
    ) then
        -- Recompile if not yet up to date:
        manytimes(HTMLlatexcmd, "_html")
        pdftohtml ()
        print ("lwarpmk: Done.")
    else
        print ("lwarpmk: " .. homehtmlfilename .. ".html is up to date.")
    end
end -- not latexmk


-- lwarpmk html1:

elseif arg[1] == "html1" then
    loadconf ()
    verifyfileexists ( sourcename .. ".tex" ) ;
    onetime(HTMLlatexcmd, "_html")
    pdftohtml ()
```

```
4707     print ("lwarpmk: Done.")
4708
4709
4710 -- lwarpmk pdftohtml:
4711 elseif arg[1] == "pdftohtml" then
4712     loadconf ()
4713     pdftohtml ()
4714
4715
4716 -- lwarpmk htmlindex:
4717 -- Compile the index then touch the source
4718 -- to trigger a recompile of the document:
4719
4720 elseif arg[1] == "htmlindex" then
4721 loadconf ()
4722 os.execute ( HTMLindexcmd )
4723 print ("lwarpmk: -------")
4724 updateanddone ()
4725
4726
4727 -- lwarpmk htmlglossary:
4728 -- Compile the glossary then touch the source
4729 -- to trigger a recompile of the document.
4730 -- The <sourcename>.xdy file is created by the glossaries package.
4731
4732 elseif arg[1] == "htmlglossary" then
4733 loadconf ()
4734 print ("lwarpmk: Processing the glossary.")
4735 os.execute(glossarycmd .. " " .. sourcename .. "_html")
4736 updateanddone ()
4737
4738
4739 -- lwarpmk limages:
4740 -- Scan the <sourcename>.txt file to create lateximages.
4741
4742 elseif arg[1] == "limages" then
4743 loadconf ()
4744 print ("lwarpmk: Processing images.")
4745 createlateximages ()
4746 print ("lwarpmk: Done.")
4747
4748
4749 -- lwarpmk again:
4750 -- Touch the source to trigger a recompile.
4751
4752 elseif arg[1] == "again" then
4753 loadconf ()
4754 updateanddone ()
4755
4756
4757 -- lwarpmk clean:
4758 -- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
4759
4760 elseif arg[1] == "clean" then
4761 loadconf ()
```

```
removeaux ()
print ("lwarpmk: Done.")


-- lwarpmk cleanall
-- Remove project.aux, .toc, .lof, .lot, .log, *.idx, *.ind, *_html_inc.*, .gl*
--    and also project.pdf, project.dvi, *.html

elseif arg[1] == "cleanall" then
loadconf ()
removeaux ()
os.execute ( rmname .. " " ..
    sourcename .. ".pdf " .. sourcename .. "_html.pdf " ..
    sourcename .. ".dvi " .. sourcename .. "_html.dvi " ..
    "*.html"
    )
print ("lwarpmk: Done.")


-- lwarpmk cleanlimages
-- Remove images from the imagesdirectory.

elseif arg[1] == "cleanlimages" then
loadconf ()
os.execute ( rmname .. " " .. imagesdirectory .. dirslash .. "*" )
print ("lwarpmk: Done.")

-- lwarpmk epstopdf <list of file names>
-- Convert EPS files to PDF using epstopdf
elseif arg[1] == "epstopdf" then
convertepstopdf ()
print ("lwarpmk: Done.")


-- lwarpmk pdftosvg <list of file names>
-- Convert PDF files to SVG using pdftocairo
elseif arg[1] == "pdftosvg" then
convertpdftosvg ()
print ("lwarpmk: Done.")


-- lwarpmk with no argument :

elseif (arg[1] == nil) then
printhelp ()


-- lwarpmk -h or lwarpmk --help :

elseif (arg[1] == "-h" ) or (arg[1] == "--help") then
printusage ()


-- Unknown command:

```

```
else
printhelp ()
print ("\nlwarpmk: ****** Unknown command \""..arg[1].."\". ******\n")
end

end -- not --version
\end{filecontents*}
% \end{Verbatim}% for syntax highlighting

\end{LWR@createlwarpmk}
```

41 Stacks

for HTML output:

```
\begin{warpHTML}
```

Stacks are used to remember how to close sections and list items. Before a new section is started, previously nested sections and items must be closed out (unnested) in proper order. Note that starting a new section may close several levels of previously nested items at the same time. For example, starting a new `\section` would close any currently open subsection, subsubsection, and paragraph. General environments are not nested on the stack since they have their own close mechanism. List environments are nested, and items inside those environments are nested one level deeper still. List environments may be nested inside other list environments, and list items are nested inside list environments as well. Thus, the stack may have items which are not necessarily in order, since a description may contain an enumerate, for example. Depths to be recorded in `\LWR@closedepthone`, etc.

41.1 Assigning depths

initial depths for empty stack entries:

```
\newcommand*{\LWR@depthnone}{-5}
```

all sectioning depths are deeper than `LWR@depthfinished`:

```
\newcommand*{\LWR@depthfinished}{-4}
\newcommand*{\LWR@depthpart}{-1}
\newcommand*{\LWR@depthchapter}{0}
\newcommand*{\LWR@depthsection}{1}
\newcommand*{\LWR@depthsubsection}{2}
\newcommand*{\LWR@depthsubsubsection}{3}
\newcommand*{\LWR@depthparagraph}{4}
\newcommand*{\LWR@depthsubparagraph}{5}
```

Used by `\itemize`, `\enumerate`, `\description`:

```
\newcommand*{\LWR@depthlist}{6}
```

Used by \item:

```
\newcommand*{\LWR@depthlistitem}{7}
\let\LWR@depthdescitem\LWR@depthlistitem
```

41.2 Closing actions

A stack to record the action to take to close each nesting level: Add more levels of stack if necessary for a very deeply nested document, adding to \pushclose and \popclose as well.

```
\newcommand*{\LWR@closeone}{}% top of the stack
\newcommand*{\LWR@closetwo}{}
\newcommand*{\LWR@closethree}{}
\newcommand*{\LWR@closefour}{}
\newcommand*{\LWR@closefive}{}
\newcommand*{\LWR@closesix}{}
\newcommand*{\LWR@closeseven}{}
\newcommand*{\LWR@closeeight}{}
\newcommand*{\LWR@closenine}{}
\newcommand*{\LWR@closeten}{}
\newcommand*{\LWR@closeeleven}{}
\newcommand*{\LWR@closetwelve}{}
```

41.3 Closing depths

A stack to record the depth of each level:

⚠ Note that nested LaTeX structures may push depths which are non-sequential.

Ex:

```
\begin{itemize}
   \item{A}
   \begin{description}
      \item{B}
   \end{description}
\end{itemize}
```

```
\newcommand*{\LWR@closedepthone}{\LWR@depthnone}% top of the stack
\newcommand*{\LWR@closedepthtwo}{\LWR@depthnone}
\newcommand*{\LWR@closedepththree}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfour}{\LWR@depthnone}
\newcommand*{\LWR@closedepthfive}{\LWR@depthnone}
\newcommand*{\LWR@closedepthsix}{\LWR@depthnone}
\newcommand*{\LWR@closedepthseven}{\LWR@depthnone}
\newcommand*{\LWR@closedepteight}{\LWR@depthnone}
\newcommand*{\LWR@closedepthnine}{\LWR@depthnone}
```

```
\newcommand*{\LWR@closedepthten}{\LWR@depthnone}
\newcommand*{\LWR@closedeptheleven}{\LWR@depthnone}
\newcommand*{\LWR@closedepthtwelve}{\LWR@depthnone}
```

41.4 Pushing and popping the stack

\LWR@pushclose {⟨*sectiontype*⟩}

Pushes one return action and its LaTeX depth onto the stacks.

```
\NewDocumentCommand{\LWR@pushclose}{m}
{%
\global\let\LWR@closetwelve\LWR@closeeleven%
\global\let\LWR@closeeleven\LWR@closeten%
\global\let\LWR@closeten\LWR@closenine%
\global\let\LWR@closenine\LWR@closeeight%
\global\let\LWR@closeeight\LWR@closeseven%
\global\let\LWR@closeseven\LWR@closesix%
\global\let\LWR@closesix\LWR@closefive%
\global\let\LWR@closefive\LWR@closefour%
\global\let\LWR@closefour\LWR@closethree%
\global\let\LWR@closethree\LWR@closetwo%
\global\let\LWR@closetwo\LWR@closeone%
\global\csletcs{LWR@closeone}{LWR@printclose#1}%
\global\let\LWR@closedepthtwelve\LWR@closedeptheleven%
\global\let\LWR@closedeptheleven\LWR@closedepthten%
\global\let\LWR@closedepthten\LWR@closedepthnine%
\global\let\LWR@closedepthnine\LWR@closedeptheight%
\global\let\LWR@closedeptheight\LWR@closedepthseven%
\global\let\LWR@closedepthseven\LWR@closedepthsix%
\global\let\LWR@closedepthsix\LWR@closedepthfive%
\global\let\LWR@closedepthfive\LWR@closedepthfour%
\global\let\LWR@closedepthfour\LWR@closedepththree%
\global\let\LWR@closedepththree\LWR@closedepthtwo%
\global\let\LWR@closedepthtwo\LWR@closedepthone%
\global\csletcs{LWR@closedepthone}{LWR@depth#1}%
}
```

\LWR@popclose Pops one action and its depth off the stacks.

```
\newcommand*{\LWR@popclose}
{%
\global\let\LWR@closeone\LWR@closetwo%
\global\let\LWR@closetwo\LWR@closethree%
\global\let\LWR@closethree\LWR@closefour%
\global\let\LWR@closefour\LWR@closefive%
\global\let\LWR@closefive\LWR@closesix%
\global\let\LWR@closesix\LWR@closeseven%
\global\let\LWR@closeseven\LWR@closeeight%
\global\let\LWR@closeeight\LWR@closenine%
\global\let\LWR@closenine\LWR@closeten%
\global\let\LWR@closeten\LWR@closeeleven%
```

```
\global\let\LWR@closeeleven\LWR@closetwelve%
\global\let\LWR@closedepthone\LWR@closedepthtwo%
\global\let\LWR@closedepthtwo\LWR@closedepththree%
\global\let\LWR@closedepththree\LWR@closedepthfour%
\global\let\LWR@closedepthfour\LWR@closedepthfive%
\global\let\LWR@closedepthfive\LWR@closedepthsix%
\global\let\LWR@closedepthsix\LWR@closedepthseven%
\global\let\LWR@closedepthseven\LWR@closedeptheight%
\global\let\LWR@closedeptheight\LWR@closedepthnine%
\global\let\LWR@closedepthnine\LWR@closedepthten%
\global\let\LWR@closedepthten\LWR@closedepththeleven%
\global\let\LWR@closedepththeleven\LWR@closedepthtwelve%
}

\end{warpHTML}
```

42 Data arrays

These macros are similar to the arrayjobx package, except that `\LWR@setexparray`'s argument is expanded only once when assigned.

`name` has no backslash, `index` can be a number or a text name, and an empty `value` must be `\relax` instead of empty.

To assign an empty value:

```
\LWR@setexparray{name}{index}{}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@setexparray` {⟨*name*⟩} {⟨*index*⟩} {⟨*contents*⟩}

```
\NewDocumentCommand{\LWR@setexparray}{m m m}{%
    \begingroup%
    \let\par\relax%
    \xdef\LWR@thisexparrayname{#1#2}%
    \ifstrempty{#3}%
    {\csgdef{\LWR@thisexparrayname}{}}%
    {\csxdef{\LWR@thisexparrayname}{#3}}%
    \endgroup%
}
```

`\LWR@getexparray` {⟨*name*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@getexparray}[2]{%
    \@nameuse{#1#2}%
}

\end{warpHTML}
```

43 Localizing catcodes

for HTML & PRINT:

```
\begin{warpall}
```

⚠ Misplaced alignment tab character &

Place `\StartDefiningTabulars` and `\StopDefiningTabulars` before and after defining macros or environments which include the tabular & character in their definitions.

The catcode of & must be changed before the definitions begin, and must be restored afterwards. Doing so avoids the error

```
Misplaced alignment tab character &.
```

`\StartDefiningTabulars` Place before defining something with & in it.

```
\newcommand{\StartDefiningTabulars}{%
\LWR@traceinfo{StartDefiningTabulars}%
\warpHTMLonly{\catcode`\&=\active}%
}
```

`\StopDefiningTabulars` Place after defining something with & in it.

```
\newcommand{\StopDefiningTabulars}{%
\LWR@traceinfo{StopDefiningTabulars}%
\warpHTMLonly{\catcode`\&=4}%
}
```

`Bool` `LWR@mathmacro` True if currently defining math macros. Used to disable SVG math hashing and MathJax math contents while defining a macro using inline math. Begin a macro, it is not guaranteed that the contents are static, and so the image must be unique. The contents also almost certainly will not be parsed correctly by MathJax.

```
\newbool{LWR@mathmacro}
\boolfalse{LWR@mathmacro}
```

`\StartDefiningMath` Place before defining something with $ in it.

```
\newcommand{\StartDefiningMath}{%
\LWR@traceinfo{StartDefiningMath}%
\warpHTMLonly{\catcode`\$=\active}%
}
```

`\StopDefiningMath` Place after defining something with $ in it.

```
\newcommand{\StopDefiningMath}{%
\LWR@traceinfo{StopDefiningMath}%
\warpHTMLonly{\catcode`\$=3}% math shift
}
```

```
\end{warpall}
```

44 Localizing dynamic math

Inline SVG math usually uses a hash of its contents to generate `lateximages` which are reusable for multiple instances with the same contents. If the contents may change for each use, such as depending on the current value of a counter, then `\inlinemathother` must be used before the inline math expression, and `\inlinemathnormal` must be used after.

For MathJax, the inline math expression is usually printed for MathJax to interpret. When marked as dynamic math, the following inline math expression will be displayed as an unhashed inline SVG image instead.

For existing code and packages, it may be possible to patch macros after they have been defined, using the xpatch package, which is pre-loaded by lwarp:

```
\xpatchcmd{\macroname}
    {$math expression$}
    {\inlinemathother$math expression$\inlinemathnormal}
    {}
    {\typeout{Error patching macroname.}}
```

for HTML & PRINT:

```
\begin{warpall}
```

Bool `LWR@dynamicmath` Default: `false`

True to mark inline math which is dynamic in nature, thus should not be hashed for reuse.

```
\newbool{LWR@dynamicmath}
\boolfalse{LWR@dynamicmath}
```

`\inlinemathother`

Place before using `$ ... $` or `\( ...\)` if the contents of the math are not static, depending on counters or dynamic macros.

```
\newcommand{\inlinemathother}{%
\LWR@traceinfo{inlinemathother}%
\booltrue{LWR@dynamicmath}%
}
```

`\inlinemathnormal`

Place after using `$ ... $` or `\( ...\)` with dynamic contents.

```
\newcommand{\inlinemathnormal}{%
\LWR@traceinfo{inlinemathnormal}%
\boolfalse{LWR@dynamicmath}%
}
```

```
\end{warpall}
```

45 HTML entities

for HTML output:

```
4962 \begin{warpHTML}
```

HTML Unicode entities:

```
4963 \let\LWR@origampersand\&
```

\HTMLentity {⟨*entitytag*⟩}

```
4964 \newcommand*{\HTMLentity}[1]{%
4965 % \LWR@traceinfo{HTMLentity \detokenize{#1}}%
4966 \begingroup%
4967 \LWR@FBcancel%
4968 \LWR@origampersand#1;%
4969 \endgroup%
4970 % \LWR@traceinfo{HTMLentity done}%
4971 }
```

\HTMLunicode {⟨*hex_unicode*⟩}

```
4972 \newcommand*{\HTMLunicode}[1]{\HTMLentity{\LWR@origpound{}x#1}}
```

\&

```
4973 \renewrobustcmd*{\&}{\HTMLentity{amp}}
```

\textless

```
4974 \let\LWR@origtextless\textless
4975 \renewrobustcmd*{\textless}{\HTMLentity{lt}}
```

\textgreater

```
4976 \let\LWR@origtextgreater\textgreater
4977 \renewrobustcmd*{\textgreater}{\HTMLentity{gt}}
```

```
4978 \end{warpHTML}
```

46 HTML filename generation

The filename of the homepage is set to `\HomeHTMLFilename.html`. The filenames of additional sections start with `\HTMLFilename`, to which is appended a section number or a simplified section name, depending on `FileSectionNames`.

for HTML & PRINT:

```
4979 \begin{warpall}
```

\BaseJobname The \jobname of the printed version, even if currently compiling the HTML version. I.e. this is the \jobname without _html appended. This is used to set \HomeHTMLFilename if the user did not provide one.

```
\providecommand*{\BaseJobname}{\jobname}
```

\HTMLFilename The prefix for all generated HTML files other than the home page, defaulting to empty. See section 7.4.1.

```
\providecommand*{\HTMLFilename}{}
```

\HomeHTMLFilename The filename of the home page, defaulting to the \BaseJobname. See section 7.4.1.

```
\providecommand*{\HomeHTMLFilename}{\BaseJobname}
```

\SetHTMLFileNumber {⟨*number*⟩}

Sets the file number for the next file to be generated. 0 is the home page. Use just before the next sectioning command, and set it to one less than the desired number of the next section. May be used to generate numbered groups of nodes such as 100+ for one chapter, 200+ for another chapter, etc.

```
\newcommand*{\SetHTMLFileNumber}[1]{%
\setcounter{LWR@htmlfilenumber}{#1}%
}
```

Bool FileSectionNames Selects how to create HTML file names.

Defaults to use section names in the filenames.

```
\newbool{FileSectionNames}
\booltrue{FileSectionNames}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@htmlfilenumber Records the number of each HTML file as it is being created. Number 0 is the home page.

```
\newcounter{LWR@htmlfilenumber}
\setcounter{LWR@htmlfilenumber}{0}
```

\LWR@htmlsectionfilename {⟨*htmlfilenumber or name*⟩}

Prints the filename for a given section: \HTMLFilename{}filenumber/name.html

```
\newcommand*{\LWR@htmlsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlsectionfilename A !\detokenize{#1}!}%
```

Section 0 or empty is given the home filename. The filename must be detokenized for underscores.

```
% \LWR@traceinfo{about to assign temp}%
\LWR@sanitize{#1}%
\LWR@traceinfo{about to compare with ??}%
\ifthenelse{\equal{\LWR@sanitized}{??}}%
    {\LWR@traceinfo{found ??}}%
    {\LWR@traceinfo{not found ??}}%
\LWR@traceinfo{about to compare with zero or empty}%
\ifthenelse{%
    \equal{\LWR@sanitized}{0}%
    \OR \equal{\LWR@sanitized}{}%
    \OR \equal{\LWR@sanitized}{??}%
}%
{%
    \LWR@traceinfo{LWR@htmlsectionfilename B \HomeHTMLFilename.html}%
    \HomeHTMLFilename.html%
}%
```

For a LaTeX section named “Index” or “index” without a prefix, create a filename with a leading underscore to avoid colliding with the HTML filename `index.html`:

```
{%
    \LWR@traceinfo{LWR@htmlsectionfilename C \LWR@sanitized}%
    \ifthenelse{%
        \equal{\HTMLFilename}{} \AND
        \equal{\LWR@sanitized}{Index} \OR
        \equal{\LWR@sanitized}{index}%
    }%
    {%
        \LWR@traceinfo{Prefixing the index name with an underscore.}%
        \_\LWR@sanitized.html%
    }%
```

Otherwise, create a filename with the chosen prefix:

```
    {%
        \HTMLFilename\LWR@isolate{\LWR@sanitized}.html%
    }%
}%
\LWR@traceinfo{LWR@htmlsectionfilename Z}%
}
```

`\LWR@htmlrefsectionfilename` {⟨*label*⟩}

Prints the filename for the given label

```
\newcommand*{\LWR@htmlrefsectionfilename}[1]{%
\LWR@traceinfo{LWR@htmlrefsectionfilename: !\detokenize{#1}!}%
```

`\LWR@nullfonts` to allow math in a section name.

```
\begingroup%
```

```
\LWR@nullfonts%
\LWR@htmlsectionfilename{\LWR@htmlfileref{#1}}%
\endgroup%
\LWR@traceinfo{LWR@htmlrefsectionfilename: done}%
}
```

```
\end{warpHTML}
```

47 Homepage link

for HTML & PRINT:

```
\begin{warpall}
```

`\linkhomename` Holds the default name for the home link.

```
\newcommand{\linkhomename}{Home}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LinkHome` May be used wherever you wish to place a link back to the homepage. The filename must be detokenized for underscores.

```
\newcommand*{\LinkHome}{%
\LWR@subhyperrefclass{\HomeHTMLFilename.html}{\linkhomename}{linkhome}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

`\LinkHome` May be used wherever you wish to place a link back to the homepage. For print output, if hyperref is available a hyperlink to the first page is used, named by `\linkhomename`. If hyperref is not available, a pageref is used instead.

`\BaseJobname` is included in the link label in case multiple documents are cross-referenced.

```
\AtBeginDocument{
\@ifundefined{hyperref}{
    \newcommand*{\LinkHome}{%
        \linkhomename\ --- page \pageref{\BaseJobname-page-LWRfirstpage}%
    }
}{
    \newcommand*{\LinkHome}{%
        \hyperref[\BaseJobname-page-LWRfirstpage]{\linkhomename}%
    }
}
```

```
}

\AfterEndPreamble{\label{\BaseJobname-page-LWRfirstpage}}

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@topnavigation` Creates a link to the homepage at the top of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@topnavigation}{
\LWR@htmlelementclassline{nav}{topnavigation}{\LinkHome}
}
```

`\LWR@botnavigation` Creates a link to the homepage at the bottom of the page for use when the window is too narrow for the sideTOC.

```
\newcommand*{\LWR@botnavigation}{
\LWR@htmlelementclassline{nav}{botnavigation}{\LinkHome}
}

\end{warpHTML}
```

48 `\LWRPrintStack` diagnostic tool

Diagnostics tool: Prints the LaTeX nesting depth values for the stack levels. `\LWR@startpars` is used before printing the stack, so that `\LWRPrintStack` may be called from anywhere in the normal text flow.

for HTML output:

```
\begin{warpHTML}
```

`\LWRPrintStack` Prints the closedepth stack.

```
\newcommand*{\LWR@subprintstack}{
\LWR@closedepthone\ \LWR@closedepththwo\ \LWR@closedepththree\
\LWR@closedepthfour\ \LWR@closedepthfive\ \LWR@closedepthsix\
\LWR@closedepthseven\ \LWR@closedepthheight\ \LWR@closedepthnine\
\LWR@closedepthten\ \LWR@closedepthheleven\ \LWR@closedepthtwelve\
}

\newcommand*{\LWRPrintStack}{
\LWR@startpars
\LWR@subprintstack
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

```
\newcommand*{\LWRPrintStack}{}

\end{warpprint}
```

49 Closing stack levels

for HTML output:

```
\begin{warpHTML}
```

Close one nested level:

```
\newcommand*{\LWR@closeoneprevious}{%

\LWR@closeone

\LWR@popclose
}
```

`\LWR@closeprevious` {⟨*sectintype*⟩} Close everything up to the given depth:

```
\newcommand*{\LWR@closeprevious}[1]{
\LWR@traceinfo{%
    LWR@closeprevious to depth \csuse{LWR@depth#1}, %
    depths are \LWR@subprintstack%
}%
```

Close any pending paragraph:

```
\LWR@stoppars%
```

Close anything nested deeper than the desired depth. First close anything deeper, then at most one of the same level.

```
\whileboolexpr{test{\ifnumcomp{\LWR@closedepthone}{>}{\csuse{LWR@depth#1}}}}%
{%
    \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
    \LWR@closeoneprevious%
}%
\ifboolexpr{test{\ifnumcomp{\LWR@closedepthone}{=}{\csuse{LWR@depth#1}}}}%
{%
    \LWR@traceinfo{LWR@closeprevious: closing out depth \LWR@closedepthone}%
    \LWR@closeoneprevious%
}{}%
\LWR@traceinfo{LWR@closeprevious: done, depths are \LWR@subprintstack}%
}

\end{warpHTML}
```

50 PDF pages and styles

for HTML output:
```
\begin{warpHTML}
```

\LWR@forcenewpage New PDF page a before major environment.

This is used just before major environments, such as verse. Reduces the chance of an environment overflowing the HTML PDF output page.

```
\newcommand{\LWR@forcenewpage}{%
\LWR@traceinfo{LWR@forcenewpage}%
\ifinner\else%
\LWR@stoppars\LWR@orignewpage\LWR@startpars%
\fi%
}
```

\pagestyle, etc. are nullified for HTML output.

\pagestyle {⟨*style*⟩}

```
\renewcommand*{\pagestyle}[1]{}
```

\thispagestyle {⟨*style*⟩}

```
\renewcommand*{\thispagestyle}[1]{}
```

\markboth {⟨*left*⟩} {⟨*right*⟩}

```
\renewcommand*{\markboth}[2]{}
```

\markright {⟨*right*⟩}

```
\renewcommand*{\markright}[1]{}
```

\raggedbottom

```
\renewcommand*{\raggedbottom}{}
```

\flushbottom

```
\renewcommand*{\flushbottom}{}
```

\sloppy

```
\renewcommand*{\sloppy}{}
```

\fussy

```
\renewcommand*{\fussy}{}
```

\pagenumbering * {⟨*commands*⟩}

```
\RenewDocumentCommand{\pagenumbering}{s m}{}
```

```
\end{warpHTML}
```

51 HTML tags, spans, divs, elements

for HTML output:

```
\begin{warpHTML}
```

51.1 Mapping LaTeX sections to HTML sections

```
\newcommand*{\LWR@tagtitle}{h1}
\newcommand*{\LWR@tagtitleend}{/h1}
\newcommand*{\LWR@tagpart}{h2}
\newcommand*{\LWR@tagpartend}{/h2}
\newcommand*{\LWR@tagchapter}{h3}
\newcommand*{\LWR@tagchapterend}{/h3}
\newcommand*{\LWR@tagsection}{h4}
\newcommand*{\LWR@tagsectionend}{/h4}
\newcommand*{\LWR@tagsubsection}{h5}
\newcommand*{\LWR@tagsubsectionend}{/h5}
\newcommand*{\LWR@tagsubsubsection}{h6}
\newcommand*{\LWR@tagsubsubsectionend}{/h6}
\newcommand*{\LWR@tagparagraph}{span class="paragraph"}
\newcommand*{\LWR@tagparagraphend}{/span}
\newcommand*{\LWR@tagsubparagraph}{span class="subparagraph"}
\newcommand*{\LWR@tagsubparagraphend}{/span}

\newcommand*{\LWR@tagregularparagraph}{p}
```

51.2 Babel-French tag modifications

Adjust babel-french for HTML spaces. So far, this only works for *pdflatex* and *xelatex*.

(*Emulates or patches code by* Daniel Flipo.)

```
\providecommand*{\LWR@FBcancel}{}

\AtBeginDocument{%
\@ifundefined{frenchbsetup}%
{}%
{%
    \frenchbsetup{FrenchFootnotes=false}%

%
    \LetLtxMacro\LWR@FBcancel\NoAutoSpacing%
    \renewrobustcmd*{\FBcolonspace}{%
```

```
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;%
        \endgroup%
    }%
    \renewrobustcmd*{\FBthinspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \renewrobustcmd*{\FBguillspace}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;% ~,  for \og xyz \fg{}
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBmedkern}{}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand\LWR@origpound{}x202f;% \,
        \endgroup%
    }%
    \DeclareDocumentCommand{\FBthickkern}{}{%
        \begingroup%
        \LWR@FBcancel%
        \LWR@origampersand{}nbsp;% ~
        \endgroup%
    }%
    \renewrobustcmd*{~}{\HTMLentity{nbsp}}% was overwritten by babel-french
    \ifFBunicode%
    \else%
        \DeclareTextSymbol{\FBtextellipsis}{LY1}{133}%
        \DeclareTextCommandDefault{\FBtextellipsis}{\textellipsis\xspace}%
    \fi%
}%
}
```

51.3 HTML output formatting

Helps format the output HTML code for human readability.

`\LWR@indentHTML` Newline and indent the output HTML code.

```
\newcommand*{\LWR@indentHTML}{%
    \LWR@orignewline\LWR@origrule{2em}{0pt}%
}
```

51.4 HTML tags

\LWR@htmltagc {⟨*tag*⟩} Break ligatures and use upright apostrophes in HTML tags.

\protect is in case the tag appears in TOC, LOF, LOT.

```
\newcommand*{\LWR@htmltagc}[1]{%
\LWR@traceinfo{LWR@htmltagc !\detokenize{#1}!}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\protect\LWR@origtextless%
\LWR@isolate{#1}%
\protect\LWR@origtextgreater%
\endgroup%
}
```

Env LWR@nestspan Disable minipage, \parbox, and HTML s inside a .

⚠ \begin{LWR@nestspan} must follow the opening tag to allow a paragraph to start if the span is at the beginning of a new paragraph.

⚠ \end{LWR@nestspan} must follow the or a <p> may appear inside the span.

```
\newcommand*{\LWR@nestspanitem}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}

\newenvironment*{LWR@nestspan}
{%
\LWR@traceinfo{LWR@nestspan starting}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
    \LWR@traceinfo{LWR@nestspan: inside a lateximage}%
}%
{% not in a lateximage
    \LWR@traceinfo{LWR@nestspan: NOT inside a lateximage}%
    \addtocounter{LWR@spandepth}{1}%
    \RenewDocumentEnvironment{minipage}{O{t} o O{t} m}%
        {\LWR@subhtmlelementclass{span}{inlineminipage}}%
        {\LWR@htmltagc{/span}}%
    \RenewDocumentEnvironment{BlockClass}{o m}{}{}%
    \renewcommand{\BlockClassSingle}[2]{##2}%
    \renewcommand{\LWR@forcenewpage}{}%
    \renewcommand{\LWR@liststart}{%
        \let\item\LWR@nestspanitem%
    }%
    \renewcommand{\LWR@listend}{\LWR@htmltagc{br /}\LWR@htmltagc{br /}}%
}% not in a lateximage
\LWR@traceinfo{LWR@nestspan starting: done}%
}% starting env
{% ending env
\LWR@traceinfo{LWR@nestspan ending}%
```

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{\addtocounter{LWR@spandepth}{-1}}%
\LWR@traceinfo{LWR@nestspan ending: done}%
}

\AfterEndEnvironment{LWR@nestspan}{\global\let\par\LWR@closeparagraph}
```

`\LWR@htmlspan` {⟨*tag*⟩} {⟨*text*⟩}

`\LWR@spandepth` is used to ensure that paragraph tags are not generated inside a span. The exact sequence of when to add and subtract the counter is important to correctly handle the paragraph tags before and after the span.

```
\NewDocumentCommand{\LWR@htmlspan}{m +m}{%
\LWR@ensuredoingapar%
\LWR@htmltagc{#1}%
\begin{LWR@nestspan}%
#2%
\LWR@htmltagc{/#1}%
\end{LWR@nestspan}%
}
```

`\LWR@htmlspanclass` [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlspanclass}{o m +m}{%
\LWR@traceinfo{LWR@htmlspanclass |#1|#2|}%
\LWR@ensuredoingapar%
\LWR@subhtmlelementclass{span}[#1]{#2}%
\begin{LWR@nestspan}%
#3%
\LWR@htmltagc{/span}%
\LWR@traceinfo{LWR@htmlspanclass done}%
\end{LWR@nestspan}%
}
```

`\LWR@htmltag` {⟨*tag*⟩}

Print an HTML tag: <tag>

```
\newcommand*{\LWR@htmltag}[1]{%
% \LWR@traceinfo{LWR@htmltagb !\detokenize{#1}!}%
\LWR@htmltagc{#1}%
% \LWR@traceinfo{LWR@htmltagb: done}%
}
```

51.5 Block tags and comments

In the following, `\origttfamily` breaks ligatures, which may not be used for HTML codes:

\LWR@htmlopencomment
\LWR@htmlclosecomment

```
\newcommand*{\LWR@htmlopencomment}{%
{%
% \LWR@traceinfo{LWR@htmlopencomment}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\LWR@print@mbox{\LWR@origtextless{}!-\/-}%
\endgroup%
}%
}

\newcommand*{\LWR@htmlclosecomment}{%
{%
% \LWR@traceinfo{LWR@htmlclosecomment}%
\begingroup%
\LWR@FBcancel%
\ifmmode\else\protect\LWR@origttfamily\fi%
\LWR@print@mbox{-\/-\LWR@origtextgreater}%
\endgroup%
}%
}
```

\LWR@htmlcomment {⟨*comment*⟩}

```
\newcommand{\LWR@htmlcomment}[1]{%
\LWR@htmlopencomment{}%
{%
\LWR@origttfamily% break ligatures
#1%
}%
\LWR@htmlclosecomment{}}
```

\LWR@htmlblockcomment {⟨*comment*⟩}

```
\newcommand{\LWR@htmlblockcomment}[1]
{\LWR@stoppars\LWR@htmlcomment{#1}\LWR@startpars}
```

\LWR@htmlblocktag {⟨*tag*⟩} print a stand-alone HTML tag

```
\newcommand*{\LWR@htmlblocktag}[1]{%
\LWR@stoppars%
\LWR@htmltag{#1}%
\LWR@startpars%
}
```

51.6 Div class and element class

\LWR@subhtmlelementclass {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩}

Factored and reused in several places.

The trailing spaces allow more places for a line break.

The use of \textquotedbl instead of " provides improved compatibility with xeCJK.

```
\NewDocumentCommand{\LWR@subhtmlelementclass}{m O{} m}{%
\LWR@traceinfo{LWR@subhtmlelementclass !#1!#2!#3!}%
\ifblank{#2}%
{% empty option
    \LWR@htmltag{%
        #1 % space
        class=\textquotedbl#3\textquotedbl\ % space
    }%
}%
{% non-empty option
    \LWR@htmltag{%
        #1\LWR@indentHTML%
        class=\textquotedbl#3\textquotedbl\LWR@indentHTML%
        style=\textquotedbl#2\textquotedbl\LWR@orignewline%
    }%
}%
\LWR@traceinfo{LWR@subhtmlelementclass done}%
}
```

\LWR@htmlelementclass {⟨*element*⟩} {⟨*class*⟩} [⟨*style*⟩]

```
\NewDocumentCommand{\LWR@htmlelementclass}{m o m}{%
\LWR@stoppars%
\LWR@subhtmlelementclass{#1}[#2]{#3}%
\LWR@startpars%
}
```

\LWR@htmlelementclassend {⟨*element*⟩} {⟨*class*⟩}

```
\newcommand*{\LWR@htmlelementclassend}[2]{%
\LWR@stoppars%
\LWR@htmltag{/#1}%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{End of #1 ‘‘#2’’}%
}{}%
\LWR@startpars%
}
```

\LWR@htmldivclass [⟨*style*⟩] {⟨*class*⟩}

```
\NewDocumentCommand{\LWR@htmldivclass}{o m}{%
\LWR@htmlelementclass{div}[#1]{#2}%
}
```

\LWR@htmldivclassend {⟨*class*⟩}

```
\newcommand*{\LWR@htmldivclassend}[1]{%
\LWR@htmlelementclassend{div}{#1}%
}
```

51.7 Single-line elements

A single-line element, without a paragraph tag for the line of text:

`\LWR@htmlelementclassline` {⟨*element*⟩} [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlelementclassline}{m o m +m}{%
\LWR@stoppars
\LWR@subhtmlelementclass{#1}[#2]{#3}%
#4%
\LWR@htmltag{/#1}
\LWR@startpars
}
```

51.8 HTML5 semantic elements

`\LWR@htmlelement` {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelement}[1]{%
\LWR@htmlblocktag{#1}
}
```

`\LWR@htmlelementend` {⟨*element*⟩}

```
\newcommand*{\LWR@htmlelementend}[1]{%
\LWR@stoppars
\LWR@htmltag{/#1}
\LWR@startpars
}

\end{warpHTML}
```

51.9 High-level block and inline classes

These are high-level commands which allow the creation of arbitrary block or inline sections which may be formatted with css.

Nullified versions are provided for print mode.

For other direct-formatting commands, see section 90.

Env `BlockClass` [⟨*style*⟩] {⟨*class*⟩} High-level interface for classes.

Ex: \begin{BlockClass}{class} text \end{BlockClass}

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{BlockClass}{o m}{}{}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@BlockClass}{o m}{}{}%
\NewDocumentEnvironment{LWR@HTML@BlockClass}{o m}%
{%
    \LWR@origpar%
    \LWR@htmldivclass[#1]{#2}%
}
{\LWR@htmldivclassend{#2}}

\LWR@formattedenv{BlockClass}
\end{warpHTML}
```

`\BlockClassSingle` {⟨*class*⟩} {⟨*text*⟩} A single-line , without a paragraph tag for the line of text.

for HTML & PRINT:

```
\begin{warpall}
\newcommand{\BlockClassSingle}[2]{#2}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
\newcommand{\LWR@HTML@BlockClassSingle}[2]{%
\LWR@origpar%
\LWR@htmlelementclassline{div}{#1}{#2}%
}

\LWR@formatted{BlockClassSingle}
\end{warpHTML}
```

`\InlineClass` (⟨*WP style*⟩) [⟨*style*⟩] {⟨*class*⟩} {⟨*text*⟩}

High-level interface for inline span classes.

(⟨*WP style*⟩) is css styling to add when formatting for a word processor import.

[⟨*style*⟩] is the css styling to add when not formatting for a word processor.

for PRINT output:

```
\begin{warpprint}
\NewDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{#4}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentCommand{\LWR@print@InlineClass}{D{(}{)}{} o m +m}{#4}%

\NewDocumentCommand{\LWR@HTML@InlineClass}{D{(}{)}{} o m +m}{%
\ifbool{FormatWP}{%
    \LWR@htmlspanclass[#1]{#3}{#4}%
}{%
```

```
    \LWR@htmlspanclass[#2]{#3}{#4}%
}%
}

\LWR@formatted{InlineClass}
\end{warpHTML}
```

Env LWR@BlockClassWP {⟨*WPstyle*⟩} {⟨*HTMLstyle*⟩} {⟨*class*⟩} Low-level interface for classes with an automatic float ID. These are often used when \ifbool{FormatWP}.

The use of \textquotedbl instead of " provides improved compatibility with xeCJK.

for PRINT output:

```
\begin{warpprint}
\NewDocumentEnvironment{LWR@BlockClassWP}{m m m}{}{}%
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
\NewDocumentEnvironment{LWR@print@LWR@BlockClassWP}{m m m}{}{}%
\NewDocumentEnvironment{LWR@HTML@LWR@BlockClassWP}{m m m}%
{%
\LWR@stoppars%
\ifbool{FormatWP}%
{%
    \addtocounter{LWR@thisautoidWP}{1}%

    \LWR@htmltag{%
        div class=\textquotedbl#3\textquotedbl\ % space
        id=\textquotedbl%
            \LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}%
        \textquotedbl%
        \ifblank{#1}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
}% FormatWP
{% not FormatWP
    \LWR@htmltag{%
        div class=\textquotedbl#3\textquotedbl%
        \ifblank{#2}{}{ style=\textquotedbl#2\textquotedbl}%
    }%
}% not FormatWP
\LWR@startpars%
}
{\LWR@htmldivclassend{#3}}

\LWR@formattedenv{LWR@BlockClassWP}
\end{warpHTML}
```

51.10 Closing HTML tags

for HTML output:

```
\begin{warpHTML}
```

Sections H1, H2, etc. do not need a closing HTML tag, but we add a comment for readability:

```
\newcommand*{\LWR@printclosepart}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing part}}{}}
\newcommand*{\LWR@printclosechapter}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing chapter}}{}}
\newcommand*{\LWR@printclosesection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing section}}{}}
\newcommand*{\LWR@printclosesubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsection}}{}}
\newcommand*{\LWR@printclosesubsubsection}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subsubsection}}{}}
\newcommand*{\LWR@printcloseparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing paragraph}}{}}
\newcommand*{\LWR@printclosesubparagraph}
    {\ifbool{HTMLDebugComments}{\LWR@htmlcomment{Closing subparagraph}}{}}
```

Lists require closing HTML tags:

```
\newcommand*{\LWR@printcloselistitem}
    {\LWR@htmltag{/li}}
\newcommand*{\LWR@printclosedescitem}
    {\LWR@htmltag{/dd}}
\newcommand*{\LWR@printcloseitemize}
    {\LWR@htmltag{/ul}}
\newcommand*{\LWR@printcloseenumerate}
    {\LWR@htmltag{/ol}}
\newcommand*{\LWR@printclosedescription}
    {\LWR@htmltag{/dl}}
```

```
\end{warpHTML}
```

52 Paragraph handling

These commands generate the HTML paragraph tags when allowed and required.

Paragraph tags are or are not allowed depending on many conditions. Section 53 has high-level commands which allow paragraph-tag generation to start/stop. Even when allowed (`\LWR@doingstartpars`), tags are not generated until a LaTeX paragraph is being used (`\LWR@doingapar`). `LWR@lateximagedepth` is used to prevent nesting tags inside a `lateximage`. `LWR@spandepth` is used to prevent nesting paragraph tags inside a paragraph, which became important inside `\fbox` commands and other spans.

for HTML output:

```
\begin{warpHTML}
```

Ctr `LWR@spandepth`

Do not create paragraph tags inside of an HTML span.

```
\newcounter{LWR@spandepth}
\setcounter{LWR@spandepth}{0}
```

Bool LWR@doingstartpars Tells whether paragraphs may be generated.

```
\newbool{LWR@doingstartpars}
\boolfalse{LWR@doingstartpars}
```

Bool LWR@doingapar Tells whether have actually generated and are currently processing paragraph text.

```
\newbool{LWR@doingapar}
\global\boolfalse{LWR@doingapar}
```

\LWR@ensuredoingapar If are about to print something visible, and if allowed to start a new paragraph, ensure that are LWR@doingapar, so that paragraph tags are placed:

```
\newcommand*{\LWR@ensuredoingapar}{%
\ifbool{LWR@doingstartpars}%
{\global\booltrue{LWR@doingapar}}%
{}%
}
```

\PN@parnotes@auto Redefined by parnotes to print paragraph notes at the end of each paragraph.

```
\def\PN@parnotes@auto{}%
```

\LWR@openparagraph

```
\newcommand*{\LWR@openparagraph}
{%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingstartpars}%
{% handling pars
```

See if have already started a lateximage or a . If so, do not generate nested paragraph tags.

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }% nested par tags?
```

If so: Do nothing if already started a lateximage page. Cannot nest a lateximage. Also do nothing if already inside a . Do not nest paragraph tags inside a .

```
    {}% no nested par tags
```

Else: No lateximage or has been started yet, so it's OK to generate paragraph tags.

```
    {% yes nest par tags
```

If parnotes is used, paragraph notes are inserted before starting the next paragraph:

```
        \PN@parnotes@auto%
```

The opening paragraph tag:

```
        \LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline%
```

Now have started a paragraph.

```
        \global\booltrue{LWR@doingapar}%
```

At the endof each paragraph, generate closing tag and do regular /par stuff. (Attempting to use the everyhook cr hook for \LWR@closeparagraph does not work well.)

```
        \let\par\LWR@closeparagraph%
    }% end of yes nest par tags
}% end of handling pars
{}% not handling pars
}
```

\LWR@closeparagraph@br Add an HTML break if in a span, and not in a lateximage, and not in tabular metadata. Factored from \LWR@closeparagraph.

```
\newcommand*{\LWR@closeparagraph@br}
{%
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}} and
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}} and
        not bool {LWR@intabularmetadata}
    }%
        {\unskip\LWR@htmltagc{br /}}%
        {}%
}
```

\LWR@closeparagraph

```
\newcommand*{\LWR@closeparagraph}
{%
% \LWR@traceinfo{LWR@closeparagraph}%
```

See if paragraph handling is enabled:

```
\ifbool{LWR@doingapar}%
```

If currently in paragraph mode:

```
{% handling pars
```

See if already started a lateximage or a :

```
    \ifboolexpr{
        test {\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}} or
        test {\ifnumcomp{\value{LWR@spandepth}}{>}{0}}
    }%
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
    {% no nested par tags
        \LWR@closeparagraph@br%
    }% no nested par tags
```

If have not already started a lateximage or a :

```
    {% yes nest par tags
```

Print a closing tag and some extra vertical space.

(The fill seems to be required to force the caption package to create flush left caption text in the HTML.)

```
        \@hspacer{\fill}% \hspace*{\fill}
        \leavevmode\LWR@orignewline%
        \LWR@htmltagc{/\LWR@tagregularparagraph}%
```

No longer doing a paragraph:

```
        \global\boolfalse{LWR@doingapar}%
```

Disable the special minipage & \hspace interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}%
```

If parnotes is used, paragraph notes are inserted after ending the previous paragraph:

```
        \PN@parnotes@auto%
    }% end of yes nest par tags
}% end of handling pars
```

Add a parbreak if in a span, not in a lateximage, and not in table metadata.

```
{% not handling pars
    \LWR@closeparagraph@br%
}% not handling pars
```

In most cases, finish with a LaTeX \par, but in the case of paragraphs between lines in a tabular fetch the next token instead:

```
\ifboolexpr{%
    not bool {LWR@doingapar} and
    test {\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}} and
```

```
    test {
        \ifnumcomp{\value{LWR@tabulardepth}}{=}{\value{LWR@tabularpardepth}}
    } and
    bool {LWR@intabularmetadata} and
    not bool {LWR@tableparcell} and
    test {\ifnumcomp{\value{LWR@lateximagedepth}}{=}{0}}
}%
{%
    \LWR@getmynexttoken%
}{%
    \LWR@origpar%
}%
}

\end{warpHTML}
```

53 Paragraph start/stop handling

These commands allow/disallow the generation of HTML paragraph tags.

Section 52 has the commands which actually generate the tags.

The everyhook package is used to generate the opening paragraph tags. The closing tags are generated by \par.

for HTML output:

```
\begin{warpHTML}
```

\LWR@startpars

Begin handling HTML paragraphs. This allows an HTML paragraph to start, but one has not yet begun.

```
\newcommand*{\LWR@startpars}%
{%
% \LWR@traceinfo{LWR@startpars}%
```

Ignore if inside a span:

```
\ifnumcomp{\value{LWR@spandepth}}{>}{0}%
{}%
{%
```

See if currently handling HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If already in paragraph mode, do nothing.

```
    {}%
```

If not currently in paragraph mode:

```
    {%
```

At the start of each paragraph, generate an opening tag:

```
5544         \PushPreHook{par}{\LWR@openparagraph}%
```

At the end of each paragraph, generate closing tag then do regular /par actions:

```
5545         \let\par\LWR@closeparagraph
5546
5547     }% an intentionally blank line
```

Are now handling paragraphs, but have not yet actually started one:

```
5548     \global\setbool{LWR@doingstartpars}{true}%
```

No <par> tag yet to undo:

```
5549     \global\boolfalse{LWR@doingapar}%
5550 }% nestspan
5551 % \LWR@traceinfo{LWR@startpars: done}%
5552 }
```

\LWR@stoppars Stop handling HTML paragraphs. Any currently open HTML paragraph is closed, and no more will be opened.

```
5553 \newcommand*{\LWR@stoppars}%
5554 {%
```

Ignore if inside a span:

```
5555 \ifnumcomp{\value{LWR@spandepth}}{>}{0}%
5556 {}%
5557 {%
```

See if currently handling HTML paragraphs:

```
5558     \ifbool{LWR@doingapar}%
```

if currently in an HTML paragraph:

```
5559     {%
```

Print a closing tag:

```
5560         \leavevmode\LWR@orignewline%
5561         \LWR@htmltagc{/\LWR@tagregularparagraph}%
5562         \LWR@orignewline%
```

No longer have an open HTML paragraph:

```
5563         \global\boolfalse{LWR@doingapar}%
```

Disable the special minipage & \hspace interaction until a new minipage is found:

```
        \global\boolfalse{LWR@minipagethispar}
    }%
```

If was not in an HTML paragraph:

```
    {}%
```

See if currently allowing HTML paragraphs:

```
    \ifbool{LWR@doingstartpars}%
```

If so: clear the par hook to no longer catch paragraphs:

```
        {\ClearPreHook{par}}%
```

Else: Do nothing:

```
        {}%
```

No longer in paragraph mode:

```
    \global\setbool{LWR@doingstartpars}{false}%
```

No <p> tag to undo:

```
    \global\boolfalse{LWR@doingapar}%
}% nestspan
}
```

```
\end{warpHTML}
```

54 Indentfirst

Pkg indentfirst indentfirst redefines \@afterindentfalse to be \@afterindenttrue. This is reversed \AtBeginDocument here.

for HTML output:

```
\begin{warpHTML}
```

```
\AtBeginDocument{
\def\@afterindentfalse{\let\if@afterindent\iffalse}
\@afterindentfalse
}
\let\LWR@afterindent@syntaxhighlight\fi% syntax highlighting
```

```
\end{warpHTML}
```

55 Page headers and footers

for HTML & PRINT:
```
\begin{warpall}
```

In the following, catcode is manually changed back and forth without groups, since new macros are being defined which must not be contained within the groups.

```
\newcommand{\LWR@firstpagetop}{} % for the home page alone
\newcommand{\LWR@pagetop}{} % for all other pages
\newcommand{\LWR@pagebottom}{}
```

`\HTMLFirstPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLFirstPageTop}[1]{%
    \renewcommand{\LWR@firstpagetop}{#1}%
}
```

`\HTMLPageTop` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageTop}[1]{%
    \renewcommand{\LWR@pagetop}{#1}%
}
```

`\HTMLPageBottom` {⟨*text and logos*⟩}

```
\newcommand{\HTMLPageBottom}[1]{%
    \renewcommand{\LWR@pagebottom}{#1}%
}
```

```
\end{warpall}
```

56 css

for HTML output:
```
\begin{warpHTML}
```

`\LWR@currentcss` The css filename to use. This may be changed mid-document using `\CSSFilename`, allowing different css files to be used for different sections of the document.

```
\newcommand*{\LWR@currentcss}{lwarp.css}
```

`\CSSFilename` {⟨*new-css-filename.css*⟩} Assigns the css file to be used by the following HTML pages.

```
\newcommand*{\CSSFilename}[1]{%
\renewcommand*{\LWR@currentcss}{#1}%
\@onelevel@sanitize\LWR@currentcss%
```

```
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\CSSFilename}[1]{}
\end{warpprint}
```

57 MathJax script

for HTML output:

```
\begin{warpHTML}
```

Default: `lwarp_mathjax.txt`

`\LWR@mathjaxfilename` The MathJax script filename to use. This file is copied into the head of each HTML page. This may be changed mid-document using `\MathJaxFilename`, allowing the use of a custom MathJax script, such as for a local repository, or different MathJax script files to be used for different sections of the document.

```
\newcommand*{\LWR@mathjaxfilename}{lwarp_mathjax.txt}
```

`\MathJaxFilename` {⟨*filename*⟩} Assigns the MathJax script file to be used by the following HTML pages.

```
\newcommand*{\MathJaxFilename}[1]{%
    \renewcommand*{\LWR@mathjaxfilename}{#1}%
    \@onelevel@sanitize\LWR@mathjaxfilename%
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
\newcommand*{\MathJaxFilename}[1]{}
\end{warpprint}
```

58 Title, HTML meta author, HTML meta description

for HTML output:

```
\begin{warpHTML}
```

`\title` {⟨*title*⟩} Modified to remember `\thetitle`, which is used to set the HTML page titles.

```
\let\LWR@origtitle\title

\renewcommand*{\title}[1]{%
    \LWR@origtitle{#1}%
    \begingroup%
```

```
        \renewcommand{\thanks}[1]{}%
        \protected@xdef\thetitle{#1}%
    \endgroup%
}

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

`\HTMLTitle` {⟨*Titlename*⟩} The Title to place into an HTML meta tag. The default is to use the document `\title`'s setting.

```
\providecommand{\thetitle}{}

\newcommand{\theHTMLTitle}{\thetitle}

\newcommand{\HTMLTitle}[1]{\renewcommand{\theHTMLTitle}{#1}}
```

`\HTMLAuthor` {⟨*authorname*⟩} The author to place into an HTML meta tag. If none given, the default is `\theauthor`, which is empty unless the titling package is used.

```
\providecommand{\theauthor}{}

\newcommand{\theHTMLAuthor}{\theauthor}

\newcommand{\HTMLAuthor}[1]{\renewcommand{\theHTMLAuthor}{#1}}
```

This is placed inside an HTML meta tag at the start of each file. This may be changed mid-document using `\HTMLDescription`, allowing different HTML descriptions to be used for different sections of the document.

⚠ HTML author Do not use double quotes, and do not exceed 150 characters.

`\HTMLDescription` {⟨*New HTML meta description.*⟩} Assigns the HTML file's description meta tag.

```
\newcommand{\LWR@currentHTMLDescription}{}

\newcommand{\HTMLDescription}[1]{%
\renewcommand{\LWR@currentHTMLDescription}{#1}
}

\end{warpall}
```

59 Footnotes

lwarp uses native LaTeX footnote code, although with its own `\box` to avoid the LaTeX output routine. The usual functions mostly work as-is.

footnote numbering

To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for \alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

footmisc

The footmisc stable option is emulated by lwarp.

⚠ sectioning commands

When using footnotes in sectioning commands, to generate consistent results between print and HTML, use the footmisc package with the stable option, provide a short TOC entry, and \protect the \footnote:

```
\usepackage[stable]{footmisc}
. . .
\subsection[Subsection Name]
    {Subsection Name\protect\footnote{A footnote.}}
```

memoir with footmisc

⚠ memoir

If using memoir class, with which lwarp preloads footmisc, the stable option must be declared before lwarp is loaded:

```
\PassOptionsToPackage{stable}{footmisc}
\usepackage{lwarp}
. . .
```

Do not use a starred sectioning command. As an alternative, it may be possible to adjust \secnumdepth instead.

Several kinds of footnotes are used: in a regular page, in a minipage, or as thanks in the titlepage. Each of these is handle differently.

59.1 Regular page footnotes

In HTML documents, footnotes are placed at the bottom of the web page or the section, depending on FootnoteDepth, using the LaTeX box \LWR@footnotebox. Using this instead of the original \footins box avoids having footnotes be printed by the output routine, since footnotes should be printed per HTML page instead of per PDF page.

See section 59.4 for the implementation.

59.2 Minipage footnotes

See section 59.5 for how minipage footnotes are gathered. See section 89.3 for how minipage footnotes are placed into the document.

59.3 Titlepage thanks

See section 66.7 for titlepage footnotes.

59.4 Regular page footnote implementation

for HTML & PRINT:

```
\begin{warpall}
```

Ctr `FootnoteDepth` Default: 3

Determines how deeply to place footnotes in the HTML files, similar to `tocdepth`. The default of 3 places footnotes before each `\subsubsection` or higher. See table 9 for a table of LaTeX section headings.

```
\newcounter{FootnoteDepth}
\setcounter{FootnoteDepth}{3}
```

Ctr `footnoteReset` Default: 0

If non-zero, the `footnote` counter is reset to this value each time the footnotes are printed, as controlled by `FootnoteDepth`. For the manyfoot and bigfoot packages, additional counters such as `footnote<suffix>Reset` will be defined as well. These counters may be set non-zero by the user, and are also set if the perpage's `\MakePerPage` or `\MakeSortedPerPage` macros are used for the `footnote` or `footnote<suffix>` counters.

(The name is not capitalized because it is made from the counter's name with "Reset" appended.)

```
\newcounter{footnoteReset}
\setcounter{footnoteReset}{0}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@footnotebox` Patch LaTeX footnotes to use a new `\box` instead of an insert for lwarp footnotes. This avoids having the original `\footins` appear at the bottom of a `lateximage`, which is on its own new page.

```
\newbox\LWR@footnotebox
```

Much of the following has unneeded print-mode formatting removed.

`\@makefntext` {⟨*text*⟩}

```
\long\def\@makefntext#1{\textsuperscript{\@thefnmark}~#1}
```

\@makefnmark

```
\def\@makefnmark{%
    \textsuperscript{\@thefnmark}%
}
```

Footnotes may be in regular text, in which case paragraphs are tagged, or in a table data cell or lateximage, in which case paragraph tags must be added manually.

In a lateximage during HTML output, the lateximage is placed inside a print-mode minipage, but the footnotes are broken out by:

```
\def\@mpfn{footnote}
\def\thempfn{\thefootnote}
\let\@footnotetext\LWR@footnotetext
```

\LWR@@footnotetext {⟨*text*⟩} {⟨*footnote box name*⟩}

Factored to allow multiple footnote boxes for manyfoot.

```
\long\def\LWR@@footnotetext#1#2{%
\LWR@traceinfo{LWR@footnotetext}%
\global\setbox\csname #2\endcsname=\vbox{%
```

Add to any current footnotes:

```
    \unvbox\csname #2\endcsname%
```

Remember the footnote number for \ref:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Open a group:

```
    \color@begingroup%
```

Use HTML superscripts in the footnote even inside a lateximage:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{#1}%
```

Closing paragraph tag:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {\par}%
        {%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@orignewline%
        }%
```

Close the group:

```
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
}%
```

`\LWR@footnotetext` {⟨*text*⟩}

```
\long\def\LWR@footnotetext#1{\LWR@@footnotetext{#1}{LWR@footnotebox}}
```

`\@footnotetext` {⟨*text*⟩}

```
\LetLtxMacro\@footnotetext\LWR@footnotetext
```

59.5 Minipage footnote implementation

Patch LaTeX minipage footnotes to use a new \box instead of an insert for lwarp minipage footnotes. This avoids having the original `\@mpfootins` appear at the bottom of a `lateximage`, which is on its own new page.

```
\newbox\LWR@mpfootnotes
```

`\@mpfootnotetext` {⟨*text*⟩}

```
\long\def\@mpfootnotetext#1{%
\LWR@traceinfo{@mpfootnotetext}%
\global\setbox\LWR@mpfootnotes\vbox{%
    \unvbox\LWR@mpfootnotes%
    \reset@font\footnotesize%
    \hsize\columnwidth%
    \@parboxrestore%
```

```
    \protected@edef\@currentlabel%
        {\csname p@mpfootnote\endcsname\@thefnmark}%
    \color@begingroup%
```

Use paragraph tags if in a tabular data cell or a lateximage:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%

    \@makefntext{%
        \ignorespaces#1%
    }%
```

Don't add the closing paragraph tag if are inside a lateximage:

```
    \ifthenelse{\cnttest{\value{LWR@lateximagedepth}}{>}{0}}%
        {}%
        {%
            \leavevmode\LWR@orignewline%
            \LWR@htmltagc{/\LWR@tagregularparagraph}%
            \LWR@origpar%
        }%
    \color@endgroup%
}% vbox
```

Paragraph handling:

```
\LWR@ensuredoingapar%
\LWR@traceinfo{@mpfootnotetext: done}%
}
```

\thempfootnote Redefined to remove the \itshape, which caused an obscure compiling error in some situations.

```
\AtBeginDocument{
\def\thempfootnote{\@alph\c@mpfootnote}
}
```

59.6 Printing pending footnotes

\LWR@@printpendingfootnotes {⟨*footnote counter name*⟩}

```
\newcommand*{\LWR@@printpendingfootnotes}[1]{%
\expandafter\ifvoid\csname LWR@#1box\endcsname\else
    \LWR@forcenewpage
    \begin{BlockClass}{footnotes}
```

```
    \LWR@origmedskip
    \unvbox\csuse{LWR@#1box}
    \setbox\csuse{LWR@#1box}=\vbox{}
    \end{BlockClass}
    \ifltxcounter{#1Reset}{%
        \ifnumgreater{\value{#1Reset}}{0}{%
            \setcounter{#1}{\value{#1Reset}}%
            \addtocounter{#1}{-1}%
        }{}%
    }{}%
\fi
}
```

`\LWR@printpendingfootnotes` Enclose the footnotes in a class, print, then clear. For manynotes, new footnotes may be added via `\appto`.

```
\newcommand*{\LWR@printpendingfootnotes}{%
    \LWR@@printpendingfootnotes{footnote}%
}
```

`\LWR@maybeprintpendingfootnotes` {⟨*depth*⟩} Used to print footnotes before sections only if formatting for an EPUB or word processor:

```
\newcommand*{\LWR@maybeprintpendingfootnotes}[1]{%
\ifboolexpr{
    not test{\ifnumcomp{#1}{>}{\value{FootnoteDepth}}} or
    bool{FormatEPUB} or
    bool{FormatWP}
}%
{\LWR@printpendingfootnotes}%
{}%
}
```

`\LWR@printpendingmpfootnotes` Enclose the minipage footnotes in a class, print, then clear.

```
\newcommand*{\LWR@printpendingmpfootnotes}{%
\ifvoid\LWR@mpfootnotes\else
    \LWR@forcenewpage
    \begin{BlockClass}{footnotes}
    \LWR@print@vspace*{\baselineskip}
    \unvbox\LWR@mpfootnotes
    \setbox\LWR@mpfootnotes=\vbox{}
    \end{BlockClass}
\fi
}
```

```
\end{warpHTML}
```

60 Marginpars

\marginpar [⟨*left*⟩] {⟨*right*⟩} \marginpar may contains paragraphs, but in order to remain inline with the surrounding text lwarp nullifies block-related macros inside the \marginpar. Paragraph breaks are converted to <br /> tags.

\marginparBlock [⟨*left*⟩] {⟨*right*⟩} To include block-related macros, use \marginparBlock, which takes the same arguments but creates a instead of a . A line break will occur in the text where the \marginBlock occurs.

for HTML output:

```
\begin{warpHTML}
```

\marginpar [⟨*left*⟩] {⟨*right*⟩}

```
\renewcommand{\marginpar}[2][]{%
\ifbool{FormatWP}%
{%
\begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}
#2
\end{LWR@BlockClassWP}
}%
{%
    \LWR@htmlspanclass{marginpar}{#2}%
}%
}
```

\marginparBlock [⟨*left*⟩] {⟨*right*⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

HTML version.

```
\newcommand{\marginparBlock}[2][]{%
\ifbool{FormatWP}%
{%
\begin{LWR@BlockClassWP}{width:2in; float:right; margin:10pt}{}{marginblock}
#2
\end{LWR@BlockClassWP}
}%
{%
\begin{BlockClass}[width:2in; float:right; margin:10pt]{marginparblock}
#2
\end{BlockClass}
}%
}
```

\reversemarginpar

```
\renewcommand*{\reversemarginpar}{}
```

\normalmarginpar

```
\renewcommand*{\normalmarginpar}{}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\marginparBlock [⟨*left*⟩] {⟨*right*⟩}

For use when the marginpar will be more than one paragraph, and/or contains more than simple text.

Print version.

```
\LetLtxMacro\marginparBlock\marginpar
\end{warpprint}
```

61 Splitting HTML files

- Files are split according to FileDepth and CombineHigherDepths.
- Filenames are sanitized by \LWR@filenamenoblanks.
- \LWR@newhtmlfile finishes an HTML page, adds a comment to tell where and how to split the file, then starts a new HTML page.

for HTML & PRINT:

```
\begin{warpall}
```

Ctr FileDepth {⟨*section depth*⟩} determines how deeply to break into new HTML files, similar to tocdepth. The default of -5 produces one large HTML file.

```
\newcounter{FileDepth}
\setcounter{FileDepth}{-5}
```

Bool CombineHigherDepths Combile higher-level sections together into one file?

```
\newbool{CombineHigherDepths}
\booltrue{CombineHigherDepths}
```

\FilenameLimit Maximum length of the generated filenames.

```
\newcommand*{\FilenameLimit}{80}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

`\LWR@thisfilename` The currently-active filename or number. At first, this is the homepage.

```
\AtBeginDocument{
\ifbool{FileSectionNames}%
    {\newcommand*{\LWR@thisfilename}{\HomeHTMLFilename}}
    {\newcommand*{\LWR@thisfilename}{0}}
}
```

`\LWR@thisnewfilename` The filename being sanitized.

```
\newcommand*{\LWR@thisnewfilename}{}
```

`\LWR@simplifyname` * {⟨*expression*⟩} Simplify `\LWR@thisnewfilename`.

If starred, detokenizes the input expression. If found, changes the expression to a single detokenized dash.

```
\NewDocumentCommand{\LWR@simplifyname}{s m}{%
\IfBooleanTF{#1}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {\detokenize{#2}}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}{%
    \StrSubstitute{\LWR@thisnewfilename}%
        {#2}%
        {\detokenize{-}}[\LWR@thisnewfilename]%
}
}
```

`\LWR@simplifycustom` User-defined filename simplifications. Redefine with `\newcommand`.

```
\newcommand*{\LWR@simplifycustom}{}
```

`\FilenameSimplify` * {⟨*phrase*⟩} Assign a user-defined filename simplification. Appends to `\LWR@simplifycustom`.

```
\NewDocumentCommand{\FilenameSimplify}{s m}{%
\IfBooleanTF{#1}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname*{#2}%
    }%
}{%
    \appto{\LWR@simplifycustom}{%
        \LWR@simplifyname{#2}%
    }%
}%
}
```

`\LWR@filenamenoblanks` {⟨*filename*⟩}

Convert blanks into dashes, removes short words, store result in `\LWR@thisfilename`.

Also see \LWR@nullfonts for nullified macros.

```
\newcommand*{\LWR@filenamenoblanks}[1]{%
\begingroup
```

Locally temporarily disable direct-formatting commands, not used in filenames:

```
\LWR@nullfonts%
\renewcommand*{\LWR@htmltagc}[1]{}%
```

```
\edef\LWR@thisnewfilename{#1}%
```

Replaces common macros with hyphens. (\& is done by \LWR@nullfonts.)

```
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\LWR@simplifyname{\_}
\LWR@simplifyname{\#}
\LWR@simplifyname{\textbackslash}
\LWR@simplifyname{\protect}
\LWR@simplifyname{\ }
\LWR@simplifyname{\textless}
\LWR@simplifyname{\textgreater}
```

```
\edef\LWR@thisnewfilename{\detokenize\expandafter{\LWR@thisnewfilename}}%
```

```
\LWR@traceinfo{LWR@filenamenoblanks edef: !\LWR@thisnewfilename!}%
\fullexpandarg%
```

Convert spaces into hyphens:

```
\LWR@simplifyname*{ }
```

Convert punctutation into hyphens:

```
\LWR@simplifyname*{!}
\LWR@simplifyname*{,}
\LWR@simplifyname*{'}
\LWR@simplifyname*{+}
\LWR@simplifyname*{,}
\LWR@simplifyname*{/}
\LWR@simplifyname*{:}
\LWR@simplifyname*{;}
\LWR@simplifyname*{=}
\LWR@simplifyname*{?}
\LWR@simplifyname*{@}
\LWR@simplifyname*{^}
\LWR@simplifyname*{&}
\LWR@simplifyname*{"}
\LWR@simplifyname*{<}
\LWR@simplifyname*{>}
```

```
\LWR@simplifyname{\LWRbackslash}
```

Braces are removed entirely to avoid extra dashes in the result.

```
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRleftbrace}{}[\LWR@thisnewfilename]%
\StrSubstitute{\LWR@thisnewfilename}%
    {\LWRrightbrace}{}[\LWR@thisnewfilename]%

\LWR@simplifyname{\LWRpercent}
\LWR@simplifyname{\LWRdollar}

\LWR@simplifyname*{|}
\LWR@simplifyname*{^}
\LWR@simplifyname*{~}
\LWR@simplifyname*{[}
\LWR@simplifyname*{]}
\LWR@simplifyname*{‘}
```

Convert short words:

```
\LWR@simplifyname*{-s-}
\LWR@simplifyname*{-S-}
\LWR@simplifyname*{-a-}
\LWR@simplifyname*{-A-}
\LWR@simplifyname*{-an-}
\LWR@simplifyname*{-AN-}
\LWR@simplifyname*{-to-}
\LWR@simplifyname*{-TO-}
\LWR@simplifyname*{-by-}
\LWR@simplifyname*{-BY-}
\LWR@simplifyname*{-of-}
\LWR@simplifyname*{-OF-}
\LWR@simplifyname*{-and-}
\LWR@simplifyname*{-AND-}
\LWR@simplifyname*{-for-}
\LWR@simplifyname*{-FOR-}
\LWR@simplifyname*{-the-}
\LWR@simplifyname*{-THE-}
```

Convert custom words:

```
\LWR@simplifycustom%
```

Convert multiple hyphens:

```
\LWR@simplifyname*{-----}
\LWR@simplifyname*{----}
\LWR@simplifyname*{---}
\LWR@simplifyname*{--}
```

If pdfLaTeX and not `utf8` encoding, don't try to convert emdash, endash:

```
\ifPDFTeX% pdflatex or dvi latex
\ifdefstring{\inputencodingname}{utf8}{%
\LWR@simplifyname*{—}
```

```
%     emdash
\LWR@simplifyname*{-}
%     endash
}{}%
\else% not PDFTeX
\LWR@simplifyname*{-}
\LWR@simplifyname*{-}
\fi%
```

If starts with a dash, remove the leading dash:

```
\IfBeginWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleLeft{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

If ends with a dash, remove the trailing dash:

```
\IfEndWith{\LWR@thisnewfilename}{\detokenize{-}}{%
    \StrGobbleRight{\LWR@thisnewfilename}{1}[\LWR@thisnewfilename]%
}{}%
```

Limits the length of the filename:

```
\StrLeft{\LWR@thisnewfilename}{\FilenameLimit}[\LWR@thisnewfilename]%
```

Return the global result:

```
\global\let\LWR@thisfilename\LWR@thisnewfilename%
\endgroup%
\LWR@traceinfo{LWR@filenamenoblanks: result is \LWR@thisfilename}%
}
```

Ctr `LWR@previousautopagelabel`

Remembers which autopage label was most recently generated. Used to avoid duplicates.

```
\newcounter{LWR@previousautopagelabel}
\setcounter{LWR@previousautopagelabel}{-1}
```

File `*_html.aux`

A new entry in the `*_html.aux` file is used to help cross-references:

```
\newlabel{autopage-<nnn>}{{<x>}{<y>}}
```

`\LWR@newautopagelabel` {⟨*pagenumber counter*⟩}

`\BaseJobname` is added to the label in case xr or xr-hyper are used.

```
\newcommand*{\LWR@newautopagelabel}[1]{%
\ifnumequal{\value{LWR@previousautopagelabel}}{\value{page}}%
{}% no action if this autopage label has already been defined
{%
    \label{\BaseJobname-autopage-\arabic{#1}}%
    \setcounter{LWR@previousautopagelabel}{\value{page}}
}%
}
```

61.1 Customizing MathJax

\LWR@customizedMathJax Additional MathJax definitions to be added to the start of each html page.

```
\newcommand*{\LWR@customizedMathJax}{}
```

\CustomizeMathJax MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each html page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

```
\newcommand*{\CustomizeMathJax}[1]{%
   \appto{\LWR@customizedMathJax}{%
       \(#1\)\par
   }%
}
```

\LWR@customizeMathJax

```
\newcommand{\LWR@customizeMathJax}{%
\ifbool{mathjax}{

\LWR@stoppars
\LWR@htmlcomment{Nullify \textbackslash{}ensuremath, footnotes for MathJax:}

\(\newcommand\ensuremath[1]{##1}\)

\(\newcommand\footnote[2][]{\text{( Footnote ##1 )}}\)

\(\newcommand\footnotemark[1][]{\text{( Footnote ##1 )}}\)

\LWR@htmlcomment{Additional customizations for MathJax:}

\LWR@customizedMathJax

\LWR@startpars
}{}
}

\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\CustomizeMathJax The print-mode version:

```
\newcommand*{\CustomizeMathJax}[1]{}
```

\FilenameSimplify * {⟨*expression*⟩}

```
\NewDocumentCommand{\FilenameSimplify}{s m}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@newhtmlfile {⟨*section name*⟩}

Finishes the current HTML page with footnotes, footer, navigation, then starts a new HTML page with an HTML comment telling where to split the page and what the new filename and CSS are, then adds navigation, side TOC, header, and starts the text body.

```
\newcommand*{\LWR@newhtmlfile}[1]{
\LWR@traceinfo{LWR@newhtmlfile}
```

At the bottom of the ending file:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{div}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}

\LWR@printpendingfootnotes

```

No footer between files if EPUB:

```
\ifbool{FormatEPUB}
{}
{
    \LWR@htmlelement{footer}

    \LWR@pagebottom

    \LWR@htmlelementend{footer}
}
```

No bottom navigation if are finishing the home page or formatting for EPUB or a word-processor.

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}}
```

End of this HTML file:

```
\LWR@stoppars
\LWR@htmltag{/body}\LWR@orignewline
\LWR@htmltag{/html}\LWR@orignewline
\LWR@traceinfo{LWR@newhtmlfile: about to LWR@orignewpage}
\LWR@orignewpage

\addtocounter{LWR@htmlfilenumber}{1}%
```

If using a filename based on section name, create a version without blanks. The filename without blanks will be placed into `\LWR@thisfilename`. Duplicates will be detected using MD5 hashes.

If not using a filename, the file number will be used instead.

```
\ifbool{FileSectionNames}%
{%
```

Convert the section name to a filename with blanks and common words removed. The resulting filename is in `\LWR@thisfilename`.

```
    \LWR@filenamenoblanks{#1}%
```

Create a macro name from the MD5 hash of the file name, to detect duplicates:

```
    \edef\LWR@hashedname{\LWR@mdfive{\LWR@thisfilename}}%
```

If the macro name is not yet defined, this filename is unique.

```
    \ifcsundef{LWR@filename\LWR@hashedname}{%
```

If the filename is unique, create a macro using the hashed name, to be used to test for additional duplicates in the future.

```
        \csdef{LWR@filename\LWR@hashedname}{}%
    }{%
```

If the filename is not unique, create an error.

```
        \PackageError{lwarp}
            {%
                Section name\MessageBreak
                ``#1'',\MessageBreak
                at the line number listed below,\MessageBreak
                generates the filename\MessageBreak
                ``\LWR@thisfilename'',\MessageBreak
                which appears to be a duplicate.\MessageBreak
                There is a previous section with an\MessageBreak
                identical or similar name%
            }
            {%
                Lwarp sanitizes most symbols and a few common short words
                when generating file names, and this may cause a conflict.
            }
```

```
    }
}
```

If using file numbers instead of names, the name is set to the next file number.

```
{\renewcommand*{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}
```

Include an HTML comment to instruct lwarpmk where to split the files apart. Uses pipe-separated fields for `split_html.gawk`. Uses monospaced font with ligatures disabled for everything except the title.

```
\LWR@traceinfo{LWR@newhtmlfile: about to print start file}%
```

`\LWR@nullfonts` to allow math in a section name.

```
\begingroup%
\LWR@nullfonts%
\LWR@htmlblockcomment{%
|Start file|%
\LWR@htmlsectionfilename{\LWR@thisfilename}|%
}
\endgroup%
```

At the top of the starting file:

```
\LWR@stoppars

```

Start a new file with the given section name:

```
\LWR@filestart[#1]

```

Track the page numbers:

```
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@latestautopage}%
```

No navigation between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {\LWR@topnavigation}

```

No header if between files if formatting for an EPUB or word processor:

```
\ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
    {}
    {
        \LWR@htmlelement{header}

        \LWR@pagetop
```

```
6039
6040          \LWR@htmlelementend{header}
6041      }
6042
```

The container for the sidetoc and text body:

```
6043 \LWR@htmlelementclass{div}{bodyandsidetoc}
```

No sidetoc if formatting for an epub or word processor:

```
6044 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
6045     {}
6046     {\LWR@sidetoc}
6047
```

Start of the <textbody>:

```
6048 \LWR@htmlelementclass{div}{bodycontainer}
6049 \LWR@htmlelementclass{section}{textbody}
6050
```

Print title only if there is one. Skip if formatting for an epub or word processor:

```
6051 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}%
6052     {}%
6053     {%
6054         \ifcsvoid{thetitle}{}{%
6055             \LWR@printthetitle%
6056         }%
6057     }%
```

Keep paragraph tags disabled for now:

```
6058 \LWR@stoppars
6059
```

If using MathJax, disable \ensuremath by printing a nullified definition at the start of each file, and add further customizations:

```
6060 \LWR@customizeMathJax

6061 \LWR@traceinfo{LWR@newhtmlfile: done}
6062 }

6063 \end{warpHTML}
```

62 Sectioning

Sectioning and cross-references have been emulated from scratch, rather than try to patch several layers of existing LaTeX code and packages. Formatting is handled by CSS, so the emulated code has much less work to do than the print versions.

Unicode

⚠ accents in filenames

Section names and the resulting filenames with accented characters are partially supported, depending on the ability of *pdflatex* to generate characters and *pdftotext* to read them. If extra symbols appear in the text, it may be that *pdflatex* is actually producing a symbol over or under a character, resulting in *pdftotext* picking up the accent symbol separately.

XeLaTeX and LuaLaTeX directly support accented section and file names.

for HTML output:

```
6064 \begin{warpHTML}
```

62.1 User-level starred section commands

\ForceHTMLPage

For HTML output, forces the next section to be on its own HTML page, if FileDepth allows, even if starred. For use with \printindex and others which generate a starred section which should be on its own HTML page. Also see \ForceHTMLTOC.

For print output, no effect.

```
6065 \newbool{LWR@forcinghtmlpage}
6066 \boolfalse{LWR@forcinghtmlpage}
6067
6068 \newcommand*{\ForceHTMLPage}{%
6069 \global\booltrue{LWR@forcinghtmlpage}%
6070 }
```

\ForceHTMLTOC

For HTML output, forces the next section to have a TOC entry, even if starred. For use with \printindex and others which generate a starred section which should be in the TOC so that it may be accessed via HTML. Not necessary if used with tocbibind. Also see \ForceHTMLPage.

For print output, no effect.

```
6071 \newbool{LWR@forcinghtmltoc}
6072 \boolfalse{LWR@forcinghtmltoc}
6073
6074 \newcommand*{\ForceHTMLTOC}{%
6075 \global\booltrue{LWR@forcinghtmltoc}%
6076 }
```

```
6077 \end{warpHTML}
```

for PRINT output:

```
6078 \begin{warpprint}
6079 \newcommand*{\ForceHTMLPage}{}
6080 \newcommand*{\ForceHTMLTOC}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

62.2 Book class commands

`\mainmatter` ⚠ Declare the main matter section of the document. Does not reset the page number, which must be consecutive arabic numbers for the HTML conversion.

```
\newbool{LWR@mainmatter}
\DeclareDocumentCommand{\mainmatter}{}{%
\booltrue{LWR@mainmatter}%
}
```

`\frontmatter` Declare the front matter section of the document, using arabic numbering for the internal numbering. Does not reset the page number.

```
\DeclareDocumentCommand{\frontmatter}{}{%
\boolfalse{LWR@mainmatter}%
}
```

`\backmatter` Declare the back matter section of the document. Does not reset the page number.

```
\DeclareDocumentCommand{\backmatter}{}{%
\boolfalse{LWR@mainmatter}
}
```

62.3 Sectioning support macros

`\LWR@sectionumber` {⟨*section type*⟩}

Typeset a section number and its trailing space with CSS formatting:

```
\newcommand*{\LWR@sectionnumber}[1]{%
\InlineClass{sectionnumber}{#1}%
}
```

`autosec` A tag used by the TOC and index.

`\LWR@createautosec` {⟨*section type*⟩}

Create an autosection tag.

```
\newcommand*{\LWR@createautosec}[1]{%
\LWR@htmltag{%
    #1 % space
    id=\textquotedbl\LWR@print@mbox{autosec-\arabic{page}}\textquotedbl%
```

```
}%
}
```

`\LWR@pushoneclose` {⟨*sectiontype*⟩} Stacks the new sectioning level's closing tag, to be used when this section is closed some time later.

⚠ `\LWR@stoppars` must be executed first.

```
\NewDocumentCommand{\LWR@pushoneclose}{m}{%
\LWR@traceinfo{LWR@pushoneclose #1}%
    \LWR@pushclose{#1}%
}
```

`\LWR@startnewdepth` {⟨*sectiontype*⟩}

Closes currently stacked tags of a lesser level, then opens the new nesting level by saving this new sectioning level's closing tag for later use.

⚠ `\LWR@stoppars` must be executed first.

```
\NewDocumentCommand{\LWR@startnewdepth}{m}{%
```

Close any stacked sections up to this new one.

```
\LWR@closeprevious{#1}%
```

Push a new section depth:

```
\LWR@pushoneclose{#1}%
}
```

Ctr `LWR@prevFileDepth` Remembers the previous `LWR@FileDepth`.

Initialized to a deep level so that any section will trigger a new HTML page after the home page.

```
\newcounter{LWR@prevFileDepth}
\setcounter{LWR@prevFileDepth}{\LWR@depthsubparagraph}
```

`\@seccntformat` {⟨*sectiontype*⟩}

```
\def\@seccntformat#1{\csname the#1\endcsname\quad}
```

`\simplechapterdelim` Used by tocbibind and anonchap.

```
\newcommand*{\simplechapterdelim}{}
```

`\@chapcntformat` {⟨*sectiontype*⟩}

\let to \@seccntformat by default, but may be redefined by \simplechapter and \restorechapter from tocbibind or anonchap.

```
\let\@chapcntformat\@seccntformat
```

\@partcntformat {⟨*sectiontype*⟩}

\let to \@seccntformat by default, but may be redefined by ctex.

```
\let\@partcntformat\@seccntformat
```

\@partnameformat Prints "Part" for part sections.

Nullified by ctex.

```
\newcommand*{\@partnameformat}{\LWR@isolate{\partname}~}%
```

Ctr LWR@currentautosec Records the page number when the section was created. If a math expression is included in the section name, and SVG math is used, the corresponding lateximage will cause the page number to change by the time the following autosec label is created.

```
\newcounter{LWR@currentautosec}
\setcounter{LWR@currentautosec}{1}
```

\LWR@section * [⟨*TOC name*⟩] {⟨*name*⟩} {⟨*sectiontype*⟩}

The common actions for the high-level sectioning commands.

```
\DeclareDocumentCommand{\LWR@section}{m m m m}{%
\IfValueTF{#2}%
    {\LWR@traceinfo{LWR@section: starting #4 #2}}%
    {\LWR@traceinfo{LWR@section: starting #4 #3}}%
\LWR@maybeprintpendingfootnotes{\csuse{LWR@depth#4}}%
\LWR@stoppars%
\LWR@startnewdepth{#4}%
```

Cancel special minipage horizontal space interaction:

```
\global\boolfalse{LWR@minipagethispar}%
```

Start a new HTML file unless starred, and if is a shallow sectioning depth.

Exception: Also start a new HTML file for \part*, for appendix.

Generate a new LaTeX page so that TOC and index page number points to the section:

```
\LWR@traceinfo{LWR@section: testing whether to start a new HTML file}%
\IfBooleanT{#1}{\LWR@traceinfo{LWR@section: starred}}%
\ifbool{LWR@forcinghtmlpage}{\LWR@traceinfo{LWR@section: forcinghtmlpage}}{}%
\ifthenelse{%
```

```
    \(%
        \(\NOT\equal{#1}{\BooleanTrue}\)\OR%
        \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)\OR%
        \(\boolean{LWR@forcinghtmlpage}\)%
    \)%
    \AND%
    \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{FileDepth}}%
    \AND%
    \(%
        \NOT\boolean{CombineHigherDepths}\OR%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{LWR@prevFileDepth}}%
    \)%
    \AND%


    \(% phantomsection
        \NOT\isempty{#3}%
        \OR%
        \(\NOT\equal{#1}{\BooleanTrue}\)%
    \)%
}%
```

If so: start a new HTML file:

```
{% new file
    \LWR@traceinfo{LWR@section: new HTML file}%
```

See if there was an optional TOC name entry:

```
    \IfNoValueTF{#2}%
```

If no optional entry

```
        {\LWR@newhtmlfile{#3}}%
```

If yes an optional entry

```
        {\LWR@newhtmlfile{#2}}%
}% new file
```

Else: No new HTML file:

```
{% not new file
```

Generate a new LaTeX page so that TOC and index page number points to the section:

```
    \LWR@traceinfo{LWR@section: not a new HTML file, about to LWR@orignewpage}%
    \LWR@orignewpage%
}% not new file

```

Remember this section's name for `\nameref`:

```
\IfValueT{#3}{%
```

```
    \LWR@traceinfo{LWR@section: about to LWR@setlatestname}%
    \IfValueTF{#2}{\LWR@setlatestname{#2}}{\LWR@setlatestname{#3}}%
}%
```

Print an opening comment with the level and the name; ex: “section” “Introduction” Footnotes may be used in section names, which would also appear in the HTML section opening comments, so the short TOC entry is used if possible, and a limited opening comment is made if the sectional unit is starred.

```
\ifbool{HTMLDebugComments}{%
    \begingroup%
    \LWR@nullfonts%
    \IfBooleanTF{#1}% starred
    {\LWR@htmlcomment{Opening #4*}}%
    {%
        \IfNoValueTF{#2}% short TOC
            {\LWR@htmlcomment{Opening #4 ``#3''}}%
            {\LWR@htmlcomment{Opening #4 ``#2''}}%
    }\LWR@orignewline%
    \endgroup%
}{}
```

For inline sections paragraph and subparagraph, start a new paragraph now:

```
\ifthenelse{%
    \cnttest{\@nameuse{LWR@depth#4}}{>=}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

Create the opening tag with an autosec:

```
\LWR@traceinfo{LWR@section: about to LWR@createautosec}%
\LWR@createautosec{\@nameuse{LWR@tag#4}}%

\setcounter{LWR@currentautosec}{\value{page}}%
```

Check if starred:

```
\IfBooleanTF{#1}%
{%
    \LWR@traceinfo{LWR@section: starred}%
```

Starred, but also forcing a TOC entry, so add unnumbered TOC name or regular name:

```
    \ifbool{LWR@forcinghtmltoc}%
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
    }%
    {}%
}% starred
```

Not starred, so step counter and add to TOC:

```
{% not starred
```

Only add a numbered TOC entry if section number is not too deep:

```
    \ifthenelse{%
        \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
    }%
    {% if secnumdepth
```

If in the main matter, step the counter and add the TOC entry. For `article` class, lwarp assumes that all is mainmatter.

```
        \LWR@traceinfo{LWR@section: about to test main matter}%
        \ifbool{LWR@mainmatter}%
        {%
            \LWR@traceinfo{LWR@section: yes mainmatter}%
            \refstepcounter{#4}%
```

Add main matter numbered TOC entry with the TOC name or the regular name:

```
            \LWR@traceinfo{LWR@section: about to addcontentsline}%
            \addcontentsline{toc}{#4}%
            {%
                \protect\numberline{%
                    \@nameuse{pre#4name}%
                    \@nameuse{the#4}%
                    \@nameuse{post#4name}%
                }%
                {%
                    \ignorespaces%
              \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}\protect\relax%
                }%
            }%
            \LWR@traceinfo{LWR@section: finished addcontentsline}%
        }% end of if main matter
```

If not main matter, add unnumbered TOC name or regular name:

```
        {% not main matter
            \LWR@traceinfo{LWR@section: no main matter}%
            \addcontentsline{toc}{#4}{%
                \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
            }%
        }% end of not main matter
    }% end of secnumdepth
```

Deeper than secnumdepth, so add an unnumbered TOC entry:

```
    {%
        \addcontentsline{toc}{#4}{%
            \IfValueTF{#2}{\LWR@isolate{#2}}{\LWR@isolate{#3}}%
        }%
```

```
    }%
```

For part, print “Part”:

```
    \ifbool{LWR@mainmatter}%
    {%
        \ifthenelse{%
            \(\cnttest{\@nameuse{LWR@depth#4}}{<=}%
                {\value{secnumdepth}}\) \AND%
            \(\cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}\)%
        }%
            {\@partnameformat}%
            {}%
```

Print the section number:

```
        \LWR@traceinfo{LWR@section: about to print section number}%
        \ifthenelse{%
            \cnttest{\@nameuse{LWR@depth#4}}{<=}{\value{secnumdepth}}%
        }%
            {%
                \ifstrequal{#4}{part}%
                {\protect\LWR@sectionnumber{\@partcntformat{#4}}}%
                {%
                    \ifstrequal{#4}{chapter}%
                        {\protect\LWR@sectionnumber{\@chapcntformat{#4}}}%
                        {\protect\LWR@sectionnumber{\@seccntformat{#4}}}%
                }%
            }%
            {}%
        \LWR@traceinfo{LWR@section: finished print section number}%
    }{}%
}% end of not starred
```

Print the section name:

```
\LWR@traceinfo{LWR@section: about to print the section name}%
\LWR@isolate{#3}%
```

Close the heading tag, such as /H2:

```
\LWR@traceinfo{LWR@section: about to close the heading tag}%
\LWR@htmltag{\@nameuse{LWR@tag#4end}}%
\LWR@orignewline%
```

Generate a LaTeX label:

```
\LWR@traceinfo{LWR@section: about to create the LaTeX label}%
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosec}\LWR@orignewline%
```

Start paragraph handing unless is an inline paragraph or subparagraph:

```
\ifthenelse{%
```

```
    \cnttest{\@nameuse{LWR@depth#4}}{<}{\LWR@depthparagraph}%
}%
    {\LWR@startpars}%
    {}%
```

If not starred, remember the previous depth to possibly trigger a new HTML page.

HOWEVER, allow a `\part*` to start a new HTML page. This is used by appendix.

A starred section does not trigger a new HTML page at the beginning of this macro, so it should not affect it here at the end either. This became an issue when a `\listoftables` was tested in the middle of the document. The `\chapter*` for the list was not allowing a new HTML page for the section following it while `CombineHigherDepths` was true.

```
\ifthenelse{%
    \NOT\equal{#1}{\BooleanTrue}\OR%
    \cnttest{\@nameuse{LWR@depth#4}}{=}{\LWR@depthpart}%
}%
    {% not starred
        \setcounter{LWR@prevFileDepth}{\@nameuse{LWR@depth#4}}%
    }% not starred
    {}%
```

Reset to defaults if not a phantomsection:

```
\ifstrempty{#3}%
    {}%
    {%
        \global\boolfalse{LWR@forcinghtmlpage}%
        \global\boolfalse{LWR@forcinghtmltoc}%
    }%
%
\LWR@traceinfo{LWR@section: done}%
}
```

62.4 Pre- and post- sectioning names

`\prepartname` `\postpartname` Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prepartname}{}
\providecommand*{\postpartname}{}
```

`\prechaptername` `\postchaptername` Usually null, but is used by uj* and ut* Japanese classes.

```
\providecommand*{\prechaptername}{}
\providecommand*{\postchaptername}{}
```

`\presectionname` `\postsectionname` Always null, but provided here for algorithmic simplicity in `\LWR@section`.

```
\providecommand*{\presectionname}{}
\let\postsectionname\presectionname

\let\presubsectionname\presectionname
\let\postsubsectionname\postsectionname

\let\presubsubsectionname\presectionname
\let\postsubsubsectionname\postsectionname

\let\preparagraphname\presectionname
\let\postparagraphname\postsectionname

\let\presubparagraphname\presectionname
\let\postsubparagraphname\postsectionname
```

62.5 `\section` and friends

For memoir, a second optional argument is allowed.

For hypbmsec, a second optional argument or either parenthesis argument is allowed.

Each of these additional arguments are for headers or PDF bookmarks, and are ignored for HTML output.

`\part` `*` (⟨*2:PDF name*⟩) [⟨*3:TOC name*⟩] [⟨*4:PDF name*⟩] (⟨*5:PDF name*⟩) {⟨*6:name*⟩}

```
\newcommand{\part@preamble}{}% for koma-script

\DeclareDocumentCommand{\part}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{part}%

    \part@preamble% for koma-script
    \renewcommand{\part@preamble}{}%
}
```

`\chapter` `*` (⟨*2:PDF name*⟩) [⟨*3:TOC name*⟩] [⟨*4:PDF name*⟩] (⟨*5:PDF name*⟩) {⟨*6:name*⟩}

```
\let\@printcites\relax% for quotchap package

\newcommand{\chapter@preamble}{}% for koma-script

\@ifundefined{chapter}
{}
{%
    \DeclareDocumentCommand{\chapter}{s d() o o d() m}{%
        \LWR@section{#1}{#3}{#6}{chapter}%

        \@printcites% for quotchap package

        \chapter@preamble% for koma-script
```

```
        \renewcommand{\chapter@preamble}{}%
    }
}
```

\section * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\section}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{section}%
}
```

\subsection * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subsection}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subsection}%
}
```

\subsubsection * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subsubsection}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subsubsection}%
}
```

\paragraph * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\paragraph}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{paragraph}%
}
```

\subparagraph * (⟨2:PDF name⟩) [⟨3:TOC name⟩] [⟨4:PDF name⟩] (⟨5:PDF name⟩) {⟨6:name⟩}

```
\DeclareDocumentCommand{\subparagraph}{s d() o o d() m}{%
    \LWR@section{#1}{#3}{#6}{subparagraph}%
}

\end{warpHTML}
```

63 Starting a new file

for HTML & PRINT:

```
\begin{warpall}
```

\HTMLLanguage Default language for the HTML lang tag.

```
\newcommand*{\LWR@currentHTMLLanguage}{en-US}

\newcommand*{\HTMLLanguage}[1]{%
\renewcommand*{\LWR@currentHTMLLanguage}{#1}%
}
```

\theHTMLTitleSeparator May be used inside \theHTMLTitleSection to separate the website's overall HTML title and the particular page's section name.

```
\ifPDFTeX% pdflatex or dvi latex
    \ifdefstring{\inputencodingname}{utf8}{%
        \newcommand*{\theHTMLTitleSeparator}{ — }% EMdash
    }{%
        \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
    }%
\else%
    \ifpTeX
        \newcommand*{\theHTMLTitleSeparator}{ - }% hyphen
    \else
        \newcommand*{\theHTMLTitleSeparator}{ — }% EMdash
    \fi%
\fi%
```

\HTMLTitleBeforeSection Sets the HTML page's meta title tag to show the website title before the section name.

```
\newcommand*{\HTMLTitleBeforeSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLTitle\theHTMLTitleSeparator\theHTMLSection%
    }%
}
```

\HTMLTitleAfterSection Sets the HTML page's meta title tag to show the section name before the website title.

```
\newcommand*{\HTMLTitleAfterSection}{%
    \def\theHTMLTitleSection{%
        \theHTMLSection\theHTMLTitleSeparator\theHTMLTitle%
    }%
}
```

\theHTMLTitleSection Forms the HTML page's meta title tag. The default is to show the website title before the section name.

```
\HTMLTitleBeforeSection
```

\theHTMLSection The section name is passed to \LWR@filestart, which then sets \theHTMLSection for use inside \theHTMLTitleSection to create an HTML meta title tag.

```
\newcommand*{\theHTMLSection}{}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@filestart [⟨*sectionname*⟩] Creates the opening HTML tags.

```
\newcommand*{\LWR@filestart}[1][]{%
\LWR@traceinfo{LWR@filestart !#1!}%
```

Locally temporarily disable direct-formatting commands:

```
\begingroup%
\LWR@nullfonts%
```

Save the section name for use while creating the HTML meta `title` tag:

```
\edef\theHTMLSection{#1}%
```

Create the page's HTML header:

```
\LWR@htmltag{!DOCTYPE html}\LWR@orignewline
```

The language is user-adjustable:

```
\LWR@htmltag{%
   html lang=\LWR@orig@textquotedbl\LWR@currentHTMLLanguage\LWR@orig@textquotedbl%
}\LWR@orignewline
```

Start of the meta data:

```
\LWR@htmltag{head}\LWR@orignewline
```

Charset is fixed at UTF-8:

```
\LWR@htmltag{%
    meta charset=\LWR@orig@textquotedbl{}UTF-8\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

Author:

```
\ifthenelse{\equal{\theHTMLAuthor}{}}%
    {}%
    {%
        \LWR@htmltag{%
        meta name=\LWR@orig@textquotedbl{}author\LWR@orig@textquotedbl\ % space
         content=\LWR@orig@textquotedbl\theHTMLAuthor\LWR@orig@textquotedbl\ /%
        }\LWR@orignewline%
    }%
```

lwarp is the generator:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}generator\LWR@orig@textquotedbl\ % space
   content=\LWR@orig@textquotedbl{}LaTeX lwarp package\LWR@orig@textquotedbl\ /%
}\LWR@orignewline%
```

If there is a description, add it now:

```
\ifdefempty{\LWR@currentHTMLDescription}{}{%
    \LWR@htmltag{%
      meta name=\LWR@orig@textquotedbl{}description\LWR@orig@textquotedbl\ % space
      content=\LWR@orig@textquotedbl\LWR@currentHTMLDescription\LWR@orig@textquotedbl\ /%
    }\LWR@orignewline
}%
```

Mobile-friendly viewport:

```
\LWR@htmltag{%
    meta % space
    name=\LWR@orig@textquotedbl{}viewport\LWR@orig@textquotedbl\ % space
   content=\LWR@orig@textquotedbl{}width=device-width, initial-scale=1.0\LWR@orig@textquotedbl\ /%
}\LWR@orignewline
```

IE patch:

```
\LWR@htmltag{!-\/-[if lt IE 9]}\LWR@orignewline
\LWR@htmltag{%
    script % space
    src=\LWR@orig@textquotedbl{}%
        http://html5shiv.googlecode.com/svn/trunk/html5.js%
    \LWR@orig@textquotedbl%
}%
\LWR@htmltag{/script}\LWR@orignewline
\LWR@htmltag{![endif]-\/-}\LWR@orignewline
```

The page's title, if there is one. A section name is also added if given.

```
\ifthenelse{\equal{\theHTMLTitle}{}}%
    {}%
    {%
        \LWR@htmltag{title}%
        \ifdefempty{\theHTMLSection}%
            {\theHTMLTitle}%
            {\theHTMLTitleSection}%
        \LWR@htmltag{/title}\LWR@orignewline%
    }%
```

The page's stylesheet:

```
\LWR@htmltag{%
    link % space
    rel=\LWR@orig@textquotedbl{}stylesheet\LWR@orig@textquotedbl\ % space
    type=\LWR@orig@textquotedbl{}text/css\LWR@orig@textquotedbl\ % space
    href=\LWR@orig@textquotedbl\LWR@currentcss\LWR@orig@textquotedbl\ /%
}%
\LWR@orignewline
```

Optional MathJax support. The HTML tags must be turned off during the verbatim input, and the paragraph handling which was turned on at the end of verbatim input must be immediately turned off again.

```
\ifbool{mathjax}%
```

```
{%
    \begingroup%
    \LWR@restoreoriglists%
    \boolfalse{LWR@verbtags}%

        \verbatiminput{\LWR@mathjaxfilename}%

    \booltrue{LWR@verbtags}%
    \endgroup%
    \LWR@stoppars%
}% end of mathjax
{}%
```

End of the header:

```
\LWR@htmltag{/head}\LWR@orignewline
```

Start of the body:

```
\LWR@htmltag{body}\LWR@orignewline
\endgroup
\LWR@traceinfo{LWR@filestart: done}
}

\end{warpHTML}
```

64 Starting HTML output

for HTML output:

```
\begin{warpHTML}
```

`\LWR@LwarpStart` Executed at the beginning of the entire document.

The use of `\textquotedbl` instead of " improves compatibility with xeCJK.

```
\catcode`\$=\active
\newcommand*{\LWR@LwarpStart}
{%
\LWR@traceinfo{LWR@lwarpStart}
```

If formatting for a word processor, force filedepth to single-file only, force HTML debug comments off.

```
\ifbool{FormatWP}{%
    \setcounter{FileDepth}{-5}%
    \boolfalse{HTMLDebugComments}%
}{}
```

Expand and detokenize `\HomeHTMLFilename` and `\HTMLFilename`:

```
\edef\LWR@strresult{\HomeHTMLFilename}
\edef\HomeHTMLFilename{\detokenize\expandafter{\LWR@strresult}}
\edef\LWR@strresult{\HTMLFilename}
\edef\HTMLFilename{\detokenize\expandafter{\LWR@strresult}}
```

Force onecolumn and empty page style:

```
\LWR@origonecolumn%
\LWR@origpagestyle{empty}%
```

No black box for overfull lines:

```
\overfullrule=0pt
```

Reduce chance of line overflow when HTML tags are added:

```
\LWR@print@footnotesize%
```

In PDF output, don't allow line breaks to interfere with HTML tags:

```
\LWR@print@raggedright%
\LetLtxMacro{\\}{\LWR@endofline}%
```

Spread the lines for *pdftotext* to read them well:

```
\linespread{1.3}%
```

For *pdftotext* to reliably identify paragraph splits:

```
\setlength{\parindent}{0pt}
\setlength{\parskip}{2ex}
```

For the `lateximage` record file:

```
\immediate\openout\LWR@lateximagesfile=\BaseJobname-images.txt
```

Removes space around the caption in the HTML:

```
\setlength{\belowcaptionskip}{0ex}
\setlength{\abovecaptionskip}{0ex}
```

Redefine the plain page style to be empty when used by index pages:

```
\renewcommand{\ps@plain}{}
```

Plug in some new actions. This is done just before the document start so that they won't be over-written by some other package.

Float captions:

```
\let\LWR@origcaption\caption
```

Label in html

Labels: `\ltx@label` is used in amsmath environments and is also patched by cleveref.

```
\let\LWR@origltx@label\ltx@label
\let\ltx@label\LWR@htmlmathlabel
```

Not yet started any paragraph handling:

```
\global\boolfalse{LWR@doingapar}
\global\boolfalse{LWR@doingstartpars}
```

Document and page settings:

```
\mainmatter
\LWR@origpagenumbering{arabic}
```

Start a new HTML file and a header:

```
\LWR@traceinfo{LWR@lwarpStart: Starting new file.}
\LWR@filestart
\LWR@traceinfo{LWR@lwarpStart: Generating first header.}
\LWR@htmltag{header}\LWR@orignewline
\LWR@startpars
\LWR@firstpagetop
\LWR@stoppars
\LWR@htmltag{/header}\LWR@orignewline
```

```
\LWR@htmlelementclass{div}{bodywithoutsidetoc}
\LWR@htmlelementclass{div}{bodycontainer}
\LWR@traceinfo{LWR@lwarpStart: Generating textbody.}
\LWR@htmlelementclass{section}{textbody}
```

Patch the `itemize`, `enumerate`, and `description` environments and `\item`. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\LWR@patchlists
```

Ensure that math mode is active to call lwarp's patches:

```
\catcode`\$=\active
```

Required for `\nameref` to work with SVG math:

```
\immediate\write\@mainaux{\catcode`\string$\active}%
\LetLtxMacro\LWR@syntaxhighlightone$% balance for editor syntax highlighting
```

Allow HTML paragraphs to begin:

```
\LWR@startpars
```

If using MathJax, disable `\ensuremath` by printing a nullified definition at the start of each file, and add further customizations:

```
\LWR@customizeMathJax
```

First autopage label in case a figure occurs early.

```
\setcounter{LWR@latestautopage}{\value{page}}%
\LWR@newautopagelabel{LWR@currentautosec}%

\LWR@traceinfo{LWR@lwarpStart: done}
}
\catcode`\$=3% math shift until lwarp starts

\end{warpHTML}
```

65 Ending HTML output

for HTML output:

```
\begin{warpHTML}
```

`\LWR@requesttoc` {⟨*boolean*⟩} {⟨*suffix*⟩} Requests that a TOC, LOF, or LOTbe generated.

```
\newcommand*{\LWR@requesttoc}[2]{%
\ifbool{#1}
{
    \expandafter\newwrite\@nameuse{tf@#2}
    \immediate\openout \@nameuse{tf@#2} \jobname.#2\relax
}{}
}
```

`\LWR@LwarpEnd` Final stop of all HTML output:

```
\newcommand*{\LWR@LwarpEnd}
{
\LWR@stoppars
\LWR@closeprevious{finished}
```

At the bottom of the ending file:

Close the textbody:

```
\LWR@htmlelementclassend{section}{textbody}
\LWR@htmlelementclassend{div}{bodycontainer}
\LWR@htmlelementclassend{div}{bodyandsidetoc}
```

Print any pending footnotes:

```
\LWR@printpendingfootnotes
```

Create the footer:

```
\LWR@htmlelement{footer}
```

```
6533
6534 \LWR@pagebottom
6535
6536 \LWR@htmlelementend{footer}
```

No bottom navigation if are finishing the home page, or if formatting for an EPUB or word processor.

Presumably has a table-of-contents.

```
6537 \ifthenelse{\boolean{FormatEPUB}\OR\boolean{FormatWP}}
6538     {}
6539     {
6540         \ifnumcomp{\value{LWR@htmlfilenumber}}{>}{0}{\LWR@botnavigation}{}
6541     }
```

```
6542 \LWR@stoppars% final stop of all paragraphs
```

Finish the HTML file:

```
6543 \LWR@htmltag{/body}\LWR@orignewline
6544 \LWR@htmltag{/html}\LWR@orignewline
```

Seems to be required sometimes:

```
6545 \LWR@orignewpage
6546 }
```

`\enddocument` If labels have not changed, mark successful completion of the `lateximages` file. Executed as everything is being shut down.

```
6547 \xpatchcmd{\enddocument}
6548     {%
6549         \if@tempswa
6550         \@latex@warning@no@line{Label(s) may have changed.
6551         Rerun to get cross-references right}%
6552         \fi
6553     }
6554     {%
6555         \if@tempswa
6556             \@latex@warning@no@line{Label(s) may have changed.
6557             Rerun to get cross-references right}%
6558         \else
6559             \immediate\write\LWR@lateximagesfile{%
6560                 |end|end|end|%
6561             }%
6562         \fi
6563     }
6564     {}
6565     {
6566         \PackageWarningNoLine{lwarp}
6567         {%
6568             Could not patch \protect\enddocument.\MessageBreak
6569             If labels have changed, be sure to recompile before\MessageBreak
```

```
            creating lateximages with\MessageBreak
            \space\space lwarpmk limages,\MessageBreak
            or the images may be corrupt%
        }
    }

\end{warpHTML}
```

66 Title page

package support
load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

affiliation

lwarp provides for the \author macro an additional \affiliation macro to provide an affiliation and other additional information for each author in the title page. The affiliation information is removed when using titlingpage's \theauthor in the main text.

reusing titlepage information

The titling package maintains the definitions of \thetitle, \theauthor, etc., after the title has been typeset. These commands are to be used to refer to the document's title and author, etc., in the main text. These definitions have the \thanks and \affiliation removed, and for \author the \and is replaced to generate a simple inline list of authors separated by commas. Note: \theauthor does not work well with authblk unless the traditional LaTeX syntax is used.

⚠ \theauthor, authblk

custom titlepages

\printtitle, \printauthor, etc., are provided for use inside a custom titlepage or titlingpage environment, and these retain the \thanks and \affiliation.

\printthanks

\printthanks has been added to force the printing of thanks inside a titlingpage environment when \maketitle is not used.

⚠ \thanks

Inside a \titlepage or \titlingpage environment, use \thanks instead of \footnote for acknowledgements, etc.

66.1 Setting the title, etc.

The following provide setting commands for both HTML and print outputs.

\author
\and

{⟨*author*⟩} While using \maketitle and print mode, the author is treated as a single-column tabular and the \and feature finishes the current tabular then starts a new one for the next author. Each author thus is placed into its own tabular, and an affiliation may be placed on its own line such as

```
\author{Name \\ Affiliation \and Second Name \\ Second Affiliation}
```

For HTML, the entire author block is placed inside a of class author, and each individual author is inside a of class oneauthor.

\@title
\@author
\@date

\@title, \@author, and \@date store the values as originally assigned, including any \thanks, \and, or \affiliation. These are low-level macros intended to be used by other macros only inside a titlepage or titlingpage, and are used by \maketitle. The author is printed inside a single-column tabular, which becomes multiple single-column tabulars if multiples authors are included. For HTML, these tabulars become side-by-side s of class oneauthor, all of which are combined into one of class author.

\printtitle
\printauthor
\printdate

\printtitle, etc. are user-level macros intended to be used in custom titlepage or titlingpage environments in cases where \maketitle is not desired. These commands preserve the \thanks, etc., and should not be used in the main text.

\thetitle
\theauthor
\thedate
\HTMLPageBottom

\thetitle, \theauthor, and \thedate are available if titling has been loaded, and are sanitized user-level versions from which have been removed the \thanks and \affiliation, and \and is changed for inline text usage. The author is printed inline without \affiliation or \thanks, with \and placing commas between multiple authors. Thus, these commands are to be used in the main text whenever the user wishes to refer to the document's title and such. One practical use for this is to place the authors at the bottom of each HTML page, such as:

```
\HTMLPageBottom{
  \begin{center}\textcopyright~20xx \theauthor\end{center}
}
```

⚠ \theauthor, authblk

\theauthor does not work well if authblk is used. If \theauthor is important, it is recommended to use the standard LaTeX syntax for \author, optionally with lwarp's \affiliation macro as well.

⚠ affiliations

After \maketitle has completed, \theauthor retains the definition of the author, but \and is changed to become a comma and a space, intending to print the authors names separated by spaces. This fails when affiliations are included on their own table rows.

\affiliation

A solution, provide here, is to define a macro \affiliation which, during \maketitle, starts a new row and adds the affiliation, but after \maketitle is finished \affiliation is re-defined to discard its argument, thus printing only the author names when \author is later used inline.

66.2 \if@titlepage

for HTML & PRINT:

```
\begin{warpall}
```

\if@titlepage

Some classes do not provide \if@titlepage. In this case, provide it and force it false.

```
\ifcsvoid{@titlepagefalse}{
    \newif\if@titlepage
```

```
    \@titlepagefalse
}{}

\end{warpall}
```

66.3 Changes for `\affiliation`

`\affiliation` {⟨*text*⟩}

Adds the affiliation to the author for use in `\maketitle`.

Inside `titlepage`, this macro prints its argument. Outside, it is null.

for HTML & PRINT:

```
\begin{warpall}
\providerobustcmd{\affiliation}[1]{}
\end{warpall}
```

for PRINT output:

```
\begin{warpprint}

\AtBeginEnvironment{titlepage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}

\AtBeginDocument{
\@ifpackageloaded{titling}{
\AtBeginEnvironment{titlingpage}{
\renewrobustcmd{\affiliation}[1]{\\ \textsc{\small#1}}
}
}{}% titling loaded
}% AtBeginDocument

\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

Env `titlepage` Sets up a of class `titlepage`. Provided even for memoir class, since it is used by `\maketitle`.

```
\DeclareDocumentEnvironment{titlepage}{}
{
\renewrobustcmd{\affiliation}[1]{\\ \InlineClass{affiliation}{##1}}
\LWR@printpendingfootnotes
\LWR@forcenewpage
\BlockClass{titlepage}
}
{
\endBlockClass
\LWR@printpendingfootnotes
}

\end{warpHTML}
```

66.4 Printing the thanks

for HTML & PRINT:

```
\begin{warpall}
```

`\printthanks` Forces the `\thanks` to be printed.

This is necessary in a `titlingpage` environment when `\maketitle` was not used.

```
\newcommand*{\printthanks}{\@thanks}
```

```
\end{warpall}
```

66.5 Printing the title, etc. in HTML

The following are for printing the title, etc. in a `titlepage` or a `titlingpage` in HTML:

for HTML output:

```
\begin{warpHTML}
```

`\printtitle`

```
\newcommand*{\printtitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

`\LWR@printthetitle` A private version which prints the title without footnotes, used to title each HTML page.

```
\newcommand*{\LWR@printthetitle}
{%
    \LWR@stoppars%
    \LWR@htmltag{\LWR@tagtitle}%
    \thetitle%
    \LWR@htmltag{\LWR@tagtitleend}%
    \LWR@startpars%
}
```

`\printauthor` HTML version.

```
\newcommand*{\printauthor}{
```

The entire author block is contained in a `<div>` named `author`:

```
\begin{BlockClass}{author}
```

\and finishes one author and starts the next:

```
\renewcommand{\and}{%
\end{BlockClass}
\begin{BlockClass}{oneauthor}
}
```

Individual authors are contained in a named oneauthor:

```
\begin{BlockClass}{oneauthor}
\@author
\end{BlockClass}
\end{BlockClass}
}
```

\printdate

```
\newcommand*{\printdate}{%
\begin{BlockClass}{titledate}
\@date
\end{BlockClass}
}
```

```
\end{warpHTML}
```

66.6 Printing the title, etc. in print form

The following are for printing the title, etc. in a titlepage or a titlingpage in print form:

for PRINT output:

```
\begin{warpprint}
```

\printtitle

```
\newcommand*{\printtitle}{{\Huge\@title}}
```

\printauthor Print mode.

```
\newcommand*{\printauthor}
    {{\large\begin{tabular}[t]{c}\@author\end{tabular}}}
```

\printdate

```
\newcommand*{\printdate}{{\small\textit{\@date}}}
```

```
\end{warpprint}
```

66.7 \maketitle for HTML output

An HTML of class titlepage is used.

\thanks are a form of footnotes used in the title page. See section 59 for other kinds of footnotes.

See \thanksmarkseries{series}, below, to set the style of the footnote marks.

for HTML output:

```
\begin{warpHTML}

\@ifclassloaded{memoir}
{
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
}{% not memoir
\if@titlepage
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@arabic\c@footnote}%
}
\else
\newcommand{\LWR@setfootnoteseries}{%
    \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
}
\fi
}% not memoir
```

\LWR@maketitlesetup Patches \thanks macros.

```
\newcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\LWR@setfootnoteseries%
\def\@makefnmark{\textsuperscript{\thefootnote}}
```

\thefootnote ⇒ \nameuse{arabic}{footnote}, or
\thefootnote ⇒ \nameuse{fnsymbol}{footnote}

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\textsuperscript{\@thefnmark}~%
```

\makethanksmark ⇒ \thanksfootmark ⇒ \tamark ⇒
\@thefnmark ⇒ \itshape a (or similar)

Print the text:

```
##1%
}%
}
```

`\@fnsymbol` {⟨*counter*⟩}

Re-defined to use an HTML entity for the double vertical bar symbol. The original definition used `\|` which was not being seen by *pdftotext*.

```
\def\@fnsymbol#1{\ifcase#1\or *\or \HTMLentity{dagger}\or \HTMLentity{Dagger}\or
   \HTMLentity{sect}\or \HTMLentity{para}\or \text{\HTMLunicode{2016}}\or
   **\or \HTMLentity{dagger}\HTMLentity{dagger} \or
   \HTMLentity{Dagger}\HTMLentity{Dagger} \else\@ctrerr\fi}
```

`\maketitle` HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage `<div>` is used for all classes.

```
\begin{titlepage}
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\@thanks
```

Close the HTML titlepage div and cleanup:

```
\end{titlepage}
\setcounter{footnote}{0}%
\global\let\thanks\relax
\global\let\maketitle\relax
\global\let\@maketitle\relax
\global\let\@thanks\@empty
\global\let\@author\@empty
\global\let\@date\@empty
\global\let\@title\@empty
\global\let\title\relax
\global\let\author\relax
\global\let\date\relax
```

```
\global\let\and\relax
}
```

\@maketitle HTML mode. Typesets the title, etc.:

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
    \@title%
    \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
    \begin{BlockClass}{author}%
```

For IEEEtran class:

```
    \renewcommand*{\cr}{}%
    \renewcommand*{\crcr}{}%
    \renewcommand*{\noalign}{}%

        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }%
        \begin{BlockClass}{oneauthor}%
            \@author%
        \end{BlockClass}%
    \end{BlockClass}%
    \begin{BlockClass}{titledate}%
    \@date%
    \end{BlockClass}%
}
```

\LWR@titlingmaketitle \maketitle for use inside an HTML titlingpage environment.

```
\newcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\@thanks
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\@thanks
}

\end{warpHTML}
```

66.8 \published and \subtitle

\subtitle and \published

To add \subtitle and \published to the titlepage, load the titling package and use \AddSubtitlePublished in the preamble.

The default lwarp.css has definitions for the published and subtitle classes.

If titling is loaded, \AddSubtitlePublished creates a number of additional macros, and also assigns some of the titling hooks. If titling is not loaded, \AddSubtitlePublished creates null macros.

⚠ titling hooks

Do not use \AddSubtitlePublished if the user has patched the titling hooks for some other reason. Portions are marked \warpprintonly to reduce extra tags in HTML. Similarly, BlockClass has no effect in print mode. Thus, the following may be marked warpall.

for HTML & PRINT:

```
\begin{warpall}
```

\AddSubtitlePublished

Adds \published and \subtitle, and related.

```
\newcommand*{\AddSubtitlePublished}{%
\@ifpackageloaded{titling}{% yes titling package
    \newcommand{\@published}{}%
    \newcommand{\published}[1]{\gdef\@published{##1}}%
    \renewcommand*{\maketitlehooka}{\printpublished}%
    \newcommand*{\printpublished}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{published}%
        \warpprintonly{\large\itshape}%
        \@published%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
    \newcommand{\@subtitle}{}%
    \newcommand{\subtitle}[1]{\gdef\@subtitle{##1}}%
    \renewcommand*{\maketitlehookb}{\printsubtitle}%
    \newcommand*{\printsubtitle}{%
        \warpprintonly{\begin{center}\unskip}%
        \begin{BlockClass}{subtitle}%
        \warpprintonly{\Large\itshape}%
        \@subtitle%
        \end{BlockClass}%
        \warpprintonly{\end{center}}%
    }%
}% yes titling package
{% no titling package
    \newcommand{\published}[1]{}%
    \newcommand*{\printpublished}{}%
    \newcommand{\subtitle}{}%
    \newcommand*{\printsubtitle}%
}% no titling package
}% \AddSubtitlePublished

\end{warpall}
```

67 Abstract

The following code replaces the LaTeX default, and will itself be replaced later if the abstract package is loaded.

for HTML output:

```
\begin{warpHTML}
```

`\abstractname` User-redefinable title for the abstract.

Also over-written by the babel package.

```
\providecommand*{\abstractname}{Abstract}
```

Some classes allow an optional name, so it is allowed here.

Env `abstract`

```
\DeclareDocumentEnvironment{abstract}{O{\abstractname}}
{
\LWR@forcenewpage
\BlockClass{abstract}
\BlockClassSingle{abstracttitle}{#1}
}
{
\endBlockClass
}
```

```
\end{warpHTML}
```

68 Quote and verse

68.1 Attributions

`\attribution` {⟨*name*⟩}

For use with quote, quotation, verse:

Ex: `"A quotation." \attribution{\textsc{Author Name}\\\textsl{Book Title}}`

for HTML output:

```
\begin{warpHTML}
\newcommand{\attribution}[1]{%
    \begin{BlockClass}{attribution}
    #1
    \end{BlockClass}
}
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

```
\newcommand{\attribution}[1]{
    \begin{flushright}
    \unskip
    #1
    \end{flushright}%
}
\end{warpprint}
```

68.2 Quotes, quotations

for HTML output:

```
\begin{warpHTML}
```

Env quote

```
\renewenvironment*{quote}
{
    \LWR@forcenewpage
    \LWR@htmlblocktag{blockquote}
}
{\LWR@htmlblocktag{/blockquote}}
```

Env quotation

```
\renewenvironment*{quotation}
{
    \LWR@forcenewpage
    \LWR@htmlblocktag{blockquote}
}
{\LWR@htmlblocktag{/blockquote}}

\end{warpHTML}
```

68.3 Verse

When using verse or memoir, always place a \\ after each line.

\attrib The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and

\HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

68.3.1 LaTeX core verse environment

for HTML output:

```
\begin{warpHTML}
```

Env verse

```
\renewenvironment{verse}
               {\let\\\newline% lwarp
                \list{}{\itemsep      \z@
                        \itemindent   -1.5em%
                        \listparindent\itemindent
                        \rightmargin  \leftmargin
                        \advance\leftmargin 1.5em}%
                \item\relax}
               {\endlist}

\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

68.3.2 verse and memoir

The following lengths are used by verse and memoir. They may be set in either print or HTML output, but are only used in HTML. This allows the user to set \vleftskip and \leftmargini for print output, and optionally select different values for HTML.

Len \HTMLvleftskip Sets \vleftskip inside a verse environment in HTML.

```
\newlength{\HTMLvleftskip}
\setlength{\HTMLvleftskip}{1em}
```

Len \HTMLleftmargini Sets \leftmargini inside a verse environment in HTML.

```
\newlength{\HTMLleftmargini}
\setlength{\HTMLleftmargini}{4.5em}

\end{warpall}
```

69 Verbatim and tabbing

for HTML & PRINT:

```
\begin{warpall}
```

Len `\VerbatimHTMLWidth` Width to use in HTML `Verbatim` environment.

This width is used when placing line numbers to the right. Ignored during print output.

```
\newlength{\VerbatimHTMLWidth}
\setlength{\VerbatimHTMLWidth}{4in}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

Bool `LWR@verbtags` Used to temporarily turn off verbatim tags while doing `\verbatiminput` in the HTML head.

```
\newbool{LWR@verbtags}
\booltrue{LWR@verbtags}
```

`\LWR@atbeginverbatim` `[`⟨*1: style*⟩`]` `{`⟨*2: negative* `\baselineskip` `\vspace`⟩`}` `{`⟨*3: class*⟩`}`

Encloses a verbatim environment with the given CSS class.

The use of `\textquotedbl` instead of " improves compatibility with xeCJK.

```
\newcommand*{\LWR@atbeginverbatim}[3][]
{%
```

Avoid excessive space between lines:

```
\setlength{\parskip}{0ex}%
```

Stop generating HTML paragraph tags:

```
\LWR@stoppars%
```

Create a new `pre` of the given class. The tags may temporarily be turned off for internal use, such as loading the MathJax script.

```
\ifbool{LWR@verbtags}{%
    \LWR@htmltag{pre class=\textquotedbl#3\textquotedbl%
        \ifthenelse{\equal{#1}{}}{}{ style=\textquotedbl#1\textquotedbl}%
    }%
    \LWR@orignewline% pre
    \leavevmode\unskip\LWR@print@vspace*{-#2\baselineskip}%
}{}%
```

Use a mono-spaced font to preserve horizontal positioning. If horizontal alignment is important for the user, use a mono-spaced font in the CSS for the `verse` class.

```
\begingroup%
```

```
% \LWR@print@normalsize%
\LWR@origttfamily%
\LWR@print@small%
```

Since inside a <pre>, restore the original list processing:

```
\LWR@restoreoriglists%
```

Turn off babel-french extra space before punctuation:

```
\LWR@FBcancel%
```

Do not produce HTML tags for \hspace inside a verse par. Restore plain LaTeX \hspace functionality:

```
\LWR@select@print@hspace%
}
```

\LWR@afterendverbatim {⟨*negative* \baselineskip \vspace⟩}

Finishes enclosing a verbatim environment.

```
\newcommand*{\LWR@afterendverbatim}[1]{%
\endgroup%
\par%
```

At the end of the environment, close the pre:

```
\ifbool{LWR@verbtags}{%
    \LWR@print@vspace*{-#1\baselineskip}%
    \noindent\LWR@htmltag{/pre}\LWR@orignewline% pre
}{}%
```

Resume regular paragraph handling:

```
\LWR@startpars%
}
```

\verbatiminput {⟨*filename*⟩}

Patch \verbatiminput to add HTML tags:

```
\let\LWRV@origverbatim@input\verbatim@input

\renewcommand{\verbatim@input}[2]{%
\ifbool{LWR@verbtags}{\LWR@forcenewpage}{}%
\LWR@atbeginverbatim{2.5}{Verbatim}%
\LWRV@origverbatim@input{#1}{#2}%
\LWR@afterendverbatim{1.5}%
}
```

Env verbatim

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verbatim.}
\AtBeginEnvironment{verbatim}{%
\LWR@forcenewpage%
\LWR@atbeginverbatim{2.5}{verbatim}%
}
\AfterEndEnvironment{verbatim}{%
    \LWR@afterendverbatim{1}%
}
}
```

Env tabbing The tabbing environment works, except that SVG math and lateximages do not yet work inside the environment.

⚠ math in tabbing If math is used inside tabbing, place tabbing inside a lateximage environment, which will render the entire environment as a single SVG image.

```
\newcommand*{\LWR@HTML@tabbing}{%
\LWR@forcenewpage%
\LWR@atbeginverbatim{3}{tabbing}%
\LWR@print@tabbing%
}

\newcommand*{\LWR@HTML@endtabbing}{%
    \LWR@print@endtabbing%
    \LWR@afterendverbatim{1}%
}

\LWR@formatted{tabbing}
\LWR@formatted{endtabbing}


\end{warpHTML}
```

70 Theorems

\newtheorem {⟨*text*⟩} [⟨*counter*⟩] -or- [⟨*oldname*⟩] {⟨*text*⟩}

A few minor changes are made to supply HTML tags.

- The entire theorem is placed into a of class theoremcontents.
- The label for each theorem is placed inside a of class theoremlabel.
- The contents are placed inside a of class theoremcontents.

for HTML output:

```
\begin{warpHTML}
```

\@begintheorem {⟨*name*⟩} {⟨*number*⟩}

```
\renewcommand{\@begintheorem}[2]{%
\LWR@forcenewpage
\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ }]\itshape
}
```

\@opargbegintheorem {⟨*name*⟩} {⟨*number*⟩} {⟨*oparg*⟩}

```
\renewcommand{\@opargbegintheorem}[3]{%
\LWR@forcenewpage
\BlockClass{theoremcontents}
\trivlist
\item[\InlineClass{theoremlabel}{#1\ #2\ (#3)\ }]\itshape
}
```

\@endtheorem

```
\renewcommand*{\@endtheorem}{%
\endtrivlist
\endBlockClass% theoremcontents
}
```

```
\end{warpHTML}
```

71 Lists

The environments `itemize`, `enumerate`, and `description` are patched when lwarp is started. These patches support the standard LaTeX environments, as well as those of enumerate, enumitem, and paralist, and at least the French version of babel. Additional patches are done on a package-specific basis.

The LaTeX source for `itemize` and `enumerate` are found in `source2e`, but the source for `description` is found in `article.cls`, etc.

empty item To have an empty item,use `\mbox{}` or a trailing backslash. This forces a new line in print output, matching the new line which will appear in HTML output. Ex:

```
begin{itemize}
item \mbox{}
    \begin{itemize}
...
    \end{itemize}
item \
    \begin{itemize}
```

```
...
  \end{itemize}
```

\makelabel While inside a list environment, lwarp nullifies a number of TEX horizontal skip and fill commands, allowing the user to define \makelabel for print mode while HTML mode ignores those commands.

⚠ label font When defining \makelabel in a list environment, use \textbf etc. instead of \bfseries.

71.1 List environment

for HTML output:
```
\begin{warpHTML}
```

\LWR@printcloselist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
```

\LWR@printopenlist May be locally redefined by enumerate or description.

```
\newcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
```

\@mklab Removes PDF spacing.

```
\AtBeginDocument{
\def\@mklab#1{%
%     \hfil %
    #1}
\let\makelabel\@mklab
}
```

\@donoparitem Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\@donoparitem{%
  \@noparitemfalse
%   \global\setbox\@labels\hbox{\hskip -\leftmargin
%                               \unhbox\@labels
%                                \hskip \leftmargin}%
%   \if@minipage\else
%     \@tempskipa\lastskip
%     \vskip -\lastskip
%     \advance\@tempskipa\@outerparskip
%     \advance\@tempskipa -\parskip
%     \vskip\@tempskipa
%   \fi
}
```

\@item Modified for HTML output by replacing TEX boxes with plain text. Also removes PDF spacing.

```
\def\LWR@HTML@item[#1]{%
\LWR@traceinfo{@item}
  \if@noparitem
    \@donoparitem
  \else
%     \if@inlabel
%       \indent
        \par
%     \fi
    \ifhmode
%       \unskip\unskip
        \par
    \fi
    \if@newlist
      \if@nobreak
        \@nbitem
      \else
%         \addpenalty\@beginparpenalty
%         \addvspace\@topsep
%         \addvspace{-\parskip}%
      \fi
    \else
%       \addpenalty\@itempenalty
%       \addvspace\itemsep
    \fi
    \global\@inlabeltrue
  \fi
%   \everypar{%
    \@minipagefalse
    \global\@newlistfalse


%     \if@inlabel
%       \global\@inlabelfalse


%       {\setbox\z@\lastbox
%        \ifvoid\z@
%          \kern-\itemindent
%        \fi}%


%       \box\@labels
%       \penalty\z@
%     \fi


%     \if@nobreak
%       \@nobreakfalse
%       \clubpenalty \@M
%     \else
%       \clubpenalty \@clubpenalty
%       \everypar{}%
%     \fi}%
```

```
  \if@noitemarg
    \@noitemargfalse
    \if@nmbrlist

      \refstepcounter\@listctr
    \fi
  \fi


    \makelabel{#1} % extra space
%   \sbox\@tempboxa{\makelabel{#1}%
%   \global\setbox\@labels\hbox{%
%     \unhbox\@labels
%     \hskip \itemindent
%     \hskip -\labelwidth
%     \hskip -\labelsep
%     \ifdim \wd\@tempboxa >\labelwidth
%       \box\@tempboxa

%     \else
%       \hbox to\labelwidth {\unhbox\@tempboxa}%
%     \fi
%     \hskip \labelsep}%
  \ignorespaces%
}
```

\@nbitem

```
\def\@nbitem{%
%   \@tempskipa\@outerparskip
%   \advance\@tempskipa -\parskip
%   \addvspace\@tempskipa
}
```

\LWR@listitem [⟨*label*⟩]

Handles \item inside a list, itemize, or enumerate.

See \LWR@openparagraph where extra \hspace is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@listitem}{%
\LWR@stoppars%
\LWR@startnewdepth{listitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

\LWR@nulllistfills Nullifies various TEX fill commands, in case they are used inside \makelabel. Problems are caused when these are nullified all the time.

```
\newcommand*{\LWR@nulllistfills}{%
```

```
\renewcommand*{\hss}{}%
\renewcommand*{\llap}[1]{##1}%
\renewcommand*{\rlap}[1]{##1}%
\renewcommand*{\hfil}{}%
\renewcommand*{\hfilneg}{}%
\renewcommand*{\hfill}{}%
}
```

Env `list` {⟨*label*⟩} {⟨*commands*⟩}

```
\newcommand*{\LWR@liststart}{%
\LWR@traceinfo{LWR@liststart}%
\LWR@stoppars%
\LWR@pushoneclose{list}%
\LWR@htmltag{\LWR@printopenlist}\LWR@orignewline%
\LWR@startpars%
\setlength{\topsep}{0pt}%
\setlength{\partopsep}{0pt}%
\setlength{\itemsep}{0pt}%
\setlength{\parsep}{0pt}%
\setlength{\leftmargin}{0pt}%
\setlength{\rightmargin}{0pt}%
\setlength{\listparindent}{0pt}%
\setlength{\itemindent}{0pt}%
\setlength{\labelsep}{1em}%
\LWR@nulllistfills%
}
```

```
\newcommand*{\LWR@listend}{%
\LWR@traceinfo{LWR@listend}%
\LWR@stoppars%
\LWR@closeprevious{list}%
\LWR@startpars%
}
```

71.2 Itemize

`\LWR@itemizeitem` [⟨*label*⟩]

Handles `\item` inside an itemize or enumerate.

See `\LWR@openparagraph` where extra `\hspace` is used to leave room for the label while inside a list during paragraph construction.

```
\newcommand*{\LWR@itemizeitem}{%
\LWR@stoppars%
\LWR@startnewdepth{listitem}%
\LWR@htmltag{li}%
\LWR@startpars%
\LWR@origitem%
}
```

Env itemize [⟨*options*⟩]

```
\newcommand*{\LWR@itemizestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

71.3 Enumerate

An HTML unordered list is used with customized LaTeX-generated labels.

Env enumerate [⟨*options*⟩]

```
\newcommand*{\LWR@enumeratestart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}
\renewcommand*{\LWR@printopenlist}{ul style="\LWR@print@mbox{list-style-type:none}"}
\let\item\LWR@itemizeitem%
\LWR@nulllistfills%
}
```

71.4 Description

\LWR@descitem [⟨*label*⟩] Handles an \item inside a description.

```
\newcommand*{\LWR@descitem}[1][]%
{%
\LWR@stoppars%
\LWR@setlatestname{#1}%
\LWR@startnewdepth{descitem}%
```

Temporarily disable \hspace, which article.cls, etc. use per \item for descriptions only. This causes lwarp to mistakenly place an empty span between HTML list tags.

```
\LWR@select@html@nohspace%
```

Process the original \item code:

```
\LWR@origitem[]%
```

Restore \hspace for use in the item text:

```
\LWR@select@html@hspace%

\LWR@htmltag{dt}#1\LWR@htmltag{/dt}%
\LWR@orignewline%
\LWR@htmltag{dd}%
```

```
\LWR@startpars%
}
```

Env description [⟨*options*⟩]

```
\newcommand*{\LWR@descriptionstart}{%
\renewcommand*{\LWR@printcloselist}{\LWR@printclosedescription}
\renewcommand*{\LWR@printopenlist}{dl}
\let\item\LWR@descitem%
\LWR@nulllistfills%
}
```

71.5 Patching the lists

\LWR@patchlists Patches list environments.

\LWR@patchlists remembers \item as defined by whatever packages have been loaded, then patches the itemize, enumerate, and description environments and \item. This works with the native LaTeX environments, as well as those provided by enumitem, enumerate, and paralist.

```
\newcommand*{\LWR@patchlists}{%
    \LetLtxMacro\item\LWR@listitem%
    \LetLtxMacro\@item\LWR@HTML@item%
    \renewcommand*{\@trivlist}{%
        \LWR@traceinfo{@trivlist start}%
        \LWR@liststart%
        \LWR@orig@trivlist%
        \LWR@traceinfo{@trivlist done}%
    }%
    \renewcommand*{\trivlist}{%
        \LWR@traceinfo{trivlist}%
        \LWR@origtrivlist%
    }%
    \renewcommand*{\endtrivlist}{%
        \LWR@traceinfo{endtrivlist start}%
        \LWR@origendtrivlist\LWR@listend%
        \LWR@traceinfo{endtrivlist done}%
    }%
    \renewcommand*{\itemize}{%
        \LWR@itemizestart\LWR@origitemize%
    }%
    \renewcommand*{\enumerate}{%
        \LWR@enumeratestart\LWR@origenumerate%
    }%
    \renewcommand*{\description}{%
        \LWR@descriptionstart\LWR@origdescription%
    }%
}
```

\LWR@restoreoriglists Restores the original `trivlist` environment.

```
\newcommand*{\LWR@restoreoriglists}{%
\LWR@traceinfo{LWR@restoreoriglists}%
\LetLtxMacro\item\LWR@origitem%
\LetLtxMacro\@item\LWR@orig@item%
\let\@trivlist\LWR@orig@trivlist%
\let\trivlist\LWR@origtrivlist%
\let\endtrivlist\LWR@origendtrivlist%
\LetLtxMacro\itemize\LWR@origitemize%
\LetLtxMacro\enditemize\LWR@endorigitemize%
\LetLtxMacro\enumerate\LWR@origenumerate%
\LetLtxMacro\endenumerate\LWR@endorigenumerate%
\LetLtxMacro\description\LWR@origdescription%
\LetLtxMacro\enddescription\LWR@endorigdescription%
\let\@mklab\LWR@orig@mklab%
\let\makelabel\LWR@origmakelabel%
\let\@donoparitem\LWR@orig@donoparitem%
\let\@nbitem\LWR@orig@nbitem%
}

\end{warpHTML}
```

72 Tabular

This is arguably the most complicated part of the entire package. Numerous tricks are employed to handle the syntax of the LaTeX core and the various tabular-related packages.

72.1 Limitations

Tabular mostly works as expected, but pay special attention to the following, especially if working with environments, macros inside tabulars, multirows, siunitx `S` columns, or the packages multirow, longtable, supertabular, or xtab.

Defining macros and environments:

⚠ Misplaced alignment tab character &

- When defining environments or macros which include `tabular` and instances of the `&` character, it may be necessary to make `&` active before the environment or macro is defined, then restore `&` to its default catcode after, using the following commands. These are are ignored in print mode.

```
\StartDefiningTabulars
<define macros or environments using tabular and & here>
\StopDefiningTabulars
```

⚠ floatrow This includes before and after defining any macro which used `\ttabbox` from floatrow.

⚠ tabular inside another environment

- When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars  % because  &  is  used  in  a
definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

Cell contents:

⚠ macro in a table

- Using a custom macro inside a tabular data cell may result in an extra HTML data cell tag, corrupting the HTML table. To avoid this, use \TabularMacro just before the macro. This is ignored in print mode.

```
\TabularMacro\somemacro & more row contents \\
```

Column specifiers:

@ and !

- Only one each of @ and ! is used at each column, and they are used in that order.

\multirow

- In \multirow cells, the print version may have extra instances of <, >, @, and ! cells on the second and later rows in the \multirow which do not appear in the HTML version.

⚠ \newcolumntype

- \newcolumntype is ignored; unknown column types are set to l.

Rules:

- Doubled \hlines, \midrules, and vertical rules are supported.

vertical rules

- Vertical rules next to either side of an @ or ! column are displayed on both sides of the column.

width and trim

- Width options are honored. Trim options are converted to rounded top corners. Trim corners are not rounded with @ or ! columns, and full-width rules ignore trim.

full-width rules

- \toprule, \midrule, \bottomrule, and \hline ignore trim. When given an optional width, each cell is styled to create the custom border. Without an optional width, the entire row is given a class to assign the standard border.

combined rules

- If you wish to use \cmidrule followed by \bottomrule, it may be necessary to use:

```
\cmidrule{2-3} \\[-2ex]
\bottomrule
```

The optional -2ex is ignored in HTML, but improves the visual formatting in the print output.

⚠ \warpprintonly
⚠ Misplaced \noalign

- For \toprule and \bottomrule, when combined with a warpprint or warpHTML environment, if a "Misplaced \noalign" error occurs, change

  ```
  This & That \endhead
  ```

  to

  ```
  \warpprintonly{This & That \endhead}
  ```

  and likewise with the other \end headings. Keep the \endfirsthead row unchanged, as it is still relevent to HTML output.

Other:

- tabularx ignores the width, but X columns do produce paragraph columns or multicolumns.

longtable headings

- For longtable, place headings and footings which do not apply to HTML inside \warpprintonly{}.

⚠ S columns

- For S columns (from the siunitx package), while producing print output, anything non-numeric must be placed inside { } braces, including commands such as \multirow. While producing HTML output, though, anything placed inside braces is not seen by lwarp's tabular handling algorithm. To resolve this problem, make a copy of the row, with one version for print output, containing the extra braces, and another version for HTML output, without the extra braces, such as:

  ```
  \warpprintonly{1 & 2 & {\multirow{2}{2cm}{Text}} & 3 \\}
  \warpHTMLonly{1 & 2 & \multirow{2}{2cm}{Text} & 3 \\}
  ```

for HTML output:

```
\begin{warpHTML}
```

72.2 Temporary package-related macros

These macros are temporary placeholders for macros defined by various packages. If the relevent package is not loaded, these placeholders are used instead.

72.2.1 arydshln

Emualated by the original LaTeX non-dashed versions.

```
\LetLtxMacro\hdashline\hline
\LetLtxMacro\cdashline\cline
\LetLtxMacro\firsthdashline\hline
\LetLtxMacro\lasthdashline\hline
```

72.3 Token lookahead

Used by \LWR@futurenonspacelet to look at the next token.

\LWR@mynexttoken

```
\newcommand\LWR@mynexttoken\relax
```

\futurelet copies the next token then executes a function to analyze

\LWR@futurenonspacelet does the same, but ignores intervening white space

Based on the booktabs style:

\LWR@futurenonspacelet

```
\def\LWR@futurenonspacelet#1{\def\LWR@cs{#1}%
\afterassignment\LWR@fnslone\let\nexttoken= }
\def\LWR@fnslone{\expandafter\futurelet\LWR@cs\LWR@fnsltwo}
\def\LWR@fnsltwo{%
\expandafter\ifx\LWR@cs\@sptoken\let\next=\LWR@fnslthree%
\else\let\next=\nexttoken\fi\next}
\def\LWR@fnslthree{\afterassignment\LWR@fnslone\let\next= }
```

\LWR@getmynexttoken Looks ahead and copies the next token into \LWR@mynexttoken.

```
\newcommand*{\LWR@getmynexttoken}{%
\LWR@traceinfo{LWR@getmynexttoken}%
% nothing must follow this next line
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@tabledatacolumntag
}
```

72.4 Tabular variables

Bool LWR@startedrow True if should print a row tag before this column.

```
\newbool{LWR@startedrow}
\boolfalse{LWR@startedrow}
```

Bool LWR@tabularcelladded True if have added a data cell for this position.

```
\newbool{LWR@tabularcelladded}
\boolfalse{LWR@tabularcelladded}
```

Ctr LWR@hlines Number of \hlines or \midrules above the next row.

```
\newcounter{LWR@hlines}
```

Ctr LWR@hdashedlines Number of arydshln dashed lines above the next row.

```
\newcounter{LWR@hdashedlines}
```

Bool LWR@doingtbrule True if the next row will have a top/bottom rule above it.

```
\newbool{LWR@doingtbrule}
\boolfalse{LWR@doingtbrule}
```

Bool LWR@doingcmidrule — True if the next row will have a cmidrule above it.

This is used by \LWR@tabularfinishrow to force a final empty row to create the border for the \cmidrule.

```
\newbool{LWR@doingcmidrule}
\boolfalse{LWR@doingcmidrule}
```

Bool LWR@tableparcell — True if are handling a paragraph inside a table cell, so must close the paragraph tag before moving on.

```
\newbool{LWR@tableparcell}
```

Bool LWR@skippingmrowcell — True if are doing an empty \multirow cell, and thus there is no data tag to close.

```
\newbool{LWR@skippingmrowcell}
```

Bool LWR@skippingmcolrowcell — True if are doing an empty \multicolumnrow cell, and thus there is no data tag to close, and do not print @ and ! columns.

```
\newbool{LWR@skippingmcolrowcell}
```

Bool LWR@usedmultirow — Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
\newbool{LWR@usedmultirow}
```

Bool LWR@foundmrowcell — Used to error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
\newbool{LWR@foundmrowcell}
```

Bool LWR@skipatbang — True if just finished a \multicolumn so should not create the trailing @ or ! columns table data cells.

```
\newbool{LWR@skipatbang}
```

Bool LWR@emptyatbang — True if finishing a row and should print empty @ or ! column table data cells.

```
\newbool{LWR@emptyatbang}
```

Bool LWR@intabularmetadata — True if are in a tabular but not in a data cell. Used to prevent extra HTML breaks if not inside table data.

```
\newbool{LWR@intabularmetadata}
\boolfalse{LWR@intabularmetadata}
```

Ctr LWR@tabularDepth — Tracks whether & is being used inside a tabular.

```
\newcounter{LWR@tabulardepth}
\setcounter{LWR@tabulardepth}{0}
```

Ctr `LWR@tabularpardepth` Tracks whether should look ahead at the next token when encountering a `\par` while processing tabular contents.

When `LWR@tabularpardepth` is deeper than `LWR@tabulardepth` then lwarp has started looking at the contents of the `tabular`, and thus any `\par`s encountered must be followed by another token lookahead.

```
\newcounter{LWR@tabularpardepth}
\setcounter{LWR@tabularpardepth}{0}
```

```
\newcommand*{\LWR@colsresult}{}%temp storage for column format results
\newcommand*{\LWR@pposition}{}
\newcommand*{\LWR@pleft}{}
\newcommand*{\LWR@pright}{}
```

`LWR@tablecolspec` Holds the parsed column specification, of total width `LWR@tabletotalLaTeXcols`, not counting `@` and `!` columns.

Will contain a string such as `llrrccpc`, exactly one letter per LaTeX table column, without `@`, `!`, `>`, `<`, or the vertical bar.

`\LWR@strresult` Holds the result of `Str` functions.

```
\providecommand*{\LWR@strresult}{}
\providecommand*{\LWR@strresulttwo}{}
```

`\LWR@origcolspec` Holds the original column specs given to `tabular`.

```
\newcommand*{\LWR@origcolspec}{}
```

Ctr `LWR@tablecolspecwidth` Holds the number of tokens in the table columns specification.

This is includes one for each `@`, `!`, `<`, `>` column, and also one for each of the parameters of `p`, `@`, `!`, `<`, `>` columns, and three for each `D` column.

(This is not the total # of LaTeX columns in the table.)

```
\newcounter{LWR@tablecolspecwidth}
```

Ctr `LWR@tablecolspecindex` While parsing the LaTeX table column specification, starts at 1 and is incremented per token of the specification.

```
\newcounter{LWR@tablecolspecindex}
```

Ctr `LWR@tableLaTeXcolindex` While producing the table, resets to 1 at the start of the table and also at each end of line, and is incremented by 1 by each ampersand.

```
\newcounter{LWR@tableLaTeXcolindex}
```

Ctr LWR@tabletotalLaTeXcols — While parsing a table column specification, begins at 0 and increments by 1 per LaTeX table column. Eventually holds the final number of LaTeX table columns in each row, not counting @ and ! columns. (In HTML, @ and ! cells become their own columns, but are not included in LWR@tabletotalLaTeXcols.)

```
\newcounter{LWR@tabletotalLaTeXcols}
```

Ctr LWR@tabletotalLaTeXcolsnext — Holds the next LaTeX table column index while parsing, equal to one more than LWR@tabletotalLaTeXcols.

```
\newcounter{LWR@tabletotalLaTeXcolsnext}
```

LWR@colatspec — A data array of specifications for @ columns. The leftmost's index is leftedge, the others are counter values. See section 42.

LWR@colbangspec — A data array of specifications for ! columns. The leftmost's index is leftedge, the others are counter values. See section 42.

LWR@colbeforespec — A data array of specifications for > columns.

LWR@colafterspec — A data array of specifications for < columns.

LWR@colbarspec — A data array of specifications for vertical rules.

72.5 Handling &, @, !, and bar

For technical discussion regarding problems redefining \&, See:
http://tex.stackexchange.com/questions/11638/where-do-i-find-futurelets-nasty-behaviour-documented/11860#11860

\LWR@instertatbangcols

```
\newcommand*{\LWR@insertatbangcols}{%
\ifbool{LWR@skipatbang}%
{}%
{%
    \LWR@printatbang{at}{\arabic{LWR@tableLaTeXcolindex}}%
    \LWR@printatbang{bang}{\arabic{LWR@tableLaTeXcolindex}}%
}%
}
```

\LWR@closetabledatacell — If LWR@skippingmrowcell or LWR@skippingmcolrowcell then there is no data tag to close. Otherwise, close any paragraphs, then close the data tag.

```
\newcommand*{\LWR@closetabledatacell}{%
\global\booltrue{LWR@intabularmetadata}%
\ifbool{LWR@exitingtabular}%
{%

    \LWR@stoppars%
```

```
}%
{% not exiting tabular
    \ifboolexpr{bool{LWR@skippingmrowcell} or bool{LWR@skippingmcolrowcell}}%
    {%
        \LWR@stoppars%
```

If not skipping a \multicolumnrow cell, insert the @ and ! columns after this non-existant column.

```
        \ifbool{LWR@skippingmcolrowcell}%
            {}%
            {\LWR@insertatbangcols}%
    }%
    {% not skippingmrowcell
```

Insert any < then any @ and ! column contents, unless muted for the \bottomrule or a \multicolumn:

```
        \unskip%
        \ifboolexpr{%
            bool{LWR@tabularmutemods} or
            bool{LWR@skipatbang} or
            bool{LWR@emptyatbang}
        }%
        {}%
        {\LWR@getexparray{LWR@colafterspec}{\arabic{LWR@tableLaTeXcolindex}}}%
```

Close paragraphs:

```
        \LWR@stoppars%
        \global\boolfalse{LWR@tableparcell}%
```

Close the table data cell.

Close any color s.

```
        \whileboolexpr{test {\ifnumcomp{\value{LWR@cellcolordepth}}{>}{0}}}{%
            \LWR@htmltag{/div}\LWR@orignewline%
            \addtocounter{LWR@cellcolordepth}{-1}%
        }%
```

Skip the @ and ! cells if are closing a multicolumn cell.

```
        \leavevmode\unskip\LWR@htmltag{/td}\LWR@orignewline%
        \global\booltrue{LWR@tabularcelladded}%
        \LWR@insertatbangcols%
    }% not skipping mrowcell
}% not exiting tabular
\global\boolfalse{LWR@skippingmrowcell}%
\global\boolfalse{LWR@skippingmcolrowcell}%
\global\boolfalse{LWR@skipatbang}%
```

Color control. Column is set by >{} for each cell, so it must be cleared here.

```
\gdef\LWR@cellHTMLcolor{}
\gdef\LWR@columnHTMLcolor{}
\setcounter{LWR@cellcolordepth}{0}
}
```

When not used inside a tabular, & performs its original function as recorded here (with catcode 4).

```
\let\LWR@origampmacro&
```

```
\end{warpHTML}
```

72.5.1 Handling &

for HTML output:

```
\begin{warpHTML}
```

& Will behave depending on whether it is being used inside tabular.

& is redefined to test whether it is inside a tabular environment, in which case it performs special processing for HTML conversion. If not, it behaves normally.

```
\newcommand*{\LWR@tabularampersand}{%
\LWR@traceinfo{LWR@tabularampersand}%
\ifnumcomp{\value{LWR@tabulardepth}}{>}{0}%
{%
```

If not skipping a multirow cell, close the current data cell.

```
    \unskip%
    \LWR@closetabledatacell%
```

Move to the next column.

```
    \addtocounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
    \global\boolfalse{LWR@tabularcelladded}%
```

Look at the next token to decide multi or single column data tag.

```
    \LWR@getmynexttoken%
}%
```

If not inside a tabular, performs the original action:

```
{\LWR@origampmacro}%
}
```

& is left with its original catcode for now.

tikz package seems to require & be left alone until after tikz has been loaded. Also, cleveref uses the ampersand in one of its options.

& is made active inside a tabular.

& is left alone when in math alignments.

72.5.2 Filling an unfinished row

\LWR@tabularfinishrow Adds empty table cells if necessary to finish the row.

At the end of the table, if any bottom rules are requested then an empty row must be generated to form the borders which show the rules.

```
\newcommand*{\LWR@tabularfinishrow}{%
```

If not exiting the tabular, or doing a rule, or have already started a row, finish this row:

```
\ifboolexpr{%
    not bool {LWR@exitingtabular} or%
    bool{LWR@doingtbrule} or%
    bool{LWR@doingcmidrule} or%
    test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
    test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
    bool{LWR@startedrow}%
}{%
```

To temporarily turn off LWR@exitingtabular so that table data tags will still be generated:

If generating a final row for the \bottomrule borders, turn off the @, !, <, and > column output:

```
\ifbool{LWR@exitingtabular}{%
    \global\booltrue{LWR@tabularmutemods}%
}{%
    \global\boolfalse{LWR@tabularmutemods}%
}%
```

Locally reenable the table data tags until finished with the final row:

```
\global\boolfalse{LWR@exitingtabular}%
```

Generate table data tags and ampersands until the right edge:

```
\whileboolexpr{%
    test {
      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
    } or %
```

```
    (%
        bool{LWR@intabularmetadata} and%
        not bool{LWR@tabularcelladded} and%
        test {
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}
        }%
    )%
}%
{%
    \LWR@tabledatasinglecolumntag%
```

The following is essentially `\LWR@tabularampersand` with `LWR@emptyatbang` added to empty the following cells:

```
    \LWR@closetabledatacell%
    \addtocounter{LWR@tableLaTeXcolindex}{1}%
    \global\boolfalse{LWR@tabularcelladded}%
    \global\booltrue{LWR@emptyatbang}%
```

Starts the next cell:

```
  \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
        {\LWR@getmynexttoken}%
        {}%
}%
```

Reenable the original `LWR@exitingtabular` to close the entire table:

```
\ifbool{LWR@tabularmutemods}{%
    \global\booltrue{LWR@exitingtabular}%
}{%
    \global\boolfalse{LWR@exitingtabular}%
}%
\global\boolfalse{LWR@tabularmutemods}%

\global\boolfalse{LWR@emptyatbang}%
}{}% ifboolexpr
}
```

72.6 Handling \\

Inside tabular, `\\` is redefined to `\LWR@tabularendofline`

Throws away options `\\[dim]` or `\\*`

`\LWR@tabularendofline`

```
\NewDocumentCommand{\LWR@tabularendofline}{s o}{%
```

Finish the row:

```
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}%
    {\LWR@tabularfinishrow}%
    {\LWR@closetabledatacell}%
\LWR@htmltag{/tr}\LWR@orignewline%
```

xcolor row color support:

```
\@rowc@lors%
```

No longer inside a data cell:

```
\global\booltrue{LWR@intabularmetadata}%
```

Not yet started a table row:

```
\global\boolfalse{LWR@startedrow}%
```

Additional setup:

```
\setcounter{LWR@hlines}{0}%
\setcounter{LWR@hdashedlines}{0}%
\global\boolfalse{LWR@doingtbrule}%
\global\boolfalse{LWR@doingcmidrule}%
\LWR@clearmidrules%
\gdef\LWR@rowHTMLcolor{}%
```

Start at first column:

```
\setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Allow TEX to flush the pending paragraph. Not doing so causes a slowdown for very large tables.

```
\LWR@stoppars
\LWR@origpar
```

Look at the next token to decide between single column data tag or a special case:

```
\LWR@getmynexttoken%
}
```

72.7 Looking ahead in the column specifications

`\LWR@columnspeclookahead` {⟨*offset*⟩}

Looks `offset` tokens ahead in the column specification, setting `\LWR@strresulttwo`.

The w column alignment will be seen as a single unit such as {c}.

```
\newcommand*{\LWR@columnspeclookahead}[1]{%
\setcounter{LWR@tempcountone}{\value{LWR@tablecolspecindex}}%
\addtocounter{LWR@tempcountone}{#1}%
\fullexpandarg%
\StrChar{\LWR@origcolspec}{\arabic{LWR@tempcountone}}[\LWR@strresulttwo]%
```

Get the contents of the first group in \LWR@strresulttwo:

```
\exploregroups%
\StrChar{\LWR@strresulttwo}{1}[\LWR@strresulttwo]%
\noexploregroups%
}
```

72.8 Parsing @, >, <, !, bar columns

Holds the parsed argument for @, >, <, or ! columns:

```
\newcommand*{\LWR@colparameter}{}
```

\LWR@parseatcolumn Handles @{text} columns.

```
\newcommand*{\LWR@parseatcolumn}{%
```

Move to the next token after the '@':

```
\LWR@traceinfo{at column}%
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into \LWR@colparameter, expanding once:

```
\LWR@traceinfo{about to read the next token:}%
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@traceinfo{have now read the next token}%
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \LWR@traceinfo{at the left edge}%
    \LWR@setexparray{LWR@colatspec}{leftedge}{\LWR@colparameter}%
    \LWR@traceinfo{at the left edge: %
    \LWR@getexparray{LWR@colatspec}{leftedge}}%
}%
{% not at the left edge:
    \LWR@traceinfo{not at the left edge}%
```

```
    \LWR@setexparray{LWR@colatspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
    \LWR@traceinfo{at \arabic{LWR@tabletotalLaTeXcols}: %
    \LWR@getexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcols}}}%
}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parsebangcolumn` Handles `!{text}` columns.

```
\newcommand*{\LWR@parsebangcolumn}{%
```

Move to the next token after the '!':

```
\LWR@traceinfo{bang column}%
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token into `\LWR@colparameter`, expanding once:

```
\LWR@traceinfo{about to read the next token:}%
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]
\fullexpandarg%
```

Store the result into a data array, expanding once out of `\LWR@colparameter`:

```
\LWR@traceinfo{have now read the next token}%
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \LWR@traceinfo{at the left edge}%
    \LWR@setexparray{LWR@colbangspec}{leftedge}{\LWR@colparameter}%
}%
{% not at the left edge:
    \LWR@traceinfo{not at the left edge}%
    \LWR@setexparray{LWR@colbangspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
    \LWR@traceinfo{bang \arabic{LWR@tabletotalLaTeXcols}: \LWR@colparameter!}%
}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parsebeforecolumn` Handles `>{text}` columns.

```
\newcommand*{\LWR@parsebeforecolumn}{%
```

Move to the next token after the '>':

```
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@setexparray{LWR@colbeforespec}%
    {\arabic{LWR@tabletotalLaTeXcolsnext}}{\LWR@colparameter}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parseaftercolumn Handles <{text} columns.

```
\newcommand*{\LWR@parseaftercolumn}{%
```

Move to the next token after the '<':

```
\addtocounter{LWR@tablecolspecindex}{1}%
```

Read the next token, expanding once into \LWR@colparameter:

```
\expandarg%
\StrChar{\LWR@origcolspec}%
    {\arabic{LWR@tablecolspecindex}}[\LWR@colparameter]%
\fullexpandarg%
```

Store the result into a data array, expanding once out of \LWR@colparameter:

```
\LWR@setexparray{LWR@colafterspec}%
    {\arabic{LWR@tabletotalLaTeXcols}}{\LWR@colparameter}%
\let\LWR@colparameter\relax%
\global\booltrue{LWR@validtablecol}%
}
```

\LWR@parsebarcolumn Handles vertical rules.

```
\newcommand*{\LWR@parsebarcolumn}{%
\LWR@traceinfo{LWR@parsebarcolumn}%
```

Remember the bar at this position:

```
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
    \ifdefstring{\LWR@tempone}{tvertbarl}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldouble}}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarl}}%
}%
```

```
{% not at the left edge:
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarr}%
    {%
        \LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdouble}%
    }%
    {%
        \LWR@setexparray{LWR@colbarspec}%
            {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarr}%
    }%
}%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parsecoloncolumn` Handles vertical rules.

```
\newcommand*{\LWR@parsecoloncolumn}{%
\LWR@traceinfo{LWR@parsecoloncolumn}%
```

Remember the bar at this position:

```
\ifnumcomp{\value{LWR@tabletotalLaTeXcols}}{=}{0}%
{% left edge of the table:
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
    \ifdefstring{\LWR@tempone}{tvertbarldash}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldoubledash}}%
    {\LWR@setexparray{LWR@colbarspec}{leftedge}{tvertbarldash}}%
}%
{% not at the left edge:
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcols}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarrdash}%
    {\LWR@setexparray{LWR@colbarspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdoubledash}}%
    {\LWR@setexparray{LWR@colbarspec}%
        {\arabic{LWR@tabletotalLaTeXcols}}{tvertbarrdash}}%
}%
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@parsesemicoloncolumn` Handles vertical rules.

```
\newcommand*{\LWR@parsesemicoloncolumn}{%
```

Treat ; as a : column:

```
\LWR@parsecoloncolumn%
```

Skip the following width token:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}
```

72.9 Parsing ‘l’, ‘c’, or ‘r’ columns

\LWR@parsenormalcolumn {⟨*thiscolumn*⟩}

Add to the accumulated column specs, advance counters, and pre-clear another column of at, before, and after specs.

```
\newcommand*{\LWR@parsenormalcolumn}[1]{%
\addtocounter{LWR@tabletotalLaTeXcols}{1}%
\addtocounter{LWR@tabletotalLaTeXcolsnext}{1}%

\LWR@setexparray{LWR@tablecolspec}{\arabic{LWR@tabletotalLaTeXcols}}{#1}%

\LWR@traceinfo{normal column \arabic{LWR@tabletotalLaTeXcols}: #1}%
\LWR@setexparray{LWR@colatspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbangspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbeforespec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colafterspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\LWR@setexparray{LWR@colbarspec}{\arabic{LWR@tabletotalLaTeXcolsnext}}{}%
\global\booltrue{LWR@validtablecol}%
}
```

72.10 Parsing ‘p’, ‘m’, or ‘b’ columns

\LWR@parsepcolumn {⟨*thiscolumn*⟩} The width will be ignored.

```
\newcommand*{\LWR@parsepcolumn}[1]{%
```

Converts to the given column type:

```
\LWR@parsenormalcolumn{#1}%
```

Skips the following width token:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}
```

72.11 Parsing ‘w’ columns

\LWR@parsewcolumn The width will be ignored.

```
\newcommand*{\LWR@parsewcolumn}{%
```

```
\LWR@columnspeclookahead{1}%
\expandafter\LWR@parsenormalcolumn\expandafter{\LWR@strresulttwo}%
```

Skips the following width and alignment tokens:

```
\addtocounter{LWR@tablecolspecindex}{2}%
}
```

72.12 Parsing '*' columns

\LWR@parsestarcolumn Star columns should already have been expanded, so this should never be used.

```
\newcommand*{\LWR@parsestarcolumn}{%
    \addtocounter{LWR@tablecolspecindex}{2}%
}
```

72.13 Parsing 'D' columns

From the dcolumn package.

\LWR@parseDcolumn {⟨*thiscolumn*⟩} The three parameters will be ignored.

```
\newcommand*{\LWR@parseDcolumn}[1]{%
```

Converts to the given column type.

```
\LWR@parsenormalcolumn{#1}%
```

Skips the following three parameters.

```
\addtocounter{LWR@tablecolspecindex}{3}%
}
```

72.14 Expanding the star column specifiations

Ctr LWR@starcount Internal count for duplicating star columns.

```
\newcount\LWR@starcount
```

\LWR@expcolspec Temporary storage used to build the expanded column specifier.

```
\newcommand*{\LWR@expcolspec}{}
```

Ctr LWR@splitstarindex Indexes into the column specifiers.

```
\newcounter{LWR@splitstarindex}
```

Ctr LWR@splitstarcopies Number of copies.

```
\newcounter{LWR@splitstarcopies}
```

\LWR@splitstarcontents Contents to duplicate.

```
\newcommand*{\LWR@splitstarcontents}{}
```

\expandcolspec Expands \LWR@origcolspec for star columns.

```
\newcommand*{\expandcolspec}{%
```

Find the position of any star token.

```
    \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
```

Expand until no stars are found:

```
    \whileboolexpr{ test {\ifnumgreater{\LWR@tempone}{0}}}%
    {%
```

Begin with any characters to the left of the star.

```
        \setcounter{LWR@splitstarindex}{\LWR@tempone}%
        \addtocounter{LWR@splitstarindex}{-1}%
      \StrLeft{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@expcolspec]%
```

Move past the star to remember its number of copies.

```
        \addtocounter{LWR@splitstarindex}{2}%
        \StrChar{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@tempone]%
       \setcounter{LWR@splitstarcopies}{\expandafter\@firstofone\LWR@tempone}%
```

Move past the number of copies and remember the contents.

```
        \addtocounter{LWR@splitstarindex}{1}%
     \StrChar{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\LWR@splitstarcontents]%
```

For each copy, append the contents.

```
        \ifnumgreater{\value{LWR@splitstarcopies}}{0}%
        {%
            \LWR@starcount=\value{LWR@splitstarcopies}%
            \loop
                \appto\LWR@expcolspec{%
```

(Remove the enclosing braces.)

Table 10: Tabular baseline

l	p	m	b	r
			bot	
		mid	bot	
l	par	mid	bot	r
	par	mid		
	par			

```
                    \expandafter\@firstofone\LWR@splitstarcontents%
                }%
                \advance \LWR@starcount -1
            \ifnum \LWR@starcount>0 \repeat
        }{}%
```

Remove any token to the left, and append the rightmost remainding tokens.

```
    \StrGobbleLeft{\LWR@origcolspec}{\value{LWR@splitstarindex}}[\colspecremainder]%
        \appto{\LWR@expcolspec}{\colspecremainder}%
```

Remember the final result.

```
        \edef\LWR@origcolspec{\LWR@expcolspec}%
```

See if more stars exist.

```
        \StrPosition{\LWR@origcolspec}{*}[\LWR@tempone]%
    }%
}
```

72.15 Parsing the column specifications

⚠ tabular baselines

HTML CSS cannot exactly match the LaTeX concept of a baseline for a table row. Table 10 shows the LaTeX results for various vertical-alignment choices, with the baseline of the first column drawn across all the columns for comparison. See the p column specification in table 11 for details.

Table 11 describes how each kind of column is converted to HTML.

Bool LWR@validtablecol True if found a valid table column type.

```
\newbool{LWR@validtablecol}
```

Bool LWR@opttablecol True if found a table column optional argument.

```
\newbool{LWR@opttablecol}
```

\LWR@parsetablecols {⟨*colspecs*⟩}

Table 11: Tabular html column conversions

l, r, c: Converted to table cells without paragraph tags.
Uses css `vertical-align:middle` so that top or bottom-aligned cells may go above or below this cell.

p: Converted to table cells with paragraph tags. Ref: Table 10, LaTeX places the top line of a parbox aligned with the rest of the text line, so css `vertical-align:bottom` is used to have the html result appear with the paragraph extending below the L, R, C cells at the middle, if possible. This may be confusing as a P cell may not top-align with an L,R,C cell in the html conversion, especially in the presence of a B cell, and two P cells side-by-side will be aligned at the bottom instead of the top. Some adjustment of the css may be desired, changing `td.tdp`, `td.tdP`, `td.tdprule`, and `td.tdPrule` to `vertical-align: middle`. Another possibility is to change L,R,C, and P to `vertical-align: top` and not worry about the alignment of B and M cells or trying to approximate LaTeX baselines.

m: With paragraph tags, css `vertical-align:middle`.

b: With paragraph tags, css `vertical-align:top` so that the bottom of the text is closest to the middle of the text line.

P, M, B: Horizontally-centered versions.

S: Converted to 'r'. Ignores optional argument. From the siunitx package.

D: Converted to 'c'. From the dcolumn package.

@, !, >, <: One each, in that order.

|: Vertical rule.

Unknown: Converted to 'l'.

`\newcolumn`: Currently treated as unknown.

Scans the column specification left to right.

Builds \LWR@tablecolspec with the final specification, one LaTeX column per entry. The final number of LaTeX columns in each row is stored in LWR@tabletotalLaTeXcols, which is the number of & and \\ in each line, but which does not include @, !, <, > specifications in the count.

```
\newcommand*{\LWR@parsetablecols}[1]{%
\LWR@traceinfo{LWR@parsetablecols}%
```

Remember the original supplied column spec:

```
\renewcommand*{\LWR@origcolspec}{#1}%
```

Remove spaces:

```
\expandarg%
\StrSubstitute{\LWR@origcolspec}{ }{}[\LWR@origcolspec]%
```

Expand any star columns:

```
\expandcolspec%
```

The parsed column spec data array, LWR@tablecolspec, will be overwritten with new values.

Total number of columns found so far. Also pre-initialize the first several columns of specs:

```
\setcounter{LWR@tabletotalLaTeXcols}{0}%
\setcounter{LWR@tabletotalLaTeXcolsnext}{1}%
\LWR@setexparray{LWR@colatspec}{leftedge}{}%
\LWR@setexparray{LWR@colatspec}{1}{}%
\LWR@setexparray{LWR@colatspec}{2}{}%
\LWR@setexparray{LWR@colatspec}{3}{}%
\LWR@setexparray{LWR@colbangspec}{leftedge}{}%
\LWR@setexparray{LWR@colbangspec}{1}{}%
\LWR@setexparray{LWR@colbangspec}{2}{}%
\LWR@setexparray{LWR@colbangspec}{3}{}%
\LWR@setexparray{LWR@colbeforespec}{1}{}%
\LWR@setexparray{LWR@colbeforespec}{2}{}%
\LWR@setexparray{LWR@colbeforespec}{3}{}%
\LWR@setexparray{LWR@colafterspec}{1}{}%
\LWR@setexparray{LWR@colafterspec}{2}{}%
\LWR@setexparray{LWR@colafterspec}{3}{}%
\LWR@setexparray{LWR@colbarspec}{leftedge}{}%
\LWR@setexparray{LWR@colbarspec}{1}{}%
\LWR@setexparray{LWR@colbarspec}{2}{}%
\LWR@setexparray{LWR@colbarspec}{3}{}%
```

Starting at the first column specification:

```
\setcounter{LWR@tablecolspecindex}{1}%
```

Place the colspecs string length into \LWR@strresult, and remember the number of characters in the column specification:

```
\expandarg%
\StrLen{\LWR@origcolspec}[\LWR@strresult]%
\fullexpandarg%
\LWR@traceinfo{original column spec length: \LWR@strresult}%
\setcounter{LWR@tablecolspecwidth}{\LWR@strresult}%
```

Haven't seen any optional arguments so far

```
\global\boolfalse{LWR@opttablecol}%
```

Scan through the column specifications:

```
\whileboolexpr{%
    not test{%
        \ifnumcomp{\value{LWR@tablecolspecindex}}{>}%
            {\value{LWR@tablecolspecwidth}}%
    }%
}%
{%
```

Place the next single-character column type into \LWR@strresult:

```
\expandarg%
\StrChar{\LWR@origcolspec}{\arabic{LWR@tablecolspecindex}}[\LWR@strresult]%
\LWR@traceinfo{position \arabic{LWR@tablecolspecindex}: \LWR@strresult}%
\fullexpandarg%
```

Not yet found a valid column type:

```
\global\boolfalse{LWR@validtablecol}%
```

Skip over any optional arguments, such as siunitx S column:

```
\IfStrEq{\LWR@strresult}{[}{\global\booltrue{LWR@opttablecol}}{}%
```

Throw away anything found inside the optional argument:

```
\ifbool{LWR@opttablecol}%
{}% inside an optional argument
{% not an optional tabular argument
```

Not inside an optional argument, so consider the column type:

```
\IfStrEq{\LWR@strresult}{l}{\LWR@parsenormalcolumn{l}}{}%
\IfStrEq{\LWR@strresult}{c}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{r}{\LWR@parsenormalcolumn{r}}{}%
\IfStrEq{\LWR@strresult}{L}{\LWR@parsenormalcolumn{l}}{}%
\IfStrEq{\LWR@strresult}{C}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{R}{\LWR@parsenormalcolumn{r}}{}%
\IfStrEq{\LWR@strresult}{J}{\LWR@parsenormalcolumn{l}}{}%
```

```
\IfStrEq{\LWR@strresult}{S}{\LWR@parsenormalcolumn{c}}{}%
\IfStrEq{\LWR@strresult}{s}{\LWR@parsenormalcolumn{c}}{}%

\IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@parseatcolumn}{}%
\IfStrEq{\LWR@strresult}{!}{\LWR@parsebangcolumn}{}%
\IfStrEq{\LWR@strresult}{>}{\LWR@parsebeforecolumn}{}%
\IfStrEq{\LWR@strresult}{<}{\LWR@parseaftercolumn}{}%
\IfStrEq{\LWR@strresult}{|}{\LWR@parsebarcolumn}{}%
\IfStrEq{\LWR@strresult}{:}{\LWR@parsecoloncolumn}{}%
\IfStrEq{\LWR@strresult}{;}{\LWR@parsesemicoloncolumn}{}%

\IfStrEq{\LWR@strresult}{p}{\LWR@parsepcolumn{p}}{}%
\IfStrEq{\LWR@strresult}{m}{\LWR@parsepcolumn{m}}{}%
\IfStrEq{\LWR@strresult}{b}{\LWR@parsepcolumn{b}}{}%

\IfStrEq{\LWR@strresult}{w}{\LWR@parsewcolumn}{}%
\IfStrEq{\LWR@strresult}{W}{\LWR@parsewcolumn}{}%
```

A star column:

```
\IfStrEq{\LWR@strresult}{*}{\LWR@parsestarcolumn}{}%
```

From the dcolumn package:

```
\IfStrEq{\LWR@strresult}{D}{\LWR@parseDcolumn{c}}{}%
```

From the tabularx package. X column has no parameter, but will be given paragraph tags.

```
\IfStrEq{\LWR@strresult}{X}{\LWR@parsenormalcolumn{X}}{}%
```

Many people define centered versions "P", "M", and "B":

```
\newcolumntype{P}[1]{>{\centering\arraybackslash}p{#1}}
```

```
\IfStrEq{\LWR@strresult}{P}{\LWR@parsepcolumn{P}}{}%
\IfStrEq{\LWR@strresult}{M}{\LWR@parsepcolumn{M}}{}%
\IfStrEq{\LWR@strresult}{B}{\LWR@parsepcolumn{B}}{}%
```

If this column was an invalid column type, convert it to an l column:

```
\ifbool{LWR@validtablecol}{}{%
    \LWR@traceinfo{invalid column type: \LWR@strresult}%
    \LWR@parsenormalcolumn{l}%
}%
}% not an optional column argument
```

If read the closing bracket, no longer inside the optional argument:

```
\IfStrEq{\LWR@strresult}{]}{\global\boolfalse{LWR@opttablecol}}{}%
```

Move to the next character:

```
\addtocounter{LWR@tablecolspecindex}{1}%
}% whiledo
}%
```

72.16 colortbl and xparse tabular color support

These macros provide a minimal emulation of some colortbl macros which might appear between table cells. If colortbl is loaded, these macros will be replaced with functional versions.

For each of the HTML colors below, the text for the HTML color is set if requested, but the macro is empty if none has been set.

`\rownum` Reserve a counter register.

```
\@ifundefined{rownum}{\newcount\rownum}{}
```

`\@rowcolors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowcolors}{}
```

`\@rowc@lors` Emulated in case xcolor is not used.

```
\newcommand*{\@rowc@lors}{}
```

`\LWR@xcolorrowHTMLcolor` Emulated xcolor row color.

```
\newcommand*{\LWR@xcolorrowHTMLcolor}{}
```

`\LWR@columnHTMLcolor` HTMLstyle code for the column color.

```
\def\LWR@columnHTMLcolor{}
```

`\LWR@rowHTMLcolor` HTMLstyle code for the row color.

```
\def\LWR@rowHTMLcolor{}
```

`\LWR@cellHTMLcolor` HTMLstyle code for the cell color.

```
\def\LWR@cellHTMLcolor{}
```

`\LWR@ruleHTMLcolor` HTMLstyle code for the cell color.

```
\newcommand*{\LWR@ruleHTMLcolor}{}
```

\rowcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩] Print version. The HTML version is in lwarp-colortbl. Used before starting a tabular data cell, thus \LWR@getmynexttoken.

```
\newcommand*{\rowcolor}{\LWR@getmynexttoken}%
```

\arrayrulecolor [⟨*model*⟩] {⟨*color*⟩}

\arrayrulecolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use outside and inside a tabular:

```
\newcommand{\arrayrulecolor}[2][named]{}
\newcommand{\arrayrulecolornexttoken}[2][named]{\LWR@getmynexttoken}
```

\doublerulesepcolor [⟨*model*⟩] {⟨*color*⟩}

\doublerulesepcolornexttoken [⟨*model*⟩] {⟨*color*⟩}

Print versions for use inside and outside a tabular:

```
\newcommand{\doublerulesepcolor}[2][named]{}
\newcommand{\doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}
```

72.17 Starting a new row

\LWR@maybenewtablerow If have not yet started a new table row, begin one now. Creates a new row tag, adding a class for hline or tbrule if necessary.

```
\newcommand*{\LWR@maybenewtablerow}
{%
\ifbool{LWR@startedrow}%
{}% started the row
{% not started the row
```

Remember that now have started the row:

```
    \global\booltrue{LWR@startedrow}%
```

Create the row tag, with a class if necessary.

```
    \global\booltrue{LWR@intabularmetadata}%
    \ifboolexpr{%
        test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
        test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}}%
    }%
    {%
        \LWR@htmltag{tr class="hline" }%
        \LWR@orignewline%
    }%
```

```
    {% not doing hline
        \ifbool{LWR@doingtbrule}%
        {%
            \ifdefvoid{\LWR@ruleHTMLcolor}{%
                \LWR@htmltag{tr class="tbrule"}%
            }{%
                \LWR@htmltag{%
                    tr class="tbrule" % space
                    style="border-top: 1px solid % space
                        \LWR@origpound\LWR@ruleHTMLcolor "%
                }%
            }%
            \LWR@orignewline%
        }%
        {\LWR@htmltag{tr}\LWR@orignewline}%
    }% end of not doing hline
}% end of not started the row
}
```

72.18 Printing vertical bar tags

\LWR@printbartag {⟨*index*⟩}

Adds to a tabular data cell an HTML class name for a left/right vertical bar.

```
\newcommand*{\LWR@printbartag}[1]{%
\LWR@traceinfo{LWR@printbartag !#1!}%
\ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
{}% muting or empty
{% not muting
    \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{#1}}%
    \ifdefempty{\LWR@tempone}{}{ \LWR@tempone}%
}% not muting
\LWR@traceinfo{LWR@printbartag done}%
}
```

72.19 Printing at or bang tags

\LWR@printatbang {⟨*at -or- bang*⟩} {⟨*index*⟩}

```
\newcommand*{\LWR@printatbang}[2]{%
```

Fetch the column at or bang spec:

```
\xdef\LWR@atbangspec{\LWR@getexparray{LWR@col#1spec}{#2}}%
\LWR@traceinfo{atbang: #2 !\LWR@atbangspec!}%
```

Only generate if is not empty;

```
\ifdefempty{\LWR@atbangspec}%
{}%
{% not empty
    \LWR@htmltag{%
        td class="td#1%
        \LWR@subaddcmidruletrim{}{}%
        \LWR@printbartag{#2}%
        "%
        \LWR@tdstartstyles%
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%
        \LWR@addtabularrulecolors%
        \LWR@tdendstyles%
    }%
```

Create an empty cell if muting for the `\bottomrule`:

```
    \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
    {}%
    {\LWR@atbangspec}%
%
    \LWR@htmltag{/td}\LWR@orignewline%
    \global\booltrue{LWR@tabularcelladded}%
}% not empty
}%
```

`\LWR@addleftmostbartag`

```
\newcommand*{\LWR@addleftmostbartag}{%
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}{%
    \LWR@printbartag{leftedge}%
}{}%
}
```

`\LWR@tabularleftedge`

```
\newcommand*{\LWR@tabularleftedge}{%
\ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{1}%
{%
    \LWR@printatbang{at}{leftedge}%
    \LWR@printatbang{bang}{leftedge}%
}% left edge
{}% not left edge
}
```

72.20 Data opening tag

`\LWR@thiscolspec` Temporary storage.

```
\newcommand*{\LWR@thiscolspec}{}
```

\LWR@tabledatasinglecolumntag Print a table data opening tag with style for alignment and color.

```
\newcommand*{\LWR@tabledatasinglecolumntag}%
{%
\LWR@traceinfo{LWR@tabledatasinglecolumntag}%
\LWR@maybenewtablerow%
```

Don't start a new paragraph tag if have already started one:

```
\ifbool{LWR@intabularmetadata}%
{%
```

If have found the end of tabular command, do not create the next data cell:

```
    \ifbool{LWR@exitingtabular}{}%
    {% not exiting tabular
```

Print the `@` and `!` contents before first column:

```
        \LWR@tabularleftedge%
```

Fetch the current column's alignment character into `\LWR@strresult`:

```
        \xdef\LWR@strresult{%
          \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
```

print the start of a new table data cell:

```
\LWR@traceinfo{LWR@tabledatasinglecolumntag: about to print td tag}%
        \LWR@htmltag{td class="td%
```

append this column's spec:

```
        \LWR@strresult%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add vertical bar tags.

```
        \LWR@addcmidruletrim%
        \LWR@addleftmostbartag%
        \LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
        "%
```

Add styles for rules, alignment:

```
        \LWR@tdstartstyles%
        \LWR@addcmidrulewidth%
        \LWR@addcdashline%


        \xdef\LWR@thiscolspec{%
          \LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

```
        }%
        \LWR@addformatwpalignment{\LWR@thiscolspec}%
```

Add styles for cell and rule colors:

```
        \LWR@addtabularrowcolor%
        \LWR@addtabularrulecolors%

        \LWR@tdendstyles%
        }% HTML td
        \LWR@traceinfo{LWR@tabledatasinglecolumntag: done printing td tag}%
```

If this is a `p`, `m`, `b`, or `X` column, allow paragraphs:

```
        \ifboolexpr{%
            test{ \ifdefstring{\LWR@strresult}{p} } or
            test{ \ifdefstring{\LWR@strresult}{m} } or
            test{ \ifdefstring{\LWR@strresult}{b} } or
            test{ \ifdefstring{\LWR@strresult}{P} } or
            test{ \ifdefstring{\LWR@strresult}{M} } or
            test{ \ifdefstring{\LWR@strresult}{B} } or
            test{ \ifdefstring{\LWR@strresult}{X} }
        }%
        {% allow pars
          \LWR@traceinfo{LWR@tabledatasinglecolumntag: about to LWR@startpars}%
            \global\booltrue{LWR@tableparcell}%
            \LWR@startpars%
         \LWR@traceinfo{LWR@tabledatasinglecolumntag: done with LWR@startpars}%
        }% allow pars
        {}% no pars
```

Print the > contents unless muted for the `\bottomrule`:

```
        \ifboolexpr{bool{LWR@tabularmutemods} or bool{LWR@emptyatbang}}%
        {}%
        {%
         \LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
        }%
        \global\boolfalse{LWR@intabularmetadata}%
    }% not exiting tabular
}{}% in tabular metadata
\LWR@traceinfo{LWR@tabledatasinglecolumntag: done}%
}%
```

72.21 Midrules

`LWR@midrules` `LWR@midrules` is a data array (section 42) of columns each containing a non-zero width if a midrule should be created for this column.

`LWR@trimlrules` `LWR@trimlrules` is a data array (section 42) of columns containing `l` if a midrule should be left trimmed for each column.

LWR@trimrrules — LWR@trimrrules is a data array (section 42) of columns containing r if a midrule should be right trimmed for each column.

LWR@cdashlines — LWR@cdashlines is a data array (section 42) of columns each containing a Y if an arydshln package "cdashed line" should be created for this column.

Ctr LWR@midrulecounter — Indexes across the LWR@midrules and LWR@trim<l/r>rules data arrays.

```
\newcounter{LWR@midrulecounter}
```

Len \LWR@heavyrulewidth — The default width of the rule.

```
\newlength{\LWR@heavyrulewidth}
\setlength{\LWR@heavyrulewidth}{.08em}
```

Len \LWR@lightrulewidth — The default width of the rule.

```
\newlength{\LWR@lightrulewidth}
\setlength{\LWR@lightrulewidth}{.05em}
```

Len \LWR@cmidrulewidth — The default width of the rule.

```
\newlength{\LWR@cmidrulewidth}
\setlength{\LWR@cmidrulewidth}{.03em}
```

Len \LWR@thiscmidrulewidth — The width of the next rule, defaulting to \LWR@cmidrulewidth.

If not \LWR@cmidrulewidth, a style will be used to generate the custom width.

Assigned from the LWR@midrules array.

```
\newlength{\LWR@thiscmidrulewidth}
\setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}
```

\LWR@clearmidrules — Start new midrules. Called at beginning of tabular and also at \\.

Clears all LWR@midrules and LWR@trimrules markers for this line.

```
\newcommand*{\LWR@clearmidrules}
{%
\setcounter{LWR@midrulecounter}{1}%
\whileboolexpr{%
    not test{%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}%
            {\value{LWR@tabletotalLaTeXcols}}%
    }%
}%
{%
    \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{0pt}%
    \setlength{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
    \LWR@setexparray{LWR@trimlrules}{\arabic{LWR@midrulecounter}}{}%
    \LWR@setexparray{LWR@trimrrules}{\arabic{LWR@midrulecounter}}{}%
    \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{N}%
    \addtocounter{LWR@midrulecounter}{1}%
```

```
}%
}
```

\LWR@subcmidrule {⟨*width*⟩} {⟨*trim*⟩} {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks LWR@midrules data array elements to be non-zero widths from left to right columns. Also marks trimming for the L and/or R columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcmidrule}[4]{%
\setcounter{LWR@midrulecounter}{#3}%
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}{#4}%
    }%
}%
{%
    \LWR@setexparray{LWR@midrules}{\arabic{LWR@midrulecounter}}{#1}%
    \addtocounter{LWR@midrulecounter}{1}%
}% whiledo
\IfSubStr{#2}{l}{\LWR@setexparray{LWR@trimlrules}{#3}{l}}{}%
\IfSubStr{#2}{r}{\LWR@setexparray{LWR@trimrrules}{#4}{r}}{}%
\global\booltrue{LWR@doingcmidrule}%
}
```

\LWR@docmidrule [⟨*width*⟩] (⟨*trim*⟩) {⟨*leftcolumn-rightcolumn*⟩}

Marks LWR@midrules array elements to be a non-zero width from left to right columns. Also marks trimming for the L and/or R columns.

```
\NewDocumentCommand{\LWR@docmidrule}
    {O{\LWR@cmidrulewidth} D(){} >{\SplitArgument{1}{-}}m}
    {\LWR@subcmidrule{#1}{#2}#3}
```

\LWR@subcdashline {⟨*leftcolumn*⟩} {⟨*rightcolumn*⟩}

Marks LWR@cdashlines data array elements to be Y from left to right columns.

LWR@doingcmidrule is set to force an empty row at the end of the tabular to create the rule.

```
\newcommand*{\LWR@subcdashline}[2]{%
\setcounter{LWR@midrulecounter}{#1}%
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@midrulecounter}}{>}{#2}%
    }%
}%
{%
    \LWR@setexparray{LWR@cdashlines}{\arabic{LWR@midrulecounter}}{Y}%
    \addtocounter{LWR@midrulecounter}{1}%
```

```
}% whiledo
\global\booltrue{LWR@doingcmidrule}%
}
```

`\LWR@docdashline` {⟨*leftcolumn-rightcolumn*⟩}

Marks `LWR@cdashlines` data array elements to be `Y` from left to right columns.

```
\NewDocumentCommand{\LWR@docdashline}
    {>{\SplitArgument{1}{-}}m}%
    {%
        \LWR@subcdashline#1%
    }
```

Used to compute margins, tabular trims, column offsets:

```
\newlength{\LWR@templengthone}
\newlength{\LWR@templengthtwo}
\newlength{\LWR@templengththree}
\newcounter{LWR@tempcountone}
```

Used to add a style to a table data cell:

```
\newbool{LWR@tdhavecellstyle}
```

`\LWR@tdstartstyles` Begins possibly adding a table data cell style.

```
\newcommand*{\LWR@tdstartstyles}{\global\boolfalse{LWR@tdhavecellstyle}}
```

`\LWR@tdaddstyle` Starts adding a table data cell style.

```
\newcommand*{\LWR@tdaddstyle}{%
\ifbool{LWR@tdhavecellstyle}%
{; }%
{ style="}%
\booltrue{LWR@tdhavecellstyle}%
}
```

`\LWR@tdendstyles` Finishes possibly adding a table data cell style. Prints the closing quote.

```
\newcommand*{\LWR@tdendstyles}{%
\ifbool{LWR@tdhavecellstyle}{%
    "%
    \global\boolfalse{LWR@tdhavecellstyle}%
}{}%
}
```

`\LWR@subaddcmidruletrim` {⟨*lefttrim*⟩} {⟨*righttrim*⟩} Adds a `\cmidrule` with optional trim.

```
\newcommand*{\LWR@subaddcmidruletrim}[2]{%
```

```
\setlength{\LWR@templengthone}{%
        \LWR@getexparray{LWR@midrules}{\arabic{LWR@tableLaTeXcolindex}}%
}%
\ifdimcomp{\LWR@templengthone}{>}{0pt}%
{%
```

Print the class with left and right trim letters appended:

```
    \LWR@origtilde tdrule#1#2%
```

Remember the width of the rule:

```
    \setlength{\LWR@thiscmidrulewidth}{\LWR@templengthone}%
}%
{%
    \setlength{\LWR@thiscmidrulewidth}{0pt}%
}%
}
```

`\LWR@addcmidruletrim` Adds left or right trim to a `\cmidrule`.

```
\newcommand*{\LWR@addcmidruletrim}{%
\LWR@subaddcmidruletrim%
{\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
{\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@tableLaTeXcolindex}}}%
}
```

`\LWR@addrulewidth` {⟨*thiswidth*⟩} {⟨*defaultwidth*⟩}

If not default width, add a custom style with width and color depending on `thiswidth`.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addrulewidth}[2]{%
```

Only add a custom width if `thiswidth` is different than the `defaultwidth`, or if a color is being used:

```
\ifboolexpr{%
    test{\ifdimcomp{#1}{=}{0pt}} or
    (
        ( test{\ifdimcomp{#1}{=}{#2}} and not bool{FormatWP} )
        and ( test {\ifdefvoid{\LWR@ruleHTMLcolor}} )
    )
}%
{}% default width and color
{% custom width and/or color
```

Ensure that the width is wide enough to display in the browser:

```
    \LWR@forceminwidth{#1}%
```

Begin adding another style:

```
    \LWR@tdaddstyle%
```

The style itself:

```
    border-top:\LWR@printlength{\LWR@atleastonept} solid %
```

If default gray, the darkness of the color depends on the thickness of the rule:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}{%
        \ifdimcomp{#1}{<}{\LWR@lightrulewidth}%
        {\LWR@origpound{}A0A0A0}%
        {% lightrule or heaver
            \ifdimcomp{#1}{<}{\LWR@heavyrulewidth}%
            {\LWR@origpound{}808080}%
            {black}%
        }% lightrule or heavier
    }{%
        \LWR@origpound\LWR@ruleHTMLcolor%
    }
}% custom width and/or color
}
```

`\LWR@addcmidrulewidth` Adds a `style` for the rule width.

Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addcmidrulewidth}{%
\LWR@addrulewidth{\LWR@thiscmidrulewidth}{\LWR@cmidrulewidth}%
}
```

`\LWR@addcdashline` Must be placed between `\LWR@tdstartstyles` and `\LWR@tdendstyles`.

```
\newcommand{\LWR@addcdashline}{%
\edef\LWR@tempone{%
    \LWR@getexparray{LWR@cdashlines}{\arabic{LWR@tableLaTeXcolindex}}%
}%
\ifdefstring{\LWR@tempone}{Y}{%
    \LWR@tdaddstyle%
    border-top: 1pt dashed %
    \ifdefvoid{\LWR@ruleHTMLcolor}%
        {black}%
        {\LWR@origpound\LWR@ruleHTMLcolor}%
}{}%
}
```

`\LWR@WPcell` {⟨*text-align*⟩} {⟨*vertical-align*⟩}

```
\newcommand*{\LWR@WPcell}[2]{%
\LWR@tdaddstyle%
\LWR@print@mbox{text-align:#1}; \LWR@print@mbox{vertical-align:#2}%
}
```

\LWR@addformatwpalignment If FormatWP, adds a style for the alignment.

Must be placed between \LWR@tdstartstyles and \LWR@tdendstyles.

```
\newcommand*{\LWR@addformatwpalignment}[1]{%
\ifbool{FormatWP}{%
\IfSubStr{#1}{l}{\LWR@WPcell{left}{middle}}{}%
\IfSubStr{#1}{c}{\LWR@WPcell{center}{middle}}{}%
\IfSubStr{#1}{r}{\LWR@WPcell{right}{middle}}{}%
\IfSubStr{#1}{p}{\LWR@WPcell{left}{bottom}}{}%
\IfSubStr{#1}{m}{\LWR@WPcell{left}{middle}}{}%
\IfSubStr{#1}{b}{\LWR@WPcell{left}{top}}{}%
\IfSubStr{#1}{P}{\LWR@WPcell{center}{bottom}}{}%
\IfSubStr{#1}{M}{\LWR@WPcell{center}{middle}}{}%
\IfSubStr{#1}{B}{\LWR@WPcell{center}{top}}{}%
}{}%
}
```

72.22 Cell colors

\LWR@addtabularrowcolor Adds a cell's row color style, if needed.

No color is added for the final row of empty cells which finishes each tabular.

```
\newcommand*{\LWR@addtabularrowcolor}{%
\ifbool{LWR@tabularmutemods}{}{%
    \ifdefvoid{\LWR@rowHTMLcolor}{%
        \ifdefvoid{\LWR@xcolorrowHTMLcolor}{}%
        {% xcolor row color
            \LWR@tdaddstyle%
            background:\LWR@origpound\LWR@xcolorrowHTMLcolor%
        }%
    }%
    {% explicit row color
        \LWR@tdaddstyle%
        background:\LWR@origpound\LWR@rowHTMLcolor%
    }%
}%
}
```

\LWR@addtabularhrulecolor Adds a cell's horizontal rule color style, if needed.

```
\newcommand*{\LWR@addtabularhrulecolor}{%
```

If either form of horizontal rule is requested:

```
\ifboolexpr{%
    test{\ifnumcomp{\value{LWR@hlines}}{>}{0}} or%
    test{\ifnumcomp{\value{LWR@hdashedlines}}{>}{0}} or%
    bool{LWR@doingtbrule}%
}{%
```

If there is a no custom color:

```
    \ifdefvoid{\LWR@ruleHTMLcolor}%
    {%
        \ifnumcomp{\value{LWR@hlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 4px double%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 2px dashed%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 1px dashed%
        }{}}}%
```

If no color and not doubled or dashed, then add nothing, since a simpler rule is the default.

```
    }%
```

If there is a custom color:

```
    {%
        \ifnumcomp{\value{LWR@hlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 4px double \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{>}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 2px dashed \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
        \ifnumcomp{\value{LWR@hdashedlines}}{=}{1}%
        {%
            \LWR@tdaddstyle%
            border-top: 1px dashed \LWR@origpound\LWR@ruleHTMLcolor%
        }{% else
            \LWR@tdaddstyle%
            border-top: 1px solid \LWR@origpound\LWR@ruleHTMLcolor%
        }}}%
    }%
}{}%
}
```

`\LWR@addtabularrulecolors` Adds a cell's rule color styles, if needed.

No color is added for the final row of empty cells which finishes each `tabular`.

```
\newcommand*{\LWR@addtabularrulecolors}{%
```

Custom horizonal rule color:

```
\LWR@addtabularhrulecolor%
```

No vertical rules if finishing the `tabular` with a row of empty cells:

```
\ifbool{LWR@tabularmutemods}{}{%
```

If at the leftmost cell, possibly add a leftmost vertical rule:

```
    \ifnumequal{\value{LWR@tableLaTeXcolindex}}{1}{%
```

Fetch the left edge's vertical bar specification:

```
        \edef\LWR@tempone{\LWR@getexparray{LWR@colbarspec}{leftedge}}%
```

Add a custom style if a vertical bar was requested:

```
        \ifdefstring{\LWR@tempone}{tvertbarl}{%
                \LWR@tdaddstyle%
                border-left: 1px solid % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldouble}{%
                \LWR@tdaddstyle%
                border-left: 4px double % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldash}{%
                \LWR@tdaddstyle%
                border-left: 1px dashed % space
                    \LWR@vertruleHTMLcolor%
        }{}%
        \ifdefstring{\LWR@tempone}{tvertbarldoubledash}{%
                \LWR@tdaddstyle%
                border-left: 2px dashed % space
                    \LWR@vertruleHTMLcolor%
        }{}%
    }{}%
```

Possibly add a right vertical rule for this cell:

```
    \edef\LWR@tempone{%
        \LWR@getexparray{LWR@colbarspec}{\arabic{LWR@tableLaTeXcolindex}}%
    }%
    \ifdefstring{\LWR@tempone}{tvertbarr}{%
```

Add a custom style if a vertical bar was requested:

```
            \LWR@tdaddstyle%
            border-right: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
```

```
    \ifdefstring{\LWR@tempone}{tvertbarrdouble}{%
            \LWR@tdaddstyle%
            border-right: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdash}{%
            \LWR@tdaddstyle%
            border-right: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifdefstring{\LWR@tempone}{tvertbarrdoubledash}{%
            \LWR@tdaddstyle%
            border-right: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
}%
}
```

Ctr `LWR@cellcolordepth` Counts how many cell color s were added to the current tabular data cell.

```
\newcounter{LWR@cellcolordepth}
```

`\LWR@subaddtabularcellcolor` {⟨*HTML color*⟩}

```
\newcommand*{\LWR@subaddtabularcellcolor}[1]{%
\LWR@htmltag{div class="cellcolor" style="%
    background:\LWR@origpound{}{}#1 %
" }%
\addtocounter{LWR@cellcolordepth}{1}%
}
```

`\LWR@addtabularcellcolor` Adds a cell color style, if needed.

```
\newcommand*{\LWR@addtabularcellcolor}{%
\ifdefvoid{\LWR@cellHTMLcolor}%
{%
    \ifdefvoid{\LWR@rowHTMLcolor}%
    {%
        \ifdefvoid{\LWR@xcolorrowHTMLcolor}%
        {%
            \ifdefvoid{\LWR@columnHTMLcolor}%
            {}%
            {\LWR@subaddtabularcellcolor{\LWR@columnHTMLcolor}}%
        }%
        {\LWR@subaddtabularcellcolor{\LWR@xcolorrowHTMLcolor}}%
    }%
    {\LWR@subaddtabularcellcolor{\LWR@rowHTMLcolor}}%
}%
{\LWR@subaddtabularcellcolor{\LWR@cellHTMLcolor}}%
}
```

72.23 Multicolumns

72.23.1 Parsing multicolumns

```
\newcounter{LWR@tablemulticolswidth}
```

Indexes into the multicolumn specification:

```
\newcounter{LWR@tablemulticolspos}
```

Remembers multicolumn vertical rules if found in the column spec.

```
\newcounter{LWR@mcolvertbarsl}
\newcounter{LWR@mcolvertbarsr}
\newcounter{LWR@mcolvertbarsldash}
\newcounter{LWR@mcolvertbarsrdash}
\newbool{LWR@mcolvertbaronleft}%
```

`\LWR@printmccoltype` {⟨*colspec*⟩} Print any valid column type found. Does not print `@`, `!`, `>`, or `<` columns or their associated tokens.

This is printed as part of the table data tag's `class`.

```
\newcommand*{\LWR@printmccoltype}[1]{%
\LWR@traceinfo{lwr@printmccoltype -#1-}%
```

Get one token of the column spec:

```
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Add to the HTML tag depending on which column type is found:

```
\IfStrEq{\LWR@strresult}{l}{l}{}%
\IfStrEq{\LWR@strresult}{c}{c}{}%
\IfStrEq{\LWR@strresult}{r}{r}{}%
\IfStrEq{\LWR@strresult}{p}{p}{}%
\IfStrEq{\LWR@strresult}{m}{m}{}%
\IfStrEq{\LWR@strresult}{b}{b}{}%
\IfStrEq{\LWR@strresult}{P}{P}{}%
\IfStrEq{\LWR@strresult}{M}{M}{}%
\IfStrEq{\LWR@strresult}{B}{B}{}%

\IfStrEq{\LWR@strresult}{w}{w}{}%
\IfStrEq{\LWR@strresult}{W}{W}{}%

\IfStrEq{\LWR@strresult}{S}{c}{}%
\IfStrEq{\LWR@strresult}{s}{c}{}%

\IfStrEq{\LWR@strresult}{X}{p}{}%

\IfStrEq{\LWR@strresult}{|}%
{%
```

```
    \ifbool{LWR@mcolvertbaronleft}%
        {\addtocounter{LWR@mcolvertbarsl}{1}}% left edge
        {\addtocounter{LWR@mcolvertbarsr}{1}}% not left edge
}%
{%
    \IfStrEq{\LWR@strresult}{:}%
    {%
        \ifbool{LWR@mcolvertbaronleft}%
            {\addtocounter{LWR@mcolvertbarsldash}{1}}% left edge
            {\addtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
    }%
    {%
        \IfStrEq{\LWR@strresult}{;}%
        {%
            \ifbool{LWR@mcolvertbaronleft}%
                {\addtocounter{LWR@mcolvertbarsldash}{1}}% left edge
                {\addtocounter{LWR@mcolvertbarsrdash}{1}}% not left edge
        }%
        {\boolfalse{LWR@mcolvertbaronleft}}%
    }%
}%
\LWR@traceinfo{lwr@printmccoltype done}%
}
```

`\LWR@multicolpartext` {⟨*num parameters*⟩} Print the data with paragraph tags, advance to bypass the given number of parameters.

```
\newcommand*{\LWR@multicolpartext}[1]{%
\LWR@startpars%
\LWR@multicoltext%
\addtocounter{LWR@tablemulticolspos}{#1}%
\LWR@stoppars%
}
```

`\LWR@multicolother` {⟨*colspec*⟩} For `@`, `!`, `>`, `<`, print the next token without paragraph tags:

```
\newcommand*{\LWR@multicolother}[1]{%
\addtocounter{LWR@tablemulticolspos}{1}%
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
\LWR@strresult%
```

A valid column data type was found:

```
\global\booltrue{LWR@validtablecol}%
}
```

`\LWR@multicolskip` Nothing to print for this column type.

```
\newcommand*{\LWR@multicolskip}{%
```

A valid column data type was found:

```
\global\booltrue{LWR@validtablecol}%
```

```
}
```

`\LWR@printmccoldata` {⟨*colspec*⟩} Print the data for any valid column type found.

```
\newcommand*{\LWR@printmccoldata}[1]{%
\LWR@traceinfo{lwr@printmccoldata -#1}%
```

Not yet found a valid column type:

```
\global\boolfalse{LWR@validtablecol}%
```

Get one token of the column spec:

```
\StrChar{#1}{\arabic{LWR@tablemulticolspos}}[\LWR@strresult]%
```

Print the text depending on which column type is found. Also handles `@`, `>`, `<` as it comes to them.

```
\IfStrEq{\LWR@strresult}{l}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{c}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{r}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{D}{%
\addtocounter{LWR@tablemulticolspos}{3}% skip parameters
\LWR@multicoltext%
}{}%

\IfStrEq{\LWR@strresult}{p}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{m}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{b}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{P}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{M}{\LWR@multicolpartext{2}}{}%
\IfStrEq{\LWR@strresult}{B}{\LWR@multicolpartext{2}}{}%

\IfStrEq{\LWR@strresult}{w}{\LWR@multicolpartext{3}}{}%
\IfStrEq{\LWR@strresult}{W}{\LWR@multicolpartext{3}}{}%

\IfStrEq{\LWR@strresult}{S}{\LWR@multicoltext}{}%
\IfStrEq{\LWR@strresult}{s}{\LWR@multicoltext}{}%

\IfStrEq{\LWR@strresult}{X}{\LWR@multicolpartext{1}}{}%
\IfStrEq{\LWR@strresult}{|}{\LWR@multicolskip}{}%
\IfStrEq{\LWR@strresult}{:}{\LWR@multicolskip}{}%
\IfStrEq{\LWR@strresult}{;}{%
    \LWR@multicolskip%
    \addtocounter{LWR@tablemulticolspos}{1}% skip parameter
}{}%
\IfStrEq{\LWR@strresult}{\detokenize{@}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{!}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{>}}{\LWR@multicolother{#1}}{}%
\IfStrEq{\LWR@strresult}{\detokenize{<}}{\LWR@multicolother{#1}}{}%
```

If an invalid column type:

```
\ifbool{LWR@validtablecol}{}{\LWR@multicoltext}%
```

Tracing:

```
\LWR@traceinfo{lwr@printmccoldata done}%
}
```

\parsemulticolumnalignment {⟨*1: colspec*⟩} {⟨*2: printresults*⟩}

Scan the multicolumn specification and execute the printfunction for each entry.

Note that the spec for a p{spec} column, or @, >, <, is a token list which will NOT match l, c, r, or p.

```
\newcommand*{\LWR@parsemulticolumnalignment}[2]{%
\setcounter{LWR@tablemulticolspos}{1}%
\StrLen{#1}[\LWR@strresult]%
\setcounter{LWR@tablemulticolswidth}{\LWR@strresult}%
```

Scan across the tokens in the column spec:

```
\whileboolexpr{%
    not test {%
        \ifnumcomp{\value{LWR@tablemulticolspos}}{>}%
            {\value{LWR@tablemulticolswidth}}%
    }%
}%
{%
```

Execute the assigned print function for each token in the column spec:

```
#2{#1}%
```

Move to the next token in the column spec:

```
\addtocounter{LWR@tablemulticolspos}{1}%
}%
}
```

72.23.2 Multicolumn factored code

\LWR@addmulticolvertrulecolor

```
\newcommand*{\LWR@addmulticolvertrulecolor}{%
```

No vertical rules if finishing the tabular with a row of empty cells:

```
\ifbool{LWR@tabularmutemods}{}{%
```

Left side:

```
    \ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{%
        \LWR@tdaddstyle%
        border-left: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{%
        \LWR@tdaddstyle%
        border-left: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{%
        \LWR@tdaddstyle%
        border-left: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{%
        \LWR@tdaddstyle%
        border-left: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
```

Right side:

```
    \ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{%
        \LWR@tdaddstyle%
        border-right: 1px solid \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{%
        \LWR@tdaddstyle%
        border-right: 4px double \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{%
        \LWR@tdaddstyle%
        border-right: 1px dashed \LWR@vertruleHTMLcolor%
    }{}%
    \ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{%
        \LWR@tdaddstyle%
        border-right: 2px dashed \LWR@vertruleHTMLcolor%
    }{}%
}%
}
```

```
\newcommand{\LWR@multicoltext}{}
```

To find multicolumn right trim:

```
\newcounter{LWR@lastmulticolumn}
```

`\LWR@domulticolumn` `[`⟨*1: vpos*⟩`]` `[`⟨*2: #rows*⟩`]` {⟨*3: numLaTeXcols*⟩} {⟨*4: numHTMLcols*⟩} {⟨*5: colspec*⟩} {⟨*6: text*⟩}

```
\NewDocumentCommand{\LWR@domulticolumn}{o o m m m +m}{%
\LWR@traceinfo{LWR@domulticolumn -#1- -#2- -#4- -#5-}%
```

Remember the text to be inserted, and remember that a valid column type was found:

```
\renewcommand{\LWR@multicoltext}{%
#6%
\global\booltrue{LWR@validtablecol}%
}%
```

Compute the rightmost column to be included. This is used to create the right trim.

```
\setcounter{LWR@lastmulticolumn}{\value{LWR@tableLaTeXcolindex}}%
\addtocounter{LWR@lastmulticolumn}{#3}%
\addtocounter{LWR@lastmulticolumn}{-1}%
```

Row processing:

```
\LWR@maybenewtablerow%
```

Begin the opening table data tag:

```
\LWR@htmltag{td colspan="#4" %

\IfValueT{#2}{ % rows?
rowspan="#2" %


\IfValueT{#1}{% vpos?
\ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
\ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
}% vpos?
}% rows?

 class="td%
```

Print the column type and vertical bars:

```
\setcounter{LWR@mcolvertbarsl}{0}%
\setcounter{LWR@mcolvertbarsr}{0}%
\setcounter{LWR@mcolvertbarsldash}{0}%
\setcounter{LWR@mcolvertbarsrdash}{0}%
\booltrue{LWR@mcolvertbaronleft}%
\LWR@parsemulticolumnalignment{#5}{\LWR@printmccoltype}%
```

If this column has a cmidrule, add “rule” to the end of the HTML class tag.

If this position had a “Y” then add “rule” for a horizontal rule:

```
\LWR@subaddcmidruletrim%
{\LWR@getexparray{LWR@trimlrules}{\arabic{LWR@tableLaTeXcolindex}}}%
{\LWR@getexparray{LWR@trimrrules}{\arabic{LWR@lastmulticolumn}}}%
```

Also add vertical bar class.

```
\ifnumcomp{\value{LWR@mcolvertbarsl}}{=}{1}{ tvertbarl}{}%
\ifnumcomp{\value{LWR@mcolvertbarsl}}{>}{1}{ tvertbarldouble}{}%
\ifnumcomp{\value{LWR@mcolvertbarsr}}{=}{1}{ tvertbarr}{}%
\ifnumcomp{\value{LWR@mcolvertbarsr}}{>}{1}{ tvertbarrdouble}{}%
\ifnumcomp{\value{LWR@mcolvertbarsldash}}{=}{1}{ tvertbarldash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsldash}}{>}{1}{ tvertbarldoubledash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsrdash}}{=}{1}{ tvertbarrdash}{}%
\ifnumcomp{\value{LWR@mcolvertbarsrdash}}{>}{1}{ tvertbarrdoubledash}{}%
```

Close the class tag's opening quote: " NOT A TYPO

```
%
```

```
\LWR@tdstartstyles%
```

```
\LWR@addtabularrowcolor%
```

```
\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularhrulecolor%
\LWR@addmulticolvertrulecolor%
\LWR@addformatwpalignment{#5}%
\LWR@tdendstyles%
}% end of the opening table data tag
\global\boolfalse{LWR@intabularmetadata}%
\LWR@parsemulticolumnalignment{#5}{\LWR@printmccoldata}%
}
```

72.23.3 Multicolumn

`\LWR@htmlmulticolumn` {⟨*numcols*⟩} {⟨*alignment*⟩} {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@htmlmulticolumn}{m m +m}%
{%
```

Figure out how many extra HTML columns to add for `@` and `!` columns:

```
\LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn tag:

```
\LWR@domulticolumn{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#3}%
```

Move to the next LaTeX column:

```
\addtocounter{LWR@tableLaTeXcolindex}{#1}%
\addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing `@` or `!` columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}
```

72.23.4 Longtable captions

longtable captions use \multicolumn.

Bool LWR@starredlongtable Per the caption pacakge, step the counter if longtable*.

```
\newbool{LWR@starredlongtable}
\boolfalse{LWR@starredlongtable}
```

Per the caption package. User-redefinable float type.

```
\providecommand*{\LTcaptype}{table}
```

\LWR@longtabledatacaptiontag * [⟨*toc entry*⟩] {⟨*caption*⟩}

```
\NewDocumentCommand{\LWR@longtabledatacaptiontag}{s o +m}
{%
```

Remember the latest name for \nameref:

```
\IfValueTF{#2}{% optional given?
    \ifblank{#2}% optional empty?
    {\LWR@setlatestname{#3}}% empty
    {\LWR@setlatestname{#2}}% given and non-empty
}% optional given
{\LWR@setlatestname{#3}}% no optional
```

Create a multicolumn across all the columns:

Figure out how many extra HTML columns to add for @ and ! columns found between the first and the last column:

```
\LWR@tabularhtmlcolumns{1}{\arabic{LWR@tabletotalLaTeXcols}}
```

Create the multicolumn tag:

```
\LWR@domulticolumn{\arabic{LWR@tabletotalLaTeXcols}}%
    {\arabic{LWR@tabhtmlcoltotal}}%
    {P}%
{% \LWR@domulticolumn
\IfBooleanTF{#1}% star?
```

Star version, show a caption but do not make a LOT entry:

```
{% yes star
    \LWR@figcaption%
    \LWR@isolate{#3}%
    \endLWR@figcaption%
}%
{% No star:
```

Not the star version:

Don't step the counter if `\caption[]{A caption.}`

```
    \ifbool{LWR@starredlongtable}%
    {%
        \ifblank{#2}% TOC entry
        {}%
        {%
            \refstepcounter{\LTcaptype}%
            \protected@edef\@currentlabel{%
                \@nameuse{p@\LTcaptype}\@nameuse{the\LTcaptype}%
            }%
        }%
    }{}%
```

Create an HTML caption. Afterwards, maybe make a LOT entry.

```
    \LWR@figcaption%
    \LWR@isolate{\@nameuse{fnum@\LTcaptype}}%
    \CaptionSeparator%
    \LWR@isolate{#3}%
    \endLWR@figcaption%
```

See if an optional caption was given:

```
    \ifblank{#2}% TOC entry empty
```

if the optional caption was given, but empty, do not form a TOC entry

```
    {}%
```

If the optional caption was given, but might only be `[]`:

```
    {% TOC entry not empty
        \IfNoValueTF{#2}% No TOC entry?
```

The optional caption is `[]`:

```
        {% No TOC entry
            \addcontentsline%
            {\@nameuse{ext@\LTcaptype}}%
            {\LTcaptype}%
            {%
                \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                {\ignorespaces \LWR@isolate{#3}\protect\relax}%
            }%
        }% end of No TOC entry
```

The optional caption has text enclosed:

```
        {% yes TOC entry
            \addcontentsline%
            {\@nameuse{ext@\LTcaptype}}%
            {\LTcaptype}%
```

```
            {%
                \protect\numberline%
              {\LWR@isolate{\@nameuse{p@\LTcaptype}}\@nameuse{the\LTcaptype}}%
                {\ignorespaces \LWR@isolate{#2}\protect\relax}%
            }%
        }% end of yes TOC entry
    }% end of TOC entry not empty
}% end of no star
```

Skip any trailing @ or ! columns for this cell:

```
\global\booltrue{LWR@skipatbang}%
}% end of \LWR@domulticolumn

\addtocounter{LWR@tableLaTeXcolindex}{\arabic{LWR@tabletotalLaTeXcols}}
\addtocounter{LWR@tableLaTeXcolindex}{-1}

}
```

72.23.5 Counting HTML tabular columns

The LaTeX specification for a table includes a number of columns separated by the & character. These columns differ in content from line to line. Additional virtual columns may be specified by the special @ and ! columns. These columns are identical from line to line, but may be skipped during a multicolumn cell.

For HTML output, @ and ! columns are placed into their own tabular columns. Thus, a LaTeX \multicolumn command may span several additional @ and ! columns in HTML output. These additional columns must be added to the total number of columns spanned by an HTML multi-column data cell.

```
\newcounter{LWR@tabhtmlcolindex}
\newcounter{LWR@tabhtmlcolend}
\newcounter{LWR@tabhtmlcoltotal}
```

\LWR@subtabularhtmlcolumns {⟨*index*⟩}

Factored from \LWr@tabularhtmlcolumns, which follows.

```
\newcommand*{\LWR@subtabularhtmlcolumns}[1]{%
```

Temporarily define a macro equal to the @ specification for this column:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colatspec}{#1}}%
```

If the @ specification is not empty, add to the count:

```
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\addtocounter{LWR@tabhtmlcoltotal}{1}}%
```

Likewise for the ! columns:

```
    \edef\LWR@atbangspec{\LWR@getexparray{LWR@colbangspec}{#1}}%
    \ifdefempty{\LWR@atbangspec}%
        {}%
        {\addtocounter{LWR@tabhtmlcoltotal}{1}}%
}
```

\LWR@tabularhtmlcolumns {⟨*starting LaTeX column*⟩} {⟨*number LaTeX columns*⟩}

Compute the total number of HTML columns being spanned, considering the starting LaTeX table column and the number of LaTeX tabular columns being spanned. Any @ and ! columns within this span are included in the total count. The resulting number of HTML columns is returned in the counter LWR@tabhtmlcoltotal.

```
\newcommand*{\LWR@tabularhtmlcolumns}[2]{%
```

Count the starting index, compute ending index, and begin with the count being the LaTeX span, to which additional @ and ! columns may be added:

```
\setcounter{LWR@tabhtmlcolindex}{#1}%
\setcounter{LWR@tabhtmlcoltotal}{#2}%
\setcounter{LWR@tabhtmlcolend}{#1}%
\addtocounter{LWR@tabhtmlcolend}{#2}%
```

If at the left edge, add the at/bang columns for the left edge:

```
\ifnumcomp{\value{LWR@tabhtmlcolindex}}{=}{1}{%
    \LWR@subtabularhtmlcolumns{leftedge}%
}{}%
```

Walk across the LaTeX columns looking for @ and ! columns:

```
\whileboolexpr{%
    test {%
        \ifnumcomp{\value{LWR@tabhtmlcolindex}}{<}{\value{LWR@tabhtmlcolend}}%
    }%
}%
{%
    \LWR@subtabularhtmlcolumns{\arabic{LWR@tabhtmlcolindex}}%
    \addtocounter{LWR@tabhtmlcolindex}{1}%
}% whiledo
}
```

```
\end{warpHTML}
```

72.24 Multirow if not loaded

A default defintion in case multirow is not loaded. This is used during table parsing.

```
\begin{warpHTML}
```

```
\newcommand{\multirow}[2][c]{}
\end{warpHTML}
```

72.25 Multicolumnrow

A print-mode version is defined here, and is also used during HTML output while inside a `latexmage`.

See section 338 for the HTML versions.

for HTML & PRINT:

```
\begin{warpall}
```

`\multicolumnrow` {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

For discussion of the use of `\DeclareExpandableDocumentCommand`, see:
https://tex.stackexchange.com/questions/168434/problem-with-abbreviation-of-multirow-and-multicolumn-latex

`\AtBeginDocument` to adjust after the user may have loaded multirow, which requires several tests to determine which version is loaded and thus which options are available.

```
\AtBeginDocument{
```

`\@ifundefined{@xmultirow}` determines if multirow was never loaded.

Null action if not loaded:

```
\@ifundefined{@xmultirow}
{
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {}%
}% no version of multirow was loaded
{% \@xmultirow defined, so some version of multirow was loaded
```

`\@ifpackageloaded{multirow}` determines if v2.0 or later of multirow was used, which included the `\ProvidesPackage` macro.

The print version:

```
\@ifpackageloaded{multirow}{% v2.0 or newer
\@ifpackagelater{multirow}{2016/09/01}% 2016/09/27 for v2.0
{% v2.0+:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow[#3]{#4}[#5]{#6}[#7]{#8}}}%
}
{% loaded but older, probably not executed:
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
```

```
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
}
}% packageloaded{multirow}
```

If not `\@ifpackageloaded{multirow}` but `\@xmultirow` is defined, then this must be v1.6 or earlier, which did not `\ProvidesPackage{multirow}`, and did not have the `vposn` option.

```
{% v1.6 or older did not \ProvidePackage
\DeclareExpandableDocumentCommand{\LWR@print@multicolumnrow}%
    {+m +m +O{c} +m +O{0} +m +O{0pt} +m}%
    {\multicolumn{#1}{#2}{\@xmultirow{#4}[#5]{#6}[#7]{#8}}}%
}

}% \@ifundefined{@xmultirow}

\providecommand*{\multicolumnrow}{\LWR@print@multicolumnrow}

}% AtBeginDocument

\end{warpall}
```

72.26 Utility macros inside a table

for HTML output:

```
\begin{warpHTML}
```

Used to prevent opening a tabular data cell if the following token is one which does not create tabular data:

```
\newcommand*{\LWR@donothing}{}
```

In case array is not loaded:

```
\let\firsthline\relax
\let\lasthline\relax
\newcommand*{\firsthline}{}
\newcommand*{\lasthline}{}
```

In case bigdelim is not loaded:

```
\newcommand*{\ldelim}{}
\newcommand*{\rdelim}{}

\end{warpHTML}
```

72.27 Special-case tabular markers

for HTML & PRINT:

```
\begin{warpall}
```

\TabularMacro Place this just before inserting a custom macro in a table data cell. Doing so tells lwarp not to automatcally start a new HTML table data cell yet. See section 8.10.1.

```
\newcommand*{\TabularMacro}{}
```

```
\end{warpall}
```

\ResumeTabular Used to resume tabular entries after resuming an environment.

⚠ tabular inside another environment When creating a new environment which contains a tabular environment, lwarp's emulation of the tabular does not automatically resume when the containing enviroment ends, resulting in corrupted HTML rows. To fix this, use \ResumeTabular as follows. This is ignored in print mode.

```
\StartDefiningTabulars % because & is used in a definition
\newenvironment{outerenvironment}
{
\tabular{cc}
left & right \\
}
{
\TabularMacro\ResumeTabular
left & right \\
\endtabular
}
\StopDefiningTabulars
```

for HTML output:

```
\begin{warpHTML}
```

```
\newcommand*{\ResumeTabular}{%
\global\boolfalse{LWR@exitingtabular}%
\global\boolfalse{LWR@tabularmutemods}%
\LWR@getmynexttoken%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

```
\newcommand*{\ResumeTabular}{}
```

```
\end{warpprint}
```

72.28 Checking for a new table cell

for HTML output:

```
\begin{warpHTML}
```

Bool LWR@exitingtabular When \end is found, turns off the next opening data tag.

```
\newbool{LWR@exitingtabular}
```

Bool LWR@tabularmutemods Mutes HTML output for @, !, < and >.

This is used while printing the final row to generate \bottomrules.

```
\newbool{LWR@tabularmutemods}
```

\LWR@tabledatacolumntag Open a new HTML table cell unless the next token is for a macro which does not create data, such as \hline, \toprule, etc:

```
\newcommand*{\LWR@tabledatacolumntag}%
{%
\LWR@traceinfo{LWR@tabledatacolumntag}%
```

\show\LWR@mynexttoken to see what tokens to look for

If not any of the below, start a new table cell:

```
\global\let\LWR@mynextaction\LWR@tabledatasinglecolumntag%
```

If exiting the tabular:

```
\ifdefequal{\LWR@mynexttoken}{\end}%
    {\global\booltrue{LWR@exitingtabular}}{}%
```

longtable can have a caption in a cell

```
\ifdefequal{\LWR@mynexttoken}{\caption}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Look for other things which would not start a table cell:

```
\ifdefequal{\LWR@mynexttoken}{\multicolumn}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\multirow}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\multicolumnrow}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
\ifdefequal{\LWR@mynexttoken}{\noalign}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mrowcell, this is a cell to be skipped over:

```
\ifdefequal{\LWR@mynexttoken}{\mrowcell}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

If an \mcolrowcell, this is a cell to be skipped over:

```
\ifdefequal{\LWR@mynexttoken}{\mcolrowcell}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\TabularMacro}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

```
\ifdefequal{\LWR@mynexttoken}{\hline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\firsthline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\lasthline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\toprule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\midrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cmidrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%


\ifdefequal{\LWR@mynexttoken}{\morecmidrules}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\specialrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\bottomrule}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\rowcolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\arrayrulecolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\doublerulesepcolor}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\warpprintonly}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\warpHTMLonly}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\ldelim}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\rdelim}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

For arydshln:

```
\ifdefequal{\LWR@mynexttoken}{\hdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\cdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\firsthdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%

\ifdefequal{\LWR@mynexttoken}{\lasthdashline}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

Ignore an empty line between rows:

```
\ifdefequal{\LWR@mynexttoken}{\par}%
    {\global\let\LWR@mynextaction\LWR@donothing}{}%
```

No action for an \end token.

Add similar to the above for any other non-data tokens which might appear in the table.

Start the new table cell if was not any of the above:

```
\LWR@traceinfo{LWR@tabledatacolumntag: about to do mynext}%
\LWR@mynextaction%
\LWR@traceinfo{LWR@tabledatacolumntag: done}%
}
```

```
\end{warpHTML}
```

72.29 \mrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mrowcell

⚠ multirow cells

The user must insert \mrowcell into any \multirow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mrowcell}{}
```

```
\end{warpall}
```

72.30 \mcolrowcell

for HTML & PRINT:

```
\begin{warpall}
```

\mcolrowcell ⚠ multirow cells The user must insert \mcolrowcell into any \multicolumnrow cells which must be skipped. This command has no action during print output.

```
\newcommand*{\mcolrowcell}{}
```

```
\end{warpall}
```

72.31 HTML tabular environment

for HTML output:

```
\begin{warpHTML}
```

These are default defininitions in case booktabs is not loaded, and are not expected to used, but must exist as placeholders. They are pre-deleted in case memoir has already loaded booktabs.

```
\LetLtxMacro\toprule\relax
\LetLtxMacro\midrule\relax
\LetLtxMacro\cmidrule\cline
\LetLtxMacro\bottomrule\relax
\LetLtxMacro\addlinespace\relax
\LetLtxMacro\morecmidrules\relax
\LetLtxMacro\specialrule\relax

\newcommand*{\toprule}[1][]{\hline}
\newcommand*{\midrule}[1][]{\hline}
\LetLtxMacro\cmidrule\cline
\newcommand*{\bottomrule}[1][]{\hline}
\newcommand*{\addlinespace}[1][]{}
\newcommand*{\morecmidrules}{}
\newcommand*{\specialrule}[3]{\hline}
```

\noalign {⟨*text*⟩} Redefined for use inside tabular.

```
\LetLtxMacro\LWR@orignoalign\noalign

\newcommand{\LWR@tabularnoalign}[1]{%
\begingroup%
\global\advance\rownum\m@ne%
\renewcommand*{\LWR@xcolorrowHTMLcolor}{}%
\multicolumn{\value{LWR@tabletotalLaTeXcols}}{l}{#1} \\
\endgroup%
% \@rowc@lors%
\LWR@getmynexttoken%
}
```

\LWR@HTMLhline The definition of \hline depends on whether tabls has been loaded. If so, optional space below the line may be specified, but will be ignored.

```
\AtBeginDocument{
\@ifpackageloaded{lwarp-tabls}
```

```
{
\newcommand*{\LWR@HTMLhline}[1][]{%
    \ifbool{FormatWP}%
    {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
    {\addtocounter{LWR@hlines}{1}}%
    \LWR@getmynexttoken}%
}
{
\newcommand*{\LWR@HTMLhline}{%
    \ifbool{FormatWP}%
    {\LWR@docmidrule{1-\arabic{LWR@tabletotalLaTeXcols}}}%
    {\addtocounter{LWR@hlines}{1}}%
    \LWR@getmynexttoken}%
}
}% AtBeginDocument
```

`\LWR@HTMLcline` {⟨*columns*⟩}

```
\NewDocumentCommand{\LWR@HTMLcline}{m}%
{\LWR@docmidrule{#1}\LWR@getmynexttoken}%
```

`\LWR@tabular@warpprintonly` {⟨*contents*⟩}

Only process the contents if producing printed output. Modified inside a `tabular` to grab the next token.

```
\newcommand{\LWR@tabular@warpprintonly}[1]{%
    \ifbool{warpingprint}{#1}{}%
    \LWR@getmynexttoken%
}
```

`\LWR@nullifyNoAutoSpacing` For babel-french, turn off auto spacing at the start of the tabular, then nullify the autospacing commands inside the tabular, since they were not compatible with the tabular column parsing code, which uses xstring.

```
\AtBeginDocument{
\@ifundefined{frenchbsetup}%
{% no babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{}
}% no babel-french
{% yes babel-french
    \newcommand*{\LWR@nullifyNoAutoSpacing}{%
        \NoAutoSpacing%
        \renewcommand*{\NoAutoSpacing}{}%
        \renewcommand*{\LWR@FBcancel}{}%
    }
}% yes babel-french
}% AtBeginDocument
```

Env `tabular` `<direction>` [⟨*vertposition*⟩] {⟨*colspecs*⟩}

The `<direction>` is from plext for Japanese documents, and is ignored.

```
\StartDefiningTabulars

\NewDocumentCommand{\LWR@HTML@@tabular}{d<> o m}
{%
\LWR@traceinfo{LWR@HTML@@tabular started}%
\addtocounter{LWR@tabulardepth}{1}%
```

Not yet started a table row:

```
\global\boolfalse{LWR@startedrow}%
```

Not yet doing any rules:

```
\setcounter{LWR@hlines}{0}%
\setcounter{LWR@hdashedlines}{0}%
\global\boolfalse{LWR@doingtbrule}%
\global\boolfalse{LWR@doingcmidrule}%
```

For babel-french, turn off auto spacing one time, then nullify the autospacing commands since were not compatible with the tabular parsing code.

```
\LWR@nullifyNoAutoSpacing%
```

Have not yet found the end of tabular command. Unmute the `@` and `!` columns.

```
\global\boolfalse{LWR@exitingtabular}%
\global\boolfalse{LWR@tabularmutemods}%
```

Error if failed to use `\mrowcell` or `\mcolrowcell` when needed.

```
\boolfalse{LWR@usedmultirow}
\boolfalse{LWR@foundmrowcell}
```

Create the `table` tag:

```
\global\booltrue{LWR@intabularmetadata}%
\LWR@traceinfo{LWR@@tabular: About to LWR@forecenewpage.}%
\LWR@forcenewpage
\LWR@htmlblocktag{table}%
```

Parse the table columns:

```
\LWR@parsetablecols{#3}%
```

Table col spec is: `\LWR@tablecolspec` which is a string of `llccrr`, etc.

Do not place the table inside a paragraph:

```
\LWR@stoppars%
```

Track column #:

```
\setcounter{LWR@tableLaTeXcolindex}{1}%
```

Have not yet added data in this column:

```
\global\boolfalse{LWR@tabularcelladded}%
```

Start looking for midrules:

```
\LWR@clearmidrules%
```

\\ becomes a macro to end the table row:

```
\LetLtxMacro{\\}{\LWR@tabularendofline}%
```

\warpprintonly inside a tabular must grab the next token.

```
\LetLtxMacro\warpprintonly\LWR@tabular@warpprintonly%
```

The following adjust for colortbl.

```
\LetLtxMacro\arrayrulecolor\arrayrulecolornexttoken%
\LetLtxMacro\doublerulesepcolor\doublerulesepcolornexttoken%
\gdef\LWR@columnHTMLcolor{}%
\gdef\LWR@rowHTMLcolor{}%
\gdef\LWR@cellHTMLcolor{}%
\@rowcolors%
```

The vertical rules are set to the color active at the start of the tabular. \arrayrulecolor will then affect horizontal rules inside the tabular, but not the vertical rules.

```
\ifdefvoid{\LWR@ruleHTMLcolor}%
    {\edef\LWR@vertruleHTMLcolor{black}}%
    {\edef\LWR@vertruleHTMLcolor{\LWR@origpound\LWR@ruleHTMLcolor}}%
```

Tracking the depth of cell color s:

```
\setcounter{LWR@cellcolordepth}{0}%
```

The following may appear before a data cell is created, so after doing their actions, we look ahead with \LWR@getmynextoken to see if the next token might create a new data cell:

The optional parameter for \hline supports the tabls package.

```
\LWR@traceinfo{LWR@@HTML@tabular: redefining macros}%
\LetLtxMacro\noalign\LWR@tabularnoalign%
\LetLtxMacro\hline\LWR@HTMLhline%
\LetLtxMacro\cline\LWR@HTMLcline%

\DeclareDocumentCommand{\hdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%
```

```
\DeclareDocumentCommand{\cdashline}{m}{%
    \LWR@docdashline{##1}\LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\firsthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%

\DeclareDocumentCommand{\lasthdashline}{o}{%
    \ifbool{FormatWP}%
        {\LWR@docdashline{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {\addtocounter{LWR@hdashedlines}{1}}%
    \LWR@getmynexttoken%
}%
```

The following create data cells and will have no more data in this cell, so we do not want to look ahead for a possible data cell, so do not want to use `\LWR@getmynexttoken`.

```
\renewcommand{\multicolumn}{\LWR@htmlmulticolumn}%
\renewcommand*{\mrowcell}{%
    \LWR@maybenewtablerow%
    \LWR@tabularleftedge%
    \global\booltrue{LWR@skippingmrowcell}%
    \booltrue{LWR@foundmrowcell}%
}%
\renewcommand*{\mcolrowcell}{%
    \LWR@maybenewtablerow%
    \global\booltrue{LWR@skippingmcolrowcell}%
    \booltrue{LWR@foundmrowcell}%
}%
\LetLtxMacro\caption\LWR@longtabledatacaptiontag%
```

Reset for new processing:

```
\global\boolfalse{LWR@tableparcell}%
\global\boolfalse{LWR@skippingmrowcell}%
\global\boolfalse{LWR@skippingmcolrowcell}%
\global\boolfalse{LWR@skipatbang}%
\global\boolfalse{LWR@emptyatbang}%
```

Set & for its special meaning inside the tabular:

```
\StartDefiningTabulars%
\protected\gdef&{\LWR@tabularampersand}%
```

Locally force any minipages to be fullwidth, until the end of the `tabular`:

```
\booltrue{LWR@forceminipagefullwidth}
```

Nest one level deeper of tabular paragraph handling:

```
\addtocounter{LWR@tabularpardepth}{1}%
```

Look ahead for a possible table data cell:

```
\LWR@traceinfo{LWR@@HTML@tabular: about to LWR@getmynexttoken}%
\LWR@getmynexttoken%
}%
```

Ending the environment:

```
\newcommand*{\LWR@HTML@endtabular}
{%
\LWR@traceinfo{LWR@HTML@endtabular}%
```

Unnest one level of tabular paragraph handling:

```
\addtocounter{LWR@tabularpardepth}{-1}%
\ifboolexpr{%
    test {%
      \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{<}{\value{LWR@tabletotalLaTeXcols}}
    } or %
    (%
        bool{LWR@intabularmetadata} and%
        not bool{LWR@tabularcelladded} and%
        test {%
        \ifnumcomp{\value{LWR@tableLaTeXcolindex}}{=}{\value{LWR@tabletotalLaTeXcols}}%
        }%
    )%
}%
{%
    \LWR@tabularfinishrow%
}%
{%
    \LWR@closetabledatacell%
}%
\LWR@htmlblocktag{/tr}%
```

xcolor row color support:

```
\@rowc@lors%

\LWR@htmlblocktag{/table}%
\global\boolfalse{LWR@intabularmetadata}%
```

Unnest one level of tabular:

```
\addtocounter{LWR@tabulardepth}{-1}%
```

Restore & to its usual meaning:

```
\protected\gdef&{\LWR@origampmacro}%
\StopDefiningTabulars%
```

Error if used \multirow or \multicolumnrow without using \mrowcell or \mcolrowcell.

```
\ifbool{LWR@usedmultirow}{%
    \ifbool{LWR@foundmrowcell}%
        {}%
        {%
            \PackageError{lwarp}%
            {%
            When using \protect\multirow, \protect\multicolumnrow,\MessageBreak
                or the bigdelim package,\MessageBreak
             place \protect\mrowcell\space or \protect\mcolrowcell\MessageBreak
                in empty cells which are to be skipped.\MessageBreak
                See the lwarp package documentation:\MessageBreak
                "Special cases and limitations" -> "Tabular"
            }%
            {%
                See the lwarp package documentation:\MessageBreak
                "Special cases and limitations" -> "Tabular".
            }%
        }%
}{}%

\LWR@traceinfo{LWR@HTML@endtabular finished}%
}

\csletcs{LWR@HTML@endtabular*}{LWR@HTML@endtabular}

\StopDefiningTabulars
```

siunitx may redefine tabular, so set the following later:

```
\AtBeginDocument{
    \LetLtxMacro\LWR@origendtabular\endtabular
    \csletcs{LWR@origendtabular*}{endtabular*}
    \LWR@formatted{@tabular}
    \LWR@formatted{endtabular}
    \LWR@formatted{endtabular*}
}

\end{warpHTML}
```

73 Cross-references

Sectioning commands have been emulated from scratch, so the cross-referencing commands are custom-written for them. Emulating both avoids several layers of patches.

File *_html.aux

A new entry in *_html.aux is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

Table 12 shows the data structures related to cross-referencing.

for HTML output:
```
\begin{warpHTML}
```

73.1 Setup

`\@currentlabelname` To remember the most recently defined section name, description, or caption, for `\nameref`.

```
\providecommand*{\@currentlabelname}{}
```

`\LWR@stripperiod` {⟨*text*⟩} [⟨.⟩]

Removes a trailing period.

```
\def\LWR@stripperiod#1.\ltx@empty#2\@nil{#1}%
```

`\LWR@setlatestname` {⟨*object name*⟩}

Removes `\label`, strips any final period, and remembers the result.

```
\newcommand*{\LWR@setlatestname}[1]{%
```

Remove `\label` and other commands from the name, the strip any final period. See gettitlestring.

```
\GetTitleStringExpand{#1}%
\edef\@currentlabelname{\detokenize\expandafter{\GetTitleStringResult}}%
\edef\@currentlabelname{%
    \expandafter\LWR@stripperiod\@currentlabelname%
    \ltx@empty.\ltx@empty\@nil%
}%
}
```

73.2 New lwarp labels.

File `*_html.aux` A new entry in `*_html.aux` is used to remember section name, file, and lateximage depth and number for each label:

```
\newlabel{<labelname>@lwarp}{{<section name>}{<filename>}
                                    {<limagedepth>}{<limagenumber>}}
```

See:
http://tex.stackexchange.com/questions/57194/extract-section-number-from-equation-reference

Table 12: Cross-referencing data structures

Original LaTeX: (print and html)

\refstepcounter: Steps the couunter and sets \@currentlabel.

\@currentlabel: \p@<ctr>\the<ctr> Updated by \refstepcounter.

\label: Writes to the .aux file:
\newlabel{<label>}{{\@currentlabel}{\thepage}}

\newlabel: When the .aux file is read, sets \r@<label>.

\r@<label>: Set to: {{\@currentlabel}{\thepage}}

\ref: Returns the first part of \r@<label>.

\pageref: Returns the second part of \r@<label>.

Added by lwarp: (html only)

\label: Adds html tags (section 73.3), and another .aux entry (section 73.2).

\newlabel: Unchanged. When the .aux file is read, sets \r@<label>@lwarp.

\r@<label>@lwarp: Set to {{section_name}{file_name}{depth}{number}}:

\LWR@nameref: The section name for this label.

\LWR@htmlfileref: The filenumber or name for this label.

\LWR@lateximagedepthref: The lateximagedepth for this label.

\LWR@lateximagenumberref: The lateximagenumber for this label.

\nameref: Emualted from hyperref for lwarp. See section 73.4.

\ref and \nameref: Adds html tags. See section 73.4.

Added by amsmath: (print and html)

\label: Execution is delayed until the math environment is completed.

\ltx@label: LaTeX \label, (html: patched by lwarp,) later patched by cleveref.

Added by cleveref: (print and html)

\refstepcounter: Added: sets \cref@currentlabel.

\cref@currentlabel: (<type>=<ctr> unless an alias is used):
[<type>][\arabic{<ctr>}][<parent ctrs>]{\p@<ctr>\the<ctr>} Also see section 59.4 for use with footnotes.

\label: Writes to the .aux file:
\newlabel{<label>@cref}{{\cref@currentlabel}{\thepage}}

\newlabel: Unchanged. When the .aux file is read, sets \r@<label>@cref.

\r@<label>@cref: Set to: {{\cref@currentlabel}{\thepage}}

Utility functions: See \cref@getlabel, \cref@gettype, \cref@getcounter, \cref@getprefix.

Cross-referencing names: \crefname and \Crefname assign human-readable names for references to this counter type.

Additionally patched by lwarp: (html only)

\cref, etc.: Modified for lwarp. See section 87.

\label inside math: See section 79.7.1.

Footnotes: See \noteentry in section 59.4.

`\LWR@setref` {⟨*args list*⟩} {⟨*selector*⟩} {⟨*label*⟩}

`\@setref` without the `\null` (`\hbox`), and without the warning messages. Each caused problems with lwarp references. The regular reference will cause the warning.

```
\def\LWR@setref#1#2#3{%
  \ifx#1\relax%
    ??%
  \else%
   \expandafter#2#1%
  \fi}
```

`\LWR@nameref` {⟨*label*⟩} Returns the section name for this label:

```
\newcommand*{\LWR@nameref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@firstoffour{#1}%
}
```

`\LWR@htmlfileref` {⟨*label*⟩} Returns the file number or name for this label:

```
\newcommand*{\LWR@htmlfileref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@secondoffour{#1}%
}
```

`\LWR@lateximagedepthref` {⟨*label*⟩} Returns the `lateximagedepth` for this label:

```
\newcommand*{\LWR@lateximagedepthref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@thirdoffour{#1}%
}
```

`\LWR@lateximagenumberref` {⟨*label*⟩} Returns the `lateximagenumber` for this label:

```
\newcommand*{\LWR@lateximagenumberref}[1]{%
    \expandafter\LWR@setref\csname r@#1@lwarp\endcsname\LWR@fourthoffour{#1}%
}
```

`\LWR@lwarplabel` {⟨*label*⟩} Sanitize the name and then creates the label:

```
\newcommand*{\LWR@lwarplabel}[1]{%
\LWR@traceinfo{LWR@lwarplabel !#1!}%
\LWR@setlatestname{\@currentlabelname}%
    \@bsphack%
    \protected@write\@auxout{}%
        {\string\newlabel{#1@lwarp}{%
            {\@currentlabelname}%
        {\ifbool{FileSectionNames}{\LWR@thisfilename}{\arabic{LWR@htmlfilenumber}}}%
            {\arabic{LWR@lateximagedepth}}%
            {\arabic{LWR@lateximagenumber}}%
        }}%
    \@esphack%
}
```

73.3 Labels

\LWR@sublabel {⟨*label*⟩} Creates an HTML id tag.

\detokenize is used to allow underscores in the labels.

```
\newcommand*{\LWR@sublabel}[1]{%
\LWR@traceinfo{LWR@sublabel !#1!}%
```

Create an HTML id tag unless are inside a lateximage, since it would appear in the image:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{% not lateximage
```

If not doing a lateximage, create an HTML ID tag: (To be factored...)

```
    \LWR@sanitize{#1}%
    \ifbool{LWR@doingstartpars}%
    {% pars allowed
        \ifbool{LWR@doingapar}%
        {% par started
         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
        }% par started
        {% par not started
            \LWR@stoppars%
         \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
            \LWR@startpars%
        }% par not started
    }% pars allowed
    {% pars not allowed
        \LWR@htmltag{a \LWR@print@mbox{id="\LWR@sanitized"}}\LWR@htmltag{/a}%
    }% pars not allowed
}% not lateximage
}
```

\LWR@new@label (⟨*bookmark*⟩) {⟨*label*⟩} [⟨*type*⟩]

\label during HTML output when not in SVG math mode, removing extra spaces around the label, as done by a regular LaTeX \label.

The is also used during a lateximage, including SVG math, since the special label handling is required, but \LWR@sublabel does not generate HTML tags inside a lateximage.

clevereref later encases this to add its own cross-referencing.

The optional ⟨*bookmark*⟩ is per the memoir class, and is ignored.

The optional ⟨*type*⟩ is per the ntheorem package, and is ignored.

```
\NewDocumentCommand{\LWR@new@label}{d() m o}{%
```

```
\LWR@traceinfo{LWR@new@label: starting}%
\LWR@traceinfo{LWR@new@label: !#2!}%
% \@bsphack%
```

Create a traditional LaTeX label, as modified by cleveref:

```
\LWR@orig@label{#2}%
```

Create a special label which holds the section number, LWR@htmlfilenumber, LWR@lateximagedepth, and LWR@lateximagenumber:

```
\LWR@traceinfo{LWR@new@label: filesectionnames is \ifbool{FileSectionNames}{true}{false}}%
\LWR@traceinfo{LWR@new@label: LWR@thisfilename is !\LWR@thisfilename!}%
\LWR@traceinfo{LWR@new@label: LWR@htmlfilenumber is \arabic{LWR@htmlfilenumber}}%
\LWR@lwarplabel{#2}%
\LWR@sublabel{#2}%
% \@esphack%
\LWR@traceinfo{LWR@new@label: done}%
}
```

73.4 References

\LWR@startref {⟨*label*⟩} (Common code for \ref and \nameref.)

Open an HTML tag reference to a filename, # character, and a label.

```
\newcommand*{\LWR@startref}[1]
{%
\LWR@sanitize{#1}%
\LWR@traceinfo{LWR@startref A: !#1!}%
```

Create the filename part of the link:

```
\LWR@htmltag{a href="%
\LWR@traceinfo{LWR@startref B}%
\LWR@print@mbox{\LWR@htmlrefsectionfilename{#1}}%
\LWR@traceinfo{LWR@startref C}%
\LWR@origpound%
```

Create the destination id:

See if LWR@lateximagedepth is unknown:

```
\LWR@traceinfo{LWR@startref D: !#1!}%
\ifcsundef{r@#1@lwarp}%
```

"??" if LWR@lateximagedepth is unknown, so create a link with an unknown destination:

```
{%
    \LWR@traceinfo{LWR@startref D0: ??}%
```

```
    ??%
}%
```

If LWR@lateximagedepth is known. Use a latexmage if the depth is greater than zero, or a regular link otherwise:

```
{%
    \ifthenelse{\cnttest{\LWR@lateximagedepthref{#1}}{>}{0}}%
        {%
            \LWR@ImagesName\LWR@lateximagenumberref{#1}%
        }%
        {%
            \LWR@traceinfo{LWR@startref D3}%
```

\detokenize is used to allow underscores in the labels:

```
            \LWR@print@mbox{\LWR@sanitized}%
        }%
}%
\LWR@traceinfo{LWR@startref E}%
```

Closing quote:

```
"}%
\LWR@traceinfo{LWR@startref F}%
}
```

\LWR@subnewref {⟨*label*⟩} {⟨*label or sub@label*⟩}

Factored for the subfig package. Uses the original label for the hyper-reference, but prints its own text, such as "1(b)".

```
\NewDocumentCommand{\LWR@subnewref}{m m}{%
\LWR@traceinfo{LWR@subnewref #1 #2}%
\LWR@startref{#1}%
\LWR@print@ref{#2}%
\LWR@htmltag{/a}%
}
```

\ref * {⟨*label*⟩} \ref is redefined to \LWR@HTML@ref, except inside the text part of a \hyperref, where it is redefined to \LWR@ref@ignorestar.

\LWR@HTML@ref * {⟨*label*⟩} Create an internal document reference link, or without a link if starred per hyperref.

```
\NewDocumentCommand{\LWR@HTML@ref}{s m}{%
\LWR@traceinfo{LWR@HTML@ref !#2!}%
\IfBooleanTF{#1}%
{\LWR@print@ref{#2}}%
{\LWR@subnewref{#2}{#2}}%
}

\LWR@formatted{ref}
```

`\LWR@ref@ignorestar` * {⟨*label*⟩} For use inside `\hyperref`. Ignores the star, then uses the original `\ref`.

```
\NewDocumentCommand{\LWR@ref@ignorestar}{s m}{%
    \LWR@print@ref{#2}%
}
```

`\pagerefPageFor` Text for page references.

```
\newcommand*{\pagerefPageFor}{see }
```

`\pageref` * {⟨*label*⟩} Create an internal document reference, or just the unlinked number if starred, per hyperref.

```
\NewDocumentCommand{\LWR@new@pageref}{s m}{%
\IfBooleanTF{#1}%
{(\pagerefPageFor\LWR@print@ref{#2})}%
{(\cpageref{#2})}%
}
```

`\nameref` {⟨*label*⟩}

```
\newrobustcmd*{\nameref}[1]{%
\LWR@traceinfo{nameref}%
\LWR@startref{#1}%
\LWR@traceinfo{nameref B}%
\LWR@nameref{#1}%
\LWR@traceinfo{nameref C}%
\LWR@htmltag{/a}%
\LWR@traceinfo{nameref: done}%
}
```

`\Nameref` {⟨*label*⟩} In print, adds the page number. In HTML, does not.

```
\LetLtxMacro\Nameref\nameref
```

73.5 Hyper-references

⚠ Note that the code currently only sanitizes the underscore character. Additional characters should be rendered inert as well. See the `hyperref.sty` definition of `\gdef\hyper@normalise` for an example.

`Pkg` `hyperref`

⚠ Do not tell other packages that hyperref is emulated. Some packages patch various commands if hyperref is present, which will probably break something, and the emulation already handles whatever may be emulated anyhow.

```
% DO NOT TELL OTHER PACKAGES TO ASSUME HYPERREF, lest they attempt to patch it:
% \EmulatesPackage{hyperref}[2015/08/01]% Disabled.  Do not do this.
```

Emulates hyperref:

\@currentHref Added to support backref.

```
\AtBeginDocument{
\def\@currentHref{%
autopage-\theLWR@currentautosec%
}
}
```

\LWR@subhyperref {⟨*URL*⟩}

Starts a link for \LWR@hrefb. A group must have been opened first, with nullified catcodes. The text name is printed afterwards, after the group is closed and catcodes restored.

```
\NewDocumentCommand{\LWR@subhyperref}{m}{%
\LWR@traceinfo{LWR@subhyperref !#1!}%
\LWR@sanitize{#1}%
\LWR@htmltag{%
    a href="\LWR@sanitized" % space
    target="\_{}blank" % space
}%
}
```

\LWR@subhyperreftext {⟨*text*⟩}

Finishes the hyperref for \LWR@hrefb. Catcodes must have been restored already. To be used after \LWR@subhyperref, and after its group has been closed.

```
\newcommand{\LWR@subhyperreftext}[1]{%
#1%
\LWR@htmltag{/a}%
\LWR@ensuredoingapar%
}
```

\LWR@subhyperrefclass {⟨*URL*⟩} {⟨*text*⟩} {⟨*htmlclass*⟩}

```
\NewDocumentCommand{\LWR@subhyperrefclass}{m +m m}{%
\LWR@htmltag{%
    a % space
    href="\begingroup\@sanitize#1\endgroup" % space
    class="#3" % space
}\LWR@orignewline%
#2\LWR@orignewline%
\LWR@htmltag{/a}%
\LWR@ensuredoingapar%
}
```

\href [⟨*options*⟩] {⟨*URL*⟩}

Create a link with accompanying text:

```
\DeclareDocumentCommand{\LWR@hrefb}{O{} m}{%
\LWR@ensuredoingapar%
\LWR@subhyperref{#2}%
\endgroup% restore catcodes
\LWR@subhyperreftext%
}

\newrobustcmd*{\href}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hrefb%
}
```

`\nolinkurl` {⟨*URL*⟩}

Print the name of the link without creating the link:

```
\newcommand*{\LWR@nolinkurlb}[1]{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\LWR@templink%
\endgroup%
}

\newrobustcmd*{\nolinkurl}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@nolinkurlb%
}
```

`\url` {⟨*URL*⟩}

Create a link whose text name is the address of the link.

The url package may redefine `\url`, so it is `\let` to `\LWR@urlahere` and also redefined by lwarp-url.

```
\DeclareDocumentCommand{\LWR@urlb}{m}{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\href{\LWR@templink}{\LWR@templink}%
\endgroup%
```

```
}

\newrobustcmd*{\url}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@urlb%
}
```

`\LWR@subinlineimage` `[`⟨*alttag*⟩`]` `{`⟨*class*⟩`}` `{`⟨*filename*⟩`}` `{`⟨*extension*⟩`}` `{`⟨*style*⟩`}`

```
\newcommand*{\LWR@subinlineimage}[5][]{%
\ifblank{#1}%
{%
    \LWR@htmltag{img \LWR@indentHTML
        src="#3.#4" \LWR@indentHTML
        alt="#3" \LWR@indentHTML
        style="#5" \LWR@indentHTML
        class="#2" \LWR@orignewline
    }%
}%
{%
    \LWR@htmltag{img \LWR@indentHTML
        src="#3.#4" \LWR@indentHTML
        alt="#1" \LWR@indentHTML
        style="#5" \LWR@indentHTML
        class="#2" \LWR@orignewline
    }%
}%
}

\end{warpHTML}
```

Table 13: Float data structures

For each <type> of float (figure, table, etc.) there exists the following:
counter <type>: A counter called <type>, such as figure, table.
\<type>name: Name. \figurename prints "Figure", etc.
\ext@<type>: File extension. \ext@figure prints "lof", etc.
\fps@<type>: Placement.
\the<type>: Number. \thetable prints the number of the table, etc.
\p@<type>: Parent's number. Prints the number of the [within] figure, etc.
\fnum@<type>: Prints the figure number for the caption. \<type>name \the<type>, "Figure 123".
\<type>: Starts the float environment. \figure or \begin{figure}
\end<type>: Ends the float environment. \endfigure or \end{figure}
\tf@<ext>: The LaTeX file identifier for the output file.
LWR@have<type>: A boolean remembering whether a \listof was requested for a float of this type.
File with extension lo<f,t,a-z>: An output file containing the commands to build the \listof<type> "table-of-contents" structure.
Cross-referencing names: For cleveref's \cref and related, \crefname and \Crefname assign human-readable names for references to this float type.

74 Floats

Floats are supported, although partially through emulation.

Table 13 shows the data structure associated with each <type> of float.

\@makecaption is redefined to print the float number and caption text, separated by \CaptionSeparator, which works with the babel package to adjust the caption separator according to the language. French, for example, uses an en-dash instead of a colon: "Figure 123 – Caption text".

74.1 Float environment

for HTML output: 8930 \begin{warpHTML}

\LWR@floatbegin {⟨*type*⟩} [⟨*placement*⟩] Begins a \newfloat environment.

```
\NewDocumentCommand{\LWR@floatbegin}{m o}{%
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars
```

There is a new float, so increment the unique float counter:

```
\addtocounter{LWR@thisautoid}{1}%
\booltrue{LWR@freezethisautoid}%

\begingroup%
```

Settings while inside the environment:

```
\LWR@print@raggedright%
```

Open an HTML `figure` tag. The figure is assigned a `class` equal to its type, and another class according to the float package style, if used. Note that `\csuse` returns an empty string if `\LWR@floatstyle@<type>` is not defined.

```
\LWR@htmltag{%
    figure id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}" % space
    class="#1 \@nameuse{LWR@floatstyle@#1}"%
}%
\ifbool{FormatWP}{%
    \LWR@orignewline%
    \LWR@BlockClassWP{}{}{wp#1}%
}{}%
```

Update the caption type:

```
\renewcommand*{\@captype}{#1}%
\caption@settype{#1}%
```

Mark the float for a word processor conversion:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

=== begin #1 ===

}{}%
```

Look for `\centering`, etc:

```
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
```

For koma-script. The following does not work for tables.

```
\AtBeginDocument{
\@ifpackageloaded{tocbasic}{
\appto\figure@atbegin{%
```

```
\LWR@futurenonspacelet\LWR@mynexttoken\LWR@floatalignment%
}
}{}
}
```

\@float
\@dlbfloat

Support packages which create floats directly.

```
\let\@float\LWR@floatbegin
\let\@dblfloat\LWR@floatbegin
```

\LWR@floatend

Ends a \newfloat environment.

```
\newcommand*{\LWR@floatend}{%
```

If saw a \centering, finish the center environment:

```
\LWR@endfloatalignment%
```

Mark the float end for a word processor conversion:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkFloats}}{%

=== end ===

}{}%
\LWR@stoppars%
```

Close an HTML figure tag:

```
\ifbool{FormatWP}{\endLWR@BlockClassWP}{}%
\LWR@htmlelementend{figure}%
\endgroup%
\boolfalse{LWR@freezethisautoid}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
}
```

\end@float
\end@dlbfloat

Support packages which create floats directly.

```
\let\end@float\LWR@floatend
\let\end@dblfloat\LWR@floatend
```

74.2 Float tracking

Ctr LWR@thisautoid

A sequential counter for all floats and theorems. This is used to identify the float or theorem then reference it from the List of Figures and List of Tables.

```
\newcounter{LWR@thisautoid}
```

Ctr LWR@thisautoidWP A sequential counter for all word processor conversion s. This is used to convince LibreOffice to form a frame around this element.

```
\newcounter{LWR@thisautoidWP}
```

Bool LWR@freezethisautoid Prevents multiple increments of \LWR@thisautoid inside a float.

```
\newbool{LWR@freezethisautoid}
\boolfalse{LWR@freezethisautoid}
```

\LWR@newautoidanchor Adds a new <autoid> anchor.

```
\newcommand*{\LWR@newautoidanchor}{%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{}%
{%
    \ifbool{LWR@freezethisautoid}{}{%
        \addtocounter{LWR@thisautoid}{1}%
        \LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}%
            \LWR@htmltag{/a}%
    }%
}%
}
```

\@captype Remembers which float type is in use.

```
\newcommand*{\@captype}{}
```

\LWR@floatalignmentname Set to center, flushleft, or flushright if saw \centering, \raggedright, or \raggedleft.

```
\newcommand*{\LWR@floatalignmentname}{}
```

\LWR@floatalignment If sees a \centering, \raggedleft, or \raggedright, creates a center, flushright, or flushleft environment.

```
\newcommand*{\LWR@floatalignment}{%
\ifdefstrequal{\LWR@mynexttoken}{\centering}{%
    \center%
    \renewcommand*{\LWR@floatalignmentname}{center}%
}{}%
\ifdefstrequal{\LWR@mynexttoken}{\raggedright}{%
    \flushleft%
    \renewcommand*{\LWR@floatalignmentname}{flushleft}%
}{}%
\ifdefstrequal{\LWR@mynexttoken}{\raggedleft}{%
    \flushright%
    \renewcommand*{\LWR@floatalignmentname}{flushright}%
}{}%
}
```

\LWR@endfloatalignment Closes an environment from \LWR@floatalignment.

```
\newcommand*{\LWR@endfloatalignment}{%
\ifdefvoid{\LWR@floatalignmentname}{}{\@nameuse{end\LWR@floatalignmentname}}%
\renewcommand*{\LWR@floatalignmentname}{}%
}
```

74.3 Caption inside a float environment

\CaptionSeparator How to separate the float number and the caption text.

```
\AtBeginDocument{\providecommand*{\CaptionSeparator}{:~}}
```

\@makecaption {⟨*name and num*⟩} {⟨*text*⟩}

Prints the float type and number, the caption separator, and the caption text.

```
\AtBeginDocument{\renewcommand{\@makecaption}[2]{%
    \LWR@traceinfo{@makecaption}%
    \LWR@isolate{#1}\CaptionSeparator\LWR@isolate{#2}%
    \LWR@traceinfo{@makecaption: done}%
}%
}
```

74.4 Caption and LOF linking and tracking

When a new HTML file is marked in the LaTeX PDF file, the LaTeX page number at that point is stored in LWR@latestautopage, (and the associated filename is remembered by the special LaTeX labels). This page number is used to generate an autopage HTML <id> in the HTML output at the start of the new HTML file. Meanwhile, there is a float counter used to generate an HTML autoid <id> at the start of the float itself in the HTML file. The autopage and autoid values to use for each float are written to the .lof, etc. files just before each float's entry. These values are used by \l@figure, etc. to create the HTML links in the List of Figures, etc.

Ctr LWR@nextautoid Tracks autoid for floats. Tracks autopage for floats.

Ctr LWR@nextautopage These are updated per float as the .lof, .lot file is read.

```
\newcounter{LWR@nextautoid}
\newcounter{LWR@nextautopage}
```

\LWRsetnextfloat {⟨*autopage*⟩} {⟨*float autoid*⟩}

File *_html.lof This is written to the *_html.lof or *_html.lot file just before each float's usual entry. The autopage and the float's autoid are remembered for \l@figure to use when creating the HTML links.

File *_html.lot

```
\newcommand*{\LWRsetnextfloat}[2]{%
    \setcounter{LWR@nextautopage}{#1}%
    \setcounter{LWR@nextautoid}{#2}%
}
```

Ctr LWR@latestautopage

Updated each time a new HTML file is begun. `\LWRsetnextfloat` is written with this and the `autoid` by the modified `\addcontentsline` just before each float's entry.

```
\newcounter{LWR@latestautopage}
\setcounter{LWR@latestautopage}{1}
```

Env LWR@figcaption

An HTML `<figcaption>` is not allowed in places where LaTeX does allow a figure caption, such as inside a `longtable` where the tabular has already started, or inside a `center` environment. Therefore, a `<div>` of class `figurecaption` is used instead.

```
\newenvironment*{LWR@figcaption}
    {
        \ifbool{FormatWP}{%
            \BlockClass[font-style:italic]{figurecaption}
% \LWR@print@vspace*{\baselineskip}
        }{
            \BlockClass{figurecaption}
        }%
    }
    {\endBlockClass}
```

\LWR@HTML@caption@begin {⟨*type*⟩}

Low-level code to create HTML tags for captions.

The print versions are from the caption package.

```
\newcommand*{\LWR@HTML@caption@begin}[1]
{%
\LWR@traceinfo{LWR@HTML@caption@begin}%
```

Keep par and minipage changes local:

```
\begingroup%
```

No need for a `minipage` or `\parbox` inside the caption:

```
\RenewDocumentEnvironment{minipage}{O{t} o O{t} m}{}{}%
\RenewDocumentCommand{\parbox}{O{t} O{} O{t} m +m}{##5}%
```

Enclose the original caption code inside an HTML tag:

```
\LWR@figcaption%
\LWR@traceinfo{LWR@HTML@caption@begin: about to LWR@origcaption@begin}%
\LWR@print@caption@begin{#1}%
\LWR@traceinfo{LWR@HTML@caption@begin: done}%
}
```

\LWR@HTML@caption@end Low-level patches to create HTML tags for captions.

```
\newcommand*{\LWR@HTML@caption@end}
{%
\LWR@traceinfo{LWR@HTML@caption@end}%
\LWR@print@caption@end%
```

Closing tag:

```
\endLWR@figcaption%
\endgroup%
% \leavevmode% avoid bad space factor (0) error
\LWR@traceinfo{LWR@HTML@caption@end: done}%
}
```

\caption@begin
\caption@end Low-level patches to create HTML tags for captions. These are assigned \AtBeginDocument so that other packages which modify captions will have already been loaded before saving the print-mode version.

```
\AtBeginDocument{
\LWR@formatted{caption@begin}
\LWR@formatted{caption@end}
}
```

\captionlistentry Tracks the float number for this caption used outside a float. Patched to create an HTML anchor.

```
\let\LWR@origcaptionlistentry\captionlistentry

\renewcommand*{\captionlistentry}{%
\LWR@ensuredoingapar%
\LWR@origcaptionlistentry%
}

\def\LWR@LTcaptionlistentry{%
\LWR@ensuredoingapar%
\LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
  \bgroup
  \@ifstar{\egroup\LWR@LT@captionlistentry}% gobble *
          {\egroup\LWR@LT@captionlistentry}}%
\def\LWR@LT@captionlistentry#1{%
  \caption@listentry\@firstoftwo[\LTcaptype]{#1}}%
```

\addcontentsline Patched to write the autopage and autoid before each float's entry. No changes if writing .toc For a theorem, automatically defines \ext@<type> as needed, to mimic and reuse the float mechanism.

f

```
\let\LWR@origaddcontentsline\addcontentsline

\renewcommand*{\addcontentsline}[3]{%
\ifstrequal{#1}{toc}{}{% not TOC
```

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {}%
    {\LWR@newautoidanchor}%

    \ifcsvoid{ext@#2}{\csdef{ext@#2}{#1}}{}%

    \addtocontents{\@nameuse{ext@#2}}{%
        \protect\LWRsetnextfloat%
        {\arabic{LWR@latestautopage}}%
        {\arabic{LWR@thisautoid}}%
    }%
}% not TOC
\LWR@origaddcontentsline{#1}{#2}{#3}%
}
```

Pkg capt-of
Pkg caption

Either package provides `\captionof`, which is later patched at the beginning of the document.

`\captionof`

Patched to handle paragraph tags.

```
\AtBeginDocument{
\let\LWR@origcaptionof\captionof

\renewcommand*{\captionof}{%
\LWR@stoppars
\LWR@origcaptionof%
}
}

\end{warpHTML}
```

75 Table of Contents, LOF, LOT

This section controls the generation of the TOC, LOF, and LOT.

The `.toc`, `.lof`, and `.lot` files are named by the source code `\jobname`.

In HTML, the printed tables are placed inside a `<div>` of class `toc`, `lof`, or `lot`.

A "sidetoc" is provided which prints a subset of the TOC on the side of each page other than the homepage.

The regular LaTeX infrastructure is used for TOC, along with some patches to generate HTML output.

for HTML output:

```
\begin{warpHTML}
```

75.1 Reading and printing the TOC

`\LWR@myshorttoc` {⟨*toc/lof/lot/sidetoc*⟩}

Reads in and prints the TOC/LOF/LOT at the current position. While doing so, makes the `@` character into a normal letter to allow formatting commands in the section names.

Unlike in regular LaTeX, the file is not reset after being read, since the sideTOC may be referred to again in each HTML page.

```
\newcommand*{\LWR@myshorttoc}[1]{%
\LWR@traceinfo{LWR@myshorttoc: #1}%
\LWR@ensuredoingapar%
```

Only if the file exists:

```
\IfFileExists{\jobname.#1}{%
\LWR@traceinfo{LWR@myshorttoc: loading}%
```

⚠ Many of the commands in the file will have `@` characters in them, so `@` must be made a regular letter.

```
\begingroup%
\makeatletter%
```

Read in the TOC file:

```
\@input{\jobname.#1}%
\endgroup%
}%
{}%
\LWR@traceinfo{LWR@myshorttoc: done}%
}
```

`\LWR@subtableofcontents` {⟨*toc/lof/lot*⟩} {⟨*sectionstarname*⟩}

Places a TOC/LOF/LOT at the current position.

```
\NewDocumentCommand{\LWR@subtableofcontents}{m m}{%
```

Closes previous levels:

```
\@ifundefined{chapter}
{\LWR@closeprevious{section}}
{\LWR@closeprevious{chapter}}
```

Prints any pending footnotes so that they appear above the potentially large TOC:

```
\LWR@printpendingfootnotes
```

Place the list into its own chapter (if defined) or section:

```
\@ifundefined{chapter}{\section*{#2}}{\chapter*{#2}}
```

Create a new HTML nav containing the TOC/LOF/LOT:

```
\LWR@htmlelementclass{nav}{#1}
```

Create the actual list:

```
\LWR@myshorttoc{#1}
```

Close the nav:

```
\LWR@htmlelementclassend{nav}{#1}
}
```

`\@starttoc` {⟨*ext*⟩}

Patch `\@starttoc` to encapsulate the TOC inside HTML tags:

```
\let\LWR@orig@starttoc\@starttoc

\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Bool `LWR@copiedsidetoc` Used to only copy the TOC file to the sidetoc a single time.

(listings and perhaps other packages would re-use `\tableofcontents` for their own purposes, causing the sidetoc to be copied more than once, and thus end up empty.)

```
\newbool{LWR@copiedsidetoc}
\boolfalse{LWR@copiedsidetoc}
```

`\tableofcontents` Patch `\tableofcontents`, etc. to print footnotes first. newfloat uses `\listoffigures` for all future float types.

```
\AtBeginDocument{
\let\LWR@origtableofcontents\tableofcontents

\renewcommand*{\tableofcontents}{%
```

Do not print the table of contents if formatting for a word processor, which will presumably auto-generate its own updated table of contents:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkTOC}}{

=== table of contents ===

}
{
```

Copy the .toc file to .sidetoc for printing the sideTOC. The original .toc file is renewed when \tableofcontents is finished.

```
    \ifbool{LWR@copiedsidetoc}{}{%
        \LWR@copyfile{\jobname.toc}{\jobname.sidetoc}%
        \booltrue{LWR@copiedsidetoc}%
    }%
    \LWR@printpendingfootnotes
    \LWR@origtableofcontents
}
}% \tableofcontents
}% AtBeginDocument
```

\listoffigures

```
\let\LWR@origlistoffigures\listoffigures

\renewcommand*{\listoffigures}{
\ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{

=== list of figures ===

}
{
    \LWR@printpendingfootnotes
    \LWR@origlistoffigures
}
}
```

\listoftables

```
\let\LWR@origlistoftables\listoftables

\renewcommand*{\listoftables}{
\ifboolexpr{bool{FormatWP} and bool{WPMarkLOFT}}{

=== list of tables ===

}
{
    \LWR@printpendingfootnotes
    \LWR@origlistoftables
}
}
```

75.2 High-level TOC commands

\listof {⟨*type*⟩} {⟨*title*⟩}

Emulate the \listof command from the float package (section 230). Used to create lists of custom float types. Also used to redefine the standard LaTeX \listoffigures and \listoftables commands.

```
\NewDocumentCommand{\listof}{m +m}{%
\@ifundefined{l@#1}{%
    \csdef{l@#1}##1##2{\hypertocfloat{1}{#1}{\@nameuse{ext@#1}}{##1}{##2}}%
}{}%
\LWR@subtableofcontents{\@nameuse{ext@#1}}{#2}
\expandafter\newwrite\csname tf@\csname ext@#1\endcsname\endcsname
\immediate\openout \csname tf@\csname ext@#1\endcsname\endcsname
    \jobname.\@nameuse{ext@#1}\relax
}
```

75.3 Side TOC

The "side TOC" is a table-of-contents positioned to the side.

It may be renamed by redefining \sidetocname, and may contain paragraphs.

CSS may be used to format the sideTOC:

CSS related to sideTOC:

div.sidetoccontainer: The entire sideTOC.
div.sidetoctitle: The title.
div.sidetoccontents: The table of contents.

```
\end{warpHTML}
```

for HTML & PRINT:

```
\begin{warpall}
```

Ctr SideTOCDepth — Controls how deep the side-TOC gets. Use a standard LaTeX section level similar to tocdepth.

```
\newcounter{SideTOCDepth}
\setcounter{SideTOCDepth}{1}
```

\sidetocname — Holds the default name for the sideTOC.

```
\newcommand{\sidetocname}{Contents}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

\LWR@sidetoc Creates the actual side-TOC.

```
\newcommand*{\LWR@sidetoc}{
\LWR@forcenewpage
\LWR@stoppars
```

The entire sideTOC is placed into a nav of class sidetoc.

```
\LWR@htmlelementclass{div}{sidetoccontainer}
\LWR@htmlelementclass{nav}{sidetoc}

\setcounter{tocdepth}{\value{SideTOCDepth}}
```

The title is placed into a of class sidetoctitle, and may contain paragraphs.

```
\begin{BlockClass}{sidetoctitle}
\ifcsvoid{thetitle}{}{\InlineClass{sidetocthetitle}{\thetitle}\par}
\sidetocname
\end{BlockClass}
```

The table of contents is placed into a of class sidetoccontents.

```
\begin{BlockClass}{sidetoccontents}
\LinkHome

\LWR@myshorttoc{sidetoc}
\end{BlockClass}
\LWR@htmlelementclassend{nav}{sidetoc}
\LWR@htmlelementclassend{div}{sidetoccontainer}
}
```

75.4 Low-level TOC line formatting

\numberline {⟨*number*⟩}

(Called from each line in the .aux, .lof files.)

Record this section number for further use:

```
\newcommand*{\LWR@numberline}[1]{%
\LWR@sectionnumber{#1}\quad%
}

\LetLtxMacro\numberline\LWR@numberline
```

\LWR@maybetocdata Replaced by tocdata. Adds author name.

```
\newcommand*{\LWR@maybetocdata}{}
```

\hypertoc {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: name*⟩} {⟨*4: page*⟩}

Called by \l@section, etc. to create a hyperlink to a section.

The autopage label is always created just after the section opens.

#1 is depth

#2 is section, subsection, etc.

#3 the text of the caption

#4 page number

```
\NewDocumentCommand{\hypertoc}{m m +m m}{%
\LWR@traceinfo{hypertoc !#1!#2!#3!#4!}%
```

Respond to tocdepth:

```
\ifthenelse{\cnttest{#1}{<=}{\value{tocdepth}}}%
    {%
        \LWR@startpars%
```

Create an HTML link to <filename>#autosec-(page), with the name, of the given HTML class.

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
        \LWR@subhyperrefclass{%
            \LWR@htmlrefsectionfilename{\BaseJobname-autopage-#4}%
                \LWR@origpound\LWR@print@mbox{autosec-#4}%
        }{#3}{toc#2}%

        \LWR@maybetocdata%

        \LWR@stoppars%
    }%
    {}%
\LWR@traceinfo{hypertoc done}%
}
```

Ctr lofdepth TOC depth for figures.

```
\@ifclassloaded{memoir}{}{
\newcounter{lofdepth}
\setcounter{lofdepth}{1}
}
```

Ctr lotdepth TOC depth for tables.

```
\@ifclassloaded{memoir}{}{
\newcounter{lotdepth}
\setcounter{lotdepth}{1}
}
```

\hypertocfloat {⟨*1: depth*⟩} {⟨*2: type*⟩} {⟨*3: ext of parent*⟩} {⟨*4: caption*⟩} {⟨*5: page*⟩}

#1 is depth

#2 is figure, table, etc.

#3 is lof, lot, of the parent.

#4 the text of the caption

#5 page number

```
\newcommand{\hypertocfloat}[5]{%
\LWR@startpars
```

If some float-creation package has not yet defined the float type's lofdepth counter, etc, define it here:

```
\@ifundefined{c@#3depth}{%
\newcounter{#3depth}%
\setcounter{#3depth}{1}%
}{}%
```

Respond to lofdepth, etc.:

```
\LWR@traceinfo{hypertocfloat depth is #1 #3depth is \arabic{#3depth}}%
\ifthenelse{\cnttest{#1}{<=}{\arabic{#3depth}}}%
    {%
        \LWR@startpars%
```

Create an HTML link to filename#autoid-(float number), with text of the caption, of the given HTML class.

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
        \LWR@subhyperrefclass{%
        \LWR@htmlrefsectionfilename{%
            \BaseJobname-autopage-\arabic{LWR@nextautopage}%
        }%
        \LWR@origpound\LWR@print@mbox{autoid-\arabic{LWR@nextautoid}}}%
        {#4}{toc#2}%

        \LWR@maybetocdata%

        \LWR@stoppars%
    }%
    {}%
}
```

Automatically called by \contentsline:

`\l@part` {⟨*name*⟩} {⟨*page*⟩}

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\part`.

```
\DeclareDocumentCommand{\l@part}{m m}{\hypertoc{-1}{part}{#1}{#2}}
```

`\l@chapter` {⟨*name*⟩} {⟨*page*⟩}

Uses `\DeclareDocumentCommand` in case the class does not happen to have a `\chapter`.

```
\@ifundefined{chapter}
{}
{
\DeclareDocumentCommand{\l@chapter}{m m}
    {\hypertoc{0}{chapter}{#1}{#2}}
}
```

`\l@section` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@section}[2]{\hypertoc{1}{section}{#1}{#2}}
```

`\l@subsection` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsection}[2]{\hypertoc{2}{subsection}{#1}{#2}}
```

`\l@subsubsection` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subsubsection}[2]{\hypertoc{3}{subsubsection}{#1}{#2}}
```

`\l@paragraph` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@paragraph}[2]{\hypertoc{4}{paragraph}{#1}{#2}}
```

`\l@subparagraph` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@subparagraph}[2]{\hypertoc{5}{subparagraph}{#1}{#2}}
```

`\l@figure` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@figure}[2]{\hypertocfloat{1}{figure}{lof}{#1}{#2}}
```

`\l@table` {⟨*name*⟩} {⟨*page*⟩}

```
\renewcommand{\l@table}[2]{\hypertocfloat{1}{table}{lot}{#1}{#2}}
```

```
\end{warpHTML}
```

76 Index and glossary

See:
http://tex.stackexchange.com/questions/187038/how-to-mention-section-number-in-index-created-by-imakeidx

Index links are tracked by the counter LWR@autoindex. This counter is used to create a label for each index entry, and a reference to this label for each entry in the index listing. This method allows each index entry to link directly to its exact position in the document.

for HTML output:

```
\begin{warpHTML}

\newcounter{LWR@autoindex}
\setcounter{LWR@autoindex}{0}

\newcounter{LWR@autoglossary}
\setcounter{LWR@autoglossary}{0}
```

Env theindex

```
\@ifundefined{chapter}
{\newcommand*{\LWR@indexsection}[1]{\section*{#1}}}
{\newcommand*{\LWR@indexsection}[1]{\chapter*{#1}}}

\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

\LWR@indexitem [⟨*index key*⟩] The optional argument is added to support repeatindex.

```
\newcommand{\LWR@indexitem}[1][\@empty]{

\InlineClass{indexitem}{}#1%
}
```

\LWR@indexsubitem

```
\newcommand{\LWR@indexsubitem}{

\InlineClass{indexsubitem}{}
}
```

\LWR@indexsubsubitem

```
\newcommand{\LWR@indexsubsubitem}{
\InlineClass{indexsubsubitem}{}
}
```

`\@wrindex` {⟨*term*⟩} Redefined to write the `LWR@autoindex` counter instead of `page`.

```
\def\LWR@wrindex#1{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
\protected@write\@indexfile{}%
{\string\indexentry{#1}{\arabic{LWR@autoindex}}}%
\endgroup
\@esphack}

\AtBeginDocument{
\let\@wrindex\LWR@wrindex
}
```

`\@wrglossary` {⟨*term*⟩} Redefined to write the `LWR@latestautopage` counter instead of `page`.

```
\def\@wrglossary#1{%
\addtocounter{LWR@autoglossary}{1}%
\LWR@new@label{LWRglossary-\theLWR@autoglossary}%
\protected@write\@glossaryfile{}%
{\string\glossaryentry{#1}{\theLWR@autoglossary}}%
\endgroup
\@esphack}
```

`\LWR@indexnameref` {⟨*LWR@autoindex*⟩}

Creates a hyperlink based on the given entry's autoindex.

```
\newcommand*{\LWR@indexnameref}[1]{\nameref{LWRindex-#1}}
```

`\LWR@doindexentry` {⟨*LWR@autoindex, or macros.*⟩}

Creates a hyperlink, or handles `\see`, `\textbf`, etc.

```
\newrobustcmd{\LWR@doindexentry}[1]{%
\IfInteger{#1}%
    {\LWR@indexnameref{#1}}%
    {#1}%
}
```

`\LWR@hyperindexrefnullified` Handles macros commonly seen inside an `\index` entry. Each macro is redefined to create and format a link to its entry.

⚠ index formatting To handle additional macros:

```
\appto\LWR@hyperindexrefnullified{. . . }
```

```
\newcommand{\LWR@hyperindexrefnullified}{%
\renewrobustcmd{\emph}[1]{\LWR@HTML@emph{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textbf}[1]{\LWR@HTML@textbf{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\texteb}[1]{\LWR@HTML@texteb{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textlg}[1]{\LWR@HTML@textlg{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textrm}[1]{\LWR@HTML@textrm{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsf}[1]{\LWR@HTML@textsf{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\texttt}[1]{\LWR@HTML@texttt{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textup}[1]{\LWR@HTML@textup{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsc}[1]{\LWR@HTML@textsc{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textulc}[1]{\LWR@HTML@textulc{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsi}[1]{\LWR@HTML@textsi{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textit}[1]{\LWR@HTML@textit{\LWR@doindexentry{##1}}}%
\renewrobustcmd{\textsl}[1]{\LWR@HTML@textsl{\LWR@doindexentry{##1}}}%
}
```

`\hyperindexref` {⟨*LWR@autoindex*⟩}

`\hyperindexref{LWR@autoindex}` is inserted into `*.ind` by the makeindex style file `lwarp.ist` or the xindy style file `lwarp.xdy`.

```
\newcommand{\hyperindexref}[1]{%
```

In long index lines with numerous entries, *makeindex* can insert a newline before the page number, resulting in an extra space before the first digit. If the first character is a space, remove it first.

```
\def\LWR@tempone{#1}%
\IfBeginWith{\LWR@tempone}{ }{%
    \StrGobbleLeft{\LWR@tempone}{1}[\LWR@tempone]%
}{}%
```

If a numeric entry, create a link. If not numeric, such as `\see`, use the entry as-is. `\emph`, `\textit`, etc. have been redefined above to create and format the entry.

```
\IfInteger{\LWR@tempone}%
    {\LWR@indexnameref{\LWR@tempone}}%
    {%
        \begingroup%
        \LWR@hyperindexrefnullified
        #1%
        \endgroup%
    }%
}
```

```
\end{warpHTML}
```

for PRINT output: A null command for print mode, in case hyperref was not used:

```
\begin{warpprint}
\newcommand{\hyperindexref}[1]{#1}
\end{warpprint}
```

for HTML & PRINT: For the glossaries package, try to prevent an error where \glo@name was not found:

```
\begin{warpall}
\providecommand{\glo@name}{}
\end{warpall}
```

77 Bibliography presentation

for HTML output:

```
\begin{warpHTML}
```

\bibliography {⟨*filenames*⟩}

Modified to use the base jobname instead of the _html jobname.

```
\def\bibliography#1{%
    \if@filesw
    \immediate\write\@auxout{\string\bibdata{#1}}%
    \fi
%     \@input@{\jobname.bbl}% original
    \begingroup%
    \@input@{\BaseJobname.bbl}% lwarp
    \endgroup%
}
```

\@biblabel {⟨*text-refnumber*⟩}

```
\renewcommand{\@biblabel}[1]{[#1]\quad}
```

Env thebibliography To emphasize document titles in the bibliography, the following redefines \em inside thebibliography to gather everything until the next closing brace, then display these tokens with \textit.

Adapted from embracedef.sty, *which is by* Takayuki YATO*:*
https://gist.github.com/zr-tex8r/b72555e3e7ad2f0a37f1

```
\AtBeginDocument{
\AtBeginEnvironment{thebibliography}{
\providecommand*{\LWR@newem}[1]{\textit{#1}}

\renewrobustcmd{\em}{%
  \begingroup
    \gdef\LWR@em@after{\LWR@em@finish\LWR@newem}%
    \afterassignment\LWR@em@after
    \toks@\bgroup
}

\def\LWR@em@finish#1{%
    \xdef\LWR@em@after{\noexpand#1{\the\toks@}}%
  \endgroup
  \LWR@em@after\egroup
```

```
}
}% \AtBeginEnvironment{thebibliography}
}% \AtBeginDocument

\end{warpHTML}
```

78 Restoring original formatting

\LWR@restoreorigformatting

Used to temporarily restore the print-mode meaning of a number of formatting, graphics, and symbols-related macros while generating SVG math or a `lateximage`.

Must be used inside a group.

Sets `\LWR@formatting` to `print` until the end of the group.

A number of packages will `\appto` additional actions to this macro.

Various packages add to this macro using `\appto`.

for HTML output:

```
\begin{warpHTML}

\newcommand*{\LWR@restoreorigformatting}{%
\LWR@traceinfo{LWR@restoreorigformatting}%
```

Numerous macros change their print/HTML meaning depending on `\LWR@formatting`:

```
\renewcommand*{\LWR@formatting}{print}%
\linespread{1}%

\let\par\LWR@origpar%

\LWR@select@print@hspace%

\LetLtxMacro\hfil\LWR@orighfil%
\let\hss\LWR@orighss%
\let\llap\LWR@origllap%
\let\rlap\LWR@origrlap%
\let\hfilneg\LWR@orighfilneg%

\let\,\LWR@origcomma% disable HTML short unbreakable space
\let\thinspace\LWR@origthinspace% disable HTML short unbreakable space
\let\negthinspace\LWR@orignegthinspace% disable HTML negative short unbreakable space
\let\textellipsis\LWR@origtextellipsis%
\let\textless\LWR@origtextless%
\let\textgreater\LWR@origtextgreater%

\let\&\LWR@origampersand%

\LetLtxMacro\em\LWR@origem%
```

```
\LetLtxMacro\normalfont\LWR@orignormalfont%
\let\sp\LWR@origsp%
\let\sb\LWR@origsb%
\LetLtxMacro\textsuperscript\LWR@origtextsuperscript%
\LetLtxMacro\@textsuperscript\LWR@orig@textsuperscript%
\LetLtxMacro\textsubscript\LWR@origtextsubscript%
\LetLtxMacro\@textsubscript\LWR@orig@textsubscript%
\LetLtxMacro\underline\LWR@origunderline%
\let~\LWR@origtilde%
\let\enskip\LWR@origenskip%
\let\quad\LWR@origquad%
\let\qquad\LWR@origqquad%
```

`\endtabular` must be restored to its original, instead of relying on lwarp's `\LWR@formatted` mechanism:

```
\LetLtxMacro\endtabular\LWR@origendtabular%
\csletcs{endtabular*}{LWR@origendtabular*}%

\LetLtxMacro\noalign\LWR@orignoalign%
\LetLtxMacro\hline\LWR@orighline%

\let\newline\LWR@orignewline%
\LetLtxMacro\includegraphics\LWR@origincludegraphics%


\LetLtxMacro\@ensuredmath\LWR@origensuredmath%
%
\LWR@restoreorigaccents%
\LWR@restoreoriglists%
%
\LWR@FBcancel%
}

\end{warpHTML}
```

79 Math

79.1 Limitations

79.1.1 Math in section names

⚠ math in section names

If using named HTML files, in section names use paren math `\(x+y\)` instead of dollar math `$x+y$`. (Dollar math works, but appears in the filename.) Or, use a short name for the TOC entry without the math, or use `\texorpdfstring`:

```
\section{A name with math
    \texorpdfstring{$1+2=3$}{text description}}
```

79.1.2 Rendering tradeoffs

Math rendering

Math may be rendered as SVG graphics or using the MATHJAX JavaScript display engine.

SVG files

Rendering math as images creates a new SVG file for each expression, except that an MD5 hash is used to combine identical duplicates of the same inline math expression into a single file, which must be converted to SVG only once. Display math is still handled as individual files, since it may contain labels or references which are likely to change.

SVG inline

The SVG images are currently stored separately, but they could be encoded in-line directly into the HTML document. This may reduce the number of files and potentially speed loading the images, but slows the display of the rest of the document before the images are loaded.

PNG files

Others LaTeX-to-HTML converters have used PNG files, sometimes pre-scaled for print resolution but displayed on-screen at a scaled down size. This allows high-quality print output at the expense of larger files, but SVG files are the preferred approach for scalable graphics.

MathML

Conversion to MathML might be a better approach, among other things allowing a more compact representation of math than SVG drawings. Problems with MathML include limited browser support and some issues with the fine control of the appearance of the result. Also see section 10 regarding EPUB output with MATHJAX.

79.1.3 SVG option

SVG math option

For SVG math, math is rendered as usual by LaTeX into the initial PDF file using the current font[18], then is captured from the PDF and converted to SVG graphics via a number of utility programs. The SVG format is a scalable-vector web format, so math may be typeset by LaTeX with its fine control and precision, then displayed or printed at any size, depending on (sometimes broken) browser support. An HTML `alt` attribute carries the LaTeX code which generated the math, allowing copy/paste of the LaTeX math expression into other documents.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

SVG math copy/paste

For SVG math, text copy/paste from the HTML `<alt>` tags lists the equation number or tag for single equations, along with the LaTeX code for the math expression. For $\mathcal{AMS}$ environments with multiple numbers in the same environment, only the first and

[18] See section 517 regarding fonts and fractions.

last is copy/pasted, as a range. No tags are listed inside a starred $\mathcal{AMS}$ environment, although the \tag macro will still appear inside the LaTeX math expression.

⚠ SVG math in TeX boxes

SVG math does not work inside TeX boxes, since a \newpage is required before and after each image.

79.1.4 MathJax option

MathJax math option

Prog MathJax

The popular MathJax alternative (mathjax.org) may be used to display math.

When MathJax is enabled, math is rendered twice:

1. As regular LaTeX PDF output placed inside an HTML comment, allowing equation numbering and cross referencing to be almost entirely under the control of LaTeX, and
2. As detokenized printed LaTeX commands placed directly into the HTML output for interpretation by the MathJax display scripts. An additional script is used to pre-set the equation number format and value according to the current LaTeX values, and the MathJax cross-referencing system is ignored in favor of the LaTeX internal system, seamlessly integrating with the rest of the LaTeX code.

79.1.5 Customizing MathJax

MathJax does not have preexisting support every possible math function. Additional MathJax function definitions may be defined. These will be declared at the start of each HTML page, and thus will have a global effect.

Examples:

```
\CustomizeMathJax{
    \newcommand{\expval}[1]{\langle#1\rangle}
    \newcommand{\abs}[1]{\lvert#1\rvert}
}
\CustomizeMathJax{\newcommand{\arsinh}{\text{arsinh}}}
\CustomizeMathJax{\newcommand{\arcosh}{\text{arcosh}}}
\CustomizeMathJax{\newcommand{\NN}{\mathbb{N}}}
```

79.1.6 MathJax limitations

MathJax limitations

Prog MathJax

Limitations when using MathJax include:

subequations

- MathJax itself does not support subequations. This may be improved by parsing the LaTeX math expression to manually insert tags, but this has not yet been done.

footnotes in math

- Footnotes inside equations are not yet supported while using MathJax.

lateximage

- Math appearing inside a lateximage, and therefore also inside a Ti*k*z or `picture` environment, is rendered as SVG math even if MathJax is used in the rest of the document.

siunitx

- Usage of siunitx inside a math equation is supported via a third-party MathJax extension. While inside a math expression, do not use `\SI` or `\si` inside `\text`, where it will be rendered as normal text.

⚠ siunitx inside an equation

`https://github.com/burnpanck/MathJax-siunitx`

Also see section 8.7.11.

tabbing

- A `tabbing` environment is emulated using an HTML <pre>.While MathJax is enabled inside `tabbing`, the browser may not correctly render the horizontal alignment of the math and text following after on the same line.

⚠ other macros and packages

- Other math-related macros and packages are not supported by MathJax, including `\ensuremath` and bigdelim, along with occasionally-used macros such as `\relax`. lwarp emulates footnotes, units, and nicefrac for MathJax.

79.1.7 Catcode changes

preamble macros with math

The math shift character `$` is not set for HTML output until after the preamble. Macros defined in the preamble which contain `$` must be enclosed between `\StartDefiningMath` and `\StopDefiningMath` to temporarily change to the HTML meaning of `$`:

```
\StartDefiningMath
\newcommand{. . . }
\StopDefiningMath
```

As an alternative, use `\(` and `\)` instead of `$`, in which case `\StartDefiningMath` and `\StopDefiningMath` are not necessary.

If a package defines macros using `$`, it may be nessary to use `\StartDefiningMath` and `\StopDefiningMath` before and after loading the package.

79.1.8 Complicated inline math objects

`\inlinemathnormal`
`\inlinemathother`

changing contents
complicated `alt` tag

An inline math expression is usually converted to a reusable hashed SVG math image, or a MathJax expression. The hash or expression depends on the contents of the math expression. In most cases this math expression is static, such as `$x+1$`, so the image can be reused for multiples instances of the same expression. In some cases, the math expression includes a counter or other object which may change between uses. Another problem is complicated contents which do not expand well in an `alt` tag. The macro `\inlinemathother` may be used before a dynamic math expression, and `\inlinemathnormal` after. Doing so tells lwarp to use an unhashed SVG math image, even if MathJax is in use. See section 44.

79.1.9 Complicated display math objects

\displaymathnormal By default, or when selecting \displaymathnormal, MathJax math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother MathJax unsupported complicated alt tag When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML alt tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

79.2 HTML alt tag names

Redefinable names for the HTML alt tags, for translation according to the reader's native language.

for HTML & PRINT:

```
\begin{warpall}
```

\mathimagename Default: "math image" The HTML alt tag for an SVG math image.

```
\newcommand*{\mathimagename}{math image}
```

\packagediagramname Default: "diagram" Appended to the lateximage HTML alt tag for the images generated by many packages.

```
\newcommand*{\packagediagramname}{diagram}
```

```
\end{warpall}
```

79.3 Inline and display math

for HTML output:

```
\begin{warpHTML}
```

Ctr LWR@externalfilecnt Counter for the external files which are generated and then referenced from the HTML:

```
\newcounter{LWR@externalfilecnt}
```

Bool LWR@indisplaymathimage True if processing display math for SVG output. Inside a lateximage, display math is only set to print-mode output if LWR@indisplaymathimage is false. Used to avoid nullifying display math before it has been completed.

```
9458 \newbool{LWR@indisplaymathimage}
```

Bool LWR@xfakebold True if xfakebold \setBold is in use.

```
9459 \newbool{LWR@xfakebold}
9460 \boolfalse{LWR@xfakebold}
```

\LWR@orig@setBold Redefined by lwarp-xfakebold.

```
9461 \newcommand*{\LWR@orig@setBold}{}
```

\LWR@orig@unsetBold Redefined by lwarp-xfakebold.

```
9462 \newcommand*{\LWR@orig@unsetBold}{}
```

\LWR@applyxfakebold Redefined by lwarp-xfakebold.

```
9463 \newcommand*{\LWR@applyxfakebold}{}
```

\$ Plain dollar signs appearing in the HTML output may be interpreted by MathJax to be math shifts. For a plain text dollar \$, use an HTML entity to avoid it being interpreted by MathJax, unless are inside a lateximage, in which case it will not be seen by MathJax.

```
9464 \let\LWR@origtextdollar\$
9465
9466 \renewcommand*{\$}{%
9467 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
9468 {\LWR@origtextdollar}%
9469 {\HTMLentity{dollar}}%
9470 }
```

File lwarp_baseline_marker.png File lwarp_baseline_marker.eps A marker to be used to help *pdfcrop* identify the inline math baseline and width. If either graphicx or graphics is loaded, this marker is placed at the lower left and lower right corners of the inline math. *pdfcrop* is then able to identify the width of the image, and also the height of an image such as a horizontal dash which does not otherwise touch the baseline.

A marker with alpha or opacity of 0% is not registered by *pdfcrop*, so the marker is a small square block of 1% alpha, which seems to work while still being effectively invisible in the final SVG image.

If graphicx is loaded, this marker is sized as a tiny 1 sp square. If graphics is loaded, this marker is used at its default size of around .25 pt. If neither graphics package is loaded, the marker is replaced by a 10 sp horizontal space, and there is no assistance for determining baseline or width of the inline math image. The best results are obtained when using graphicx.

\LWR@addbaselinemarker Places a small marker in an SVG inline image. If graphics or graphicx are loaded, the marker is a mostly transparent image. If neither is loaded, no marker is used.

```
\AtBeginDocument{

\ifpdf
    \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
\else
    \ifXeTeX
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.png}
    \else
        \newcommand*{\LWR@baselinename}{lwarp_baseline_marker.eps}
    \fi
\fi

\IfFileExists{\LWR@baselinename}%
{
    \@ifpackageloaded{graphicx}{
        \newcommand*{\LWR@addbaselinemarker}{%
            \LWR@origincludegraphics{\LWR@baselinename}%
        }
    }{
        \@ifpackageloaded{graphics}{
            \newcommand*{\LWR@addbaselinemarker}{%
                \LWR@origincludegraphics{\LWR@baselinename}%
            }
        }{
            \PackageWarningNoLine{lwarp}{Load graphicx or graphics
                for improved SVG math baselines,}
            \newcommand*{\LWR@addbaselinemarker}{}
        }
    }
}{% lwarp_baseline_marker.png or .eps is not present
   \PackageWarningNoLine{lwarp}{File \LWR@baselinename\space is not installed alongside
        the lwarp-*.sty files, so SVG math baselines may not be accurate,}
    \newcommand*{\LWR@addbaselinemarker}{}
}

}% AtBeginDocument
```

\LWR@subsingledollar * {⟨*2: alt text*⟩} {⟨*3: add'l hashing*⟩} {⟨*4: math expression*⟩}

For inline math. Uses MathJax, or for SVG math the image is measured and ajusted to the baseline of the HTML output, and placed inside a `latexmage`.

image filename hashing

If starred, a hashed filename is used.If so, the hash is based on the `alt` tag and also the additional hashing argument.

This may be used to provide an expression with a simple `alt` tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing

argument in order to make the hash unique according to the set of options, even if the simple `alt` tag is still the same.

```
\newlength{\LWR@singledollarwidth}
\newlength{\LWR@singledollarheight}
\newlength{\LWR@singledollardepth}

\newsavebox{\LWR@singledollarbox}

\NewDocumentCommand{\LWR@subsingledollar}{s m m m}{%
\LWR@traceinfo{LWR@subsingledollar}%

\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
{%
\LWR@traceinfo{LWR@subsingledollar: already in a lateximage}%
    #4% contents
}%
{% not in a lateximage
\begingroup%
```

Support for xfakebold:

```
\LWR@applyxfakebold%
```

MathJax cannot parse the often complicated TEX expressions which appear in the various uses of `\ensuredmath`. `\ensuremath` forces the `alt` tag to "`(math image)`", as translated according to `\mathimagename`. If this is the case, force the use of a `lateximage` even if MathJax. Likewise for siunitx if `parse-numbers=false`.

If MathJax, or if formatting math for a word processor, and not `\ensuredmath`, and not a dynamic math expression, print the math expression:

```
\ifboolexpr{%
    (
        bool{mathjax} or
        ( bool{FormatWP} and bool{WPMarkMath} )
    ) and
   ( not test { \ifstrequal {#2} {(\mathimagename)} } ) and % from \ensuredmath
    ( not bool{LWR@dynamicmath} )
}%
```

For MATHJAX, print the math between `\(` and `\)`:

```
{%
    \LWR@traceinfo{LWR@subsingledollar: Mathjax}%
    {\textbackslash(\LWR@HTMLsanitize{#4}\textbackslash)}%
}% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the LATEX code, and a CSS style to control the baseline adjustment.

```
{% not mathjax
\LWR@traceinfo{LWR@subsingledollar: NOT mathjax, or is ensuremath, or is dynamic}%
```

Measure the depth, width, and height of the math image:

```
\begingroup%
```

Temporarily disable formatting while measuring the image parameters:

```
\LWR@restoreorigformatting%
\RenewDocumentEnvironment{lateximage}{s o o o}{}{}% inside group
\LWR@print@normalsize%
```

Temporarily set font for the HTML PDF output:

```
\LWR@traceinfo{Using font family \LWR@f@family}%
\@nameuse{LWR@orig\LWR@f@family family}%
\LWR@traceinfo{Using font series \LWR@f@series}%
\@nameuse{LWR@orig\LWR@f@series series}%
\LWR@traceinfo{Using font shape \LWR@f@shape}%
\@nameuse{LWR@orig\LWR@f@shape shape}%
\LWR@traceinfo{Using font caps shape \LWR@f@shapecaps}%
\@nameuse{LWR@orig\LWR@f@shapecaps shape}%
```

`lateximagedepth` must be nested to avoid generating paragraph tags. $\mathcal{AMS}$ math modifies the `\text` macro such that `\addtocounter` does not always occur as expected. Lower-level code is used instead.

```
\global\advance\c@LWR@lateximagedepth 1\relax%
```

Typeset and save the contents, depending on how they were generated:

SVG math: `\LWR@origensuredmath` is part of argument #4.

SVG math `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

SVG dynamic math: `\LWR@origensuredmath` is part of argument #4.

Mathjax: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`. This case is handled above.

Mathjax `\ensuremath`: `\LWR@origensuredmath` is part of argument #4.

Mathjax dynamic math: Argument #4 is the contents of the math expression without `\LWR@origensuredmath`, so `\LWR@origensuredmath` is added below.

`\ifmmode`: Included "just in case".

```
\ifmmode%
    \global\sbox{\LWR@singledollarbox}{#4}%
\else%
    \ifbool{LWR@dynamicmath}{%
        \ifbool{mathjax}{%
            \global\sbox{\LWR@singledollarbox}{\LWR@origensuredmath{#4}}%
        }{%
            \global\sbox{\LWR@singledollarbox}{#4}%
        }%
```

```
        }{%
            \global\sbox{\LWR@singledollarbox}{#4}%
        }%
    \fi%
```

Add a small and almost transparent marker at the depth of the image.

A math minus sign has the same depth as a plus, even though it does not draw anything below the baseline. This means that *pdfcrop* would crop the image without depth. The marker below the baseline is seen by *pdfcrop* and preserves the depth.

```
    \global\sbox{\LWR@singledollarbox}{%
        \usebox{\LWR@singledollarbox}%
        \raisebox{-\dp\LWR@singledollarbox}{%
            \LWR@addbaselinemarker%
        }%
    }%
```

More low-level code to undo the counter change.

```
    \global\advance\c@LWR@lateximagedepth -1\relax% Due to AmS \text macro.
```

Measure the depth:

```
    \setlength{\LWR@singledollardepth}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
```

Make the length a global change:

```
    \global\LWR@singledollardepth=\LWR@singledollardepth%
```

Likewise for width:

```
    \setlength{\LWR@singledollarwidth}{%
        \LateximageFontScale\wd\LWR@singledollarbox%
    }%
    \global\LWR@singledollarwidth=\LWR@singledollarwidth%
```

Likewise for total height:

```
    \setlength{\LWR@singledollarheight}{%
        \LateximageFontScale\ht\LWR@singledollarbox%
    }%
    \addtolength{\LWR@singledollarheight}{%
        \LateximageFontScale\dp\LWR@singledollarbox%
    }%
    \global\LWR@singledollarheight=\LWR@singledollarheight%

    \endgroup%
```

Set a style for the the height or width. The `em` unit is used so that the math scales according to the user's selected font size.

Start with the greater of the width or the height, biased towards the width:

```
    \ifdimgreater{\LWR@singledollarwidth}{.7\LWR@singledollarheight}{%
        \def\LWR@singledollarstyle{%
            width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
        }%
    }{%
        \def\LWR@singledollarstyle{%
            height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
        }%
    }%
```

If a very narrow width, use the height.

```
    \ifdimless{\LWR@singledollarwidth}{.2em}%
    {%
        \def\LWR@singledollarstyle{%
            height:\LWR@convertto{em}{\the\LWR@singledollarheight} em%
        }%
    }%
    {}%
```

If very wide and short, use the width:

```
    \ifdimless{\LWR@singledollarheight}{.2em}%
    {%
        \def\LWR@singledollarstyle{%
            width:\LWR@convertto{em}{\the\LWR@singledollarwidth} em%
        }%
    }%
    {}%
```

If there is significant text depth, add the depth to the style.

```
    \ifdimgreater{\LWR@singledollardepth}{0.05ex}{%
        \def\LWR@singledollardepthstyle{%
            \ ; % extra space
            \LWR@print@mbox{%
            vertical-align:-\LWR@convertto{em}{\the\LWR@singledollardepth} em%
            } % extra space
        }%
    }{%
        \def\LWR@singledollardepthstyle{}%
    }%
```

Create the `lateximage` using the alternate tag and the computed size and depth. The star causes `lateximage` to use an MD5 hash as the filename. When hashing, also include the current font and color in the hash.

```
    \ifbool{LWR@dynamicmath}{%
        \LWR@traceinfo{subsingledollar: dynamic}%
        \begin{lateximage}% no hashing
            [(\mathimagename)]% alt tag
            []% no add'l hashing
```

```
            [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
    }{%
        \LWR@traceinfo{subsingledollar: static}%
        \IfValueTF{#1}{%
            \LWR@findcurrenttextcolor% sets \LWR@tempcolor
```

Support for xfakebold:

```
            \ifbool{LWR@xfakebold}%
                {\def\LWR@tempone{Y}}%
                {\def\LWR@tempone{N}}%

            \begin{lateximage}*% use hashing
                [#2]% alt
                [% addl' hashing
                    #3%
                    FM\LWR@f@family%
                    SR\LWR@f@series%
                    SH\LWR@f@shape%
                    SHC\LWR@f@shapecaps%
                    CL\LWR@tempcolor%
                    FB\LWR@tempone% xfakebold
                ]%
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
        }{%
            \begin{lateximage}% no hashing
                [#2]% alt
                []% no add'l hashing
                [\LWR@singledollarstyle \LWR@singledollardepthstyle]% CSS
        }%
    }%
```

Place small and almost transparent markers on the baseline at the left and right edges of the image. These markers are seen by *pdfcrop*, and force vertically-centered objects such as a dash to be raised off the baseline in the cropped image, and also force the total width and left / right margins to be correct. (Except that in some fonts a character may exceed the bounding box, and thus may appear wider than expected when converted to an image.)

```
    \LWR@addbaselinemarker%
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Typeset the contents:

```
    \usebox{\LWR@singledollarbox}%
```

The closing baseline marker:

```
    \LWR@addbaselinemarker%
```

```
    \end{lateximage}%
%
}% not mathjax
\endgroup%
}% not in a lateximage
\LWR@traceinfo{LWR@subsingledollar: done}%
}

\LetLtxMacro\LWR@origdollar$
\LetLtxMacro\LWR@secondorigdollar$% balance for editor syntax highlighting

\LetLtxMacro\LWR@origopenparen\(
\LetLtxMacro\LWR@origcloseparen\)
\LetLtxMacro\LWR@origopenbracket\[
\LetLtxMacro\LWR@origclosebracket\]
```

$
$$

Redefine the dollar sign to place math inside a `lateximage`, or use MathJax:

```
\begingroup
\catcode`\$=\active%
\protected\gdef${\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

Used by chemformula to escape single-dollar math:

```
\protected\gdef\LWR@newsingledollar{\@ifnextchar$\LWR@doubledollar\LWR@singledollar}%
```

\LWR@doubledollar

Redefine the double dollar sign to place math inside a `lateximage`, or use MathJax:

```
\protected\gdef\LWR@doubledollar$#1$${%
```

If MathJax or formatting for a word processor, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

For MathJax, print the math between `\[` and `\]`:

```
{

    \textbackslash[%
    \LWR@HTMLsanitize{#1}%
    \textbackslash]

}% mathjax
```

For SVG, print the math inside a `lateximage`, with an `<alt>` tag of the LaTeX code:

```
{% not mathjax
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [%
        \textbackslash{[} % extra space
```

```
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash{]}%
    ]%
```

Support for xfakebold:

```
    \LWR@applyxfakebold%

    \LWR@origdollar\LWR@origdollar#1\LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
}%
```

`\LWR@singledollar` {⟨*alt text*⟩} {⟨*math expression*⟩}

```
\protected\gdef\LWR@singledollar#1${%
\ifbool{mathjax}{%
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {#1}% contents
}{% not mathjax
    \LWR@subsingledollar*%
    {% alt tag
        \textbackslash( %
        \LWR@HTMLsanitize{#1} % extra space
        \textbackslash)%
    }%
    {singledollar}% add'l hashing
    {\LWR@origensuredmath{#1}}% contents
}% not mathjax
}
```

`\(` `\[` Redefine to the above dollar macros.

```
\AtBeginDocument{
\protected\gdef\(#1\){$#1$}
\protected\gdef\[#1\]{$$#1$$}
}

\endgroup

\AtBeginDocument{
\LetLtxMacro\LWR@openbracketnormal\[
\LetLtxMacro\LWR@closebracketnormal\]
}
```

`\@ensuredmath` {⟨*expression*⟩}

If MathJax, a lateximage is used, since \ensuremath is often used for complex TEX expressions which MathJax may not render. If SVG math, a hashed file is used with a simple alt tag, but additional hashing provided by the contents.

```
\LetLtxMacro\LWR@origensuredmath\@ensuredmath

\renewcommand{\@ensuredmath}[1]{%
\ifbool{mathjax}{%
    \LWR@subsingledollar*{(\mathimagename)}{%
           \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{\relax%
        \LWR@origensuredmath{#1}%
    }%
}{% SVG math
```

If already inside a lateximage in math mode, continue as-is.

```
\ifmmode%
    \LWR@origensuredmath{#1}%
\else%
```

Create an inline math lateximage with a simple alt tag and additional hashing according to the contents.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
    {\LWR@origensuredmath{#1}}%
    {%
        \LWR@subsingledollar*{(\mathimagename)}{%
           \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
        }{%
            \LWR@origensuredmath{#1}%
        }%
    }%
\fi%
}%
}
```

Remove the old math and displaymath environments:

```
\let\math\relax
\let\endmath\relax
\let\displaymath\relax
\let\enddisplaymath\relax
```

Env math Set math mode then typeset the body of what was between the begin/end. See the environ package for \BODY.

```
\NewEnviron{math}{\expandafter\(\BODY\)}
```

Env LWR@displaymathnormal Set math mode then typeset the body of what was between the begin/end. See the environ package for \BODY.

```
\NewEnviron{LWR@displaymathnormal}{\expandafter\[\BODY\]\@ignoretrue}
```

Set the default displaymath to the normal version:

```
\LetLtxMacro\[\LWR@openbracketnormal%
\LetLtxMacro\]\LWR@closebracketnormal%
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
```

Env LWR@displaymathother A version of displaymath which can handle complicated objects, but does not supply MathJax or HTML alt tags.

```
\newenvironment{LWR@displaymathother}
{%
    \begin{BlockClass}{displaymath}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [(display math)]%
    \LWR@origdollar\LWR@origdollar%
}
{%
    \LWR@origdollar\LWR@origdollar%
    \end{lateximage}%
    \end{BlockClass}%
}
```

Env LWR@equationother A version of displaymath which can handle complicated objects, but does not supply MathJax or HTML alt tags.

```
\newenvironment{LWR@equationother}
{%
    \begin{BlockClass}{displaymathnumbered}%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}%
    [(display math)]%
    \LWR@origequation%
}
{%
    \LWR@origendequation%
    \end{lateximage}%
    \end{BlockClass}%
}
```

79.4 MathJax support

Ctr LWR@nextequation Used to add one to compute the next equation number.

```
\newcounter{LWR@nextequation}
```

\LWR@syncmathjax Sets the MathJax equation format and number for the following equations.

These MathJax commands are printed inside "\(" and "\)" characters. They are printed to HTML output, not interpreted by LaTeX.

```
\newcommand*{\LWR@syncmathjax}{%
```

If using chapters, place the chapter number in front of the equation. Otherwise, use the simple equation number.

```
\ifcsdef{thechapter}{
    \InlineClass{hidden}{
        \textbackslash(
        \textbackslash{}seteqsection \{\thechapter\}
        \textbackslash)
    }
}
{}% not using chapters
```

MathJax doesn't allow setting the equation number to 1:

```
\ifthenelse{\cnttest{\value{equation}}>0}
{
```

Tell MathJax that the next set of equations begins with the current LaTeX equation number, plus one.

```
    \setcounter{LWR@nextequation}{\value{equation}}
    \addtocounter{LWR@nextequation}{1}
```

Place the MathJax command inside "\(" and "\)" characters, to be printed to HTML, not interpreted by LaTeX.

```
    \InlineClass{hidden}{
        \textbackslash(
        \textbackslash{}seteqnumber \{\arabic{LWR@nextequation}\}
        \textbackslash)
    }
}{}% not eq > 0
}
```

`\LWR@hidelatexequation` {⟨*environment*⟩} {⟨*contents*⟩}

Creates the LaTeX version of the equation inside an HTML comment.

```
\NewDocumentCommand{\LWR@hidelatexequation}{m +m}{%
```

Stop HTML paragraph handling and open an HTML comment:

```
\LWR@stoppars
\LWR@htmlopencomment
```

Start the LaTeX math environment inside the HTML comment:

```
\begingroup
\@nameuse{LWR@orig#1}
```

While in the math environment, restore various commands to their LaTeX meanings.

```
\LWR@restoreorigformatting
```

See `\LWR@htmlmathlabel` in section 79.7.1.

Print the contents of the equation:

```
#2
```

End the LaTeX math environment inside the HTML comment:

```
\@nameuse{LWR@origend#1}
\endgroup

```

Close the HTML comment and resume HTML paragraph handling:

```
\LWR@htmlclosecomment
\LWR@startpars
}
```

`\LWR@addmathjax` {⟨*environment*⟩} {⟨*contents*⟩}

Given the name of a math environment and its contents, create a MathJax instance. The contents are printed to HTML output, not interpreted by LaTeX.

```
\NewDocumentCommand{\LWR@addmathjax}{m +m}{%
```

Enclose the MathJax environment inside printed "`\(`" and "`\)`" characters.

```
\LWR@origtilde\LWR@orignewline
\textbackslash{}begin\{#1\}
```

Print the contents, sanitizing for HTML special characters.

```
\LWR@HTMLsanitizeexpand{\detokenize\expandafter{#2}}
```

Close the MathJax environment:

```
\textbackslash{}end\{#1\}
\LWR@orignewline
}
```

79.5 Equation environment

Remember existing `equation` environment, after redefined by amsmath, if loaded.

```
\AtBeginDocument{
\let\LWR@origequation\equation
\let\LWR@origendequation\endequation
\csletcs{LWR@origequation*}{equation*}
\csletcs{LWR@origendequation*}{endequation*}
}
```

`\LWR@doequation` {⟨*env contents*⟩} {⟨*env name*⟩}

For SVG math output, the contents are typeset using the original `equation` inside a `lateximage`, along with an `<alt>` tag containing a detokenized copy of the LaTeX source for the math.

For MathJax output, the contents are typeset in an original `equation` environment placed inside a HTML comment, with special processing for `\label`s. The contents are also printed to the HTML output for processing by the MathJax script.

```
\newcommand*{\LWR@doequation}[2]{%
```

If `mathjax` or `FormatWP`, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
```

MathJax output:

```
{
```

Print commands to syncronize MathJax's equation number and format to the current LaTeX chapter/section and equation number:

```
    \LWR@syncmathjax
```

Print the LaTeX math inside an HTML comment:

```
    \LWR@hidelatexequation{#2}{#1}
}
```

SVG output: Create the `lateximage` along with an HTML `<alt>` tag having an equation number, the LaTeX equation environment commmands, and the contents of the environment's `\BODY`.

```
{% not mathjax
```

Begin the `lateximage` with an `<alt>` tag containing the math source:

```
    \ifstrequal{#2}{equation*}{%
        \begin{BlockClass}{displaymath}%
    }{%
        \begin{BlockClass}{displaymathnumbered}%
    }%
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
```

```
    \begin{lateximage}[%
        \ifstrequal{#2}{equation*}{%
            \ifdefequal{\LWR@equationtag}{\theequation}{%
% no tag was given
            }{%
                (\LWR@equationtag) % tag was given
            }%
        }{%
            (\LWR@equationtag) % automatic numbering
        }%
        \textbackslash{begin\{#2\}} % extra space
        \LWR@HTMLsanitizeexpand{\detokenize\expandafter{#1}} % extra space
        \textbackslash{end\{#2\}}%
    ]% alt tag
```

Support for xfakebold:

```
    \LWR@applyxfakebold%
```

Create the actual LaTeX-formatted equation inside the lateximage using the contents of the environment.

```
    \@nameuse{LWR@orig#2}%
    #1% contents collected by \collect@body
    \@nameuse{LWR@origend#2}%
    \end{lateximage}%
    \end{BlockClass}%
}% not mathjax
}
```

After the environment, if MathJax, print the math to the HTML output for MathJax processing:

```
\newcommand*{\LWR@doendequation}[1]{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {%
        \LWR@addmathjax{#1}{\BODY}%
    }{}%

}
```

Remove existing equation environment:

```
\AtBeginDocument{
\let\equation\relax
\let\endequation\relax
\csletcs{equation*}{relax}
\csletcs{endequation*}{relax}
}
```

Env equation The new equation environment is created with \NewEnviron (from the environ package), which stores the contents of its environment in a macro called \BODY.

```
\AtBeginDocument{
\NewEnviron{equation}%
{\LWR@doequation{\BODY}{equation}}%
[\LWR@doendequation{equation}]

\LetLtxMacro\LWR@equationnormal\equation
\LetLtxMacro\endLWR@equationnormal\endequation
}
```

Env equation*

```
\AtBeginDocument{
\NewEnviron{equation*}%
{\LWR@doequation{\BODY}{equation*}}%
[\LWR@doendequation{equation*}]

\csletcs{LWR@equationnormalstar}{equation*}
\csletcs{LWR@endequationnormalstar}{endequation*}
}
```

Remember the "less" version of equation, which uses MathJax and alt tags, but does not support complicated contents such as some Ti*k*z expressions.

```
\AtBeginDocument{
\LetLtxMacro\LWR@equationless\equation
\LetLtxMacro\endLWR@equationless\endequation
\csletcs{LWR@equationlessstar}{equation*}
\csletcs{LWR@endequationlessstar}{endequation*}
}
```

79.6 \displaymathnormal and \displaymathother

\displaymathnormal

By default, or when selecting \displaymathnormal, MathJax math display environments print their contents as text into HTML, and SVG display math environments render their contents as SVG images and use their contents as the alt tag of HTML output. To do so, the contents are loaded into a macro for reuse. In some cases, such as complicated Ti*k*z pictures, compilation will fail.

\displaymathother
MathJax unsupported complicated alt tag

When selecting \displaymathother, it is assumed that the contents are more complicated than "pure" math. An example is an elaborate Ti*k*z picture, which will not render in MathJax and will not make sense as an HTML alt tag. In this mode, MathJax is turned off, math display environments become SVG images, even if MathJax is selected, and the HTML alt tags become simple messages. The contents are internally processed as an environment instead of a macro argument, so complicated objects such as Ti*k*z pictures are more likely to compile successfully.

\displaymathnormal
simple math objects

Use when display math environments have simple math which is to sent to MathJax or included in HTML alt tags.

```
\newcommand*{\displaymathnormal}{%
```

```
\ifbool{LWR@origmathjax}{\booltrue{mathjax}}{\boolfalse{mathjax}}%
\LetLtxMacro\[\LWR@openbracketnormal%
\LetLtxMacro\]\LWR@closebracketnormal%
\LetLtxMacro\displaymath\LWR@displaymathnormal%
\LetLtxMacro\enddisplaymath\endLWR@displaymathnormal%
\LetLtxMacro\equation\LWR@equationnormal%
\LetLtxMacro\endequation\endLWR@equationnormal%
\csletcs{equation*}{LWR@equationnormalstar}%
\csletcs{endequation*}{LWR@endequationnormalstar}%
}
```

`\displaymathother`
complicated math objects

Use when display math environments have complicated objects which will not work with MathJax or should not be included in HTML `alt` tags. Complicated contents are more likely to compile correctly.

```
\newcommand*{\displaymathother}{%
\boolfalse{mathjax}%
\LetLtxMacro\displaymath\LWR@displaymathother%
\LetLtxMacro\enddisplaymath\endLWR@displaymathother%
\LetLtxMacro\[\LWR@displaymathother%
\LetLtxMacro\]\endLWR@displaymathother%
\LetLtxMacro\equation\LWR@equationother%
\LetLtxMacro\endequation\endLWR@equationother%
\csletcs{equation*}{displaymath}%
\csletcs{endequation*}{enddisplaymath}%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Print-mode versions:

```
\newcommand*{\displaymathnormal}{}
\newcommand*{\displaymathother}{}
```

```
\end{warpprint}
```

for HTML output:

```
\begin{warpHTML}
```

79.7 AMS Math environments

79.7.1 Support macros

Bool `LWR@amsmultline`

True if processing a multline environment.

To compensate for `multline`-spefific code, `LWR@amsmultline` is used to add extra horizontal space in `\LWR@htmlmathlabel` if is used in an amsmath environment which is not a `multline` environment and not an `equation`.

```
\newbool{LWR@amsmultline}
\boolfalse{LWR@amsmultline}
```

`\LWR@htmlmathlabel` {⟨*label*⟩}

lwarp points `\ltx@label` here. This is used by `\label` when inside a LaTeX AMS math environment's math display environment.

`\LWR@origltx@label` points to the LaTeX original, modified by lwarp, then by amsmath, then by cleveref.

```
\newcommand*{\LWR@htmlmathlabel}[1]{%
\LWR@traceinfo{LWR@htmlmathlabelb #1}%
```

If `mathjax` or `FormatWP`, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{%
```

The combined LaTeX & HTML label is printed in a `\text` field:

```
    \text{%
```

Shift the label over to the right side of the environment to avoid over-printing the math:

```
    \ifbool{LWR@amsmultline}{}{\hspace*{\totwidth@}}%
```

Temporarily end the HTML comment, insert the LaTeX & HTML label, then resume the HTML comment. `\@firstofone` is required to remove extra braces introduced by the amsmath package.)

```
    \LWR@htmlclosecomment%
    \LWR@origltx@label{#1}%
    \LWR@htmlopencomment%
    }% text
}% mathjax
{%
    \LWR@origltx@label{#1}%
}%
}
```

`\LWR@beginhideamsmath` Starts hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@beginhideamsmath}{
\LWR@stoppars
\LWR@origtilde\LWR@orignewline
\LWR@htmlopencomment

\begingroup
\LWR@restoreorigformatting
}
```

\LWR@endhideamsmath Ends hiding LaTeX math inside an HTML comment.

```
\newcommand*{\LWR@endhideamsmath}{
\endgroup

\LWR@htmlclosecomment
\LWR@orignewline
\LWR@startpars
}
```

79.7.2 Environment patches

The amsmath environments already collect their contents in \@envbody for further processing. eqnarray is not an $\mathcal{AMS}$ package, and thus requires special handling.

For SVG math: Each envrionment is encapsulated inside a lateximage environment, along with a special optional argument of \LWR@amsmathbody or \LWR@amsmathbodynumbered telling lateximage to use as the HTML <alt> tag the environment's contents which were automatically captured by the $\mathcal{AMS}$ environment.

For MathJax: Each environment is syched with LaTeX's equation numbers, typeset with LaTeX inside an HTML comment, then printed to HTML output for MathJax to process.

Env eqnarray This environmnet is not an $\mathcal{AMS}$ environment and thus its body is not automatically captured, so the environ package is used to capture the environment into \BODY.

```
\let\LWR@origeqnarray\eqnarray
\let\LWR@origendeqnarray\endeqnarray
```

To remember whether the starred environment was used, and thus whether to number the equations:

```
\newbool{LWR@numbereqnarray}
\booltrue{LWR@numbereqnarray}
```

Common code used by eqnarray and Beqnarray (from fancybox):

```
\newcommand{\LWR@eqnarrayfactor}{%
```

If mathjax or FormatWP, print the LaTeX expression:

```
\ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
{%
```

If MathJax, the environment contents (the \BODY) are executed in a HTML comment to trigger the correct equation number increment (if not starred), then are included verbatim in the output for MathJax to interpret:

```
    \LWR@syncmathjax
    \boolfalse{LWR@amsmultline}
```

```
    \ifbool{LWR@numbereqnarray}
    {
```

If numbering the equations, execute a copy inside an HTML comment block:

```
        \LWR@beginhideamsmath
        \LWR@origeqnarray
        \BODY
        \LWR@origendeqnarray
        \LWR@endhideamsmath
```

Then print the (sanitized) contents to the output for MathJax to interpret:

```
        \LWR@addmathjax{eqnarray}{\BODY}
    }%
    {% not LWR@numbereqnarray
```

If not numbering equations, just create the contents for MathJax:

```
    \LWR@addmathjax{eqnarray*}{\BODY}
    }% LWR@numbereqnarray
}% mathjax
{% not mathjax
    \ifbool{LWR@numbereqnarray}
    {
```

For numbered SVG equations, first create a `lateximage` with an `alt` attribute containing sanitized copy of the source code:

```
        \begin{BlockClass}{displaymathnumbered}%
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
        \begin{lateximage}[(\LWR@startingequationtag--\LWR@equationtag)
            \LWR@addmathjax{eqnarray}{\BODY}]
```

Support for xfakebold:

```
        \LWR@applyxfakebold%
```

Create the image contents using an actual `eqnarray`:

```
        \LWR@origeqnarray
        \BODY
        \LWR@origendeqnarray
        \end{lateximage}
        \end{BlockClass}
    }%
    {% not LWR@numbereqnarray
```

If not numbered, do the same, but an extra `\nonumber` seems to be required:

```
        \begin{BlockClass}{displaymath}
        \LWR@newautoidanchor%
        \booltrue{LWR@indisplaymathimage}%
```

```
        \begin{lateximage}[\LWR@addmathjax{eqnarray*}{\BODY}]
```

Support for xfakebold:

```
        \LWR@applyxfakebold%

        \LWR@origeqnarray
        \BODY
        \nonumber
        \LWR@origendeqnarray
        \end{lateximage}
        \end{BlockClass}
    }% LWR@numbereqnarray
}% not mathjax
```

Default to number equations in the future:

```
\booltrue{LWR@numbereqnarray}
}
```

eqnarray itself is made with a blank line before and after to force it to be on its own line:

```
\RenewEnviron{eqnarray}
{%

\LWR@eqnarrayfactor

}
```

The starred version is patched to turn off the numbering:

```
\csgpreto{eqnarray*}{\boolfalse{LWR@numbereqnarray}}

\end{warpHTML}
```

80 Lateximages

80.1 Description

Env lateximage

A lateximage is a piece of the document which is typeset in LaTeX then included in the HTML output as an image. This is used for math if SVG math is chosen, and also for the picture, tikzpicture, and other environments.

Before typesetting the lateximage a large number of formatting, graphics, and symbols-related macros are temporarily restored to their print-mode meaning by \LWR@restoreorigformatting. (See section 78.)

A lateximage is typeset on its own PDF page inside an HTML comment which starts on the preceeding page and ends on following page, and instructions are written

to `lateximage.txt` for *lwarpmk* to extract the `lateximage` from the page of the PDF file then generate an accompanying `.svg` file image file. Meanwhile, instructions to show this image are placed into the HTML file after the comment.

An HTML `<span>` is created to hold both the HTML comment, which will have the *pdftotext* conversion, and also the link to the final `.svg` image.

A LaTeX label is used to remember which PDF page has the image. A label is used because footnotes, endnotes, and pagenotes may cause the image to appear at a later time. The label is declared along with the image, and so it correctly remembers where the image finally ended up.

html `alt` tag

The HTML `alt` tag is set to the LaTeX source for SVG math, some chemistry expressions, and perhaps some other expressions which make sense for text copy/paste. In some other cases, the `alt` tag is set according to the package name.

When creating an SVG math image, its `alt` tag may be set to the math expression, which may be hashed for image reuse. In the case of `\ensuremath` or after `\inlinemathother`, where the contents require a unique image for each instance of the same expression, the `alt` tag is set to `\mathimagename`, and the image is not reused.

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "math image", and it may be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following SVG math images.

For many packages, the output is placed inside a `lateximage` with an HTML `alt` tag set to the package name followed by `\packagediagramname`. For example:

```
(-xy- diagram)
```

This expression is visible in the browser if images are not loaded, and appears when the text is copied and pasted. The default is "diagram", and may it be changed according to the document's language. This may be set in the preamble, or changed as necessary inside the document, where it will affect the following `lateximages`.

SVG image font size

For the `lateximage` environment, the size of the math and text used in the SVG image may be adjusted by setting `\LateximageFontSizeName` to a font size name — *without the backslash*, which defaults to:

```
\renewcommand{\LateximageFontSizeName}{normalsize}
```

For inline SVG math, font size is instead controlled by `\LateximageFontScale`, which defaults to:

```
\newcommand*{\LateximageFontScale}{.75}
```

80.2 Support counters and macros

for HTML output: 10032 `\begin{warpHTML}`

Ctr LWR@lateximagenumber Sequence the images.

```
\newcounter{LWR@lateximagenumber}
\setcounter{LWR@lateximagenumber}{0}
```

Ctr LWR@lateximagedepth Do not create \lateximage inside of \lateximage.

```
\newcounter{LWR@lateximagedepth}
\setcounter{LWR@lateximagedepth}{0}
```

A few utility macros to write special characters:

```
\edef\LWR@hashmark{\string#} % for use in \write
\edef\LWR@percent{\@percentchar} % for use in \write
```

Ctr LWR@LIpage Used to reference the PDF page number of a lateximage to be written into <project>-images.txt.

```
\newcounter{LWR@LIpage}
```

```
\end{warpHTML}
```

80.3 Font size

for HTML & PRINT:

```
\begin{warpall}
```

\LateximageFontSizeName Declares how large to write text in \lateximages. The .svg file text size should blend well with the surrounding HTML text size.

⚠ no backslash *Do not include the leading backslash in the name.*

```
\newcommand*{\LateximageFontSizeName}{normalsize}
```

\LateximageFontScale Declares how large to scale inline SVG math images. The .svg file text size should blend well with the surrounding HTML text size. The default is .75, but it may be redefined as needed depending on the HTML font.

```
\newcommand*{\LateximageFontScale}{.75}
```

```
\end{warpall}
```

80.4 Sanitizing math expressions for HTML

for HTML output:

```
\begin{warpHTML}
```

\LWR@HTMLsanitize {⟨*text*⟩}

Math expressions are converted to `lateximages`, and some math environments may contain &, <, or >, which should not be allowed inside an HTML <alt> tag, so must convert them to HTML entities.

Two versions follow, depending on expansion needs. There may be a better way…

```
\newrobustcmd{\LWR@HTMLsanitize}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
\begingroup%
\LWR@FBcancel%
\fullexpandarg%
```

The &, <, and > may be interpreted by the browser:

```
\protect\StrSubstitute{\detokenize{#1}}%
{\detokenize{&}}{\detokenize{&amp;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{<}}{\detokenize{&lt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{>}}{\detokenize{&gt;}}[\LWR@strresult]%
```

The double quote occasionally causes problems.

```
\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{"}}{\detokenize{&quot;}}[\LWR@strresult]%
```

MathJax allows expressions to be defined with `\newcommand`. These expressions would appear with ## for each argument, and each must be changed to a single #. This must be done after all the above changes. Attempting another conversion after this causes an error upon further expansion.

```
\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{##}}{\LWR@origpound}[\LWR@strresult]%

\LWR@strresult%
\endgroup%
}
```

`\LWR@HTMLsanitizeexpand` {⟨*text*⟩}

This version expands the argument before sanitizing it.

```
\newrobustcmd{\LWR@HTMLsanitizeexpand}[1]{%
```

Cancel French babel character handling, and fully expand the strings:

```
\begingroup%
\LWR@FBcancel%
\fullexpandarg%
```

The difference between this and \LWR@HTMLsanitize (without “expand”) is the following \expandafter:

```
\protect\StrSubstitute{\detokenize\expandafter{#1}}%
{\detokenize{&}}{\detokenize{&amp;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{<}}{\detokenize{&lt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{>}}{\detokenize{&gt;}}[\LWR@strresult]%

\protect\StrSubstitute{\detokenize\expandafter{\LWR@strresult}}%
{\detokenize{"}}{\detokenize{&quot;}}[\LWR@strresult]%
```

\LWR@HTMLsanitizeexpand is not used for defining new MathJax macros, so the ## conversion is not needed here.

```
\LWR@strresult%
\endgroup%
}
```

80.5 Equation numbers

Ctr LWR@startingequation

For use with lateximage and multi-line numbered equations. Remembers the next equation number so that it may be printed in the alt tag.

```
\newcounter{LWR@startingequation}

\@ifundefined{chapter}
{
\renewcommand{\theLWR@startingequation}{%
\arabic{LWR@startingequation}%
}
}
{% chapter defined
\renewcommand{\theLWR@startingequation}{%
\ifnumcomp{\value{chapter}}{>}{0}{\arabic{chapter}.}{}%
\arabic{LWR@startingequation}%
}
}
```

Bool LWR@isstartingequation

True for the first equation tag, false for later tags in the same environment.

```
\newbool{LWR@isstartingequation}
```

\LWR@startingequationtag

Prints the starting equation number or tag.

```
\let\LWR@startingequationtag\theLWR@startingequation
```

\LWR@equationtag Prints the ending equation number or tag.

This is reset by lateximage, may be temporarily overwritten by \tag calling \LWR@remembertag.

```
\newcommand*{\LWR@equationtag}{}
```

Only if SVG math, patch \tag after packages have loaded, in case someone else modified \tag.

```
\AtBeginDocument{

\ifbool{mathjax}{}{% not mathjax
```

\LWR@remembertag {⟨*tag*⟩}

For use inside the math environments while using SVG math. Sets \theLWR@startingequation and \theequation to the given tag.

```
\NewDocumentCommand{\LWR@remembertag}{m}{%
\ifbool{LWR@isstartingequation}%
{%
    \global\boolfalse{LWR@isstartingequation}%
    \xdef\LWR@startingequationtag{#1}%
}{}%
\xdef\LWR@equationtag{#1}%
}%

}% not mathjax
}% AtBeginDocument
```

80.6 HTML alt tags

\LWR@amsmathbody {⟨*envname*⟩} For use inside the optional argument to a lateximage to add the contents of a AMS math environment to the <alt> tag.

```
\newcommand*{\LWR@amsmathbody}[1]
{%
\textbackslash\{begin\}\{#1\} % extra space
\LWR@HTMLsanitizeexpand{\detokenize\expandafter{\the\@envbody}}%
\textbackslash\{end\}\{#1\}%
}
```

\LWR@amsmathbodynumbered {⟨*envname*⟩} For use inside the optional argument to a lateximage to add the contents of a AMS math environment to the alt tag, prefixed by the equation numbers.

```
\newcommand*{\LWR@amsmathbodynumbered}[1]
{%
\ifnumcomp{\value{LWR@startingequation}}{=}{\value{equation}}%
```

```
{(\LWR@equationtag)}%
{(\LWR@startingequationtag--\LWR@equationtag)} % extra space
\LWR@amsmathbody{#1} % extra space
}
```

80.7 lateximage environment

Env lateximage * [⟨*2:* <alt> *tag*⟩] [⟨*3: add'l hashing*⟩] [⟨*4: css style*⟩]

Typesets the contents and then renders the result as an SVG file. Star causes the image to be hashed for reuse.

The optional <alt> tag is included in the HTML code for use with copy/paste.

image filename hashing If starred, a hashed filename is used.If so, the hash is based on the alt tag and also the additional hashing argument.

This may be used to provide an expression with a simple alt tag but also enough additional information to provide a unique hash.

An example is when the expression is a complicated TEX expression, which would not copy/paste well. A simplified tag may be used, while the complicated expression is duplicated in the additional hashing argument.

Another example is when the expression is simple, but the image depends on options. These options may be decoded into text form and included in the additional hashing argument in order to make the hash unique according to the set of options, even if the simple alt tag is still the same.

File *_html.aux A new label is placed into the file *_html.aux:

```
\newlabel{LWRlateximage-<BaseJobname>-<number>}{{<x>}{<y>}}
```

This is used to find the image in the PDF file, according to its name.

File *-images.txt A list of images to generate is created in <jobname>-images.txt. Each line has three pipe-delimited fields, containing the PDF page number from <jobname>_html.pdf, where the image is located, a boolean indicating whether the image is hashed, and the filename of the image. The last line has "end" in each field, and is used to detect an incomplete compile.

```
\catcode`\$=\active%

\NewDocumentEnvironment{lateximage}{s O{(image)} O{} O{}}
{%
\LWR@traceinfo{lateximage: starting on \jobname.pdf page \arabic{page}}%
\LWR@traceinfo{lateximage: entering depth is \arabic{LWR@lateximagedepth}}%
```

Nested lateximages remain one large lateximage:

```
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
```

If nesting inside an already-existing lateximage, simply record one more level. $\mathcal{AMS}$ packages redefine \addtocounter to do nothing if inside a \text, so lower-level TEX macros are used for tracking nested lateximages.

```
{%
%     \addtocounter{LWR@lateximagedepth}{1}%
    \global\advance\c@LWR@lateximagedepth 1\relax% Due to AmS \text macro.
}%
```

Otherwise, this is the outer-most lateximage:

```
{% start of outer-most lateximage
```

Remember the next equation number to be allocated, in case it must be printed in a multi-equation environment:

```
\LWR@traceinfo{lateximage: starting outer-most lateximage}%
    \setcounter{LWR@startingequation}{\value{equation}}%
    \addtocounter{LWR@startingequation}{1}%
    \booltrue{LWR@isstartingequation}%
    \let\LWR@startingequationtag\theLWR@startingequation%
```

The default equation tag, unless overwritten by \tag:

```
    \let\LWR@equationtag\theequation%
```

Starting a new lateximage:

```
    \addtocounter{LWR@lateximagenumber}{1}%
   \LWR@traceinfo{lateximage: LWR@lateximagenumber is \arabic{LWR@lateximagenumber}}%
```

While inside a lateximage, locally do not use mathjax:

```
    \boolfalse{mathjax}%
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Next file:

```
    \addtocounter{LWR@externalfilecnt}{1}%
   \LWR@traceinfo{lateximage: LWR@externalfilecnt is \arabic{LWR@externalfilecnt}}%
```

Figure out what the next page number will be. \setcounterpageref assigns LWR@LIpage to the page number for the reference LWRlateximage-BaseJobname-XXX:

```
    \setcounterpageref{LWR@LIpage}{%
        LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}%
    }%
    \LWR@traceinfo{lateximage: LWR@LIpage is \arabic{LWR@LIpage}}%
```

Create an HTML span which will hold the comment which contains the *pdftotext* translation of the image's page, and also will hold the link to the .svg file:

```
\LWR@htmltag{span\LWR@indentHTML%
 id="lateximage-\BaseJobname-\arabic{LWR@lateximagenumber}"\LWR@indentHTML
    class="lateximagesource"\LWR@orignewline
}%
```

Write instructions to the <ImagesDirectory>.txt file:

```
\LWR@traceinfo{lateximage: about to write to \BaseJobname-images.txt}%
\IfBooleanTF{#1}% starred
{% hash
    \LWR@traceinfo{lateximage: hash true, adding %
        !\detokenize\expandafter{#2}!\detokenize\expandafter{#3}!}%
```

Compute and save the hashed file name for later use:

```
    \edef\LWR@hashedname{%
        \LWR@mdfive{\detokenize\expandafter{#2}-!-#3}%
    }%
    \LWR@traceinfo{lateximage: hash is \LWR@hashedname}%
```

Write the page, hashing, and hashed name:

```
    \immediate\write\LWR@lateximagesfile{%
        |\arabic{LWR@LIpage}|true|\LWR@hashedname|%
    }%
}% hash
{% no hash
```

No hash, so write the page, no hashing, and the image number:

```
    \LWR@traceinfo{lateximage: hash false}%
    \immediate\write\LWR@lateximagesfile{%
    |\arabic{LWR@LIpage}|false|\LWR@ImagesName\arabic{LWR@externalfilecnt}|%
    }%
}% no hash
```

Place an open comment tag. This will hide any traces of the lateximage PDF page which were picked up by *pdftotext*.

```
\LWR@traceinfo{lateximage: about to create open comment}%
\LWR@htmlopencomment%
```

One level deeper. At this outer-most lateximage, it is known that this is not being used inside an $\mathcal{AMS}$ \text, since the outer-most level will never be in math mode.

```
 \addtocounter{LWR@lateximagedepth}{1}%
```

Start the new PDF page:

```
\LWR@traceinfo{lateximage: about to create a new page}%
\LWR@orignewpage%
```

Typeset the image in a “standard” width page and font size:

```
    \LWR@traceinfo{lateximage: about to create minipage}%
    \LWR@print@minipage{6in}%
    \@nameuse{LWR@print@\LateximageFontSizeName}%
```

Temporarily restore formatting to its PDF definitions: Do not produce HTML tags for \hspace, etc. inside a lateximage.

```
    \LWR@traceinfo{lateximage: about to temporarily restore formatting}%
    \LWR@restoreorigformatting%
```

Use full-page footnotes instead of minipage footnotes. These become HTML footnotes.

```
    \def\@mpfn{footnote}%
    \def\thempfn{\thefootnote}%
    \LetLtxMacro\@footnotetext\LWR@footnotetext%
```

Create the LWRlateximage<number> label:

```
    \LWR@traceinfo{lateximage: about to create label}%
    \LWR@orig@label{LWRlateximage-\BaseJobname-\arabic{LWR@lateximagenumber}}%
    \LWR@traceinfo{lateximage: finished creating the label}%
```

Enable print-mode math functions:

```
    \LetLtxMacro$\LWR@origdollar%
    \catcode`\$=3% math shift
    \LetLtxMacro\(\LWR@origopenparen%
    \LetLtxMacro\)\LWR@origcloseparen%
```

Only enable print-mode display math if are not already inside display math:

```
    \ifbool{LWR@indisplaymathimage}{}{% not in display math
        \LetLtxMacro\[\LWR@origopenbracket%
        \LetLtxMacro\]\LWR@origclosebracket%
        \let\equation\LWR@origequation%
        \let\endequation\LWR@origendequation%
        \csletcs{equation*}{LWR@origequation*}%
        \csletcs{endequation*}{LWR@origendequation*}%
    }% not in display math
```

For chemformula:

```
    \LetLtxMacro\LWR@newsingledollar$%
    \LetLtxMacro\LWR@newsingledollar$% syntax highlighting

}% end of outer-most lateximage
\LWR@traceinfo{lateximage: finished start of environment}%
}% end of \begin{lateximage}
```

\endlateximage When the environment closes:

```
{% start of \end{lateximage}
\LWR@traceinfo{lateximage: starting end of lateximage}%
```

Nested more than one deep?

```
\LWR@traceinfo{lateximage: internal depth was \arabic{LWR@lateximagedepth}}%
\ifnumcomp{\value{LWR@lateximagedepth}}{>}{1}%
```

If nesting inside an already existing lateximage, simply record one less level. Uses a lower-level TEX macro due to $\mathcal{AMS}$ `\text` change of `\addtocounter`.

```
{%
    \LWR@traceinfo{lateximage: unnesting}%
    \global\advance\c@LWR@lateximagedepth -1\relax%
}%
```

If this is the outer-most lateximage:

```
{% end of outer-most lateximage
```

Finish the lateximage minipage and start a new PDF page:

```
\LWR@traceinfo{lateximage: ending outer-most lateximage}%
    \endLWR@print@minipage%
    \LWR@orignewpage%
```

Close the HTML comment which encapsulated any traces of the lateximage picked up by *pdftotext*:

```
    \LWR@print@vspace*{.5\baselineskip}%
    \LWR@htmlclosecomment%
    \LWR@traceinfo{lateximage: The page after the image is \arabic{page}}%
```

Create a link to the lateximage, allowing its natural height:

```
    \IfBooleanTF{#1}% starred
    {% hash
        \LWR@subinlineimage[#2]{lateximage}%
        {%
            \LWR@ImagesDirectory\OSPathSymbol%
            \LWR@print@mbox{\LWR@hashedname}%
        }{svg}{#4}%
    }% hash
    {% no hash
        \LWR@subinlineimage[#2]{lateximage}%
        {%
            \LWR@ImagesDirectory\OSPathSymbol%
            \LWR@print@mbox{\LWR@ImagesName\theLWR@externalfilecnt}%
        }{svg}{#4}%
    }% no hash
```

Be sure that are doing a paragraph:

```
    \LWR@ensuredoingapar%
```

Close the HTML span which has the *pdftotext* comment and also the link to the .svg image:

```
    \LWR@htmltag{/span}%
    \ifbool{HTMLDebugComments}{%
        \LWR@htmlcomment{End of lateximage}%
    }{}%
```

Undo one lateximage level. This is not inside an $\mathcal{AMS}$ \text, so regular \addtocounter may be used here.

```
    \addtocounter{LWR@lateximagedepth}{-1}%
}% end of outer-most lateximage
\LWR@traceinfo{lateximage: exiting depth is \arabic{LWR@lateximagedepth}}%
\LWR@traceinfo{lateximage: done}%
}%
\catcode`\$=3% math shift
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

Env lateximage [⟨<alt> *tag*⟩] [⟨*css style*⟩]

varwidth is used to create a box of the natural width of its contents.

```
\NewDocumentEnvironment{lateximage}{s o o o}
    {\begin{varwidth}[b]{\linewidth}}
    {\end{varwidth}}
```

```
\end{warpprint}
```

81 center, flushleft, flushright

for HTML output:

```
\begin{warpHTML}
```

Env center Replace center functionality with css tags:

```
\renewenvironment*{center}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:center}]{center}}
{\BlockClass{center}}
}
{\endBlockClass}
```

Env flushright

```
\renewenvironment*{flushright}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:right}]{flushright}}
{\BlockClass{flushright}}
}
{\endBlockClass}
```

Env flushleft

```
\renewenvironment*{flushleft}
{
\LWR@forcenewpage
\ifbool{FormatWP}
{\BlockClass[\LWR@print@mbox{text-align:left}]{flushleft}}
{\BlockClass{flushleft}}
}
{\endBlockClass}
```

\centering, \raggedleft, and \raggedright usually have no effect on the HTML output, but they may be used to compare with the next token to identify their use at the start of a float. See \LWR@floatalignment.

\centering

```
\newcommand*{\LWR@HTML@centering}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{centering}%
}{}%
}
\LWR@formatted{centering}
```

\raggedleft

```
\newcommand*{\LWR@HTML@raggedleft}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{raggedleft}%
}{}%
}
\LWR@formatted{raggedleft}
```

\raggedright

```
\newcommand*{\LWR@HTML@raggedright}{%
\ifbool{HTMLDebugComments}{%
    \LWR@htmlcomment{raggedright}%
}{}%
}
\LWR@formatted{raggedright}
```

\leftline {⟨*text*⟩}

```
\renewcommand{\leftline}[1]{\begin{flushleft}#1\end{flushleft}}
```

\centerline {⟨*text*⟩}

```
\renewcommand{\centerline}[1]{\begin{center}#1\end{center}}
```

\rightline {⟨*text*⟩}

```
\renewcommand{\rightline}[1]{\begin{flushright}#1\end{flushright}}
```

```
\end{warpHTML}
```

82 Preloaded packages

for HTML output:

```
\begin{warpHTML}
```

If the given package was loaded before or by lwarp, load the lwarp version as well.

\LWR@PreloadedPackage {⟨*packagename*⟩}

```
\newcommand*{\LWR@PreloadedPackage}[1]{%
    \@ifpackageloaded{#1}%
        {%
            \AtBeginDocument{
                \LWR@origRequirePackage{lwarp-#1}%
            }
        }%
        {}%
}
```

If inputtrc was loaded before lwarp, as is usually done, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{inputtrc}
```

If textcomp was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{textcomp}
```

If xunicode was loaded before lwarp, perhaps as part of the font-related packages, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{xunicode}
```

If graphics or graphicx were loaded before lwarp, perhaps by xunicode, explicitly load the lwarp patches now:

```
\LWR@PreloadedPackage{graphics}
\LWR@PreloadedPackage{graphicx}
```

fontaxes must be preloaded so that lwarp may patch it for HTML.

```
\LWR@PreloadedPackage{fontaxes}
```

nfssext-cfr may be preloaded by cfm-lm or related font packages.

```
\LWR@PreloadedPackage{nfssext-cfr}
```

ulem may be preloaded by ctex, ctexart, and related classes.

```
\LWR@PreloadedPackage{ulem}
```

xetexko-vertical may be preloaded by xetexko.

```
\LWR@PreloadedPackage{xetexko-vertical}
```

geometry is preloaded by lwarp, and perhaps by various classes.

```
\LWR@PreloadedPackage{geometry}
```

plext is preloaded by some CJK classes.

```
\LWR@PreloadedPackage{plext}
```

stfloats is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{stfloats}
```

lltjext is preloaded by ltj* classes.

```
\LWR@PreloadedPackage{lltjext}
```

```
\end{warpHTML}
```

83 siunitx

Pkg siunitx The lwarp core passes a few options to siunitx.

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first. See \MathJaxFilename to select a custom MathJax script.

⚠ tabular Tabular S columns are rendered as simple c columns, and tabular s columns are not supported. These may be replaced by c columns with each cell contained in \num or \si.

for HTML output:
```
\begin{warpHTML}
```

Options for siunitx:

```
\newrobustcmd{\LWR@siunitx@textcelsius}{\HTMLentity{deg}C}
\newrobustcmd{\LWR@siunitx@textdegree}{\HTMLentity{deg}}
\newrobustcmd{\LWR@siunitx@textprime}{\HTMLunicode{2032}}
\newrobustcmd{\LWR@siunitx@textdblprime}{\HTMLunicode{2033}}
\newrobustcmd{\LWR@siunitx@textplanckbar}{\text{\textit{\HTMLunicode{0127}}}}

\appto\LWR@restoreorigformatting{%
\renewrobustcmd{\LWR@siunitx@textcelsius}{\text{\ensuremath{^\circ}C}}%
\renewrobustcmd{\LWR@siunitx@textdegree}{\text{\ensuremath{^\circ}}}%
\renewrobustcmd{\LWR@siunitx@textprime}{\text{\ensuremath{^\prime}}}%
\renewrobustcmd{\LWR@siunitx@textdblprime}{\text{\ensuremath{^{\prime\prime}}}}%
\renewrobustcmd{\LWR@siunitx@textplanckbar}{\text{\ensuremath{\hbar}}}%
}

\PassOptionsToPackage{
    detect-mode=true,
    per-mode=symbol,% fraction is not seen by pdftotext
    text-celsius = {\LWR@siunitx@textcelsius},
    text-degree = {\LWR@siunitx@textdegree},
    text-arcminute = {\LWR@siunitx@textprime} ,
    text-arcsecond = {\LWR@siunitx@textdblprime} ,
}{siunitx}

\end{warpHTML}
```

84 Graphics print-mode modifications

84.1 General limitations

⚠ scale Avoid using the \includegraphics scale option. Change:

```
\includegraphics[scale=<xx>]{ . . . }
```

to:

```
\includegraphics[width=<yy>\linewidth]{ . . . }
```

\includegraphics file formats For \includegraphics with .pdf or .eps files, the user must provide a .pdf or .eps

image file for use in print mode, and also a `.svg`, `.png`, or `.jpg` version of the same image for use in HTML.

```
\includegraphics{filename} % print:.pdf/.eps HTML:.svg, etc.
```

For print output, lwarp will automatically choose the `.pdf` or `.eps` format if available, or some other format otherwise. For HTML, one of the other formats is used instead.

If a `.pdf` or `.eps` image is referred to with its file extension, the extension will be changed to `.svg` for HTML:

```
\includegraphics{filename.pdf} % uses .svg in html
\includegraphics{filename.eps} % uses .svg in html
```

Prog pdftocairo

PDF to SVG

To convert a PDF image to SVG, use the utility *pdftocairo*:

Enter ⇒ **`pdftocairo -svg filename.pdf`**

Prog lwarpmk pdftosvg

For a large number of images, use *lwarpmk*:

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of filenames)**

Prog lwarpmk epstopdf

Prog epstopdf

epstopdf package

For EPS images converted to PDF using the package epstopdf, use

Enter ⇒ **`lwarpmk pdftosvg *.PDF`**

to convert to SVG images.

DVI latex

When using DVI *latex*, it is necessary to convert EPS to PDF and then to SVG:

Enter ⇒ **`lwarpmk epstopdf *.eps`** **(or a list of filenames)**

Enter ⇒ **`lwarpmk pdftosvg *.pdf`** **(or a list of filenames)**

PNG and JPG

For PNG or JPGwhile using *pdflatex*, *lualatex*, or *xelatex*, the same file may be used in both print or HTML versions, and may be used with a file extension, but will also be used without the file extension if it is the only file of its base name.

GIF

GIF files may be used for HTML, but another format must also be provided for print output.

file extension priorities

If a file extension is not used, for HTML the file extension priorities are: SVG, GIF, PNG, then JPG.

⚠ graphics vs. graphicx

⚠ viewport

⚠ viewport units

If using the older graphics syntax, use both optional arguments for `\includegraphics`. A single optional parameter is interpreted as the newer graphicx syntax. Note that viewports are not supported by lwarp — the entire image will be shown.

For `\includegraphics`, avoid `px` and `%` units for width and height, or enclose them inside `warpHTML` environments. For font-proportional image sizes, use `ex` or `em`. For fixed-sized images, use `cm`, `mm`, `in`, `pt`, or `pc`. Use the keys `width=.5\linewidth`, or similar for `\textwidth` or `\textheight` to give fixed-sized images proportional to a 6 by 9 inch text area. Do not use the `scale` option, since it is not well supported by HTML browsers.

options `\includegraphics` accepts `width` and `height`, `origin`, `rotate` and `scale`, plus new `class` and `alt` keys.

html class With HTML output, `\includegraphics` accepts an optional `class=xyz` keyval combination, and if this is given then the HTML output will include that class for the image. The class is ignored for print output.

html `alt` tags Likewise, the `\includegraphics` `alt` key adds an HTML `alt` tag to an image, and is ignored for print output. If not assigned, each image is given an `alt` tag of "`(image)`".

`\rotatebox` `\rotatebox` accepts the optional `origin` key.

⚠ browser support `\rotatebox`, `\scalebox`, and `\reflectbox` depend on modern browser support. The css3 standard declares that when an object is transformed the whitespace which they occupied is preserved, unlike LaTeX, so expect some ugly results for scaling and rotating.

84.2 Print-mode modifications

for PRINT output: For print output, accept and then discard the new `class` key:

```
\begin{warpprint}
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
```

Print-mode additions for the overpic package. See section 359 for the HTML version.

```
\AtBeginDocument{
\@ifpackageloaded{overpic}{
\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}
}{}
}
\end{warpprint}
```

85 xcolor boxes

Pkg xcolor A few new definitions are provided for enhanced HTML colored boxes, and `\fcolorbox` is slightly modified. Print-mode version are also provided.

Print-mode versions of new xcolor defintions. These are defined inside `warpall` because they are also used for HTML while inside a `lateximage`. They are defined `\AtBeginDocument` so that the xcolor originals may first be loaded and saved for reuse.

The framed versions are modified to allow a background color of `none`, in which case only the frame is drawn, allowing the background page color to show.

for HTML & PRINT:

```
\begin{warpall}
```

After xparse may have been loaded …

```
10358 \AtBeginDocument{
```

… and *only* if xcolor was loaded:

```
10359 \@ifpackageloaded{xcolor}{
10360 \LWR@traceinfo{patching xcolor}
```

The print version:

\colorboxBlock `\colorboxBlock` is the same as `\colorbox`:

```
10361 \LetLtxMacro\colorboxBlock\colorbox
```

The original definition is reused by the new versions:

```
10362 \LetLtxMacro\LWR@orig@print@fcolorbox\fcolorbox
```

\fcolorbox `[`⟨*framemodel*⟩`]` `{`⟨*framecolor*⟩`}` `[`⟨*boxmodel*⟩`]` `{`⟨*boxcolor*⟩`}` `{`⟨*text*⟩`}`

In print mode, `\fcolorbox` is modified to accept a background color of `none`.

(`\fcolorbox` is particular about its optional arguments, thus the elaborate combinations of `\ifthenelse`.)

```
10363 \newsavebox{\LWR@colorminipagebox}
10364
10365 \NewDocumentCommand{\LWR@print@fcolorbox}{o m o m +m}{%
10366 \LWR@traceinfo{LWR@print@fcolorbox #2 #4}%
```

Pre-load the contents into an LR box so that they can be used inside a `\fcolorbox`:

```
10367 \begin{lrbox}{\LWR@colorminipagebox}%
10368 #5%
10369 \end{lrbox}%
```

Sort out the various optional arguments and the background color of `none`. In each case, the LRbox is placed inside a `\fcolorbox`.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
10370 \ifstrequal{#4}{none}%
10371 {% #4 none
10372     \LWR@traceinfo{background is none}%
10373     {% scope the \colorlet
10374         \colorlet{LWR@currentcolor}{.}%
10375         \color{#2}%
10376         \fbox{%
10377             \color{LWR@currentcolor}%
10378             \usebox{\LWR@colorminipagebox}%
```

```
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
\LWR@traceinfo{background not none}%
\IfValueTF{#1}%
{%
    \IfValueTF{#3}%
   {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}%
{% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
}% no value #1
}% #4 not none
\LWR@traceinfo{LWR@print@fcolorbox done}%
}

\renewcommand*{\fcolorbox}{\LWR@print@fcolorbox}
```

\fcolorboxBlock [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

In print mode, \fcolorboxBlock is the same as \fcolorbox.

```
\newcommand*{\LWR@print@fcolorboxBlock}{\LWR@print@fcolorbox}
\newcommand*{\fcolorboxBlock}{\LWR@print@fcolorboxBlock}
```

Env fcolorminipage [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

In print mode, becomes a \fcolorbox containing a minipage:

```
\NewDocumentEnvironment{LWR@print@fcolorminipage}{o m o m O{c} O{} o m}
{%
\LWR@traceinfo{*** fcolorminipage: #2 #4 #8}%
```

Pre-load the contents into an LR box so that they can be used inside a \fcolorbox:

```
\begin{lrbox}{\LWR@colorminipagebox}%
```

If inner alignment is not given, use the outer alignment instead:

```
\IfValueTF{#7}%
{\begin{minipage}[#5][#6][#7]{#8}}%
{\begin{minipage}[#5][#6][#5]{#8}}%
}%
{%
\end{minipage}%
\end{lrbox}%
\LWR@traceinfo{*** starting end fcolorminipage #1 #2 #3 #4 #8}%
```

Sort out the various optional arguments and the background color of none. In each case, the LRbox is placed inside a \fcolorbox.

The current color is remembered, then set to the frame, then the current color is used for the contents.

```
\ifstrequal{#4}{none}%
{% #4 none
    {% scope the \colorlet
        \colorlet{LWR@currentcolor}{.}%
        \color{#2}%
        \fbox{%
            \color{LWR@currentcolor}%
            \usebox{\LWR@colorminipagebox}%
        }% fbox
    }% colorlet
}% #4 none
{% #4 not none
    \IfValueTF{#1}%
    {%
    \IfValueTF{#3}%
   {\LWR@orig@print@fcolorbox[#1]{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox[#1]{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }%
    {% no value #1
    \IfValueTF{#3}%
    {\LWR@orig@print@fcolorbox{#2}[#3]{#4}{\usebox{\LWR@colorminipagebox}}}%
    {\LWR@orig@print@fcolorbox{#2}{#4}{\usebox{\LWR@colorminipagebox}}}%
    }% no value #1
}% #4 not none
\LWR@traceinfo{*** finished end fcolorminipage}%
}

\newenvironment*{fcolorminipage}
    {\LWR@print@fcolorminipage}
    {\endLWR@print@fcolorminipage}

\LWR@traceinfo{xcolor patches done}
}{}% xcolor loaded
}% AtBeginDocument

\end{warpall}
```

86 chemmacros environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in print mode, and in the chemmacros code in HTML mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

for PRINT output:

```
\begin{warpprint}
```

```
\AtBeginDocument{
\@ifpackageloaded{chemmacros}{
```

Env polymerdelims

```
\DeclareDocumentEnvironment{polymerdelims}{}
    {}{}
```

Env redoxreaction {⟨*space above*⟩} {⟨*space below*⟩}

For print output, extra space is include above and below the image, and a `lateximage` is not necessary. This extra space must be enforced, even inside a float, so zero-width rules are used.

For the HTML version, see section 168.4.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
    {\rule{0pt}{#1}}{\rule[-#2]{0pt}{#2}}
}{}% chemmacros
}% AtBeginDocument
\end{warpprint}
```

87 cleveref

Pkg cleveref cleveref package is used as-is with minor patches.

⚠ cleveref page numbers cleveref and varioref are supported, but printed page numbers do not map to HTML, so a section name or a text phrase are used for `\cpageref` and `\cpagerefrange`. This phrase includes `\cpagerefFor`, which defaults to "for".

Ex:

```
    \cpageref{tab:first,tab:second}
 in html becomes:
```

"pages **for** table 4.1 and **for** table 4.2"

See `\cpagerefFor` at page 534 to redefine the message which is printed for page number references.

loading order cleveref and the following associated macro patches are automatically preloaded at the end of the preamble via `\AtEndPreamble` and `\AfterEndPreamble`. This is done because the HTML conversion requires cleveref. The user's document may not require cleveref, thus the user may never explicitly load it, so during HTML output lwarp loads it last. If the user's document preamble uses cleveref options, or functions such as `\crefname`, then cleveref may be loaded in the user's preamble near the end, and lwarp's additional loading of cleveref will have no effect.

Table 12 on page 456 shows the data structure of the label/reference system as revised by lwarp and cleveref.

A few patches allow cleveref to work as-is:

for HTML output:
```
\begin{warpHTML}
```

`\AtEndPreable` forces cleveref to be loaded last:

```
\AtEndPreamble{
    \RequirePackage{cleveref}
}
```

The following patches are applied after cleveref has loaded, and after `\AtBeginDocument`. Print-mode versions are not required since they all come down to `\ref` eventually, and `\ref` has a print-mode version.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching cleveref.}
```

`\@@@setcref` {⟨*kindofref*⟩} {⟨*label*⟩}

`\@templabel` becomes the section number.

```
\def\LWR@orig@@@setcref#1#2{\cref@getlabel{#2}{\@templabel}#1{\@templabel}{}{}}%

\ifdefequal{\@@setcref}{\LWR@orig@@@setcref}{% before v0.21
    \renewcommand*{\@@setcref}[2]{#1{\ref{#2}}{}{}}
}{
    \ifdefequal{\@@@setcref}{\LWR@orig@@@setcref}{% as of v0.21
        \renewcommand*{\@@@setcref}[2]{#1{\ref{#2}}{}{}}
    }{
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cref\space will fail.
        }%
    }
}
```

`\@@@setcrefrange` {⟨*text*⟩} {⟨*label*⟩} {⟨*label*⟩}

```
\def\LWR@orig@@@setcrefrange#1#2#3{%
  \cref@getlabel{#2}{\@labela}%
  \cref@getlabel{#3}{\@labelb}%
  #1{\@labela}{\@labelb}{}{}{}{}}%

\ifdefequal{\@@setcrefrange}{\LWR@orig@@@setcrefrange}{
    \renewcommand{\@@setcrefrange}[3]{%
        #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
    }
}{
    \ifdefequal{\@@@setcrefrange}{\LWR@orig@@@setcrefrange}{
        \renewcommand{\@@@setcrefrange}[3]{%
            #1{\ref{#2}}{\ref{#3}}{}{}{}{}%
        }
```

```
    }{
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\crefrange\space will fail.
        }
    }
}

```

\cpagerefFor Redefinable word between “page(s)” and the page numbers.

```
\newcommand*{\cpagerefFor}{for}

```

\@@@setcpageref {⟨*typeofref*⟩} {⟨*label*⟩}, where typeofref is “page” or “pages”

```
\def\LWR@orig@@setcpageref#1#2{% before v0.21
  \cref@getpageref{#2}{\@temppage}#1{\@temppage}{}{}}%

\def\LWR@orig@@@setcpageref#1#2{% as of v0.21
  \cpageref@getlabel{#2}{\@temppage}#1{\@temppage}{}{}}%

\ifdefequal{\@@setcpageref}{\LWR@orig@@setcpageref}{
    \renewcommand*{\@@setcpageref}[2]{%
        #1{\cpagerefFor\ \cref{#2}}{}{}%
    }
}{
    \ifdefequal{\@@@setcpageref}{\LWR@orig@@@setcpageref}{
        \renewcommand*{\@@@setcpageref}[2]{%
            #1{\cpagerefFor\ \cref{#2}}{}{}%
        }
    }
    {
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpageref\space will fail.
        }
    }
}

\def\LWR@orig@@setcpagerefrange#1#2#3{% before v0.21
  \cref@getpageref{#2}{\@pagea}%
  \cref@getpageref{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}}%

\def\LWR@orig@@@setcpagerefrange#1#2#3{% as of v0.21
  \cpageref@getlabel{#2}{\@pagea}%
  \cpageref@getlabel{#3}{\@pageb}%
  #1{\@pagea}{\@pageb}{}{}{}{}}%

\ifdefequal{\@@setcpagerefrange}{\LWR@orig@@setcpagerefrange}{
    \renewcommand*{\@@setcpagerefrange}[3]{%
        #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
    }
```

```
}{
    \ifdefequal{\@@@setcpagerefrange}{\LWR@orig@@@setcpagerefrange}{
        \renewcommand*{\@@@setcpagerefrange}[3]{%
            #1{\cpagerefFor\ \cref{#2}}{\cref{#3}}{}{}{}{}%
        }
    }
    {
        \PackageWarning{lwarp-cleveref}{
            Unknown version of cleveref.
            \protect\cpagerefrange\space will fail.
        }
    }
}

}% AfterEndPreamble
```

Remember and patch some label-related defintions. These will be further encased and patched by other packages later.

`\label` and `\pageref` do NOT change their behavior according to print or HTML output, and thus do not use the `\LWR@formatted` system.

```
\LetLtxMacro\LWR@orig@label\label
\RenewDocumentCommand{\label}{}{\LWR@new@label}

\LetLtxMacro\LWR@orig@pageref\pageref
\RenewDocumentCommand{\pageref}{}{\LWR@new@pageref}
\end{warpHTML}
```

88 `picture` environment

Env `picture` The `picture` environment is enclosed inside a `\lateximage`.

for HTML output:

```
\begin{warpHTML}
```

Env `picture`

```
\BeforeBeginEnvironment{picture}{\begin{lateximage}[(picture)]}

\AfterEndEnvironment{picture}{\end{lateximage}}
```

```
\end{warpHTML}
```

89 Minipages and Boxes

A css flexbox is used for minipages and parboxes, allowing external and internal vertical positioning.

⚠ inline — A line of text with an inline `minipage` or `\parbox` will have the `minipage` or `\parbox` placed onto its own line, because a paragraph is a block element and cannot be made `inline-block`.

placement — `minipages` and `\parboxes` will be placed side-by-side in HTML unless you place a `\newline` between them.

side-by-side — Side-by-side `minipages` may be separated by `\quad`, `\qquad`, `\enskip`, `\hspace`, `\hfill`, or a `\rule`. When inside a `center` environment, the result is similar in print and HTML. Paragraph tags are suppressed between side-by-side `minipages` and these spacing commands, but not at the start or end of the paragraph.

⚠ minipage in a span — There is limited support for `minipages` inside an HTML . An HTML cannot appear inside a . While in a , `minipages`, and `\parboxes`, and any enclosed lists have limited HTML tags, resulting in an "inline" format, without markup except for HTML breaks. Use `\newline` or `\par` for an HTML break.

⚠ minipage size — When using `\linewidth`, `\textwidth`, and `\textheight`, widths and heights in HTML are scaled proportionally to a 6×9 inch text area, and inside a `multicols` `\linewidth` is divided by the specified number of columns.

if width is `\linewidth` — If a `minipage` or `\parbox` is assigned a width of exactly `\linewidth`, in HTML it is automatically given no HTML width, thus allowed to fill the line as needed, similar to how it appears in print output.

full-width if html — A new macro `\minipagefullwidth` requests that, during HTML output, the next single `minipage` or `\parbox` be generated without an HTML `width` attribute, allowing it to be the full width of the display rather than the declared print-output width. This may be useful where the printed version's width makes no sense in HTML.

⚠ `tabular`, `multicols` — Inside a `tabular` or `multicols` environment, where the width depends on the browser window, `\minipagefullwidth` is effectively used by default for every `minipage` or `\parbox` inside the environment. `\UseMinipageWidths` may be used to tell lwarp to honor the specified widths of all following `minipages` and `\parboxes` until the end of the local scope, and `\IgnoreMinipageWidths` may be used to tell lwarp to ignore the specified widths.

`\UseMinipageWidths`
`\IgnoreMinipageWidths`

⚠ text alignment — Nested `minipages` adopt their parent's text alignment in HTML, whereas in regular LaTeX PDF output they do not. Use a `flushleft` or similar environment in the child `minipage` to force a text alignment.

for HTML output:
```
\begin{warpHTML}
```

89.1 Counters and lengths

Ctr `LWR@minipagedepth` — Used to only reset the line width at the outermost minipage.

```
\newcounter{LWR@minipagedepth}
\setcounter{LWR@minipagedepth}{0}
```

Len `\LWR@minipagewidth` — Used to convert the width into printable units.

```
10567 \newlength{\LWR@minipagewidth}
```

Len `\LWR@minipageheight` Used to convert the height into printable units.

```
10568 \newlength{\LWR@minipageheight}
```

89.2 Footnote handling

Also see section 59 for other forms of footnotes. Minipage footnotes are gathered in section 59.5, and then placed into the document in section 89.3.

89.3 Minipage handling

Bool `LWR@minipagefullwidth` Should the next minipage have no HTML `width`?

```
10569 \newbool{LWR@minipagefullwidth}
10570 \boolfalse{LWR@minipagefullwidth}
```

Bool `LWR@forceminipagefullwidth` Should the next minipage have no HTML `width`? Used to force full width for all minipages in an environment such as `tabular` or `multicols`, where the actual width depends on the browser width. Controlled by `\useminipagewidths` and `\ignoreminipagewidths`.

```
10571 \newbool{LWR@forceminipagefullwidth}
10572 \boolfalse{LWR@forceminipagefullwidth}
```

`\minipagefullwidth` Requests that the next minipage have no `width` tag in HTML:

for HTML output:

```
10573 \newcommand*{\minipagefullwidth}{\global\booltrue{LWR@minipagefullwidth}}
```

`\UseMinipageWidths` Locally requests that minipage widths be honored.

```
10574 \newcommand*{\UseMinipageWidths}{\boolfalse{LWR@forceminipagefullwidth}}
```

`\IgnoreMinipageWidths` Locally requests that minipage widths be ignored.

```
10575 \newcommand*{\IgnoreMinipageWidths}{\booltrue{LWR@forceminipagefullwidth}}
10576 \end{warpHTML}
```

for PRINT output:

```
10577 \begin{warpprint}
10578 \newcommand*{\minipagefullwidth}{}
10579 \newcommand*{\UseMinipageWidths}{}
10580 \newcommand*{\IgnoreMinipageWidths}{}
10581 \end{warpprint}
```

for HTML output:

```
10582 \begin{warpHTML}
```

Bool LWR@minipagethispar Has a minipage been seen this paragraph? If true, prevents paragraph tags around horizontal space between minipages.

```
\newbool{LWR@minipagethispar}
\boolfalse{LWR@minipagethispar}
```

Env minipage [⟨*vert position*⟩] [⟨*height*⟩] [⟨*inner vert position*⟩] {⟨*width*⟩}

The vertical positions may be 'c', 't', or 'b'. The inner position may also be 's'.

When using \linewidth, \textwidth, or \textheight, these are scaled proportionally to a 6×9 inch text area.

```
\NewDocumentEnvironment{LWR@HTML@sub@minipage}{m m m m}
{%
\LWR@traceinfo{minipage}%
```

Temporarily open a group, in which width and height is computed based on a virtual page size instead of the extra-large PDF page used during HTML tag generation.

The following used to be an actual LaTeX minipage.

```
\begingroup
```

Compute width, adjusted for frames:

```
\setlength{\LWR@minipagewidth}{#4}%
\ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}{%
```

Only create a new page if not yet nested:

```
    \LWR@orignewpage%
```

Adjust virtual page size:

```
    \addtolength{\LWR@minipagewidth}{3em}% room for frames
    \setlength{\linewidth}{6in}%
    \setlength{\textwidth}{6in}%
    \setlength{\textheight}{9in}%
}{}%
\LWR@traceinfo{computed width is \LWR@printlength{\LWR@minipagewidth}}%
```

Compute height:

```
\setlength{\LWR@minipageheight}{\textheight}% default unless specified
\ifblank{#2}{}{\setlength{\LWR@minipageheight}{#2}}%
```

Track nesting depth:

```
\addtocounter{LWR@minipagedepth}{1}%
```

LaTeX wants to start a paragraph for the virtual minipage, then start a paragraph again for the contents of the minipage, so cancel the paragraph tag handling until the minipage has begun.

```
\ifbool{FormatWP}{\newline}{}%
\LWR@stoppars%
```

If FormatWP, add a text frame:

```
\ifbool{FormatWP}{%

\addtocounter{LWR@thisautoidWP}{1}%
\LWR@htmltag{%
    div id="\LWR@print@mbox{autoidWP-\arabic{LWR@thisautoidWP}}" %
    class="wpminipage"%
}%

}{}%
```

Create the tag with optional alignment style:

```
\LWR@traceinfo{minipage: creating div class}%
\LWR@htmltag{div class="minipage" style="%
\ifthenelse{\equal{#1}{t}}{\LWR@print@mbox{vertical-align:bottom} ; }{}%
\ifthenelse{\equal{#1}{c}}{\LWR@print@mbox{vertical-align:middle} ; }{}%
\ifthenelse{\equal{#1}{b}}{\LWR@print@mbox{vertical-align:top} ; }{}%
\ifthenelse{\equal{#3}{t}}{\LWR@print@mbox{justify-content:flex-start} ; }{}%
\ifthenelse{\equal{#3}{c}}{\LWR@print@mbox{justify-content:center} ; }{}%
\ifthenelse{\equal{#3}{b}}{\LWR@print@mbox{justify-content:flex-end} ; }{}%
\ifthenelse{\equal{#3}{s}}{\LWR@print@mbox{justify-content:space-between} ; }{}%
```

Print the width and optional height styles:

```
\LWR@traceinfo{minipage: about to print the width of \LWR@printlength{\LWR@minipagewidth}}%
\ifbool{LWR@minipagefullwidth}%
{\global\boolfalse{LWR@minipagefullwidth}}%
{%
    \ifbool{LWR@forceminipagefullwidth}%
        {}%
        {%
            \ifthenelse{\lengthtest{#4}=\linewidth}%
                {}%
                {width:\LWR@printlength{\LWR@minipagewidth} ; }%
        }%
}%
\LWR@traceinfo{minipage: about to print the height}%
\ifblank{#2}{}{height:\LWR@printlength{\LWR@minipageheight} ; }%
"}%
```

Finish with an empty line to start the contents on a new line.

```

% The preceding empty line is required.
```

Set the user-accessible line and text width and height values inside the virtual minipage. These do not affect the actual size of the PDF output, but are used by any reference to \linewidth, etc. inside the virtual minipage being created here.

```
\setlength{\linewidth}{#4}% the original width
\setlength{\textwidth}{6in}%
\setlength{\textheight}{9in}%
```

\raggedright cancels hyphenation, which will be done by HTML instead.

```
\LWR@print@raggedright%
```

Set minipage footnotes:

```
\def\@mpfn{mpfootnote}%
\def\thempfn{\thempfootnote}\c@mpfootnote\z@%
\let\@footnotetext\@mpfootnotetext%
```

Resume paragraph tag handling for the contents of the minipage:

```
\LWR@startpars%
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== begin minipage ===

}{}%
\LWR@traceinfo{minipage: finished starting the minipage}%
}% finished \minipage
{% \endminipage
```

Print pending minipage footnotes:

```
\LWR@printpendingmpfootnotes%
```

End the environment with closing tag:

```
\ifboolexpr{bool{FormatWP} and bool{WPMarkMinipages}}{%

=== end minipage ===

}{}%
\LWR@stoppars%
```

The following used to be an actual LaTeX minipage.

```
\endgroup%

\ifbool{FormatWP}{%

\LWR@htmlelementend{div}%

}{}%
\LWR@htmldivclassend{minipage}%

```

```
\addtocounter{LWR@minipagedepth}{-1}%
\LWR@startpars%
\ifbool{FormatWP}{\newline}{}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{LWR@minipage: done}%
}

\NewDocumentEnvironment{LWR@HTML@minipage}{O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#1}{#2}{#3}{#4}}
    {\endLWR@HTML@sub@minipage}

\LWR@formattedenv{minipage}
```

89.4 \parbox, \mbox, \makebox, \framebox, \fbox, \raisebox

for HTML output:

\parbox [⟨*pos*⟩] [⟨*height*⟩] [⟨*inner-pos*⟩] {⟨*width*⟩} {⟨*text*⟩}

A parbox uses the minipage code:

```
\NewDocumentCommand{\LWR@HTML@parbox}{O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#1][#2][#3]{#4}%
#5
\end{minipage}%
}

\LWR@formatted{parbox}
```

\mbox {⟨*text*⟩} Nullified for HTML.

```
\newcommand*{\LWR@HTML@mbox}[1]{#1}

\LWR@formatted{mbox}
```

\LWR@@makebox@paren {⟨*width*⟩} , {⟨*height*⟩}

Adds to the style in \LWR@temptwo.

```
\NewDocumentCommand{\LWR@@makebox@paren}{m m}{%
\IfValueTF{#2}{%
    \setlength{\LWR@tempwidth}{#1\unitlength}%
    \setlength{\LWR@tempheight}{#2\unitlength}%
    \appto{\LWR@temptwo}{%
        \LWR@print@mbox{width:\LWR@printlength{\LWR@tempwidth}} ; % space
```

```
        \LWR@print@mbox{height:\LWR@printlength{\LWR@tempheight}} ; % space
    }%
}{%
    \PackageError{lwarp}%
        {(width,height) is missing a comma ',' character}%
        {\protect\makebox\space and \protect\framebox\space accept
            a size in the format (width,height).}%
}%
}
```

`\LWR@@makebox@align` {⟨*alignment character*⟩}

Adds to the style in `\LWR@temptwo`.

```
\newcommand*{\LWR@@makebox@align}[1]{%
    \def\LWR@align{center}%
    \ifstrequal{#1}{l}{\def\LWR@align{left}}{}%
    \ifstrequal{#1}{r}{\def\LWR@align{right}}{}%
    \ifstrequal{#1}{s}{\def\LWR@align{justify}}{}%
    \appto{\LWR@temptwo}{%
        \LWR@print@mbox{text-align:\LWR@align} ; %
    }%
}
```

`\makebox` (⟨*width,height*⟩) [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@makebox}{>{\SplitArgument{1}{,}}d() o o +m}{%
```

Build the style depending on arguments:

```
{% scope
    \def\LWR@temptwo{}%
    \IfValueTF{#1}%
    {% (width,height) ..
        \LWR@@makebox@paren #1%
        \IfValueT{#2}%
        {% (width,height) [posn]
            \LWR@@makebox@align{#2}%
        }%
    }%
    {% [width]
        \IfValueT{#2}% [width]
        {%
            \setlength{\LWR@tempwidth}{#2}%
            \ifdimgreater{\LWR@tempwidth}{0pt}{%
                \appto{\LWR@temptwo}{%
                    width:\LWR@printlength{\LWR@tempwidth} ; % space
                }%
            }{}%
        }%
    }%
    \IfValueT{#3}%
    {% [width] [posn]
        \LWR@@makebox@align{#3}%
```

```
    }%
    \InlineClass[%
        \LWR@print@mbox{display:inline-block} ; %
        \LWR@temptwo%
    ]%
    {makebox}%
    {#4}%
}% scope
}
\LWR@formatted{makebox}
```

\framebox (⟨*width,height*⟩) [⟨*width*⟩] [⟨*pos*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@framebox}{d() o o +m}{%
    \fbox{\makebox(#1)[#2][#3]{#4}}%
}

\LWR@formatted{framebox}
```

\LWR@forceminwidth {⟨*legth*⟩}

Sets \LWR@atleastonept to be at least 1pt.

```
\newlength{\LWR@atleastonept}

\newcommand*{\LWR@forceminwidth}[1]{%
\setlength{\LWR@atleastonept}{#1}%
\ifthenelse{%
    \lengthtest{\LWR@atleastonept>0pt}\AND%
    \lengthtest{\LWR@atleastonept<1pt}%
}%
    {\setlength{\LWR@atleastonept}{1pt}}%
    {}%
}
```

\LWR@fboxstyle Prints the HTML attributes for a black border and padding.

\LWR@forceminwidth must be used first in order to set the border width.

```
\newcommand*{\LWR@fboxstyle}{%
\LWR@findcurrenttextcolor%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@origpound\LWR@tempcolor ; %
padding:\LWR@printlength{\fboxsep} ; %
color:\LWR@origpound\LWR@tempcolor%
}
```

\fbox {⟨*text*⟩}

Creates a framed inline span enclosing the text.

Create a new HTML version, but don't use it until after xcolor may have loaded:

```
\newcommand{\LWR@HTML@fbox}[1]{%
\LWR@traceinfo{HTML fbox}%
\LWR@forceminwidth{\fboxrule}%
\InlineClass[%
    \LWR@print@mbox{display:inline-block} ; %
    \LWR@fboxstyle%
]{fbox}{#1}%
}
```

xcolor `\lets` things to `\fbox` when it is loaded, and this must remain even for HTML output while in a `lateximage`, so `\fbox` is not modified until `\AtBeginDocument`:

```
\AtBeginDocument{\LWR@formatted{fbox}}
```

`\fboxBlock` {⟨*text*⟩} Creates a framed HTML of the text.

First, a print-mode version. This is newly defined for print mode, so it is defined inside `warpall`.

for HTML & PRINT:

```
\end{warpHTML}
\begin{warpall}
\let\fboxBlock\fbox
\end{warpall}

\begin{warpHTML}
```

for HTML output: Next, an HTML version:

```
\newcommand{\LWR@HTML@fboxBlock}[1]{%
\LWR@forceminwidth{\fboxrule}%
\begin{BlockClass}[%
\LWR@fboxstyle%
]{fboxBlock}
#1
\end{BlockClass}
}

\LWR@formatted{fboxBlock}

\end{warpHTML}
```

Env `fminipage` [⟨*align*⟩] [⟨*height*⟩] [⟨*align*⟩] {⟨*width*⟩}

Creates a framed HTML around its contents.

for HTML & PRINT: Print version:

```
\begin{warpall}

\newsavebox{\LWR@fminipagebox}

\NewDocumentEnvironment{LWR@print@fminipage}{O{t} o O{t} m}
{%
```

An outer minipage will be used for vertical alignment. An inner minipage will be framed with \fbox.

If the optional inner alignment is not given, use the outer instead:

```
\IfValueTF{#3}%
{\def\LWR@thisalign{#3}}
{\def\LWR@thisalign{#1}}%
```

Form the outer minipage depending on whether a height was given. Make the outer minipage larger to compensate for the frame.

```
\IfValueTF{#2}%
{\minipage[#1][#2+2\fboxsep+2\fboxrule][\LWR@thisalign]{#4+2\fboxsep+2\fboxrule}}%
{\minipage[#1]{#4+2\fboxsep+2\fboxrule}}%
```

Capture the contents of the environment:

```
\begin{lrbox}{\LWR@fminipagebox}%
```

Nest the contents inside an inner minipage of the desired size:

```
\IfValueTF{#2}%
{\minipage[#1][#2][\LWR@thisalign]{#4}}%
{\minipage[#1]{#4}}%
}
{%
```

Close the inner minipage and the LR box with the contents:

```
\endminipage%
\end{lrbox}%
```

Create a frame around the contents of the environment:

```
\fbox{\usebox{\LWR@fminipagebox}}%
```

The entire thing is placed inside the outer minipage:

```
\endminipage%
}

\LetLtxMacro\fminipage\LWR@print@fminipage
\LetLtxMacro\endfminipage\endLWR@print@fminipage
% \newenvironment{fminipage}{\LWR@print@fminipage}{\endLWR@print@fminipage}

\end{warpall}
```

HTML version:

for HTML output:

```
\begin{warpHTML}

\NewDocumentEnvironment{LWR@HTML@fminipage}{O{t} o O{t} m}
{%
```

```
\LWR@traceinfo{fminipage #1 #2 #3 #4}%
\LWR@forceminwidth{\fboxrule}%
\setlength{\LWR@tempwidth}{#4}%
\IfValueT{#2}{\setlength{\LWR@tempheight}{#2}}%

\LWR@stoppars%

\begin{BlockClass}[%
\LWR@fboxstyle ; %
\IfValueT{#2}{height:\LWR@printlength{\LWR@tempheight} ; }%
\ifbool{LWR@minipagefullwidth}%
{\global\boolfalse{LWR@minipagefullwidth}}%
{%
    \ifbool{LWR@forceminipagefullwidth}%
        {}%
        {%
            \ifthenelse{\lengthtest{\LWR@tempwidth}=\linewidth}%
                {}%
                {width:\LWR@printlength{\LWR@tempwidth} ; }%
        }%
}%
]{fminipage}%
}
{%
\end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{fminipage done}%
}

\LWR@formattedenv{fminipage}
```

`\raisebox` {⟨*raiselen*⟩} [⟨*height*⟩] [⟨*depth*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@raisebox}{m o o m}{%
#4%
}

\LWR@formatted{raisebox}

\end{warpHTML}
```

90 Direct formatting

⚠ `\bfseries, etc.` `\textbf`, etc. are supported, but `\bfseries`, etc. work only in some situations.

⚠ HTML special chars &, <, and > have special meanings in HTML. If `\&`, `\textless`, and `\textgreater` are

used, proper HTML entities will be used, but there may be HTML parsing problems if these special characters occur unescaped in program listings or other verbatim text.

program listings For program listings, the listings package is supported, and its `literate` option is used to convert &, <, and > to proper HTML entities.

verbatim The various `verbatim`-related environments do not convert &, <, and >, so care must be taken to avoid accidentally including valid HTML code inside these environments. Adding a space on either side may be sufficient.

For high-level block and inline custom CSS classes, see section 51.9.

for HTML output:

```
\begin{warpHTML}
```

`\emph` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@emph}[1]{%
    {%
        \itshape%
        \LWR@htmlspan{em}{#1}%
    }%
}

\LWR@formatted{emph}

\newcommand{\LWR@null@emph}[1]{#1}
```

`\textmd` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textmd}[1]{%
    {%
        \mdseries%
        \InlineClass(font-weight:normal){textmd}{#1}%
    }%
}

\LWR@formatted{textmd}

\newcommand{\LWR@null@textmd}[1]{#1}
```

`\textbf` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textbf}[1]{%
    {%
        \bfseries%
        \LWR@htmlspan{b}{#1}%
    }%
}

\LWR@formatted{textbf}

\newcommand{\LWR@null@textbf}[1]{#1}
```

`\texteb` {⟨*text*⟩} From nfssext-cfr.

```
\DeclareRobustCommand{\LWR@HTML@texteb}[1]{%
    {%
        \ebweight%
        \InlineClass{texteb}{#1}%
    }%
}

\LWR@formatted{texteb}

\newcommand{\LWR@null@texteb}[1]{#1}
```

`\textlg` {⟨*text*⟩} From nfssext-cfr.

```
\DeclareRobustCommand{\LWR@HTML@textlg}[1]{%
    {%
        \lgweight%
        \InlineClass{textlg}{#1}%
    }%
}

\LWR@formatted{textlg}

\newcommand{\LWR@null@textlg}[1]{#1}
```

`\textrm` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textrm}[1]{%
    {%
        \rmfamily%
        \InlineClass(font-family:serif){textrm}{#1}%
    }%
}

\LWR@formatted{textrm}

\newcommand{\LWR@null@textrm}[1]{#1}
```

`\textsf` {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsf}[1]{%
    {%
        \sffamily%
        \InlineClass(font-family:sans){textsf}{#1}%
    }%
}

\LWR@formatted{textsf}

\newcommand{\LWR@null@textsf}[1]{#1}
```

\texttt {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@texttt}[1]{%
    {%
        \ttfamily%
        \LWR@htmlspan{kbd}{#1}%
    }%
}

\LWR@formatted{texttt}

\newcommand{\LWR@null@texttt}[1]{#1}
```

\textup {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textup}[1]{%
    {%
        \upshape%
        \InlineClass(font-style:normal){textup}{#1}%
    }%
}

\LWR@formatted{textup}

\newcommand{\LWR@null@textup}[1]{#1}
```

\textit {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textit}[1]{%
    {%
        \itshape%
        \LWR@htmlspan{i}{#1}%
    }%
}

\LWR@formatted{textit}

\newcommand{\LWR@null@textit}[1]{#1}
```

\textsc {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsc}[1]{%
    {%
        \scshape%
        \InlineClass{textsc}{#1}%
    }%
}

\LWR@formatted{textsc}

\newcommand{\LWR@null@textsc}[1]{#1}
```

\textulc {⟨*text*⟩} From fontaxes.

```
\DeclareRobustCommand{\LWR@HTML@textulc}[1]{%
    {%
        \ulcshape%
        \InlineClass{textulc}{#1}%
    }%
}

\LWR@formatted{textulc}

\newcommand{\LWR@null@textulc}[1]{#1}
```

\textsi {⟨*text*⟩}

```
\@ifundefined{textsi}{
    \LetLtxMacro\LWR@print@textsi\LWR@print@textsc
}{}

\DeclareRobustCommand{\LWR@HTML@textsi}[1]{%
    {%
        \sishape%
        \textsc{\textit{#1}}%
%         \InlineClass(
%             font-style: italic;
%             font-variant: small-caps ;
%             font-variant-numeric: oldstyle-nums ;
%         ){textsi}{#1}%
    }%
}

\LWR@formatted{textsi}

\newcommand{\LWR@null@textsi}[1]{#1}
```

\textsl {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textsl}[1]{%
    {%
        \slshape%
        \InlineClass(font-style:oblique){textsl}{#1}%
    }%
}

\LWR@formatted{textsl}

\newcommand{\LWR@null@textsl}[1]{#1}
```

\textnormal {⟨*text*⟩}

```
\DeclareRobustCommand{\LWR@HTML@textnormal}[1]{\textmd{\textrm{\textup{#1}}}}

\LWR@formatted{textnormal}
```

```
\newcommand{\LWR@null@textnormal}[1]{#1}

\newcommand{\LWR@null@rmfamily}{}
\newcommand{\LWR@null@sffamily}{}
\newcommand{\LWR@null@ttfamily}{}
\newcommand{\LWR@null@bfseries}{}
\newcommand{\LWR@null@ebweight}{}
\newcommand{\LWR@null@lgweight}{}
\newcommand{\LWR@null@mdseries}{}
\newcommand{\LWR@null@upshape}{}
\newcommand{\LWR@null@slshape}{}
\newcommand{\LWR@null@scshape}{}
\newcommand{\LWR@null@itshape}{}
\newcommand{\LWR@null@normalfont}{}

\newcommand{\LWR@null@em}{}
```

`\LWR@nullfonts` Removes formatting during filename operations, file references, and HTML comments.

Use only inside a group.

The following are *not* made robust, since they must be expanded to their nullified versions.

```
\catcode`\$=\active% redefining $ below
\catcode`\_=12% redefining \_ below
\newcommand*{\LWR@nullfonts}{%
\LetLtxMacro\emph\LWR@null@emph%
\LetLtxMacro\textmd\LWR@null@textmd%
\LetLtxMacro\textbf\LWR@null@textbf%
\LetLtxMacro\textrm\LWR@null@textrm%
\LetLtxMacro\textsf\LWR@null@textsf%
\LetLtxMacro\texttt\LWR@null@texttt%
\LetLtxMacro\textup\LWR@null@textup%
\LetLtxMacro\textit\LWR@null@textit%
\LetLtxMacro\textsc\LWR@null@textsc%
\LetLtxMacro\textulc\LWR@null@textulc%
\LetLtxMacro\textsi\LWR@null@textsi%
\LetLtxMacro\textsl\LWR@null@textsl%
\LetLtxMacro\textnormal\LWR@null@textnormal%
\LetLtxMacro\rmfamily\LWR@null@rmfamily%
\LetLtxMacro\sffamily\LWR@null@sffamily%
\LetLtxMacro\ttfamily\LWR@null@ttfamily%
\LetLtxMacro\bfseries\LWR@null@bfseries%
\LetLtxMacro\mdseries\LWR@null@mdseries%
\LetLtxMacro\upshape\LWR@null@upshape%
\LetLtxMacro\slshape\LWR@null@slshape%
\LetLtxMacro\scshape\LWR@null@scshape%
\LetLtxMacro\ulcshape\LWR@null@ulcshape%

\LetLtxMacro\sishape\LWR@null@sishape%
```

```
\LetLtxMacro\itshape\LWR@null@itshape%
\LetLtxMacro\normalfont\LWR@null@normalfont%
\LetLtxMacro\em\LWR@null@em%
```

Various built-in symbols.

```
\renewcommand*{\$}{-}%
\renewcommand*{\%}{-}%
\renewcommand*{\_}{-}%
\renewcommand*{\}}{-}%
\renewcommand*{\{}{-}%
\renewcommand*{\&}{and}%
\renewcommand*{\#}{-}%
\renewcommand*{\,}{-}%
\renewcommand*{~}{-}%
\renewcommand*{\^}[1]{-}%
\renewcommand*{\~}[1]{-}%
\renewcommand*{\newline}{-}%
\renewcommand*{\textasciicircum}{-}%
\renewcommand*{\textasciitilde}{-}%
\renewcommand*{\textasteriskcentered}{-}%
\renewcommand*{\textbackslash}{-}%
\renewcommand*{\textbar}{-}%
\renewcommand*{\textbardbl}{-}%
\renewcommand*{\textbigcircle}{-}%
\renewcommand*{\textbraceleft}{-}%
\renewcommand*{\textbraceright}{-}%
\renewcommand*{\textbullet}{-}%
\renewcommand*{\textcopyright}{-}%
\renewcommand*{\textdagger}{-}%
\renewcommand*{\textdaggerdbl}{-}%
\renewcommand*{\textdollar}{-}%
\renewcommand*{\textellipsis}{-}%
\renewcommand*{\textemdash}{-}%
\renewcommand*{\textendash}{-}%
\renewcommand*{\textexclamdown}{-}%
\renewcommand*{\textgreater}{-}%
\renewcommand*{\textless}{-}%
\renewcommand*{\textordfeminine}{-}%
\renewcommand*{\textordmasculine}{-}%
\renewcommand*{\textparagraph}{-}%
\renewcommand*{\textperiodcentered}{-}%
\renewcommand*{\textpertenthousand}{-}%
\renewcommand*{\textperthousand}{-}%
\renewcommand*{\textquestiondown}{-}%
\renewcommand*{\textquotedblleft}{-}%
\renewcommand*{\textquotedblright}{-}%
\renewcommand*{\textquoteleft}{-}%
\renewcommand*{\textquoteright}{-}%
\renewcommand*{\textregistered}{-}%
\renewcommand*{\textsection}{-}%
\renewcommand*{\textsterling}{-}%
\renewcommand*{\texttrademark}{-}%
\renewcommand*{\textunderscore}{-}%
\renewcommand*{\textvisiblespace}{-}%
```

```
\renewcommand*{\copyright}{-}%
\renewcommand*{\dag}{-}%
\renewcommand*{\ddag}{-}%
\renewcommand*{\dots}{-}%
\renewcommand*{\P}{-}%
\renewcommand*{\pounds}{-}%
\renewcommand*{\S}{-}%
\renewcommand*{\aa}{a}%
\renewcommand*{\AA}{A}%
\renewcommand*{\AE}{AE}%
\renewcommand*{\ae}{ae}%
\renewcommand*{\dh}{d}%
\renewcommand*{\DH}{D}%
\renewcommand*{\DJ}{D}%
\renewcommand*{\dj}{d}%
\renewcommand*{\IJ}{IJ}%
\renewcommand*{\ij}{ij}%
\renewcommand*{\L}{L}%
\renewcommand*{\l}{l}%
\renewcommand*{\NG}{NG}%
\renewcommand*{\ng}{ng}%
\renewcommand*{\O}{O}%
\renewcommand*{\o}{o}%
\renewcommand*{\oe}{oe}%
\renewcommand*{\OE}{OE}%
\renewcommand*{\ss}{ss}%
\renewcommand*{\SS}{SS}%
\renewcommand*{\th}{th}%
\renewcommand*{\TH}{TH}%
\renewcommand*{\guillemotleft}{}%
\renewcommand*{\guilsinglleft}{}%
\renewcommand*{\quotedblbase}{}%
\renewcommand*{\textquotedbl}{}%
\renewcommand*{\guillemotright}{}%
\renewcommand*{\guilsinglright}{}%
\renewcommand*{\quotesinglbase}{}%

\renewcommand*{\HTMLunicode}[1]{}%
\renewcommand*{\HTMLentity}[1]{}%

\renewcommand{\textsuperscript}[1]{##1}%
\renewcommand{\textsubscript}[1]{##1}%


\renewcommand{\underline}[1]{##1}%

\RenewDocumentCommand{\LWR@htmlspanclass}{o m +m}{##3}%
\DeclareExpandableDocumentCommand{\InlineClass}{D{(}{)}{} o m +m}{##4}%
```

Nullify math macros.

```
\def\(##1\){}%
\def\[##1\]{}%
\RenewDocumentCommand{\LWR@subsingledollar}{s m m m}{}%
\protected\def$##1${}%
```

Nullify logos:

```
\renewcommand*{\TeX}{TeX}%
\renewcommand*{\LaTeX}{LaTeX}%
\renewcommand*{\LaTeXe}{LaTeX2e}%
\renewcommand*{\LuaTeX}{LuaTeX}%
\renewcommand*{\LuaLaTeX}{LuaLaTeX}%
\renewcommand*{\XeTeX}{XeTeX}%
\renewcommand*{\XeLaTeX}{XeLaTeX}%
\renewcommand*{\ConTeXt}{ConTeXt}%
\renewcommand*{\BibTeX}{BibTeX}%
\renewcommand*{\MakeIndex}{MakeIndex}%
\renewcommand*{\AmS}{AmS}%
\renewcommand*{\MiKTeX}{MiKTeX}%
\renewcommand*{\LyX}{LyX}%
```

Use the simpler form with `\texorpdfstring`:

```
\let\texorpdfstring\relax%
\newcommand{\texorpdfstring}[2]{##2}%
}
\catcode`\$=3%
\catcode`\_=8%
```

`\FilenameNullify` {⟨*redefinitions*⟩}

Adds more nullifying definitions for filename generation.

```
\newcommand*{\FilenameNullify}[1]{%
    \appto{\LWR@nullfonts}{#1}%
}
```

Remembers the current font family, series, and shape. fontaxes support is integrated here.

```
\newcommand*{\LWR@f@family}{rm}
\newcommand*{\LWR@f@series}{md}
\newcommand*{\LWR@f@shape}{up}
\newcommand*{\LWR@f@shapecaps}{ulc}
```

`\LWR@textcurrentfont` {⟨*text*⟩}

Prints the text with the current font choices. Avoids nesting repeated font selections.

```
\newcounter{LWR@textcurrentfontdepth}
\setcounter{LWR@textcurrentfontdepth}{0}

\newcommand*{\LWR@textcurrentfont}[1]{%
    \ifnumcomp{\value{LWR@textcurrentfontdepth}}{>}{0}%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            #1%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
```

```
        }%
        {%
            \addtocounter{LWR@textcurrentfontdepth}{1}%
            \InlineClass{%
                    text\LWR@f@family\LWR@origtilde{}%
                    text\LWR@f@series\LWR@origtilde{}%
                    text\LWR@f@shape\LWR@origtilde{}%
                    text\LWR@f@shapecaps%
                }%
                {#1}%
            \addtocounter{LWR@textcurrentfontdepth}{-1}%
        }%
}
```

Env LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{%
\BlockClass{%
        text\LWR@f@family\LWR@origtilde{}%
        text\LWR@f@series\LWR@origtilde{}%
        text\LWR@f@shape\LWR@origtilde{}%
        text\LWR@f@shapecaps%
    }%
}{\endBlockClass}
```

\mdseries

```
\newrobustcmd*{\LWR@HTML@mdseries}{\renewcommand*{\LWR@f@series}{md}}
\LWR@formatted{mdseries}
```

\bfseries

```
\newrobustcmd*{\LWR@HTML@bfseries}{\renewcommand*{\LWR@f@series}{bf}}
\LWR@formatted{bfseries}
```

\ebweight From nfssext-cfr.

```
\newrobustcmd*{\LWR@HTML@ebweight}{\renewcommand*{\LWR@f@series}{eb}}
\LWR@formatted{ebweight}
```

\lgweight From nfssext-cfr.

```
\newrobustcmd*{\LWR@HTML@lgweight}{\renewcommand*{\LWR@f@series}{lg}}
\LWR@formatted{lgweight}
```

\rmfamily

```
\newrobustcmd*{\LWR@HTML@rmfamily}{\renewcommand*{\LWR@f@family}{rm}}
\LWR@formatted{rmfamily}
```

\sffamily

```
\newrobustcmd*{\LWR@HTML@sffamily}{\renewcommand*{\LWR@f@family}{sf}}
\LWR@formatted{sffamily}
```

\ttfamily

```
\newrobustcmd*{\LWR@HTML@ttfamily}{\renewcommand*{\LWR@f@family}{tt}}
\LWR@formatted{ttfamily}
```

\upshape

```
\newrobustcmd*{\LWR@HTML@upshape}{\renewcommand*{\LWR@f@shape}{up}}
\LWR@formatted{upshape}
```

\itshape

```
\newrobustcmd*{\LWR@HTML@itshape}{\renewcommand*{\LWR@f@shape}{it}}
\LWR@formatted{itshape}
```

\scshape

```
\newrobustcmd*{\LWR@HTML@scshape}{\renewcommand*{\LWR@f@shapecaps}{sc}}
\LWR@formatted{scshape}
```

\ulcshape From fontaxes.

```
\@ifundefined{ulcshape}{
    \LetLtxMacro\ulcshape\upshape
}{}
\newrobustcmd*{\LWR@HTML@ulcshape}{\renewcommand*{\LWR@f@shapecaps}{ulc}}
\LWR@formatted{ulcshape}
```

\sishape

```
\@ifundefined{sishape}{
    \LetLtxMacro\sishape\scshape
}{}
\newrobustcmd*{\LWR@HTML@sishape}{%
    \renewcommand*{\LWR@f@shape}{it}
    \renewcommand*{\LWR@f@shapecaps}{sc}%
}
\LWR@formatted{sishape}
```

\slshape

```
\newrobustcmd*{\LWR@HTML@slshape}{\renewcommand*{\LWR@f@shape}{sl}}
\LWR@formatted{slshape}
```

`\normalfont`

```
11252 \renewrobustcmd*{\normalfont}{\rmfamily\mdseries\upshape\ulcshape}
```

`\sp` {⟨*text*⟩}

For siunitx. Must work in math mode.

```
11253 \renewcommand{\sp}[1]{\text{<sup>#1</sup>}{}}
```

`\sb` {⟨*text*⟩}

For siunitx. Must work in math mode.

```
11254 \renewcommand{\sb}[1]{\text{<sub>#1</sub>}{}}
```

`\textsuperscript` {⟨*text*⟩}

```
11255 \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

`\@textsuperscript` {⟨*text*⟩}

```
11256 \renewcommand{\@textsuperscript}[1]{\LWR@htmlspan{sup}{#1}}
```

`\textsubscript` {⟨*text*⟩}

```
11257 \AtBeginDocument{
11258 \renewrobustcmd{\textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
11259 }
```

`\@textsubscript` {⟨*text*⟩}

```
11260 \AtBeginDocument{
11261 \renewcommand{\@textsubscript}[1]{\LWR@htmlspan{sub}{#1}}
11262 }
```

`\up` {⟨*text*⟩} Prints superscript.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
11263 \AtBeginDocument{\let\up\textsuperscript}
```

`\fup` {⟨*text*⟩} Prints superscript.

Supports fmtcount package.

This is `\let` at the beginning of the document in case some other package has changed the definition.

```
11264 \AtBeginDocument{\let\fup\textsuperscript}
```

\underline {⟨*text*⟩}

```
\renewcommand{\underline}[1]{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {underline}{#1}%
}
```

\LWR@overline {⟨*text*⟩}

```
\newcommand{\LWR@overline}[1]{%
    \InlineClass%
        (text-decoration:overline; text-decoration-skip: auto)%
        {overline}{#1}%
}
```

\LWR@currenttextcolor The color to use for text and \rule, defaulting to black:

```
\newcommand*{\LWR@currenttextcolor}{black}
```

\LWR@tempcolor
\LWR@tempcolortwo The color converted to HTML colorspace.

```
\newcommand*{\LWR@tempcolor}{}
\newcommand*{\LWR@tempcolortwo}{}
```

\LWR@findcurrenttextcolor Sets \LWR@tempcolor to the current color.

```
\newcommand*{\LWR@findcurrenttextcolor}{%
\renewcommand{\LWR@tempcolor}{000000}%
}
```

\LWR@textcurrentcolor {⟨*text*⟩} Like \textcolor but uses the current \color instead.

```
\NewDocumentCommand{\LWR@textcurrentcolor}{m}{%
    \renewcommand*{\LWR@currenttextcolor}{black}%
    #1%
}
```

```
\end{warpHTML}
```

for PRINT output:

```
\begin{warpprint}
```

\LWR@textcurrentfont {⟨*text*⟩}

Prints the text with the current font choices.

```
\newcommand*{\LWR@textcurrentfont}[1]{#1}
```

Env LWR@blocktextcurrentfont Prints the contents with the current font choices.

```
\newenvironment*{LWR@blocktextcurrentfont}{}{}
```

\FilenameNullify {⟨*macros to nullify*⟩}

```
\newcommand*{\FilenameNullify}[1]{}
```

```
\end{warpprint}
```

91 Skips, spaces, font sizes

for HTML output:

```
\begin{warpHTML}
```

\, and \thinspace may be redefined by other packages, so are redefined \AtBeginDocument here.

Direct-formatting space commands become HTML entities:

```
\AtBeginDocument{
\renewrobustcmd*{\,}{\HTMLunicode{202f}} % HTML thin non-breakable space
\renewrobustcmd*{\thinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{\negthinspace}{\HTMLunicode{202f}}   % HTML thin non-breakable space
\renewrobustcmd*{~}{\HTMLentity{nbsp}}
\renewrobustcmd*{\textellipsis}{\HTMLunicode{2026}}
}
```

Direct-formatting font sizes are ignored:

```
\newrobustcmd*{\LWR@HTML@normalsize}{}
\LWR@formatted{normalsize}

\newrobustcmd*{\LWR@HTML@small}{}
\LWR@formatted{small}

\newrobustcmd*{\LWR@HTML@footnotesize}{}
\LWR@formatted{footnotesize}

\newrobustcmd*{\LWR@HTML@scriptsize}{}
\LWR@formatted{scriptsize}

\newrobustcmd*{\LWR@HTML@tiny}{}
\LWR@formatted{tiny}

\newrobustcmd*{\LWR@HTML@large}{}
\LWR@formatted{large}

\newrobustcmd*{\LWR@HTML@Large}{}
\LWR@formatted{Large}

\newrobustcmd*{\LWR@HTML@LARGE}{}
\LWR@formatted{LARGE}

\newrobustcmd*{\LWR@HTML@huge}{}
\LWR@formatted{huge}
```

```
\newrobustcmd*{\LWR@HTML@Huge}{}
\LWR@formatted{Huge}


\DeclareDocumentCommand{\onecolumn}{}{}

\DeclareDocumentCommand{\twocolumn}{O{}}{
#1
}
```

\hfill

```
\newcommand*{\LWR@HTML@hfill}{\qquad}
\LWR@formatted{hfill}
```

\hrulefill

```
\newcommand*{\LWR@HTML@hrulefill}{\rule{1in}{1pt}}
\LWR@formatted{hrulefill}
```

\dotfill

```
\newcommand*{\LWR@HTML@dotfill}{\dots}
\LWR@formatted{dotfill}
```

\newpage

```
\renewcommand*{\newpage}{
}
```

\newline Uses the HTML <br /> element.

```
\newrobustcmd*{\LWR@newlinebr}{\unskip\LWR@htmltag{br /}\LWR@orignewline}%
\LetLtxMacro\newline\LWR@newlinebr
```

\\ Redefined to \LWR@endofline or \LWR@tabularendofline.

\LWR@endofline * [⟨*len*⟩]

\\ is assigned to \LWR@endofline at \LWR@LwarpStart.

Inside tabular, \\ is temporarily changed to \LWR@tabularendofline.

```
\LetLtxMacro\LWR@origendofline\\
\NewDocumentCommand{\LWR@endofline}{s O{0pt}}
{%
\newline%
```

```
\setlength{\LWR@templengthone}{#2}%
\ifdimgreater{\LWR@templengthone}{0pt}{\newline}{}%
}
```

\LWR@minipagestartpars Minipages are often placed side-by-side inside figures, with a bit of horizontal space to separate them. Since HTML does not allow a to be inside a p, paragraphs must be turned off during the generation of the minipage, then turned on after the minipage is complete. When this occurs between side-by-side minipages, lwarp correctly suppresses the paragraph tags between the minipages, unless some other text is between the minipages. Such text forms its own paragraph, resulting in text after a minipage to be on its own line. Since people often place small horizontal space between minipages, it is desirable to maintain this space if possible. lwarp tries to do this by remembering that a minipage has been seen, in which case paragraph tags are suppressed around \hspace, \enskip, \quad, and \qquad until the end of the paragraph, when the closing p tag is created.

\hspace
\enskip
\quad
\qquad

When a minipage is seen, the boolean LWR@minipagethispar is set, telling the following horizontal whitespace commands to try to suppress their surrounding paragraph tags. LWR@minipagethispar is cleared at the next end of paragraph, when the HTML paragraph closing tag is generated.

Placed just before \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestartpars}{%
\ifbool{LWR@minipagethispar}{\LWR@startpars}{}%
}
```

\LWR@minipagestoppars Placed just after \hspace, \quad, or \qquad's HTML output.

```
\newcommand*{\LWR@minipagestoppars}{%
\ifbool{LWR@minipagethispar}{\LWR@stoppars}{}%
}
```

\quad Handles special minipage & horizontal space interactions. Uses 2003 EM SPACE to pass validation.

```
\renewrobustcmd*{\quad}{%
\LWR@minipagestoppars%
\HTMLunicode{2003}%
\LWR@minipagestartpars%
}
```

\qquad Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\qquad}{\quad\quad}
```

\enskip Handles special minipage & horizontal space interactions.

```
\renewrobustcmd*{\enskip}{%
\LWR@minipagestoppars%
\HTMLunicode{2002}%
```

```
\LWR@minipagestartpars%
}
```

Len \LWR@tempwidth
Len \LWR@tempheight
Len \LWR@tempraise

Used to compute span width, height, raise for \hspace and \rule:

```
\newlength{\LWR@tempwidth}
\newlength{\LWR@tempheight}
\newlength{\LWR@tempraise}
```

\LWR@select@html@hspace
\hspace

* {⟨*length*⟩} * {⟨*length*⟩}

Handles special minipage & horizontal space interactions.

Prints a span of a given width. Ignores the optional star.

\hspace{\fill} is converted to \hspace{2em}, equal to \qquad.

```
\newcommand{\LWR@select@html@hspace}{%
\RenewDocumentCommand{\hspace}{s m}{%
\setlength{\LWR@tempwidth}{##2}%
```

If \fill, change to \qquad:

```
\ifnum\gluestretchorder\LWR@tempwidth>0%
\setlength{\LWR@tempwidth}{2em}%
\fi%
```

Only if the width is not zero:

```
\ifdimcomp{\LWR@tempwidth}{=}{0pt}{}{%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Support the HTML thin wrappable space:

```
    \ifdimcomp{\LWR@tempwidth}{=}{.16667em}%
    {%
        \HTMLunicode{2009}% thin breakable space
    }%
```

Print the span with the converted width. Not rounded.

```
    {%
        \LWR@htmltagc{%
            span style="width:\LWR@printlength{\LWR@tempwidth};  % extra space
                display:inline-block"%
        }%
```

If formatting for a word processor, approximate with a number of \quads, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \quad%
                \addtolength{\LWR@templengthone}{-1em}%
            }%
        }{}%
```

Close the span:

```
        \LWR@htmltagc{/span}%
    }%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestartpars%
}% width not 0
}%
}
```

\LWR@select@html@nohspace * {⟨*length*⟩}
\hspace

Used to disable \hspace while creating description \items.

```
\newcommand{\LWR@select@html@nohspace}{%
    \RenewDocumentCommand{\hspace}{s m}{}%
}
```

\LWR@select@print@hspace

```
\newcommand*{\LWR@select@print@hspace}{%
    \renewrobustcmd\hspace{\@ifstar\@hspacer\@hspace}%
}
```

\hspace * {⟨*length*⟩}

Handles special minipage & horizontal space interactions.

```
\LWR@select@html@hspace
```

\LWR@vspace * {⟨*length*⟩} Nullified vspace.

```
\NewDocumentCommand{\LWR@HTML@vspace}{s m}{}

\LWR@formatted{vspace}
```

\linebreak [⟨*num*⟩] Inserts an HTML br tag.

```
11413 \renewcommand*{\linebreak}[1][]{\newline}
```

`\nolinebreak` `[`⟨*num*⟩`]`

```
11414 \renewcommand*{\nolinebreak}[1][]{}
```

`\pagebreak` `[`⟨*num*⟩`]` Starts a new paragraph.

```
11415 \renewcommand*{\pagebreak}[1][]{
11416
11417 }
```

`\nopagebreak` `[`⟨*num*⟩`]`

```
11418 \renewcommand*{\nopagebreak}[1][]{}
```

`\enlargethispage` `*` `{`⟨*len*⟩`}`

```
11419 \RenewDocumentCommand{\enlargethispage}{s m}{}
```

`\clearpage`
`\cleardoublepage`

```
11420 \renewcommand*{\clearpage}{}
11421 \renewcommand*{\cleardoublepage}{}
```

`\rule` `[`⟨*raise*⟩`]` `{`⟨*width*⟩`}` `{`⟨*height*⟩`}`

Handles special minipage & horizontal space interactions.

Creates a span of a given width and height. Ignores the optional star.

`\fill` is zero-width, so `\hspace{\fill}` is ignored.

```
11422 \newcommand*{\LWR@HTML@rule}[3][]{%
```

The width is copied into a temporary LaTeX length, from which comparisons and conversions may be made:

```
11423 \setlength{\LWR@tempwidth}{#2}%
```

If it's zero-width then skip the entire rule:

```
11424 \ifthenelse{\lengthtest{\LWR@tempwidth=0pt}}%
11425 {}% zero- width
11426 {% non-zero width
```

If it's non-zero width, set a minimal thickness so that it more reliably shows in the browser:

```
11427     \ifthenelse{%
```

```
        \lengthtest{\LWR@tempwidth>0pt}\AND%
        \lengthtest{\LWR@tempwidth<1pt}%
    }%
        {\setlength{\LWR@tempwidth}{1pt}}%
        {}%
```

Likewise with height:

```
    \setlength{\LWR@tempheight}{#3}%
    \ifthenelse{%
        \lengthtest{\LWR@tempheight>0pt}\AND%
        \lengthtest{\LWR@tempheight<1pt}%
    }%
        {\setlength{\LWR@tempheight}{1pt}}%
        {}%
```

If had a minipage this paragraph, try to inline the rule without generating paragraph tags:

```
    \LWR@minipagestoppars%
```

Print the span with the converted width and height. The width and height are NOT rounded, since a height of less than 1pt is quite common in LaTeX code.

```
    \LWR@findcurrenttextcolor%
    \LWR@htmltagc{%
    span\LWR@indentHTML%
    style="%
```

The background color is used to draw the filled rule. The color may be changed by `\textcolor`.

```
    \ifbool{FormatWP}{}{background:\LWR@currenttextcolor ; }%
```

The width and height are printed, converted to PT:

```
    width:\LWR@printlength{\LWR@tempwidth} ; %
    height:\LWR@printlength{\LWR@tempheight} ; %
```

The raise height is converted to a CSS transform. The `*2` raise multiplier is to approximately match HTML output's X height. Conversion to a LaTeX length allows a typical LaTeX expression to be used as an argument for the raise, whereas printing the raise argument directly to HTML output without conversion to a LaTeX length limits the allowable syntax. To do: A superior method would compute a ratio of LaTeX ex height, then print that to HTML with an ex unit.

```
    \ifblank{#1}%
    {}%
    {%
        \setlength{\LWR@tempraise}{0pt-#1}%
        \setlength{\LWR@tempraise}{\LWR@tempraise*2}%
        \LWR@indentHTML%
        -ms-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
```

```
        \LWR@indentHTML%
        -webkit-transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
        transform: translate(0pt,\LWR@printlength{\LWR@tempraise}); %
        \LWR@indentHTML%
    }%
```

Display inline-block to place the span inline with the text:

```
    display:inline-block;"\LWR@orignewline%
    }%
```

If formatting for a word processor, approximate with a number of underscores, in case a span of a given width is not supported:

```
        \ifbool{FormatWP}{%
            \setlength{\LWR@templengthone}{\LWR@tempwidth}%
            \whiledo{\lengthtest{\LWR@templengthone>1em}}{%
                \_{}%
                \addtolength{\LWR@templengthone}{-1em}%
            }%
        }{}%
```

Close the span:

```
    \LWR@htmltagc{/span}%
```

If had a minipage this paragraph, try to inline the white space without generating paragraph tags:

```
    \LWR@minipagestartpars%
}% non-zero width
}

\LWR@formatted{rule}

\end{warpHTML}
```

92 \phantomsection

for HTML output:

```
\begin{warpHTML}
```

\phantomsection Emulate the hyperref \phantomsection command, often used to insert the bibliography into the table of contents. Ignores \ForceHTMLTOC.

```
\DeclareDocumentCommand{\phantomsection}{}{%
\begingroup%
\boolfalse{LWR@forcinghtmltoc}%
\section*{}%
\endgroup%
}
```

```
\end{warpHTML}
```

93 \LaTeX and other logos

Logos for HTML and print modes:

Some of these logos may be redefined in a later package, so after loading other packages, and at the beginning of the document, their definitions are finally set by \LWR@formatted.

For CSS conversions, see:
http://edward.oconnor.cx/2007/08/tex-poshlet
http://nitens.org/taraborelli/texlogo
and the spacing described in the metafont package documentation.

for HTML & PRINT:

```
\begin{warpall}
\newrobustcmd*{\Xe}
    {X\hspace{-.1667em}\raisebox{-.5ex}{E}}

\AtBeginDocument{
\@ifpackageloaded{graphics}{
    \@ifpackageloaded{metalogo}{}{
        \renewrobustcmd*{\Xe}
            {X\hspace{-.1667em}\raisebox{-.5ex}{\reflectbox{E}}}
    }
}{
    \PackageWarningNoLine{lwarp}{Load graphicx or graphics
        for improved XeTeX logo}
}
}

\providerobustcmd*{\XeTeX}{\mbox{\Xe\hspace{-.125em}\TeX}}
\providerobustcmd*{\XeLaTeX}{\mbox{\Xe\hspace{-.125em}\LaTeX}}
\providerobustcmd*{\AmS}{%
    \leavevmode\hbox{$\mathcal A\kern-.2em\lower.376ex%
    \hbox{$\mathcal M$}\kern-.2em\mathcal S$}%
}
\newrobustcmd*{\LyX}{\textsf{LyX}}
\providerobustcmd*{\LuaTeX}{\mbox{Lua\TeX}}
\providerobustcmd*{\LuaLaTeX}{\mbox{Lua\LaTeX}}
\providerobustcmd*{\BibTeX}{\mbox{B\textsc{ib}\TeX}}
\providerobustcmd*{\MakeIndex}{\mbox{\textit{MakeIndex}}}
\providerobustcmd*{\ConTeXt}{\mbox{Con\TeX{}t}}
\providerobustcmd*{\MiKTeX}{\mbox{MiK\TeX}}
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

The print-mode versions of the following may be changed by metalogo, so their print formatting is recorded \AtBeginDocument.

\TeX TEX

latexlogo is a css class used to properly typeset the E and A in LATEX and friends.

latexlogofont is a css class used to select the font for the rest of the logo in LATEX, LuaTEX, ConTEXt, etc.

```
\newrobustcmd*{\LWR@HTML@TeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
}
\AtBeginDocument{\LWR@formatted{TeX}}% may have been patched by metalogo
```

\LaTeX LATEX, LATEX 2ε
\LaTeXe

```
\newrobustcmd*{\LWR@HTML@LaTeX}
{%
    \InlineClass{latexlogofont}%
    {%
        \InlineClass{latexlogo}%
        {%
            L%
            \InlineClass{latexlogosup}{a}%
            T%
            \InlineClass{latexlogosub}{e}%
            X%
        }%
    }%
}

\AtBeginDocument{\LWR@formatted{LaTeX}}% may have been patched by metalogo


\newrobustcmd*{\LWR@HTML@LaTeXe}
{%
    \LaTeX%
    \InlineClass{latexlogofont}{%
        \InlineClass{latexlogotwoe}{%
            2%
            \InlineClass{latexlogotwoesub}{\HTMLunicode{03B5}}%
        }%
    }%
}
\AtBeginDocument{\LWR@formatted{LaTeXe}}% may have been patched by metalogo
```

\LuaTeX \LuaLaTeX LuaTeX, LuaLaTeX

```
\newrobustcmd*{\LWR@HTML@LuaTeX}{\InlineClass{latexlogofont}{Lua}\TeX}
\AtBeginDocument{\LWR@formatted{LuaTeX}}% may have been patched by metalogo

\newrobustcmd*{\LWR@HTML@LuaLaTeX}{\InlineClass{latexlogofont}{Lua}\LaTeX}
\AtBeginDocument{\LWR@formatted{LuaLaTeX}}% may have been patched by metalogo
```

\XeTeX \XeLaTeX XeTeX, XeLaTeX

xetexlogo is a css class which aligns the backwards E in XeTeX and spaces TeX appropriately.

xelatexlogo is a css class which aligns the backwards E in XeLaTeX and spaces LaTeX appropriately.

```
\newrobustcmd*{\LWR@HTML@Xe}
    {%
        X%
        \InlineClass{xelatexlogosub}{\HTMLunicode{18e}}%
    }
\AtBeginDocument{\LWR@formatted{Xe}}% may have been patched by metalogo

\newrobustcmd*{\LWR@HTML@XeTeX}{\InlineClass{xelatexlogo}{\Xe}\TeX}
\AtBeginDocument{\LWR@formatted{XeTeX}}% may have been patched by metalogo

\newrobustcmd*{\LWR@HTML@XeLaTeX}{\InlineClass{xelatexlogo}{\Xe}\LaTeX}
\AtBeginDocument{\LWR@formatted{XeLaTeX}}% may have been patched by metalogo
```

\ConTeXt ConTeXt

```
\newrobustcmd*{\LWR@HTML@ConTeXt}{%
    \InlineClass{latexlogofont}{Con}\TeX{}%
    \InlineClass{latexlogofont}{t}%
}
\LWR@formatted{ConTeXt}
```

\BibTeX \MakeIndex BibTeX, *MakeIndex*

```
\newrobustcmd*{\LWR@HTML@BibTeX}
    {\InlineClass{latexlogofont}{B\textsc{ib}}\TeX}
\LWR@formatted{BibTeX}

\newrobustcmd*{\LWR@HTML@MakeIndex}
    {\InlineClass{latexlogofont}{\textit{MakeIndex}}}
\LWR@formatted{MakeIndex}
```

\AmS $\mathcal{AMS}$

amslogo is a css class used for the $\mathcal{AMS}$ logo.

```
\AtBeginDocument{%
```

```
\newrobustcmd*{\LWR@HTML@AmS}
{%
    \InlineClass{amslogo}{%
        \textit{%
            A%
            \InlineClass{latexlogosub}{M}%
            S%
        }%
    }%
}%
\LWR@formatted{AmS}
}
```

\MiKTeX MiKTEX

```
\newrobustcmd*{\LWR@HTML@MiKTeX}{\InlineClass{latexlogofont}{MiK}\TeX}
\LWR@formatted{MiKTeX}
```

\LyX LyX

lyxlogo is a css class used for the LyX logo.

```
\newrobustcmd*{\LWR@HTML@LyX}{\InlineClass{lyxlogo}{LyX}}
\LWR@formatted{LyX}
```

```
\end{warpHTML}
```

94 \AtBeginDocument, \AtEndDocument

for HTML output:

```
\begin{warpHTML}
```

\LWR@LwarpStart
\LWR@LwarpEnd

Automatically sets up the HTML-related actions for the start and end of the document.

```
\AfterEndPreamble{\LWR@LwarpStart}
\AtEndDocument{\LWR@LwarpEnd}
```

```
\end{warpHTML}
```

95 Loading KOMA-SCRIPT class patches

Load patches to koma-script.

for HTML output:

```
\begin{warpHTML}
```

```
\@ifclassloaded{scrbook}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrartcl}{\RequirePackage{lwarp-patch-komascript}}{}
\@ifclassloaded{scrreprt}{\RequirePackage{lwarp-patch-komascript}}{}
```

```
\end{warpHTML}
```

96 Loading MEMOIR class patches

Load patches to memoir.

for HTML output:

```
\begin{warpHTML}
\@ifclassloaded{memoir}{\RequirePackage{lwarp-patch-memoir}}{}
\end{warpHTML}
```

97 ut* class patches

Load patches to uj* and ut* classes, as well as ltj* classes.

for HTML output:

```
\begin{warpHTML}
\newcommand*{\LWR@patchujtclasses}{
```

uj/t does not use \partname

```
    \def\@partnameformat{}

    \def\@partcntformat##1{%
        \prepartname%
        \csname the##1\endcsname%
        \postpartname%
        \quad%
    }
    \@ifundefined{chapter}{}{
        \def\@chapcntformat##1{%
            \prechaptername%
            \csname the##1\endcsname%
            \postchaptername%
            \quad%
        }
    }
```

Use decimal points instead of centered dots:

```
    \renewcommand{\thepart}{\@Roman\c@part}
    \@ifundefined{chapter}{
        \renewcommand{\thesection}{\@arabic\c@section}
    }{
        \renewcommand{\thechapter}{\@arabic\c@chapter}
        \renewcommand{\thesection}{\thechapter.\@arabic\c@section}
```

```
    }
    \renewcommand{\thesubsection}{\thesection.\@arabic\c@subsection}
    \renewcommand{\thesubsubsection}{%
    \thesubsection.\@arabic\c@subsubsection}
    \renewcommand{\theparagraph}{%
    \thesubsubsection.\@arabic\c@paragraph}
    \renewcommand{\thesubparagraph}{%
    \theparagraph.\@arabic\c@subparagraph}
    \@ifundefined{chapter}{
        \renewcommand{\thefigure}{\@arabic\c@figure}
        \renewcommand{\thetable}{\@arabic\c@table}
    }{
        \renewcommand{\thefigure}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@figure}
        \renewcommand{\thetable}{%
        \ifnum\c@chapter>\z@\thechapter.\fi\@arabic\c@table}
    }
}

\@ifclassloaded{ujarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ujreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{utarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{utbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{utreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjsreport}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjskiyou}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjspf}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtarticle}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtbook}{\LWR@patchujtclasses}{}
\@ifclassloaded{ltjtreport}{\LWR@patchujtclasses}{}

\end{warpHTML}
```

98 CTEX patches

Patches for ctex and related classes, which are loaded before lwarp.

All CTEX classes and the ctex package seem to load ctexpatch, so its presence is used to decide whether to have lwarp patch CTEX.

for HTML output:

```
\begin{warpHTML}
```

`\AtBeginDocument` in case the user set `FileSectionNames` in the preamble.

```
\AtBeginDocument{
    \@ifpackageloaded{ctexpatch}{%
```

```
        \def\@partcntformat#1{%
            \LWR@isolate{\CTEX@partname}~%
            \CTEX@part@aftername%
        }%

        \def\@partnameformat{}

        \def\@chapcntformat#1{%
            \LWR@isolate{\CTEX@chaptername}~%
            \CTEX@chapter@aftername%
        }%
    }{}
}
```

```
\end{warpHTML}
```

99 kotexutf patches

Patch for kotexutf, which is loaded before lwarp.

kotexutf's `\@setref` was conflicting with lwarp's cross references.

for HTML output:

```
\begin{warpHTML}
```

If kotexutf's version of `\@setref` is detected, it is reverted to the original.

```
\AtBeginDocument{
\@ifpackageloaded{kotexutf}{%
    \def\LWR@kotexutf@setref#1#2#3{%
        \@setref@dhucs@orig{#1}{#2}{#3}%
      \ifx#1\relax\else
        \bgroup
        \dhucs@make@cjkchar@null
        \edef\@temp{\expandafter#2#1}\global\josatoks\expandafter{\@temp}%
        \egroup
      \fi%
    }%

    \ifdefequal{\@setref}{\LWR@kotexutf@setref}{
        \let\@setref\@setref@dhucs@orig
    }{}
}{}
}
```

```
\end{warpHTML}
```

File 2 **lwarp-2in1.sty**

§ 100 Package 2in1

Pkg 2in1 2in1 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2in1}
```

File 3 **lwarp-2up.sty**

§ 101 Package 2up

Pkg 2up 2up is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{2up}[2010/05/15]

\def\source#1#2#3{}
\def\target#1#2#3{}
\def\targetlayout#1{}
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\def\twoupemptypage{}
\def\twoupclearpage{}
\def\twoupeject{}
\def\twouparticle{}
\def\twoupplain{}
\def\twouplegaltarget{}
\def\twouplandscape{}
\def\TwoupWrites{}
```

File 4 **lwarp-a4.sty**

§ 102 Package a4

Pkg a4 a4 is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4}[2004/04/15]

\newcommand*{\WideMargins}{}
```

File 5 **lwarp-a4wide.sty**

§ 103 Package a4wide

Pkg a4wide a4wide is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a4wide}[1994/08/30]
```

File 6 **lwarp-a5comb.sty**

§ 104 Package a5comb

Pkg a5comb a5comb is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{a5comb}
```

File 7 **lwarp-abstract.sty**

§ 105 Package abstract

(*Emulates or patches code by* Peter Wilson.)

Pkg abstract abstract is supported and patched by lwarp.

⚠ missing toc If using the `number` option with file splits, be sure to place the table of contents before the abstract. The `number` option causes a section break which may cause a file split, which would put a table of contents out of the home page if it is after the abstract.

for HTML output: memoir provides an `abstract` environment even though it is not an article or report class. Meanwhile, lwarp loads book to emulate memoir, but book does not have an `abstract` environment, so when the abstract package is loaded for emulation there is no pre-existing `abstract` to redefine, which would cause an error. Thus, a null `abstract` is provide here:

```
\ProvideDocumentEnvironment{abstract}{}{}{}
```

Accept all options for lwarp-abstract:

```
\LWR@ProvidesPackagePass{abstract}[2009/06/08]

\AtBeginDocument{
\BeforeBeginEnvironment{abstract}{
\LWR@forcenewpage
\BlockClass{abstract}
```

```
}
\AfterEndEnvironment{abstract}{\endBlockClass}
}

\renewcommand{\@bsrunintitle}{%
\hspace*{\abstitleskip}%
{\abstractnamefont%
\InlineClass{abstractrunintitle}{\abstractname}%
\@bslabeldelim}%
}

\@ifclassloaded{memoir}
{
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
          \end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
}{% not memoir
\if@titlepage
  \renewenvironment{abstract}{%
%     \titlepage
    \null\vfil
    \@beginparpenalty\@lowpenalty
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
          \begin{\absnamepos}%
  \abstractnamefont \BlockClassSingle{abstracttitle}{\abstractname}
            \@endparpenalty\@M
```

```
          \end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}\vfil\null%\endtitlepage
    }
\else
  \renewenvironment{abstract}{%
    \if@bsrunin
    \else
      \if@bsstyle
        \abstitlestyle{\BlockClassSingle{abstracttitle}{\abstractname}}
      \else
        \ifnumber@bs
          \num@bs
        \else
\begin{\absnamepos}%
\abstractnamefont\BlockClassSingle{abstracttitle}{\abstractname}%
\end\absnamepos%
%%        \vspace{\abstitleskip}%
        \fi
      \fi
      \vspace{\abstitleskip}%
    \fi
    \put@bsintoc%
    \begin{@bstr@ctlist}\if@bsrunin\@bsrunintitle\fi\abstracttextfont}%
    {\par\end{@bstr@ctlist}}
\fi
}% not memoir
```

File 8 **lwarp-academicons.sty**

§ 106 Package

academicons

(*Emulates or patches code by* Diogo A. B. Fernandes.)

Pkg academicons academicons is patched for use by lwarp.

If \aiicon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{academicons}[2018/06/27]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@academicons@orig@AI\AI

\newcommand*{\LWR@academicons@symbol}[1]{%
    \begin{lateximage}*[(academicon)][academicons#1]%
```

```
    \begingroup%
    \LWR@academicons@orig@AI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\AI}{%
    \LetLtxMacro\symbol\LWR@academicons@symbol%
}

\renewcommand*{\aiicon}[1]
{%
    \begin{lateximage}*[(#1 icon)][academicons#1]%
    \AI\csname aiicon@#1\endcsname%
    \end{lateximage}%
}
```

File 9 **lwarp-accsupp.sty**

§ 107 Package accsupp

Pkg accsupp accsupp is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{accsupp}[2018/03/28]

\newcommand*{\BeginAccSupp}[1]{}
\newcommand*{\EndAccSupp}[1]{}
```

File 10 **lwarp-acro.sty**

§ 108 Package acro

(*Emulates or patches code by* Clemens Niederberger.)

Pkg acro acro is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{acro}[2017/01/30]
```

\DeclareAcronym is used in the preamble, where lwarp has not yet made the dollar active, so temporarily enable lwarp math catcode just for this definition:

```
\ExplSyntaxOn
\NewDocumentCommand \LWR@DeclareAcronym {mm}
{
    \acro_declare_acronym:nn {#1} {#2}
    \catcode`\$=3% lwarp
}
\ExplSyntaxOff
```

```
\RenewDocumentCommand{\DeclareAcronym}{}{
    \catcode`\$=\active% lwarp
    \LWR@DeclareAcronym
}
```

Modified to activate the current font:

```
\ExplSyntaxOn
\cs_gset_protected:Npn \acro_write_short:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_short_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_alt:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_format_bool
        { \l__acro_custom_format_tl }
        { \l__acro_alt_format_tl }
      {\LWR@textcurrentfont{#2}}% lwarp
    \group_end:
  }

\cs_gset_protected:Npn \acro_write_long:nn #1#2
  {
    \mode_if_horizontal:F { \leavevmode }
    \group_begin:
      \bool_if:NTF \l__acro_custom_long_format_bool
        { \l__acro_custom_long_format_tl }
        { \use:n }
      {
        \use:x
          {
            \exp_not:n {#1}
            {
              \bool_if:NTF \l__acro_first_upper_bool
                { \exp_not:N \__acro_first_upper_case:n { \exp_not:n {
                    \LWR@textcurrentfont{#2}% lwarp
                } } }
                { \exp_not:n {\LWR@textcurrentfont{#2}} }% lwarp
            }
          }
      }
    \group_end:
  }
\ExplSyntaxOff
```

File 11 **lwarp-acronym.sty**

§ 109 Package

acronym

(*Emulates or patches code by* Tobias Oetiker.)

Pkg acronym acronym is patched for use by lwarp.

⚠ multiply-defined labels `\acresetall` does not work with cleveref, causing multiply-defined labels. lwarp patches acronym for HTML, but not for print mode.

for HTML output:

```
\LWR@ProvidesPackagePass{acronym}[2015/03/21]
```

Uses `\textit` instead of `\itshape`:

```
\renewcommand{\acfia}[1]{%
  {\textit{\AC@acl{#1}}} (\ifAC@starred\acs*{#1}\else\acs{#1}\fi)}
```

Removes the mbox to allow math inside:

```
\renewcommand*\AC@acs[1]{%
%     \mbox{
 \expandafter\AC@get\csname fn@#1\endcsname\@firstoftwo{#1}}
% }
```

Fix for acronym labels in the captions of floats.

```
\renewcommand{\@starttoc}[1]{
\LWR@htmlelementclass{nav}{#1}
\LetLtxMacro\@verridelabel\@gobble
\LWR@orig@starttoc{#1}
\LWR@htmlelementclassend{nav}{#1}
}
```

Modified for cleveref and lwarp:

```
\renewcommand*\AC@und@newl@bel[3]{%
    \@ifundefined{#1@#3}%
    {%
        \global\expandafter\let\csname#2@#3\endcsname\@nnil
        \global\expandafter\let\csname#2@#3@lwarp\endcsname\@nnil% lwarp
        \global\expandafter\let\csname#2@#3@cref\endcsname\@nnil% lwarp
    }%
    {%
        \global\expandafter\let\csname#1@#3\endcsname\relax
        \global\expandafter\let\csname#1@#3@lwarp\endcsname\relax% lwarp
        \global\expandafter\let\csname#1@#3@cref\endcsname\relax% lwarp
    }%
}%
```

File 12 **lwarp-adjmulticol.sty**

§ 110 Package

adjmulticol

(*Emulates or patches code by* Boris Veytsman.)

Pkg adjmulticol adjmulticol is emulated.

Emulation similar to multicols is used, with adjusted margins. If the number of columns is specified as 1, it is set so, but if two or greater are used, lwarp allows a variable number of columns up to three.

for HTML output:

```
\LWR@ProvidesPackageDrop{adjmulticol}[2012/01/20]
\RequirePackage{multicol}
```

adjmulticols * {⟨*numcols*⟩} {⟨*left margi*⟩} {⟨*right margin*⟩}

```
\NewDocumentEnvironment{adjmulticols}{s m m m}
{%
```

Compute the margins, and limit to positive only:

```
\setlength{\LWR@templengthone}{#3}%
\ifdimcomp{\LWR@templengthone}{<}{0pt}{\setlength{\LWR@templengthone}{0pt}}{}%
\setlength{\LWR@templengthtwo}{#4}
\ifdimcomp{\LWR@templengthtwo}{<}{0pt}{\setlength{\LWR@templengthtwo}{0pt}}{}%
```

If one column is specified, use a of class singlecolumn, else use multicols:

```
\newcommand*{\LWR@mcolstype}{multicols}%
\ifnumcomp{#2}{=}{1}{\renewcommand*{\LWR@mcolstype}{singlecolumn}}{}%
```

Help avoid page overflow:

```
\LWR@forcenewpage%
```

Create the with the given margin and class:

```
\BlockClass[%
\LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
\LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}%
]{\LWR@mcolstype}%
}
{\endBlockClass}
```

File 13 **lwarp-addlines.sty**

§ 111 Package addlines

(*Emulates or patches code by* Will Robertson.)

Pkg addlines addlines is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{addlines}[2018/12/05]

\newcommand\addlines{\@ifstar\addlines@a\addlines@a}
\newcommand\addlines@a[1][1]{}
\let\addline\addlines
\newcommand\removelines{\@ifstar\removelines@a\removelines@a}
\newcommand\removelines@a[1][1]{}
\let\removeline\removelines
\newcommand\squeezepage[1][0]{}
```

File 14 **lwarp-afterpage.sty**

§ 112 Package afterpage

(*Emulates or patches code by* David Carlisle.)

Pkg afterpage afterpage is emulated.

for HTML output: Discard all options for lwarp-afterpage:

```
\LWR@ProvidesPackageDrop{afterpage}[2014/10/28]

\newcommand{\afterpage}[1]{#1}
```

File 15 **lwarp-algorithm2e.sty**

§ 113 Package algorithm2e

(*Emulates or patches code by* Christophe Fiorio.)

Pkg algorithm2e algorithm2e is patched for use by lwarp.

For print output, captions are placed according to package options, but for HTML output captions are placed where used. Therefore, to have captions appear at the top of the algorithms for both print and HTML, place each captions at the top of each algorithm.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithm2e}[2017/07/18]
```

For the list-of entries:

```
\renewcommand{\l@algocf}[2]{\hypertocfloat{1}{algocf}{loa}{#1}{#2}}
```

Select the lwarp float style according to the algorithm2e style:

```
\newcommand*{\LWR@floatstyle@algocf}{ruled}

\ifdefstring{\algocf@style}{boxed}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxed}
}{}

\ifdefstring{\algocf@style}{boxruled}{%
\renewcommand*{\LWR@floatstyle@algocf}{boxruled}
}{}

\ifdefstring{\algocf@style}{plain}{%
\renewcommand*{\LWR@floatstyle@algocf}{plain}
}{}
```

Paragraph handling to allow line numbers under certain conditions:

```
\newbool{LWR@algocf@dopars}
\booltrue{LWR@algocf@dopars}

\renewcommand{\algocf@everypar}{%
\ifbool{LWR@algocf@dopars}{%
    \ifbool{LWR@doingstartpars}{%
        \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
            {}%
            {%
                \algocf@everyparnl\algocf@everyparhanging%
            }%
    }{}%
}{}%
}
```

lwarp caption handling:

```
\renewcommand{\algocf@makecaption}[2]{%
\LWR@HTML@caption@begin{algocf}%
\LWR@isolate{\algocf@captiontext{#1}{#2}}%
\LWR@HTML@caption@end%
}
```

Print any caption where it is declared:

```
\renewcommand{\algocf@makecaption@plain}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@boxed}[2]{%
    \LWR@HTML@caption@begin{algocf}%
```

```
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}

\renewcommand{\algocf@makecaption@ruled}[2]{%
    \LWR@HTML@caption@begin{algocf}%
    \LWR@isolate{\algocf@captiontext{#1}{#2}}%
    \LWR@HTML@caption@end%
}
```

Turn off line numbering while making the caption:

```
\long\def\algocf@latexcaption#1[#2]#3{% original definition of caption
\boolfalse{LWR@algocf@dopars}%  lwarp
  \par%
  \addcontentsline{\csname ext@#1\endcsname}{#1}%
 {\protect\numberline{\csname the#1\endcsname}{\ignorespaces \LWR@isolate{#2}}}%
  \begingroup%
  \@parboxrestore%
  \if@minipage%
    \@setminipage%
  \fi%
  \normalsize%
  \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par%
  \endgroup%
\booltrue{LWR@algocf@dopars}%   lwarp
}
```

Line numbers are printed in a of class alg2elinenumber:

```
\renewcommand{\algocf@printnl}[1]{%
    \InlineClass{alg2elinenumber}{\NlSty{#1}}~%
}%
```

While initializing an algorithm environment, locally declare the style of a regular figure to be the same as the algorithm style, in case the figure option was used.

```
\preto\@algocf@init{%
  \edef\LWR@floatstyle@figure{\LWR@floatstyle@algocf}%
}
```

For lwarp, the algorithm is not assembled inside a box, since lateximages would not work, so the captions are printed where declared.

```
\renewcommand{\@algocf@start}{%
    \let\@mathsemicolon=\;\def\;{\ifmmode\@mathsemicolon\else\@endalgoln\fi}%
%     \raggedright%
    \AlFnt{}%
    \booltrue{LWR@algocf@dopars}% lwarp
}

\renewcommand{\@algocf@finish}{%
    \boolfalse{LWR@algocf@dopars}% lwarp
    \lineskip\normallineskip\setlength{\skiptotal}{\@defaultskiptotal}%
```

```
    \let\;=\@mathsemicolon%
    \let\]=\@emathdisplay%
}
```

Use an HTML break:

```
\renewcommand{\BlankLine}{%
\LWR@stoppars%
\LWR@htmltagc{br /}%
\LWR@startpars%
}
```

Simplified for HTML. The paragraph handling must be preserved.

```
\renewcommand{\SetKwInOut}[2]{%
  \algocf@newcommand{#1}[1]{%
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@seteveryparhanging{\relax}}%
    \ifthenelse{\boolean{algocf@inoutnumbered}}%
        {\relax}%
        {\algocf@seteveryparnl{\relax}}%
    {%
            \KwSty{#2\algocf@typo:}%
        ~##1\par%
    }%
    \algocf@linesnumbered% reset the numbering of the lines
    \ifthenelse{\boolean{algocf@hanginginout}}%
        {\relax}%
        {\algocf@reseteveryparhanging}%
  }%
}%

\renewcommand{\ResetInOut}[1]{}%
```

Each of the following creates a of a given class, and turns off line numbering while creating the tags:

```
\renewcommand{\algocf@Vline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2evline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
\booltrue{LWR@algocf@dopars}%
}

\renewcommand{\algocf@Vsline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2evsline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
```

```
\booltrue{LWR@algocf@dopars}%
}

\renewcommand{\algocf@Noline}[1]{%
\boolfalse{LWR@algocf@dopars}%
\begin{BlockClass}{alg2enoline}
\booltrue{LWR@algocf@dopars}%
#1
\boolfalse{LWR@algocf@dopars}%
\end{BlockClass}
\booltrue{LWR@algocf@dopars}%
}
```

The [H] environment is converted to a regular float, which in HTML is placed where declared. Reusing the regular float allows the [H] version to reuse the ruled and boxed options.

```
\LetLtxMacro\algocf@Here\algocf
\LetLtxMacro\endalgocf@Here\endalgocf
```

File 16 **lwarp-algorithmicx.sty**

§ 114 Package algorithmicx

(*Emulates or patches code by* Szász János.)

Pkg algorithmicx algorithmicx is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{algorithmicx}[2005/04/27]
```

Inside the algorithmic environment, level indenting is converted to a of the required length, and comments are placed inside a which is floated right.

⚠ package conflicts If using \newfloat, trivfloat, and/or algorithmicx together, see section 486.1.

for HTML output:

```
\begin{warpHTML}

\AtBeginEnvironment{algorithmic}{%
%
\let\origALG@doentity\ALG@doentity%
%
\renewcommand*{\ALG@doentity}{%
\origALG@doentity%
\LWR@htmltagc{%
span style="width:\LWR@printlength{\ALG@thistlm}; display:inline-block;"%
}%
\ifbool{FormatWP}{%
\setlength{\LWR@templengthone}{\the\ALG@thistlm}%
\whiledo{\lengthtest{\LWR@templengthone>1em}}{%
\quad%
\addtolength{\LWR@templengthone}{-1em}%
}%
```

```
}{}%
\LWR@htmltagc{/span}%
}%

\let\LWR@origComment\Comment%

\renewcommand{\Comment}[1]{%
    \InlineClass{floatright}{\LWR@origComment{#1}}%
}%
}

\renewcommand\algorithmiccomment[1]{%
\hfill\HTMLunicode{25B7} #1% white right triangle
}%

\end{warpHTML}
```

File 17 **lwarp-alltt.sty**

§ 115 Package alltt

(*Emulates or patches code by* Johannes Braams.)

Pkg alltt alltt is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{alltt}[1997/06/16]

\AfterEndPreamble{
\LWR@traceinfo{Patching alltt.}
\AtBeginEnvironment{alltt}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{alltt}%
}
\AfterEndEnvironment{alltt}{%
    \LWR@afterendverbatim{2}%
}
}
```

File 18 **lwarp-amsmath.sty**

§ 116 Package amsmath

(*Emulates or patches code by* American Mathematical Society, LaTeX3 Project.)

Pkg amsmath amsmath is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{amsmath}[2017/09/02]
```

Patches to allow `\eqref` inside a caption:

```
\def\maketag@@@#1{\text{#1}}
\def\tagform@#1{\maketag@@@{(\ignorespaces#1\unskip)}}
```

Patches for $\mathcal{AMS}$ math \tag macro to remember the first tag:

```
\ifbool{mathjax}{}{% not mathjax

\LetLtxMacro\LWR@origmake@df@tag@@\make@df@tag@@
\LetLtxMacro\LWR@origmake@df@tag@@@\make@df@tag@@@

\renewcommand*{\make@df@tag@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@{#1}%
}

\renewcommand*{\make@df@tag@@@}[1]{%
\LWR@remembertag{#1}%
\LWR@origmake@df@tag@@@{#1}%
}

}% not mathjax
```

The following $\mathcal{AMS}$ environments are patched in-place:

\LWR@amsmathenv@@before {⟨*environment name*⟩}

Embeds the environment inside a lateximage.

```
\newcommand*{\LWR@amsmathenv@@before}[1]{%
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[\LWR@amsmathbodynumbered{#1}]
    \LWR@applyxfakebold%
}
```

\LWR@amsmathenv@before {⟨*environment name*⟩}

Embeds the environment with MathJax or a lateximage.

```
\newcommand*{\LWR@amsmathenv@before}[1]{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {
        \LWR@syncmathjax
        \boolfalse{LWR@amsmultline}
        \ifstrequal{#1}{multline}{\booltrue{LWR@amsmultline}}{}
        \ifstrequal{#1}{multline*}{\booltrue{LWR@amsmultline}}{}
```

autonum's "+" environments are not supported by MathJax.

```
        \LWR@beginhideamsmath
    }
    {
        \LWR@amsmathenv@@before{multline}
    }
}
```

\LWR@amsmathenv@@after

Embeds the environment inside a lateximage.

```
\newcommand*{\LWR@amsmathenv@@after}{%
    \end{lateximage}\end{BlockClass}
}
```

\LWR@amsmathenv@after {⟨*environment name*⟩}

Embeds the environment with MathJax or a lateximage.

```
\newcommand*{\LWR@amsmathenv@after}[1]{%
    \ifboolexpr{bool{mathjax} or ( bool{FormatWP} and bool{WPMarkMath} ) }%
    {
        \LWR@endhideamsmath
        \boolfalse{LWR@amsmultline}
        \LWR@addmathjax{#1}{\the\@envbody}
    }
    {\LWR@amsmathenv@@after}
}
```

Env multline

```
\BeforeBeginEnvironment{multline}{\LWR@amsmathenv@before{multline}}

\AfterEndEnvironment{multline}{\LWR@amsmathenv@after{multline}}
```

Env multline*

```
\BeforeBeginEnvironment{multline*}{\LWR@amsmathenv@before{multline*}}

\AfterEndEnvironment{multline*}{\LWR@amsmathenv@after{multline*}}

```

Env gather

```
\BeforeBeginEnvironment{gather}{\LWR@amsmathenv@before{gather}}

\AfterEndEnvironment{gather}{\LWR@amsmathenv@after{gather}}
```

Env gather*

```
\BeforeBeginEnvironment{gather*}{\LWR@amsmathenv@before{gather*}}

\AfterEndEnvironment{gather*}{\LWR@amsmathenv@after{gather*}}
```

Env align

```
\BeforeBeginEnvironment{align}{\LWR@amsmathenv@before{align}}

\AfterEndEnvironment{align}{\LWR@amsmathenv@after{align}}
```

Env align*

```
\BeforeBeginEnvironment{align*}{\LWR@amsmathenv@before{align*}}

\AfterEndEnvironment{align*}{\LWR@amsmathenv@after{align*}}
```

Env flalign

```
\BeforeBeginEnvironment{flalign}{\LWR@amsmathenv@before{flalign}}

\AfterEndEnvironment{flalign}{\LWR@amsmathenv@after{flalign}}
```

Env flalign*

```
\BeforeBeginEnvironment{flalign*}{\LWR@amsmathenv@before{flalign*}}

\AfterEndEnvironment{flalign*}{\LWR@amsmathenv@after{flalign*}}
```

Env alignat

```
\BeforeBeginEnvironment{alignat}{\LWR@amsmathenv@before{alignat}}

\AfterEndEnvironment{alignat}{\LWR@amsmathenv@after{alignat}}
```

Env alignat*

```
\BeforeBeginEnvironment{alignat*}{\LWR@amsmathenv@before{alignat*}}

\AfterEndEnvironment{alignat*}{\LWR@amsmathenv@after{alignat*}}
```

File 19 **lwarp-amsthm.sty**

§ 117 Package

amsthm

(*Emulates or patches code by* Publications Technical Group — American Mathematical Society.)

The original source code is located in amsclass.dtx, and printed in amsclass.pdf.

Pkg amsthm amsthm is patched for use by lwarp.

for HTML output: amsthm must be loaded before mdframed:

```
\@ifpackageloaded{mdframed}{
    \PackageError{lwarp}
    {Package mdframed must be loaded after package amsthm}
    {%
        Move \detokenize{\usepackage}{amsthm} before
        \detokenize{\usepackage}{mdframed}.\MessageBreak
        Package amsthm may be loaded by something else,\MessageBreak
        which must also be moved before mdframed.%
```

Table 14: amsthm package — css styling of theorems and proofs

Theorem: of class amsthmbody<theoremstyle>

Theorem Name: of class amsthmname<theoremtyle>

Theorem Number: of class amsthmnumber<theoremstyle>

Theorem Note: of class amsthmnote<theoremstyle>

Proof: of class amsthmproof

Proof Name: of class amsthmproofname

where <theoremstyle> is plain, definition, etc.

```
    }
}
{}

\LWR@ProvidesPackagePass{amsthm}[2017/10/31]
```

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\renewcommand{\theoremstyle}[1]{%
  \@ifundefined{th@#1}{%
    \PackageWarning{amsthm}{Unknown theoremstyle `#1'}%
    \thm@style{plain}%
    \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
  }{%
    \thm@style{#1}%
    \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
  }%
}
```

Patched to remember the style for this theorem type:

```
\def\@xnthm#1#2{%
  \csedef{LWR@thmstyle#2}{\LWR@newtheoremstyle}% lwarp
  \let\@tempa\relax
  \@xp\@ifdefinable\csname #2\endcsname{%
    \global\@xp\let\csname end#2\endcsname\@endtheorem
    \ifx *#1% unnumbered, need to get one more mandatory arg
      \edef\@tempa##1{%
        \gdef\@xp\@nx\csname#2\endcsname{%
          \@nx\@thm{\@xp\@nx\csname th@\the\thm@style\endcsname}%
            {}{##1}}}%
    \else % numbered theorem, need to check for optional arg
      \def\@tempa{\@oparg{\@ynthm{#2}}[]}%
```

```
    \fi
   \AtBeginEnvironment{#2}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#2}}}% lwarp
  }%
  \@tempa
}
```

Patched to enclose with css:

```
\newcommand{\LWR@haveamsthmname}{
\renewcommand{\thmname}[1]{\InlineClass{amsthmname\LWR@thisthmstyle}{##1}}
}

\newcommand{\LWR@haveamsthmnumber}{
\renewcommand{\thmnumber}[1]{\InlineClass{amsthmnumber\LWR@thisthmstyle}{##1}}
}

\newcommand{\LWR@haveamsthmnote}{
\renewcommand{\thmnote}[1]{\InlineClass{amsthmnote\LWR@thisthmstyle}{##1}}
}

\LWR@haveamsthmname
\LWR@haveamsthmnumber
\LWR@haveamsthmnote
```

Patches for css:

```
\def\@begintheorem#1#2[#3]{%
    \item[
%   \deferred@thm@head{
%     \the\thm@headfont \thm@indent
    \@ifempty{#1}{\let\thmname\@gobble}{\LWR@haveamsthmname}% lwarp
    \@ifempty{#2}{\let\thmnumber\@gobble}{\LWR@haveamsthmnumber}% lwarp
    \@ifempty{#3}{\let\thmnote\@gobble}{\LWR@haveamsthmnote}% lwarp
    \thm@swap\swappedhead\thmhead{#1}{#2}{#3}%
    \the\thm@headpunct~
    \thmheadnl % possibly a newline.
    \hskip\thm@headsep
%   }%
    ]
  \ignorespaces}
```

Patched for css:

```
\def\@thm#1#2#3{%
  \ifhmode\unskip\unskip\par\fi
  \normalfont
  \LWR@forcenewpage% lwarp
  \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
  \trivlist
  \let\thmheadnl\relax
  \let\thm@swap\@gobble
  \thm@notefont{\fontseries\mddefault\upshape}%
  \thm@headpunct{.}% add period after heading
  \thm@headsep 5\p@ plus\p@ minus\p@\relax
  \thm@space@setup
```

```
  #1% style overrides
  \@topsep \thm@preskip               % used by thm head
  \@topsepadd \thm@postskip           % used by \@endparenv
  \def\@tempa{#2}\ifx\@empty\@tempa
    \def\@tempa{\@oparg{\@begintheorem{#3}{}}[]}%
  \else
    \refstepcounter{#2}%
    \def\@tempa{\@oparg{\@begintheorem{#3}{\csname the#2\endcsname}}[]}%
  \fi
  \@tempa
}
```

cleveref patches `\@thm` to do `\cref@thmoptarg` if an optional argument is given. lwarp then patches `\cref@thmoptarg` `\AtBeginDocument`.

```
\AtBeginDocument{%
\def\cref@thmoptarg[#1]#2#3#4{%
    \ifhmode\unskip\unskip\par\fi%
    \normalfont%
    \LWR@forcenewpage% lwarp
    \BlockClass{amsthmbody\LWR@thisthmstyle}% lwarp
    \trivlist%
    \let\thmheadnl\relax%
    \let\thm@swap\@gobble%
    \thm@notefont{\fontseries\mddefault\upshape}%
    \thm@headpunct{.}% add period after heading
    \thm@headsep 5\p@ plus\p@ minus\p@\relax%
    \thm@space@setup%
    #2% style overrides
    \@topsep \thm@preskip               % used by thm head
    \@topsepadd \thm@postskip           % used by \@endparenv
    \def\@tempa{#3}\ifx\@empty\@tempa%
        \def\@tempa{\@oparg{\@begintheorem{#4}{}}[]}%
    \else%
        \refstepcounter[#1]{#3}%  <<< cleveref modification
        \def\@tempa{\@oparg{\@begintheorem{#4}{\csname the#3\endcsname}}[]}%
    \fi%
    \@tempa
}%
}% AtBeginDocument

\def\@endtheorem{\endtrivlist\endBlockClass\@endpefalse }
```

Proof QED symbol:

```
\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

```

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
}{}% @ifundefined
}% AtBeginDocument
```

Patched for css:

```
\renewenvironment{proof}[1][\proofname]{\par
\LWR@forcenewpage% lwarp
    \BlockClass{amsthmproof}% lwarp
  \pushQED{\qed}%
  \normalfont \topsep6\p@\@plus6\p@\relax
  \trivlist
  \item[
        \InlineClass{amsthmproofname}{#1\@addpunct{.}}]\ignorespaces% changes
}{%
  \InlineClass{theoremendmark}{\popQED}\endtrivlist%
  \endBlockClass% lwarp
  \@endpefalse
}
```

File 20 **lwarp-anonchap.sty**

§ 118 Package

anonchap

(*Emulates or patches code by* Peter Wilson.)

Pkg anonchap

anonchap is emulated.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its `titles` option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

The code is shared by tocbibind.

for HTML output:

```
\LWR@ProvidesPackageDrop{anonchap}[2009/08/03]

\newcommand{\simplechapter}[1][\@empty]{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\newcommand{\restorechapter}{%
\let\@chapcntformat\@seccntformat%
}
```

File 21 **lwarp-anysize.sty**

§ 119 Package anysize

(*Emulates or patches code by* Michael Salzenberg, Thomas Esser.)

Pkg anysize anysize is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{anysize}[1994/08/13]

\def\papersize#1#2{}
\def\marginsize#1#2#3#4{}
```

File 22 **lwarp-appendix.sty**

§ 120 Package appendix

(*Emulates or patches code by* Peter Wilson.)

Pkg appendix appendix is patched for use by lwarp.

⚠ incorrect toc link During HTML conversion, the option `toc` without the option `page` results in a TOC link to whichever section was before the `appendices` environment. It is recommended to use both `toc` and also `page` at the same time.

for HTML output:

```
\LWR@ProvidesPackagePass{appendix}[2009/09/02]

\renewcommand*{\@chap@pppage}{%
\part*{\appendixpagename}
 \if@dotoc@pp
 \addappheadtotoc
 \fi
}

\renewcommand*{\@sec@pppage}{%
\part*{\appendixpagename}
 \if@dotoc@pp
 \addappheadtotoc
 \fi
}
```

File 23 **lwarp-ar.sty**

§ 121 Package ar

(*Emulates or patches code by* Agostino De Marco.)

Pkg ar ar is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ar}[2012/01/23]
```

Measure and print the width of the supplied glyph.

```
\newlength{\LWR@ar@width}

\newcommand*{\LWR@ar@printwidth}[1]{%
    \setlength{\LWR@ar@width}{\widthof{#1}}%
    width:%
    \LWR@convertto{em}{\the\LWR@ar@width}em%
}
```

The HTML version of \AR:

```
\newrobustcmd*{\LWR@HTML@AR}{%
```

Start a hashed lateximage, additionally hashed by the font series, with a width depending on the given glyph:

```
    \begin{lateximage}*[AR][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@AR}]%
```

For text mode, set the font series according to the HTML font series:

```
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
```

Print the original glyph using the newly set font series:

```
    \LWR@print@AR%
```

Done.

```
    \end{lateximage}%
}
```

Combine the print and HTML versions:

```
\LWR@formatted{AR}

\newrobustcmd*{\LWR@HTML@ARb}{%
    \begin{lateximage}*[AR][b][\LWR@ar@printwidth{\LWR@print@ARb}]%
    \LWR@print@ARb%
    \end{lateximage}%
}
\LWR@formatted{ARb}

\newrobustcmd*{\LWR@HTML@ARss}{%
   \begin{lateximage}*[ARss][\LWR@f@series][\LWR@ar@printwidth{\LWR@print@ARss}]%
    \ifmmode\else\csuse{LWR@orig\LWR@f@series series}\fi%
    \LWR@print@ARss%
    \end{lateximage}%
}
\LWR@formatted{ARss}
```

```
\newrobustcmd*{\LWR@HTML@ARssb}{%
    \begin{lateximage}*[AR][ssb][\LWR@ar@printwidth{\LWR@print@ARssb}]%
    \LWR@print@ARssb%
    \end{lateximage}%
}
\LWR@formatted{ARssb}

\newrobustcmd*{\LWR@HTML@ARtt}{%
    \begin{lateximage}*[AR][tt][\LWR@ar@printwidth{\LWR@print@ARtt}]%
    \LWR@print@ARtt%
    \end{lateximage}%
}
\LWR@formatted{ARtt}
```

File 24 **lwarp-arabicfront.sty**

§ 122 Package arabicfront

Pkg arabicfront arabicfront is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{arabicfront}[2006/09/03]
```

File 25 **lwarp-array.sty**

§ 123 Package array

Pkg array array is used as-is for print output, and emulated for HTML.

plarray and plextarray do not affect \firsthline or \lasthline, and so are not affected by the following.

for HTML output: Remove the default nullfied macros:

```
\let\firsthline\relax
\let\lasthline\relax

\LWR@ProvidesPackagePass{array}[2018/12/30]

\newcommand*{\LWR@HTML@firsthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{firsthline}

\newcommand*{\LWR@HTML@lasthline}{\LWR@HTMLhline}%
\LWR@expandableformatted{lasthline}

\providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
\LWR@formatted{tabularnewline}
```

File 26 **lwarp-arydshln.sty**

§ 124 Package

arydshln

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg arydshln arydshln heavily patches tabular code, so the actual package is not used. arydshln is emulated for HTML `tabular`, and reverts to solid rules for SVG math `array` and `tabular` in a `lateximage`.

CSS is not able to display a double-dashed border, so a single-dashed rule is displayed as a single-dashed border, and a double-dashed rule is displayed as a thicker single-dashed border.

for HTML output: array is required to allow `\newcolumn` below.

```
\RequirePackage{array}
```

```
\LWR@ProvidesPackageDrop{arydshln}[2018/09/26]
```

Ignored, but included for source compatibility:

```
\newdimen\dashlinedash \dashlinedash4pt %
\newdimen\dashlinegap \dashlinegap4pt %
\let\hdashlinewidth\dashlinedash
\let\hdashlinegap\dashlinegap

\def\ADLnullwide{}
\def\ADLsomewide{}
\def\ADLnullwidehline{}
\def\ADLsomewidehline{}

\def\ADLactivate{}
\def\ADLinactivate{}
\newcommand*{\ADLdrawingmode}[1]{}
\newcommand*{\ADLnoshorthanded}{}
\newcommand*{\dashgapcolor}[2][]{}
\newcommand*{\nodashgapcolor}{}
```

In a `lateximage`, revert to solid vertical rules:

```
\appto\LWR@restoreorigformatting{%
\newcolumntype{:}{|}%
\newcolumntype{;}[1]{|}%
\LetLtxMacro\hdashline\hline%
}
```

Some of these macros are already defined as temporary placeholders in the lwarp core, so they must be redefined here.

The emulated defaults also work for an emulated print mode inside a `lateximage`:

```
\def\hdashline{
%     \adl@hdashline\adl@ihdashline
    \adl@hdashline\adl@inactivehdl
}
\def\adl@hdashline#1{\noalign{\ifnum0=`}\fi
%         \ifadl@zwhrule \vskip-\arrayrulewidth
%         \else
%             \adl@hline\adl@connect\arrayrulewidth
                \hrule \@height \arrayrulewidth% lwarp
%         \fi
        \@ifnextchar[%]
                     {#1}%
                     {#1[%
%                          \dashlinedash/\dashlinegap
                        1pt/1pt
                     ]}}
% \def\adl@ihdashline[#1/#2]{\ifnum0=`{\fi}%
%         \multispan{\adl@columns}\unskip \adl@hcline\z@[#1/#2]%
%         \noalign{\ifnum0=`}\fi
%         \futurelet\@tempa\adl@xhline}
\def\adl@inactivehdl[#1/#2]{
%         \ifadl@zwhrule \vskip-\arrayrulewidth \fi
        \hrule\@height\arrayrulewidth
        \futurelet\@tempa\adl@xhline}
\def\adl@xhline{\ifx\@tempa\hline \adl@ixhline\fi
        \ifx\@tempa\hdashline \adl@ixhline\fi
        \ifnum0=`{\fi}}
\def\adl@ixhline{\vskip\doublerulesep \adl@hline\relax\doublerulesep}
\def\adl@hline#1#2{%
% \@tempcnta#2
%         \global\advance\adl@totalheight\@tempcnta
%         \xdef\adl@rowsL{\adl@rowsL
%                 (#1/\number\@tempcnta);}%
%         \xdef\adl@rowsR{\adl@rowsR
%                 (#1/\number\@tempcnta);}
}

\def\cdashline#1{\noalign{\ifnum0=`}\fi
        \@ifnextchar[%]
%                       {\adl@cdline[#1]}%
%                       {\adl@cdline[#1][\dashlinedash/\dashlinegap]}
                     {\adl@inactivecdl[#1]}%
                     {\adl@inactivecdl[#1][\dashlinedash/\dashlinegap]}
}

\def\adl@inactivecdl[#1-#2][#3]{\ifnum0=`{\fi}\cline{#1-#2}}
```

File 27 **lwarp-asymptote.sty**

§ 125 Package asymptote

(*Emulates or patches code by* Andy Hammerlindl, John Bowman, Tom Prince.)

Pkg asymptote asymptote is patched for use by lwarp.

To compile:

```
pdflatex project.tex
asy project-*.asy
pdflatex project.tex

lwarpmk print
asy project-*.asy
lwarpmk print1
lwarpmk print1

lwarpmk html
asy project_html-*.asy
lwarpmk html1
lwarpmk html1
lwarpmk limages
```

for HTML output:

```
\LWR@ProvidesPackagePass{asymptote}[2016/11/26]

\BeforeBeginEnvironment{asy}{\begin{lateximage}[(-asymptote-~\packagediagramname)]}
\AfterEndEnvironment{asy}{\end{lateximage}}

\xpatchcmd{\asyinclude}
    {\begingroup}
    {\begin{lateximage}[(-asymptote-~\packagediagramname)]}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-begingroup}}

\xpatchcmd{\asyinclude}
    {\endgroup}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{asymptote}{asyinclude-endgroup}}
```

File 28 **lwarp-atbegshi.sty**

§ 126 Package atbegshi

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg atbegshi atbegshi is ignored.

for HTML output: Discard all options for lwarp-atbegshi:

```
\LWR@ProvidesPackageDrop{atbegshi}[2011/10/05]

\newcommand*{\AtBeginShipout}[1]{}
\newbox\AtBeginShipoutBox
\newcommand*{\AtBeginShipoutNext}[1]{}
\newcommand*{\AtBeginShipoutFirst}[1]{}
\newcommand*{\AtBeginShipoutDiscard}{}
\newcommand*{\AtBeginShipoutInit}{}
\newcommand*{\AtBeginShipoutAddToBox}[1]{}
\newcommand*{\AtBeginShipoutAddToBoxForeground}[1]{}
\newcommand*{\AtBeginShipoutUpperLeft}[1]{}
\newcommand*{\AtBeginShipoutUpperLeftForeground}[1]{}
\newcommand*{\AtBeginShipoutOriginalShipout}[1]{}
\def\AtBeginShipoutBoxWidth{0pt}
\def\AtBeginShipoutBoxHeight{0pt}
\def\AtBeginShipoutBoxDepth{0pt}

```

File 29 **lwarp-attachfile.sty**

§ 127 Package

attachfile

(*Emulates or patches code by* Scott Pakin.)

Pkg attachfile attachfile is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile}[2016/09/18]
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
            \detokenize\expandafter{\atfi@color@rgb}%
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a LWR@attachfile@icon environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
```

```
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \href{#1}{\LWR@attachfile@appearance}%
}
```

File 30 **lwarp-attachfile2.sty**

§ 128 Package

attachfile2

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg attachfile2 attachfile2 is patched for use by lwarp.

⚠ Metadata is ignored for now.

for HTML output:

```
\LWR@ProvidesPackagePass{attachfile2}[2016/05/16]
```

Adds memory of the selected color:

```
\def\LWR@attachfiletwo@color{}%

\define@key{AtFi}{color}{%
    \def\LWR@attachfiletwo@color{#1}%   lwarp
  \HyColor@AttachfileColor{#1}%
          \atfi@color@tex\atfi@color@inline\atfi@color@annot
          {attachfile2}{color}%
}
```

Encloses each icon:

```
\newenvironment*{LWR@attachfile@icon}
{
    \begin{lateximage}*%
        [-attachfile-]%
        [%
            \detokenize\expandafter{\atfi@icon@icon}-%
            \detokenize\expandafter{\LWR@attachfiletwo@color}%
        ]%
}
{
    \end{lateximage}
}
```

Each icon is enclosed inside a `LWR@attachfile@icon` environment:

```
\xpretocmd{\atfi@acroGraph}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroGraph}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPaperclip}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPaperclip}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroPushPin}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroPushPin}{\endLWR@attachfile@icon}{}{}

\xpretocmd{\atfi@acroTag}{\LWR@attachfile@icon}{}{}
\xapptocmd{\atfi@acroTag}{\endLWR@attachfile@icon}{}{}
```

Disable PDF file embedding:

```
\DeclareRobustCommand{\atfi@embedfile}[1]{}
```

The displayed output for an `\attachfile` reference:

```
\newcommand*{\LWR@attachfile@appearance}{}

\def\atfi@set@appearance@icon{%
    \atfi@set@appearance{\csname atfi@acro\atfi@icon@icon\endcsname}%
}

\DeclareRobustCommand{\atfi@set@appearance}[1]{%
    \def\LWR@attachfile@appearance{#1}%
}
```

A file annotation becomes a reference:

```
\DeclareRobustCommand{\atfi@insert@file@annot}[1]{%
    \href{#1}{\LWR@attachfile@appearance}%
}
```

Modified for text color:

```
\DeclareRobustCommand{\notextattachfile}[2][]{%
```

```
  \begingroup
    \atfi@setup{#1}%
    \ifatfi@print
      \leavevmode
      \begingroup
        \HyColor@UseColor\atfi@color@tex
        \LWR@textcurrentcolor{#2}%      lwarp
% \strut
      \endgroup
%     \else
%       \sbox\ltx@zero{#2\strut}%
%       \makebox[\wd0]{}%
    \fi
  \endgroup
}
```

Modified to draw the icon:

```
\DeclareRobustCommand{\noattachfile}[1][]{%
  \begingroup
    \atfi@setup{#1}%
    \atfi@set@appearance@icon
    \ifatfi@print
        \LWR@attachfile@appearance%     lwarp
%       \expandafter
%       \atfi@refxform\csname atfi@appobj@\atfi@icon@icon\endcsname
%     \else
%       \makebox[\atfi@appearancewidth]{}%
    \fi
  \endgroup
}
```

File 31 **lwarp-authblk.sty**

§ 129 Package

authblk

(*Emulates or patches code by* Patrick W. Daly.)

Pkg authblk

authblk is patched for HTML.

package support

⚠ load order

lwarp supports the native LaTeX titling commands, and also supports the packages authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

(*Emulates or patches code by* Patrick W. Daly.)

for HTML output:

Require that authblk be loaded before titling:

```
\@ifpackageloaded{titling}{
\PackageError{lwarp-authblk}
{Package authblk must be loaded before titling}
```

```
{Titling appends authblk's author macro, so authblk must be loaded first.}
}
{}
```

Load authblk:

```
\LWR@ProvidesPackagePass{authblk}[2001/02/27]
```

Patch to add a class for the affiliation:

```
\LetLtxMacro\LWRAB@affil\affil

\renewcommand{\affil}[2][]{%
\LWRAB@affil[#1]{\protect\InlineClass{affiliation}{#2}}
}
```

Create an HTML break for an \authorcr:

```
\renewcommand*{\authorcr}{\protect\LWR@newlinebr}
```

File 32 **lwarp-autonum.sty**

§ 130 Package

autonum

Pkg autonum autonum is ignored.

⚠ numbering All equations are numbered in HTML output.

MathJax does not support the "+" environments.

for HTML output:

```
\LWR@ProvidesPackageDrop{autonum}[2015/01/18]

\RequirePackage{amsmath}


\newenvironment{equation+}{\equation}{\endequation}


\newenvironment{gather+}{\gather}{\endgather}

\BeforeBeginEnvironment{gather+}{\LWR@amsmathenv@@before{gather+}}

\AfterEndEnvironment{gather+}{\LWR@amsmathenv@@after}


\newenvironment{multline+}{\multline}{\endmultline}

\BeforeBeginEnvironment{multline+}{\LWR@amsmathenv@@before{multline+}}

\AfterEndEnvironment{multline+}{\LWR@amsmathenv@@after}


```

```
\newenvironment{flalign+}{\flalign}{\endflalign}

\BeforeBeginEnvironment{flalign+}{\LWR@amsmathenv@@before{flaline+}}

\AfterEndEnvironment{flalign+}{\LWR@amsmathenv@@after}


\newenvironment{align+}{\align}{\endalign}

\BeforeBeginEnvironment{align+}{\LWR@amsmathenv@@before{aline+}}

\AfterEndEnvironment{align+}{\LWR@amsmathenv@@after}


\newenvironment{alignat+}{\alignat}{\endalignat}

\BeforeBeginEnvironment{alignat+}{\LWR@amsmathenv@@before{alineat+}}

\AfterEndEnvironment{alignat+}{\LWR@amsmathenv@@after}


\newenvironment{split+}{\split}{\endsplit}
```

File 33 **lwarp-axessibility.sty**

§ 131 Package axessibility

Pkg axessibility axessibility is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{axessibility}

\newcommand{\wrap}[1]{}
```

File 34 **lwarp-axodraw2.sty**

§ 132 Package axodraw2

(*Emulates or patches code by* John C. Collins, J.A.M. Vermaseren.)

Pkg axodraw2 axodraw2 is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{axodraw2}[2018/02/15]

\BeforeBeginEnvironment{axopicture}{\begin{lateximage}[(-axopicture-~\packagediagramname)]}

\AfterEndEnvironment{axopicture}{\end{lateximage}}
```

File 35 **lwarp-backnaur.sty**

§ 133 Package

backnaur

(*Emulates or patches code by* Adrian P. Robson.)

Pkg backnaur backnaur is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{backnaur}[2019/04/14]
```

A purely HTML text output is generated, without math images.

The various instances of `\LWR@stoppars` are added because the print version uses the `eqnarray` environment with `\\` between lines. For HTML, paragraph handling must be turned off so that these `\\` macros are converted to `<br>` elements without extra paragraph space.

```
\renewenvironment*{bnf}{%
    \BlockClass{backnaur}%
    \LWR@stoppars%
}{\endBlockClass}

\renewenvironment*{bnf*}{%
    \BlockClass{backnaur}%
    \LWR@stoppars%
}{\endBlockClass}

\renewcommand{\bnfpn}[1]{\HTMLunicode{27e8}#1\HTMLunicode{27e9}}% \langle, rangle
\renewcommand{\bnfor}{ \HTMLunicode{7c} }% \mid
\renewcommand{\bnfsp}{ }
\renewcommand{\bnfes}{\HTMLunicode{3bb}}% \lambda
\renewcommand{\bnftd}[1]{\textnormal{\textit{#1}}}
\renewcommand{\bnfsk}{\HTMLunicode{2026} }% \dots, ellipsis
\renewcommand{\bnfpo}{\HTMLunicode{22a8}}% \models

\renewcommand{\bnfprod}[2]{%
    \begin{BlockClass}{backnaurprod}\bnfpn{#1} \bnfpo \end{BlockClass}%
    \begin{BlockClass}{backnaurdesc}#2\end{BlockClass}%
    \LWR@stoppars%
}%

\renewcommand{\bnfmore}[1]{%
    \begin{BlockClass}{backnaurprod}\end{BlockClass}
    \begin{BlockClass}{backnaurdesc}#1\end{BlockClass}
    \LWR@stoppars%
}

\@ifpackagewith{backnaur}{perp}{\renewcommand{\bnfes}{\HTMLunicode{27c2}}}{}% \perp
\@ifpackagewith{backnaur}{epsilon}{\renewcommand{\bnfes}{\HTMLunicode{3f5}}}{}% \epsilon
```

File 36 **lwarp-backref.sty**

§ 134 Package backref

(*Emulates or patches code by* David Carlisle and Sebastian Rahtz.)

Pkg backref backref is patched for use by lwarp.

⚠ loading Note that backref must be explicitly loaded, and is not automatically loaded by hyperref when generating HTML output.

for HTML output:

```
\LWR@ProvidesPackagePass{backref}[2016/05/21]
```

Force the hyperref option:

```
\def\backref{}\let\backrefxxx\hyper@section@backref
```

File 37 **lwarp-balance.sty**

§ 135 Package balance

(*Emulates or patches code by* Patrick W. Daly.)

Pkg balance balance is ignored.

for HTML output: Discard all options for lwarp-balance:

```
\LWR@ProvidesPackageDrop{balance}[1999/02/23]
```

```
\newcommand*{\balance}{}
\newcommand*{\nobalance}{}
```

File 38 **lwarp-bbding.sty**

§ 136 Package bbding

(*Emulates or patches code by* Karel Horak, Peter Møller Neergaard.)

Pkg bbding bbding is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bbding}[1999/04/15]
```

```
\newcommand*{\LWR@bbdingsymbol}[2]{\HTMLunicode{#2}}

\newcommand{\LWR@HTML@ScissorRightBrokenBottom}{\LWR@bbdingsymbol{000}   {2701}}
```

```
\newcommand{\LWR@HTML@ScissorRight}{\LWR@bbdingsymbol{001}              {2702}}
\newcommand{\LWR@HTML@ScissorRightBrokenTop}{\LWR@bbdingsymbol{002}     {2703}}
\newcommand{\LWR@HTML@ScissorLeftBrokenBottom}{\LWR@bbdingsymbol{003}   {2701}}
\newcommand{\LWR@HTML@ScissorLeft}{\LWR@bbdingsymbol{004}               {2702}}
\newcommand{\LWR@HTML@ScissorLeftBrokenTop}{\LWR@bbdingsymbol{005}      {2703}}
\newcommand{\LWR@HTML@ScissorHollowRight}{\LWR@bbdingsymbol{006}        {2704}}
\newcommand{\LWR@HTML@ScissorHollowLeft}{\LWR@bbdingsymbol{007}         {2704}}
\newcommand{\LWR@HTML@Phone}{\LWR@bbdingsymbol{010}                     {260E}}
\newcommand{\LWR@HTML@PhoneHandset}{\LWR@bbdingsymbol{011}              {2706}}
\newcommand{\LWR@HTML@Tape}{\LWR@bbdingsymbol{012}                      {2707}}
\newcommand{\LWR@HTML@Plane}{\LWR@bbdingsymbol{013}                     {2708}}
\newcommand{\LWR@HTML@Envelope}{\LWR@bbdingsymbol{014}                  {2709}}
\newcommand{\LWR@HTML@HandCuffRight}{\LWR@bbdingsymbol{015}             {261B}}
\newcommand{\LWR@HTML@HandCuffLeft}{\LWR@bbdingsymbol{016}              {261A}}
\newcommand{\LWR@HTML@HandCuffRightUp}{\LWR@bbdingsymbol{017}           {261D}}
\newcommand{\LWR@HTML@HandCuffLeftUp}{\LWR@bbdingsymbol{020}            {261F}}
\newcommand{\LWR@HTML@HandRight}{\LWR@bbdingsymbol{021}                 {261E}}
\newcommand{\LWR@HTML@HandLeft}{\LWR@bbdingsymbol{022}                  {261C}}
\newcommand{\LWR@HTML@HandRightUp}{\LWR@bbdingsymbol{023}               {261D}}
\newcommand{\LWR@HTML@HandLeftUp}{\LWR@bbdingsymbol{024}                {261F}}
\newcommand{\LWR@HTML@Peace}{\LWR@bbdingsymbol{025}                     {270C}}
\newcommand{\LWR@HTML@HandPencilLeft}{\LWR@bbdingsymbol{026}            {270D}}
\newcommand{\LWR@HTML@PencilRight}{\LWR@bbdingsymbol{027}               {270F}}
\newcommand{\LWR@HTML@PencilLeft}{\LWR@bbdingsymbol{030}                {270F}}
\newcommand{\LWR@HTML@PencilRightUp}{\LWR@bbdingsymbol{031}             {2710}}
\newcommand{\LWR@HTML@PencilLeftUp}{\LWR@bbdingsymbol{032}              {2710}}
\newcommand{\LWR@HTML@PencilRightDown}{\LWR@bbdingsymbol{033}           {270E}}
\newcommand{\LWR@HTML@PencilLeftDown}{\LWR@bbdingsymbol{034}            {270E}}
\newcommand{\LWR@HTML@NibRight}{\LWR@bbdingsymbol{035}                  {2711}}
\newcommand{\LWR@HTML@NibLeft}{\LWR@bbdingsymbol{036}                   {2711}}
\newcommand{\LWR@HTML@NibSolidRight}{\LWR@bbdingsymbol{037}             {2712}}
\newcommand{\LWR@HTML@NibSolidLeft}{\LWR@bbdingsymbol{040}              {2712}}
\newcommand{\LWR@HTML@Checkmark}{\LWR@bbdingsymbol{041}                 {2713}}
\newcommand{\LWR@HTML@CheckmarkBold}{\LWR@bbdingsymbol{042}             {2714}}
\newcommand{\LWR@HTML@XSolid}{\LWR@bbdingsymbol{043}                    {2715}}
\newcommand{\LWR@HTML@XSolidBold}{\LWR@bbdingsymbol{044}                {2716}}
\newcommand{\LWR@HTML@XSolidBrush}{\LWR@bbdingsymbol{045}               {2717}}
\newcommand{\LWR@HTML@PlusOutline}{\LWR@bbdingsymbol{046}               {2719}}
\newcommand{\LWR@HTML@Plus}{\LWR@bbdingsymbol{047}                      {271A}}
\newcommand{\LWR@HTML@PlusCenterOpen}{\LWR@bbdingsymbol{050}            {271C}}
\newcommand{\LWR@HTML@PlusThinCenterOpen}{\LWR@bbdingsymbol{051}        {271B}}
\newcommand{\LWR@HTML@Cross}{\LWR@bbdingsymbol{052}                     {271D}}
\newcommand{\LWR@HTML@CrossOpenShadow}{\LWR@bbdingsymbol{053}           {271E}}
\newcommand{\LWR@HTML@CrossOutline}{\LWR@bbdingsymbol{054}              {271F}}
\newcommand{\LWR@HTML@CrossBoldOutline}{\LWR@bbdingsymbol{055}          {271F}}
\newcommand{\LWR@HTML@CrossMaltese}{\LWR@bbdingsymbol{056}              {2720}}
\newcommand{\LWR@HTML@DavidStarSolid}{\LWR@bbdingsymbol{057}            {2721}}
\newcommand{\LWR@HTML@DavidStar}{\LWR@bbdingsymbol{060}                 {2721}}
\newcommand{\LWR@HTML@FourAsterisk}{\LWR@bbdingsymbol{061}              {2722}}
\newcommand{\LWR@HTML@JackStar}{\LWR@bbdingsymbol{062}                  {2723}}
\newcommand{\LWR@HTML@JackStarBold}{\LWR@bbdingsymbol{063}              {2724}}
\newcommand{\LWR@HTML@CrossClowerTips}{\LWR@bbdingsymbol{064}           {2725}}
\newcommand{\LWR@HTML@FourStar}{\LWR@bbdingsymbol{065}                  {2726}}
\newcommand{\LWR@HTML@FourStarOpen}{\LWR@bbdingsymbol{066}              {2727}}
\newcommand{\LWR@HTML@FiveStarLines}{\LWR@bbdingsymbol{067}             {2729}}
```

```
\newcommand{\LWR@HTML@FiveStar}{\LWR@bbdingsymbol{070}                    {2605}}
\newcommand{\LWR@HTML@FiveStarOpen}{\LWR@bbdingsymbol{071}                {2729}}
\newcommand{\LWR@HTML@FiveStarOpenCircled}{\LWR@bbdingsymbol{072}         {272A}}
\newcommand{\LWR@HTML@FiveStarCenterOpen}{\LWR@bbdingsymbol{073}          {272B}}
\newcommand{\LWR@HTML@FiveStarOpenDotted}{\LWR@bbdingsymbol{074}          {272C}}
\newcommand{\LWR@HTML@FiveStarOutline}{\LWR@bbdingsymbol{075}             {272D}}
\newcommand{\LWR@HTML@FiveStarOutlineHeavy}{\LWR@bbdingsymbol{076}        {272E}}
\newcommand{\LWR@HTML@FiveStarConvex}{\LWR@bbdingsymbol{077}              {272F}}
\newcommand{\LWR@HTML@FiveStarShadow}{\LWR@bbdingsymbol{100}              {2730}}
\newcommand{\LWR@HTML@AsteriskBold}{\LWR@bbdingsymbol{101}                {2731}}
\newcommand{\LWR@HTML@AsteriskCenterOpen}{\LWR@bbdingsymbol{102}          {2732}}
\newcommand{\LWR@HTML@AsteriskThin}{\LWR@bbdingsymbol{103}                {273B}}
\newcommand{\LWR@HTML@AsteriskThinCenterOpen}{\LWR@bbdingsymbol{104}      {273C}}
\newcommand{\LWR@HTML@EightStarTaper}{\LWR@bbdingsymbol{105}              {2733}}
\newcommand{\LWR@HTML@EightStarConvex}{\LWR@bbdingsymbol{106}             {2735}}
\newcommand{\LWR@HTML@SixStar}{\LWR@bbdingsymbol{107}                     {2736}}
\newcommand{\LWR@HTML@EightStar}{\LWR@bbdingsymbol{110}                   {2737}}
\newcommand{\LWR@HTML@EightStarBold}{\LWR@bbdingsymbol{111}               {2738}}
\newcommand{\LWR@HTML@TwelweStar}{\LWR@bbdingsymbol{112}                  {2739}}
\newcommand{\LWR@HTML@SixteenStarLight}{\LWR@bbdingsymbol{113}            {273A}}
\newcommand{\LWR@HTML@SixFlowerPetalRemoved}{\LWR@bbdingsymbol{114}       {273B}}
\newcommand{\LWR@HTML@SixFlowerOpenCenter}{\LWR@bbdingsymbol{115}         {273C}}
\newcommand{\LWR@HTML@Asterisk}{\LWR@bbdingsymbol{116}                    {273D}}
\newcommand{\LWR@HTML@SixFlowerAlternate}{\LWR@bbdingsymbol{117}          {273E}}
\newcommand{\LWR@HTML@FiveFlowerPetal}{\LWR@bbdingsymbol{120}             {273F}}
\newcommand{\LWR@HTML@SixFlowerPetalDotted}{\LWR@bbdingsymbol{121}        {2740}}
\newcommand{\LWR@HTML@FiveFlowerOpen}{\LWR@bbdingsymbol{122}              {2740}}
\newcommand{\LWR@HTML@EightFlowerPetal}{\LWR@bbdingsymbol{123}            {2741}}
\newcommand{\LWR@HTML@SunshineOpenCircled}{\LWR@bbdingsymbol{124}         {2742}}
\newcommand{\LWR@HTML@SixFlowerAltPetal}{\LWR@bbdingsymbol{125}           {2743}}
\newcommand{\LWR@HTML@FourClowerOpen}{\LWR@bbdingsymbol{126}              {273F}}
\newcommand{\LWR@HTML@FourClowerSolid}{\LWR@bbdingsymbol{127}             {273F}}
\newcommand{\LWR@HTML@AsteriskRoundedEnds}{\LWR@bbdingsymbol{130}         {2749}}
\newcommand{\LWR@HTML@EightFlowerPetalRemoved}{\LWR@bbdingsymbol{131}     {274A}}
\newcommand{\LWR@HTML@EightAsterisk}{\LWR@bbdingsymbol{132}               {274B}}
\newcommand{\LWR@HTML@SixFlowerRemovedOpenPetal}{\LWR@bbdingsymbol{133}    {2740}}
\newcommand{\LWR@HTML@SparkleBold}{\LWR@bbdingsymbol{134}                 {2748}}
\newcommand{\LWR@HTML@Sparkle}{\LWR@bbdingsymbol{135}                     {2747}}
\newcommand{\LWR@HTML@SnowflakeChevron}{\LWR@bbdingsymbol{136}            {2744}}
\newcommand{\LWR@HTML@SnowflakeChevronBold}{\LWR@bbdingsymbol{137}        {2746}}
\newcommand{\LWR@HTML@Snowflake}{\LWR@bbdingsymbol{140}                   {2744}}
\newcommand{\LWR@HTML@CircleSolid}{\LWR@bbdingsymbol{141}                 {25CF}}
\newcommand{\LWR@HTML@Ellipse}{\LWR@bbdingsymbol{142}                     {274D}}
\newcommand{\LWR@HTML@EllipseSolid}{\LWR@bbdingsymbol{143}                {25CF}}
\newcommand{\LWR@HTML@CircleShadow}{\LWR@bbdingsymbol{144}                {274D}}
\newcommand{\LWR@HTML@EllipseShadow}{\LWR@bbdingsymbol{145}               {274D}}
\newcommand{\LWR@HTML@Square}{\LWR@bbdingsymbol{146}                      {25A1}}
\newcommand{\LWR@HTML@SquareSolid}{\LWR@bbdingsymbol{147}                 {25A0}}
\newcommand{\LWR@HTML@SquareShadowBottomRight}{\LWR@bbdingsymbol{150}     {2751}}
\newcommand{\LWR@HTML@SquareShadowTopRight}{\LWR@bbdingsymbol{151}        {2752}}
\newcommand{\LWR@HTML@SquareShadowTopLeft}{\LWR@bbdingsymbol{152}         {2752}}
\newcommand{\LWR@HTML@SquareCastShadowBottomRight}{\LWR@bbdingsymbol{153} {2751}}
\newcommand{\LWR@HTML@SquareCastShadowTopRight}{\LWR@bbdingsymbol{154}    {2752}}
\newcommand{\LWR@HTML@SquareCastShadowTopLeft}{\LWR@bbdingsymbol{155}     {2752}}
\newcommand{\LWR@HTML@TriangleUp}{\LWR@bbdingsymbol{156}                  {25B2}}
```

```
\newcommand{\LWR@HTML@TriangleDown}{\LWR@bbdingsymbol{157}              {25BC}}
\newcommand{\LWR@HTML@DiamondSolid}{\LWR@bbdingsymbol{160}              {25C6}}
\newcommand{\LWR@HTML@OrnamentDiamondSolid}{\LWR@bbdingsymbol{161}      {2756}}
\newcommand{\LWR@HTML@HalfCircleRight}{\LWR@bbdingsymbol{162}           {25D7}}
\newcommand{\LWR@HTML@HalfCircleLeft}{\LWR@bbdingsymbol{163}            {25D6}}
\newcommand{\LWR@HTML@RectangleThin}{\LWR@bbdingsymbol{164}             {2758}}
\newcommand{\LWR@HTML@Rectangle}{\LWR@bbdingsymbol{165}                 {2759}}
\newcommand{\LWR@HTML@RectangleBold}{\LWR@bbdingsymbol{166}             {275A}}
\newcommand{\LWR@HTML@ArrowBoldRightStrobe}{\LWR@bbdingsymbol{167}      {27A0}}
\newcommand{\LWR@HTML@ArrowBoldUpRight}{\LWR@bbdingsymbol{170}          {27A6}}
\newcommand{\LWR@HTML@ArrowBoldDownRight}{\LWR@bbdingsymbol{171}        {27A5}}
\newcommand{\LWR@HTML@ArrowBoldRightShort}{\LWR@bbdingsymbol{172}       {27A7}}
\newcommand{\LWR@HTML@ArrowBoldRightCircled}{\LWR@bbdingsymbol{173}     {27B2}}


\LWR@formatted{ScissorRightBrokenBottom}
\LWR@formatted{ScissorRight}
\LWR@formatted{ScissorRightBrokenTop}
\LWR@formatted{ScissorLeftBrokenBottom}
\LWR@formatted{ScissorLeft}
\LWR@formatted{ScissorLeftBrokenTop}
\LWR@formatted{ScissorHollowRight}
\LWR@formatted{ScissorHollowLeft}
\LWR@formatted{Phone}
\LWR@formatted{PhoneHandset}
\LWR@formatted{Tape}
\LWR@formatted{Plane}
\LWR@formatted{Envelope}
\LWR@formatted{HandCuffRight}
\LWR@formatted{HandCuffLeft}
\LWR@formatted{HandCuffRightUp}
\LWR@formatted{HandCuffLeftUp}
\LWR@formatted{HandRight}
\LWR@formatted{HandLeft}
\LWR@formatted{HandRightUp}
\LWR@formatted{HandLeftUp}
\LWR@formatted{Peace}
\LWR@formatted{HandPencilLeft}
\LWR@formatted{PencilRight}
\LWR@formatted{PencilLeft}
\LWR@formatted{PencilRightUp}
\LWR@formatted{PencilLeftUp}
\LWR@formatted{PencilRightDown}
\LWR@formatted{PencilLeftDown}
\LWR@formatted{NibRight}
\LWR@formatted{NibLeft}
\LWR@formatted{NibSolidRight}
\LWR@formatted{NibSolidLeft}
\LWR@formatted{Checkmark}
\LWR@formatted{CheckmarkBold}
\LWR@formatted{XSolid}
\LWR@formatted{XSolidBold}
\LWR@formatted{XSolidBrush}
\LWR@formatted{PlusOutline}
\LWR@formatted{Plus}
```

```
\LWR@formatted{PlusCenterOpen}
\LWR@formatted{PlusThinCenterOpen}
\LWR@formatted{Cross}
\LWR@formatted{CrossOpenShadow}
\LWR@formatted{CrossOutline}
\LWR@formatted{CrossBoldOutline}
\LWR@formatted{CrossMaltese}
\LWR@formatted{DavidStarSolid}
\LWR@formatted{DavidStar}
\LWR@formatted{FourAsterisk}
\LWR@formatted{JackStar}
\LWR@formatted{JackStarBold}
\LWR@formatted{CrossClowerTips}
\LWR@formatted{FourStar}
\LWR@formatted{FourStarOpen}
\LWR@formatted{FiveStarLines}
\LWR@formatted{FiveStar}
\LWR@formatted{FiveStarOpen}
\LWR@formatted{FiveStarOpenCircled}
\LWR@formatted{FiveStarCenterOpen}
\LWR@formatted{FiveStarOpenDotted}
\LWR@formatted{FiveStarOutline}
\LWR@formatted{FiveStarOutlineHeavy}
\LWR@formatted{FiveStarConvex}
\LWR@formatted{FiveStarShadow}
\LWR@formatted{AsteriskBold}
\LWR@formatted{AsteriskCenterOpen}
\LWR@formatted{AsteriskThin}
\LWR@formatted{AsteriskThinCenterOpen}
\LWR@formatted{EightStarTaper}
\LWR@formatted{EightStarConvex}
\LWR@formatted{SixStar}
\LWR@formatted{EightStar}
\LWR@formatted{EightStarBold}
\LWR@formatted{TwelweStar}
\LWR@formatted{SixteenStarLight}
\LWR@formatted{SixFlowerPetalRemoved}
\LWR@formatted{SixFlowerOpenCenter}
\LWR@formatted{Asterisk}
\LWR@formatted{SixFlowerAlternate}
\LWR@formatted{FiveFlowerPetal}
\LWR@formatted{SixFlowerPetalDotted}
\LWR@formatted{FiveFlowerOpen}
\LWR@formatted{EightFlowerPetal}
\LWR@formatted{SunshineOpenCircled}
\LWR@formatted{SixFlowerAltPetal}
\LWR@formatted{FourClowerOpen}
\LWR@formatted{FourClowerSolid}
\LWR@formatted{AsteriskRoundedEnds}
\LWR@formatted{EightFlowerPetalRemoved}
\LWR@formatted{EightAsterisk}
\LWR@formatted{SixFlowerRemovedOpenPetal}
\LWR@formatted{SparkleBold}
\LWR@formatted{Sparkle}
\LWR@formatted{SnowflakeChevron}
```

```
\LWR@formatted{SnowflakeChevronBold}
\LWR@formatted{Snowflake}
\LWR@formatted{CircleSolid}
\LWR@formatted{Ellipse}
\LWR@formatted{EllipseSolid}
\LWR@formatted{CircleShadow}
\LWR@formatted{EllipseShadow}
\LWR@formatted{Square}
\LWR@formatted{SquareSolid}
\LWR@formatted{SquareShadowBottomRight}
\LWR@formatted{SquareShadowTopRight}
\LWR@formatted{SquareShadowTopLeft}
\LWR@formatted{SquareCastShadowBottomRight}
\LWR@formatted{SquareCastShadowTopRight}
\LWR@formatted{SquareCastShadowTopLeft}
\LWR@formatted{TriangleUp}
\LWR@formatted{TriangleDown}
\LWR@formatted{DiamondSolid}
\LWR@formatted{OrnamentDiamondSolid}
\LWR@formatted{HalfCircleRight}
\LWR@formatted{HalfCircleLeft}
\LWR@formatted{RectangleThin}
\LWR@formatted{Rectangle}
\LWR@formatted{RectangleBold}
\LWR@formatted{ArrowBoldRightStrobe}
\LWR@formatted{ArrowBoldUpRight}
\LWR@formatted{ArrowBoldDownRight}
\LWR@formatted{ArrowBoldRightShort}
\LWR@formatted{ArrowBoldRightCircled}
```

File 39 **lwarp-biblatex.sty**

§ 137 Package

biblatex

(*Emulates or patches code by* Philipp Lehman.)

Pkg biblatex When biblatex is used, modifications from newfloat may have to be undone.

for HTML output:

1. lwarp uses newfloat.
2. For classes with chapters which newfloat does not know about, such as CTEX-related classes, newfloat may modify `\addtocontents`.
3. biblatex, though, wants to patch `\addtocontents`, which causes an error if `\addtocontents` has been changed.
4. Therefore, `\addtocontents` is restored to its original here, since biblatex is about to be loaded.
5. This means that the newfloat's `chapterlistsgaps` option may no longer work.

```
\ifdef{\newfloat@addtocontents@ORI}{
    \let\addtocontents\newfloat@addtocontents@ORI
}{}
```

```
4 \LWR@ProvidesPackagePass{biblatex}[2018/03/04]
```

File 40 **lwarp-bibunits.sty**

§ 138 Package

bibunits

(*Emulates or patches code by* Thorsten Hansen.)

Pkg bibunits bibunits is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{bibunits}[2004/05/12]
2 \def\bu@bibdata{\BaseJobname}
```

File 41 **lwarp-bigdelim.sty**

§ 139 Package

bigdelim

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigdelim bigdelim is used as-is for print or `lateximage`, and patched for HTML.

The delimiters are displayed in HTML by printing the delimiter, the text, and a thick border across the side of the `\multirow` which indicates the actual height of the delimiter. The delimiter character is given a `<span>` class of `ldelim` or `rdelim`, and the default css sets this to `font-size:200%`

⚠ use `\mrowcell` `\ldelim` and `\rdelim` use `\multirow`, so `\mrowcell` must be used in the proper number of empty cells in the same column below `\ldelim` or `\rdelim`, but not in cells which are above or below the delimiter:

```
\begin{tabular}{lll}
<empty> & a & b \\
\ldelim{\{}{3}{.25in}[left ] & c & d \\
\mrowcell & e & f \\
\mrowcell & g & h \\
<empty> & i & j \\
\end{tabular}
```

<-> a b

left { c d
e f
g h

<-> i j

for HTML output:

First, remove the temporary definitions of \ldelim and \rdelim, which were previously defined for tabular scanning in case bigdelim was not loaded:

```
\let\ldelim\relax
\let\rdelim\relax
```

Next, load the package's new definitions:

```
\LWR@ProvidesPackagePass{bigdelim}[2018/08/03]
```

\ldelim {⟨*1:delimiter*⟩} {⟨*2:#rows*⟩} {⟨*3:width*⟩} [⟨*4:text*⟩]
\rdelim

```
\NewDocumentCommand{\LWR@HTML@ldelim}{m m m O{}}{%
\renewcommand{\LWR@multirowborder}{right}%
\multirow{#2}{#3}{#4 \InlineClass{ldelim}{#1}}%
}

\LWR@formatted{ldelim}

\NewDocumentCommand{\LWR@HTML@rdelim}{m m m O{}}{%
\renewcommand{\LWR@multirowborder}{left}%
\multirow{#2}{#3}{\InlineClass{rdelim}{#1} #4}%
}

\LWR@formatted{rdelim}
```

File 42 **lwarp-bigfoot.sty**

§ 140 Package

bigfoot

Pkg bigfoot bigfoot is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{bigfoot}[2015/08/30]

\RequirePackage{manyfoot}
\RequirePackage{perpage}

\def\RestyleFootnote#1#2{}
\def\FootnoteSpecific#1{}
\def\DefineFootnoteStack#1{}
\def\PushFootnoteMark#1{}
\def\PopFootnoteMark#1{}
\def\hfootfraction{0.9}
\def\vtypefraction{0.7}
\def\FootnoteMinimum{1sp}
\def\FootnoteMainMinimum{0pt}
\newcount\bigfoottolerance
\bigfoottolerance=100
\providecommand\footnotecarryratio{2}
```

File 43 **lwarp-bigstrut.sty**

§ 141 Package bigstrut

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg bigstrut bigstrut is used as-is for print or lateximage, and patched for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{bigstrut}[2018/08/03]

\LetLtxMacro\LWR@origbigstrut\bigstrut

\renewcommand\bigstrut[1][x]{}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bigstrut\LWR@origbigstrut%
}
```

File 44 **lwarp-bitpattern.sty**

§ 142 Package bitpattern

(*Emulates or patches code by* Jean-Marc Bourguet.)

Pkg bitpattern bitpattern is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bitpattern}[2015/12/11]

\xpatchcmd{\bitpattern}
    {\begingroup}
    {\begin{lateximage}[(-bitpattern-~\packagediagramname)]}
    {}
    {\LWR@patcherror{bitpattern}{bitpattern}}

\xpatchcmd{\bp@Done}
    {\endgroup}
    {\end{lateximage}}
    {}
    {\LWR@patcherror{bitpattern}{bp@Done}}
```

File 45 **lwarp-blowup.sty**

§ 143 Package blowup

Pkg blowup blowup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{blowup}[2018/01/02]
\newcommand*\blowUp[1]{}
```

File 46 **lwarp-booklet.sty**

§ 144 Package booklet

(*Emulates or patches code by* Peter Wilson.)

Pkg booklet booklet is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{booklet}[2009/09/02]
\newdimen\pageseplength
\newdimen\pagesepwidth
\newdimen\pagesepoffset
\newif\ifsidebyside     \sidebysidetrue
\newif\ifuselandscape   \uselandscapefalse
\newif\ifprintoption    \printoptionfalse
\newcommand*{\pagespersignature}[1]{}
\def\magstepminus#1{}
\newcommand*{\target}[3]{}
\newcommand*{\source}[3]{}
\newcommand*{\setpdftargetpages}{}
\newcommand*{\setdvipstargetpages}{}
\newcommand*{\targettopbottom}{}
\newcommand*{\twoupemptypage}{}
\newcommand*{\twoupclearpage}{}
\newcommand*{\checkforlandscape}{}
```

File 47 **lwarp-bookmark.sty**

§ 145 Package bookmark

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg bookmark bookmark is ignored.

for HTML output: Discard all options for lwarp-bookmark:

```
\LWR@ProvidesPackageDrop{bookmark}[2016/05/17]
\newcommand*{\bookmarksetup}[1]{}
\newcommand*{\bookmarksetupnext}[1]{}
\newcommand*{\bookmark}[2][]{}
\newcommand*{\bookmarkdefinestyle}[2]{}
\newcommand*{\bookmarkget}[1]{}
\newcommand{\BookmarkAtEnd}[1]{}
```

File 48 **lwarp-booktabs.sty**

§ 146 Package

booktabs

(*Emulates or patches code by* Simon Fear.)

Pkg booktabs

booktabs is emulated during HTML output, and used as-is during print output and inside an HTML lateximage.

for HTML output:

First, forget the placeholder macros:

```
\LetLtxMacro\toprule\relax
\LetLtxMacro\midrule\relax
\LetLtxMacro\cmidrule\cline
\LetLtxMacro\bottomrule\relax
\LetLtxMacro\addlinespace\relax
\LetLtxMacro\morecmidrules\relax
\LetLtxMacro\specialrule\relax

\LWR@ProvidesPackagePass{booktabs}[2016/04/27]


\DeclareDocumentCommand{\LWR@HTML@toprule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
                {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\global\booltrue{LWR@doingtbrule}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{toprule}

\DeclareDocumentCommand{\LWR@HTML@midrule}{o d()}%
    {%
        \IfValueTF{#1}%
            {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {%
                \ifbool{FormatWP}%
                {\LWR@docmidrule[#1](){1-\arabic{LWR@tabletotalLaTeXcols}}}%
                {\addtocounter{LWR@hlines}{1}}%
            }%
    \LWR@getmynexttoken}

\LWR@expandableformatted{midrule}

\DeclareDocumentCommand{\LWR@HTML@cmidrule}{O{\LWR@cmidrulewidth} d() m}{%
    \LWR@docmidrule[#1](#2){#3}%
    \LWR@getmynexttoken%
}%
```

```
\LWR@expandableformatted{cmidrule}

\DeclareDocumentCommand{\LWR@HTML@bottomrule}{o d()}{%
    \IfValueTF{#1}%
        {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
        {%
            \ifbool{FormatWP}%
            {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}}%
            {\global\booltrue{LWR@doingtbrule}}%
        }%
    \LWR@getmynexttoken%
}%

\LWR@expandableformatted{bottomrule}

\DeclareDocumentCommand{\LWR@HTML@addlinespace}{o}{}%

\LWR@expandableformatted{addlinespace}

\DeclareDocumentCommand{\LWR@HTML@morecmidrules}{}{}%

\LWR@expandableformatted{morecmidrules}

\DeclareDocumentCommand{\LWR@HTML@specialrule}{m m m d()}%
  {\LWR@docmidrule[#1]()}{1-\arabic{LWR@tabletotalLaTeXcols}}\LWR@getmynexttoken}%

\LWR@expandableformatted{specialrule}
```

File 49 **lwarp-bophook.sty**

§ 147 Package bophook

Pkg bophook bophook is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bophook}[2001/03/29]

\newcommand*{\AtBeginPage}[1]{}
\newcommand*{\PageLayout}[1]{}
```

File 50 **lwarp-bounddvi.sty**

§ 148 Package bounddvi

Pkg bounddvi bounddvi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bounddvi}[2016/12/28]
```

File 51 **lwarp-boxedminipage2e.sty**

§ 149 Package boxedminipage2e

(*Emulates or patches code by* Scott Pakin.)

Pkg boxedminipage2e boxedminipage2e is emulated for HTML, and used as-is for lateximages.

for HTML output: Discard all options for lwarp-boxedminipage2e:

```
\LWR@ProvidesPackagePass{boxedminipage2e}[2015/03/09]

\newenvironment{LWR@HTML@boxedminipage}{%
    \begin{BlockClass}{framebox}%
    \minipage%
}
{%
    \endminipage%
    \end{BlockClass}%
}
\LWR@formattedenv{boxedminipage}
```

File 52 **lwarp-breakurl.sty**

§ 150 Package breakurl

(*Emulates or patches code by* Vilar Camara Neto.)

Pkg breakurl breakurl is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{breakurl}[2013/04/10]

\LetLtxMacro\burl\url

\NewDocumentCommand{\LWR@burlaltb}{O{} +m m}{%
\LWR@ensuredoingapar%
\LWR@subhyperref{#2}%
\LWR@subhyperreftext{#3}%
\endgroup% restore catcodes
}

\newrobustcmd*{\burlalt}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
```

```
\LWR@burlaltb%
}

\LetLtxMacro\urlalt\burlalt
```

File 53 **lwarp-breqn.sty**

§ 151 Package

breqn

(*Emulates or patches code by* Michael J. Downes, Morten Høgholm.)

Pkg breqn breqn is patched for use by lwarp.

⚠ darray darray is not supported.

⚠ MathJax MathJax does not support breqn.

for HTML output:

```
\LWR@ProvidesPackagePass{breqn}[2017/01/27]

\setkeys{breqn}{spread={5pt}}

\def\eqnumside{R}
% \def\eqnumplace{T}

\BeforeBeginEnvironment{dmath}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath- \mathimagename]
}

\AfterEndEnvironment{dmath}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dmath*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dmath*- \mathimagename]
}

\AfterEndEnvironment{dmath*}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dseries}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dseries- \mathimagename]
}

```

```
\AfterEndEnvironment{dseries}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dseries*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dseries*- \mathimagename]
}

\AfterEndEnvironment{dseries*}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dgroup}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dgroup- \mathimagename]
}

\AfterEndEnvironment{dgroup}{
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{dgroup*}{
    \begin{BlockClass}{displaymath}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-breqn dgroup*- \mathimagename]
}

\AfterEndEnvironment{dgroup*}{
    \end{lateximage}\end{BlockClass}
}
```

File 54 **lwarp-bsheaders.sty**

§ 152 Package bsheaders

Pkg bsheaders bsheaders is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bsheaders}[1997/10/06]
```

File 55 **lwarp-bxpapersize.sty**

§ 153 Package bxpapersize

Pkg bxpapersize bxpapersize is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{bxpapersize}[2017/10/08]

\providecommand*\papersizesetup{\bxpapersizesetup}
\newcommand*\bxpapersizesetup[1]{}
```

File 56 **lwarp-bytefield.sty**

§ 154 Package

bytefield

(*Emulates or patches code by* Scott Pakin.)

Pkg bytefield bytefield is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{bytefield}[2017/09/15]

\BeforeBeginEnvironment{bytefield}{\begin{leximage}[(-bytefield-~\packagediagramname)]}

\AfterEndEnvironment{bytefield}{\end{leximage}}
```

File 57 **lwarp-cancel.sty**

§ 155 Package

cancel

Pkg cancel cancel is used as-is for SVG math, and emulated for HTML text output.

for HTML output:

```
\LWR@origRequirePackage{lwarp-xcolor}% for \convertcolorspec
\LWR@ProvidesPackagePass{cancel}[2013/04/12]
```

\cancelto is math-only, so is used as-is.

```
\LetLtxMacro\LWR@origcancel\cancel
\LetLtxMacro\LWR@origbcancel\bcancel
\LetLtxMacro\LWR@origxcancel\xcancel

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\cancel\LWR@origcancel%
\LetLtxMacro\bcancel\LWR@origbcancel%
\LetLtxMacro\xcancel\LWR@origxcancel%
}
```

\LWR@cancelcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@cancelcolor}[5]{%
\ifcsempty{#2}%
{\InlineClass(#5){#3}{#1}}%
{\LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}}%
}
```

\cancel {⟨*text*⟩}

```
\DeclareRobustCommand{\cancel}[1]{%
\begingroup%
\CancelColor%
\LWR@findcurrenttextcolor%
\color{black}%
\LWR@cancelcolor{#1}{LWR@tempcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
\endgroup%
}

\LetLtxMacro\bcancel\cancel
\LetLtxMacro\xcancel\cancel
```

File 58 **lwarp-canoniclayout.sty**

§ 156 Package canoniclayout

Pkg canoniclayout canoniclayout is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{canoniclayout}[2011/11/05]

\newcommand*{\currentfontletters}{}
\newcommand*{\charactersperpage}{}
```

File 59 **lwarp-caption.sty**

§ 157 Package caption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg caption caption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{caption}[2018/10/05]

\renewcommand\caption@ibox[3]{%
  \@testopt{\caption@iibox{#1}{#2}{#3}}{%
%         \wd\@tempboxa%
        \linewidth% lwarp
  }%
% \LWR@traceinfo{caption@ibox: done}%
}

\long\def\caption@iibox#1#2#3[#4]{%
  \@testopt{\caption@iiibox{#1}{#2}{#3}{#4}}\captionbox@hj@default
}

\long\def\caption@iiibox#1#2#3#4[#5]#6{%
```

```
%   \setbox\@tempboxa\hbox{#6}%
  \begingroup
  #1*% set \caption@position
  \caption@iftop{%
    \LWR@traceinfo{caption@iiibox top}%
    \endgroup
    \parbox[t]{#4}{%
      #1\relax
      \caption@setposition t%
%       \vbox{\caption#2{#3}}%
      {\caption#2{#3}}% lwarp
%       \captionbox@hrule
%       \csname caption@hj@#5\endcsname
%       \unhbox\@tempboxa
       #6% lwarp
    }%
  }{%
    \LWR@traceinfo{caption@iiibox bottom}%
    \endgroup
    \parbox[b]{#4}{%
      #1\relax
      \caption@setposition b%
%       \csname caption@hj@#5\endcsname
%       \unhbox\@tempboxa
         #6% lwarp
%       \captionbox@hrule
%       \vtop{\caption#2{#3}}%
      {\caption#2{#3}}% lwarp
     }%
  }%
\LWR@traceinfo{caption@iiibox: done}%
}

\def\caption@caption{%
  \caption@iftype
    {%
     \caption@checkgrouplevel\@empty\caption
     \caption@star
       {\caption@refstepcounter\@captype}%
       {\caption@dblarg{\@caption\@captype}}}%
    {\caption@Error{\noexpand\caption outside float}%
     \caption@gobble}%
}

\long\def\caption@@caption#1[#2]#3{%

  \ifcaption@star \else
    \caption@prepareanchor{#1}{#2}%
    \memcaptioninfo{#1}{\csname the#1\endcsname}{#2}{#3}%
    \@nameuse{nag@hascaptiontrue}%
  \fi

  \par
  \caption@beginex{#1}{#2}{#3}%
    \caption@setfloatcapt{%
```

```
      \caption@boxrestore
      \if@minipage
        \@setminipage
      \fi
      \caption@normalsize
      \ifcaption@star
        \let\caption@makeanchor\@firstofone
      \fi
      \@makecaption{\csname fnum@#1\endcsname}%
                   {\ignorespaces\caption@makeanchor{#3}}%

% \par
      \caption@if@minipage\@minipagetrue\@minipagefalse}%
  \caption@end%
}
```

\caption@@@make {⟨*caption label*⟩} {⟨*caption text*⟩}

```
\renewcommand\caption@@@make[2]{%
\LWR@traceinfo{caption@@@make}%
%   \sbox\@tempboxa{#1}%
%   \ifdim\wd\@tempboxa=\z@
%     \let\caption@lsep\relax
%   \fi
  \caption@ifempty{#2}{%
    \let\caption@lsep\@empty
    \let\caption@tfmt\@firstofone
  }%
  \caption@applyfont
%     \caption@fmt
    {\ifcaption@star\else
       \begingroup
        \captionlabelfont
         #1%
       \endgroup
     \fi}%
    {\ifcaption@star\else
       \begingroup
         \caption@iflf\captionlabelfont
         \relax
        \caption@lsep
       \endgroup
     \fi}%
    {{%
        \captiontextfont
%       \caption@ifstrut
%         {\vrule\@height\ht\strutbox\@width\z@}%
%         {}%
%       \nobreak\hskip\z@skip % enable hyphenation
        \caption@tfmt{#2}%
%       \caption@ifstrut
%         {\ifhmode\@finalstrut\strutbox\fi}%
%         {}%
      }}%
```

```
\LWR@traceinfo{caption@@@make done}%
}
```

\caption@@make@ {⟨⟩} {⟨⟩}

```
\renewcommand{\caption@@make@}[2]{%
  \caption@stepthecounter
  \caption@beginhook
      \caption@@@make{#1}{#2}%
  \caption@endhook
}
```

\caption@makecaption

```
\long\def\caption@makecaption#1#2{%
%   \caption@iftop
%     {\vskip\belowcaptionskip}%
%     {\caption@rule\vskip\abovecaptionskip}%
  \caption@@make{#1}{#2}%
%   \caption@iftop
%     {\vskip\abovecaptionskip\caption@rule}%
%     {\vskip\belowcaptionskip}%
}

% \DeclareCaptionBox{none}{#2}
\DeclareCaptionBox{parbox}{%
#2%
}
\DeclareCaptionBox{colorbox}{%
#2%
}
```

File 60 **lwarp-cases.sty**

§ 158 Package

cases

(*Emulates or patches code by* Donald Arseneau.)

Pkg cases cases is patched for use by lwarp.

⚠ MathJax MathJax does not support cases.

for HTML output:

```
\LWR@ProvidesPackagePass{cases}[2002/05/02]

\BeforeBeginEnvironment{numcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \mathimagename]
}

\AfterEndEnvironment{numcases}{
```

```
    \end{lateximage}\end{BlockClass}
}

\BeforeBeginEnvironment{subnumcases}{
    \begin{BlockClass}{displaymathnumbered}
    \LWR@newautoidanchor%
    \booltrue{LWR@indisplaymathimage}%
    \begin{lateximage}[-cases- \mathimagename]
}

\AfterEndEnvironment{subnumcases}{
    \end{lateximage}\end{BlockClass}
}
```

File 61 **lwarp-changebar.sty**

§ 159 Package

changebar

Pkg changebar changebar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{changebar}[2018/03/09]

\newcommand*{\cbstart}{}
\newcommand*{\cbend}{}
\newenvironment*{\changebar}{}{}
\newcommand*{\cbdelete}{}
\newcommand*{\nochnagebars}{}
\newcommand*{\cbcolor}[1]{}
\newlength{\changebarwidth}
\newlength{\deletebarwidth}
\newlength{\changebarsep}
\newcounter{changebargrey}
```

File 62 **lwarp-changelayout.sty**

§ 160 Package

changelayout

(*Emulates or patches code by* Ahmed Musa.)

Pkg changelayout changelayout is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{changelayout}[2009/10/07]

\renewrobustcmd\cpl@backtodefaults{}

\renewrobustcmd\cpl@checkifoddpage{%
  \cpl@oddpagefalse%
}

```

```
\renewrobustcmd\changepagelayout[1]{%
  \setkeys[KV]{changelay}{#1}%
}

\renewrobustcmd{\changetextlayout}[1]{\changepagelayout{#1}}

\renewrobustcmd\adjustpagelayout[1]{%
  \setkeys[KV@X]{changelay}{#1}%
}

\renewrobustcmd{\adjusttextlayout}[1]{\adjustpagelayout{#1}}

\renewrobustcmd\adjusttextwidth[1]{%
  \setkeys[KV]{changelay}{#1}%
   \begin{BlockClass}[color:\LWR@colorstyle{named}{\cpl@textcolor}]{changelayout}
        \color{\cpl@textcolor}%
        \cpl@content
    \end{BlockClass}
}
```

File 63 **lwarp-changepage.sty**

§ 161 Package

changepage

(*Emulates or patches code by* Peter Wilson.)

Pkg changepage changepage is ignored.

for HTML output: Discard all options for lwarp-changepage:

```
\LWR@ProvidesPackageDrop{changepage}[2009/10/20]

\newif\ifoddpage
\DeclareRobustCommand{\checkoddpage}{\oddpagetrue}
\DeclareRobustCommand{\changetext}[5]{}
\DeclareRobustCommand{\changepage}[9]{}

\@ifundefined{adjustwidth}{
\newenvironment{adjustwidth}[2]{}{}
\newenvironment{adjustwidth*}[2]{}{}
}{
\renewenvironment{adjustwidth}[2]{}{}
\renewenvironment{adjustwidth*}[2]{}{}
}

\DeclareDocumentCommand{\strictpagecheck}{}{}
\DeclareDocumentCommand{\easypagecheck}{}{}
```

File 64 **lwarp-changes.sty**

§ 162 Package

changes

(*Emulates or patches code by* Ekkart Kleinod.)

Pkg changes changes is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{changes}[2019/01/26]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\renewcommand{\ChangesListline}[4]{%
    \IfSubStr{\Changes@loc@show}{#1}{%
        \LWR@startpars%
        #2: #3 \qquad
        \nameref{\BaseJobname-autopage-#4}%
        \LWR@stoppars%
    }{}%
}

\renewcommand{\Changes@summaryline}[4]{%
    \IfSubStr{\Changes@loc@show}{#1}{%
       \ifthenelse{\not\equal{\Changes@loc@style}{compactsummary} \or #2 > 0}%
            {%
                #3:~#2#4%
            }{}%
    }{}%
}

\xpatchcmd{\listofchanges}
    {{\changesauthorname: \changesanonymousname}}
    {{\LWR@textcurrentcolor{\changesauthorname: \changesanonymousname}}}
    {}
    {\LWR@patcherror{changes}{listofchanges A}}

\xpatchcmd{\listofchanges}
    {\changesauthorname: \Changes@InID}
    {\LWR@textcurrentcolor{\changesauthorname: \Changes@InID}}
    {}
    {\LWR@patcherror{changes}{listofchanges B}}

\xpatchcmd{\listofchanges}
    {(\Changes@InName)}
    {\LWR@textcurrentcolor{(\Changes@InName)}}
    {}
    {\LWR@patcherror{changes}{listofchanges C}}

\xpatchcmd{\listofchanges}
    {\parbox{\Changes@summary@width}}
    {}
```

```
    {}
    {\LWR@patcherror{changes}{listofchanges D}}

\xpatchcmd{\Changes@Markup@comment}
    {%
        \ifthenelse{\isAnonymous{#2}}%
            {\textbf{[\arabic{Changes@commentCount#2}]:} }%
            {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
        #1%
    }
    {%
        \LWR@textcurrentcolor{%         lwarp
        \ifthenelse{\isAnonymous{#2}}%
            {\textbf{[\arabic{Changes@commentCount#2}]:} }%
            {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
        #1%
        }%                              lwarp
    }
    {}
    {\LWR@patcherror{changes}{\Changes@Markup@comment A}}

\xpatchcmd{\Changes@Markup@comment}
    {%
        \uwave{%
            \ifthenelse{\isAnonymous{#2}}%
                {\textbf{[\arabic{Changes@commentCount#2}]:} }%
                {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
            #1%
        }%
    }
    {%
        \LWR@textcurrentcolor{%         lwarp
        \uwave{%
            \ifthenelse{\isAnonymous{#2}}%
                {\textbf{[\arabic{Changes@commentCount#2}]:} }%
                {\textbf{[#3~\arabic{Changes@commentCount#2}]:} }%
            #1%
        }%
        }%                              lwarp
    }
    {}
    {\LWR@patcherror{changes}{\Changes@Markup@comment B}}

\xpatchcmd{\Changes@output}
    {\Changes@Markup@author{\Changes@output@author{#2}{left}}}
   {\LWR@textcurrentcolor{\Changes@Markup@author{\Changes@output@author{#2}{left}}}}
    {}
    {\LWR@patcherror{changes}{Changes@output A}}

\xpatchcmd{\Changes@output}
    {%
        \ifthenelse{\equal{#1}{added}}{\Changes@Markup@added{#3}}{}%
        \ifthenelse{\equal{#1}{deleted}}{\Changes@Markup@deleted{#4}}{}%
        \ifthenelse{\equal{#1}{replaced}}{%
            {\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}%
```

```
        }{}%
        \ifthenelse{\equal{#1}{highlight}}{\Changes@Markup@highlight{#3}}{}%
    }
    {%
        \LWR@textcurrentcolor{%
        \ifthenelse{\equal{#1}{added}}{\Changes@Markup@added{#3}}{}%
        \ifthenelse{\equal{#1}{deleted}}{\Changes@Markup@deleted{#4}}{}%
        \ifthenelse{\equal{#1}{replaced}}{%
            {\Changes@Markup@added{#3}}\allowbreak\Changes@Markup@deleted{#4}%
        }{}%
        \ifthenelse{\equal{#1}{highlight}}{\Changes@Markup@highlight{#3}}{}%
        }%
    }
    {}
    {\LWR@patcherror{changes}{Changes@output B}}

\xpatchcmd{\Changes@output}
    {\Changes@Markup@author{\Changes@output@author{#2}{right}}}
   {\LWR@textcurrentcolor{\Changes@Markup@author{\Changes@output@author{#2}{right}}}}
    {}
    {\LWR@patcherror{changes}{Changes@output C}}
```

File 65 **lwarp-chappg.sty**

§ 163 Package chappg

(*Emulates or patches code by* Robin Fairbairns.)

Pkg chappg chappg is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{chappg}[2006/05/09]

\renewcommand{\pagenumbering}[2][]{}
\providecommand{\chappgsep}{--}
```

File 66 **lwarp-chapterbib.sty**

§ 164 Package chapterbib

(*Emulates or patches code by* Donald Arseneau.)

Pkg chapterbib chapterbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chapterbib}[2010/09/18]

\xdef\@savedjobname{\BaseJobname}
\let\@currentipfile\@savedjobname
```

File 67 **lwarp-chemfig.sty**

§ 165 Package

chemfig

(*Emulates or patches code by* Christian Tellechea.)

Pkg chemfig chemfig is patched for use by lwarp.

If using \polymerdelim to add delimiters to a \chemfig, wrap both inside a single lateximage:

```
\begin{lateximage}[(-chemfig-~\packagediagramname)]
\chemfig{. . . }
\polymerdelim[. . . ]{. . . }
\end{lateximage}
```

The images are not hashed because they depend on external settings which may be changed at any time, and are unlikely to be reused inline anyhow.

for HTML output:

```
\LWR@ProvidesPackagePass{chemfig}

\catcode`\_=11

\@ifpackagelater{chemfig}{2019/04/18}%
{% 2019/04/18 or newer

    \LetLtxMacro\LWR@chemfig@origchemfig\chemfig

    \renewcommand*{\chemfig}[2][]{%
        \begin{lateximage}[(-chemfig-~\packagediagramname)]%
        \LWR@chemfig@origchemfig[#1]{#2}%
        \end{lateximage}%
    }

    \GlobalLetLtxMacro\LWR@chemfig@origCF_lewisc\CF_lewisc
    \gdef\CF_lewisc#1,#2\_nil{%
    \begin{lateximage}[(-chemfig-~\packagediagramname)]%
    \LWR@chemfig@origCF_lewisc#1,#2\_nil
    \end{lateximage}
    }

    \gpreto{\schemestart}{\begin{lateximage}[(-chemfig-~\packagediagramname)]}
    \gappto{\CF_schemestop}{\end{lateximage}}

}% 2019/04/18 or newer
{% older than 2019/04/18

    \LetLtxMacro\LWR@chemfig@origchemfig\chemfig

    \DeclareDocumentCommand\chemfig{s O{} O{} m}{%
```

```
        \begin{lateximage}[(-chemfig-~\packagediagramname)]%
        \IfBooleanTF{#1}{%
            \LWR@chemfig@origchemfig*[#2][#3]{#4}%
        }{%
            \LWR@chemfig@origchemfig[#2][#3]{#4}%
        }
        \end{lateximage}%
    }

    \LetLtxMacro\LWR@chemfig@origCF@lewis@b\CF@lewis@b

    \def\CF@lewis@b#1#2{%
    \begin{lateximage}[(-chemfig-~\packagediagramname)]%
    \LWR@chemfig@origCF@lewis@b{#1}{#2}%
    \end{lateximage}%
    }

    \preto{\schemestart}{\begin{lateximage}[(-chemfig-~\packagediagramname)]}
    \appto{\CF@schemestop}{\end{lateximage}}

}% older than 2019/04/18

\catcode`\_=8%



\LetLtxMacro\LWR@chemfig@origchemleft\chemleft

\def\chemleft#1#2\chemright#3{%
\begin{lateximage}[(-chemfig-~\packagediagramname)]%
\LWR@chemfig@origchemleft#1#2\chemright#3%
\end{lateximage}%
}

\LetLtxMacro\LWR@chemfig@origchemup\chemup

\def\chemup#1#2\chemdown#3{%
\begin{lateximage}[(-chemfig-~\packagediagramname)]%
\LWR@chemfig@origchemup#1#2\chemdown#3%
\end{lateximage}%
}
```

File 68 **lwarp-chemformula.sty**

§ 166 Package

chemformula

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemformula chemformula is patched for use by lwarp.

The svg images are hashed according to contents and local options. Global options are assumed to be constant document-wide.

⚠ chemformula with MathJax

chemformula works best without MathJax. If MathJax is used, `\displaymathother` must be used before `array`, and then `\displaymathnormal` may be used after. (The chemformula package adapts to `array`, but does not know about MathJax, and MathJax does not know about chemformula.)

While using MathJax, `\displaymathother` may also be used for other forms of display and inline math which contain chemformula expressions.

for HTML output:

```
\LWR@ProvidesPackagePass{chemformula}[2017/03/23]
\ExplSyntaxOn
```

`\ch` Enclose in an inline SVG image or MathJax. The `alt` tag is is the contents of the `\ch` expression. The filename is hashed, and also has additional hashing information based on the local options.

```
\RenewDocumentCommand \ch { O{}m }
 {%
```

To work inside `align` with `\displaymathother`, a simple version must be used to work with chemformula's adaptation to `align`.

```
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%  lwarp
    {
        \chemformula_ch:nn {#1} {#2}%   original
    }
```

If used as the outer level, must temporarily ensure MathJax is disabled:

```
    {
        \begingroup%
        \boolfalse{mathjax}%
```

An inline image is used, adjusted for the baseline:

```
        \LWR@subsingledollar*{% lwarp
            \textbackslash{}ch\{\LWR@HTMLsanitize{#2}\}% alt text
        }{%
         \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}% add'l hashing
        }%
        {%
            \chemformula_ch:nn {#1} {#2}%   original
        }%
        \endgroup%
    }
 }
```

`\chcpd` Similar to `\ch`.

```
\cs_gset_protected:Npn \chemformula_chcpd:nn #1#2
 {
   \begingroup%
   \boolfalse{mathjax}%
   \LWR@subsingledollar*{% lwarp
       \textbackslash{}chcpd\{\LWR@HTMLsanitize{#2}\}%
   }{%
```

```
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{% original
    \group_begin:
      \tl_if_blank:nF {#2}
        {
          \keys_set:nn {chemformula} {#1}
          \__chemformula_save_catcodes:
          \__chemformula_sanitize:Nn
            \l__chemformula_chemformula_tmpa_tl
            {#2}
          \__chemformula_input_compound_no_check:NV
            \l__chemformula_compound_tl
            \l__chemformula_chemformula_tmpa_tl
          \__chemformula_prepare_output:N \l__chemformula_compound_tl
          \chemformula_write:V \l__chemformula_compound_tl
        }
    \group_end:
    }
    \endgroup
  }
```

\charrow If standalone, appears in a regular lateximage.

```
\RenewDocumentCommand \charrow { mO{}O{} }
{
    \begin{lateximage}[(-chemformula- charrow)]
    \group_begin:
      \__chemformula_draw_arrow:nnn {#1} {#2} {#3}
    \group_end:
    \end{lateximage}
}
```

\chname If standalone, appears in a regular lateximage, hashed according to contents.

```
\RenewDocumentCommand \chname { R(){}R(){} }
  {
    \begin{lateximage}*[%
        \textbackslash{}chname(\LWR@HTMLsanitize{#1})(\LWR@HTMLsanitize{#2})
    ]%
        \chemformula_chwritebelow:nn {#1} {#2}
    \end{lateximage}
  }
```

\chlewis Placed inline, hashed according to contents and options.

```
\RenewDocumentCommand \chlewis { O{}mm }
  {
    \begingroup%
    \boolfalse{mathjax}%
    \LWR@subsingledollar*{\textbackslash{}chlewis\{#2\}\{#3\}}%
    {
        \protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{
        \chemformula_lewis:nnn {#1} {#2} {#3}
    }
```

```
    \endgroup%
}
```

lwarp redefines the $ character, so special handling is required to escape math expressions inside \ch.

This boolean tracks a new kind of escaped math:

```
\bool_new:N      \l__chemformula_first_last_LWRdollar_bool
```

\chemformula_input_escape_math

Adds additional escaping for the new dollar definition:

```
\cs_gset_protected:Npn \__chemformula_input_escape_math:n #1
  {
    \__chemformula_first_last_math:n {#1}
    \bool_if:NT \l__chemformula_first_last_dollar_bool
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool
        \__chemformula_read_escape_dollar:w #1 \q_nil
      }
    \bool_if:NT \l__chemformula_first_last_mathbraces_bool
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool
        \__chemformula_read_escape_mathbraces:w #1 \q_nil
      }
```

Added by lwarp:

```
    \bool_if:NT \l__chemformula_first_last_LWRdollar_bool%      lwarp
      {
        \bool_set_true:N \l__chemformula_first_last_math_bool%  lwarp
        \__chemformula_read_escape_LWRdollar:w #1 \q_nil%       lwarp
      }
  }
```

\chemformula_read_escape_LWRdollar

The following parses the contents inside the new dollars.

lwarp keeps the dollar as its original math shift until the document starts. While chemmacros is being patched, the dollar must temporarily be set to its new meaning during the following definition.

```
\begingroup
\catcode`\$=\active

\cs_new_protected:Npn \__chemformula_read_escape_LWRdollar:w $#1$ \q_nil
{
    \__chemformula_read_escape_math:n {#1}
}

\endgroup
```

\chemformula_bool_set_if_first_last

The following looks at the first and last tokens for delimiters to escape math inside \ch. The original definition is modified to look for the control sequences which are used by the new meaning of $.

```
\cs_new_protected:Npn \__chemformula_bool_cs_set_if_first_last:NnNN #1#2#3#4
  {
    \int_zero:N \l__chemformula_tmpa_int
    \int_zero:N \l__chemformula_tmpb_int
    \int_set:Nn \l__chemformula_tmpa_int { \tl_count:n {#2} }
    \tl_map_inline:nn {#2}
      {
        \int_incr:N \l__chemformula_tmpb_int
        \int_compare:nT { \l__chemformula_tmpb_int = 1 }
          {
```

At the start, the cs_ version compares control sequences:

```
            \ifdefstrequal{##1}{#3}% lwarp
                {
                    \bool_set_true:N #1
                }% lwarp
                {}
          }
```

At the end, compare more control sequences:

```
        \int_compare:nT { \l__chemformula_tmpb_int = \l__chemformula_tmpa_int }
          {
            \ifdefstrequal{##1}{#4}
                {}
                {
                    \bool_set_false:N #1
                }
          }
      }
  }
```

\chemformula_first_last_math

Modified to check for the new meaning of $ at first/last:

```
\cs_gset_protected:Npn \__chemformula_first_last_math:n #1
  {
    \bool_set_false:N \l__chemformula_first_last_math_bool
    \bool_set_false:N \l__chemformula_first_last_dollar_bool
    \bool_set_false:N \l__chemformula_first_last_LWRdollar_bool%    lwarp
    \bool_set_false:N \l__chemformula_first_last_mathbraces_bool
    \__chemformula_bool_set_if_first_last:Nnnn
      \l__chemformula_first_last_dollar_bool
      {#1}
      { $ } { $ }
    \bool_if:NF \l__chemformula_first_last_dollar_bool
      {
        \__chemformula_bool_set_if_first_last:Nnnn
```

```
          \l__chemformula_first_last_mathbraces_bool
          {#1}
          { \( } { \) }
```

Added by lwarp:

```
          \bool_if:NF \l__chemformula_first_last_mathbraces_bool%   lwarp
            {
                \__chemformula_bool_cs_set_if_first_last:NnNN
                \l__chemformula_first_last_LWRdollar_bool
                {#1}
                { \LWR@newsingledollar } { \LWR@newsingledollar }
            }%  lwarp
      }
  }

\ExplSyntaxOff
```

File 69 **lwarp-chemgreek.sty**

§ 167 Package

chemgreek

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemgreek chemgreek is patched for use by lwarp.

Greek symbols ⚠ package selection To use text-mode symbols, use packages textalpha or textgreek. Using the other packages supported by chemgreek will result in math-mode greek characters, which will result in svg images being used. These images will be hashed.

⚠ XeLaTeX, LuaLaTeX If using XeLaTeX or LuaLaTeX, select the fontspec mapping:

```
\selectchemgreekmapping{fontspec}
```

for HTML output:

```
\LWR@ProvidesPackagePass{chemgreek}[2016/02/10]

\ExplSyntaxOn

\cs_gset_protected:Npn \chemgreek_text:n #1
  { { \text {#1} } }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemgreek_text:n #1%
  { \ensuremath { \text {#1} } }%
}

\ExplSyntaxOff
```

File 70 **lwarp-chemmacros.sty**

§ 168 Package

chemmacros

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemmacros chemmacros is patched for use by lwarp.

for HTML output:

```
1 \LWR@ProvidesPackagePass{chemmacros}[2017/08/28]
```

SVG file hashing assumes that the relevent options are constant for the entire document.

§ 168.1 Changes to the user's document

⚠ \makepolymerdelims When using \makepolymerdelims, enclose the entire expression inside a polymerdelims environment, such as (from the chemmacros manual):

```
\begin{polymerdelims}
\chemfig{-[@{op,.75}]CH_2-CH(-[6]Cl)-[@{cl,0.25}]}
\makepolymerdelims{5pt}[27pt]{op}{cl}
\end{polymerdelims}
```

⚠ redox reactions Redox reactions must be enclosed inside a redoxreaction environment. For print output, extra space must be included above and/or below the result, so they are declared as arguments to the environment, instead of being manually entered as per the chemmacros manual. For HTML output, the extra space is ignored and a lateximage is used instead.

```
\begin{redoxreaction}{7mm}{7mm}
\OX{a,Na} $\rightarrow$ \OX{b,Na}\pch\redox(a,b){oxidation}
\end{redoxreaction}
```

§ 168.2 Code

§ 168.3 Loading modules

Patching chemmacros modules must be done \AtBeginDocument, since modules are invoked by the user in the preamble, and each patch is only done if the module is loaded.

```
2 \ExplSyntaxOn
3
4 \newcommand{\@ifchemmacrosmoduleloaded}[1]{%
5 \@ifl@aded{\c__chemmacros_module_extension_tl}{\c__chemmacros_module_prefix_tl.#1}%
6 }
7
8 \ExplSyntaxOff
```

§ 168.4 New environments

\makepolymerdelims and redox reactions must be enclosed in a lateximage during HTML output. These environments are provided here in HTML mode, and in the lwarp core in print mode, as a high-level semantic syntax which automatically embeds the contents in a lateximage with an appropriate alt tag.

Env polymerdelims

```
\DeclareDocumentEnvironment{polymerdelims}{}
{\begin{lateximage}[(-chemmacros- polymer)]}
{\end{lateximage}}
```

Env redoxreaction {⟨*space above*⟩} {⟨*space below*⟩}

For HTML output, the above and below space is ignored, and a lateximage is used instead. For the print output version, see section 86.

```
\DeclareDocumentEnvironment{redoxreaction}{m m}
{\begin{lateximage}[(-chemmacros- redoxreaction)]}
{\end{lateximage}}
```

```
\ExplSyntaxOn
```

§ 168.5 Acid-base

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{acid-base}{
\PackageInfo{lwarp}{Patching~chemmacros~module~acid-base}

\cs_gset_protected:Npn \chemmacros_p:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{
        \textbackslash{}p\{\LWR@HTMLsanitize{#1}\}
    }{
        chemmacrosp\protect\LWR@HTMLsanitize{\detokenize\expandafter{#1}}%
    }{
    \group_begin:
      \mbox
        {
          \chemmacros_p_style:n {p}
          \ensuremath {#1}
        }
    \group_end:
    }
    \endgroup
  }

\RenewDocumentCommand \pH  {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {H} }
```

```
    }
    \endgroup
}

\RenewDocumentCommand \pOH {} {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pOH}{chemmacros}{
        \chemmacros_p:n { \chemmacros_chemformula:n {OH} }
    }
    \endgroup
}

\RenewDocumentCommand \pKa {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKa{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Ka \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
    \endgroup
  }

\RenewDocumentCommand \pKb {O{}}
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}pKb{[}#1{]}}{chemmacros #1}{
        \chemmacros_p:n
        {
            \Kb \ifblank {#1} {}
            { {} \c_math_subscript_token { \chemmacros_bold:n {#1} } }
        }
    }
    \endgroup
  }

\LetLtxMacro\LWR@chemmacros@origKa\Ka
\renewcommand*{\Ka}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Ka}{chemmacros}{%
        \LWR@chemmacros@origKa%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKb\Kb
\renewcommand*{\Kb}{%
    \begingroup
    \boolfalse{mathjax}
```

```
    \LWR@subsingledollar*{\textbackslash{}Kb}{chemmacros}{%
        \LWR@chemmacros@origKb%
    }%
    \endgroup
}

\LetLtxMacro\LWR@chemmacros@origKw\Kw
\renewcommand*{\Kw}{%
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}Kw}{chemmacros}{
        \LWR@chemmacros@origKw
    }
    \endgroup
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.6 Charges

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{charges}{
\PackageInfo{lwarp}{Patching~chemmacros~module~charges}

\cs_gset_protected:Npn \fplus  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fplus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fplus:}  }
    \endgroup
}
\cs_gset_protected:Npn \fminus {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}fminus}{chemmacros}
    { \LWR@origensuredmath{\chemformula_fminus:} }
    \endgroup
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.7 Nomenclature

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{nomenclature}{
\PackageInfo{lwarp}{Patching~chemmacros~module~nomenclature}

\cs_gset_protected:Npn \chemmacros_charge:n #1
  {
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}
    {\chemmacros_chemformula:n { {}^{#1} }}
    {
        \ifmmode
```

```
            {\chemmacros_chemformula:n { {}^{#1} }}
        \else
            { \textsuperscript{\ensuremath{#1}} }
        \fi
    }
  }


\LetLtxMacro\LWR@chemmacros@origchemprime\chemprime

\protected\def\chemprime { \HTMLunicode{2032} }

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\chemprime\LWR@chemmacros@origchemprime%
}

\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_cip:n #1
  {
    \tl_set:Nn \l__chemmacros_tmpa_tl {#1}
    \int_step_inline:nnnn {0} {1} {9}
      {
        \tl_replace_all:Nnn \l__chemmacros_tmpa_tl
          {##1}
          { { \l__chemmacros_cip_number_tl ##1} }
      }
    {
        \l__chemmacros_cip_inner_tl
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \l__chemmacros_tmpa_tl
        }}% lwarp
    }
  }
\EndChemCompatibility

\RenewDocumentCommand \Sconf { O{S} } {
\begin{lateximage}[\textbackslash{}Sconf{[}#1{]}]
    \chemmacros_sconf:n {#1}
\end{lateximage}
}

\RenewDocumentCommand \Rconf { O{R} } {
\begin{lateximage}[\textbackslash{}Rconf{[}#1{]}]
    \chemmacros_rconf:n {#1}
\end{lateximage}
}

\cs_gset_protected:Npn \chemmacros_hapto:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}hapto\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
```

```
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemeta }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_dento:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}dento\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        {
            \chemmacros_if_compatibility:nnTF {>} {5.7}
            { \c_true_bool }
            { \c_false_bool }
        }
        { \chemkappa }
        {#1}
    }
    \endgroup
  }

\cs_gset_protected:Npn \chemmacros_bridge:n #1
  {
    \begingroup
    \boolfalse{mathjax}
    \LWR@subsingledollar*{\textbackslash{}bridge\{#1\}}{chemmacros}{
        \chemmacros_coordination_symbol:nnnn
        { \l__chemmacros_coord_use_hyphen_bool }
        { \l__chemmacros_bridge_super_bool }
        { \chemmu }
        {#1}
    }
    \endgroup
  }
}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.8 Particles

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{particles}{
\PackageInfo{lwarp}{Patching~chemmacros~module~particles}

\cs_gset_protected:Npn \chemmacros_declare_nucleophile:Nn #1#2
  {
    \cs_set_protected:cpn {__chemmacros_ \chemmacros_remove_backslash:N #1:}
      {
        \bool_if:NTF \l__chemmacros_nucleophile_elpair_bool
          {
```

```
            \chemmacros_elpair:n { #2 }
            \chemmacros_if_compatibility:nnT {>=} {5.3}
              { \skip_horizontal:N \l__chemmacros_nucleophile_dim }
            \chemmacros_chemformula:n { {}^{-} }
          }
          { \chemmacros_chemformula:n { #2^{-} } }
      }
    \DeclareDocumentCommand #1 {o}
      {%
        \begin{lateximage}%
        \group_begin:%
          \IfNoValueF {##1}%
            { \chemmacros_set_keys:nn {particles} {##1} }%
          \use:c {__chemmacros_ \chemmacros_remove_backslash:N #1:}%
        \group_end:%
        \end{lateximage}%
      }
  }

\RenewChemNucleophile \Nuc {Nu}
\RenewChemNucleophile \ba  {ba}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.9 Phases

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{phases}{
\PackageInfo{lwarp}{Patching~chemmacros~module~phases}

\cs_undefine:N \chemmacros_phase:n
\cs_new_protected:Npn \chemmacros_phase:n #1
  {
    \chemmacros_leave_vmode:
    \bool_if:NTF \l__chemmacros_phases_sub_bool
      {
        \ifnumequal{\value{LWR@lateximagedepth}}{0}
        {
            \textsubscript{ (#1) }
        }
        {
            \chemformula_subscript:n { (#1) }
        }
      }
      {
        \skip_horizontal:N \l__chemmacros_phases_space_dim
        \chemmacros_text:n { (#1) }
      }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.10 Mechanisms

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{mechanisms}{
\PackageInfo{lwarp}{Patching~chemmacros~module~mechanisms}

\chemmacros_define_keys:nn {textmechanisms}
 {
   type      .choice: ,
   type /    .code:n    =
     {
       \__chemmacros_set_mechanisms:nnn { S }
         {
             \textsubscript{N}
         }
         { }
     } ,
   type / 1  .code:n    =
     {
       \__chemmacros_set_mechanisms:nnn { S }
         {
             \textsubscript{N}
           1
         }
         { }
     } ,
   type / 2  .code:n    =
     {
       \__chemmacros_set_mechanisms:nnn { S }
         {
             \textsubscript{N}
           2
         }
         { }
     } ,
   type / se .code:n    =
     {
       \__chemmacros_set_mechanisms:nnn { S }
         {
             \textsubscript{E}
         }
         { }
     } ,
   type / 1e .code:n    =
     {
       \__chemmacros_set_mechanisms:nnn { S }
         {
             \textsubscript{E}
           1
         }
         { }
     } ,
   type / 2e .code:n    =
     {
       \__chemmacros_set_mechanisms:nnn { S }
         {
```

```
              \textsubscript{E}
            2
          }
          { }
      } ,
    type / ar .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { S }
          {
              \textsubscript{E}
          }
          { Ar - }
      } ,
    type / e  .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { } { } } ,
    type / e1 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 1 } { } } ,
    type / e2 .code:n    =
      { \__chemmacros_set_mechanisms:nnn { E } { 2 } { } } ,
    type / cb .code:n    =
      {
        \__chemmacros_set_mechanisms:nnn { E }
          {
            1
              \textsubscript{cb}
          }
          { }
      } ,
    type      .default:n =
  }

\cs_gset_protected:Npn \chemmacros_mechanisms:n #1
  {
    \tl_if_blank:nTF {#1}
      { \chemmacros_set_keys:nn {textmechanisms} { type } }
      { \chemmacros_set_keys:nn {textmechanisms} { type = #1 } }
    \mbox
      {
        \tl_use:N \l__chemmacros_mechanisms_ar_tl
        \tl_use:N \l__chemmacros_mechanisms_type_tl
        \tl_use:N \l__chemmacros_mechanisms_mol_tl
      }
  }

\appto\LWR@restoreorigformatting{%
\cs_set_protected:Npn \chemmacros_mechanisms:n #1%
  {%
    \tl_if_blank:nTF {#1}%
      { \chemmacros_set_keys:nn {mechanisms} { type } }%
      { \chemmacros_set_keys:nn {mechanisms} { type = #1 } }%
    \mbox%
      {%
        \tl_use:N \l__chemmacros_mechanisms_ar_tl%
        \tl_use:N \l__chemmacros_mechanisms_type_tl%
        \tl_use:N \l__chemmacros_mechanisms_mol_tl%
```

```
      }%
  }%
}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.11 Newman

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{newman}{
\PackageInfo{lwarp}{Patching~chemmacros~module~newman}

\RenewDocumentCommand \newman {od()m}%
  {
    \IfValueTF{#2}
    {\begin{lateximage}[\textbackslash{}newman(#2)\{#3\}]}
    {\begin{lateximage}[\textbackslash{}newman\{#3\}]}
    \group_begin:
      \IfNoValueF  {#1} { \chemmacros_set_keys:nn {newman} {#1} }
      \IfNoValueTF {#2}
        { \chemmacros_newman:nn {  } {#3} }
        { \chemmacros_newman:nn {#2} {#3} }
    \group_end:
    \end{lateximage}
  }%

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.12 Orbital

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{orbital}{
\PackageInfo{lwarp}{Patching~chemmacros~module~orbital}

\RenewDocumentCommand \orbital {om}
  {
    \IfValueTF{#1}
    {
        \begin{lateximage}[%
            \textbackslash{}orbital{[}\LWR@HTMLsanitize{#1}{]}\{#2\}%
        ][][margin-left: 1em ; margin-right: 1em]
    }
    {
        \begin{lateximage}[%
            \textbackslash{}orbital\{#2\}%
        ][][margin-left: 1em ; margin-right: 1em]
    }
    \group_begin:
      \chemmacros_set_keys:nn {orbital/type} {#2}
      \IfNoValueTF {#1}
        { \chemmacros_orbital:n {  } }
        { \chemmacros_orbital:n {#1} }
    \group_end:
```

```
    \end{lateximage}
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.13 Reactions

\chemmacros_declare_reaction_env {⟨*chem*⟩} {⟨*math*⟩} {⟨*args number*⟩} {⟨*argument list ({#2}{#3}...)*⟩}

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{reactions}{
\PackageInfo{lwarp}{Patching~chemmacros~module~reactions}

\cs_gset_protected:Npn \chemmacros_declare_reaction_env:nnnn #1#2#3#4
  {
   \exp_args:Nnx \DeclareDocumentEnvironment {#1} { O{} \prg_replicate:nn {#3+0} {m} }
      {
        \boolfalse{mathjax}%    lwarp
        \chemmacros_add_reaction_description:n {##1}
        \__chemmacros_begin_reaction:
        \chemmacros_reaction_read:nnw {#2} {#4}
      }
      {
        \__chemmacros_end_reaction:
      }
  }
\cs_generate_variant:Nn \chemmacros_declare_reaction_env:nnnn {nnnV}

\RenewChemReaction {reaction}   {equation}
\RenewChemReaction {reaction*}  {equation*}
\RenewChemReaction {reactions}  {align}
\RenewChemReaction {reactions*} {align*}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.14 Redox

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{redox}{
\PackageInfo{lwarp}{Patching~chemmacros~module~redox}

\NewDocumentCommand \LWR@chemmacros@ox { s m >{\SplitArgument{1}{,}}m }
  {
    \IfBooleanTF {#1}
      { \chemmacros_ox:nnnn {#1} {#2} #3 }
      { \chemmacros_ox:nnnn {  } {#2} #3 }
  }

\RenewDocumentCommand \ox { s O{} m }
  {
    \begingroup
    \boolfalse{mathjax}
    \IfBooleanTF {#1}
```

```
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            star \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox* {#2} {#3}% contents
        }%
      }
      {
        \LWR@subsingledollar*{% yes hash
            \textbackslash{}ox*\{\LWR@HTMLsanitize{#3}\}% alt
        }{%
            \protect\LWR@HTMLsanitize{\detokenize\expandafter{#2}}%
        }{%
            \LWR@chemmacros@ox {#2} {#3}% contents
        }%
      }
    \endgroup
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.15 Scheme

Fix for chemmacros as of v5.8b, when using newfloat and babel:

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{scheme}{
\PackageInfo{lwarp}{Patching~chemmacros~module~scheme}

\ifdefstring{\schemename}{los}{
\SetupFloatingEnvironment{scheme}{
name = \chemmacros_translate:n {scheme-name}
}
}{}

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.16 Spectroscopy

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{spectroscopy}{
\PackageInfo{lwarp}{Patching~chemmacros~module~spectroscopy}

\ChemCompatibilityTo{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
      {
        \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
        \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
      }
```

```
    \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%     \chemmacros_chemformula:n { ^{#1} }
    \textsuperscript{#1}
    \bool_if:NTF \l__chemmacros_nmr_parse_bool
      { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
      { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
    \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
    \tl_use:N \l__chemmacros_nmr_method_tl
  }
\EndChemCompatibility
\ChemCompatibilityFrom{5.8}
\cs_gset_protected:Npn \__chemmacros_nmr_base:nn #1#2
  {
    \group_begin:
      \tl_use:N \l__chemmacros_nmr_base_format_tl
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl { \{ }
          \tl_put_right:Nn \g__chemmacros_nmr_element_coupled_tl { \} }
        }
      \tl_put_left:Nn \g__chemmacros_nmr_element_coupled_tl {#2}
%       \chemmacros_chemformula:n { ^{#1} }
      \textsuperscript{#1}
      \tl_if_blank:VF \g__chemmacros_nmr_element_coupled_tl
        {
          \bool_if:NTF \l__chemmacros_nmr_parse_bool
            { \chemformula_ch:nV {} \g__chemmacros_nmr_element_coupled_tl }
            { \chemmacros_chemformula:V \g__chemmacros_nmr_element_coupled_tl }
        }
      \tl_use:N \l__chemmacros_nmr_element_method_connector_tl
      \tl_use:N \l__chemmacros_nmr_method_tl
    \group_end:
  }
\EndChemCompatibility


\cs_gset_protected:Npn \chemmacros_nmr_position:n #1
  {
    \chemmacros_chemformula:x
      {
        \exp_not:V \g__chemmacros_nmr_element_tl
        \bool_if:NF \l__chemmacros_nmr_position_side_bool
          {
            \tl_if_eq:NnTF \l__chemmacros_nmr_position_tl {^}% lwarp
            { \textsuperscript{\exp_not:n { {#1} }} }% lwarp
            { \textsubscript{\exp_not:n { {#1} }} }% lwarp
%             \exp_not:V \l__chemmacros_nmr_position_tl
%             \exp_not:n { {#1} }
          }
      }
    \bool_if:NT \l__chemmacros_nmr_position_side_bool
      {
        \tl_use:N \l__chemmacros_nmr_position_tl
        \__chemmacros_nmr_position:n {#1}
      }
```

```
  }

\cs_gset_protected:Npn \__chemmacros_nmr_coupling:w (#1;#2)
  {
    \tl_set:Nn \l__chemmacros_nmr_coupling_bonds_tl
      {
        \l__chemmacros_nmr_coupling_bonds_pre_tl
        #1
        \l__chemmacros_nmr_coupling_bonds_post_tl
      }
    \bool_if:NTF \l__chemmacros_nmr_coupling_nuclei_sub_bool
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
%             \c_math_subscript_token
            \textsubscript% lwarp
              {
                \l__chemmacros_nmr_coupling_nuclei_pre_tl
                \chemmacros_chemformula:n {#2}
                \l__chemmacros_nmr_coupling_nuclei_post_tl
              }
          }
      }
      {
        \tl_set:Nn \l__chemmacros_nmr_coupling_nuclei_tl
          {
            \l__chemmacros_nmr_coupling_nuclei_pre_tl
            \chemmacros_chemformula:n {#2}
            \l__chemmacros_nmr_coupling_nuclei_post_tl
          }
      }
    \__chemmacros_nmr_coupling_aux_i:w
  }

\AfterEndPreamble{% After \AtBeginDocument
% \NMR{<num>,<elem>}(<num>,<unit>)[<solvent>] ALL arguments are optional
% \NMR* same but without ": $\delta$" at end
\cs_gset_protected:Npn \chemmacros_nmr:nnnn #1#2#3#4
    {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item \scan_stop: }
    \group_begin:
        \chemmacros_leave_vmode:
        \bool_set_false:N \l__chemmacros_nmr_frequency_bool
        \bool_set_false:N \l__chemmacros_nmr_solvent_bool
        \tl_if_empty:nF {#3}
        { \bool_set_true:N \l__chemmacros_nmr_frequency_bool }
        \tl_if_empty:nF {#4}
        { \bool_set_true:N \l__chemmacros_nmr_solvent_bool }
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            ||
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_delimiters_bool }
```

```
        \bool_if:nT
        {
            \l__chemmacros_nmr_frequency_bool
            &&
            \l__chemmacros_nmr_solvent_bool
        }
        { \bool_set_true:N \l__chemmacros_nmr_comma_bool }
        \tl_if_empty:nTF {#2}
        {
            \__chemmacros_nmr_nucleus:VV
            \l__chemmacros_nmr_isotope_default_tl
            \l__chemmacros_nmr_element_default_tl
        }
        { \__chemmacros_nmr_nucleus:w #2 \q_stop }
        \mode_if_math:TF
        {
            \text
            {
                \group_begin:
                \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
                \__chemmacros_nmr_base:VV
                    \g__chemmacros_nmr_isotope_tl
                    \g__chemmacros_nmr_element_tl
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ~ ( }
                \bool_if:NT \l__chemmacros_nmr_frequency_bool
                    { \__chemmacros_nmr_frequency:n {#3} }
                \bool_if:NT \l__chemmacros_nmr_comma_bool
                    { , ~ }
                \bool_if:NT \l__chemmacros_nmr_solvent_bool
                    { \chemmacros_chemformula:n {#4} }
                \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                    { ) }
                \tl_if_blank:nT {#1} {:~}
}}% lwarp
                \group_end:
            }
            \tl_if_blank:nT {#1}
            {
                \delta
                \text { \l__chemmacros_nmr_delta_tl }
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {=}
            }
        }
        {
            \group_begin:
            \tl_use:N \l__chemmacros_nmr_format_tl
\LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            \__chemmacros_nmr_base:VV
                \g__chemmacros_nmr_isotope_tl
                \g__chemmacros_nmr_element_tl
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {~(}
            \bool_if:NT \l__chemmacros_nmr_frequency_bool
```

```
                { \__chemmacros_nmr_frequency:n {#3} }
            \bool_if:NT \l__chemmacros_nmr_comma_bool
                {,~}
            \bool_if:NT \l__chemmacros_nmr_solvent_bool
                {
                \bool_if:NTF \l__chemmacros_nmr_parse_bool

% lwarp
                    { \chemformula_ch:nn { } {#4} }%  original
                   {\ch{#4}}%  lwarp
                    {#4}
                }
            \bool_if:NT \l__chemmacros_nmr_delimiters_bool
                {()}
}}% lwarp
            \tl_if_blank:nT {#1} {:}
            \group_end:
            \tl_if_blank:nT {#1}
            {
                \tl_use:N \c_space_tl
                \c_math_toggle_token
                \delta
                \c_math_toggle_token
                \l__chemmacros_nmr_delta_tl
                \bool_if:NT \l__chemmacros_nmr_use_equal_bool {~=}
            }
        }
    \group_end:
    }
}% AfterEndPremble


\RenewDocumentCommand \chemmacros_data:w { smo }
  {
    \bool_if:NT \l__chemmacros_nmr_list_bool { \item }
      {
% lwarp
        \tl_use:N \l__chemmacros_nmr_format_tl #2
        \tl_use:N \l__chemmacros_nmr_format_tl
        \LWR@textcurrentcolor{\LWR@textcurrentfont{% lwarp
            #2
            \IfNoValueF {#3} { ~ ( #3 ) }
         \IfBooleanT {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { : } }
        }}% lwarp
      }
    \IfBooleanF {#1} { \bool_if:NT \l__chemmacros_nmr_use_equal_bool { ~ = } }
  }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument
```

§ 168.17 Thermodynamics

```
\AtBeginDocument{
\@ifchemmacrosmoduleloaded{thermodynamics}{
\PackageInfo{lwarp}{Patching~chemmacros~module~thermodynamics}

```

```
\cs_gset_protected:Npn \chemmacros_state:nn #1#2
 {
   \group_begin:
     \boolfalse{mathjax}
     \chemmacros_set_keys:nn {thermodynamics} {#1}
       \LWR@subsingledollar*{% yes hashing
           \textbackslash{}state\{\LWR@HTMLsanitize{#2}\}% alt
       }{%
           chemmacros_state% add'l hashing
           #1% options
           LSP \tl_use:N \l__chemmacros_state_sp_left_tl% super/subscripts
           LSB \tl_use:N \l__chemmacros_state_sb_left_tl
           RSP \tl_use:N \l__chemmacros_state_sp_right_tl
           RSB \tl_use:N \l__chemmacros_state_sb_right_tl
       }
       {
        \LWR@origensuredmath{
         \chemmacros_text:V \l__chemmacros_state_pre_tl
         \c_math_superscript_token
           { \chemmacros_text:V \l__chemmacros_state_sp_left_tl }
```

Only add the subscripts if they are being used. This avoids causing an incorrect depth, as the empty subscript will be measured by TEX but cropped out by *pdfcrop*.

```
         \tl_if_empty:NTF \l__chemmacros_state_sb_left_tl
         {}
         {
           \c_math_subscript_token
           { \chemmacros_text:V \l__chemmacros_state_sb_left_tl }
         }
         #2
         \c_math_superscript_token
           { \chemmacros_text:V \l__chemmacros_state_sp_right_tl }
         \tl_if_empty:NTF \l__chemmacros_state_sb_right_tl
         {}
         {
           \c_math_subscript_token
           { \chemmacros_text:V \l__chemmacros_state_sb_right_tl }
         }
         \chemmacros_text:V \l__chemmacros_state_post_tl
        }
       }
   \group_end:
 }
\cs_generate_variant:Nn \chemmacros_state:nn { nV }

\cs_gset_protected:Npn \chemmacros_declare_state:Nn #1#2
 {
   \chemmacros_define_keys:xn
     {thermodynamics/\chemmacros_remove_backslash:N #1}
     {
       pre               .meta:nn = {chemmacros/thermodynamics} { pre = ##1 } ,
       post              .meta:nn = {chemmacros/thermodynamics} { post = ##1 } ,
     superscript-left  .meta:nn = {chemmacros/thermodynamics} { superscript-left = ##1 } ,
     superscript-right .meta:nn = {chemmacros/thermodynamics} { superscript-right = ##1 } ,
```

```
      superscript       .meta:n  = { superscript-right = ##1 } ,
    subscript-left   .meta:nn = {chemmacros/thermodynamics} { subscript-left = ##1 } ,
    subscript-right  .meta:nn = {chemmacros/thermodynamics} { subscript-right = ##1 } ,
      subscript         .meta:n     = { subscript-left = ##1 } ,
      subscript-pos     .choices:nn =
        { left , right }
        { \tl_set_eq:NN \l__chemmacros_state_sb_pos_tl \l_keys_choice_tl } ,
      symbol            .tl_set:N = \l__chemmacros_state_symbol_tl ,
      unit              .tl_set:N = \l__chemmacros_state_unit_tl
    }
  \DeclareDocumentCommand #1 { sO{}D(){}m }
    {
      \group_begin:
        \chemmacros_set_keys:xn
          {thermodynamics/\chemmacros_remove_backslash:N #1}
          {#2}
        \tl_if_blank:nF {##3}
          {
            \chemmacros_set_keys:nx {thermodynamics}
             { subscript-\l__chemmacros_state_sb_pos_tl = \exp_not:n {##3} }
          }
            \chemmacros_state:nV {##2} \l__chemmacros_state_symbol_tl
           \chemmacros_set_keys_groups:nnn {thermodynamics} {variables} {##2}
          \IfBooleanF {##1} {  = ~ \SI {##4} { \l__chemmacros_state_unit_tl } }
      \group_end:
    }
}
```

The pre-existing macros are redefined with the new definition:

```
\RenewChemState \enthalpy { symbol = H , unit = \kilo\joule\per\mole }
\RenewChemState \entropy  { symbol = S , unit = \joule\per\kelvin\per\mole , pre = }
\RenewChemState \gibbs    { symbol = G , unit = \kilo\joule\per\mole }

}{}% \@ifchemmacrosmoduleloaded
}% AtBeginDocument

\ExplSyntaxOff
```

File 71 **lwarp-chemnum.sty**

§ 169 Package chemnum

(*Emulates or patches code by* Clemens Niederberger.)

Pkg chemnum chemnum is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{chemnum}[2016/04/14]

\ExplSyntaxOn

\cs_gset_protected:Npn \chemnum_compound_write:n #1
  {
```

```
    \chemnum_get_compound_property:nn {#1} {pre-main-label-code}
    \group_begin:
      \bool_if:NTF \l__chemnum_compound_local_bool
        { \l__chemnum_local_label_format_tl }
        { \chemnum_get_compound_property:nn {#1} {label-format} }
      {
        \LWR@textcurrentfont{
            \chemnum_get_compound_property:nn {#1} {counter-representation}
        }
      }
    \group_end:
    \chemnum_get_compound_property:nn {#1} {post-main-label-code}
  }

\cs_gset_protected:Npn \chemnum_subcompound_write:nn #1#2
  {
    \group_begin:
      \bool_if:NTF \l__chemnum_compound_local_bool
        { \l__chemnum_local_label_format_tl }
        { \chemnum_get_compound_property:nn {#1} {label-format} }
      {
        \LWR@textcurrentfont{
            \chemnum_get_subcompound_property:nnn {#1} {#2}
            {counter-representation}
        }
      }
    \group_end:
  }

\ExplSyntaxOff
```

File 72 **lwarp-chkfloat.sty**

§ 170 Package chkfloat

Pkg chkfloat chkfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{chkfloat}[2012/08/19]
```

File 73 **lwarp-chngpage.sty**

§ 171 Package chngpage

(*Emulates or patches code by* Peter Wilson.)

Pkg chngpage chngpage is ignored.

for HTML output: Discard all options for lwarp-chngpage:

```
\LWR@ProvidesPackageDrop{chngpage}[2009/10/20]
```

```
\LWR@origRequirePackage{lwarp-changepage}
```

File 74 **lwarp-cite.sty**

§ 172 Package cite

(*Emulates or patches code by* Donald Arseneau.)

Pkg cite cite is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{cite}[2015/02/27]
```

For the [super] option, the \kern must be removed:

```
\def\LWRCT@biblabel#1{\@citess{#1}\kern-\labelsep\,}

\ifdefstrequal{\@biblabel}{\LWRCT@biblabel}
{
    \def\@biblabel#1{\@citess{#1}}
}{}
```

For the [super] option, \textsuperscript is used instead of math superscript:

```
\def\@citess#1{\textsuperscript{#1}}

\DeclareDocumentCommand\citepunct{}{,\,\relax}
```

File 75 **lwarp-CJK.sty**

§ 173 Package CJK

Pkg CJK CJK does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJK}{ctex, xeCJK}
}

\LWR@ProvidesPackagePass{CJK}[2015/04/18]
```

File 76 **lwarp-CJKutf8.sty**

§ 174 Package CJKutf8

Pkg CJKutf8 CJKutf8 does not work with lwarp unless called from ctex.

for HTML output:

```
\@ifpackageloaded{xeCJK}{}{
    \LWR@loadnever{CJKutf8}{ctex, xeCJK}
```

```
}

\LWR@ProvidesPackagePass{CJKutf8}[2015/04/18]
```

File 77 **lwarp-clrdblpg.sty**

§ 175 Package clrdblpg

Pkg clrdblpg clrdblpg is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{clrdblpg}[2018/04/21]
```

File 78 **lwarp-cmdtrack.sty**

§ 176 Package cmdtrack

Pkg cmdtrack cmdtrack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{cmdtrack}[2012/12/18]

\newcommand{\untrack}[1]{}
```

File 79 **lwarp-color.sty**

§ 177 Package color

Pkg color Allowed but ignored. xcolor is then required as well.

color is superceded by xcolor, and lwarp requires several of the features of xcolor. When color is requested, xcolor is loaded as well.

for HTML output:

```
\LWR@ProvidesPackageDrop{color}[2016/07/10]
\RequirePackage{xcolor}
```

File 80 **lwarp-colortbl.sty**

§ 178 Package colortbl

Pkg colortbl colortbl is used as-is for print output, and emulated for HTML.

⚠ row/cell color Only use \rowcolor and \cellcolor at the start of a row, in that order.

colortbl ignores the overhang arguments.

for HTML output: A placeholder definition is forgotten first:

```
\let\rowcolor\relax

\LWR@ProvidesPackagePass{colortbl}[2018/12/12]
```

The following \LWR@HTML versions are used inside an HTML tabular.

\columncolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

\LWR@getmynexttoken is not used here because \columncolor is not used inside the data area of the tabular.

```
\NewDocumentCommand{\LWR@HTML@columncolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@columnHTMLcolor%
\LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{columncolor}}
```

\LWR@getmynexttoken is used for \rowcolor because it is used inside the data area of the tabular.

\rowcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@rowcolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@rowHTMLcolor%
\LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{rowcolor}}
```

\cellcolor [⟨*model*⟩] {⟨*color*⟩} [⟨*left overhang*⟩] [⟨*right overhang*⟩]

```
\NewDocumentCommand{\LWR@HTML@cellcolor}{O{named} m o o}{%
\convertcolorspec{#1}{#2}{HTML}\LWR@cellHTMLcolor%
\LWR@addtabularcellcolor%
}

\AtBeginDocument{\LWR@formatted{cellcolor}}
```

\arrayrulecolor [⟨*model*⟩] {⟨*color*⟩}

The HTML version for use outside a tabular. Inside a tabular, \LWR@HTML@arrayrulecolornexttoken is used instead.

```
\newcommand{\LWR@HTML@arrayrulecolor}[2][named]{%
\convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolor}}
```

[⟨*model*⟩] {⟨*color*⟩}

\LWR@arrayrulecolornexttoken The HTML version for use inside a tabular.

```
\newcommand{\LWR@HTML@arrayrulecolornexttoken}[2][named]{%
\convertcolorspec{#1}{#2}{HTML}\LWR@ruleHTMLcolor%
\LWR@getmynexttoken%
}

\AtBeginDocument{\LWR@expandableformatted{arrayrulecolornexttoken}}
```

\doublerulesepcolor `[⟨model⟩] {⟨color⟩}`

The version for use outside a `tabular`.

```
\newcommand{\LWR@HTML@doublerulesepcolor}[2][named]{}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolor}}
```

`[⟨model⟩] {⟨color⟩}`

\LWR@doublerulesepcolornexttoken The version for use inside a `tabular`.

```
\newcommand{\LWR@HTML@doublerulesepcolornexttoken}[2][named]{\LWR@getmynexttoken}

\AtBeginDocument{\LWR@expandableformatted{doublerulesepcolornexttoken}}
```

File 81 **lwarp-continue.sty**

§ 179 Package

continue

Pkg continue continue is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{continue}}[2018/12/09]

\newcommand*{\flagcont}{}
\newcommand*{\flagend}{}
\newcommand*{\flagword}{}
\newcommand*{\preflagword}{}
\newcommand*{\postflagword}{}
\newlength\contsep
\newlength\contdrop
```

File 82 **lwarp-copyrightbox.sty**

§ 180 Package

copyrightbox

(*Emulates or patches code by* Thomas Fischer, Ives van der Flaas.)

Pkg copyrightbox copyrightbox is emulated for use by lwarp.

The entire copyright box is placed inside a `<div>` of class `copyrightbox`.

The contents are placed inside a `<div>` of class `copyrightboxcontents`.

The copyright notice is placed inside a of class copyrightboxnote.

for HTML output:

```
\LWR@ProvidesPackageDrop{copyrightbox}[2011/11/27]

\newcommand{\copyrightbox}[3][r]{%
\begin{BlockClass}[
    display: inline-flex;
    flex-direction: column ;
]{copyrightbox}
\begin{BlockClass}{copyrightboxcontents}
#2
\end{BlockClass}
\begin{BlockClass}{copyrightboxnote}
#3
\end{BlockClass}
\end{BlockClass}
}

\newcommand{\CRB@setcopyrightfont}{}
\newcommand{\CRB@setcopyrightparagraphstyle}{}
```

File 83 **lwarp-crop.sty**

§ 181 Package crop

(*Emulates or patches code by* Melchior FRANZ.)

Pkg crop crop is ignored.

for HTML output: Discard all options for lwarp-crop:

```
\LWR@ProvidesPackageDrop{crop}[2003/05/20]

\newcommand*{\crop}[1][]{}
\newcommand*{\cropdef}[6][]{}
```

File 84 **lwarp-ctable.sty**

§ 182 Package ctable

(*Emulates or patches code by* Wybo Dekker.)

Pkg ctable ctable is patched for use by lwarp.

⚠ Misplaced alignment tab character &

Use \StartDefiningTabulars before one or more \ctables, and \StopDefiningTabulars after. These change the meaning of the ampersand & character.

for HTML output:

```
\LWR@ProvidesPackagePass{ctable}[2015/10/17]
```

The following is in the original:

```
\newcommand{\LWR@HTML@ctable}[4][]{%
   \let\@CTtaborfig  \@dfltCTtaborfig
   \let\@CTalign     \@dfltCTalign
   \let\@CTsideways  \@dfltCTsideways
   \let\@CTcontinued \empty
   \let\@CTpos       \@dfltCTpos
   \let\@CTcaption   \empty
   \let\@CTcap       \undefined
   \let\@CTlabel     \empty
   \let\@CTbotcap    \@dfltCTbotcap
   \let\@CTstarred   \@dfltCTstarred
   \let\@CTsuper     \@dfltCTsuper
   \let\@CTnotespar  \@dfltCTnotespar
   \let\@CTdoinside  \@dfltCTdoinside
   \let\@CTbgopacity \@dfltCTbgopacity
   \@CTframerule     \@dfltCTframerule
   \@CTcaptionskip   \@dfltCTcaptionskip
   \@CTframesep      \@dfltCTframesep
   \@CTwidth         \@dfltCTwidth
   \@CTmaxwidth      \@dfltCTmaxwidth
   \@CTmincapwidth   \@dfltCTmincapwidth
   \@CTfooterwidth   \@dfltCTfooterwidth
   \def\@CTfgactual {@dfltCTframefg}%
   \def\@CTbgactual {@dfltCTframebg}%
   \def\@CTbeg      {\begin{\@CTsideways\@CTtaborfig\@CTstarred}}%
   \def\@CTbegin    {\@CTbeg}%
   \def\@CTend      {\end{\@CTsideways\@CTtaborfig\@CTstarred}}%
   \setkeys{CT}{#1}%
   \ifx\@CTcap\undefined\let\@CTcap\@CTcaption\fi
   \ifx\@CTcap\empty
     \if@CTcaptionloaded\else
       \PackageWarningNoLine{lwarp-ctable}{\MessageBreak
          An empty cap= option prevents lot/loc entry only\MessageBreak
          if the caption package is loaded!}
     \fi
   \fi
   \if@CTinmemoir\else
      \ifx\@CTbotcap\undefined
         \PackageError{lwarp-ctable}{\MessageBreak
            You can, currently, use the sidecap option only with\MessageBreak
            memoir documents. Use topcap or botcap only}
      \fi
   \fi
   \ifdim\@CTwidth=0pt\else
      \ifdim\@CTmaxwidth=0pt\else
         \PackageError{lwarp-ctable}{\MessageBreak
           You may not use the width and maxwidth options together\MessageBreak
            Use either width or maxwidth}
      \fi
   \fi
   \ifx\@CTpos\empty
      \ifx\@CTsideways\empty\else
      \PackageError{lwarp-ctable}{\MessageBreak
```

```
        You may not use the pos and sideways options together\MessageBreak
        Rotated tables and figures are always typeset on a separate page}
     \fi
  \fi
  \ifx\@CTcaption\empty
     \ifx\@CTlabel\empty\else
        \PackageError{lwarp-ctable}{\MessageBreak
           You may not label a captionless table\MessageBreak
           Such a label can't be referenced}
     \fi
  \fi
```

Some of the original, regarding computing the width of `\CT@t`, is removed here.

```
  \@CTbegin
     \ifx\@CTcontinued\empty\else\addtocounter{\@CTtaborfig}{-1}\fi
     \@CTalign
```

lwarp's patches begin here:

```
   \begin{center}
       \setlength{\fboxrule}{\@CTframerule}
       \setlength{\fboxsep}{\@CTframesep}
       \LWR@forceminwidth{\fboxrule}%  lwarp
       \convertcolorspec{named}{\@CTbgactual}{HTML}\LWR@tempcolor% lwarp
       \begin{BlockClass}[%                            lwarp
           border:
               \LWR@printlength{\LWR@atleastonept}
               solid
               \LWR@colorstyle{named}{\@CTfgactual} ; %
           padding:\LWR@printlength{\fboxsep} ; %
           \ifdefstring{\LWR@tempcolor}{FFFFFF}{}{%
               background: \LWR@colorstyle{named}{\@CTbgactual} ; %
           }%
       ]{fminipage}%       lwarp
        \ifx\@CTbotcap\@CTfalse\@CTCaption\vskip\@CTcaptionskip\fi
        \ifx\@CTbotcap\undefined%
            \begin{sidecaption}[\@CTcap]{\@CTcaption}[\@CTlabel]
        \fi
        \@CTdoinside
        \begin{tabularx}{\linewidth}{#2}%      lwarp
           #4%
        \end{tabularx}%                    lwarp
        \def\@CTfootnotes{#3}%
        \ifx#3\empty\else{% append footnotes, if any
           \begin{BlockClass}{tnotes}%     lwarp
           #3
           \end{BlockClass}%               lwarp
        }
        \fi
        \ifx\@CTbotcap\undefined\end{sidecaption}\fi
        \ifx\@CTbotcap\@CTtrue\vskip\@CTcaptionskip\@CTCaption\fi
       \end{BlockClass}
    \end{center}
  \@CTend
```

```
}
\LWR@formatted{ctable}
```

Required to properly detect the toprule:

```
\LetLtxMacro\FL\toprule
```

Table notes are redefined for HTML:

```
\newcommand{\LWR@HTML@tmark}[1][a]{%
   \textsuperscript{\textrm{\textit{#1}}}
}
\LWR@formatted{tmark}

\newcommand{\LWR@HTML@tnote}[2][a]{%
    \tmark[#1]\,#2\par
}
\LWR@formatted{tnote}
```

File 85 **lwarp-cuted.sty**

§ 183 Package cuted

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg cuted cuted is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{cuted}[2012/10/04]

\newenvironment{strip}{}{}
\newskip\stripsep
\def\oldcolsbreak#1{}
```

File 86 **lwarp-cutwin.sty**

§ 184 Package cutwin

(*Emulates or patches code by* Peter Wilson and Alan Hoenig.)

Pkg cutwin cutwin is emulated.

for HTML output: Discard all options for lwarp-cutwin:

```
\LWR@ProvidesPackageDrop{cutwin}[2010/09/29]

\newcommand*{\opencutleft}{}
\newcommand*{\opencutright}{}
\newcommand*{\opencutcenter}{}
\newcommand*{\cutfuzz}{}
```

```
6
7 \newenvironment{cutout}[4]
8 {\marginpar{\windowpagestuff}}
9 {}
10
11 \newcommand*{\windowpagestuff}{}
12
13 \newcommand*{\pageinwindow}{%
14 % \begin{minipage}{.3\linewidth}
15 \windowpagestuff
16 % \end{minipage}
17 }
18
19 \newenvironment{shapedcutout}[3]
20 {\marginpar{\picinwindow}}
21 {}
22
23 \newcommand*{\putstuffinpic}{}
24
25 \newcommand*{\picinwindow}{%
26 \begin{picture}(0,0)
27 \putstuffinpic
28 \end{picture}}
```

File 87 **lwarp-dblfloatfix.sty**

§ 185 Package dblfloatfix

Pkg dblfloatfix dblfloatfix is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{dblfloatfix}[2012/12/31]
```

File 88 **lwarp-dblfnote.sty**

§ 186 Package dblfnote

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg dblfnote dblfnote is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{dblfnote}[1999/07/14]

2 \newcounter{DFNsloppiness}
3 \newdimen\DFNcolumnsep
4 \newdimen\DFNcolumnwidth
5 \def\DFNallowcbreak{}
6 \def\DFNinhibitcbreak{}
7 \def\DFNtrysingle{}
8 \def\DFNalwaysdouble{}
9 \def\DFNruleboth{}
```

```
\def\DFNruleleft{}
```

File 89 **lwarp-dcolumn.sty**

§ 187 Package dcolumn

Pkg dcolumn dcolumn is emulated by the lwarp core.

```
\LWR@ProvidesPackageDrop{dcolumn}[2014/10/28]
```

File 90 **lwarp-diagbox.sty**

§ 188 Package diagbox

(*Emulates or patches code by* Leo Liu.)

Pkg diagbox diagbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{diagbox}[2016/12/28]
```

To restore print-mode inside a `lateximage`:

```
\LetLtxMacro\LWR@origdiagbox@double\diagbox@double
\LetLtxMacro\LWR@origdiagbox@triple\diagbox@triple

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\diagbox@double\LWR@origdiagbox@double%
\LetLtxMacro\diagbox@triple\LWR@origdiagbox@triple%
}
```

`\LWR@diagbox@AB` {⟨*E*/*W*⟩} {⟨*A*⟩} {⟨*E*/*W*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagbox@AB}[4]{
\begingroup%
\LetLtxMacro\\\newline%
\BlockClassSingle{diagbox#1}{#2}%
\BlockClassSingle{diagbox#3}{#4}%
\endgroup%
\LWR@stoppars%
}
```

`\LWR@diagboxNW` {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxNW}[2]{%
\LWR@diagbox@AB{E}{#2}{W}{#1}%
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxNE}[2]{%
\LWR@diagbox@AB{W}{#1}{E}{#2}%
}

\let\LWR@diagboxSW\LWR@diagboxNE
\let\LWR@diagboxSE\LWR@diagboxNW
```

`\diagbox@double` {⟨*keys*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\def\diagbox@double#1#2#3{%
\setkeys{diagbox}{dir=NW,#1}%
\@nameuse{LWR@diagbox\diagbox@dir}{#2}{#3}%
}
```

`\LWR@diagboxTNW` {⟨*title*⟩} {⟨*A*⟩} {⟨*B*⟩}

```
\newcommand{\LWR@diagboxTNW}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNW{#2}{#3}
}
```

Likewise for NE, SW, SE:

```
\newcommand{\LWR@diagboxTNE}[3]{%
\BlockClassSingle{diagboxtitleN}{#1}
\LWR@diagboxNE{#2}{#3}
}

\newcommand{\LWR@diagboxTSW}[3]{%
\LWR@diagboxSW{#2}{#3}
\BlockClassSingle{diagboxtitleS}{#1}
\LWR@stoppars%
}

\newcommand{\LWR@diagboxTSE}[3]{%
\LWR@diagboxSE{#2}{#3}
\BlockClassSingle{diagboxtitleS}{#1}
\LWR@stoppars%
}
```

`\diagbox@triple` {⟨*keys*⟩} {⟨*A*⟩} {⟨*T*⟩} {⟨*B*⟩}

```
\def\diagbox@triple#1#2#3#4{%
\setkeys{diagbox}{dir=NW,#1}%
\@nameuse{LWR@diagboxT\diagbox@dir}{#3}{#2}{#4}%
}
```

File 91 **lwarp-dingbat.sty**

§ 189 Package dingbat

(*Emulates or patches code by* Scott Pakin.)

Pkg dingbat dingbat is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{dingbat}[2001/04/27]

\newcommand*{\LWR@dingbatsymbol}[1]{\HTMLunicode{#1}}

\newcommand{\LWR@HTML@rightpointright}{\LWR@dingbatsymbol{261E}}
\newcommand{\LWR@HTML@leftpointright}{\LWR@dingbatsymbol{261E}}
\newcommand{\LWR@HTML@leftthumbsdown}{\LWR@dingbatsymbol{1F44E}}
\newcommand{\LWR@HTML@leftthumbsup}{\LWR@dingbatsymbol{1F44D}}
\newcommand{\LWR@HTML@rightpointleft}{\LWR@dingbatsymbol{261C}}
\newcommand{\LWR@HTML@rightthumbsdown}{\LWR@dingbatsymbol{1F44E}}
\newcommand{\LWR@HTML@rightthumbsup}{\LWR@dingbatsymbol{1F44D}}
\newcommand{\LWR@HTML@squarewithdots}{\LWR@dingbatsymbol{25C7}}
\newcommand{\LWR@HTML@filledsquarewithdots}{\LWR@dingbatsymbol{25C6}}
\newcommand{\LWR@HTML@Sborder}{\LWR@dingbatsymbol{271A}}
\newcommand{\LWR@HTML@Zborder}{\LWR@dingbatsymbol{274B}}
\newcommand{\LWR@HTML@largepencil}{\LWR@dingbatsymbol{270E}}
\newcommand{\LWR@HTML@anchor}{\LWR@dingbatsymbol{2693}}
\newcommand{\LWR@HTML@carriagereturn}{\LWR@dingbatsymbol{23CE}}
\newcommand{\LWR@HTML@checkmark}{\LWR@dingbatsymbol{2713}}
\newcommand{\LWR@HTML@eye}{\LWR@dingbatsymbol{1F441}}
\newcommand{\LWR@HTML@satellitedish}{\LWR@dingbatsymbol{1F4E1}}
\newcommand{\LWR@HTML@smallpencil}{\LWR@dingbatsymbol{270E}}

\LWR@formatted{rightpointright}
\LWR@formatted{leftpointright}
\LWR@formatted{leftthumbsdown}
\LWR@formatted{leftthumbsup}
\LWR@formatted{rightpointleft}
\LWR@formatted{rightthumbsdown}
\LWR@formatted{rightthumbsup}
\LWR@formatted{squarewithdots}
\LWR@formatted{filledsquarewithdots}
\LWR@formatted{Sborder}
\LWR@formatted{Zborder}
\LWR@formatted{largepencil}
\LWR@formatted{anchor}
\LWR@formatted{carriagereturn}
\LWR@formatted{checkmark}
\LWR@formatted{eye}
\LWR@formatted{satellitedish}
\LWR@formatted{smallpencil}
```

File 92 **lwarp-dprogress.sty**

§ 190 Package dprogress

Pkg dprogress dprogress is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{dprogress}[2008/02/21]
```

File 93 **lwarp-draftcopy.sty**

§ 191 Package draftcopy

Pkg draftcopy draftcopy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftcopy}[2002/02/25]

\newcommand{\draftcopyVersion}[1]{}
\newcommand{\draftcopySetGrey}[1]{}
\newcommand{\draftcopySetScale}[1]{}
\newcommand{\draftcopySetScaleFactor}[1]{}
\newcommand{\draftcopyFirstPage}[1]{}
\newcommand{\draftcopyLastPage}[1]{}
\newcommand{\draftcopyName}[2]{}
\newcommand{\draftcopyPageTransform}[1]{}
\newcommand{\draftcopyBottomTransform}[1]{}
\newcommand{\draftcopyPageX}[1]{}
\newcommand{\draftcopyPageY}[1]{}
\newcommand{\draftcopyBottomX}[1]{}
\newcommand{\draftcopyBottomY}[1]{}
```

File 94 **lwarp-draftfigure.sty**

§ 192 Package draftfigure

Pkg draftfigure draftfigure is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftfigure}[2017/07/19]
\RequirePackage{xkeyval}

\define@key{draftfigure}{code}{}
\define@key{draftfigure}{noframe}[true]{}
\define@key{draftfigure}{filename}[true]{}
\define@key{draftfigure}{content}[]{}
\define@key{draftfigure}{style}[normal]{}
\define@key{draftfigure}{position}[left]{}
\define@key{draftfigure}{size}[normal]{}
\newcommand\setdf[1]{\setkeys{draftfigure}{#1}}
```

File 95 **lwarp-draftwatermark.sty**

§ 193 Package draftwatermark

(*Emulates or patches code by* Sergio Callegari.)

Pkg draftwatermark draftwatermark is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{draftwatermark}[2015/02/19]

\newcommand{\SetWatermarkAngle}[1]{}
\newcommand{\SetWatermarkColor}[1]{}
\newcommand{\SetWatermarkLightness}[1]{}
\newcommand{\SetWatermarkFontSize}[1]{}
\newcommand{\SetWatermarkScale}[1]{}
\newcommand{\SetWatermarkHorCenter}[1]{}
\newcommand{\SetWatermarkVertCenter}[1]{}
\newcommand{\SetWatermarkText}[1]{}
```

File 96 **lwarp-easy-todo.sty**

§ 194 Package

easy-todo

(*Emulates or patches code by* Juan Rada-Vilela.)

Pkg easy-todo easy-todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{easy-todo}[2014/01/01]
```

\listoftodos Modified to correct buggy use of \flushright.

```
\let\LWR@origlistoftodos\listoftodos

\renewcommand{\listoftodos}{%
\begingroup
\renewcommand{\flushright}{}
\LWR@origlistoftodos
\endgroup
}
```

\todoii Modified to use \textcolor instead of \color.

```
\renewcommand{\todoii}[2]{%
\ifthenelse{\equal{\@todoobeyfinal}{true}}%
    {%
        \ifoptionfinal{\todoenable{false}}{\todoenable{true}}%
    }%
    {}%
\ifthenelse{\equal{\@todoenable}{true}}%
    {%
        \refstepcounter{todos}%
        \noindent{%
            \todocolor%
            \LWR@textcurrentcolor{%
                \normalfont\scriptsize{\bfseries{\thetodos.#1}}%
            }%
        }%
        \addcontentsline{lod}{todos}{\protect{\thetodos. }\LWR@isolate{#2}}%
```

```
    }%
    {}%
}
```

File 97 **lwarp-ebook.sty**

§ 195 Package

ebook

(*Emulates or patches code by* Jørgen Steensgaard.)

Pkg ebook ebook is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ebook}

\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}

\providecommand{\pagefill}[1][0.001mm]{\noindent}

\providecommand{\ebook}{
\setcounter{secnumdepth}{0}
\setcounter{tocdepth}{2}
}
```

File 98 **lwarp-ed.sty**

§ 196 Package

ed

(*Emulates or patches code by* Michael Kohlhase.)

Pkg ed ed is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{ed}[2012/01/29]
```

Bugs:

1. `todolist` fails with the `hide` option, as does `\edexplanation`.
2. `\edstubURI` is actually `\edstuURI`.

```
\RequirePackage{xcolor}

\renewenvironment{edstub}[2][The following blue text]
{%
    \def\@test{#1}%
    \begin{center}%
        \huge%
        \textcolor{red}{%
            #1 is only a provisional stub\\\Large
```

```
            the Office document
            \ifx\ed@stubURI\@empty{#2}\else\href{\ed@stubURI}{#2}\fi\
            contains more text\\which will be merged for the final document%
        }%
    \end{center}%
    \BlockClass[color:blue]{edstub}%
}
{\endBlockClass}
```

File 99 **lwarp-ellipsis.sty**

§ 197 Package ellipsis

(*Emulates or patches code by* Peter J. Heslin.)

Pkg ellipsis ellipsis is emulated.

```
\LWR@ProvidesPackageDrop{ellipsis}[2004/09/28]

\newcommand{\ellipsisgap}{0.1em}

\newcommand*{\midwordellipsis}{\,\textellipsis\,}
```

File 100 **lwarp-embrac.sty**

§ 198 Package embrac

(*Emulates or patches code by* Clemens Niederberger.)

Pkg embrac embrac is nullfied for HTML and used as-is for print.

for HTML output:

```
\LWR@ProvidesPackagePass{embrac}[2017/07/04]

\LetLtxMacro\LWR@orig@HTML@emph\LWR@HTML@emph
\RenewDocumentCommand{\LWR@HTML@emph}{s m}{\LWR@orig@HTML@emph{#2}}

\LetLtxMacro\LWR@orig@HTML@textit\LWR@HTML@textit
\RenewDocumentCommand{\LWR@HTML@textit}{s m}{\LWR@orig@HTML@textit{#2}}

\LetLtxMacro\LWR@orig@HTML@textsl\LWR@HTML@textsl
\RenewDocumentCommand{\LWR@HTML@textsl}{s m}{\LWR@orig@HTML@textsl{#2}}

\ifxetexorluatex
    \LetLtxMacro\LWR@orig@HTML@textsi\LWR@HTML@textsi
    \RenewDocumentCommand{\LWR@HTML@textsi}{s m}{%
    \LWR@orig@HTML@textsi{#2}}
\fi

\AtBeginDocument{
    \LWR@formatted{emph}
```

```
    \LWR@formatted{textit}
    \LWR@formatted{textsl}
    \ifxetexorluatex
        \LWR@formatted{textsi}
    \fi
}

\newcommand{\LWR@HTML@EmbracOff}{}
\LWR@formatted{EmbracOff}

\newcommand{\LWR@HTML@EmbracOn}{}
\LWR@formatted{EmbracOn}
```

File 101 **lwarp-emptypage.sty**

§ 199 Package emptypage

Pkg emptypage emptypage is ignored.

for HTML output: Discard all options for lwarp-emptypage:

```
\LWR@ProvidesPackageDrop{emptypage}[2010/05/30]
```

File 102 **lwarp-endfloat.sty**

§ 200 Package endfloat

Pkg endfloat endfloat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endfloat}[2019/04/15]

\newcommand\figureplace{}
\newcommand\tableplace{}
\newcommand\floatplace[1]{}
\newcounter{posttable}
\newcounter{postfigure}
\newcommand*{\theposttbl}{}
\newcommand*{\thepostfig}{}
\newcommand{\AtBeginFigures}[1]{}
\newcommand{\AtBeginTables}[1]{}
\newcommand{\AtBeginDelayedFloats}[1]{}
\newcommand*{\processdelayedfloats}{}
\newcommand*{\efloatseparator}{}
\def\efloattype{}
\providecommand\efloatheading[1]{}
\providecommand\efloatpreamble{}
\providecommand\efloatpostamble{}
\NewDocumentCommand{\addtodelayedfloat}{s m m}{}
\providecommand{\efloatbegin}{}
\providecommand{\efloatend}{}
```

```
\providecommand{\efloatbeginlist}{}
\providecommand{\efloatendlist}{}
```

File 103 **lwarp-endheads.sty**

§ 201 Package endheads

Pkg endheads endheads is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{endheads}[2017/04/06]

\newcommand{\changesinglepageabbrev}[1]{}
\newcommand{\changemultiplepageabbrev}[1]{}
\newcommand{\changenotesname}[1]{}
\newcommand{\changenotesheader}[1]{}
\newcommand{\changenotescontentsname}[1]{}
\newcommand{\changechapternotesline}[1]{}
\newcommand{\checknoteheaders}{}
\newif\ifnotesincontentson \notesincontentsonfalse
\newcommand{\notesincontents}{\notesincontentsontrue}
\newif\ifendnoteheaderson \endnoteheadersonfalse
\newcommand{\setupendnoteheaders}{%
    \endnoteheadersontrue%
}
\newif\iftitleinnotes \titleinnotestrue
\newcommand{\styleforchapternotebegin}{}
\newcommand{\styleforchapternoteend}{}
\newcommand{\setstyleforchapternotebegin}[1]{%
    \renewcommand{\styleforchapternotebegin}{#1}%
}
\newcommand{\setstyleforchapternoteend}[1]{%
    \renewcommand{\styleforchapternoteend}{#1}%
}
\newcommand{\resetendnotes}{}
\newif\ifnotesbychapteron \notesbychapteronfalse
\newcommand{\notesbychapter}{\notesbychapterontrue}
```

File 104 **lwarp-endnotes.sty**

§ 202 Package endnotes

(*Emulates or patches code by* John Lavagnino.)

Pkg endnotes Used as-is.

table of contents To place the endnotes in the toc, use:

```
\usepackage{endnotes}
\appto\enoteheading{\addcontentsline{toc}{section}{\notesname}}
\renewcommand*{\notesname}{Endnotes} % optional
```

html page To additionally have the endnotes on their own HTML page, if `FileDepth` allows:

```
\ForceHTMLPage
\theendnotes
```

for HTML output:

```
\LWR@ProvidesPackagePass{endnotes}

\def\enoteformat{%
% \rightskip\z@ \leftskip\z@ \parindent=1.8em
\leavevmode
% \llap{
\makeenmark
% }
}

\def\@makeenmark{\hbox{\LWR@htmlspan{sup}{\normalfont\theenmark}}}
\def\makeenmark{\@makeenmark}
```

File 105 **`lwarp-enumerate.sty`**

§ 203 Package enumerate

Pkg `enumerate` enumerate is supported with no changes.

This package is only required because it was used in the past to drop and then emulate the package. It cannot be removed because an older version which dropped the package may still remain, for example in a local vs. distribution directory, but it is now supported directly by lwarp and thus must no longer be dropped.

for HTML output:

```
\LWR@ProvidesPackagePass{enumerate}[2015/07/23]
```

File 106 **`lwarp-enumitem.sty`**

§ 204 Package enumitem

(*Emulates or patches code by* Javier Bezos.)

Pkg `enumitem` enumitem is supported with minor adjustments.

for HTML output:

```
\LWR@ProvidesPackagePass{enumitem}[2018/11/30]
```

for HTML output:

```
\begin{warpHTML}
```

`\newlist` {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}
`\renewlist` {⟨*name*⟩} {⟨*type*⟩} {⟨*maxdepth*⟩}

For enumitem lists, new lists must have the start and end actions assigned to the new environment. Renewed lists already have their actions assigned, and thus need no changes.

```
\let\LWR@enumitem@orignewlist\newlist

\renewcommand*{\newlist}[3]{%
\LWR@enumitem@orignewlist{#1}{#2}{#3}%
\AtBeginEnvironment{#1}{\@nameuse{LWR@#2start}}%
\AtEndEnvironment{#1}{\@nameuse{LWR@#2end}}%
}

\def\DrawEnumitemLabel{}

\end{warpHTML}
```

File 107 **lwarp-epigraph.sty**

§ 205 Package

epigraph

(*Emulates or patches code by* Peter Wilson.)

Pkg epigraph epigraph is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{epigraph}[2009/09/02]

\DeclareDocumentCommand{\qitem}{m m}
{
\begin{BlockClass}{qitem}
#1
\ifbool{FormatWP}
{\begin{BlockClass}[border-top:1px solid gray]{epigraphsource}}
{\begin{BlockClass}{epigraphsource}}
#2
\end{BlockClass}
\end{BlockClass}
}


\DeclareDocumentCommand{\epigraph}{m m}
{
\begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{epigraph}
\qitem{#1}{#2}
\end{LWR@BlockClassWP}
}

\DeclareDocumentEnvironment{epigraphs}{}
{\LWR@BlockClassWP{\LWR@print@mbox{text-align:right}}{}{epigraph}}
{\endLWR@BlockClassWP}
```

Use css to format epigraphs.

The following are null commands for source compatibility:

```
\newenvironment*{flushepinormal}{}{}
```

```
\@ifclassloaded{memoir}{
\setlength{\epigraphwidth}{.5\linewidth}
\renewcommand{\textflush}{flushepinormal}
\renewcommand{\epigraphhead}[2][0]{#2}
\renewcommand{\dropchapter}[1]{}
\renewcommand*{\undodrop}{}
}{% not memoir
\newlength{\epigraphwidth}
\setlength{\epigraphwidth}{.5\linewidth}
\newcommand{\textflush}{flushepinormal}
\newcommand{\epigraphflush}{flushright}
\newcommand{\sourceflush}{flushright}
\newcommand*{\epigraphsize}{\small}
\newlength{\epigraphrule}
\newlength{\beforeepigraphskip}
\newlength{\afterepigraphskip}
\newcommand{\epigraphhead}[2][0]{#2}
\newcommand{\dropchapter}[1]{}
\newcommand*{\undodrop}{}
}% not memoir

\let\cleartoevenpage\relax% also in nextpage
\newcommand{\cleartoevenpage}[1][]{}
```

File 108 **lwarp-epsfig.sty**

§ 206 Package

epsfig

Pkg epsfig epsfig is emulated for use by lwarp.

⚠ Only the LaTeX2e syntax is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{epsfig}[2017/06/25]
```

A few additional keys to capture the filename:

```
\RequirePackage{graphics}

\define@key{igraph}{file}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{figure}{%
    \xdef\LWR@epsfig@filename{#1}%
}

\define@key{igraph}{prolog}{}

\define@key{igraph}{silent}[]{}
```

The captured filename is used as the argument to `\includegraphics`:

```
\newcommand{\epsfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}

\newcommand{\psfig}[1]{\includegraphics[#1]{\LWR@epsfig@filename}}
```

File 109 **lwarp-epstopdf.sty**

§ 207 Package

epstopdf

Pkg epstopdf

Previous versions of lwarp had a nullfied version, but now epstopdf-base is supported. lwarp-epstopdf becomes a placeholder to overwrite previous versions.

See package epstopdf-base for details.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf}[2016/05/15]
```

File 110 **lwarp-epstopdf-base.sty**

§ 208 Package

epstopdf-base

Pkg epstopdf-base

⚠ convert to .svg

Images with an .eps extension will be converted to .pdf. The HTML output uses the .svg version, so use

Enter ⇒ **lwarpmk pdftosvg <listofPDFfiles>**

to generate .svg versions.

for HTML output:

```
\LWR@ProvidesPackagePass{epstopdf-base}[2016/05/15]
```

Redefine to remember the image filename, replacing .pdf with .svg. Use the epstopdf print version inside a lateximage.

```
\newcommand*{\LWR@HTML@ETE@OrgGin@setfile}[3]{%
    \edef\LWR@tempone{#3}%
    \StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
    \StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
    \xdef\LWR@parsedfilename{\LWR@tempone}%
}

\LWR@formatted{ETE@OrgGin@setfile}
```

\includegraphics in HTML mode redefines \Gin@setfile to be \LWR@HTML@Gin@setfile, which is now redirected to epstopdf's version:

```
\renewcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \ETE@Gin@setfile{#1}{#2}{#3}%
}
```

Allow .eps images to be found if a suffix is not provided:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{%
    .eps,.EPS,.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Likewise when inside a `lateximage`:

```
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{%
    .eps,.EPS,.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG%
}%
}
```

File 111 **lwarp-eqlist.sty**

§ 209 Package eqlist

Pkg eqlist eqlist is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{eqlist}[2002/08/15]
```

```
\newenvironment{eqlist}[1][]{\description}{\enddescription}
\newenvironment{eqlist*}[1][]{\description}{\enddescription}
\newenvironment{Eqlist}[2][]{\description}{\enddescription}
\newenvironment{Eqlist*}[2][]{\description}{\enddescription}
\newcommand*{\longitem}[1][]{\item[#1]}
\newcommand*{\eqlistinit}{}
\newcommand*{\eqliststarinit}{}
\newcommand*{\eqlistinitpar}{}
\def\eqlistlabel#1{#1}
\newcommand{\eqlistauto}[1]{}
\newcommand{\eqlistnoauto}{}
```

File 112 **lwarp-eqparbox.sty**

§ 210 Package eqparbox

(*Emulates or patches code by* Scott Pakin.)

Pkg eqparbox eqparbox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eqparbox}[2017/09/03]
```

```
\NewDocumentCommand{\LWR@HTML@eqparbox}{O{t} O{} O{t} m +m}{%
```

```
    {%
        \minipagefullwidth%
        \parbox[#1][#2][#3]{\linewidth}{#5}%
    }%
}
\LWR@formatted{eqparbox}

\NewDocumentCommand{\LWR@HTML@eqmakebox}{o o m}{%
    \makebox[#2]{#3}%
}
\LWR@formatted{eqmakebox}

\NewDocumentCommand{\LWR@HTML@eqframebox}{o o m}{%
    \framebox[#2]{#3}%
}
\LWR@formatted{eqframebox}

\NewDocumentEnvironment{LWR@HTML@eqminipage}{O{t} O{} O{t} m}
{%
    \begingroup%
    \minipagefullwidth%
    \minipage[#1][#2][#3]{\linewidth}%
}%
{%
    \endminipage%
    \endgroup%
}

\newcommand*{\LWR@HTML@eqboxwidth}[1]{.25\linewidth}
\LWR@formatted{eqboxwidth}

\newcommand*{\LWR@HTML@eqsetminwidth}[2]{}
\newcommand*{\LWR@HTML@eqsetmaxwidth}[2]{}

\newcommand*{\LWR@HTML@eqsetminwidthto}[2]{}
\newcommand*{\LWR@HTML@eqsetmaxwidthto}[2]{}
```

File 113 **lwarp-errata.sty**

§ 211 Package

errata

(*Emulates or patches code by* Michael Kohlhase.)

Pkg errata errata is patched for use by lwarp.

This is for v0.3 of errata. A newer version of errata with more features is under development, at which time the lwarp version will have to be updated.

for HTML output: Macros are being defined with the math dollar, so enable the HTML version during package loading:

```
\StartDefiningMath
```

Now load the package:

```
\LWR@ProvidesPackagePass{errata}[2006/11/12]
```

Patches for dynamic inline math:

```
\xpatchcmd{\erratumAdd}
    {$_a^{\arabic{erratum}}$}
%     {\inlinemathother$_a^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{a}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumAdd}}

\xpatchcmd{\erratumDelete}
    {$_d^{\arabic{erratum}}$}
%     {\inlinemathother$_d^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratumReplace}
    {$_r^{\arabic{erratum}}$}
%     {\inlinemathother$_r^{\arabic{erratum}}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\arabic{erratum}}}
    {}
    {\LWR@patcherror{erratum}{erratumReplace}}

\xpatchcmd{\erratum}
    {$_a$}
%     {\inlinemathother$_a$\inlinemathnormal}
    {\textsubscript{a}}
    {}
    {\LWR@patcherror{erratum}{erratumDelete}}

\xpatchcmd{\erratum}
    {$_d^{\@thefnmark}$}
%     {\inlinemathother$_d^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{d}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eDelete}}

\xpatchcmd{\erratum}
    {$_r^{\@thefnmark}$}
%     {\inlinemathother$_r^{\@thefnmark}$\inlinemathnormal}
    {\textsubscript{r}\textsuperscript{\@thefnmark}}
    {}
    {\LWR@patcherror{erratum}{eReplace}}
```

Finish the current page's errata before closing and reloading the list:

```
\preto\PrintErrata{\LWR@orignewpage}
```

No longer defining math macros with the HTML $:

```
\StopDefiningMath
```

File 114 **lwarp-eso-pic.sty**

§ 212 Package eso-pic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg eso-pic eso-pic is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{eso-pic}[2018/04/12]

\newcommand*{\LenToUnit}{}
\newcommand{\AtPageUpperLeft}[1]{}
\newcommand{\AtPageLowerLeft}[1]{}
\newcommand{\AtPageCenter}[1]{}
\newcommand{\AtStockLowerLeft}[1]{}
\newcommand{\AtStockUpperLeft}[1]{}
\newcommand{\AtStockCenter}[1]{}
\newcommand{\AtTextUpperLeft}[1]{}
\newcommand{\AtTextLowerLeft}[1]{}
\newcommand{\AtTextCenter}[1]{}
\NewDocumentCommand{\AddToShipoutPictureBG}{s +m}{}

\newcommand{\AddToShipoutPicture}{\AddToShipoutPictureBG}
\NewDocumentCommand{\AddToShipoutPictureFG}{s +m}{}
\newcommand*{\ClearShipoutPictureBG}{}
\newcommand*{\ClearShipoutPicture}{}
\newcommand*{\ClearShipoutPictureFG}{}
\newcommand{\gridSetup}[6][]{}
```

File 115 **lwarp-eurosym.sty**

§ 213 Package eurosym

(*Emulates or patches code by* Henrik Theiling.)

Pkg eurosym eurosym is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{eurosym}[1998/08/06]

\renewrobustcmd\officialeuro{\HTMLentity{euro}}
\let\geneuro\officialeuro
\let\geneuronarrow\officialeuro
\let\geneurowide\officialeuro
\let\euro\officialeuro
\renewrobustcmd\eurobars{}
\renewrobustcmd\eurobarsnarrow{}
\renewrobustcmd\eurobarswide{}
```

File 116 **lwarp-everypage.sty**

§ 214 Package everypage

(*Emulates or patches code by* Sergio Callegari.)

Pkg everypage everypage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{everypage}[2007/06/20]

\newcommand*{\AddEverypageHook}[1]{}
\newcommand*{\AddThispageHook}[1]{}
```

File 117 **lwarp-everyshi.sty**

§ 215 Package everyshi

(*Emulates or patches code by* Martin Schröder.)

Pkg everyshi ignored.

for HTML output: Discard all options for lwarp-everyshi:

```
\LWR@ProvidesPackageDrop{everyshi}[2001/05/15]

\newcommand*{\EveryShipout}[1]{}
\newcommand*{\AtNextShipout}[1]{}
```

File 118 **lwarp-extramarks.sty**

§ 216 Package extramarks

(*Emulates or patches code by* Piet van Oostrum.)

Pkg extramarks extramarks is ignored.

for HTML output: Discard all options for lwarp-extramarks:

```
\LWR@ProvidesPackageDrop{extramarks}[2019/01/31]

\newcommand*{\extramarks}[2]{}
\newcommand*{\firstleftxmark}{}
\newcommand*{\lastleftxmark}{}
\newcommand*{\firstrightxmark}{}
\newcommand*{\lastrightxmark}{}
\newcommand*{\firstxmark}{}
```

```
\newcommand*{\lastxmark}{}
\newcommand*{\topxmark}{}
\newcommand*{\topleftxmark}{}
\newcommand*{\toprightxmark}{}
\newcommand*{\firstleftmark}{}
\newcommand*{\lastrightmark}{}
\newcommand*{\firstrightmark}{}
\newcommand*{\lastleftmark}{}
```

File 119 **lwarp-fancybox.sty**

§ 217 Package

fancybox

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancybox

fancybox is supported with some patches.

framed equation example

fancybox's documentation has an example FramedEqn environment which combines math, \Sbox, a minipage, and an \fbox. This combination requires that the entire environment be enclosed inside a lateximage, which is done by adding \lateximage at the very start of FramedEqn's beginning code, and \endlateximage at the very end of the ending code. Unfortunately, the HTML alt attribute is not used here.

```
\newenvironmentFramedEqn
{
\lateximage% NEW
\setlength{\fboxsep}{15pt}
. . . }{. . .
\[\fbox{\TheSbox}\]
\endlateximage% NEW
}
```

framing alternatives

\fbox works with fancybox. Also see lwarp's \fboxBlock macro and fminipage environment for alternatives to \fbox for framing environments.

framed table example

The fancybox documentation's example framed table using an \fbox containing a tabular does not work with lwarp, but the FramedTable environment does work if \fbox is replaced by \fboxBlock. This method loses HTML formatting. A better method is to enclose the table's contents inside a fminipage environment. The caption may be placed either inside or outside the fminipage:

```
\begin{table}
\begin{fminipage}{\linewidth}
\begin{tabular}{lr}
. . .
\end{tabular}
\end{fminipage}
\end{table}
```

⚠ framed verbatim

lwarp does not support the verbatim environment inside a span, box, or fancybox's

\Sbox, but a verbatim may be placed inside a fminipage. The fancybox documentation's example FramedVerb may be defined as:

```
\newenvironment{FramedVerb}[1] % width
{
  \VerbatimEnvironment
  \fminipage{#1}
  \beginVerbatim
}{
  \endVerbatim
  \endfminipage
}
```

framed \VerbBox

fancybox's \VerbBox may be used inside \fbox.

indented alignment

LVerbatim, \LVerbatimInput, and \LUseVerbatim indent with horizontal space which may not line up exactly with what *pdftotext* detects. Some lines may be off slightly in their left edge.

fancybox, fancyvrb

⚠ \VerbatimFootnotes

⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\LWR@ProvidesPackagePass{fancybox}[2010/05/15]
```

After the preamble is loaded, after any patches to Verbatim:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancybox.}
```

\VerbatimFootnotes

Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

\V@@footnotetext

Patches in a subset of lwarp's \LWR@footnotetext to the fancyvrb version of \V@@footnotetext.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for `\ref`:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote to the list:

```
    \@makefntext{}%
```

The footnote text will follow after `\V@@@footnotetext` has completed.

```
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
  \ignorespaces%
}%

}% AfterEndPreamble

\renewcommand*{\@shadowbox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black]{shadowbox}{#1}}%
{\InlineClass{shadowbox}{#1}}%
}

\renewcommand*{\@doublebox}[1]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px double black]{doublebox}{#1}}%
{\InlineClass{doublebox}{#1}}%
}

\renewcommand*{\@ovalbox}[2]{%
\ifbool{FormatWP}%
{\InlineClass[border:1px solid black; border-radius:1ex]{ovalbox}{#2}}%
{%
    \ifthenelse{\isequivalentto{#1}{\thinlines}}%
        {\InlineClass{ovalbox}{#2}}%
        {\InlineClass{Ovalbox}{#2}}%
}%
}
```

Convert minipages, parboxes, and lists into linear text using the `LWR@nestspan` environment:

```
\let\LWR@origSbox\Sbox

\def\Sbox{\LWR@origSbox\LWR@nestspan}


\let\LWR@origendSbox\endSbox

\def\endSbox{\endLWR@nestspan\LWR@origendSbox}
```

`Beqnarray` is adapted for MathJax or enclosed inside a `lateximage`:

```
\RenewEnviron{Beqnarray}
{\LWR@eqnarrayfactor}

\csgpreto{Beqnarray*}{\boolfalse{LWR@numbereqnarray}}
```

`\GenericCaption` is enclosed in an HTML block:

```
\renewcommand{\GenericCaption}[1]{%
\LWR@figcaption%
\LWR@isolate{#1}%
\endLWR@figcaption%
}
```

`Btrivlist` is enclosed in an HTML block. This is a tabular, and does not use `\item`.

`\trivlist` {⟨*l/c/r*⟩} [⟨*t/c/b*⟩]

```
\RenewDocumentEnvironment{Btrivlist}{m o}
{%
    \begin{BlockClass}{Btrivlist}%
    \tabular{#1}%
}
{%
    \endtabular%
    \end{BlockClass}%
}
```

`Btrivlist` is also neutralized when used inside a span:

```
\AtBeginEnvironment{LWR@nestspan}{%
\RenewDocumentEnvironment{Btrivlist}{m o}{}{}%
}
```

lwarp's handling of `\item` is patched to accept fancybox's optional arguments:

```
\let\LWRFB@origitemizeitem\LWR@itemizeitem
\let\LWRFB@origdescitem\LWR@descitem

\RenewDocumentCommand{\LWR@itemizeitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origitemizeitem[#2]%
    }{%
```

```
        \LWRFB@origitemizeitem%
    }%
}

\RenewDocumentCommand{\LWR@descitem}{d()o}{%
    \IfValueTF{#2}{%
        \LWRFB@origdescitem[#2]~%
    }{%
        \LWRFB@origdescitem%
    }%
}


\RenewDocumentCommand{\LWR@nestspanitem}{d()}{%
\if@newlist\else{\LWR@htmltagc{br /}}\fi%
\LWR@origitem%
}
```

The various boxed lists become regular lists:

```
\renewenvironment{Bitemize}[1][]{\begin{itemize}}{\end{itemize}}
\renewenvironment{Benumerate}[1][]{\begin{enumerate}}{\end{enumerate}}
\renewenvironment{Bdescription}[1][]{\begin{description}}{\end{description}}
```

\boxput simply prints one then the other argument, side-by-side instead of above and behind:

```
\RenewDocumentCommand{\boxput}{s d() m m}{%
\IfBooleanTF{#1}{#3\quad#4}{#4\quad#3}%
}
```

Neutralized commands:

```
\RenewDocumentCommand{\fancyput}{s d() m}{}
\RenewDocumentCommand{\thisfancyput}{s d() m}{}

\RenewDocumentCommand{\fancypage}{m m}{}
\RenewDocumentCommand{\thisfancypage}{m m}{}

\def\LandScape#1{}
\def\endLandScape{}
\def\@Landscape#1#2#3{}
\def\endLandscape{}
```

Low-level patches for UseVerbatim and friends:

```
\let\LWRFB@UseVerbatim\UseVerbatim
\renewcommand*{\UseVerbatim}[1]{%
\LWR@atbeginverbatim{3}{Verbatim}%
\LWRFB@UseVerbatim{#1}%
\LWR@afterendverbatim{.5}%
}

```

```
\let\LWRFB@LUseVerbatim\LUseVerbatim

\renewcommand*{\LUseVerbatim}[1]{%
\LWR@atbeginverbatim{3}{LVerbatim}%
\noindent%
\LWRFB@LUseVerbatim{#1}%
\LWR@afterendverbatim{.5}%
}

\def\@BUseVerbatim[#1]#2{%
\LWR@atbeginverbatim{3}{BVerbatim}%
\LWRFB@UseVerbatim{#2}%
\LWR@afterendverbatim{.5}%
}
```

File 120 **lwarp-fancyhdr.sty**

§ 218 Package

fancyhdr

(*Emulates or patches code by* Piet van Oostrum.)

Pkg fancyhdr fancyhdr is ignored.

for HTML output: Discard all options for lwarp-fancyhdr:

```
\LWR@ProvidesPackageDrop{fancyhdr}[2019/01/31]

\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}
\newcommand*{\fancypagestyle}[2]{}
\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}
\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}
\newlength{\headwidth}
\newcommand*{\fancyheadoffset}[2][]{}
\newcommand*{\fancyfootoffset}[2][]{}
\newcommand*{\fancyhfoffset}[2][]{}
\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
\newcommand*{\iffootnote}[2]{#2}
```

File 121 **lwarp-fancyref.sty**

§ 219 Package

fancyref

Pkg fancyref fancyref is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{fancyref}[1999/02/03]
```

To remove the margin option, if \fancyrefhook is anything other than the paren option, then force it to the default instead. (Comparing to the margin option was not possible since lwarp has revised the meaning of \mbox so the comparison failed.)

```
\newcommand*{\LWRfref@parenfancyrefhook}[1]{(#1)}

\ifdefstrequal{\fancyrefhook}{\LWRfref@parenfancyrefhook}
{}{
    \renewcommand*{\fancyrefhook}[1]{#1}%
}
```

Modified to ignore the page number and varioref.

```
\renewcommand*{\@f@ref}[4]{%
  \@ifundefined{#1r@#2@#3}{%
    \PackageError{lwarp-fancyref}{%
      \backslashchar#1ref\space format ``#2''
      undefined\MessageBreak
      for label type ``#3''%
    }{%
      The format ``#2'' was not defined for the label type
      ``#3''\MessageBreak
      and the \backslashchar#1ref\space command.  Perhaps
      you have only misspelled its name.\MessageBreak
      Otherwise you will have to define it with
      \protect\new#1refformat\MessageBreak
      prior to using it.%
    }%
  }{%
    \fancyrefhook{%
      \@nameuse{#1r@#2@#3}%
        {\ref{#3\fancyrefargdelim#4}}%
%         {\pageref{#3\fancyrefargdelim#4}}% original
%         {\@fancyref@page@ref{#3\fancyrefargdelim#4}}% original
        {}% lwarp
        {}% lwarp
    }%
  }%
}%
```

File 122 **lwarp-fancytabs.sty**

§ 220 Package

fancytabs

Pkg fancytabs

fancytabs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fancytabs}[2016/03/29]

\newcommand{\fancytab}[3][RIGHT]{}
\newcommand{\fancytabsStyle}[1]{}
\newcommand{\fancytabsHeight}[1]{}
\newcommand{\fancytabsWidth}[1]{}
\newcommand{\fancytabsCount}[1]{}
\newcommand{\fancytabsLeftColor}[1]{}
\newcommand{\fancytabsRightColor}[1]{}
\newcommand{\fancytabsTop}[1]{}
\newcommand{\fancytabsTextVPos}[1]{}
\newcommand{\fancytabsTextHPos}[1]{}
\newcommand{\fancytabsGap}[1]{}
\newcommand{\fancytabsFloor}[1]{}
\newcommand{\fancytabsRotate}[1]{}
```

File 123 **lwarp-fancyvrb.sty**

§ 221 Package

fancyvrb

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg fancyvrb

fancyvrb is supported with some patches.

fancybox, fancyvrb
⚠ \VerbatimFootnotes
⚠ sectioning or displaymath

If using fancybox or fancyvrb with \VerbatimFootnotes, and using footnotes in a sectioning command or display math, use \footnotemark and \footnotetext:

```
\subsection[Subsection Name]
    {Subsection Name\protect\footnotemark}
\footnotetext{A footnote with \verb+verbtim+.}
```

and likewise for equations or display math.

At present there is a bug such that paragraph closing tags are not present in footnotes when \VerbatimFootnotes are selected. The browser usually compensates.

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackagePass{fancyvrb}[2008/02/07]
```

Initial default patch for fancyvrb:

```
\fvset{frame=none}%
```

After the preamble is loaded, after any patches to `Verbatim`:

```
\AfterEndPreamble{
\LWR@traceinfo{Patching fancyvrb.}
```

`\VerbatimFootnotes` Patched to use the new version.

```
\def\VerbatimFootnotes{%
\let\@footnotetext\V@footnotetext%
\let\footnote\V@footnote%
\let\LWR@footnotetext\V@footnotetext% lwarp
}
```

`\V@@footnotetext` Patches in a subset of lwarp's `\LWR@footnotetext` to the fancyvrb version of `\V@@footnotetext`.

```
\def\V@@footnotetext{%
\LWR@traceinfo{V@footnotetext}%
\global\setbox\LWR@footnotebox=\vbox\bgroup%
```

Add to any current footnotes:

```
    \unvbox\LWR@footnotebox%
```

Remember the footnote number for `\ref`:

```
    \protected@edef\@currentlabel{%
        \csname p@footnote\endcsname\@thefnmark%
    }% @currentlabel
```

Use HTML superscripts in the footnote even inside a `lateximage`:

```
    \renewrobustcmd{\textsuperscript}[1]{\LWR@htmlspan{sup}{##1}}%
```

Use paragraph tags if in a tabular data cell or a `lateximage`:

```
    \ifthenelse{%
        \boolean{LWR@doingstartpars} \AND%
        \cnttest{\value{LWR@lateximagedepth}}{=}{0}%
    }%
        {}%
        {\LWR@htmltagc{\LWR@tagregularparagraph}\LWR@orignewline}%
```

Append the footnote mark to the list:

```
    \@makefntext{}%
```

The footnote text will follow after `\V@@@footnotetext` has completed.

```
  \bgroup%
  \aftergroup{\V@@@footnotetext}%
  \ignorespaces%
}%

\preto\FVB@Verbatim{\LWR@forcenewpage}
```

```
\preto\FVB@LVerbatim{\LWR@forcenewpage}
% \preto\FVB@BVerbatim{\LWR@forcenewpage}% Fails, so done below.
```

Simplified to remove PDF formatting:

```
\def\FV@BeginListFrame@Single{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Single{%
  \FV@SingleFrameLine{\@ne}%
}

\def\FV@BeginListFrame@Lines{%
  \FV@SingleFrameLine{\z@}%
}

\def\FV@EndListFrame@Lines{%
    \FV@SingleFrameLine{\@ne}%
}

\renewcommand*{\FV@SingleFrameSep}{}
```

Adds HTML formatting:

```
\def\FV@BUseVerbatim#1{%
    \LWR@atbeginverbatim[\LWR@FVstyle]{0}{verbatim}%
    \FV@BVerbatimBegin#1\FV@BVerbatimEnd%
    \LWR@afterendverbatim{0}%
}
```

`\LWR@FVstyle` Holds the style of the verbatim.

```
\newcommand*{\LWR@FVstyle}{}
```

The following patches to `Verbatim` are executed at the start and end of the environment, depending on the choice of `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@fvstartnone}{%
\LWR@traceinfo{fvstartnone}%
% \hbox to\z@{
\LWR@atbeginverbatim[\LWR@FVstyle]{0}{verbatim}%
% }%
}

\newcommand*{\LWR@fvendnone}{%
\LWR@traceinfo{fvendnone}%
% \hbox to\z@{
\LWR@afterendverbatim{0}%
% }%
}

```

```
\newcommand*{\LWR@fvstartsingle}{%
\LWR@traceinfo{fvstartsingle}%
\LWR@fvstartnone%
\FV@BeginListFrame@Single%
}

\newcommand*{\LWR@fvendsingle}{%
\LWR@traceinfo{fvendsingle}%
\FV@EndListFrame@Single%
\LWR@fvendnone%
}

\newcommand*{\LWR@fvstartline}{%
\LWR@traceinfo{fvstartline}%
\LWR@fvstartnone%
% \setlength{\LWR@templengthone}{\baselineskip}%
\FV@BeginListFrame@Lines%
% \setlength{\baselineskip}{\LWR@templengthone}%
% \setlength{\baselineskip}{5pt}%
}

\newcommand*{\LWR@fvendline}{%
\LWR@traceinfo{fvendline}%
\FV@EndListFrame@Lines%
\LWR@fvendnone%
}
```

The following patches select the start/left/right/end behaviors depending on `frame`. Original code is from the fancyvrb package.

```
\newcommand*{\LWR@FVfindbordercolor}{%
\FancyVerbRuleColor%
\LWR@findcurrenttextcolor%
\color{black}%
}

% border width of \FV@FrameRule
\newcommand*{\LWR@FVborderstyle}[1]{%
padding#1: \strip@pt\dimexpr \FV@FrameSep\relax\relax pt ; %
\LWR@FVfindbordercolor %
border#1: \strip@pt\dimexpr \FV@FrameRule\relax\relax pt %
solid \LWR@origpound\LWR@tempcolor ; %
}

\def\FV@Frame@none{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle}%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}

\FV@Frame@none% default values

\def\FV@Frame@single{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{}}%
```

```
\let\FV@BeginListFrame\LWR@fvstartsingle%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\FV@RightListFrame@Single%
\let\FV@EndListFrame\LWR@fvendsingle}

\def\FV@Frame@lines{%
\renewcommand*{\LWR@FVstyle}{%
  \LWR@currenttextcolorstyle\LWR@FVborderstyle{-top}\LWR@FVborderstyle{-bottom}%
}%
\let\FV@BeginListFrame\LWR@fvstartline%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendline}

\def\FV@Frame@topline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-top}}%
\let\FV@BeginListFrame\LWR@fvstartline%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}

\def\FV@Frame@bottomline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-bottom}}%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\relax%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendline}

\def\FV@Frame@leftline{%
\renewcommand*{\LWR@FVstyle}{\LWR@currenttextcolorstyle\LWR@FVborderstyle{-left}}%
% To define the \FV@FrameFillLine macro (from \FV@BeginListFrame)
\ifx\FancyVerbFillColor\relax%
\let\FV@FrameFillLine\relax%
\else%
\@tempdima\FV@FrameRule\relax%
\multiply\@tempdima-\tw@%
\edef\FV@FrameFillLine{%
{\noexpand\FancyVerbFillColor{\vrule\@width\number\@tempdima sp}%
\kern-\number\@tempdima sp}}%
\fi%
\let\FV@BeginListFrame\LWR@fvstartnone%
\let\FV@LeftListFrame\FV@LeftListFrame@Single%
\let\FV@RightListFrame\relax%
\let\FV@EndListFrame\LWR@fvendnone}
```

Adds the optional label to the top and bottom edges. Original code is from the fancyvrb package.

```
\def\FV@SingleFrameLine#1{%
%   \hbox to\z@{%
%     \kern\leftmargin
    \ifnum#1=\z@\relax
      \let\FV@Label\FV@LabelBegin
    \else
      \let\FV@Label\FV@LabelEnd
```

```
    \fi
    \ifx\FV@Label\relax
%       \FancyVerbRuleColor{\vrule \@width\linewidth \@height\FV@FrameRule}%
    \else
      \ifnum#1=\z@
%         \setbox\z@\hbox{\strut\enspace\FV@LabelBegin\enspace\strut}%
        \ifx\FV@LabelPositionTopLine\relax
        \else
        \LWR@FVfindbordercolor
        \LWR@htmltagc{%
            div class="fancyvrblabel" % extra space
                style="color: \LWR@origpound\LWR@tempcolor"%
        }
        \LWR@print@textrm{\FV@LabelBegin}% \textrm preserves emdash
        \LWR@htmltagc{/div}
        \fi
      \else
%         \setbox\z@\hbox{\strut\enspace\FV@LabelEnd\enspace\strut}%
        \ifx\FV@LabelPositionBottomLine\relax
        \else
        \LWR@FVfindbordercolor

        \LWR@htmltagc{%
            div class="fancyvrblabel" % extra space
                style="color: \LWR@origpound\LWR@tempcolor"%
        }
        \LWR@print@textrm{\FV@LabelEnd}
        \LWR@htmltagc{/div}
        \fi
      \fi
    \fi
%     \hss
%     }
}
```

Processes each line, adding optional line numbers. Original code is from the fancyvrb package.

```
\def\FV@ListProcessLine#1{%
   \hbox to \hsize{%
%      \kern\leftmargin
      \hbox to \VerbatimHTMLWidth {%
       \ifcsvoid{FV@LeftListNumber}{}{\kern 2.5em}%
        \FV@LeftListNumber%
%       \FV@LeftListFrame
      \FancyVerbFormatLine{#1}%
      \hss%
%       \FV@RightListFrame
      \FV@RightListNumber%
    }%
      \hss% required to avoid underfull hboxes
}
}
```

Env BVerbatim

```
\AtBeginEnvironment{BVerbatim}
{%
\LWR@forcenewpage% instead of \preto
\LWR@atbeginverbatim{0}{bverbatim}%
}

\AfterEndEnvironment{BVerbatim}
{%
\LWR@afterendverbatim{0}%
}
```

End of the modifications to make at the end of the preamble:

```
} % \AfterEndPreamble
```

File 124 **lwarp-figcaps.sty**

§ 222 Package figcaps

(*Emulates or patches code by* Patrick W. Daly.)

Pkg figcaps figcaps is ignored.

for HTML output: Discard all options for lwarp-figcaps:

```
\LWR@ProvidesPackageDrop{figcaps}[1999/02/23]

\newcommand*{\figcapson}{}
\newcommand*{\figcapsoff}{}
\newcommand*{\printfigures}{}
\newcommand*{\figmarkon}{}
\newcommand*{\figmarkoff}{}
\def\figurecapname{Figure Captions}
\def\tablepagename{Tables}
\def\figurepagename{Figures}
```

File 125 **lwarp-figsize.sty**

§ 223 Package figsize

(*Emulates or patches code by* Anthony A. Tanbakuchi.)

Pkg figsize figsize is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{figsize}[2002/03/18]
```

Emulates a virtual 6×9 inch textsize.

```
\newlength{\figwidth}
\newlength{\figheight}

\newcommand{\SetFigLayout}[3][0]{%
\setlength{\figheight}{8in}%
\setlength{\figheight}{\figheight / #2}%
%
\setlength{\figwidth}{5.5in}%
\setlength{\figwidth}{\figwidth / #3}%
}
```

File 126 **lwarp-fitbox.sty**

§ 224 Package fitbox

Pkg fitbox fitbox is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fitbox}[2019/02/20]

\NewDocumentCommand{\fitbox}{s o m}{%
    \begin{BlockClass}{fitbox}
    #3
    \end{BlockClass}
}

\newcommand*{\fitboxset}[1]{}

\newdimen\fitboxnatheight
\newdimen\fitboxnatwidth

\newcommand\SetFitboxLayout[3][]{}
```

File 127 **lwarp-fix2col.sty**

§ 225 Package fix2col

Pkg fix2col fix2col is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fix2col}[2015/11/13]
```

File 128 **lwarp-fixme.sty**

§ 226 Package fixme

(*Emulates or patches code by* Didier Verna.)

Pkg fixme fixme is patched for use by lwarp.

⚠ external layouts

External layouts (`\fxloadlayouts`) are not supported.

User control is provided for setting the HTML styling of the "faces". The defaults are as follows, and may be changed in the preamble after fixme is loaded:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}
\def\FXFaceEnvHTMLStyle{font-weight:bold}
\def\FXFaceSignatureHTMLStyle{font-style:italic}
\def\FXFaceTargetHTMLStyle{font-style:italic}
```

for HTML output:

```
\LWR@ProvidesPackagePass{fixme}[2017/03/05]
```

Restore lwarp's version of `\@wrindex`, ignoring the fixme package's `target` option:

```
\let\@wrindex\LWR@wrindex
```

Float-related macros required by lwarp:

```
\newcommand{\ext@fixme}{lox}

\renewcommand{\l@fixme}[2]{\hypertocfloat{1}{fixme}{lox}{#1}{#2}}
```

Other modifications:

```
\def\FXFaceInlineHTMLStyle{font-weight:bold}

\renewcommand*\FXLayoutInline[3]{ %
\InlineClass[\FXFaceInlineHTMLStyle]{fixmeinline}%
    {\@fxtextstd{#1}{#2}{#3}}%
}

\def\FXFaceEnvHTMLStyle{font-weight:bold}

\renewcommand*\FXEnvLayoutPlainBegin[2]{%
\BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
\ignorespaces#2 \fxnotename{#1}: \ignorespaces}

\renewcommand*\FXEnvLayoutPlainEnd[2]{\endBlockClass}

\renewcommand*\FXEnvLayoutSignatureBegin[2]{%
\BlockClass[\FXFaceEnvHTMLStyle]{fixmebold}
\fxnotename{#1}: \ignorespaces}

\renewcommand*\FXEnvLayoutSignatureEnd[2]{\@fxsignature{#2}\endBlockClass}

\def\FXFaceSignatureHTMLStyle{font-style:italic}

\DeclareRobustCommand*\@fxsignature[1]{%
\ifthenelse{\equal{#1}{}}%
    {}%
    { -- {\InlineClass[\FXFaceSignatureHTMLStyle]{fixmesignature}{#1}}}%
}


```

```
\def\FXFaceTargetHTMLStyle{font-style:italic}

\renewcommand\FXTargetLayoutPlain[2]{%
    \InlineClass[\FXFaceTargetHTMLStyle]{fixmetarget}{#2}%
}
```

File 129 **lwarp-fixmetodonotes.sty**

§ 227 Package fixmetodonotes

(*Emulates or patches code by* Gioele Barabucci.)

Pkg fixmetodonotes fixmetodonotes is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{fixmetodonotes}[2013/04/28]

\renewcommand{\NOTES@addtolist}[2]{%
    \refstepcounter{NOTES@note}%
%   \phantomsection% REMOVED
    \addcontentsline{notes}{NOTES@note}{%
        \protect\numberline{\theNOTES@note}{{#1}: {#2}}%
    }%
}

\renewcommand{\NOTES@marker}[2]{\fbox{%
    \textcolor{#2}{% WAS \color
        \textbf{#1}}%
    }}

\renewcommand{\NOTES@colorline}[2]{%
  \bgroup%
    \ULon{\LWR@backgroundcolor{#1}{#2}}%
}
```

File 130 **lwarp-flafter.sty**

§ 228 Package flafter

Pkg flafter flafter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flafter}[2018/01/08]
\providecommand\fl@trace[1]{}
```

File 131 **lwarp-flippdf.sty**

§ 229 Package flippdf

Pkg flippdf flippdf is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{flippdf}[2006/06/30]

\newcommand\FlipPDF{}
\newcommand\UnFlipPDF{}
```

File 132 **lwarp-float.sty**

§ 230 Package

float

(*Emulates or patches code by* Anselm Lingnau.)

Pkg float

float is emulated.

Float styles boxed and ruled are emulated by CSS and a float class according to style.

The HTML <figure> class is set to the float type, so CSS may also be used to format the float and its caption, according to float type. Furthermore, an additional class is set to the float style: plain, plaintop, boxed, or ruled, so CSS may be used to format by float style as well. Default formatting by CSS is provided for ruled and boxed styles.

for HTML output:

```
\LWR@ProvidesPackageDrop{float}[2001/11/08]
```

\listof

See section 75.2 for the \listof command.

\LWR@floatstyle

The default float style:

```
\newcommand*{\LWR@floatstyle}{plain}
```

\newfloat

{⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the \newfloat command from the float package.

"placement" is ignored.

```
\NewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{\DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}}%
{\DeclareFloatingEnvironment[fileext=#3]{#1}}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later.

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
```

Likesize, newfloat also creates \l@<type>, but float does not, so remove it here:

```
\cslet{l@#1}\relax%
}
```

`\floatname` {⟨*type*⟩} {⟨*name*⟩}

Sets the text name of the float, such as “Figure”.

```
\NewDocumentCommand{\floatname}{m +m}{%
    \SetupFloatingEnvironment{#1}{name=#2}%
}
```

`\floatplacement` {⟨*type*⟩} {⟨*placement*⟩}

Float placement is ignored.

```
\newcommand*{\floatplacement}[2]{%
    \SetupFloatingEnvironment{#1}{placement=#2}%
}
```

`\floatstyle` {⟨*style*⟩}

Remember the style for future floats:

```
\newcommand{\floatstyle}[1]{%
    \def\LWR@floatstyle{#1}%
}
```

`\restylefloat` * {⟨*type*⟩}

Remember the style for this float:

```
\NewDocumentCommand{\restylefloat}{s m}{%
    \csedef{LWR@floatstyle@#2}{\LWR@floatstyle}%
}
```

File 133 **`lwarp-floatflt.sty`**

§ 231 Package

floatflt

(*Emulates or patches code by* Mats Dahlgren.)

`Pkg floatflt` floatflt is emulated.

for HTML output: Discard all options for lwarp-floatflt:

```
\LWR@ProvidesPackageDrop{floatflt}[1997/07/16]
```

`Env [⟨⟩]` offset {⟨*type*⟩} {⟨*width*⟩} Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTfloatflt@marginfloat}{O{-1.2ex} m m}
{%
\setlength{\LWR@templengthone}{#3}%
\LWR@BlockClassWP{%
    float:right; %
    width:\LWR@printlength{\LWR@templengthone};  % extra space
    margin:10pt%
}{%
```

```
    width:\LWR@printlength{\LWR@templengthone}%
}%
{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}
```

Env floatingfigure [⟨*placement*⟩] {⟨*width*⟩}

```
\DeclareDocumentEnvironment{floatingfigure}{o m}
  {\begin{KFLTfloatflt@marginfloat}{figure}{#2}}
  {\end{KFLTfloatflt@marginfloat}}
```

Env floatingtable [⟨*placement*⟩]

```
\DeclareDocumentEnvironment{floatingtable}{o}
  {\begin{KFLTfloatflt@marginfloat}{table}{1.5in}}
  {\end{KFLTfloatflt@marginfloat}}
```

File 134 **lwarp-floatpag.sty**

§ 232 Package

floatpag

(*Emulates or patches code by* Vytas Statulevičius and Sigitas Tolušis.)

Pkg floatpag floatpag is ignored.

for HTML output: Discard all options for lwarp-floatpag:

```
\LWR@ProvidesPackageDrop{floatpag}[2012/05/29]
```

```
\newcommand*{\floatpagestyle}[1]{}
\newcommand*{\rotfloatpagestyle}[1]{}
\newcommand*{\thisfloatpagestyle}[1]{}
```

File 135 **lwarp-floatrow.sty**

§ 233 Package

floatrow

(*Emulates or patches code by* Olga Lapko.)

Pkg floatrow floatrow is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{floatrow}[2008/08/02]
```

⚠ Misplaced alignment tab character & Use \StartDefiningTabulars and \StopDefiningTabulars before and after defining macros using \ttabbox with a tabular inside. See section 8.10.1.

⚠ subfig package When combined with the subfig package, while inside a subfloatrow \ffigbox and \ttabbox must have the caption in the first of the two of the mandatory arguments.

⚠ \FBwidth, \FBheight The emulation of floatrow does not support \FBwidth or \FBheight. These values are pre-set to .3\linewidth and 2in. Possible solutions include:

- Use fixed lengths. lwarp will scale the HTML lengths appropriately.
- Use warpprint and warpHTML environments to select appropriate values for each case.
- Inside a warpHTML environment, manually change \FBwidth or \FBheight before the \ffigbox or \ttabbox. Use \FBwidth or \FBheight normally afterwards; it will be used as expected in print output, and will use your custom-selected value in HTML output. This custom value will be used repeatedly, until it is manually changed to a new value.

After everything has loaded, remember whether subcaption was loaded. If not, it is assumed that subfig is used instead:

```
\newbool{LWR@subcaptionloaded}

\AtBeginDocument{
\@ifpackageloaded{subcaption}
{\booltrue{LWR@subcaptionloaded}}
{\boolfalse{LWR@subcaptionloaded}}
}
```

\floatbox [⟨*1 preamble*⟩] {⟨*2 captype*⟩} [⟨*3 width*⟩] [⟨*4 height*⟩] [⟨*5 vert pos*⟩] {⟨*6 caption*⟩} {⟨*7 object*⟩}

Only parameters for captype, width, caption, and object are used.

LWR@insubfloatrow is true if inside a subfloatrow environment.

There are two actions, depending on the use of subcaption or subfig.

```
\NewDocumentCommand{\floatbox}{o m o o o +m +m}{%
\ifbool{LWR@subcaptionloaded}%
{% subcaption
```

For subcaption:

```
    \ifbool{LWR@insubfloatrow}%
    {% subcaption in a subfloatrow
```

subfigure and subtable environments take width as an argument.

```
        \IfValueTF{#3}%
        {\@nameuse{sub#2}{#3}}%
        {\@nameuse{sub#2}{\linewidth}}%
    }% subcaption in a subfloatrow
    {% subcaption not in subfloatrow
```

figure and table environments do not take a width argument.

```
        \@nameuse{#2}%
    }% subcaption not in subfloatrow
```

```
    #6

    #7
```

End the environments:

```
    \ifbool{LWR@insubfloatrow}%
    {\@nameuse{endsub#2}}%
    {\@nameuse{end#2}}%
}% subcaption
{% assume subfig
```

For subfig:

```
\ifbool{LWR@insubfloatrow}%
{% subfig in a subfloatrow
```

`\subfloat` is a macro, not an environment.

Package subfig's `\subfloat` command takes an optional argument which is the caption, but `\floatbox` argument #6 contains commands to create the caption and label, not the caption itself. Thus, `\caption` is temporarily disabled to return its own argument without braces.

```
    \begingroup
    \let\caption\@firstofone
    \subfloat[#6]{#7}
    \endgroup
}% subfig in a subfloatrow
{% subfig package, but not a subfig
```

`figure` and `table` are environments:

```
\@nameuse{#2}
#6

#7
\@nameuse{end#2}
}% subfig package, but not a subfig
}% assume subfig
}
```

Not used:

```
\newcommand*{\nocapbeside}{}
\newcommand*{\capbeside}{}
\newcommand*{\captop}{}
\newlength{\FBwidth}
\setlength{\FBwidth}{.3\linewidth}
\newlength{\FBheight}
\setlength{\FBheight}{2in}
\newcommand*{\useFCwidth}{}
\newcommand{\floatsetup}[2][]{}
\newcommand{\thisfloatsetup}[1]{}
\newcommand{\clearfloatsetup}[1]{}
\newcommand*{\killfloatstyle}{}
```

`\newfloatcommand` {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\newfloatcommand}{m m o o}{%
\@namedef{#1}{
\floatbox{#2}
}
}
```

\renewfloatcommand {⟨*1 command*⟩} {⟨*2 captype*⟩} [⟨*3 preamble*⟩] [⟨*4 default width*⟩]

Preamble and default width are ignored.

```
\NewDocumentCommand{\renewfloatcommand}{m m o o}{%
\@namedef{#1}{%
\floatbox{#2}
}
}
```

\ffigbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ffigbox}{figure}[\nocapbeside][]
```

\ttabbox [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{ttabbox}{table}[\captop][\FBwidth]
```

\fcapside [⟨*width*⟩] [⟨*height*⟩] [⟨*vposn*⟩] {⟨*caption commands*⟩} {⟨*contents*⟩}

```
\newfloatcommand{fcapside}{figure}[\capbeside][]
```

Env floatrow [⟨*numfloats*⟩]

The row of floats is placed into a of class floatrow.

```
\newenvironment*{floatrow}[1][2]
{
\LWR@forcenewpage
\BlockClass{floatrow}
```

While inside the floatrow, divide the \linewidth by the number of floats.

```
\booltrue{LWR@infloatrow}
\setlength{\linewidth}{6in/#1}
}
{
\boolfalse{LWR@infloatrow}
\endBlockClass
}
```

Keys for \DeclareNewFloatType:

```
\newcommand*{\LWR@frowkeyplacement}{}
\newcommand*{\LWR@frowkeyname}{}
\newcommand*{\LWR@frowkeyfileext}{}
\newcommand*{\LWR@frowkeywithin}{}
\newcommand*{\LWR@frowkeycapstyle}{}

```

```
\define@key{frowkeys}{placement}{}%
\define@key{frowkeys}{name}{\renewcommand{\LWR@frowkeyname}{#1}}%
\define@key{frowkeys}{fileext}{\renewcommand{\LWR@frowkeyfileext}{#1}}%
\define@key{frowkeys}{within}{\renewcommand{\LWR@frowkeywithin}{#1}}%
\define@key{frowkeys}{relatedcapstyle}{}%
```

\DeclareNewFloatType {⟨*type*⟩} {⟨*options*⟩}

Use `\listof{type}{Title}` to print a list of the floats.

```
\newcommand*{\DeclareNewFloatType}[2]{%
```

Reset key values:

```
\renewcommand*{\LWR@frowkeyplacement}{}%
\renewcommand*{\LWR@frowkeyname}{}%
\renewcommand*{\LWR@frowkeyfileext}{}%
\renewcommand*{\LWR@frowkeywithin}{}%
\renewcommand*{\LWR@frowkeycapstyle}{}%
```

Read new key values:

```
\LWR@traceinfo{about to setkeys frowkeys}%
\setkeys{frowkeys}{#2}%
\LWR@traceinfo{finished setkeys frowkeys}%
```

Create a new float with optional [within]:

```
\ifthenelse{\equal{\LWR@frowkeywithin}{}}%
{%
    \LWR@traceinfo{about to newfloat #1 \LWR@frowkeyplacement\ %
        \LWR@frowkeyfileext}%
    \newfloat{#1}{\LWR@frowkeyplacement}{\LWR@frowkeyfileext}%
}%
{%
    \LWR@traceinfo{about to newfloat #1\ \LWR@frowkeyplacement\ %
        \LWR@frowkeyfileext\ \LWR@frowkeywithin}%
    \newfloat{#1}{\LWR@frowkeyplacement}%
    {\LWR@frowkeyfileext}[\LWR@frowkeywithin]%
    \LWR@traceinfo{finished newfloat #1}%
}%
```

Rename the float if a name was given:

```
\ifthenelse{\equal{\LWR@frowkeyname}{}}%
    {}%
    {\floatname{#1}{\LWR@frowkeyname}}%
}
```

Not used:

```
\newcommand{\buildFBBOX}[2]{}
\newcommand*{\CenterFloatBoxes}{}
\newcommand*{\TopFloatBoxes}{}
\newcommand*{\BottomFloatBoxes}{}
\newcommand*{\PlainFloatBoxes}{}

\newcommand{\capsubrowsettings}{}

```

```
126 \NewDocumentCommand{\RawFloats}{o o}{}
```

\RawCaption {⟨*text*⟩}

To be used inside a minipage or parbox.

```
127 \newcommand{\RawCaption}[1]{#1}
```

\floatfoot {⟨*text*⟩}

Places additional text inside a float, inside a css of class floatfoot.

```
128 \NewDocumentCommand{\floatfoot}{s +m}{%
129 \begin{BlockClass}{floatfoot}
130 #2
131 \end{BlockClass}
132 }
```

Used to compute \linewidth.

```
133 \newbool{LWR@insubfloatrow}
134 \boolfalse{LWR@insubfloatrow}
```

Env subfloatrow [⟨*num_floats*⟩]

```
135 \newenvironment*{subfloatrow}[1][2]
136 {
```

The row of floats is placed into a of class floatrow:

```
137 \LWR@forcenewpage
138 \BlockClass{floatrow}
```

While inside the floatrow, LWR@insubfloatrow is set true, which tells \floatbox to use \subfigure or \subtable.

```
139 \begingroup
140 \booltrue{LWR@insubfloatrow}
141 }
142 {
143 \endgroup
144 \endBlockClass
145 \boolfalse{LWR@insubfloatrow}
146 }
```

File 136 **lwarp-fltrace.sty**

§ 234 Package fltrace

Pkg fltrace fltrace is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{fltrace}[2018/01/08]
```

```
2 \def\tracefloats{}
```

```
\def\tracefloatsoff{}
\def\tracefloatvals{}
```

File 137 **lwarp-flushend.sty**

§ 235 Package flushend

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg flushend flushend is ignored.

for HTML output: Discard all options for lwarp-flushend:

```
\LWR@ProvidesPackageDrop{flushend}[2017/03/27]

\newcommand*{\flushend}{}
\newcommand*{\raggedend}{}
\newcommand*{\flushcolsend}{}
\newcommand*{\raggedcolsend}{}
\newcommand*{\atColsBreak}[1]{}
\newcommand*{\atColsEnd}[1]{}
\newcommand*{\showcolsendrule}{}
```

File 138 **lwarp-fnbreak.sty**

§ 236 Package fnbreak

Pkg fnbreak fnbreak is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnbreak}[2012/01/01]

\newcommand*{\fnbreakverbose}{}
\newcommand*{\fnbreaknonverbose}{}
\newcommand*{\fnbreaklabel}{}
\newcommand*{\fnbreaknolabel}{}
```

File 139 **lwarp-fncychap.sty**

§ 237 Package fncychap

(*Emulates or patches code by* Ulf A. Lindgren.)

Pkg fncychap fncychap is ignored.

for HTML output: Discard all options for lwarp-fncychap:

```
\LWR@ProvidesPackageDrop{fncychap}[2007/07/30]
```

```
\def\mghrulefill#1{}
\def\ChNameLowerCase{}
\def\ChNameUpperCase{}
\def\ChNameAsIs{}
\def\ChTitleLowerCase{}
\def\ChTitleUpperCase{}
\def\ChTitleAsIs{}
\newcommand{\ChRuleWidth}[1]{}
\newcommand{\ChNameVar}[1]{}
\newcommand{\ChNumVar}[1]{}
\newcommand{\ChTitleVar}[1]{}
\newcommand{\TheAlphaChapter}{}
\newcommand{\DOCH}{}
\newcommand{\DOTI}[1]{}
\newcommand{\DOTIS}[1]{}
\newlength{\mylen}
\newlength{\myhi}
\newlength{\px}
\newlength{\py}
\newlength{\pyy}
\newlength{\pxx}
\newlength{\RW}
\newcommand{\FmN}[1]{#1}
\newcommand{\FmTi}[1]{#1}
```

File 140 **lwarp-fnlineno.sty**

§ 238 Package fnlineno

Pkg fnlineno fnlineno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnlineno}[2011/01/07]
```

File 141 **lwarp-fnpara.sty**

§ 239 Package fnpara

Pkg fnpara fnpara is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpara}
```

File 142 **lwarp-fnpos.sty**

§ 240 Package fnpos

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg fnpos fnpos is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fnpos}[1999/07/14]

\newcommand*{\makeFNbottom}{}
\newcommand*{\makeFNmid}{}
\newcommand*{\makeFNbelow}{}
\newcommand*{\makeFNabove}{}
```

File 143 **lwarp-fontawesome.sty**

§ 241 Package

fontawesome

(*Emulates or patches code by* Xavier Danaux.)

Pkg fontawesome fontawesome is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

⚠ *poppler* syntax warning If using pdfLaTeX, *poppler* may issue a syntax warning regarding parsing a ligature component. XeLaTeX or LuaLaTeX may be used to avoid this warning.

In the following, the general strategy is to intercept `\symbol` and embed it inside a `lateximage`. These changes are done inside a local group.

For pdfLaTeX, the `alt` tag includes the icon (symbol) number. For XeLaTeX and LuaLaTeX, the `alt` tag is generic.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome}[2016/05/15]

\LetLtxMacro\LWR@orig@symbol\symbol

\ifxetexorluatex

\newfontfamily{\LWR@orig@FA}{FontAwesome}

\newcommand*{\LWR@fontawesome@xelatex@symbol}[1]{%
\begin{lateximage}*[(icon)][fontawesomexetex#1]%
\begingroup%
\LWR@orig@FA%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\RenewDocumentCommand{\FA}{}{%
    \LetLtxMacro\symbol\LWR@fontawesome@xelatex@symbol%
}

\else

\newcommand*{\LWR@fontawesome@symbolone}[1]{%
```

```
\begin{lateximage}*[(icon #1)][fontawesomeone#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesomeone}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symboltwo}[1]{%
\begin{lateximage}*[(icon #1)][fontawesometwo#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesometwo}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\newcommand*{\LWR@fontawesome@symbolthree}[1]{%
\begin{lateximage}*[(icon #1)][fontawesomethree#1]%
\begingroup%
\fontencoding{U}\fontfamily{fontawesomeonethree}\selectfont%
\LWR@orig@symbol{#1}%
\endgroup%
\end{lateximage}%
}

\renewrobustcmd\FAone{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolone%
}

\renewrobustcmd\FAtwo{%
    \LetLtxMacro\symbol\LWR@fontawesome@symboltwo%
}

\renewrobustcmd\FAthree{%
    \LetLtxMacro\symbol\LWR@fontawesome@symbolthree%
}
\fi
```

File 144 **lwarp-fontawesome5.sty**

§ 242 Package fontawesome5

(*Emulates or patches code by* Marcel Krüger.)

Pkg fontawesome5 fontawesome5 is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

The `alt` tag has the name of the icon.

for HTML output:

```
\LWR@ProvidesPackagePass{fontawesome5}[2018/07/27]
```

```
\ExplSyntaxOn
\cs_set:Nn\fontawesome_use_icon:nn{
  \cs_if_exist:cTF{c__fontawesome_slot_#2_tl}{
    \begin{lateximage}*[(#2)][#1]
    \exp_last_unbraced:Nv
      \__fontawesome_icon_at:nnnn
      {c__fontawesome_slot_#2_tl}
        {#1}{#2}
    \end{lateximage}
  }{
    \msg_error:nnxx{fontawesome5}{icon-not-found}{#2}{#1}
  }
}
\ExplSyntaxOff
```

File 145 **lwarp-fontaxes.sty**

§ 243 Package

fontaxes

(*Emulates or patches code by* Andreas Bühmann, Michael Ummels.)

Pkg fontaxes

fontaxes is emulated for HTML, and used as-is for print output.

Functionality for small caps is in the lwarp core. Swashes and figure styles are ignored for HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{fontaxes}[2014/03/23]

\newrobustcmd{\LWR@HTML@sscshape}{\LWR@HTML@scshape}
\LWR@formatted{sscshape}
\newcommand*{\LWR@null@sscshape}{}

\newrobustcmd{\LWR@HTML@textssc}[1]{\textsc{#1}}
\LWR@formatted{textssc}
\newcommand*{\LWR@null@textssc}[1]{#1}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by nfssext-cfr
    \newcommand{\LWR@HTML@swshape}{}
    \LWR@formatted{swshape}
    \newcommand*{\LWR@null@swshape}{}

    \newcommand{\LWR@HTML@textsw}[1]{#1}
    \LWR@formatted{textsw}
    \newcommand*{\LWR@null@textsw}[1]{#1}
}

\appto{\LWR@nullfonts}{%
\LetLtxMacro\sscshape\LWR@null@sscshape%
\LetLtxMacro\textssc\LWR@null@textssc%
\LetLtxMacro\swshape\LWR@null@swshape%
\LetLtxMacro\textsw\LWR@null@textsw%
}
```

File 146 **lwarp-fontenc.sty**

§ 244 Package fontenc

Pkg fontenc If using pdfLaTeX, lwarp used to require fontenc be loaded before lwarp, but now lwarp itself loads `\fontenc` with T1 encoding, which lwarp requires. fontenc is now allowed to be loaded with another encoding after lwarp.

lwarp-fontenc is no longer necessary, but is still provided to overwrite older versions.

for HTML output:

```
\LWR@ProvidesPackagePass{fontenc}[2017/04/05]
```

File 147 **lwarp-footmisc.sty**

§ 245 Package footmisc

(*Emulates or patches code by* Robin Fairbairns.)

Pkg footmisc footmisc is emulated.

lwarp incidentally happens to emulate the `stable` option.

```
\LWR@ProvidesPackageDrop{footmisc}[2011/06/06]
```

Some nullified commands:

```
\newcommand{\footnotelayout}{}
\newcommand{\setfnsymbol}[1]{}
\NewDocumentCommand{\DefineFNsymbols}{s m o m}{}

\newdimen\footnotemargin
\footnotemargin1.8em\relax

\newcommand*\hangfootparskip{0.5\baselineskip}
\newcommand*\hangfootparindent{0em}%

\let\pagefootnoterule\footnoterule
\let\mpfootnoterule\footnoterule
\def\splitfootnoterule{\kern-3\p@ \hrule \kern2.6\p@}

\providecommand*{\multiplefootnotemarker}{3sp}
\providecommand*{\multfootsep}{,}
```

Using cleveref:

```
\providecommand*{\footref}[1]{\labelcref{#1}}
```

The following work as-is:

```
\newcommand\mpfootnotemark{%
  \@ifnextchar[%
    \@xmpfootnotemark%
    {%
      \stepcounter\@mpfn%
      \protected@xdef\@thefnmark{\thempfn}%
      \@footnotemark%
    }%
}
\def\@xmpfootnotemark[#1]{%
  \begingroup%
    \csname c@\@mpfn\endcsname #1\relax%
    \unrestored@protected@xdef\@thefnmark{\thempfn}%
  \endgroup%
  \@footnotemark%
}
```

File 148 **lwarp-footnote.sty**

§ 246 Package

footnote

(*Emulates or patches code by* Mark Wooding.)

Pkg footnote footnote is used with minor patches.

for HTML output:

```
\LWR@ProvidesPackagePass{footnote}[1997/01/28]
```

Removed print-version formatting:

```
\def\fn@startnote{%
%   \@parboxrestore%
  \protected@edef\@currentlabel{\csname p@\@mpfn\endcsname\@thefnmark}%
%   \color@begingroup% *** conflicts with lwarp
}

% \let\fn@endnote\color@endgroup% *** conflicts with lwarp
\def\fn@endnote{%
\LWR@htmltagc{/\LWR@tagregularparagraph}%
\LWR@orignewline%
}
```

Removed print-version formatting:

```
\def\fn@startfntext{%
  \setbox\z@\vbox\bgroup%
    \fn@startnote%
    \fn@prefntext%
    \ignorespaces%
}
```

Removed print-version formatting, added closing paragraph tag:

```
\def\fn@endfntext{%
    \LWR@htmltagc{/\LWR@tagregularparagraph}%
    \LWR@orignewline%
    \fn@postfntext%
  \egroup%
  \begingroup%
    \let\@makefntext\@empty%
    \let\@finalstrut\@gobble%
    \LetLtxMacro\rule\@gobbletwo% *8* also the optional argument?
    \@footnotetext{\unvbox\z@}%
  \endgroup%
}
```

These have been redefined, so re-`\let` them again:

```
\let\endfootnote\fn@endfntext
\let\endfootnotetext\endfootnote
```

File 149 **lwarp-footnotebackref.sty**

§ 247 Package

footnotebackref

Pkg footnotebackref

footnotebackref is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnotebackref}[2012/07/01]
```

File 150 **lwarp-footnotehyper.sty**

§ 248 Package

footnotehyper

Pkg footnotehyper

footnotehyper is a hyperref-safe version of footnote. For lwarp, footnotehyper is emulated.

for HTML output:

Discard all options for lwarp-footnotehyper:

```
\RequirePackage{footnote}
\LWR@ProvidesPackageDrop{footnotehyper}[2018/01/23]
```

File 151 **lwarp-footnoterange.sty**

§ 249 Package

footnoterange

(*Emulates or patches code by* H.-Martin Münch.)

Pkg footnoterange

footnoterange is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{footnoterange}[2012/02/17]

\csletcs{footnoterange}{footnoterange*}
\csletcs{endfootnoterange}{endfootnoterange*}
```

File 152 **lwarp-footnpag.sty**

§ 250 Package footnpag

Pkg footnpag footnpag is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{footnpag}
```

File 153 **lwarp-foreign.sty**

§ 251 Package foreign

(*Emulates or patches code by* Philip G. Ratcliffe.)

Pkg foreign foreign is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{foreign}[2012/09/25]

\renewcommand\foreignabbrfont{\emph}
```

File 154 **lwarp-forest.sty**

§ 252 Package forest

(*Emulates or patches code by* Sašo Živanović.)

Pkg forest forest is patched for use by lwarp.

⚠ \Forest* The starred version of the macro \Forest* is not supported. lwarp encases each lateximage in an environment, so the global results of the starred \Forest* are lost.

for HTML output:

```
\LWR@ProvidesPackagePass{forest}[2017/07/14]

\BeforeBeginEnvironment{forest}{\begin{lateximage}[forest]}

\AfterEndEnvironment{forest}{\end{lateximage}}

\RenewDocumentCommand{\Forest}{s D(){} m}{%
  \forest@config{#2}%
  \IfBooleanTF{#1}{%
        \PackageError{lwarp-forest}%
```

```
      {Starred \Forest is not supported}%
    {Lwarp uses an environment for images, but \Forest* cannot work in an environment.}%
      \let\forest@next\forest@env%
   }{\let\forest@next\forest@group@env}%
   \begin{lateximage}[forest]%     lwarp
 \forest@next{#3}%
   \end{lateximage}%               lwarp
}
```

File 155 **lwarp-framed.sty**

§ 253 Package

framed

(*Emulates or patches code by* Donald Arseneau.)

Pkg framed framed is supported and patched by lwarp.

for HTML output: Accept all options for lwarp-framed:

```
\LWR@ProvidesPackagePass{framed}[2011/10/22]
\RequirePackage{xcolor}% for \convertcolorspec

\renewenvironment{framed}{%
\LWR@forcenewpage
\BlockClass{framed}%
}
{\endBlockClass}
\renewenvironment{oframed}{%
\LWR@forcenewpage
\BlockClass{framed}%
}
{\endBlockClass}


\renewenvironment{shaded}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
}
{\endBlockClass}
\renewenvironment{shaded*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{shaded}%
}
{\endBlockClass}


\renewenvironment{leftbar}{%
\LWR@forcenewpage
```

```
    \BlockClass{framedleftbar}
  \def\FrameCommand{}%
  \MakeFramed {}
}%
 {\endMakeFramed\endBlockClass}


\renewenvironment{snugshade}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\renewenvironment{snugshade*}{%
\convertcolorspec{named}{shadecolor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\BlockClass[background: \LWR@origpound\LWR@tempcolor]{snugframed}%
}
{\endBlockClass}

\let\oframed\framed
\let\endoframed\endframed


\RenewEnviron{titled-frame}[1]{%
\CustomFBox{#1}{}{0pt}{0pt}{0pt}{0pt}{\BODY}
}
```

\CustomFBox {⟨*toptitle*⟩} {⟨*bottitle*⟩} {⟨*thicknesstop*⟩} {⟨*bottom*⟩} {⟨*left*⟩} {⟨*right*⟩} {⟨*text contents*⟩}

```
\renewcommand{\CustomFBox}[7]{%
\convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
\LWR@forcenewpage
\begin{BlockClass}[border: 3px solid \LWR@origpound\LWR@tempcolor]{framed}%
\ifthenelse{\isempty{#1}}{}{% not empty
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#1}}%
    \end{BlockClass}
}% not empty

#7

\ifthenelse{\isempty{#2}}{}{% not empty
    \convertcolorspec{named}{TFFrameColor}{HTML}\LWR@tempcolor%
    \begin{BlockClass}[background: \LWR@origpound\LWR@tempcolor]{framedtitle}%
    \textcolor{TFTitleColor}{\textbf{#2}}%
    \end{BlockClass}
}% not empty
\end{BlockClass}
}
```

\TitleBarFrame [⟨*marker*⟩] {⟨*title*⟩} {⟨*contents*⟩}

```
\renewcommand\TitleBarFrame[3][]{
\CustomFBox
    {#2}{}%
    \fboxrule\fboxrule\fboxrule\fboxrule
    {#3}%
}

\renewcommand{\TF@Title}[1]{#1}
```

MakeFramed {⟨*settings*⟩}

```
\let\MakeFramed\relax
\let\endMakeFramed\relax

\NewEnviron{MakeFramed}[1]{%
\FrameCommand{\begin{minipage}{\linewidth}\BODY\end{minipage}}%
}
```

\fb@put@frame {⟨*frame cmd no split*⟩} {⟨*frame cmd split*⟩}

```
\renewcommand*{\fb@put@frame}[2]{%
\relax%
\@tempboxa%
}
```

File 156 **lwarp-ftcap.sty**

§ 254 Package ftcap

Pkg ftcap ftcap is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ftcap}
```

File 157 **lwarp-ftnright.sty**

§ 255 Package ftnright

Pkg ftnright ftnright is ignored.

for HTML output: Discard all options for lwarp-ftnright:

```
\LWR@ProvidesPackageDrop{ftnright}[2014/10/28]
```

File 158 **lwarp-fullminipage.sty**

§ 256 Package fullminipage

Pkg fullminipage fullminipage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullminipage}[2014/07/06]
\newenvironment{fullminipage}[1][]{}{}
```

File 159 **lwarp-fullpage.sty**

§ 257 Package fullpage

Pkg fullpage fullpage is ignored.

for HTML output: Discard all options for lwarp-fullpage:

```
\LWR@ProvidesPackageDrop{fullpage}[1994/06/01]
```

File 160 **lwarp-fullwidth.sty**

§ 258 Package fullwidth

(*Emulates or patches code by* Marco Daniel.)

Pkg fullwidth fullwidth is emulated.

A minipage is used, of no HTML width.

for HTML output:

```
\LWR@ProvidesPackageDrop{fullwidth}[2011/11/18]
\newenvironment*{fullwidth}[1][]{%
\minipagefullwidth%
\minipage{\linewidth}%
}
{%
\endminipage%
}
```

File 161 **lwarp-fwlw.sty**

§ 259 Package fwlw

Pkg fwlw fwlw is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{fwlw}

\newbox\FirstWordBox      \global\setbox\FirstWordBox\hbox{}
\newbox\NextWordBox       \global\setbox\NextWordBox\hbox{}
\newbox\LastWordBox       \global\setbox\LastWordBox\hbox{}
\def\ps@fwlwhead{}
\def\ps@NextWordFoot{}
```

File 162 **lwarp-gentombow.sty**

§ 260 Package gentombow

Pkg gentombow gentombow is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gentombow}[2018/05/17]

\newcommand{\settombowbanner}[1]{}
\newcommand{\settombowbannerfont}[1]{}
\newcommand{\settombowwidth}[1]{}
\newcommand{\settombowbleed}[1]{}
\newcommand{\settombowcolor}[1]{}
```

File 163 **lwarp-geometry.sty**

§ 261 Package geometry

(*Emulates or patches code by* Hideo Umeki.)

Pkg geometry geometry is preloaded by lwarp, but must be nullified as seen by the user's source code.

for HTML output: Discard all options for lwarp-geometry:

```
\LWR@ProvidesPackageDrop{geometry}[2018/04/16]

\renewcommand*{\geometry}[1]{}
\renewcommand*{\newgeometry}[1]{}
\renewcommand*{\restoregeometry}{}
\renewcommand*{\savegeometry}[1]{}
\renewcommand*{\loadgeometry}[1]{}
```

File 164 **lwarp-gloss.sty**

§ 262 Package

gloss

(*Emulates or patches code by* Jose Luis Díiaz, Javier Bezos.)

Pkg gloss

gloss is patched for use by lwarp.

To process the HTML glossary:

```
bibtex <projectname>_html.gls
```

for HTML output:

```
\LWR@ProvidesPackagePass{gloss}[2002/07/26]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\xpatchcmd{\gls@gloss@iii}
    {\thepage}
    {\theLWR@previousautopagelabel}
    {}
    {\LWR@patcherror{gloss}{gls@gloss@iii}}

\def\gls@page@i#1#2{%
  \endgroup%
  \global\@namedef{glsp@#1}{\nameref{\BaseJobname-autopage-#2}}}%
```

File 165 **lwarp-glossaries.sty**

§ 263 Package

glossaries

(*Emulates or patches code by* Nicola L.C. Talbot.)

Pkg glossaries

processing glossaries

lwarpmk has the commands `lwarpmk printglossary` and `lwarpmk htmlglossary`, which process the glossaries created by the glossaries package using that package's *makeglossaries* program.

Opt GlossaryCmd

Default: makeglossaries

Opt [lwarpmk] printglossary

Opt [lwarpmk] htmlglossary

The shell command to execute is set by the lwarp option `GlossaryCmd`, which defaults to **`makeglossaries`**. The print or HTML glossary filename is appended to this command.

⚠ *makeglossaries* not found

In some situations it may be required to modify the default command, such as to add the **`perl`** command in front:

```
\usepackage[
   GlossaryCmd={perl makeglossaries},
] {lwarp}
```

xindy language

To set the language to use for processing glossaries with *xindy*:

```
\usepackage[
   GlossaryCmd={makeglossaries -L english},
] {lwarp}
```

Other options for *makeglossaries* may be set as well.

placement and toc options

The glossaries may be placed in a numbered or unnumbered section, given a TOC entry, and placed inline or on their own HTML page:

Numbered section, on its own HTML page:

```
\usepackage[xindy,toc,numberedsection=nolabel]{glossaries}
. . .
\printglossaries
```

Unnumbered section, inline with the current HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\printglossaries
```

Unnumbered section, on its own HTML page:

```
\usepackage[xindy,toc]{glossaries}
. . .
\ForceHTMLPage
\printglossaries
```

⚠ glossary style

The default `style=item` option for glossaries conflicts with lwarp, so the style is forced to `index` instead.

⚠ number list

The page number list in the printed form would become `\namerefs` in HTML, which could become a very long string if many items are referenced. For now, the number list is simply turned off.

print/html versions

The print and HTML versions of the glossary differ in their internal page numbers. Separate commands for generating print and HTML glossaries are used, even though the page number is currently ignored.

for HTML output:

```
\PassOptionsToPackage{xindy}{glossaries}

\LWR@ProvidesPackagePass{glossaries}[2018/07/23]

\setupglossaries{nonumberlist}
\setglossarystyle{index}
```

Patched to fix TOC pointing to the previous page:

```
\renewcommand*{\@p@glossarysection}[2]{%
  \glsclearpage
  \phantomsection
  \ifdefempty\@@glossarysecstar
  {%
    \csname\@@glossarysec\endcsname{#2}%
  }%
  {%
```

In the original, the TOC entry was made before the section, thus linking to the phantomsection in the printed version, but for HTML, this caused the link to point to the page before the glossaries, which could be a different HTML file. Here, the TOC entry is made after the section is created:

```
      \csname\@@glossarysec\endcsname*{#2}%
    \@gls@toc{#1}{\@@glossarysec}% Moved after the previous line.
  }%
  \@@glossaryseclabel
}
```

lwarp's sectioning commands cannot handle robust macros when splitting HTML into named filenames. glossaries uses `\translate` in sectioning names, and `\translate` is robust and cannot be expanded. The following pre-expands the translations at this moment, making use of `\translatelet`.

```
\newcommand*{\LWR@comp@glossaryname}{\translate{Glossary}}

\ifdefstrequal{\glossaryname}{\LWR@comp@glossaryname}{
    \translatelet\LWR@translatetemp{Glossary}
    \edef\glossaryname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@acronymname}{\translate{Acronym}}

\ifdefstrequal{\acronymname}{\LWR@comp@acronymname}{
    \translatelet\LWR@translatetemp{Acronym}
    \edef\acronymname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glssymbolsgroupname}{\translate{Symbols (glossaries)}}

\ifdefstrequal{\glssymbolsgroupname}{\LWR@comp@glssymbolsgroupname}{
    \translatelet\LWR@translatetemp{Symbols (glossaries)}
    \edef\glssymbolsgroupname{\LWR@translatetemp}
}{}

\newcommand*{\LWR@comp@glsnumbersgroupname}{\translate{Numbers (glossaries)}}

\ifdefstrequal{\glsnumbersgroupname}{\LWR@comp@glsnumbersgroupname}{
    \translatelet\LWR@translatetemp{Numbers (glossaries)}
    \edef\glsnumbersgroupname{\LWR@translatetemp}
}{}
```

File 166 **lwarp-gmeometric.sty**

§ 264 Package

gmeometric

Pkg gmeometric gmeometric is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gmeometric}[2008/11/22]
```

File 167 **lwarp-graphics.sty**

§ 265 Package

graphics

(*Emulates or patches code by* D. P. Carlisle.)

Pkg graphics graphics is emulated.

for HTML output:

```
\LWR@ProvidesPackagePass{graphics}[2017/06/25]
```

§ 265.1 Graphics extensions

\DeclareGraphicsExtensions {⟨*list*⟩}

\AtBeginDocument allow svg files instead of pdf:

```
\AtBeginDocument{
\DeclareGraphicsExtensions{.svg,.SVG,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}
\DeclareGraphicsRule{.svg}{svg}{.svg}{}
\DeclareGraphicsRule{.SVG}{svg}{.SVG}{}
}
```

Inside a lateximage, allow pdf instead of svg:

```
\ifpdf
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
\else% \ifpdf
        \ifXeTeX
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \else
\appto\LWR@restoreorigformatting{%
\DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
}
        \fi
\fi
```

§ 265.2 Length conversions and graphics options

⚠ whitespace

A scaled image in LaTeX by default takes only as much space on the page as it requires, but HTML browsers use as much space as the original unscaled image would have taken, with the scaled image over- or under-flowing the area.

Used to store the user's selected dimensions and HTML class.

The class defaults to "inlineimage" unless changed by a `class=xyx` option.

```
\newlength{\LWR@igwidth}
\newlength{\LWR@igheight}
\newcommand*{\LWR@igwidthstyle}{}
\newcommand*{\LWR@igheightstyle}{}
\newcommand*{\LWR@igorigin}{}
\newcommand*{\LWR@igangle}{}
\newcommand*{\LWR@igxscale}{1}
\newcommand*{\LWR@igyscale}{1}
\newcommand*{\LWR@igclass}{inlineimage}
```

```
\newcommand*{\LWR@igalt}{(image)}
```

Set the actions of each of the key/value combinations for `\includegraphics`. Many are ignored.

If an optional width was given, set an HTML style:

```
\define@key{igraph}{width}{%
\setlength{\LWR@igwidth}{#1}%
\ifthenelse{\lengthtest{\LWR@igwidth > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igwidthstyle}{width:#1}}% yes px
    {}% not px
}{}% end of length > 0pt
}
```

If an optional height was given, set an HTML style:

```
\define@key{igraph}{height}{%
\setlength{\LWR@igheight}{#1}%
\ifthenelse{\lengthtest{\LWR@igheight > 0pt}}%
{%
```

Default to use the converted fixed length given:

```
    \renewcommand*{\LWR@igheightstyle}{%
    height:\LWR@printlength{\LWR@igheight} % extra space
    }%
```

If ex or em dimensions were given, use those instead:

```
    \IfEndWith{#1}{ex}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes ex
    {}% not ex
    \IfEndWith{#1}{em}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes em
    {}% not em
    \IfEndWith{#1}{\%}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes percent
    {}% not percent
    \IfEndWith{#1}{px}%
    {\renewcommand*{\LWR@igheightstyle}{height:#1}}% yes px
    {}% not px
}{}% end of length > 0pt
}
```

Handle origin key:

```
\define@key{igraph}{origin}[c]{%
    \renewcommand*{\LWR@igorigin}{#1}%
}
```

Handle angle key:

```
\define@key{igraph}{angle}{\renewcommand*{\LWR@igangle}{#1}}
```

Handle class key:

```
\define@key{igraph}{class}{\renewcommand*{\LWR@igclass}{#1}}
```

Handle alt key:

```
\define@key{igraph}{alt}{\renewcommand*{\LWR@igalt}{#1}}
```

It appears that graphicx does not have separate keys for `xscale` and `yscale`. `scale` adjusts both at the same time.

```
\define@key{igraph}{scale}{%
    \ifthenelse{\equal{#1}{1}}{}{%  must expand #1
        \PackageWarning{lwarp}{%
```

```
            It is recommended to use\MessageBreak
            [width=xx\protect\linewidth]\MessageBreak
            instead of [scale=yy],%
        }%
    }%
    \renewcommand*{\LWR@igxscale}{#1}%
    \renewcommand*{\LWR@igyscale}{#1}%
}
```

Numerous ignored keys:

```
\define@key{igraph}{bb}{}
\define@key{igraph}{bbllx}{}
\define@key{igraph}{bblly}{}
\define@key{igraph}{bburx}{}
\define@key{igraph}{bbury}{}
\define@key{igraph}{natwidth}{}
\define@key{igraph}{natheight}{}
\define@key{igraph}{hiresbb}[true]{}
\define@key{igraph}{viewport}{}
\define@key{igraph}{trim}{}
\define@key{igraph}{totalheight}{}
\define@key{igraph}{keepaspectratio}[true]{}
\define@key{igraph}{clip}[true]{}
\define@key{igraph}{draft}[true]{}
\define@key{igraph}{type}{}
\define@key{igraph}{ext}{}
\define@key{igraph}{read}{}
\define@key{igraph}{command}{}
```

New in v1.1a:

```
\define@key{igraph}{quite}{}
\define@key{igraph}{page}{}
\define@key{igraph}{pagebox}{}
\define@key{igraph}{interpolate}[true]{}
```

New in v1.1b:

```
\define@key{igraph}{decodearray}{}
```

§ 265.3 Printing HTML styles

`\LWR@rotstyle` {⟨*prefix*⟩} {⟨*degrees*⟩}

Prints the rotate style with the given prefix.

`prefix` is `-ms-` or `-webkit-` or nothing, and is used to generate three versions of the `transform:rotate` style.

```
\newcommand*{\LWR@rotstyle}[2]{%
 #1transform:rotate(-#2deg);
}
```

\LWR@scalestyle {⟨*prefix*⟩} {⟨*xscale*⟩} {⟨*yscale*⟩}

Prints the scale style with the given prefix.

prefix is -ms- or -webkit- or nothing, and is used to generate three versions of the transform:scale style.

```
\newcommand*{\LWR@scalestyle}[3]{%
 #1transform:scale(#2,#3);
}
```

§ 265.4 \includegraphics

Bool LWR@infloatrow Used to compute \linewidth.

```
\newbool{LWR@infloatrow}
\boolfalse{LWR@infloatrow}
```

\LWR@opacity For HTML, used only for \includegraphics.

\LWR@opacity may be set by the transparent package.

```
\def\LWR@opacity{1}
```

\LWR@imagesizebox Used to determine the actual image size if needed.

```
\newsavebox{\LWR@imagesizebox}
```

\LWR@HTML@Gin@setfile {⟨*w*⟩} {⟨*h*⟩} {⟨*filename*⟩} Sets the parsed filename for HTML output.

```
\newcommand*{\LWR@HTML@Gin@setfile}[3]{%
    \xdef\LWR@parsedfilename{#3}%
}
```

Key [Gin] class CSS class for the image.

Define the new class key for the print-mode version of \includegraphics, which is enabled inside a lateximage.

```
\AtBeginDocument{
\define@key{Gin}{class}{}
\define@key{Gin}{alt}{}
}
```

\LWR@replaceEPSSVG Usually, references to EPS files become SVG files, but if the epstopdf package is being used, it automatically converts EPS to PDF, and the following must NOT be done.

```
\AtBeginDocument{
\@ifpackageloaded{epstopdf}
{
    \newcommand*{\LWR@replaceEPSSVG}{}
```

```
}{%
    \newcommand*{\LWR@replaceEPSSVG}{%
        \StrSubstitute{\LWR@tempone}{.eps}{.svg}[\LWR@tempone]%
        \StrSubstitute{\LWR@tempone}{.EPS}{.SVG}[\LWR@tempone]%
    }
}%
}
```

\LWR@includegraphicsb * [⟨*2: options*⟩] [⟨*3: options*⟩] {⟨*4: filename*⟩}

graphics syntax is \includegraphics * [⟨*llx,lly*⟩] [⟨*urx,ury*⟩] {⟨*file*⟩}

graphicx syntax is \includegraphics [⟨*key values*⟩] {⟨*file*⟩}

If #3 is empty, only one optional argument was given, thus graphicx syntax.

If using \epsfig or \psfig from the epsfig package, #4 will be \LWR@epsfig@filename, which will have been set by the file or figure keys. Therefore, #4 must not be used until after the keys have been processed.

```
\NewDocumentCommand{\LWR@includegraphicsb}{s o o m}
{%
```

Start the image tag on a new line, allow PDF output word wrap:

```
\LWR@origtilde \LWR@orignewline%
```

Temporarily compute \linewidth, \textwidth, \textheight arguments with a 6x9 inch size until the next \endgroup.

```
\begingroup%
\ifthenelse{\cnttest{\value{LWR@minipagedepth}}{=}{0}}%
{%
    \ifbool{LWR@infloatrow}%
    {}
    {% not in a minipage or a floatrow:
        \setlength{\linewidth}{6in}%
        \setlength{\textwidth}{6in}%
        \setlength{\textheight}{9in}%
    }%
}{}%
```

For correct em sizing during the width and height conversions:

```
\large%
```

Reset some defaults, possibly will be changed below if options were given:

```
\setlength{\LWR@igwidth}{0pt}%
\setlength{\LWR@igheight}{0pt}%
\renewcommand*{\LWR@igwidthstyle}{}%
\renewcommand*{\LWR@igheightstyle}{}%
\renewcommand*{\LWR@igorigin}{}%
```

```
\renewcommand*{\LWR@igangle}{}%
\renewcommand*{\LWR@igxscale}{1}%
\renewcommand*{\LWR@igyscale}{1}%
\renewcommand*{\LWR@igclass}{inlineimage}%

\renewcommand*{\LWR@igalt}{(image)}%
```

If #3 is empty, only one optional argument was given, thus graphicx syntax:

```
\IfValueF{#3}{%
    \IfValueTF{#2}%
        {\setkeys{igraph}{#2}}%
        {\setkeys{igraph}{}}%
}%
```

Fully expand and detokenize the filename, changing the file extension to .svg if necessary.

```
\begingroup%
\LetLtxMacro\Gin@setfile\LWR@HTML@Gin@setfile%
\edef\LWR@tempone{#4}%
\StrSubstitute{\LWR@tempone}{.pdf}{.svg}[\LWR@tempone]%
\StrSubstitute{\LWR@tempone}{.PDF}{.SVG}[\LWR@tempone]%
\LWR@replaceEPSSVG%
\xdef\LWR@parsedfilename{\LWR@tempone}%
\Ginclude@graphics{\detokenize\expandafter{\LWR@tempone}}%
\endgroup%
\filename@parse{\LWR@parsedfilename}%
\LWR@traceinfo{LWR@parsedfilename is \LWR@parsedfilename}%
% \LWR@sanitize{\LWR@parsedfilename}%
```

If formatting for a word processor, find and set the actual image size, without rotation, using PDF instead of SVG to find the original bounding box:

```
\ifbool{FormatWP}{%
    \begingroup%
    \LWR@restoreorigformatting%
    \ifpdf%
    \appto\LWR@restoreorigformatting{%
   \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
    \else% \ifpdf
            \ifXeTeX%
    \appto\LWR@restoreorigformatting{%
   \DeclareGraphicsExtensions{.pdf,.PDF,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
            \else%
    \appto\LWR@restoreorigformatting{%
   \DeclareGraphicsExtensions{.eps,.EPS,.gif,.GIF,.png,.PNG,.jpg,.JPG,.jpeg,.JPEG}%
    }%
            \fi%
    \fi% \ifpdf
    \define@key{Gin}{angle}{}%
    \IfBooleanTF{#1}%
```

```
    {% starred
        \IfValueTF{#3}%
        {%
        \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*[#2][#3]{#4}}%
        }%
        {%
            \IfValueTF{#2}%
            {%
           \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*[#2]{#4}}%
            }{%
               \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics*{#4}}%
            }%
        }%
    }% starred
    {% not starred
        \IfValueTF{#3}%
        {%
        \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics[#2][#3]{#4}}%
        }%
        {%
            \IfValueTF{#2}%
            {%
            \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics[#2]{#4}}%
            }{%
                \global\sbox{\LWR@imagesizebox}{\LWR@origincludegraphics{#4}}%
            }%
        }%
    }% not starred
    \endgroup%
    \settowidth{\LWR@igwidth}{\usebox{\LWR@imagesizebox}}%
   \global\renewcommand*{\LWR@igwidthstyle}{width:\LWR@printlength{\LWR@igwidth}}%
    \settoheight{\LWR@igheight}{\usebox{\LWR@imagesizebox}}%
   \global\renewcommand*{\LWR@igheightstyle}{height:\LWR@printlength{\LWR@igheight}}%
}{}% FormatWP
```

Create the HTML reference with the graphicspath, filename, extension, alt tag, style, and class.

The \LWR@origtilde adds space between tags in case this is being done inside a \savebox where \newline has no effect.

```
\LWR@traceinfo{LWR@includegraphicsb: about to create href}%
\href{\LWR@parsedfilename}%
{% start of href
\LWR@traceinfo{LWR@includegraphicsb: about to LWR@htmltag}%
\LWR@htmltag{% start of image tags
img\LWR@indentHTML%
src="%

\detokenize\expandafter{\LWR@parsedfilename}%

"\LWR@indentHTML%
```

Only include a style tag if a width, height, angle, or scale was given:

```
\ifthenelse{
    \NOT\equal{\LWR@igwidthstyle}{} \OR
    \NOT\equal{\LWR@igheightstyle}{} \OR
    \NOT\equal{\LWR@igorigin}{} \OR
    \NOT\equal{\LWR@igangle}{} \OR
    \NOT\equal{\LWR@igxscale}{1} \OR
    \NOT\equal{\LWR@igyscale}{1}
}%
{%
    style="\LWR@indentHTML
    \ifthenelse{\NOT\equal{\LWR@igwidthstyle}{}}%
        {\LWR@igwidthstyle;\LWR@indentHTML}{}%
    \ifthenelse{\NOT\equal{\LWR@igheightstyle}{}}%
        {\LWR@igheightstyle;\LWR@indentHTML}{}%
    \ifthenelse{\NOT\equal{\LWR@igorigin}{}}%
        {%
            transform-origin: \LWR@originnames{\LWR@igorigin};\LWR@indentHTML%
        }{}%
    \ifthenelse{\NOT\equal{\LWR@igangle}{}}%
    {%
        \LWR@rotstyle{-ms-}{\LWR@igangle}\LWR@indentHTML
        \LWR@rotstyle{-webkit-}{\LWR@igangle}\LWR@indentHTML
        \LWR@rotstyle{}{\LWR@igangle }\LWR@indentHTML
    }{}%
    \ifthenelse{%
        \NOT\equal{\LWR@igxscale}{1}\OR%
        \NOT\equal{\LWR@igyscale}{1}%
    }%
    {%
        \LWR@scalestyle{-ms-}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
        \LWR@scalestyle{-webkit-}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
        \LWR@scalestyle{}{\LWR@igxscale}{\LWR@igyscale}\LWR@indentHTML
    }{}%
    %
    \ifthenelse{\NOT\equal{\LWR@opacity}{1}}%
        {opacity:\LWR@opacity;\LWR@indentHTML}{}%
    %
    "\LWR@indentHTML%
}{}%
```

Set the class and alt tag:

```
class="\LWR@igclass"\LWR@indentHTML%
alt="\LWR@igalt" \LWR@orignewline%
}% end of image tags
}% end of href
```

Return to original page size and font size:

```
\endgroup
\LWR@traceinfo{LWR@includegraphicsb done}%
}
```

\includegraphics [⟨*key=val*⟩] {⟨*filename*⟩}

Handles width and height, converted to fixed width and heights.

The user should always use no file suffix in the document source.

```
\AtBeginDocument{

\LWR@traceinfo{Patching includegraphics.}

\LetLtxMacro\LWR@originincludegraphics\includegraphics

\renewcommand*{\includegraphics}
{%
```

This graphic should trigger an HTML paragraph even if alone, so ensure that are doing paragraph handling:

```
\LWR@traceinfo{includegraphics}%
\LWR@ensuredoingapar%
\LWR@includegraphicsb%
}% includegraphics
}% AtBeginDocument
```

§ 265.5 Boxes

\LWR@rotboxorigin Holds the origin key letters.

```
\newcommand*{\LWR@rotboxorigin}{}
```

\LWR@originname {⟨*letter*⟩}

Given one LaTeX origin key value, translate into an HTML origin word:

```
\newcommand*{\LWR@originname}[1]{%
    \ifthenelse{\equal{#1}{t}}{top}{}%
    \ifthenelse{\equal{#1}{b}}{bottom}{}%
    \ifthenelse{\equal{#1}{c}}{center}{}%
    \ifthenelse{\equal{#1}{l}}{left}{}%
    \ifthenelse{\equal{#1}{r}}{right}{}%
}
```

\LWR@originnames {⟨*letters*⟩}

Given one- or two-letter LaTeX origin key values, translate into HTML origin words:

```
\newcommand*{\LWR@originnames}[1]{%
\StrChar{#1}{1}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
\StrChar{#1}{2}[\LWR@strresult]%
\LWR@originname{\LWR@strresult}
}
```

Handle the origin key for \rotatebox:

```
\define@key{krotbox}{origin}{%
\renewcommand*{\LWR@rotboxorigin}{#1}%
}
```

These keys are ignored:

```
\define@key{krotbox}{x}{}
\define@key{krotbox}{y}{}
\define@key{krotbox}{units}{}
```

\rotatebox [⟨*keyval list*⟩] {⟨*angle*⟩} {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@rotatebox}{O{} m +m}{%
```

Reset the origin to “none-given”:

```
\renewcommand*{\LWR@rotboxorigin}{}
```

Process the optional keys, which may set \LWR@rotateboxorigin:

```
\setkeys{krotbox}{#1}%
```

Select inline-block so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style="\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

If an origin was given, translate and print the origin information:

```
    \ifthenelse{\NOT\equal{\LWR@rotboxorigin}{}}%
      {transform-origin: \LWR@originnames{\LWR@rotboxorigin};\LWR@indentHTML}%
        {}%
```

Print the rotation information:

```
    \LWR@rotstyle{-ms-}{#2}\LWR@indentHTML
    \LWR@rotstyle{-webkit-}{#2}\LWR@indentHTML
    \LWR@rotstyle{}{#2}"\LWR@orignewline%
}\LWR@orignewline%
```

Print the text to be rotated:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{rotatebox}

}% AtBeginDocument
```

\scalebox {⟨*h-scale*⟩} [⟨*v-scale*⟩] {⟨*text*⟩}

```
\AtBeginDocument{
```

The HTML version:

```
\NewDocumentCommand{\LWR@HTML@scalebox}{m o m}{%
```

Select `inline-block` so that HTML will transform this span:

```
\LWR@htmltagc{%
    span\LWR@indentHTML
    style="\LWR@indentHTML
    display: inline-block;\LWR@indentHTML
```

Print the scaling information:

```
    \LWR@scalestyle{-ms-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{-webkit-}{#1}{\IfNoValueTF{#2}{#1}{#2}}\LWR@indentHTML
    \LWR@scalestyle{}{#1}{\IfNoValueTF{#2}{#1}{#2}}
    "\LWR@orignewline
}\LWR@orignewline%
```

Print the text to be scaled:

```
\begin{LWR@nestspan}%
#3%
```

Close the span:

```
\LWR@htmltagc{/span}%
\end{LWR@nestspan}%
}
```

The high-level interface:

```
\LWR@formatted{scalebox}

}% AtBeginDocument
```

\reflectbox {⟨*text*⟩}

```
\AtBeginDocument{

\newcommand{\LWR@HTML@reflectbox}[1]{%
\scalebox{-1}[1]{#1}%
}% \reflectbox

\LWR@formatted{reflectbox}

}% AtBeginDocument
```

\resizebox {⟨*h-length*⟩} {⟨*v-length*⟩} {⟨*text*⟩}

Simply prints its text argument.

```
\AtBeginDocument{

\NewDocumentCommand{\LWR@HTML@resizebox}{s m m m}{%
#4%
}

\LWR@formatted{resizebox}

}% AtBeginDocument
```

File 168 **lwarp-graphicx.sty**

§ 266 Package graphicx

Pkg graphicx graphicx is emulated.

graphicx loads graphics, which also loads lwarp-graphics, which remembers the original graphics definitions for use inside a lateximage, and then patches them \AtBeginDocument for HTML output.

lwarp-graphics handles the syntax of either graphics or graphicx.

for HTML output:

```
\LWR@ProvidesPackagePass{graphicx}[2017/06/01]
```

File 169 **lwarp-grffile.sty**

§ 267 Package grffile

Pkg grffile grffile is supported as-is. File types known to the browser are displayed, and unknown file types are given a link. Each PDF image for print mode should be accompanied by an SVG, PNG, or JPG version for HTML.

⚠ matching pdf and svg

lwarp-grffile now exists as a placeholder since grffile used to be emulated by lwarp, and thus older versions of lwarp-grffile may exist and should be overwritten by this newer version.

for HTML output:

```
\LWR@ProvidesPackagePass{grffile}[2017/06/30]
```

File 170 **lwarp-grid.sty**

§ 268 Package grid

Pkg grid grid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{grid}[2009/06/16]
\newenvironment*{gridenv}{}{}
```

File 171 **lwarp-grid-system.sty**

§ 269 Package grid-system

(*Emulates or patches code by* Marcus Bitzl.)

Pkg grid-system grid-system is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{grid-system}[2014/02/16]
```

(\ifdef is in case the older syntax is removed.)

```
\AtBeginEnvironment{Row}{\setlength{\linewidth}{6in}}

\ifdef{\endrow}{
    \AtBeginEnvironment{row}{\setlength{\linewidth}{6in}}
}{}

\renewcommand{\gridsystem@finishcell}{\hspace{\gridsystem@cellsep}}
```

File 172 **lwarp-gridset.sty**

§ 270 Package gridset

Pkg gridset gridset is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{gridset}
\newcommand*{\gridbase}{}
```

```
\newcommand*{\gridinterval}{}
\newcommand*{\savepos}[1]{}
\newcounter{gridcnt}
\newcommand*{\vskipnextgrid}{}
\newcommand*{\thegridinfo}[1]{}
\newcommand*{\theposinfo}[1]{}
\newcommand*{\theypos}[1]{}
```

File 173 **lwarp-hang.sty**

§ 271 Package hang

(*Emulates or patches code by* Andreas Nolda.)

Pkg hang hang is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hang}[2017/02/18]

\newlength{\hangingindent}
\setlength{\hangingindent}{1em}
\newlength{\hangingleftmargin}
\setlength{\hangingleftmargin}{0em}

\newcommand*{\LWR@findhangingleftmargin}{%
\setlength{\LWR@templengthone}{\hangingleftmargin}%
\addtolength{\LWR@templengthone}{\hangingindent}%
}

\newenvironment{hangingpar}
{
    \LWR@findhangingleftmargin%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}

\newenvironment{hanginglist}
{%
    \renewcommand*{\LWR@printcloselist}{\LWR@printcloseitemize}%
    \renewcommand*{\LWR@printopenlist}{%
        \LWR@findhangingleftmargin%
        ul style="%
            \LWR@print@mbox{list-style-type:none;} % extra space
            \LWR@print@mbox{%
                margin-left:\LWR@printlength{\LWR@templengthone}%
            } ; % extra space
            \LWR@print@mbox{%
                text-indent:-\LWR@printlength{\hangingindent}%
            }%
        "%
```

```
    }%
    \let\item\LWR@itemizeitem%
    \list{}{}%
}
{\endlist}

\newenvironment{compacthang}
{\hanginglist}
{\endhanginglist}

\newlength{\labeledleftmargin}
\setlength{\labeledleftmargin}{0em}

\newenvironment{labeledpar}[2]
{%
    \BlockClass[%
        \LWR@findhangingleftmargin%
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{\hangingindent}}%
    ]{labeledpar}#2%
}
{\endBlockClass}

\newenvironment{labeledlist}[1]
{\hanginglist}
{\endhanginglist}

\newenvironment{compactlabel}[1]
{\hanginglist}
{\endhanginglist}
```

File 174 **lwarp-hanging.sty**

§ 272 Package

hanging

Pkg hanging hanging is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{hanging}[2009/09/02]

\@ifclassloaded{memoir}{
\let\hangpara\relax
\let\hangparas\relax
\let\endhangparas\relax
\let\hangpunct\relax
\let\endhangpunct\relax
}{}
```

\hangpara {⟨*indent*⟩} {⟨*afternum*⟩}

Use hangparas instead.

```
\newcommand*{\hangpara}[2]{}
```

Env hangparas {⟨*indent*⟩} {⟨*afternum*⟩}

```
\newenvironment*{hangparas}[2]
{%
    \BlockClass[%
        \LWR@print@mbox{margin-left:\LWR@printlength{#1}} ; %
        \LWR@print@mbox{text-indent:-\LWR@printlength{#1}}%
    ]%
    {hangingpar}%
}
{\endBlockClass}
```

Env hangpunct

```
\newenvironment*{hangpunct}
{\BlockClass{hangpunct}}
{\endBlockClass}

\newcommand{\nhpt}{.}
\newcommand{\nhlq}{‘}
\newcommand{\nhrq}{’}
```

File 175 **lwarp-hypbmsec.sty**

§ 273 Package hypbmsec

Pkg hypbmsec hypbmsec is emulated by the lwarp core.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypbmsec}[2016/05/16]
```

File 176 **lwarp-hypcap.sty**

§ 274 Package hypcap

Pkg hypcap hypcap is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypcap}[2016/05/16]

\newcommand*{\capstart}{}
\newcommand*{\hypcapspace}{}
\newcommand*{\hypcapredef}[1]{}
\newcommand*{\capstartfalse}{}
\newcommand*{\capstarttrue}{}
```

File 177 **lwarp-hypdestopt.sty**

§ 275 Package hypdestopt

Pkg hypdestopt hypdestopt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypdestopt}[2016/05/21]
```

File 178 **lwarp-hypernat.sty**

§ 276 Package hypernat

Pkg hypernat hypernat is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{hypernat}[2001/07/09]
```

File 179 **lwarp-hyperref.sty**

§ 277 Package hyperref

(*Emulates or patches code by* Sebastian Rahtz, Heiko Oberdiek.)

Pkg hyperref hyperref is emulated.

for HTML output:

```
% \LWR@ProvidesPackageDrop{hyperref}% not allowed
% \ProvidesPackage{lwarp-#1-#2}% not allowed
\PackageInfo{lwarp}{%
Using the lwarp HTML version of package ‘hyperref’,\MessageBreak
and discarding options.\MessageBreak
(Not using \protect\ProvidesPackage, so that other packages\MessageBreak
do not attempt to patch lwarp’s version of ‘hyperref’.)\MessageBreak}

\DeclareOption*{}


% \ProcessOptions\relax
\let\ds@\@empty%         from the original \ProcessOptions
\edef\@curroptions{}%    lwarp modification to \ProcessOptions
\@process@ptions\relax%  from the original \ProcessOptions

\newcommand*{\hypersetup}[1]{}
\newcommand*{\hyperbaseurl}[1]{}
```

\hyperimage {⟨*URL*⟩} {⟨*alt text*⟩}

Insert an image with alt text:

```
\NewDocumentCommand{\LWR@hyperimageb}{m +m}{%
\LWR@ensuredoingapar%
\def\LWR@templink{#1}%
\@onelevel@sanitize\LWR@templink%
\LWR@htmltag{img src="\LWR@templink" alt="#2" class="hyperimage"}%
\LWR@ensuredoingapar%
\endgroup%
}

\newrobustcmd*{\hyperimage}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperimageb%
}

```

`\hyperdef` {⟨*1: category*⟩} {⟨*2: name*⟩} {⟨*3: text*⟩}

Creates an HTML anchor to `category.name` with the given text.

```
\NewDocumentCommand{\LWR@hyperdefb}{m m +m}{%
\LWR@ensuredoingapar%
\LWR@sublabel{#1.#2}%
#3%
\endgroup%
}

\newcommand*{\hyperdef}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperdefb%
}

```

`\LWR@hyperrefb` {⟨*1: URL*⟩} {⟨*2: category*⟩} {⟨*3: name*⟩} {⟨*4: text*⟩}

Creates an HTML link to `URL#category.name` with the given text.

```
\newcommand{\LWR@hyperreffinish}[1]{%
\begingroup%
\RenewDocumentCommand{\ref}{}{\LWR@ref@ignorestar}%
#1%
\endgroup%
\LWR@htmltag{/a}%
}

\newcommand*{\LWR@hyperrefbb}[3]{%
```

```
\LWR@htmltag{%
    a href="%
        \detokenize\expandafter{#1}\LWR@hashmark%
        \detokenize\expandafter{#2}.\detokenize\expandafter{#3}%
    "%
}%
\endgroup%
\LWR@hyperreffinish%
}

\newrobustcmd*{\LWR@hyperrefb}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperrefbb%
}
```

`\LWR@hyperrefc` `[`⟨*label*⟩`]` `{`⟨*text*⟩`}`

Creates text as an HTML link to the LaTeX label.

```
\NewDocumentCommand{\LWR@hyperrefcb}{O{label}}{%
\LWR@startref{#1}%
\endgroup%
\LWR@hyperreffinish%
}

\newcommand*{\LWR@hyperrefc}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperrefcb%
}
```

`\hyperref` `{`⟨*1: URL*⟩`}` `{`⟨*2: category*⟩`}` `{`⟨*3: name*⟩`}` `{`⟨*4: text*⟩`}` — or — `[`⟨*1: label*⟩`]` `{`⟨*2: text*⟩`}`

```
\DeclareRobustCommand*{\hyperref}{%
\LWR@ensuredoingapar%
\@ifnextchar[\LWR@hyperrefc\LWR@hyperrefb%
}
```

`\hypertarget` `{`⟨*name*⟩`}` `{`⟨*text*⟩`}`

Creates an anchor to `name` with the given text.

```
\NewDocumentCommand{\LWR@hypertargetb}{m +m}{%
\label{LWR-ht-#1}%
#2%
```

```
\endgroup%
}

\newcommand*{\hypertarget}{%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hypertargetb%
}
```

\hyperlink {⟨*name*⟩} {⟨*text*⟩}

Creates a link to the anchor created by hypertarget, with the given link text. Declared because also defined by memoir.

```
\DeclareDocumentCommand{\LWR@hyperlinkb}{m}{%
\LWR@hyperrefcb[LWR-ht-#1]%
}

\DeclareDocumentCommand{\hyperlink}{}{%
\LWR@ensuredoingapar%
\begingroup%
\catcode`\#=12%
\catcode`\%=12%
\catcode`\&=12%
\catcode`\~=12%
\catcode`\_=12%
\LWR@hyperlinkb%
}
```

\autoref * {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autoref}{s m}{%
    \IfBooleanTF{#1}{\ref{#2}}{\cref{#2}}%
}
```

\autopageref {⟨*label*⟩}

For HTML, \cleveref is used instead.

```
\NewDocumentCommand{\autopageref}{s m}{%
    \IfBooleanTF{#1}{\cpageref{#2}}{\cref{#2}}%
}
```

\pdfstringdef {⟨*macroname*⟩} {⟨*TEXstring*⟩}

```
\newcommand{\pdfstringdef}[2]{}
```

\pdfbookmark [⟨*level*⟩] {⟨*text*⟩} {⟨*name*⟩}

```
136 \newcommand{\pdfbookmark}[3][]{}
```

\currentpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
137 \newcommand{\currentpdfbookmark}[2]{}
```

\subpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
138 \newcommand{\subpdfbookmark}[2]{}
```

\belowpdfbookmark {⟨*text*⟩} {⟨*name*⟩}

```
139 \newcommand{\belowpdfbookmark}[2]{}
```

\texorpdfstring {⟨*TEXstring*⟩} {⟨*PDFstring*⟩}

```
140 \newcommand{\texorpdfstring}[2]{#1}
```

\hypercalcbp {⟨*dimen*⟩} From hyperref.

```
141 \def\hypercalcbp#1{%
142 \strip@pt\dimexpr 0.99626401\dimexpr(#1)\relax\relax
143 }%
```

\Acrobatmenu {⟨*menuoption*⟩} {⟨*text*⟩}

```
144 \newcommand{\Acrobatmenu}[2]{}
```

\TextField [⟨*parameters*⟩] {⟨*label*⟩}

```
145 \DeclareRobustCommand{\TextField}[2][]{}
```

\CheckBox [⟨*parameters*⟩] {⟨*label*⟩}

```
146 \DeclareRobustCommand{\CheckBox}[2][]{}
```

\ChoiceMenu [⟨*parameters*⟩] {⟨*label*⟩} {⟨*choices*⟩}

```
147 \DeclareRobustCommand{\ChoiceMenu}[3][]{}
```

\PushButton [⟨*parameters*⟩] {⟨*label*⟩}

```
148 \DeclareRobustCommand{\PushButton}[2][]{}
```

\Submit [⟨*parameters*⟩] {⟨*label*⟩}

```
149 \DeclareRobustCommand{\Submit}[2][]{}
```

\Reset [⟨*parameters*⟩] {⟨*label*⟩}

```
150 \DeclareRobustCommand{\Reset}[2][]{}
```

\Gauge [⟨*parameters*⟩] {⟨*label*⟩}

```
151 \DeclareRobustCommand{\Gauge}[2][]{}
```

\LayoutTextField {⟨*label*⟩} {⟨*field*⟩}

```
152 \newcommand*{\LayoutTextField}[2]{}
```

\LayoutChoiceField {⟨*label*⟩} {⟨*field*⟩}

```
153 \newcommand*{\LayoutChoiceField}[2]{}
```

\LayoutCheckField {⟨*label*⟩} {⟨*field*⟩}

```
154 \newcommand*{\LayoutCheckField}[2]{}
```

\MakeRadioField {⟨*width*⟩} {⟨*height*⟩}

```
155 \newcommand*{\MakeRadioField}[2]{}
```

\MakeCheckField {⟨*width*⟩} {⟨*height*⟩}

```
156 \newcommand*{\MakeCheckField}[2]{}
```

\MakeTextField {⟨*width*⟩} {⟨*height*⟩}

```
157 \newcommand*{\MakeTextField}[2]{}
```

\MakeChoiceField {⟨*width*⟩} {⟨*height*⟩}

```
158 \newcommand*{\MakeChoiceField}[2]{}
```

\MakeFieldButton {⟨*text*⟩}

```
159 \newcommand{\MakeFieldButton}[1]{}
```

File 180 **lwarp-hyperxmp.sty**

§ 278 Package

hyperxmp

Pkg hyperxmp hyperxmp is ignored.

for HTML output: Discard all options for lwarp-hyperxmp:

```
1 \LWR@ProvidesPackageDrop{hyperxmp}[2018/11/27]
```

File 181 **lwarp-hyphenat.sty**

§ 279 Package hyphenat

Pkg hyphenat hyphenat is emulated during HTML output, while the print-mode version is used inside a lateximage.

for HTML output:

```
\LWR@ProvidesPackagePass{hyphenat}[2009/09/02]

\LetLtxMacro\LWRHYNAT@origtextnhtt\textnhtt
\LetLtxMacro\LWRHYNAT@orignhttfamily\nhttfamily
\LetLtxMacro\LWRHYNAT@orignohyphens\nohyphens
\LetLtxMacro\LWRHYNAT@origbshyp\bshyp
\LetLtxMacro\LWRHYNAT@origfshyp\fshyp
\LetLtxMacro\LWRHYNAT@origdothyp\dothyp
\LetLtxMacro\LWRHYNAT@origcolonhyp\colonhyp
\LetLtxMacro\LWRHYNAT@orighyp\hyp

\LetLtxMacro\textnhtt\texttt
\LetLtxMacro\nhttfamily\ttfamily

\renewcommand{\nohyphens}[1]{#1}
\renewrobustcmd{\bshyp}{%
    \ifmmode\backslash\else\textbackslash\fi%
}
\renewrobustcmd{\fshyp}{/}
\renewrobustcmd{\dothyp}{.}
\renewrobustcmd{\colonhyp}{:}
\renewrobustcmd{\hyp}{-}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\textnhtt\LWRHYNAT@origtextnhtt%
\LetLtxMacro\nhttfamily\LWRHYNAT@orignhttfamily%
\LetLtxMacro\nohyphens\LWRHYNAT@orignohyphens%
\LetLtxMacro\bshyp\LWRHYNAT@origbshyp%
\LetLtxMacro\fshyp\LWRHYNAT@origfshyp%
\LetLtxMacro\dothyp\LWRHYNAT@origdothyp%
\LetLtxMacro\colonhyp\LWRHYNAT@origcolonhyp%
\LetLtxMacro\hyp\LWRHYNAT@orighyp%
}
```

File 182 **lwarp-idxlayout.sty**

§ 280 Package idxlayout

(*Emulates or patches code by* Thomas Titz.)

Pkg idxlayout idxlayout is emulated.

for HTML output: Discard all options for lwarp-idxlayout:

```
\LWR@ProvidesPackageDrop{idxlayout}[2012/03/30]

\newcommand{\LWR@indexprenote}{}

\preto\printindex{

\LWR@orignewpage
\LWR@startpars

\LWR@indexprenote

}

\newcommand{\setindexprenote}[1]{\renewcommand{\LWR@indexprenote}{#1}}
\newcommand*{\noindexprenote}{\renewcommand{\LWR@indexprenote}{}}

\newcommand{\idxlayout}[1]{}
\newcommand*{\indexfont}{}
\newcommand*{\indexjustific}{}
\newcommand*{\indexsubsdelim}{}
\newcommand*{\indexstheadcase}{}
```

File 183 **lwarp-ifoddpage.sty**

§ 281 Package ifoddpage

(*Emulates or patches code by* Martin Scharrer.)

Pkg ifoddpage ifoddpage is emulated.

for HTML output: Discard all options for lwarp-ifoddpage:

```
\LWR@ProvidesPackageDrop{ifoddpage}[2016/04/23]

\newif\ifoddpage

\newif\ifoddpageoroneside

\DeclareRobustCommand{\checkoddpage}{\oddpagetrue\oddpageoronesidetrue}

\def\oddpage@page{1}

\def\@ifoddpage{%
        \expandafter\@firstoftwo
}

\def\@ifoddpageoroneside{%
        \expandafter\@firstoftwo
}
```

File 184 **lwarp-imakeidx.sty**

§ 282 Package

imakeidx

(*Emulates or patches code by* Enrico Gregorio.)

Pkg imakeidx imakeidx is patched for use by lwarp.

letter headings When using *makeindex*, to match the print and HTML output's display of index letter headings, specify the `lwarp.ist` style:

```
\makeindex[options={-s lwarp.ist}]
```

(For HTML the `lwarp.ist` style is used automatically, which displays letter headings. When using *xindy* the default style also displays letter headings.)

index setup See section 8.6.17 for how to setup *lwarpmk* to process the indexes with imakeidx, both with and without shell escape.

for HTML output:

```
\LWR@ProvidesPackagePass{imakeidx}[2016/10/15]
```

Use the new HTML suffix:

```
\catcode`\_=12%
\define@key{imki}{name}{\def\imki@name{#1_html}}
\catcode`\_=8%
```

\printindex The HTML version of \printindex:

```
\catcode`\_=12%

\renewcommand*{\printindex}[1][\imki@jobname]{%
\LWR@orignewpage%
\LWR@startpars%
\ifstrequal{#1}{\imki@jobname}{%
  \@ifundefined{#1@idxfile}{%
        \imki@error{#1}%
    }{%
        \imki@putindex{#1}%
    }%
}{%
 \@ifundefined{#1_html@idxfile}{\imki@error{#1_html}}{\imki@putindex{#1_html}}%
}%
}

\catcode`\_=8%
```

\@index The HTML version of \index:

```
\catcode`\_=12%
```

```
\def\@index[#1]{%
    \ifstrequal{#1}{\imki@jobname}%
    {%
        \@ifundefined{#1@idxfile}%
        {%
            \PackageWarning{lwarp-imakeidx}{Undefined index file `#1'}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
    {%
        \@ifundefined{#1_html@idxfile}%
        {%
            \PackageWarning{lwarp-imakeidx}{Undefined index file `#1_html'}%
            \begingroup
            \@sanitize
            \imki@nowrindex%
        }%
        {%
            \edef\@idxfile{#1_html}%
            \begingroup
            \@sanitize
            \@wrindex\@idxfile%
        }%
    }%
}

\catcode`\_=8%
```

\item
\subitem
\subsubitem

HTML versions of \item, etc.:

```
\appto\theindex{%
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
```

\imki@wrindexentrysplit {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}
\imki@wrindexentryunique {⟨*file*⟩} {⟨*entry*⟩} {⟨*page*⟩}

While writing index entries, adds an HTML label, and writes the label's index instead of the page number:

```
\renewcommand\imki@wrindexentrysplit[3]{%
```

```
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
  \expandafter\protected@write\csname#1@idxfile\endcsname{}%
    {\string\indexentry{#2}{\arabic{LWR@autoindex}}}%
}

\renewcommand\imki@wrindexentryunique[3]{%
\addtocounter{LWR@autoindex}{1}%
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
  \protected@write\@indexfile{}%
    {\string\indexentry[#1]{#2}{\arabic{LWR@autoindex}}}%
}

\def\imki@wrindexsplit#1#2{%
\imki@wrindexentrysplit{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
}

\def\imki@wrindexunique#1#2{%
\imki@wrindexentryunique{#1}{#2}{\thepage}%
\endgroup\imki@showidxentry{#1}{#2}%
  \@esphack%
  }

```

`\LWR@imki@setxdydefopts`

Sets the xindy HTML options, ignoring the user's settings.

```
\newcommand*{\LWR@imki@setxdydefopts}{%
    \edef\imki@options{ \space %
        -M \space \LWR@xindyStyle\space %
        -L \space \LWR@xindyLanguage\space %
        -C \space \LWR@xindyCodepage\space %
    }%
}
```

`\LWR@imki@setdefopts` {⟨*user options*⟩}

Sets the HTML options, added to the user's settings, depending on whether makeindex or xindy are used.

For *makeindex*, the user's choice is ignored, and only the lwarp version is used. (Only one style at a time is possible.)

For *xindy*, multiple modules may be specified, and the lwarp version is appended.

```
\newcommand*{\LWR@imki@setdefopts}[1]{%
\ifblank{#1}{%
    \edef\imki@options{\space -s \space \LWR@makeindexStyle \space}%
    \ifdefstring{\imki@progdefault}{xindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{texindy}{\LWR@imki@setxdydefopts}{}%
    \ifdefstring{\imki@progdefault}{truexindy}{\LWR@imki@setxdydefopts}{}%
}{%
    \edef\imki@options{\space #1 \space}%
}%
```

```
}
```

\imki@makeindex Use the new HTML options:

```
\xpatchcmd{\imki@makeindex}
    {\let\imki@options\space}
    {\LWR@imki@setdefopts{}}%
    {}
    {\LWR@patcherror{imakeidx}{makeindex}}
```

Use the new HTML options.

```
\define@key{imki}{options}{\LWR@imki@setdefopts{#1}}
```

\imki@resetdefaults Use the new HTML options:

```
\xpatchcmd{\imki@resetdefaults}
    {\def\imki@options{ }}
    {\LWR@imki@setdefopts{}}
    {}
    {\LWR@patcherror{imakeidx}{resetdefaults}}
```

theindex was already defined \AtBeginDocument by the lwarp core, so it must be redefined here similarly, but patched for imakeidx:

Env theindex

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \imki@maybeaddtotoc
     \imki@indexlevel{\indexname}
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Update to the new defaults:

```
\imki@resetdefaults
```

Update to the new patches:

\AtBeginDocument is because \@wrindex is previously defined as \AtBeginDocument in the lwarp core.

```
\ifimki@splitindex
  \let\imki@startidx\imki@startidxunique
  \AtBeginDocument{\let\@wrindex\imki@wrindexunique}
  \let\imki@putindex\imki@putindexunique
  \let\imki@wrindexentry\imki@wrindexentryunique
  \let\imki@startidxsplit\@undefined
  \let\imki@wrindexsplit\@undefined
  \let\imki@putindexsplit\@undefined
\else
```

```
\let\imki@startidx\imki@startidxsplit
\AtBeginDocument{\let\@wrindex\imki@wrindexsplit}
\let\imki@putindex\imki@putindexsplit
\let\imki@wrindexentry\imki@wrindexentrysplit
\let\imki@startidxunique\@undefined
\let\imki@wrindexunique\@undefined
\let\imki@putindexunique\@undefined
\fi
```

File 185 **lwarp-index.sty**

§ 283 Package

index

(*Emulates or patches code by* David M. Jones.)

Pkg index index is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{index}[2004/01/20]
```

Use \theLWR@autoindex instead of \thepage. \@tempswatrue is used to force an immediate write to the index file instead of waiting until the end of the page.

```
\xpatchcmd{\newindex}
    {\x@newindex[thepage]}
    {%
        \@tempswatrue%
        \x@newindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{newindex}}

\xpatchcmd{\renewindex}
    {\x@renewindex[thepage]}
    {%
        \@tempswatrue%
        \x@renewindex[theLWR@autoindex]%
    }
    {}
    {\LWR@patcherror{index}{renewindex}}
```

Patched to set a new autoindex:

```
\xpatchcmd{\@wrindex}
    {\begingroup}
    {%
        \addtocounter{LWR@autoindex}{1}%                    lwarp
        \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
        \begingroup%
    }
    {}
    {\LWR@patcherror{index}{@wrindex}}
```

`\AtBeginDocument` lwarp core `\lets` `\@wrindex` to `\LWR@wrindex`. Since the index package has been loaded, `\let` to its version instead:

```
\let\LWR@index@wrindex\@wrindex

\AtBeginDocument{
\let\@wrindex\LWR@index@wrindex
}
```

Modified to add `\index@prologue`:

```
\AtBeginDocument{
\renewenvironment*{theindex}{%
    \LWR@indexsection{\indexname}%
    \ifx\index@prologue\@empty\else
        \index@prologue
        \bigskip
    \fi
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}{}
}% AtBeginDocument
```

Disabled:

```
\def\@showidx#1{}
\let\@texttop\relax
\renewcommand*{\raggedbottom}{}
\renewcommand*{\flushbottom}{}
\renewcommand*{\markboth}[2]{}
\renewcommand*{\markright}[1]{}
```

File 186 **lwarp-inputtrc.sty**

§ 284 Package

inputtrc

(*Emulates or patches code by* Uwe Lück.)

Pkg inputtrc inputtrc is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{inputtrc}[2012/10/10]
```

Patched to remove extraneous spaces, which sometimes showed up in logos inside a `lateximage`.

```
\renewcommand*{\IT@prim@input}[1]{%
  \typeout{\IT@indent\IT@currfile INPUTTING #1}%
%% ... TODO: option to write to '.log' only.
  \xdef\IT@filestack{{\IT@currfile}\IT@filestack}%
  \xdef\IT@currfile{#1}%
  \expandafter \gdef\expandafter \IT@indent\expandafter{%
```

```
    \IT@indent \IT@indent@unit}%                lwarp
  \@@input#1%                                   lwarp
  \expandafter\IT@pop@indent\IT@indent   \@nil% lwarp
  \expandafter\IT@pop@file  \IT@filestack\@nil% lwarp
  \IT@maybe@returnmessage%% v0.2                lwarp
}
```

File 187 **lwarp-intopdf.sty**

§ 285 Package intopdf

Pkg intopdf intopdf is emulated.

The MIME type and description are ignored for now.

for HTML output:

```
\LWR@ProvidesPackageDrop{intopdf}[2018/03/15]
```

```
\NewDocumentCommand{\attachandlink}{m o m m}{%
    \href{#1}{#4}%
}
```

File 188 **lwarp-karnaugh-map.sty**

§ 286 Package karnaugh-map

(*Emulates or patches code by* Mattias Jacobsson.)

Pkg karnaugh-map karnaugh-map is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{karnaugh-map}[2017/02/20]
```

(It is hard to patch this macro, so the entire thing is redefined here, with the lwarp modificaitions identified in comments.)

```
\RenewDocumentEnvironment{karnaugh-map}{s O{4} O{4} O{1} O{$X_1X_0$} O{$X_3X_2$} O{$X_5X_4$}} {%
  \begingroup
    % store map size {[START]
      \renewcommand{\@karnaughmap@var@mapsizex@}{#2}%
      \renewcommand{\@karnaughmap@var@mapsizey@}{#3}%
      \renewcommand{\@karnaughmap@var@mapsizez@}{#4}%
    % [END]}
    % determinate if markings should be color or black and white
    \IfBooleanTF{#1}{%
      % should be black and white
      \renewcommand{\@karnaughmap@var@bw@}{1}%
    }{%
      % should be color
      \renewcommand{\@karnaughmap@var@bw@}{0}%
    }%
```

```
%
% find matching matrix template and alignment parameters {[START]
\newcommand{\@karnaughmap@local@matrixtemplate@}{0}% '0' is considered as missing matrix template
  \newcommand{\@karnaughmap@local@maprealignmentx@}{0}%
  \newcommand{\@karnaughmap@local@maprealignmenty@}{0}%
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=221
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
              \&                 0 \&                  1 \& \phantom{0} \\
         0 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&         \\
         1 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&         \\
    \phantom{0}  \&                   \&                   \&          \\
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=241
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
               \&                 0 \&                  1 \& \phantom{00} \\
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \&         \\
         01 \& |(000010)| \phantom{0} \& |(000011)| \phantom{0} \&         \\
         11 \& |(000110)| \phantom{0} \& |(000111)| \phantom{0} \&         \\
         10 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \&         \\
    \phantom{00} \&                   \&                   \&          \\
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=421
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
            \&              00 \&              01 \&              11 \&              10 \& \phanto
         0  \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(00001
         1  \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(00011
   \phantom{00} \&                \&                \&                \&                \&
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=441
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
            \&              00 \&              01 \&              11 \&              10 \& \phanto
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
   \phantom{00} \&                \&                \&                \&                \&
    }%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=442
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
            \&              00 \&              01 \&              11 \&              10 \& \phanto
         00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
         01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
         11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
         10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
   \phantom{00} \&                \&                \&                \&                \&
    }%
    \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
  \fi
\ifnum\@karnaughmap@var@mapsizex@\@karnaughmap@var@mapsizey@\@karnaughmap@var@mapsizez@=444
    \renewcommand{\@karnaughmap@local@matrixtemplate@}{%
            \&              00 \&              01 \&              11 \&              10 \& \phanto
```

```
            00 \& |(000000)| \phantom{0} \& |(000001)| \phantom{0} \& |(000011)| \phantom{0} \& |(0000
            01 \& |(000100)| \phantom{0} \& |(000101)| \phantom{0} \& |(000111)| \phantom{0} \& |(0001
            11 \& |(001100)| \phantom{0} \& |(001101)| \phantom{0} \& |(001111)| \phantom{0} \& |(0011
            10 \& |(001000)| \phantom{0} \& |(001001)| \phantom{0} \& |(001011)| \phantom{0} \& |(0010
     \phantom{00} \&                \&                \&                \&                \&
            00 \& |(100000)| \phantom{0} \& |(100001)| \phantom{0} \& |(100011)| \phantom{0} \& |(1000
            01 \& |(100100)| \phantom{0} \& |(100101)| \phantom{0} \& |(100111)| \phantom{0} \& |(1001
            11 \& |(101100)| \phantom{0} \& |(101101)| \phantom{0} \& |(101111)| \phantom{0} \& |(1011
            10 \& |(101000)| \phantom{0} \& |(101001)| \phantom{0} \& |(101011)| \phantom{0} \& |(1010
     \phantom{00} \&                \&                \&                \&                \&
      }%
      \renewcommand{\@karnaughmap@local@maprealignmentx@}{2.5}%
      \renewcommand{\@karnaughmap@local@maprealignmenty@}{-2.5}%
    \fi
  % [END]}
 % test if a matrix template is found or not(aka "\@karnaughmap@local@matrixtemplate@" equals to '0')
  \ifdefstring{\@karnaughmap@local@matrixtemplate@}{0}{%  lwarp
%   \ifnum0=\@karnaughmap@local@matrixtemplate@%  original
    % print error if no template could be found
    \PackageError{lwarp-karnaugh-map}{%
     Can not find a template fitting your specification (\@karnaughmap@var@mapsizex@\space x \@karnaughma
    }{%
     Existing templates have the following dimensions: 2x2x1, 2x4x1, 4x2x1, 4x4x1, 4x4x2, and 4x4x4.
    }%
%   \fi   original
  }{}%    lwarp
  \begin{tikzpicture}
    % grid
    % for all dimensions
  \draw[color=black, ultra thin] (0,0) grid (\@karnaughmap@var@mapsizex@,\@karnaughmap@var@mapsizey@);
    % when there are 2 sub maps
    \ifnum\@karnaughmap@var@mapsizez@=2
      \draw[color=black, ultra thin] (5,0) grid (9,4);
    \fi
    % when there are 4 sub maps
    \ifnum\@karnaughmap@var@mapsizez@=4
      \draw[color=black, ultra thin] (5,0) grid (9,4);
      \draw[color=black, ultra thin] (0,-5) grid (4,-1);
      \draw[color=black, ultra thin] (5,-5) grid (9,-1);
    \fi
    % labels
    % for all dimensions
  \node[above] at (\@karnaughmap@var@mapsizex@*0.5,\@karnaughmap@var@mapsizey@+0.9) {\small{#5}};
    \node[left] at (-0.9,\@karnaughmap@var@mapsizey@*0.5) {\small{#6}};
    % when there are 2 sub maps
    \ifnum\@karnaughmap@var@mapsizez@=2
      \node[above] at (7,4.9) {\small{#5}};
      % extra sub maps labels
      \node[below] at (2,-0.1) {\small{#7$=0$}};
      \node[below] at (7,-0.1) {\small{#7$=1$}};
    \fi
    % when there are 4 sub maps
    \ifnum\@karnaughmap@var@mapsizez@=4
      \node[above] at (7,4.9) {\small{#5}};
      \node[left] at (-0.9,-3) {\small{#6}};
```

```
        % extra sub maps labels
        \node[below] at (2,-0.1) {\small{#7$=00$}};
        \node[below] at (7,-0.1) {\small{#7$=01$}};
        \node[below] at (2,-5.1) {\small{#7$=10$}};
        \node[below] at (7,-5.1) {\small{#7$=11$}};
      \fi
      % data
      \matrix[
        matrix of nodes,
        ampersand replacement=\&,
        column sep={1cm,between origins},
        row sep={1cm,between origins},
    ] at (\@karnaughmap@var@mapsizex@*0.5+\@karnaughmap@local@maprealignmentx@,\@karnaughmap@var@mapsiz
        \@karnaughmap@local@matrixtemplate@%
      };
}{
    \end{tikzpicture}
  \endgroup
}
```

File 189 **lwarp-keyfloat.sty**

§ 287 Package keyfloat

(*Emulates or patches code by* Brian Dunn.)

Pkg keyfloat keyfloat is supported with a considerable amount of hacking. (It's a mashup of lwarp, keyfloat, and tocdata.)

⚠ keywrap If placing a `\keyfig[H]` inside a keywrap, use an absolute width for `\keyfig`, instead of `lw`-proportional widths. (The `[H]` option forces the use of a minipage, which internally adjusts for a virtual 6-inch wide minipage, which then corrupts the `lw` option.)

for HTML output:

```
\LWR@ProvidesPackagePass{keyfloat}[2019/03/21]

\@ifpackagelater{keyfloat}{2019/03/21}{}{
    \PackageError{lwarp-keyfloat}
    {%
        The keyfloat package is out of date.\MessageBreak
        Update to keyfloat v2.00 2019/03/21 or later%
    }
    {%
        Please update the keyfloat package.  It's worth it!%
    }
}
```

After keyfloat has loaded:

```
\AtBeginDocument{

\providecommand*{\KFLT@LWR@hook@boxouter}{}
```

```
\renewcommand*{\KFLT@LWR@hook@boxouter}{%
    \ifbool{KFLT@keywrap}{}{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
}

\let\KFLT@LWR@hook@boxouter@minipage\relax
\let\endKFLT@LWR@hook@boxouter@minipage\relax
\newenvironment*{KFLT@LWR@hook@boxouter@minipage}[2][]{}{}

\providecommand*{\KFLT@LWR@hook@keysubfloats}{}
\renewcommand*{\KFLT@LWR@hook@keysubfloats}{%
    \ifbool{KFLT@keywrap}{}{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
}

\let\KFLT@LWR@hook@keyfloatsminipage\relax
\let\endKFLT@LWR@hook@keyfloatsminipage\relax
\newenvironment*{KFLT@LWR@hook@keyfloatsminipage}[1]{}{}

\providecommand*{\KFLT@LWR@hook@keyfloats}{}
\renewcommand*{\KFLT@LWR@hook@keyfloats}{%
    \ifbool{KFLT@keywrap}{}{%
        \ifnumequal{\value{KFLT@keyfloatdepth}}{0}{%
            \setlength{\linewidth}{6in}%
            \setlength{\textwidth}{6in}%
            \setlength{\textheight}{9in}%
        }{}%
    }%
}

\renewcommand*{\KFLT@maybeendfloatrow}{%
    \ifnumless{\value{KFLT@thiscol}}{\value{KFLT@numcols}}%
    {}% thiscol < numcols
    {% >=
        \defcounter{KFLT@thiscol}{0}%
    }%
}%

\renewcommand{\KFLT@trackrows}%
{%
```

If are nested inside a keyfloats or a subfloat:

```
    \ifboolexpr{%
        test {\ifnumgreater{\value{KFLT@keyfloatdepth}}{0}} or%
```

```
        bool{KFLT@inkeysubfloats}%
    }%
    {% nested
```

Tracks row start and end:

```
        \KFLT@maybestartfloatrow%
```

Possibly fill space between columns:

```
        \ifnumgreater{\value{KFLT@thiscol}}{1}%
            {%
%                   \hfill%
            }%
            {}%
    }% nested
    {}% not nested
}

\RenewDocumentCommand{\KFLT@onefigureimage}{m}
{%
\LWR@traceinfo{KFLT@onefigureimage}%
% \begin{lrbox}{\KFLT@envbox}%
\ifthenelse{\NOT\equal{\KFLT@lw}{}}%
    {%
        \KFLT@frame{\includegraphics%
        [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
    }%
    {% not linewidth
        \ifthenelse{\dimtest{\KFLT@w}{>}{0pt}}%
        {% width is given
            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
            {% w and h
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,%
                width=\KFLT@imagewidth,height=\KFLT@h]{#1}}%
            }% w and h
            {% only w
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,width=\KFLT@imagewidth]{#1}}%
            }% only w
        }% width is given
        {% width is not given
            \ifthenelse{\dimtest{\KFLT@h}{>}{0pt}}%
            {%
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s,height=\KFLT@h]{#1}}%
            }%
            {%
                \KFLT@frame{\includegraphics%
                [scale=\KFLT@s]{#1}}%
            }%
        }% width is not given
    }% not linewidth
% \end{lrbox}%
```

```
% \unskip%
% \KFLT@findenvboxwidth%
% \begin{turn}{\KFLT@r}%
% \KFLT@frame{\usebox{\KFLT@envbox}}%
% \unskip%
% \end{turn}%
\LWR@traceinfo{KFLT@onefigureimage: done}%
}

\RenewDocumentEnvironment{KFLT@boxinner}{}
{%
    \LWR@traceinfo{KFLT@boxinner}%
    \LWR@stoppars%
    \minipagefullwidth%
    \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{
        \fminipage{\KFLT@imagewidth}%
    }{%
        \minipage{\KFLT@imagewidth}%
    }%
}
{%
    \ifboolexpr{bool{KFLT@ft} or bool{KFLT@f}}{
        \endfminipage%
    }{%
        \endminipage%
    }%
    \LWR@startpars%
    \LWR@traceinfo{KFLT@boxinner: done}%
}

\newcommand*{\LWR@KFLT@settextalign}[1]{%
    \def\LWR@KFLT@textalign{justify}%
    \ifcsstring{KFLT@#1textalign}{\centering}%
        {\def\LWR@KFLT@textalign{center}}%
        {}%
    \ifcsstring{KFLT@#1textalign}{\raggedleft}%
        {\def\LWR@KFLT@textalign{right}}%
        {}%
    \ifcsstring{KFLT@#1textalign}{\raggedright}%
        {\def\LWR@KFLT@textalign{left}}%
        {}%
}

\renewcommand{\KFLT@addtext}[1]
{%
```

Is there text to add?

```
    \ifcsempty{KFLT@#1t}%
    {}% no text
    {% text to add
        {% local
```

Add some space, then create a full-width minipage to contain the text:

```
        \addvspace{\smallskipamount}%
        \LWR@KFLT@settextalign{#1}%
        \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%
```

Set the alignment and some text parameters:

```
% 	  \csuse{KFLT@#1textalign}%
% 	  \footnotesize%
        \setlength{\parskip}{1.5ex}%
        \setlength{\parindent}{0em}%
```

Typeset the actual text:

```
        \csuse{KFLT@#1t}%
```

Close it all out with a little more space:

```
        \end{BlockClass}%
% 	  \par\addvspace{2ex}%
        }% local
    }% text to add
}

\@ifpackageloaded{tocdata}
{}
{% tocdata not loaded

    \newcommand*{\LWR@KFLT@setnamealign}[1]{%
        \def\LWR@KFLT@textalign{justify}%
        \ifstrequal{#1}{\centering}%
            {\def\LWR@KFLT@textalign{center}}%
            {}%
        \ifstrequal{#1}{\raggedleft}%
            {\def\LWR@KFLT@textalign{right}}%
            {}%
        \ifstrequal{#1}{\raggedright}%
            {\def\LWR@KFLT@textalign{left}}%
            {}%
    }

    \renewcommand*{\KFLT@@addartisttext}[3]{%

```

Add space and create the name inside a full-width minipage:

```
% 	  \addvspace{\medskipamount}%
    %     \begin{minipage}{\linewidth}%
        \LWR@KFLT@setnamealign{#3}%
        \begin{BlockClass}[text-align:\LWR@KFLT@textalign]{floatnotes}%

```

Text alignment is #3, and depends on artist or author:

```
    %     #3%

```

#1 is empty or 'subgrp'
#2 is empty for artist, 'u' for author:

```
        \footnotesize\textsc{%
            \KFLT@optionalname{\csuse{KFLT@#1a#2p}}%
            \KFLT@optionalname{\csuse{KFLT@#1a#2f}}%
            \csuse{KFLT@#1a#2l}%
            \csuse{KFLT@#1a#2s}%
        }%
    %     \end{minipage}%
        \end{BlockClass}
%         \par\addvspace{2ex}%
    }

}% tocdata not loaded

\DeclareDocumentEnvironment{KFLT@marginfloat}{O{-1.2ex} m}
{%
    \LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
    \captionsetup{type=#2}%
    \minipage{2in}%
}
{%
    \endminipage%
    \endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
    {\begin{KFLT@marginfloat}{figure}}
    {\end{KFLT@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
    {\begin{KFLT@marginfloat}{table}}
    {\end{KFLT@marginfloat}}

\DeclareDocumentEnvironment{keywrap}{m +m}
{%
    \LWR@ensuredoingapar%
    \setlength{\linewidth}{6in}%
    \setlength{\LWR@templengthone}{#1}%
    \begin{LWR@BlockClassWP}%
        {%
         float:right; width:\LWR@printlength{\LWR@templengthone};  % extra space
            margin:10pt%
        }%
        {%
            width:\LWR@printlength{\LWR@templengthone}%
        }%
        {marginblock}%
    \setlength{\linewidth}{.95\LWR@templengthone}%
    \booltrue{KFLT@keywrap}%
    #2%
    \end{LWR@BlockClassWP}%
}
{}
```

```
}% AtBeginDocument
```

File 190 **lwarp-layaureo.sty**

§ 288 Package layaureo

Pkg layaureo layaureo is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{layaureo}[2004/09/16]
```

File 191 **lwarp-layout.sty**

§ 289 Package layout

Pkg layout layout is ignored.

for HTML output: Discard all options for lwarp-layout:

```
\LWR@ProvidesPackageDrop{layout}[2014/10/28]
\NewDocumentCommand{\layout}{s}{}
```

File 192 **lwarp-layouts.sty**

§ 290 Package layouts

Pkg layouts layouts is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{layouts}[2009/09/02]
\newif\ifoddpagelayout
  \oddpagelayouttrue
\newif\iftwocolumnlayout
  \twocolumnlayoutfalse
\newif\ifdrawmarginpars
  \drawmarginparstrue
\newif\ifdrawparameters
  \drawparameterstrue
\newif\iflistaspara
  \listasparatrue
\newif\ifruninhead
  \runinheadfalse
\newif\ifprintparameters
  \printparameterstrue
\newif\ifdrawdimensions
  \drawdimensionsfalse
```

```
\newif\ifprintheadings
  \printheadingstrue
\newcommand{\testdrawdimensions}{}
\newcommand{\testprintparameters}{}
\newcommand{\setlabelfont}[1]{}
\newcommand{\setparametertextfont}[1]{}
\newcommand{\setvaluestextsize}[1]{}
\newcommand{\setlayoutscale}[1]{}
\newcommand{\setuplayouts}{}
\newcommand{\printinunitsof}[1]{}
\newcommand{\prntlen}[1]{}
\newcommand{\trypaperwidth}[1]{}
\newcommand{\trypaperheight}[1]{}
\newcommand{\tryhoffset}[1]{}
\newcommand{\tryvoffset}[1]{}
\newcommand{\trytopmargin}[1]{}
\newcommand{\tryheadheight}[1]{}
\newcommand{\tryheadsep}[1]{}
\newcommand{\trytextheight}[1]{}
\newcommand{\tryfootskip}[1]{}
\newcommand{\tryoddsidemargin}[1]{}
\newcommand{\tryevensidemargin}[1]{}
\newcommand{\trytextwidth}[1]{}
\newcommand{\trymarginparsep}[1]{}
\newcommand{\trymarginparwidth}[1]{}
\newcommand{\trymarginparpush}[1]{}
\newcommand{\trycolumnsep}[1]{}
\newcommand{\trycolumnseprule}[1]{}
\newcommand{\setfootbox}[2]{}
\newcommand{\currentpage}{}
\newcommand{\drawpage}{(draw page)}
\newcommand{\pagediagram}{(page diagram)}
\newcommand{\pagedesign}{(page design)}
\newcommand{\pagevalues}{(page values)}
\newcommand{\trystockwidth}[1]{}
\newcommand{\trystockheight}[1]{}
\newcommand{\trytrimedge}[1]{}
\newcommand{\trytrimtop}[1]{}
\newcommand{\tryuppermargin}[1]{}
\newcommand{\tryspinemargin}[1]{}
\newcommand{\currentstock}{}
\newcommand{\drawstock}{(draw stock)}
\newcommand{\stockdiagram}{(stock diagram)}
\newcommand{\stockdesign}{(stock design)}
\newcommand{\stockvalues}{(stock values)}
\newcommand{\tryitemindent}[1]{}
\newcommand{\trylabelwidth}[1]{}
\newcommand{\trylabelsep}[1]{}
\newcommand{\tryleftmargin}[1]{}
\newcommand{\tryrightmargin}[1]{}
\newcommand{\trylistparindent}[1]{}
\newcommand{\trytopsep}[1]{}
\newcommand{\tryparskip}[1]{}
\newcommand{\trypartopsep}[1]{}
\newcommand{\tryparsep}[1]{}
```

```
\newcommand{\tryitemsep}[1]{}
\newcommand{\currentlist}{}
\newcommand{\drawlist}{(draw list)}
\newcommand{\listdiagram}{(list diagram)}
\newcommand{\listdesign}{(list design)}
\newcommand{\listvalues}{(list values)}
\newcommand{\tryfootins}[1]{}
\newcommand{\tryfootnotesep}[1]{}
\newcommand{\tryfootnotebaseline}[1]{}
\newcommand{\tryfootruleheight}[1]{}
\newcommand{\tryfootrulefrac}[1]{}
\newcommand{\currentfootnote}{}
\newcommand{\drawfootnote}{(draw footnote)}
\newcommand{\footnotediagram}{(footnote diagram)}
\newcommand{\footnotedesign}{(footnote design)}
\newcommand{\footnotevalues}{(footnote values)}
\newcommand{\tryparindent}[1]{}
\newcommand{\tryparlinewidth}[1]{}
\newcommand{\tryparbaselineskip}[1]{}
\newcommand{\currentparagraph}{}
\newcommand{\drawparagraph}{(draw paragraph)}
\newcommand{\paragraphdiagram}{(paragraph diagram)}
\newcommand{\paragraphdesign}{(paragraph design)}
\newcommand{\paragraphvalues}{(paragraph values)}
\newcommand{\trybeforeskip}[1]{}
\newcommand{\tryafterskip}[1]{}
\newcommand{\tryindent}[1]{}
\newcommand{\currentheading}{}
\newcommand{\drawheading}[1]{(draw heading)}
\newcommand{\headingdiagram}[1]{(heading diagram)}
\newcommand{\headingdesign}[1]{(heading design)}
\newcommand{\headingvalues}{(heading values)}
\newcommand{\trytextfloatsep}[1]{}
\newcommand{\tryfloatsep}[1]{}
\newcommand{\tryintextsep}[1]{}
\newcommand{\trytopfigrule}[1]{}
\newcommand{\trybotfigrule}[1]{}
\newcommand{\currentfloat}{}
\newcommand{\drawfloat}{(draw float)}
\newcommand{\floatdiagram}{(float diagram)}
\newcommand{\floatdesign}{(float design)}
\newcommand{\floatvalues}{(float values)}
\newcommand{\trytotalnumber}[1]{}
\newcommand{\trytopnumber}[1]{}
\newcommand{\trybottomnumber}[1]{}
\newcommand{\trytopfraction}[1]{}
\newcommand{\trytextfraction}[1]{}
\newcommand{\trybottomfraction}[1]{}
\newcommand{\currentfloatpage}{}
\newcommand{\drawfloatpage}{(draw floatpage)}
\newcommand{\floatpagediagram}{(floatpage diagram)}
\newcommand{\floatpagedesign}{(floatpage design)}
\newcommand{\floatpagevalues}{(floatpage values)}
\newcommand{\trytocindent}[1]{}
\newcommand{\trytocnumwidth}[1]{}
```

```
\newcommand{\trytoclinewidth}[1]{}
\newcommand{\trytocrmarg}[1]{}
\newcommand{\trytocpnumwidth}[1]{}
\newcommand{\trytocdotsep}[1]{}
\newcommand{\currenttoc}{}
\newcommand{\drawtoc}{(draw toc)}
\newcommand{\tocdiagram}{(toc diagram)}
\newcommand{\tocdesign}{(toc design)}
\newcommand{\tocvalues}{(toc values)}
\newcommand{\drawaspread}[8][0]{(a spread)}
\newcommand{\drawfontframe}[1]{(font frame)}
\newcommand{\drawfontframelabel}[1]{}
```

File 193 **lwarp-leading.sty**

§ 291 Package leading

Pkg leading leading is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{leading}[2008/12/11]
```

```
\newcommand\leading[1]{}
```

File 194 **lwarp-letterspace.sty**

§ 292 Package letterspace

(*Emulates or patches code by* R Schlicht.)

Pkg letterspace letterspace is a subset of microtype, which is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-letterspace:

```
\LWR@ProvidesPackageDrop{letterspace}[2018/01/14]
```

```
\newcommand*\lsstyle{}
\newcommand\textls[2][]{}
\def\textls#1#{}
\newcommand*\lslig[1]{#1}
```

File 195 **lwarp-lettrine.sty**

§ 293 Package lettrine

(*Emulates or patches code by* Daniel Flipo.)

Pkg lettrine lettrine is emulated.

for HTML output: Discard all options for lwarp-lettrine:

```
\LWR@ProvidesPackageDrop{lettrine}[2018-08-28]
```

The initial letter is in a of class `lettrine`, and the following text is in a of class `lettrinetext`. `\lettrine` [⟨*keys*⟩] {⟨*letter*⟩} {⟨*additional text*⟩}

```
\DeclareDocumentCommand{\lettrine}{o m m}{%
\InlineClass{lettrine}{#2}\InlineClass{lettrinetext}{#3} % extra space
}

\newcounter{DefaultLines}
\setcounter{DefaultLines}{2}
\newcounter{DefaultDepth}
\newcommand*{\DefaultOptionsFile}{\relax}
\newcommand*{\DefaultLoversize}{0}
\newcommand*{\DefaultLraise}{0}
\newcommand*{\DefaultLhang}{0}
\newdimen\DefaultFindent
\setlength{\DefaultFindent}{\z@}
\newdimen\DefaultNindent
\setlength{\DefaultNindent}{0.5em}
\newdimen\DefaultSlope
\setlength{\DefaultSlope}{\z@}
\newdimen\DiscardVskip
\setlength{\DiscardVskip}{0.2\p@}
\newif\ifLettrineImage
\newif\ifLettrineOnGrid
\newif\ifLettrineRealHeight

\newcommand*{\LettrineTextFont}{\scshape}
\newcommand*{\LettrineFontHook}{}
\newcommand*{\LettrineFont}[1]{\InlineClass{lettrine}{#1}}
\newcommand*{\LettrineFontEPS}[1]{\includegraphics[height=1.5ex]{#1}}
```

File 196 **lwarp-lineno.sty**

§ 294 Package

lineno

(*Emulates or patches code by* Stephan I. Böttcher.)

Pkg lineno lineno is partly emulated, but mostly ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lineno}[2005/11/02]

\newcommand*\resetlinenumber[1][\@ne]{}

\def\linenumbers{%
     \@ifnextchar[{\resetlinenumber}%]
                  {\@ifstar{\resetlinenumber}{}}%
     }
```

```
8
9 \newcommand*{\nolinenumbers}{}
10
11 \@namedef{linenumbers*}{\par\linenumbers*}
12 \@namedef{runninglinenumbers*}{\par\runninglinenumbers*}
13
14 \def\endlinenumbers{\par}
15 \let\endrunninglinenumbers\endlinenumbers
16 \let\endpagewiselinenumbers\endlinenumbers
17 \expandafter\let\csname endlinenumbers*\endcsname\endlinenumbers
18 \expandafter\let\csname endrunninglinenumbers*\endcsname\endlinenumbers
19 \let\endnolinenumbers\endlinenumbers
20
21 \def\pagewiselinenumbers{\linenumbers\setpagewiselinenumbers}
22
23 \def\runninglinenumbers{\setrunninglinenumbers\linenumbers}
24
25 \def\setpagewiselinenumbers{}
26
27 \def\setrunninglinenumbers{}
28
29 \def\linenomath{}%
30 \@namedef{linenomath*}{}%
31 \def\endlinenomath{}
32 \expandafter\let\csname endlinenomath*\endcsname\endlinenomath
33
34 \let\linelabel\label
35
36 \def\switchlinenumbers{\@ifstar{}{}}
37 \def\setmakelinenumbers#1{\@ifstar{}{}}
38
39 \def\leftlinenumbers{\@ifstar{}{}}
40 \def\rightlinenumbers{\@ifstar{}{}}
41
42 \newcounter{linenumber}
43 \newcount\c@pagewiselinenumber
44 \let\c@runninglinenumber\c@linenumber
45
46 \def\runningpagewiselinenumbers{}
47 \def\realpagewiselinenumbers{}
48
49
50 \NewDocumentCommand\modulolinenumbers{s o}{}
51
52 \chardef\c@linenumbermodulo=5
53 \modulolinenumbers[1]
54
55 \newcommand*\firstlinenumber[1]{}
56
57 \newcommand\internallinenumbers{}
58 \let\endinternallinenumbers\endlinenumbers
59 \@namedef{internallinenumbers*}{\internallinenumbers*}
60 \expandafter\let\csname endinternallinenumbers*\endcsname\endlinenumbers
61
62 \newcommand*{\linenoplaceholder}[1]{% redefine per language
```

```
    (line number reference for \detokenize\expandafter{#1})
}

\newcommand*{\lineref}[2][]{\linenoplaceholder{#2}}
\newcommand*{\linerefp}[2][]{\linenoplaceholder{#2}}
\newcommand*{\linerefr}[2][]{\linenoplaceholder{#2}}

\newcommand\quotelinenumbers
   {\@ifstar\linenumbers{\@ifnextchar[\linenumbers{\linenumbers*}}}

\newdimen\linenumbersep
\newdimen\linenumberwidth
\newdimen\quotelinenumbersep

\quotelinenumbersep=\linenumbersep
\let\quotelinenumberfont\linenumberfont

\def\linenumberfont{\normalfont\tiny\sffamily}


\linenumberwidth=10pt
\linenumbersep=10pt

\def\thelinenumber{}

\def\LineNumber{}
\def\makeLineNumber{}
\def\makeLineNumberLeft{}
\def\makeLineNumberRight{}
\def\makeLineNumberOdd{}
\def\makeLineNumberEven{}
\def\makeLineNumberRunning{}


\newenvironment{numquote}     {\quote}{\endquote}
\newenvironment{numquotation} {\quotation}{\endquotation}
\newenvironment{numquote*}    {\quote}{\endquote}
\newenvironment{numquotation*}{\quotation}{\endquotation}

\newdimen\bframerule
\bframerule=\fboxrule

\newdimen\bframesep
\bframesep=\fboxsep

\newenvironment{bframe}
{%
    \LWR@forceminwidth{\bframerule}%
    \BlockClass[
        border:\LWR@printlength{\LWR@atleastonept} solid black ; %
        padding:\LWR@printlength{\bframesep}%
    ]{bframe}
}
{\endBlockClass}
```

File 197 **lwarp-lips.sty**

§ 295 Package lips

(*Emulates or patches code by* Matt Swift.)

Pkg lips lips is emulated.

```
% \LWR@ProvidesPackageDrop{lips}
\PackageInfo{lwarp}{Using the lwarp version of package ‘lips’.}%
\ProvidesPackage{lwarp-lips}[2001/08/31]

\NewDocumentCommand{\Lips}{}{\textellipsis}

\NewDocumentCommand{\BracketedLips}{}{[\textellipsis]}

\let\lips\Lips
\let\olips\lips

\DeclareOption*{}
\DeclareOption{mla}{
\let\lips\BracketedLips
}
\ProcessOptions\relax

\newcommand \LPNobreakList {}
```

File 198 **lwarp-listings.sty**

§ 296 Package listings

(*Emulates or patches code by* Carsten Heinz, Brooks Moses, Jobst Hoffmann.)

Pkg listings listings is supported with some limitations. Text formatting is not yet supported.

for HTML output:

```
\begin{warpHTML}

\LWR@ProvidesPackagePass{listings}[2018/09/02]
```

Force flexible columns. Fixed columns inserts spaces in the PDF output.

```
\lst@column@flexible
```

Patches to embed listings inside pre tags:

```
\let\LWR@origlst@Init\lst@Init
\let\LWR@origlst@DeInit\lst@DeInit
```

```
6
7 \let\LWR@origlsthkEveryPar\lsthk@EveryPar
8
9 \renewcommand{\l@lstlisting}[2]{\hypertocfloat{1}{lstlisting}{lol}{#1}{#2}}
```

\lstset {⟨*options*⟩}

Use the listings `literate` option to replace HTML entities:

```
10 \def\lstset@#1{\endgroup%
11 %  \ifx\@empty#1%
12 %         \@empty%
13 %     \else%
14         \setkeys{lst}{%
15             #1%
16             ,literate=%
17             {<}{\HTMLentity{lt}}{4}%
18             {>}{\HTMLentity{gt}}{4}%
19             {\&}{\HTMLentity{amp}}{5}%
20         }%
21 %     \fi%
22 }
```

\lst@Init {⟨*backslash-processing*⟩} Done at the start of a listing.

```
23 \renewcommand{\lst@Init}[1]{%
```

Perform the listings initialization:

```
24 \LWR@traceinfo{lst@Init}%
25 \renewcommand*{\@captype}{lstlisting}%
26 \let\lst@aboveskip\z@\let\lst@belowskip\z@%
27 \gdef\lst@boxpos{t}%
28 \let\lst@frame\@empty
29     \let\lst@frametshape\@empty
30     \let\lst@framershape\@empty
31     \let\lst@framebshape\@empty
32     \let\lst@framelshape\@empty
33 \lstframe@\lst@frameround ffff\relax%
34 \lst@multicols\@empty%
35 \LWR@origlst@Init{#1}\relax%
```

Avoids extra horizontal space:

```
36 \def\lst@framelr{}%
```

```
37 \LWR@traceinfo{finished origlst@Init}%
38 \lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the <pre>, then reenable line numbers.

```
39 \LWR@traceinfo{About to create verbatim.}%
40 \let\lsthk@EveryPar\relax%
41 \LWR@forcenewpage
42 \LWR@atbeginverbatim{2}{programlisting}%
43
```

```
\let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so open a :

```
\ifbool{LWR@verbtags}{\LWR@htmltag{span class="inlineprogramlisting"}}{}%
\fi%
}
```

`\lst@DeInit` Done at the end of a listing.

```
\renewcommand*{\lst@DeInit}{%
\lst@ifdisplaystyle%
```

Creating a display.

Disable line numbers, produce the </pre>, then reenable line numbers:

```
\let\lsthk@EveryPar\relax%
\LWR@afterendverbatim{0}%
\let\lsthk@EveryPar\LWR@origlsthkEveryPar%
\else%
```

Inline, so create the closing :

```
\ifbool{LWR@verbtags}{\noindent\LWR@htmltag{/span}}{}%
\fi%
```

Final listings deinit:

```
\LWR@origlst@DeInit%
}
```

`\lst@MakeCaption` {⟨*t/b*⟩}

This is called BOTH at the top and at the bottom of each listing.

Patched for lwarp.

```
\def\lst@MakeCaption#1{%
\LWR@traceinfo{MAKING CAPTION at #1}%
  \lst@ifdisplaystyle
\LWR@traceinfo{making a listings display caption}%
    \ifx #1t%
         \ifx\lst@@caption\@empty\expandafter\lst@HRefStepCounter \else
                                  \expandafter\refstepcounter
         \fi {lstlisting}%
\LWR@traceinfo{About to assign label: !\lst@label!}%
%         \ifx\lst@label\@empty\else
% \label{\lst@label}\fi
\LWR@traceinfo{Finished assigning the label.}%
        \let\lst@arg\lst@intname \lst@ReplaceIn\lst@arg\lst@filenamerpl
        \global\let\lst@name\lst@arg \global\let\lstname\lst@name
        \lst@ifnolol\else
            \ifx\lst@@caption\@empty
                \ifx\lst@caption\@empty
                    \ifx\lst@intname\@empty \else \def\lst@temp{ }%
                    \ifx\lst@intname\lst@temp \else
```

This code places a contents entry for a non-float. This would have to be modified for lwarp:

```
\LWR@traceinfo{addcontents lst@name: -\lst@name-}%
%                             \addcontentsline{lol}{lstlisting}{\lst@name}
                    \fi\fi
                \fi
            \else
```

This would have to be modified for lwarp:

```
\LWR@traceinfo{addcontents lst@@caption: -\lst@@caption-}%
                 \addcontentsline{lol}{lstlisting}%
{\protect\numberline{\thelstlisting}%
{\protect\ignorespaces \LWR@isolate{\lst@@caption} \protect\relax}}%
            \fi
         \fi
     \fi
    \ifx\lst@caption\@empty\else
\LWR@traceinfo{lst@caption not empty-}%
        \lst@IfSubstring #1\lst@captionpos
            {\begingroup
\LWR@traceinfo{at the selected position}%
```

These space and box commands are not needed for HTML output:

```
%              \let\@@vskip\vskip
%              \def\vskip{\afterassignment\lst@vskip \@tempskipa}%
%              \def\lst@vskip{\nobreak\@@vskip\@tempskipa\nobreak}%
%              \par\@parboxrestore\normalsize\normalfont % \noindent (AS)
%              \ifx #1t\allowbreak \fi
             \ifx\lst@title\@empty
```

New lwarp code to create a caption:

```
                  \lst@makecaption\fnum@lstlisting{\ignorespaces \lst@caption}
             \else
```

New lwarp code to create a title:

```
%                  \lst@maketitle\lst@title % (AS)
\LWR@traceinfo{Making title: \lst@title}%
\begin{BlockClass}{lstlistingtitle}% lwarp
\lst@maketitle\lst@title% lwarp
\end{BlockClass}% lwarp
             \fi
\LWR@traceinfo{About to assign label: !\lst@label!}%
        \ifx\lst@label\@empty\else
\leavevmode% gets rid of bad space factor error
\GetTitleStringExpand{\lst@caption}%
\edef\LWR@lntemp{\GetTitleStringResult}%
\edef\@currentlabelname{\detokenize\expandafter{\LWR@lntemp}}%
\label{\lst@label}\fi
\LWR@traceinfo{Finished assigning the label.}%
```

Not needed for lwarp:

```
%              \ifx #1b\allowbreak \fi
             \endgroup}{}%
    \fi
```

```
\LWR@traceinfo{end of making a listings display caption}%
  \else
\LWR@traceinfo{INLINE}%
  \fi
\LWR@traceinfo{DONE WITH CAPTION at #1}%
}
```

line numbers Patched to keep left line numbers outside of the left margin, and place right line numbers in a field `\VerbatimHTMLWidth` wide.

```
\lst@Key{numbers}{none}{%
    \let\lst@PlaceNumber\@empty
    \lstKV@SwitchCases{#1}%
    {none:\\%
     left:\def\lst@PlaceNumber{%
```

For now, lwarp places left line numbers inline. Ideally the entire line would be moved to the right, but conflicts with list indenting occurs.

```
%         \LWR@origllap{
            \LWR@orignormalfont%
            \lst@numberstyle{\thelstnumber}\kern\lst@numbersep%
%         }
    }\\%
     right:\def\lst@PlaceNumber{\LWR@origrlap{\LWR@orignormalfont
                \kern 6in \kern\lst@numbersep
                \lst@numberstyle{\thelstnumber}}}%
    }{\PackageError{lwarp-listings}{Numbers #1 unknown}\@ehc}}

\end{warpHTML}
```

File 199 **lwarp-listliketab.sty**

§ 297 Package

listliketab

Pkg listliketab listliketab is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{listliketab}[2005/01/09]

\newcommand*{\storestyleof}[1]{}
\newcommand*{\storeliststyle}{}
\newenvironment{listliketab}{}{}
```

File 200 **lwarp-lltjext.sty**

§ 298 Package

lltjext

(*Emulates or patches code by* The LuaTeX-ja project team.)

Pkg lltjext lltjext is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{lltjext}[2018/10/07]

\protected\def\yoko{%
  \directlua{luatexja.direction.set_list_direction(4, 'yoko')}%
}
\protected\def\tate{\yoko}
\protected\def\dtou{\yoko}
\protected\def\utod{\yoko}

\define@key[ltj]{japaram}{direction}{}

\yoko

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

File 201 **lwarp-longtable.sty**

§ 299 Package longtable

(*Emulates or patches code by* David Carlisle.)

Pkg longtable longtable is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{longtable}[2014/10/28]
```

Use one of either \endhead or \endfirsthead for both print and HTML, and use a \warpprintonly macro to disable the other head phrase, and also the \endfoot and \endfirstfoot phrases. (See section 8.10.4 if using threeparttablex.)

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  [ <lastfoot macros> ] \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{
  [ <lastfoot macros> ]   % HTML last footer, without \endfoot
                                                % or \endlastfoot.
}
\end{longtable}
```

⚠ Misplaced \noalign — Use the \warpprintonly macro instead of the warpprint environment. Doing so helps avoid "Misplaced \noalign." when using \begin{warpprint}.

⚠ \kill — \kill is ignored, place a \kill line inside

```
\begin{warpprint} . . .  \end{warpprint}
```

or place it inside \warpprintonly.

⚠ lateximage — longtable is not supported inside a lateximage.

See:
http://tex.stackexchange.com/questions/43006/why-is-input-not-expandable

Used to detect more than one of \endhead and \endfirsthead in use for HTML at the same time.

```
\newbool{LWR@longtable@havehead}
\boolfalse{LWR@longtable@havehead}
```

Env longtable — * [⟨*horizalignment*⟩] {⟨*colspec*⟩} Emulates the longtable environment.

Per the caption package, the starred version steps the counter per caption. The unstarred version steps the counter once at the beginning, but not at each caption.

Options [c], [l], and [r] are ignored.

```
\newenvironment{longtable*}[2][]{%
\LWR@floatbegin{table}%
\setcaptiontype{\LTcaptype}%
\caption@setoptions{longtable}%
\caption@setoptions{@longtable}%
\caption@LT@setup%
\booltrue{LWR@starredlongtable}%
\boolfalse{LWR@longtable@havehead}%
```

```
\let\captionlistentry\LWR@LTcaptionlistentry%
\tabular{#2}
}
{\endtabular\LWR@floatend}

\newenvironment{longtable}[2][]{%
\LWR@floatbegin{table}%
\setcaptiontype{\LTcaptype}%
\caption@setoptions{longtable}%
\caption@setoptions{@longtable}%
\caption@LT@setup%
\refstepcounter{\LTcaptype}%
\boolfalse{LWR@longtable@havehead}%
\let\captionlistentry\LWR@LTcaptionlistentry%
\tabular{#2}
}
{\endtabular\LWR@floatend}
```

Provided for compatibility, but ignored:

```
\newcounter{LTchunksize}
```

Error for heads which should have been in `\warpprintonly`:

```
\newcommand*{\LWR@longtable@headerror}{%
    \PackageError{lwarp}
    {For longtable:\MessageBreak
    1: Keep either one of an \protect\endhead\space or
        \protect\endfirsthead\space\MessageBreak
        \space phrase as-is, to be used by both print and HTML.\MessageBreak
    2: Place any other \protect\end... phrases inside a\MessageBreak
        \space\protect\warpprintonly\space macro,
            to be ignored by HTML.\MessageBreak
    3: Add a final footer for HTML at the end of the table\MessageBreak
        \space inside a \protect\warpHTMLonly\space macro.
            This can be\MessageBreak
        \space a copy of an \protect\endfoot\space or
            \protect\endfirstfoot\space phrase,\MessageBreak
        \space but without the actual \protect\endfoot\space
            or \protect\endfirstfoot\MessageBreak
        \space macros.  If using threeparttablex, add\MessageBreak
        \space \protect\insertTableNotes\space here,
            optionally with\MessageBreak
        \space \protect\UseMinipageWidths\space in front.\MessageBreak
    See the lwarp documentation regarding longtables\MessageBreak
    and threeparttablex}
    {See the lwarp documentation regading longtables and threeparttablex.}
}
```

Error if more than one of `\endhead` or `\endfirsthead` is outside of `warpprintonly`.

```
\newcommand*{\LWR@longtable@maybeheaderror}{%
\ifbool{LWR@longtable@havehead}%
    {\LWR@longtable@headerror}%
```

```
    {%
        \booltrue{LWR@longtable@havehead}
        \LWR@tabularendofline% throws away options //[dim] and //*
    }%
}
```

Error if more than one of these is outside of warppprint.

```
\def\endhead{\LWR@longtable@maybeheaderror}
\def\endfirsthead{\LWR@longtable@maybeheaderror}
```

Error if ANY of these is outside of warppprint.

```
\def\endfoot{\LWR@longtable@headerror}
\def\endlastfoot{\LWR@longtable@headerror}
```

```
\providecommand*{\LWR@HTML@tabularnewline}{\LWR@tabularendofline}
\LWR@formatted{tabularnewline}
```

```
\newcommand{\setlongtables}{}% Obsolete command, does nothing.
\newlength{\LTleft}
\newlength{\LTright}
\newlength{\LTpre}
\newlength{\LTpost}
\newlength{\LTcapwidth}
```

```
\LetLtxMacro\LWR@origkill\kill
\renewcommand*{\kill}{\LWR@tabularendofline}
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\kill\LWR@origkill%
}
```

File 202 **lwarp-lscape.sty**

§ 300 Package

lscape

(*Emulates or patches code by* D. P. Carlisle.)

Pkg lscape lscape is ignored.

for HTML output: Discard all options for lwarp-lscape.

```
\LWR@ProvidesPackageDrop{lscape}[2000/10/22]
```

```
\newenvironment*{landscape}{}{}
```

File 203 **lwarp-ltablex.sty**

§ 301 Package ltablex

(*Emulates or patches code by* Anil K. Goel.)

Pkg ltablex ltablex is emulated by lwarp.

for HTML output: Relies on tabularx.

```
\RequirePackage{tabularx}

\LWR@ProvidesPackageDrop{ltablex}[2014/08/13]

\DeclareDocumentEnvironment{tabularx}{m o m}
{\longtable{#3}}
{\endlongtable}

\DeclareDocumentEnvironment{tabularx*}{m o m}
{\longtable{#3}}
{\endlongtable}

\newcommand*{\keepXColumns}{}
\newcommand*{\convertXColumns}{}
```

File 204 **lwarp-ltcaption.sty**

§ 302 Package ltcaption

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg ltcaption ltcaption is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltcaption}[2018/08/26]
```

\LTcaptype is already defined by lwarp.

longtable* is already defined by lwarp-longtable.

```
\newlength{\LTcapskip}
\newlength{\LTcapleft}
\newlength{\LTcapright}
\newcommand*{\LTcapmarginsfalse}{}
```

File 205 **lwarp-ltxgrid.sty**

§ 303 Package ltxgrid

Pkg ltxgrid ltxgrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltxgrid}[2010/07/25]

\newcommand*{\onecolumngrid}{}
\newcommand*{\twocolumngrid}{}
\newcommand*{\removestuff}{}
\newcommand*{\addstuff}[2]{}
\newcommand*{\replacestuff}[2]{}
```

File 206 **lwarp-ltxtable.sty**

§ 304 Package ltxtable

Pkg ltxtable ltxtable is emulated.

⚠ table numbering The print version does not seem to honor `longtable*` from the caption package, while lwarp does.

for HTML output:

```
\LWR@ProvidesPackageDrop{ltxtable}[1995/12/11]
```

\LTXtable {⟨*width*⟩} {⟨*file*⟩}

```
\newcommand*{\LTXtable}[2]{%
\input{#2}%
}
```

File 207 **lwarp-lua-check-hyphen.sty**

§ 305 Package lua-check-hyphen

Pkg lua-check-hyphen lua-check-hyphen is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-check-hyphen}[2018/04/19]

\newcommand*{\LuaCheckHyphen}[1]{}
```

File 208 **lwarp-lua-visual-debug.sty**

§ 306 Package

lua-visual-debug

Pkg lua-visual-debug lua-visual-debug is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{lua-visual-debug}[2016/05/30]
```

File 209 **lwarp-luacolor.sty**

§ 307 Package

luacolor

Pkg luacolor luacolor is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{luacolor}[2016/05/16]
\newcommand{\luacolorProcessBox}[1]{}
```

File 210 **lwarp-luatodonotes.sty**

§ 308 Package

luatodonotes

(*Emulates or patches code by* Fabian Lipp.)

Pkg luatodonotes luatodonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{luatodonotes}[2017/09/30]
```

Nullify options:

```
\@todonotes@additionalMarginEnabledfalse

\if@todonotes@disabled
\else

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}
```

```
\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
\phantomsection%
\LWRTODONOTES@orig@todototoc%
}


\renewcommand{\@todonotes@drawMarginNoteWithLine}{%
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
        \@todonotes@text%
    }%
}

\newcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todocommon\@todocommon
```

```
64
65 \RenewDocumentCommand{\@todocommon}{m m}{%
66 \begingroup%
67 \renewcommand*{\phantomsection}{}%
68 \LWRTODONOTES@orig@todocommon{#1}{#2}%
69 \endgroup%
70 }
71
72 \renewcommand{\@todoarea}[3][]{%
73     \@todonotes@areaselectedtrue%
74     \@todocommon{#1}{#2}%
75     \todonotes@textmark@highlight{#3}%
76     \zref@label{@todonotes@\arabic{@todonotes@numberoftodonotes}@end}%
77 }%
78
79
80 \DeclareDocumentCommand{\todonotes@textmark@highlight}{m}{%
81 \InlineClass[background:\LWR@origpound{}B3FFB3]{highlight}{#1}%
82 }
83
84 \fi% \if@todonotes@disabled
```

File 211 **lwarp-magaz.sty**

§ 309 Package magaz

Pkg magaz magaz is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{magaz}[2011/11/24]

2 \newcommand\FirstLine[1]{%
3     \begingroup%
4     \FirstLineFont{%
5         \LWR@textcurrentcolor{%
6             \LWR@textcurrentfont{%
7                 #1%
8             }%
9         }%
10    }%
11    \endgroup%
12 }
13
14 \providecommand\FirstLineFont{\scshape}
```

File 212 **lwarp-makeidx.sty**

§ 310 Package makeidx

(*Emulates or patches code by* LaTeX Project Team.)

Pkg makeidx makeidx is patched for use by lwarp.

for HTML output:
```
1 \LWR@ProvidesPackagePass{makeidx}[2014/09/29]
```

\@wrindex is redefined \AtBeginDocument by the lwarp core.

\printindex

```
2 \preto\printindex{%
3     \LWR@orignewpage%
4     \LWR@startpars%
5 }
```

File 213 **lwarp-manyfoot.sty**

§ 311 Package

manyfoot

Pkg manyfoot manyfoot is emulated.

bigfoot, manyfoot ⚠ verbatim Verbatim footnotes are not yet supported.

If using the bigfoot package, and possibly also manyfoot, problems may occur with counter allocation because lwarp uses many counters, and there is a difference in how counters numbered 256 and up are handled in pdfLaTeX. With bigfoot this has been known to show up as an error related to one footnote insert being forbidden inside another. Another problem showed up as a input stack error, and which of these problems occurred depended on how many counters were allocated.

As a possible solution, try creating several new counters before defining bigfoot or manyfoot footnotes, hoping to shift the problematic counter above the 256 threshold. It may instead be necessary to use XeLaTeX or LuaLaTeX instead of pdfLaTeX.

lwarp's emulation of bigfoot uses manyfoot, so some of the bigfoot enhancements are included here.

The bigfoot "default" footnote is ignored, using the lwarp version instead.

for HTML output:
```
1 \LWR@ProvidesPackageDrop{manyfoot}[2005/09/11]
```

```
2 \RequirePackage{nccfoots}
3
4 \newcommand{\extrafootnoterule}{}
5
6 \let\defaultfootnoterule\footnoterule
7
8 \newcommand*{\SelectFootnoteRule}[2][0]{}
9
10 \newcommand{\footnoterulepriority}{1}
11
12 \newcommand{\SetFootnoteHook}[1]{}
13 \@onlypreamble\SetFootnoteHook
```

```
\newcommand{\SplitNote}{}

\newcommand*\ExtraParaSkip[1]{}

\newcommand*{\newfootnote}[2][plain]{%
    \ifstrequal{#2}{default}{}{% not "default"
        \expandafter\newbox\csname LWR@footnote#2box\endcsname%
        \appto{\LWR@printpendingfootnotes}{%
            \LWR@@printpendingfootnotes{footnote#2}%
        }
        \long\csdef{Footnotetext#2}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
        \long\csdef{Footnotetext#2+}##1##2{%
            \NCC@makefnmark{##1}%
            \LWR@@footnotetext{##2}{LWR@footnote#2box}%
        }%
    }% not "default"
}
\@onlypreamble\newfootnote

\newcommand*{\DeclareNewFootnote}[2][plain]{%
  \@ifnextchar[%
        {\LWR@manyfoot@declare{#1}{#2}}%
        {\LWR@manyfoot@declare{#1}{#2}[arabic]}%
}

\def\LWR@manyfoot@declare#1#2[#3]{%
\ifstrequal{#2}{default}{}{% not "default"
  \newfootnote[#1]{#2}%
  \newcounter{footnote#2}%
    \newcounter{footnote#2Reset}%
    \setcounter{footnote#2Reset}{0}%
    \csdef{thefootnote#2}{%
      \expandafter\noexpand\csname @#3\endcsname%
      \expandafter\noexpand\csname c@footnote#2\endcsname%
    }%
```

For bigfoot, the footnote commands may be appended with one or two plusses or one or two minuses, which are ignored in HTML.

```
  \expandafter\NewDocumentCommand\csname footnote#2\endcsname{t{+}t{+}t{-}t{-}}{%
        \stepcounter{footnote#2}%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \@footnotemark%
        \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
    }%
    \csdef{footnotemark#2}{%
        \stepcounter{footnote#2}%
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \@footnotemark%
    }%
  \expandafter\NewDocumentCommand\csname footnotetext#2\endcsname{t{+}t{+}t{-}t{-}}{%
```

```
        \protected@xdef\@thefnmark{\csname thefootnote#2\endcsname}%
        \csuse{Footnotetext#2}{\@thefnmark}% absorbs the footnote contents
    }%
    \csdef{Footnotemark#2}{%
      \Footnotemark%
    }%
    \csdef{Footnote#2}##1{%
      \Footnotemark{##1}%
      \csuse{Footnotetext#2}{##1}%
    }%
}% not "default"
}
\@onlypreamble\DeclareNewFootnote
```

File 214 **lwarp-marginal.sty**

§ 312 Package marginal

Pkg marginal marginal is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{marginal}

\newcommand*{\showlostmarginals}{}
\newcommand*{\enlargefreelist}{}
\newcommand*{\onesidemarginals}{}
```

File 215 **lwarp-marginfit.sty**

§ 313 Package marginfit

Pkg marginfit marginfit is ignored.

for HTML output: Discard all options for lwarp-marginfit:

```
\LWR@ProvidesPackageDrop{marginfit}[2018/06/08]
```

File 216 **lwarp-marginfix.sty**

§ 314 Package marginfix

(*Emulates or patches code by* Stephen Hicks.)

Pkg marginfix marginfix is ignored.

for HTML output: Discard all options for lwarp-marginfix:

```
\LWR@ProvidesPackageDrop{marginfix}[2013/09/08]
```

```
\newcommand*{\marginskip}[1]{}
\newcommand*{\clearmargin}{}
\newcommand*{\softclearmargin}{}
\newcommand*{\extendmargin}[1]{}
\newcommand*{\mparshift}[1]{}
\newdimen\marginheightadjustment
\newdimen\marginposadjustment
\newcommand*{\blockmargin}[1][]{}
\newcommand*{\unblockmargin}[1][]{}
\newcommand*{\marginphantom}[2][]{}
```

File 217 **lwarp-marginnote.sty**

§ 315 Package marginnote

(*Emulates or patches code by* Markus Kohm.)

Pkg marginnote marginnote is emulated.

for HTML output: Discard all options for lwarp-marginnote:

```
\LWR@ProvidesPackageDrop{marginnote}[2018/08/09]
```

```
\NewDocumentCommand{\marginnote}{+o +m o}{\marginpar{#2}}
```

```
\newcommand*{\marginnoteleftadjust}{}
\newcommand*{\marginnoterightadjust}{}
\newcommand*{\marginnotetextwidth}{}
\let\marginnotetextwidth\textwidth
\newcommand*{\marginnotevadjust}{}
\newcommand*{\marginfont}{}
\newcommand*{\raggedleftmarginnote}{}
\newcommand*{\raggedrightmarginnote}{}
```

File 218 **lwarp-marvosym.sty**

§ 316 Package marvosym

(*Emulates or patches code by* Thomas Henlich, Mojca Miklavec.)

Pkg marvosym marvosym is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:

```
\LWR@ProvidesPackagePass{marvosym}[2011/07/20]
```

```
\renewcommand{\mvchr}[1]{%
    \begin{lateximage}*[(symbol #1)][marvosym #1]%
    \mvs\char#1%
```

```
    \end{lateximage}%
}

\renewcommand{\textmvs}[1]{%
    \begin{lateximage}%
    \mvs #1%
    \end{lateximage}%
}
```

File 219 **lwarp-mathtools.sty**

§ 317 Package

mathtools

(*Emulates or patches code by* Morten Høgholm, Lars Madsen.)

Pkg mathtools mathtools is patched for use by lwarp.

⚠ numbering, italics showonlyrefs and mathic are disabled.

for HTML output:

```
\LWR@ProvidesPackagePass{mathtools}[2018/01/08]

\RequirePackage{graphicx}

\MHInternalSyntaxOn
```

Forces showonlyrefs off because lwarp uses cleveref, which is not compatible with showonlyrefs.

```
\renewcommand*\MT_showonlyrefs_true:{\MT_showonlyrefs_false:}
\mathtoolsset{showonlyrefs=false}
```

Forces math italic correction off. Not patched for lwarp.

```
\renewcommand*{\MT_mathic_true:}{\MT_mathic_false:}
\mathtoolsset{mathic=false}

\MHInternalSyntaxOff
```

File 220 **lwarp-mcaption.sty**

§ 318 Package

mcaption

(*Emulates or patches code by* Stephan Hennig.)

Pkg mcaption mcaption is ignored.

for HTML output: Discard all options for lwarp-mcaption:

```
\LWR@ProvidesPackageDrop{mcaption}[2009/03/13]
```

```
\newenvironment{margincap}{}{}
\newcommand*{\margincapalign}{}
\newlength{\margincapsep}
```

File 221 **lwarp-mdframed.sty**

§ 319 Package

mdframed

(*Emulates or patches code by* Marco Daniel, Elke Schubert.)

Pkg mdframed

mdframed is loaded with options forced to `framemethod=none`.

§ 319.1 Limitations

support

Most basic functionality is supported, including frame background colors and single-border colors and thickness, title and subtitle background colors and borders and thickness, border radius, and shadow. CSS classes are created for mdframed environments and frame titles.

⚠ loading

When used, lwarp loads mdframed in HTML with `framemethod=none`.

font

For title font, use

```
frametitlefont=\textbf,
```

instead of

```
frametitlefont=\bfseries,
```

where `\textbf` must appear just before the comma and will receive the following text as its argument (since the text happens to be between braces in the mdframed source). Since lwarp does not support `\bfseries` and friends, only one font selection may be made at a time.

theoremtitlefont

`theoremtitlefont` is not supported, since the following text is not in braces in the mdframed source.

ignored options

`userdefinedwidth` and `align` are currently ignored.

css classes

Environments created or encapsulated by mdframed are enclosed in a `<div>` of class `mdframed`, and also class `md<environmentname>` for new environments.

Frame titles are placed in a `<div>` of class |mdframedtitle|. Subtitles are in a `<div>` of class |mdframedsubtitle|, and likewise for subsubtitles.

Pre-existing hooks are used to patch extra functions before and after the frames.

§ 319.2 Package loading

for HTML output:

```
\RequirePackage{xcolor}% for \convertcolorspec

\LWR@ProvidesPackageDrop{mdframed}[2013/07/01]
```

Do not require Ti*k*z or pstricks:

```
\LWR@origRequirePackage[framemethod=none]{mdframed}
```

§ 319.3 Patches

Patch to remove PDF formatting and add HTML tags:

```
\AtBeginDocument{
\def\mdf@trivlist#1{%
  \edef\mdf@temp{%
%     \topsep=\the\topsep\relax%
%     \partopsep=\the\partopsep\relax%
%     \parsep=\the\parsep\relax%
  }%
%   \setlength{\topsep}{#1}%
%   \topskip\z@%
%   \partopsep\z@%
%   \parsep\z@%
%   \@nmbrlistfalse%
%   \@trivlist%
%   \labelwidth\z@%
%   \leftmargin\z@%
%   \itemindent\z@%
  \let\@itemlabel\@empty%
  \def\makelabel##1{##1}%
%   \item\relax\mdf@temp\relax%
}

\renewcommand*{\endmdf@trivlist}{%
\LWR@traceinfo{endmdf@trivlist}%
% \endtrivlist%
\LWR@listend%
}
}% AtBeginDocument
```

§ 319.4 Initial setup

To handle css and paragraphs, patch code at start and end of environment and contents. `\LWR@print@raggedright` helps avoid hyphenation.

```
\mdfsetup{
startcode={\LWR@mdframedstart\LWR@print@raggedright},
endcode={\LWR@mdframedend},
startinnercode={\LWR@startpars\LWR@print@raggedright},
endinnercode={\LWR@stoppars},
}
```

§ 319.5 Color and length HTML conversion

\LWR@mdfprintcolor {⟨*mdfcolorkey*⟩}

Given the mdframed key, print the color.

```
\newcommand*{\LWR@mdfprintcolor}[1]{%
\convertcolorspec{named}{\@nameuse{mdf@#1}}{HTML}\LWR@tempcolor%
\LWR@origpound\LWR@tempcolor
}
```

\LWR@mdfprintlength {⟨*mdflengthkey*⟩}

Given the mdframed key, print the length.

```
\newcommand*{\LWR@mdfprintlength}[1]{%
\LWR@forceminwidth{\@nameuse{mdf@#1@length}}%
\LWR@printlength{\LWR@atleastonept}%
}
```

§ 319.6 Environment encapsulation

\LWR@mdframedstart Actions before an mdframe starts.

Encapsulate a frame inside a of the desired class.

```
\newcommand*{\LWR@mdframedstart}{%
\LWR@traceinfo{LWR@mdframedstart start}%
```

Turn off paragraph handling during the generation of the encapsulating tags:

```
\LWR@stoppars%
```

Open a and with custom class and custom style. A BlockClass environment is not used because this is created by the mdframed startcode and endcode settings, which do not properly nest the inside the mdframed environment.

```
\LWR@htmltagc{div class="%
mdframed%
\ifdefstring{\LWR@mdthisenv}{mdframed}{}{ \LWR@mdthisenv}%
" \LWR@orignewline
style=" \LWR@orignewline
```

Convert and print the background color:

```
background: \LWR@mdfprintcolor{backgroundcolor} ; \LWR@orignewline
```

Convert and print the border color and width:

```
border: \LWR@mdfprintlength{linewidth} solid
\LWR@mdfprintcolor{linecolor} ; \LWR@orignewline
```

Convert and print the border radius:

```
border-radius: \LWR@mdfprintlength{roundcorner} ; \LWR@orignewline
```

Convert and print the shadow:

```
\ifbool{mdf@shadow}{%
    box-shadow:
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
    \LWR@mdfprintlength{shadowsize}
```

```
    \LWR@mdfprintcolor{shadowcolor} ;
}
{box-shadow: none ;}
\LWR@orignewline

"}
% \LWR@htmldivclass{\LWR@mdthisenv}
```

mdframed environment may not work with the HTML versions of the following, so restore them to their originals while inside mdframed:

```
\LWR@select@print@hspace%
\renewcommand*{\rule}{\LWR@print@rule}
\LetLtxMacro\makebox\LWR@print@makebox%

\LWR@startpars%
\LWR@traceinfo{LWR@mdframedstart done}%
}
```

\LWR@mdframedend Actions after an mdframe ends.

After closing the , globally restore to the default environment type:

```
\newcommand*{\LWR@mdframedend}{
\LWR@traceinfo{LWR@mdframedend start}%
```

Close the custom :

```
\LWR@htmldivclassend{\LWR@mdthisenv}
```

Reset future custom class to the default:

```
\gdef\LWR@mdthisenv{mdframed}
```

Resume paragraph handling:

```
\LWR@startpars%
\LWR@traceinfo{LWR@mdframedend done}%
}
```

§ 319.7 Mdframed environment

```
\renewenvironment{mdframed}[1][]{%
 \color@begingroup%
   \mdfsetup{userdefinedwidth=\linewidth,#1}%
   \mdf@startcode%
   \mdf@preenvsetting%
   \ifdefempty{\mdf@firstframetitle}{}%
            {\let\mdf@frametitlesave\mdf@frametitle%
             \let\mdf@frametitle\mdf@firstframetitle%
            }%
   \ifvmode\nointerlineskip\fi%
        \ifdefempty{\mdf@frametitle}{}%
            {\mdfframedtitleenv{\mdf@frametitle}%
% \mdf@@frametitle@use%
            }%
   \mdf@trivlist{\mdf@skipabove@length}%%
   \mdf@settings%
%    \mdf@lrbox{\mdf@splitbox@one}%
%    \mdf@startinnercode%
```

```
  }%
  {%
%    \mdf@@ignorelastdescenders%
   \par%
%     \unskip\ifvmode\nointerlineskip\hrule \@height\z@ \@width\hsize\fi%%
   \ifmdf@footnoteinside%
      \def\mdf@reserveda{%
        \mdf@footnoteoutput%
%         \mdf@endinnercode%
%         \endmdf@lrbox%
%         \ifdefempty{\mdf@frametitle}{}%
%             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%         \detected@mdf@put@frame
      }%
   \else%
      \def\mdf@reserveda{%
%         \mdf@endinnercode%
%         \endmdf@lrbox%
%         \ifdefempty{\mdf@frametitle}{}%
%             {\mdfframedtitleenv{\mdf@frametitle}\mdf@@frametitle@use}%
%         \detected@mdf@put@frame%
        \mdf@footnoteoutput%
        }%
   \fi%
   \mdf@reserveda%
  \aftergroup\endmdf@trivlist%
 \color@endgroup%
 \mdf@endcode%
}
```

\mdf@footnoteoutput

```
\renewrobustcmd*\mdf@footnoteoutput{%
    \LWR@printpendingmpfootnotes%
}
```

§ 319.8 Titles and subtitles

\mdfframedtitleenv {⟨*title*⟩}

Place the title inside a of class mdframedtitle:

```
\newlength{\LWR@titleroundcorner}

\renewrobustcmd\mdfframedtitleenv[1]{%
\LWR@traceinfo{LWR@mdframedtitleenv start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the title background color:

```
background:
\LWR@mdfprintcolor{frametitlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the title rule:

```
\ifbool{mdf@frametitlerule}{%
    border-bottom:
    \LWR@mdfprintlength{frametitlerulewidth}
    solid
    \LWR@mdfprintcolor{frametitlerulecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
]{mdframedtitle}%
```

Print the title inside the :

```
\mdf@frametitlefont{\LWR@textcurrentfont{#1}}%
```

Close the :

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedtitleenv end}%
}
```

\LWR@mdfsubtitlecommon {⟨*sub -or- subsub*⟩} [⟨*options*⟩] {⟨*title*⟩}

Common code for \LWR@mdfsubtitle and \LWR@mdfsubsubtitle.

Encapsulate the subtitle inside a of class mdframedsubtitle:

```
\NewDocumentCommand{\LWR@mdfsubtitlecommon}{m o m}
{% the following empty line is required

\LWR@traceinfo{LWR@mdframedsubtitlecommon start}%
```

Open a with a custom class and custom style:

```
\begin{BlockClass}[%
```

Convert and print the background color:

```
background:
\LWR@mdfprintcolor{#1titlebackgroundcolor}
; \LWR@orignewline
```

Convert and print the above line:

```
\ifbool{mdf@#1titleaboveline}{%
    border-top:
    \LWR@mdfprintlength{#1titleabovelinewidth}
    solid
    \LWR@mdfprintcolor{#1titleabovelinecolor}
    ; \LWR@orignewline
}{}%
```

Convert and print the below line:

```
\ifbool{mdf@#1titlebelowline}{%
    border-bottom:
    \LWR@mdfprintlength{#1titlebelowlinewidth}
    solid
    \LWR@mdfprintcolor{#1titlebelowlinecolor}
    ; \LWR@orignewline
}{}%
```

Finish the custom style and the opening tag:

```
]{mdframed#1title}%
```

Perform the original subtitle action:

```
\IfNoValueTF{#2}
{\@nameuse{LWR@origmdf#1title}{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
{\@nameuse{LWR@origmdf#1title}[#2]{\csuse{mdf@#1titlefont}{\LWR@textcurrentfont{#3}}}}%
```

Close the :

```
\end{BlockClass}%
\LWR@traceinfo{LWR@mdframedsubtitlecommon end}%
}
```

`\LWR@mdfsubtitle` `[⟨options⟩] {⟨title⟩}`

```
\newcommand*{\LWR@mdfsubtitle}{%
\LWR@mdfsubtitlecommon{sub}%
}
\let\mdfsubtitle\LWR@mdfsubtitle
```

`\LWR@mdfsubsubtitle` `[⟨options⟩] {⟨title⟩}`

```
\newcommand*{\LWR@mdfsubsubtitle}{%
\LWR@mdfsubtitlecommon{subsub}%
}
\let\mdfsubsubtitle\LWR@mdfsubsubtitle
```

§ 319.9 New environments

`\LWR@mdthisenv` Stores the environment of the frame about to be created:

```
\newcommand*{\LWR@mdthisenv}{mdframed}
```

`\newmdenv` `[⟨options⟩] {⟨env-name⟩}`

Modified from the original to remember the environment.

```
\renewrobustcmd*\newmdenv[2][]{%
\newenvironment{#2}%
{%
\mdfsetup{#1}%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}%
}
{\end{mdframed}}%
}
```

`\surroundwithmdframed` `[⟨options⟩] {⟨environment⟩}`

Modified from the original to remember the environment.

```
\renewrobustcmd*{\surroundwithmdframed}[2][]{%
\BeforeBeginEnvironment{#2}{%
\renewcommand*{\LWR@mdthisenv}{md#2}%
\begin{mdframed}[#1]}%
\AfterEndEnvironment{#2}{\end{mdframed}}%
```

```
}
```

\mdtheorem [⟨*mdframed-options*⟩] {⟨*envname*⟩} [⟨*numberedlike*⟩] {⟨*caption*⟩} [⟨*within*⟩]

Modified from the original to remember the environment.

```
\DeclareDocumentCommand{\mdtheorem}{ O{} m o m o }%
 {\ifcsdef{#2}%
   {\mdf@PackageWarning{Environment #2 already exits\MessageBreak}}%
   {%
    \IfNoValueTF {#3}%
     {%#3 not given -- number relationship
      \IfNoValueTF {#5}%
        {%#3+#5 not given
        \@definecounter{#2}%
        \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
        \newenvironment{#2}[1][]{%
          \refstepcounter{#2}%
          \ifstrempty{##1}%
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }%
          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                          \@temptitle}]}%
          {\end{mdframed}}%
        \newenvironment{#2*}[1][]{%
          \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
          {\end{mdframed}}%
        }%
        {%#5 given -- reset counter
        \@definecounter{#2}\@newctr{#2}[#5]%
        \expandafter\xdef\csname the#2\endcsname{\@thmcounter{#2}}%
        \expandafter\xdef\csname the#2\endcsname{%
               \expandafter\noexpand\csname the#5\endcsname \@thmcountersep%
                  \@thmcounter{#2}}%
        \newenvironment{#2}[1][]{%
          \refstepcounter{#2}%
          \ifstrempty{##1}%
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }
          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                          \@temptitle}]}%
          {\end{mdframed}}%
        \newenvironment{#2*}[1][]{%
```

```
          \ifstrempty{##1}%
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }%
          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
          {\end{mdframed}}%
        }%
     }%
     {%#3 given -- number relationship
        \global\@namedef{the#2}{\@nameuse{the#3}}%
        \newenvironment{#2}[1][]{%
          \refstepcounter{#3}%
          \ifstrempty{##1}%
            {\let\@temptitle\relax}%
            {%
             \def\@temptitle{\mdf@theoremseparator%
                             \mdf@theoremspace%
                             \mdf@theoremtitlefont%
                             \LWR@textcurrentfont{##1}}% lwarp
             \mdf@thm@caption{#2}{{#4}{\csname the#2\endcsname}{##1}}%
             }
          \begin{mdframed}[#1,frametitle={\strut#4\ \csname the#2\endcsname%
                                          \@temptitle}]}%
          {\end{mdframed}}%
        \newenvironment{#2*}[1][]{%
          \ifstrempty{##1}{\let\@temptitle\relax}{\def\@temptitle{:\ ##1}}%
          \begin{mdframed}[#1,frametitle={\strut#4\@temptitle}]}%
          {\end{mdframed}}%
     }%
    \BeforeBeginEnvironment{#2}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
    \BeforeBeginEnvironment{#2*}{\renewcommand*{\LWR@mdthisenv}{md#2}}% lwarp
   }%
}
```

\newmdtheoremenv [⟨*1: mdframed-options*⟩] {⟨*2: envname*⟩} [⟨*3: numberedlike*⟩] {⟨*4: caption*⟩} [⟨*5: within*⟩]

Modified from the original to remember the environment.

```
\DeclareDocumentCommand\newmdtheoremenv{O{} m o m o }{%
 \ifboolexpr{ test {\IfNoValueTF {#3}} and test {\IfNoValueTF {#5}} }%
    {\newtheorem{#2}{#4}}%
    {%
     \IfValueT{#3}{\newtheorem{#2}[#3]{#4}}%
     \IfValueT{#5}{\newtheorem{#2}{#4}[#5]}%
    }%
 \BeforeBeginEnvironment{#2}{%
 \renewcommand*{\LWR@mdthisenv}{md#2}%
 \begin{mdframed}[#1]}%
 \AfterEndEnvironment{#2}{%
 \end{mdframed}}%
```

```
305 }
```

File 222 **lwarp-media9.sty**

§ 320 Package media9

Pkg media9 media9 is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with …/embed/… instead of …/v/…

⚠ & in a URL Many special characters are converted to regular catcode 12 characters for use inside a URL. & is used in the flash variables fields, which are split with xparse \SplitList, which does not seem to work with a catcode 12 divider token, so & is not converted to catcode 12, and will not work in a URL with media9. Using & in a URL in a flashvars field may also cause parsing problems with print output, as well.

for HTML output:

```
\LWR@ProvidesPackageDrop{media9}[2019/02/21]

\LWR@origRequirePackage{lwarp-common-multimedia}

\RequirePackage{xkeyval}
```

\addmediapath {⟨*path*⟩}

Supported.

```
\newcommand*{\LWR@medianine@path}{}

\newcommand*{\addmediapath}[1]{\appto\LWR@medianine@path{{#1}}}
```

The options and poster text are reused in several places.

```
\newcommand*{\LWR@medianine@postertext}{}
\newcommand*{\LWR@medianine@options}{}
```

Each addresource can generate a multimedia object.

```
\define@key{LWR@medianine}{addresource}{%
    \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]
        {\LWR@medianine@postertext}
        {#1}
}
```

Each flashvars source can generate a multimedia object.

```
\newcommand*{\LWR@medianine@flashvarsb}[1]{%
    \IfBeginWith{#1}{source=}{%
        \StrGobbleLeft{#1}{7}[\LWR@tempone]%
        \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
            {\LWR@medianine@postertext}%
            {\LWR@tempone}%
    }{}%
    \IfBeginWith{#1}{src=}{%
        \StrGobbleLeft{#1}{4}[\LWR@tempone]%
        \expandafter\LWR@multimedia\expandafter[\LWR@medianine@options]%
            {\LWR@medianine@postertext}%
            {\LWR@tempone}%
    }{}%
}

\NewDocumentCommand{\LWR@medianine@flashvars}{ >{\SplitList{&}} m }{%
    \ProcessList {#1}{\LWR@medianine@flashvarsb}%
}

\define@key{LWR@medianine}{flashvars}{%
    \LWR@medianine@flashvars{#1}%
}
```

\includemedia [⟨*options*⟩] {⟨*poster text*⟩} {⟨*file or URL*⟩}

```
\newcommand*{\LWR@includemediab}[3][]{%
    \let\input@path\LWR@medianine@path%
    \renewcommand*{\LWR@medianine@options}{#1}%
    \renewcommand*{\LWR@medianine@postertext}{#2}%
    \setkeys*{LWR@medianine}{#1}%
    \IfBeginWith{#3}{http}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{HTTP}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{ftp}{\LWR@multimedia[#1]{#2}{#3}}{%
    \IfBeginWith{#3}{FTP}{\LWR@multimedia[#1]{#2}{#3}}{%
    }}}}%
    \endgroup%
}

\newrobustcmd*{\includemedia}{%
    \begingroup%
    \catcode`\#=12%
    \catcode`\%=12%
%     \catcode`\&=12% left alone for splitting flash variables
    \catcode`\~=12%
    \catcode`\_=12%
    \LWR@includemediab%
}
```

`\mediabutton` `[`⟨*options*⟩`]` `{`⟨*text*⟩`}`

Ignored.

```
\newcommand*{\mediabutton}[2][]{}
```

File 223 **lwarp-memhfixc.sty**

§ 321 Package memhfixc

Pkg memhfixc memhfixc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{memhfixc}[2013/05/30]
```

File 224 **lwarp-metalogo.sty**

§ 322 Package metalogo

(*Emulates or patches code by* Andrew Gilbert Moschou.)

Pkg metalogo metalogo is used in print mode, and emulated in HTML.

for HTML output:

```
\LWR@ProvidesPackagePass{metalogo}[2010/05/29]

\newcommand*{\LWR@HTML@setlogokern}[2]{}
\newcommand*{\LWR@HTML@setlogodrop}[2][XeTeX]{}
\newcommand*{\LWR@HTML@setLaTeXa}[1]{}
```

```
\newcommand*{\LWR@HTML@setLaTeXee}[1]{}
\newcommand*{\LWR@HTML@seteverylogo}[1]{}
\newcommand*{\LWR@HTML@everylogo}[1]{}

\LWR@formatted{setlogokern}
\LWR@formatted{setlogodrop}
\LWR@formatted{setLaTeXa}
\LWR@formatted{setLaTeXee}
\LWR@formatted{seteverylogo}
\LWR@formatted{everylogo}
```

File 225 **lwarp-metalogox.sty**

§ 323 Package metalogox

(*Emulates or patches code by* Brian Dunn.)

Pkg metalogox metalogox is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{metalogox}[2019/01/20]
```

\AtBeginDocument, adjust the logo setting according to the font which is active at that moment.

```
\AtBeginDocument{
    \let\LWR@metalogox@currentformatting\LWR@formatting
    \renewcommand*{\LWR@formatting}{print}%
    \autoadjustlogos*
    \let\LWR@formatting\LWR@metalogox@currentformatting
}
```

File 226 **lwarp-mhchem.sty**

§ 324 Package mhchem

(*Emulates or patches code by* Martin Hensel.)

Pkg mhchem mhchem is patched for use by lwarp.

without MathJax Without MathJax, mhchem expressions are converted to svg math. Inline expressions use hashed filenames to allow reuse, and assume that any mhchem options are global.

MathJax with mhchem extension For MathJax, the mhchem extension is used if the mhchem expression is used inside a math expression:

```
$\ce{C6H5-CHO}$
```

not inside math If *not* used inside a math expression, lwarp converts standalone mhchem expres-

sions into SVG math images.

MathJax without mhchem extension

If the MathJax mhchem extension is not used, expressions inside math must be placed between `\displaymathother` and `\displaymathnormal`:

```
\displaymathother
\[ \ce{ . . . } \]     . . .     $ \ce { . . . } $
\displaymathnormal
```

⚠ nested math

When producing HTML output without the MathJax mhchem extension, lwarp does not support the use of nested dollar signs in mhchem expressions.

For some examples from the mhchem manual, change as follows:

```
$\ce{NaOH(aq,$\infty$)}$            % old
$\ce{NaOH(aq,\infty)}$              % new

$\ce{Fe(CN)_{$\frac{6}{2}$}$}$      % old
$\ce{Fe(CN)_{\frac{6}{2}}}$         % new

$\ce{NO_$x$}$                       % old
$\ce{NO_x}$                         % new

$\ce{NO_${x}$}$                     % old
$\ce{NO_{x}}$                       % new

$\ce{$cis${-}[PtCl2(NH3)2]}$        % old
$\ce{\mathit{cis}{-}[PtCl2(NH3)2]}$ % new
```

for HTML output:

```
\LWR@ProvidesPackagePass{mhchem}[2018/06/22]
```

The original definition of `\ce`:

```
\LetLtxMacro\LWR@mhchem@origce\ce
```

The new definition, called from the new `\ce` after math shift is set. The starred `lateximage` uses a hashed filename for the SVG image. The `alt` tag is set to the mhchem expression.

```
\newcommand{\LWR@mhchem@HTML@ce}[1]{%
\begin{lateximage}*[\textbackslash{}ce\{\LWR@HTMLsanitize{#1}\}]%
\LWR@mhchem@origce{#1}%
\end{lateximage}%
\endgroup%
\addtocounter{LWR@mhchem@cedepth}{-1}%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cedepth}
\setcounter{LWR@mhchem@cedepth}{0}
```

The new \ce. Sets math shift then continues.

```
\renewcommand{\ce}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cedepth}}{0}{%
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cedepth}{1}%
\LWR@mhchem@HTML@ce%
}
```

The original definition of \cesplit:

```
\LetLtxMacro\LWR@mhchem@origcesplit\cesplit
```

The new definition, called from the new \cesplit after math shift is set. The starred lateximage uses a hashed filename for the SVG image. The alt tag is set to the mhchem expression.

```
\newcommand*{\LWR@mhchem@HTML@cesplit}[2]
{%
\begin{lateximage}*[\textbackslash{}cesplit\{\LWR@HTMLsanitize{#2}\}]%
\LWR@mhchem@origcesplit{#1}{#2}%
\end{lateximage}%
\endgroup%
}
```

Only set math shift if outer depth:

```
\newcounter{LWR@mhchem@cesplitdepth}
\setcounter{LWR@mhchem@cesplitdepth}{0}
```

The new \cesplit. Sets math shift then continues.

```
\renewcommand{\cesplit}{%
\begingroup%
\ifnumequal{\value{LWR@mhchem@cesplitdepth}}{0}{%
    \catcode`\$=3% math shift
}{}%
\addtocounter{LWR@mhchem@cesplitdepth}{1}%
\LWR@mhchem@HTML@cesplit%
}
```

Resore originals inside a lateximage:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\ce\LWR@mhchem@origce%
\LetLtxMacro\cesplit\LWR@mhchem@origcesplit%
}
```

File 227 **lwarp-microtype.sty**

§ 325 Package microtype

(*Emulates or patches code by* R Schlicht.)

Pkg microtype microtype is pre-loaded by lwarp. All user options and macros are ignored and disabled.

for HTML output: Discard all options for lwarp-microtype:

```
\LWR@ProvidesPackageDrop{microtype}[2018/01/14]

\DeclareDocumentCommand{\DeclareMicrotypeSet}{o m m}{}
\DeclareDocumentCommand{\UseMicrotypeSet}{o m}{}
\DeclareDocumentCommand{\DeclareMicrotypeSetDefault}{o m}{}
\DeclareDocumentCommand{\SetProtrusion}{o m m}{}
\DeclareDocumentCommand{\SetExpansion}{o m m}{}
\DeclareDocumentCommand{\SetTracking}{o m m}{}
\DeclareDocumentCommand{\SetExtraKerning}{o m m}{}
\DeclareDocumentCommand{\SetExtraSpacing}{o m m}{}
\DeclareDocumentCommand{\DisableLigatures}{o m}{}
\DeclareDocumentCommand{\DeclareCharacterInheritance}{o m m}{}
\DeclareDocumentCommand{\DeclareMicrotypeVariants}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeAlias}{m m}{}
\DeclareDocumentCommand{\LoadMicrotypeFile}{m}{}
\DeclareDocumentCommand{\DeclareMicrotypeBabelHook}{m m}{}
\DeclareDocumentCommand{\microtypesetup}{m}{}
\DeclareDocumentCommand{\microtypecontext}{m}{}
\DeclareDocumentCommand{\textmicrotypecontext}{m m}{#2}
\@ifpackageloaded{letterspace}{\let\MT@textls\relax}{%
\DeclareDocumentCommand{\lsstyle}{}{}
\DeclareDocumentCommand{\textls}{o +m}{}
\DeclareDocumentCommand{\lslig}{m}{#1}
}
\def\DeclareMicrotypeSet#1#{\@gobbletwo}
\def\DeclareMicrotypeVariants#1#{\@gobble}
\@onlypreamble\DeclareMicrotypeSet
\@onlypreamble\UseMicrotypeSet
\@onlypreamble\DeclareMicrotypeSetDefault
\@onlypreamble\DisableLigatures
\@onlypreamble\DeclareMicrotypeVariants
\@onlypreamble\DeclareMicrotypeBabelHook
```

File 228 **lwarp-midfloat.sty**

§ 326 Package midfloat

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg midfloat midfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{midfloat}[2012/05/29]

\newenvironment{strip}[1][]{}{}
\newskip\stripsep
```

File 229 **lwarp-midpage.sty**

§ 327 Package midpage

Pkg midpage midpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{midpage}[2009/09/03]

\newenvironment{midpage}
{\begin{BlockClass}[%
    \LWR@print@mbox{margin-top:6ex} ; \LWR@print@mbox{margin-bottom:6ex}%
]{midpage}}
{\end{BlockClass}}
```

File 230 **lwarp-minibox.sty**

§ 328 Package minibox

(*Emulates or patches code by* Will Robertson.)

Pkg minibox minibox is patched for use by lwarp.

Due to HTML limitations regarding paragraphs and s, miniboxes inline with other text will appear on their own line.

for HTML output:

```
\LWR@ProvidesPackagePass{minibox}[2013/06/21]

\ExplSyntaxOn
\newcommand\LWR@HTML@minibox[2][]{%
    \LWR@stoppars%
    \group_begin:
    \keys_set:nn {minibox} {#1}
    \bool_if:NTF \l_minibox_frame_bool
    {
        \setlength\fboxrule{\l_minibox_rule_dim}
        \setlength\fboxsep{\l_minibox_pad_dim}
        \fboxBlock{%
            \begin{tabular}[\l_minibox_tabular_valign_tl]%
              {\l_minibox_tabular_preamble_tl}
                {#2}
            \end{tabular}
        }%
```

```
    }
    {
        \begin{BlockClass}[display:inline-block]{minibox}
        \begin{tabular}[\l_minibox_tabular_valign_tl]%
          {\l_minibox_tabular_preamble_tl}
            {#2}
        \end{tabular}
        \end{BlockClass}
    }
    \group_end:
    \LWR@startpars%
}
\ExplSyntaxOff

\LWR@formatted{minibox}
```

File 231 **lwarp-minitoc.sty**

§ 329 Package minitoc

Pkg minitoc minitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{minitoc}[2018/07/12]
```

mtcoff disables minitoc.

```
\usepackage{mtcoff}
```

File 232 **lwarp-morefloats.sty**

§ 330 Package morefloats

Pkg morefloats morefloats is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{morefloats}[2015/07/22]
```

File 233 **lwarp-moreverb.sty**

§ 331 Package moreverb

(*Emulates or patches code by* Robin Fairbairns.)

Pkg moreverb moreverb is supported with some patches.

for HTML output:

```
\begin{warpHTML}
```

```
\LWR@ProvidesPackagePass{moreverb}[2008/06/03]
```

```
\BeforeBeginEnvironment{verbatimtab}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{Verbatim}%
}
\AfterEndEnvironment{verbatimtab}{%
\LWR@afterendverbatim{1}%
}


\LetLtxMacro\LWRMV@orig@verbatimtabinput\@verbatimtabinput

\renewcommand{\@verbatimtabinput}[2][]{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{Verbatim}%
\LWRMV@orig@verbatimtabinput[#1]{#2}%
\LWR@afterendverbatim{1}%
}

\BeforeBeginEnvironment{listing}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
}

\AfterEndEnvironment{listing}{%
\LWR@afterendverbatim{1}%
}

\BeforeBeginEnvironment{listingcont}{%
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
}

\AfterEndEnvironment{listingcont}{%
\LWR@afterendverbatim{1}%
}


\LetLtxMacro\LWRMV@@listinginput\@listinginput

\renewcommand{\@listinginput}[3][]{
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{programlisting}%
\LWRMV@@listinginput[#1]{#2}{#3}%
\LWR@afterendverbatim{1}%
}


\renewenvironment*{boxedverbatim}
{
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{boxedverbatim}%
\verbatim%
}
{
\endverbatim%
\LWR@afterendverbatim{1}%
```

```
}
\end{warpHTML}
```

File 234 **lwarp-movie15.sty**

§ 332 Package

movie15

Pkg movie15

movie15 is emualted.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with …/embed/… instead of …/v/…

for HTML output:

```
\LWR@ProvidesPackageDrop{movie15}[2012/05/16]
\LWR@origRequirePackage{lwarp-common-multimedia}
```

```
3
4 \RequirePackage{xkeyval}
5
6 \newcommand*{\LWR@moviefifteen@text}{}
7
8 \define@key{LWR@moviefifteen}{text}{\renewcommand{\LWR@moviefifteen@text}{#1}}
9
10 \newcommand*{\LWR@includemovieb}[4][]{%
11     \renewcommand{\LWR@moviefifteen@text}{(multimedia)}
12     \setkeys*{LWR@moviefifteen}{#1}%
13     \LWR@multimediab[#1,width=#2,height=#3]{\LWR@moviefifteen@text}{#4}%
14 }
15
16 \newrobustcmd*{\includemovie}{%
17     \begingroup%
18     \catcode`\#=12%
19     \catcode`\%=12%
20     \catcode`\&=12%
21     \catcode`\~=12%
22     \catcode`\_=12%
23     \LWR@includemovieb%
24 }
25
26
27 \newcommand*{\movieref}[3][]{}
28
29 \LetLtxMacro\movie\LWR@multimedia
30 % \LetLtxMacro\sound\LWR@multimedia% not in media15
31
32 \newcommand{\hyperlinkmovie}[3][]{}
```

File 235 **lwarp-mparhack.sty**

§ 333 Package mparhack

Pkg mparhack mparhack is ignored.

for HTML output: Discard all options for lwarp-mparhack:

```
1 \LWR@ProvidesPackageDrop{mparhack}[2005/04/17]
```

File 236 **lwarp-multicap.sty**

§ 334 Package multicap

Pkg multicap multicap is emualted.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{multicap}[2002/05/04]

2 \newcommand*{\mfcaption}{\captionof{figure}}
```

```
\newcommand*{\mtcaption}{\captionof{table}}
\newcounter{mcapsize}
\newcounter{mcapskip}
\newlength{\abvmcapskip}
\newlength{\blwmcapskip}
```

File 237 **lwarp-multicol.sty**

§ 335 Package

multicol

(*Emulates or patches code by* Frank Mittelbach.)

Pkg multicol multicol is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{multicol}[2018/12/27]
```

Multicols are converted into a 1–3 column display, browser-supported.

The optional multicols heading is placed inside a of class multicolsheading.

The content is placed inside a of class multicols.

```
\begin{warpHTML}
```

Env multicols * {⟨*numcols*⟩} [⟨*heading*⟩]

```
\NewDocumentEnvironment{multicols}{s m o}
```

HTML class to contain everything:

```
{
    \LWR@forcenewpage
    \BlockClass{multicols}
```

Optional HTML class for the heading:

```
    \IfValueT{#3}{\begin{BlockClass}{multicolsheading}#3\end{BlockClass}}%
```

Change \linewidth to compensate for expected size:

```
    \setlength{\linewidth}{\linewidth/#2}
```

Locally force any minipages to be fullwidth:

```
    \booltrue{LWR@forceminipagefullwidth}
}
```

When done with the environment, close the :

```
{\endBlockClass}
```

Emulated null functions which are not used in HTML:

```
\newcommand*{\columnbreak}{}
\newcommand*{\RLmulticolcolumns}{}
\newcommand*{\LRmulticolcolumns}{}
```

```
15
16 \newlength{\premulticols}
17 \newlength{\postmulticols}
18 \newlength{\multicolsep}
19 \newlength{\multicolbaselineskip}
20 \newlength{\multicoltolerance}
21 \newlength{\multicolpretolerance}
22 \newcommand*{\columnseprulecolor}{\normalcolor}
23 \newcounter{columnbadness}
24 \newcounter{finalcolumnbadness}
25 \newcounter{collectmore}
26 \newcounter{unbalance}
27 \newlength{\multicolovershoot}
28 \newlength{\multicolundershoot}

29 \NewDocumentCommand{\docolaction}{s o m m m}{%
30     \IfValueTF{#2}{#2}{#3}%
31 }

32 \end{warpHTML}
```

File 238 **lwarp-multicolrule.sty**

§ 336 Package multicolrule

Pkg multicolrule multicolrule is ignored.

for HTML output:

```
1 \RequirePackage{multicol}
2
3 \LWR@ProvidesPackageDrop{multicolrule}[2019/01/01]

4 \newcommand*{\SetMCRule}[1]{}
5 \NewDocumentCommand{\DeclareMCRulePattern}{m m}{}
```

File 239 **lwarp-multimedia.sty**

§ 337 Package multimedia

Pkg multimedia multimedia is emulated.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

for HTML output:

```
\LWR@ProvidesPackageDrop{multimedia}[2012/05/02]

\LWR@origRequirePackage{lwarp-common-multimedia}

\LetLtxMacro\movie\LWR@multimedia
\LetLtxMacro\sound\LWR@multimedia

\newcommand{\hyperlinkmovie}[3][]{}
```

File 240 **lwarp-multirow.sty**

§ 338 Package

multirow

(*Emulates or patches code by* Piet van Oostrum, Øystein Bache, Jerry Leichter.)

Pkg multirow multirow is emulated during HTML output, and used as-is while inside a lateximage.

vposn

- Note that recent versions of multirow include a new optional vposn argument.

multirow cells

- For multirow, insert \mrowcell into any empty multi-row cells. This will be a null function for the print output, and is a placeholder for parsing the table for HTML output. An error is generated if this is missed.

```
. . . &   \multirow{2}{.5in}{text}   & . . .
. . . &   \mrowcell                  & . . .
```

colored cells

- The multirow documentation regarding colored cells recommends using a negative number of rows. This will not work with lwarp, so \warpprintonly and \warpHTMLonly must be used to make versions for print and HTML.

with \multicolumn

- See section 338.2 for \multicolumrow.

⚠ \multicolumn & \multirow

lwarp does not support directly combining \multicolumn and \multirow. Use \multicolumnrow instead. To create a 2 column, 3 row cell:

```
\multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}
```

The two arguments for \multicolumn come first, followed by the five arguments for \multirow, many of which are optional, followed by the contents.

⚠ skipped cells

⚠ empty cells

As per \multirow, skipped cells to the right of the \multicolumnrow statement are not included in the source code on the same line. On the following lines, \mcolrowcell must be used for each cell of each column and each row to be skipped. An error is generated if this is missed.

```
. . . &   \multicolumnrow{2}{c}[c]{3}[0]{1in}[0pt]{Text}   & . . .
. . . &   \mcolrowcell          &          \mcolrowcell   & . . .
. . . &   \mcolrowcell          &          \mcolrowcell   & . . .
```

In a lateximage, \LWR@restoreorigformatting restores the original print-mode versions.

See section 72.25 for the print-mode versions.

for HTML output:

Remove the placeholder macro which was used if multirow was not loaded:

```
\LetLtxMacro\multirow\relax

\LWR@ProvidesPackagePass{multirow}[2018/08/03]
```

\LWR@multirowborder

Set to left or right to create a thick border for the cell, for use by bigdelim:

```
\newcommand{\LWR@multirowborder}{}
```

§ 338.1 Multirow

\multirow [⟨*vpos*⟩] {⟨*numrows*⟩} [⟨*bigstruts*⟩] {⟨*width*⟩} [⟨*fixup*⟩] {⟨*text*⟩}

```
\NewDocumentCommand{\LWR@HTML@multirow}{O{c} m o m o +m}%
{%
\LWR@traceinfo{*** LWR@HTML@multirow #1 #2 #4}%

\booltrue{LWR@usedmultirow}%

\LWR@maybenewtablerow%
\LWR@tabularleftedge%
```

Print the start of a new table data cell:

```
\LWR@htmltag{td rowspan="#2" %
```

The vertical alignment, if given:

```
\IfValueT{#1}{%
\ifstrequal{#1}{b}{style="\LWR@print@mbox{vertical-align:bottom}" }{}%
\ifstrequal{#1}{t}{style="\LWR@print@mbox{vertical-align:top}" }{}%
}%
```

The left/right border, if given:

```
\ifdefvoid{\LWR@multirowborder}{}{%
style="\LWR@print@mbox{border-\LWR@multirowborder:} 2px dotted black ; %
\LWR@print@mbox{padding-\LWR@multirowborder:} 2px" %
}%
```

A class adds the column spec and the rule:

```
class="td%
```

Append this column's spec:

```
\LWR@getexparray{LWR@tablecolspec}{\arabic{LWR@tableLaTeXcolindex}}%
```

If this column has a cmidrule, add "rule" to the end of the HTML class tag. Also add the vertical bar class.

```
\LWR@addcmidruletrim%
\LWR@addleftmostbartag%
\LWR@printbartag{\arabic{LWR@tableLaTeXcolindex}}%
"%


\LWR@tdstartstyles%
\LWR@addcmidrulewidth%
\LWR@addcdashline%
\LWR@addtabularrulecolors%
\LWR@tdendstyles%
}%
```

The column's < spec:

```
\LWR@getexparray{LWR@colbeforespec}{\arabic{LWR@tableLaTeXcolindex}}%
```

While printing the text, redefine \\ to generate a new line

```
\begingroup\LetLtxMacro{\\}{\LWR@endofline}#6\endgroup%
\LWR@stoppars%
\global\boolfalse{LWR@intabularmetadata}%
\renewcommand{\LWR@multirowborder}{}%
\LWR@traceinfo{*** LWR@HTML@multirow done}%
}%
```

```
38
39 \LWR@formatted{multirow}
```

§ 338.2 Combined multicolumn and multirow

\multicolumnrow {⟨*1:cols*⟩} {⟨*2:halign*⟩} [⟨*3:vpos*⟩] {⟨*4:numrows*⟩} [⟨*5:bigstruts*⟩] {⟨*6:width*⟩} [⟨*7:fixup*⟩] {⟨*8:text*⟩}

\@ifpackageloaded{multirow} determines if v2.0 or later of multirow was used, which included the \ProvidesPackage macro.

The HTML version follows.

\AtBeginDocument because the print version had to see if multirow was loaded before determining how to define \LWR@print@multicolumnrow.

```
40 \AtBeginDocument{
41
42 \NewExpandableDocumentCommand{\LWR@HTML@multicolumnrow}{m m O{} m O{} m O{} +m}{%


43 \booltrue{LWR@usedmultirow}%
```

Figure out how many extra HTML columns to add for @ and ! columns:

```
44 \LWR@tabularhtmlcolumns{\arabic{LWR@tableLaTeXcolindex}}{#1}
```

Create the multicolumn/multirow tag:

```
45 \begingroup%
46 \LetLtxMacro{\\}{\LWR@endofline}%
47 \LWR@domulticolumn[#3][#4]{#1}{\arabic{LWR@tabhtmlcoltotal}}{#2}{#8}%
48 \endgroup%
```

Move to the next LaTeX column:

```
49 \addtocounter{LWR@tableLaTeXcolindex}{#1}%
50 \addtocounter{LWR@tableLaTeXcolindex}{-1}%
```

Skip any trailing @ or ! columns for this cell:

```
51 \global\booltrue{LWR@skipatbang}%
52 }
53
54 \LWR@expandableformatted{multicolumnrow}
55
56 }% \AtBeginDocument
```

File 241 **lwarp-multitoc.sty**

§ 339 Package multitoc

Pkg multitoc multitoc is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{multitoc}[1999/06/08]

\newcommand{\multicolumntoc}{2}
\newcommand{\multicolumnlot}{2}
\newcommand{\multicolumnlof}{2}
\newcommand*{\immediateaddtocontents}[2]{}
```

File 242 **lwarp-musicography.sty**

§ 340 Package musicography

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg musicography musicography is patched for use by lwarp.

Images are used for the meter symbols, since the HTML fonts tend not to be the correct size. The HTML `alt` tag copies `C` and `3/2`, etc. Hashes are used for the meter images, which are then reused as necessary.

⚠ Note that browser support for musical symbols may be buggy. Copy/paste into a text editor works well.

for HTML output:

```
\LWR@ProvidesPackagePass{musicography}[2018/05/21]

\RenewDocumentCommand{\musSymbol}{ O{\musFont} m m m m }{%
\begin{lateximage}%
{#1\kern#2\raisebox{#3}{#5}\kern#4}%
\end{lateximage}%
}

\RenewDocumentCommand{\musStemmedNote}{ m }{%
\begin{lateximage}%
\musSymbol{0.05em}{0.5ex}{0.2em}{#1\musStem}%
\end{lateximage}%
}

\RenewDocumentCommand{\musFlaggedNote}{ m m }{%
\begin{lateximage}%
\musSymbol{0.05em}{0.5ex}{0pt}{#1\musStem}%
\musSymbol{0pt}{0pt}{0.9em}{#2}%
\end{lateximage}%
}
```

```
20
21 \RenewDocumentCommand{\musDottedNote}{ m }{%
22 \begin{lateximage}%
23 #1\musDot%
24 \end{lateximage}%
25 }
26
27 \RenewDocumentCommand{\musMeter}{ m m }{%
28 \begin{lateximage}*[#1/#2][#1#2]%
29 \musStack{#1}{#2}\kern0.05em%
30 \end{lateximage}%
31 }
32
33 \RenewDocumentCommand{\meterCplus}{ m }{%
34 \begin{lateximage}*[C#1]%
35     \meterC{}\kern-0.7pt#1%
36 \end{lateximage}%
37 }
38
39 \RenewDocumentCommand{\meterC}{}{%
40 \begin{lateximage}*[C]%
41 \musSymbolMeter{\symbol{83}}%
42 \end{lateximage}%
43 }
44
45 \RenewDocumentCommand{\meterCutC}{}{%
46 \begin{lateximage}*[C|]%
47 \musSymbolMeter{\symbol{82}}%
48 \end{lateximage}%
49 }
50
51 \RenewDocumentCommand{\meterCThreeTwo}{}{%
52 \begin{lateximage}*[C3/2]%
53 \meterCplus{\musStack{3}{2}}%
54 \end{lateximage}%
55 }
56
57 \RenewDocumentCommand{\musFlat}       {}{\HTMLunicode{266D}}
58 \RenewDocumentCommand{\musDoubleFlat} {}{\HTMLunicode{1D12B}}
59 \RenewDocumentCommand{\musSharp}      {}{\HTMLunicode{266F}}
60 \RenewDocumentCommand{\musDoubleSharp}{}{\HTMLunicode{1D12A}}
61 \RenewDocumentCommand{\musNatural}    {}{\HTMLunicode{266E}}
62
63 \RenewDocumentCommand{\musWhole}{}{\HTMLunicode{1D15D}}
64 \RenewDocumentCommand{\musHalf}{}{\HTMLunicode{1D15E}}
65 \RenewDocumentCommand{\musQuarter}{}{\HTMLunicode{1D15F}}
66 \RenewDocumentCommand{\musEighth}{}{\HTMLunicode{1D160}}
67 \RenewDocumentCommand{\musSixteenth}{}{\HTMLunicode{1D161}}
68
69 \RenewDocumentCommand{\musWholeDotted}{}{\HTMLunicode{1D15D}\HTMLunicode{1D16D}}
70 \RenewDocumentCommand{\musHalfDotted}{}{\HTMLunicode{1D15E}\HTMLunicode{1D16D}}
71 \RenewDocumentCommand{\musQuarterDotted}{}{\HTMLunicode{1D15F}\HTMLunicode{1D16D}}
72 \RenewDocumentCommand{\musEighthDotted}{}{\HTMLunicode{1D160}\HTMLunicode{1D16D}}
73 \RenewDocumentCommand{\musSixteenthDotted}{}{\HTMLunicode{1D161}\HTMLunicode{1D16D}}
```

File 243 **lwarp-nameauth.sty**

§ 341 Package

nameauth

(*Emulates or patches code by* Charles P. Schaum.)

Pkg nameauth nameauth is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nameauth}[2017/03/22]
```

lwarp formatting is inserted in the following.

```
\renewcommand*\@nameauth@Hook[1]
{%
  \if@nameauth@Lock
    \@nameauth@InHooktrue%
    \protected@edef\test{#1}%
    \expandafter\@nameauth@TestDot\expandafter{\test}%
    \if@nameauth@InAKA
      \if@nameauth@AlwaysFormat
        \@nameauth@FirstFormattrue%
      \else
        \unless\if@nameauth@AKAFormat
        \@nameauth@FirstFormatfalse\fi
      \fi
      \if@nameauth@MainFormat
        \if@nameauth@FirstFormat
          \bgroup\NamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\MainNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \else
        \if@nameauth@FirstFormat
          \bgroup\FrontNamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\FrontNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \fi
    \else
      \if@nameauth@AlwaysFormat
        \@nameauth@FirstFormattrue%
      \fi
      \if@nameauth@MainFormat
```

```
        \if@nameauth@FirstFormat
          \bgroup\NamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\MainNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \else
        \if@nameauth@FirstFormat
          \bgroup\FrontNamesFormat{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \else
          \bgroup\FrontNameHook{%
            \LWR@textcurrentcolor{\LWR@textcurrentfont{#1}}%    lwarp
          }\egroup%
        \fi
      \fi
    \fi
    \@nameauth@FirstFormatfalse%
    \@nameauth@InHookfalse%
  \fi
}
```

File 244 **lwarp-nameref.sty**

§ 342 Package nameref

Pkg nameref nameref is emulated by lwarp.

for HTML output: Discard all options for lwarp-nameref:

```
\PackageInfo{lwarp}{%
Using the lwarp HTML version of package ‘nameref’,\MessageBreak
and discarding options.\MessageBreak
(Not using \protect\ProvidesPackage, so that other packages\MessageBreak
do not attempt to patch lwarp’s version of ‘nameref’.)\MessageBreak
}
\DeclareOption*{}
\ProcessOptions\relax
```

File 245 **lwarp-natbib.sty**

§ 343 Package natbib

(*Emulates or patches code by* Patrick W. Daly.)

Pkg natbib natbib is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{natbib}[2010/09/13]
```

Replace math < and > with \textless and \textgreater:

A macro to compare:

```
\newcommand{\LWRNB@NAT@open}{$<$}
```

To patch \NAT@open and \NAT@close

```
\newcommand{\LWRNB@patchnatbibopenclose}{
\ifdefstrequal{\NAT@open}{\LWRNB@NAT@open}
{
    \renewcommand{\NAT@open}{\textless}
    \renewcommand{\NAT@close}{\textgreater}
}{}
}
```

Do it now in case angle was selected as an option:

```
\LWRNB@patchnatbibopenclose
```

Also patch \setcitestyle to patch after settings are made:

```
\let\LWRNB@origsetcitestyle\setcitestyle

\renewcommand{\setcitestyle}[1]{%
\LWRNB@origsetcitestyle{#1}%
\LWRNB@patchnatbibopenclose%
}
```

File 246 **lwarp-nccfancyhdr.sty**

§ 344 Package nccfancyhdr

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg nccfancyhdr nccfancyhdr is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nccfancyhdr}[2004/12/07]

\newcommand*{\headrulewidth}{}
\newcommand*{\footrulewidth}{}
\newcommand{\headstrutheight}{}
\newcommand{\footstrutheight}{}
\newcommand*{\headrule}{}
\newcommand*{\footrule}{}

\newdimen\headwidth
\newcommand*{\extendedheaders}{}
\newcommand*{\normalheaders}{}

```

```
\newcommand*{\fancyhead}[2][]{}
\newcommand*{\fancyfoot}[2][]{}
\newcommand*{\fancyhf}[2][]{}
\newcommand*{\fancypagestyle}[2]{}
\newcommand*{\lhead}[2][]{}
\newcommand*{\chead}[2][]{}
\newcommand*{\rhead}[2][]{}
\newcommand*{\lfoot}[2][]{}
\newcommand*{\cfoot}[2][]{}
\newcommand*{\rfoot}[2][]{}

\newcommand{\nouppercase}[1]{#1}

\NewDocumentCommand{\fancycenter}{o o m m m}{}

\NewDocumentCommand{\newpagestyle}{m o m}{}

\newcommand*{\iffloatpage}[2]{#2}
\newcommand*{\ifftopfloat}[2]{#2}
\newcommand*{\iffbotfloat}[2]{#2}
```

File 247 **lwarp-needspace.sty**

§ 345 Package needspace

(*Emulates or patches code by* Peter Wilson.)

Pkg needspace needspace is ignored.

for HTML output: Discard all options for lwarp-needspace:

```
\LWR@ProvidesPackageDrop{needspace}[2010/09/12]

\DeclareDocumentCommand{\needspace}{m}{}
\DeclareDocumentCommand{\Needspace}{s m}{}
```

File 248 **lwarp-nextpage.sty**

§ 346 Package nextpage

(*Emulates or patches code by* Peter Wilson.)

Pkg nextpage nextpage is ignored.

for HTML output: Discard all options for lwarp-nextpage.

```
\LWR@ProvidesPackageDrop{nextpage}[2009/09/03]

\DeclareDocumentCommand{\cleartoevenpage}{o}{}
\DeclareDocumentCommand{\movetoevenpage}{o}{}
\DeclareDocumentCommand{\cleartooddpage}{o}{}
```

```
\DeclareDocumentCommand{\movetooddpage}{o}{}
```

File 249 **lwarp-nfssext-cfr.sty**

§ 347 Package

nfssext-cfr

(*Emulates or patches code by* Clea F. Rees.)

Pkg nfssext-cfr nfssext-cfr is emulated in HTML, and used as-is in print output.

Results depend on the browser's font.

for HTML output:

```
\LWR@ProvidesPackagePass{nfssext-cfr}[2017/03/28]
```

Macros which are present in the lwarp core are commented out here.

```
\newrobustcmd{\LWR@HTML@lnstyle}{}
\newrobustcmd{\LWR@HTML@osstyle}{}
\newrobustcmd{\LWR@HTML@instyle}{}
\newrobustcmd{\LWR@HTML@sustyle}{}
\newrobustcmd{\LWR@HTML@swstyle}{}
\newrobustcmd{\LWR@HTML@pstyle}{}
\newrobustcmd{\LWR@HTML@tistyle}{}
\newrobustcmd{\LWR@HTML@ostyle}{\LWR@HTML@scshape}
\newrobustcmd{\LWR@HTML@postyle}{\LWR@HTML@scshape}
\newrobustcmd{\LWR@HTML@ltstyle}{}
\newrobustcmd{\LWR@HTML@ofstyle}{}
\newrobustcmd{\LWR@HTML@altstyle}{}
\newrobustcmd{\LWR@HTML@regstyle}{}
\newrobustcmd{\LWR@HTML@embossstyle}{}
\newrobustcmd{\LWR@HTML@ornamentalstyle}{}
\newrobustcmd{\LWR@HTML@qtstyle}{}
\newrobustcmd{\LWR@HTML@shstyle}{}
\newrobustcmd{\LWR@HTML@swashstyle}{}
\newrobustcmd{\LWR@HTML@tmstyle}{}
\newrobustcmd{\LWR@HTML@tvstyle}{\renewcommand*{\LWR@f@family}{tt}}
\newrobustcmd{\LWR@HTML@tstyle}{}
\newrobustcmd{\LWR@HTML@lstyle}{}
\newrobustcmd{\LWR@HTML@tlstyle}{}
\newrobustcmd{\LWR@HTML@plstyle}{}
\newrobustcmd{\LWR@HTML@tostyle}{\LWR@HTML@scshape}
% \newrobustcmd{\LWR@HTML@sishape}{}
\newrobustcmd{\LWR@HTML@olshape}{}
\newrobustcmd{\LWR@HTML@scolshape}{}
\newrobustcmd{\LWR@HTML@ushape}{}
\newrobustcmd{\LWR@HTML@scushape}{}
\newrobustcmd{\LWR@HTML@uishape}{\LWR@HTML@itshape}
\newrobustcmd{\LWR@HTML@rishape}{}
\newrobustcmd{\LWR@HTML@regwidth}{}
\newrobustcmd{\LWR@HTML@nwwidth}{}
\newrobustcmd{\LWR@HTML@cdwidth}{}
\newrobustcmd{\LWR@HTML@ecwidth}{}
\newrobustcmd{\LWR@HTML@ucwidth}{}
```

```
\newrobustcmd{\LWR@HTML@etwidth}{}
\newrobustcmd{\LWR@HTML@epwidth}{}
\newrobustcmd{\LWR@HTML@exwidth}{}
\newrobustcmd{\LWR@HTML@uxwidth}{}
\newrobustcmd{\LWR@HTML@mbweight}{\renewcommand*{\LWR@f@series}{md}}
\newrobustcmd{\LWR@HTML@dbweight}{\renewcommand*{\LWR@f@series}{bf}}
\newrobustcmd{\LWR@HTML@sbweight}{\renewcommand*{\LWR@f@series}{bf}}
% \newrobustcmd{\LWR@HTML@ebweight}{\renewcommand*{\LWR@f@series}{eb}}
\newrobustcmd{\LWR@HTML@ubweight}{\renewcommand*{\LWR@f@series}{eb}}
% \newrobustcmd{\LWR@HTML@lgweight}{\renewcommand*{\LWR@f@series}{lg}}
\newrobustcmd{\LWR@HTML@elweight}{\renewcommand*{\LWR@f@series}{lg}}
\newrobustcmd{\LWR@HTML@ulweight}{\renewcommand*{\LWR@f@series}{lg}}
% \newrobustcmd{\LWR@HTML@itshape}{}
% \newrobustcmd{\LWR@HTML@scshape}{}
% \newrobustcmd{\LWR@HTML@upshape}{}
\newrobustcmd{\LWR@HTML@dfshape}{}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \newrobustcmd{\LWR@HTML@swshape}{}
}

\newrobustcmd{\LWR@HTML@ornament}[1]{}

\LWR@formatted{lnstyle}
\LWR@formatted{osstyle}
\LWR@formatted{instyle}
\LWR@formatted{sustyle}
\LWR@formatted{swstyle}
\LWR@formatted{pstyle}
\LWR@formatted{tistyle}
\LWR@formatted{ostyle}
\LWR@formatted{postyle}
\LWR@formatted{ltstyle}
\LWR@formatted{ofstyle}
\LWR@formatted{altstyle}
\LWR@formatted{regstyle}
\LWR@formatted{embossstyle}
\LWR@formatted{ornamentalstyle}
\LWR@formatted{qtstyle}
\LWR@formatted{shstyle}
\LWR@formatted{swashstyle}
\LWR@formatted{tmstyle}
\LWR@formatted{tvstyle}
\LWR@formatted{tstyle}
\LWR@formatted{lstyle}
\LWR@formatted{tlstyle}
\LWR@formatted{plstyle}
\LWR@formatted{tostyle}
% \LWR@formatted{sishape}
\LWR@formatted{olshape}
\LWR@formatted{scolshape}
\LWR@formatted{ushape}
\LWR@formatted{scushape}
\LWR@formatted{uishape}
\LWR@formatted{rishape}
```

```
\LWR@formatted{regwidth}
\LWR@formatted{nwwidth}
\LWR@formatted{cdwidth}
\LWR@formatted{ecwidth}
\LWR@formatted{ucwidth}
\LWR@formatted{etwidth}
\LWR@formatted{epwidth}
\LWR@formatted{exwidth}
\LWR@formatted{uxwidth}
\LWR@formatted{mbweight}
\LWR@formatted{dbweight}
\LWR@formatted{sbweight}
% \LWR@formatted{ebweight}
\LWR@formatted{ubweight}
% \LWR@formatted{lgweight}
\LWR@formatted{elweight}
\LWR@formatted{ulweight}
% \LWR@formatted{itshape}
% \LWR@formatted{scshape}
% \LWR@formatted{upshape}
\LWR@formatted{dfshape}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \LWR@formatted{swshape}
}

\LWR@formatted{ornament}


\newcommand{\LWR@null@lnstyle}{}
\newcommand{\LWR@null@osstyle}{}
\newcommand{\LWR@null@instyle}{}
\newcommand{\LWR@null@sustyle}{}
\newcommand{\LWR@null@swstyle}{}
\newcommand{\LWR@null@pstyle}{}
\newcommand{\LWR@null@tistyle}{}
\newcommand{\LWR@null@ostyle}{}
\newcommand{\LWR@null@postyle}{}
\newcommand{\LWR@null@ltstyle}{}
\newcommand{\LWR@null@ofstyle}{}
\newcommand{\LWR@null@altstyle}{}
\newcommand{\LWR@null@regstyle}{}
\newcommand{\LWR@null@embossstyle}{}
\newcommand{\LWR@null@ornamentalstyle}{}
\newcommand{\LWR@null@qtstyle}{}
\newcommand{\LWR@null@shstyle}{}
\newcommand{\LWR@null@swashstyle}{}
\newcommand{\LWR@null@tmstyle}{}
\newcommand{\LWR@null@tvstyle}{}
\newcommand{\LWR@null@tstyle}{}
\newcommand{\LWR@null@lstyle}{}
\newcommand{\LWR@null@tlstyle}{}
\newcommand{\LWR@null@plstyle}{}
\newcommand{\LWR@null@tostyle}{}
% \newcommand{\LWR@null@sishape}{}
```

```
\newcommand{\LWR@null@olshape}{}
\newcommand{\LWR@null@scolshape}{}
\newcommand{\LWR@null@ushape}{}
\newcommand{\LWR@null@scushape}{}
\newcommand{\LWR@null@uishape}{}
\newcommand{\LWR@null@rishape}{}
\newcommand{\LWR@null@regwidth}{}
\newcommand{\LWR@null@nwwidth}{}
\newcommand{\LWR@null@cdwidth}{}
\newcommand{\LWR@null@ecwidth}{}
\newcommand{\LWR@null@ucwidth}{}
\newcommand{\LWR@null@etwidth}{}
\newcommand{\LWR@null@epwidth}{}
\newcommand{\LWR@null@exwidth}{}
\newcommand{\LWR@null@uxwidth}{}
\newcommand{\LWR@null@mbweight}{}
\newcommand{\LWR@null@dbweight}{}
\newcommand{\LWR@null@sbweight}{}
% \newcommand{\LWR@null@ebweight}{}
\newcommand{\LWR@null@ubweight}{}
% \newcommand{\LWR@null@lgweight}{}
\newcommand{\LWR@null@elweight}{}
\newcommand{\LWR@null@ulweight}{}
% \newcommand{\LWR@null@itshape}{}
% \newcommand{\LWR@null@scshape}{}
% \newcommand{\LWR@null@upshape}{}
\newcommand{\LWR@null@dfshape}{}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \newcommand{\LWR@null@swshape}{}
}

\newcommand{\LWR@null@ornament}[1]{}

\appto{\LWR@nullfonts}{%
\LetLtxMacro\lnstyle\LWR@null@lnstyle%
\LetLtxMacro\osstyle\LWR@null@osstyle%
\LetLtxMacro\instyle\LWR@null@instyle%
\LetLtxMacro\sustyle\LWR@null@sustyle%
\LetLtxMacro\swstyle\LWR@null@swstyle%
\LetLtxMacro\pstyle\LWR@null@pstyle%
\LetLtxMacro\tistyle\LWR@null@tistyle%
\LetLtxMacro\ostyle\LWR@null@ostyle%
\LetLtxMacro\postyle\LWR@null@postyle%
\LetLtxMacro\ltstyle\LWR@null@ltstyle%
\LetLtxMacro\ofstyle\LWR@null@ofstyle%
\LetLtxMacro\altstyle\LWR@null@altstyle%
\LetLtxMacro\regstyle\LWR@null@regstyle%
\LetLtxMacro\embossstyle\LWR@null@embossstyle%
\LetLtxMacro\ornamentalstyle\LWR@null@ornamentalstyle%
\LetLtxMacro\qtstyle\LWR@null@qtstyle%
\LetLtxMacro\shstyle\LWR@null@shstyle%
\LetLtxMacro\swashstyle\LWR@null@swashstyle%
\LetLtxMacro\tmstyle\LWR@null@tmstyle%
\LetLtxMacro\tvstyle\LWR@null@tvstyle%
```

```
\LetLtxMacro\tstyle\LWR@null@tstyle%
\LetLtxMacro\lstyle\LWR@null@lstyle%
\LetLtxMacro\tlstyle\LWR@null@tlstyle%
\LetLtxMacro\plstyle\LWR@null@plstyle%
\LetLtxMacro\tostyle\LWR@null@tostyle%
% \LetLtxMacro\sishape\LWR@null@sishape
\LetLtxMacro\olshape\LWR@null@olshape%
\LetLtxMacro\scolshape\LWR@null@scolshape%
\LetLtxMacro\ushape\LWR@null@ushape%
\LetLtxMacro\scushape\LWR@null@scushape%
\LetLtxMacro\uishape\LWR@null@uishape%
\LetLtxMacro\rishape\LWR@null@rishape%
\LetLtxMacro\regwidth\LWR@null@regwidth%
\LetLtxMacro\nwwidth\LWR@null@nwwidth%
\LetLtxMacro\cdwidth\LWR@null@cdwidth%
\LetLtxMacro\ecwidth\LWR@null@ecwidth%
\LetLtxMacro\ucwidth\LWR@null@ucwidth%
\LetLtxMacro\etwidth\LWR@null@etwidth%
\LetLtxMacro\epwidth\LWR@null@epwidth%
\LetLtxMacro\exwidth\LWR@null@exwidth%
\LetLtxMacro\uxwidth\LWR@null@uxwidth%
\LetLtxMacro\mbweight\LWR@null@mbweight%
\LetLtxMacro\dbweight\LWR@null@dbweight%
\LetLtxMacro\sbweight\LWR@null@sbweight%
% \LetLtxMacro\ebweight\LWR@null@ebweight%
\LetLtxMacro\ubweight\LWR@null@ubweight%
% \LetLtxMacro\lgweight\LWR@null@lgweight%
\LetLtxMacro\elweight\LWR@null@elweight%
\LetLtxMacro\ulweight\LWR@null@ulweight%
% \LetLtxMacro\itshape\LWR@null@itshape%
% \LetLtxMacro\scshape\LWR@null@scshape%
% \LetLtxMacro\upshape\LWR@null@upshape%
\LetLtxMacro\dfshape\LWR@null@dfshape%
\LetLtxMacro\swshape\LWR@null@swshape%
\LetLtxMacro\ornament\LWR@null@ornament%
}

\newrobustcmd{\LWR@HTML@textln}[1]{#1}
\newrobustcmd{\LWR@HTML@textos}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@textin}[1]{#1}
\newrobustcmd{\LWR@HTML@textsu}[1]{#1}
% \newrobustcmd{\LWR@HTML@textsi}[1]{#1}
\newrobustcmd{\LWR@HTML@textdf}[1]{#1}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \newrobustcmd{\LWR@HTML@textsw}[1]{#1}
}

\newrobustcmd{\LWR@HTML@textti}[1]{#1}
\newrobustcmd{\LWR@HTML@textlt}[1]{#1}
\newrobustcmd{\LWR@HTML@textof}[1]{#1}
\newrobustcmd{\LWR@HTML@textalt}[1]{#1}
\newrobustcmd{\LWR@HTML@textreg}[1]{#1}
\newrobustcmd{\LWR@HTML@emboss}[1]{#1}
\newrobustcmd{\LWR@HTML@textorn}[1]{#1}
```

```
\newrobustcmd{\LWR@HTML@textqt}[1]{#1}
\newrobustcmd{\LWR@HTML@textsh}[1]{#1}
\newrobustcmd{\LWR@HTML@texttm}[1]{#1}
\newrobustcmd{\LWR@HTML@texttv}[1]{\texttt{#1}}
\newrobustcmd{\LWR@HTML@textl}[1]{#1}
\newrobustcmd{\LWR@HTML@texto}[1]{#1}
\newrobustcmd{\LWR@HTML@textp}[1]{#1}
\newrobustcmd{\LWR@HTML@textt}[1]{#1}
\newrobustcmd{\LWR@HTML@textpl}[1]{#1}
\newrobustcmd{\LWR@HTML@textpo}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@texttl}[1]{#1}
\newrobustcmd{\LWR@HTML@textto}[1]{\textsc{#1}}
\newrobustcmd{\LWR@HTML@textol}[1]{#1}
\newrobustcmd{\LWR@HTML@textswash}[1]{#1}
\newrobustcmd{\LWR@HTML@textu}[1]{#1}
\newrobustcmd{\LWR@HTML@textscu}[1]{#1}
\newrobustcmd{\LWR@HTML@textui}[1]{\LWR@HTML@textit{#1}}
\newrobustcmd{\LWR@HTML@textri}[1]{#1}
\newrobustcmd{\LWR@HTML@textnw}[1]{#1}
\newrobustcmd{\LWR@HTML@textcd}[1]{#1}
\newrobustcmd{\LWR@HTML@textec}[1]{#1}
\newrobustcmd{\LWR@HTML@textuc}[1]{#1}
\newrobustcmd{\LWR@HTML@textet}[1]{#1}
\newrobustcmd{\LWR@HTML@textep}[1]{#1}
\newrobustcmd{\LWR@HTML@textex}[1]{#1}
\newrobustcmd{\LWR@HTML@textux}[1]{#1}
\newrobustcmd{\LWR@HTML@textrw}[1]{#1}
\newrobustcmd{\LWR@HTML@textmb}[1]{\textmd{#1}}
\newrobustcmd{\LWR@HTML@textdb}[1]{\textbf{#1}}
\newrobustcmd{\LWR@HTML@textsb}[1]{\textbf{#1}}
% \newrobustcmd{\LWR@HTML@texteb}[1]{#1}
\newrobustcmd{\LWR@HTML@textub}[1]{\texteb{#1}}
% \newrobustcmd{\LWR@HTML@textlg}[1]{#1}
\newrobustcmd{\LWR@HTML@textel}[1]{\textlg{#1}}
\newrobustcmd{\LWR@HTML@textul}[1]{\textlg{#1}}

\LWR@formatted{textln}
\LWR@formatted{textos}
\LWR@formatted{textin}
\LWR@formatted{textsu}
% \LWR@formatted{textsi}
\LWR@formatted{textdf}
\LWR@formatted{textsw}
\LWR@formatted{textti}
\LWR@formatted{textlt}
\LWR@formatted{textof}
\LWR@formatted{textalt}
\LWR@formatted{textreg}
\LWR@formatted{emboss}
\LWR@formatted{textorn}
\LWR@formatted{textqt}
\LWR@formatted{textsh}
\LWR@formatted{texttm}
\LWR@formatted{texttv}
\LWR@formatted{textl}
```

```
\LWR@formatted{texto}
\LWR@formatted{textp}
\LWR@formatted{textt}
\LWR@formatted{textpl}
\LWR@formatted{textpo}
\LWR@formatted{texttl}
\LWR@formatted{textto}
\LWR@formatted{textol}
\LWR@formatted{textswash}
\LWR@formatted{textu}
\LWR@formatted{textscu}
\LWR@formatted{textui}
\LWR@formatted{textri}
\LWR@formatted{textnw}
\LWR@formatted{textcd}
\LWR@formatted{textec}
\LWR@formatted{textuc}
\LWR@formatted{textet}
\LWR@formatted{textep}
\LWR@formatted{textex}
\LWR@formatted{textux}
\LWR@formatted{textrw}
\LWR@formatted{textmb}
\LWR@formatted{textdb}
\LWR@formatted{textsb}
% \LWR@formatted{texteb}
\LWR@formatted{textub}
% \LWR@formatted{textlg}
\LWR@formatted{textel}
\LWR@formatted{textul}

\newrobustcmd{\LWR@null@textln}[1]{#1}
\newrobustcmd{\LWR@null@textos}[1]{#1}
\newrobustcmd{\LWR@null@textin}[1]{#1}
\newrobustcmd{\LWR@null@textsu}[1]{#1}
% \newrobustcmd{\LWR@null@textsi}[1]{#1}
\newrobustcmd{\LWR@null@textdf}[1]{#1}

\ifdef{\LWR@HTML@swshape}{}{% duplicated by fontaxes
    \newrobustcmd{\LWR@null@textsw}[1]{#1}
}

\newrobustcmd{\LWR@null@textti}[1]{#1}
\newrobustcmd{\LWR@null@textlt}[1]{#1}
\newrobustcmd{\LWR@null@textof}[1]{#1}
\newrobustcmd{\LWR@null@textalt}[1]{#1}
\newrobustcmd{\LWR@null@textreg}[1]{#1}
\newrobustcmd{\LWR@null@emboss}[1]{#1}
\newrobustcmd{\LWR@null@textorn}[1]{#1}
\newrobustcmd{\LWR@null@textqt}[1]{#1}
\newrobustcmd{\LWR@null@textsh}[1]{#1}
\newrobustcmd{\LWR@null@texttm}[1]{#1}
\newrobustcmd{\LWR@null@texttv}[1]{#1}
\newrobustcmd{\LWR@null@textl}[1]{#1}
\newrobustcmd{\LWR@null@texto}[1]{#1}
```

```
\newrobustcmd{\LWR@null@textp}[1]{#1}
\newrobustcmd{\LWR@null@textt}[1]{#1}
\newrobustcmd{\LWR@null@textpl}[1]{#1}
\newrobustcmd{\LWR@null@textpo}[1]{#1}
\newrobustcmd{\LWR@null@texttl}[1]{#1}
\newrobustcmd{\LWR@null@textto}[1]{#1}
\newrobustcmd{\LWR@null@textol}[1]{#1}
\newrobustcmd{\LWR@null@textswash}[1]{#1}
\newrobustcmd{\LWR@null@textu}[1]{#1}
\newrobustcmd{\LWR@null@textscu}[1]{#1}
\newrobustcmd{\LWR@null@textui}[1]{#1}
\newrobustcmd{\LWR@null@textri}[1]{#1}
\newrobustcmd{\LWR@null@textnw}[1]{#1}
\newrobustcmd{\LWR@null@textcd}[1]{#1}
\newrobustcmd{\LWR@null@textec}[1]{#1}
\newrobustcmd{\LWR@null@textuc}[1]{#1}
\newrobustcmd{\LWR@null@textet}[1]{#1}
\newrobustcmd{\LWR@null@textep}[1]{#1}
\newrobustcmd{\LWR@null@textex}[1]{#1}
\newrobustcmd{\LWR@null@textux}[1]{#1}
\newrobustcmd{\LWR@null@textrw}[1]{#1}
\newrobustcmd{\LWR@null@textmb}[1]{#1}
\newrobustcmd{\LWR@null@textdb}[1]{#1}
\newrobustcmd{\LWR@null@textsb}[1]{#1}
% \newrobustcmd{\LWR@null@texteb}[1]{#1}
\newrobustcmd{\LWR@null@textub}[1]{#1}
% \newrobustcmd{\LWR@null@textlg}[1]{#1}
\newrobustcmd{\LWR@null@textel}[1]{#1}
\newrobustcmd{\LWR@null@textul}[1]{#1}

\appto{\LWR@nullfonts}{%
\LetLtxMacro\textln\LWR@null@textln%
\LetLtxMacro\textos\LWR@null@textos%
\LetLtxMacro\textin\LWR@null@textin%
\LetLtxMacro\textsu\LWR@null@textsu%
% \LetLtxMacro\textsi\LWR@null@textsi%
\LetLtxMacro\textdf\LWR@null@textdf%
\LetLtxMacro\textsw\LWR@null@textsw%
\LetLtxMacro\textti\LWR@null@textti%
\LetLtxMacro\textlt\LWR@null@textlt%
\LetLtxMacro\textof\LWR@null@textof%
\LetLtxMacro\textalt\LWR@null@textalt%
\LetLtxMacro\textreg\LWR@null@textreg%
\LetLtxMacro\emboss\LWR@null@emboss%
\LetLtxMacro\textorn\LWR@null@textorn%
\LetLtxMacro\textqt\LWR@null@textqt%
\LetLtxMacro\textsh\LWR@null@textsh%
\LetLtxMacro\texttm\LWR@null@texttm%
\LetLtxMacro\texttv\LWR@null@texttv%
\LetLtxMacro\textl\LWR@null@textl%
\LetLtxMacro\texto\LWR@null@texto%
\LetLtxMacro\textp\LWR@null@textp%
\LetLtxMacro\textt\LWR@null@textt%
\LetLtxMacro\textpl\LWR@null@textpl%
\LetLtxMacro\textpo\LWR@null@textpo%
```

```
\LetLtxMacro\texttl\LWR@null@texttl%
\LetLtxMacro\textto\LWR@null@textto%
\LetLtxMacro\textol\LWR@null@textol%
\LetLtxMacro\textswash\LWR@null@textswash%
\LetLtxMacro\textu\LWR@null@textu%
\LetLtxMacro\textscu\LWR@null@textscu%
\LetLtxMacro\textui\LWR@null@textui%
\LetLtxMacro\textri\LWR@null@textri%
\LetLtxMacro\textnw\LWR@null@textnw%
\LetLtxMacro\textcd\LWR@null@textcd%
\LetLtxMacro\textec\LWR@null@textec%
\LetLtxMacro\textuc\LWR@null@textuc%
\LetLtxMacro\textet\LWR@null@textet%
\LetLtxMacro\textep\LWR@null@textep%
\LetLtxMacro\textex\LWR@null@textex%
\LetLtxMacro\textux\LWR@null@textux%
\LetLtxMacro\textrw\LWR@null@textrw%
\LetLtxMacro\textmb\LWR@null@textmb%
\LetLtxMacro\textdb\LWR@null@textdb%
\LetLtxMacro\textsb\LWR@null@textsb%
% \LetLtxMacro\texteb\LWR@null@texteb%
\LetLtxMacro\textub\LWR@null@textub%
% \LetLtxMacro\textlg\LWR@null@textlg%
\LetLtxMacro\textel\LWR@null@textel%
\LetLtxMacro\textul\LWR@null@textul%
}

\providecommand*{\zeroslash}{0}
\newrobustcmd*{\LWR@HTML@zeroslash}{0}
\LWR@formatted{zeroslash}
```

File 250 **lwarp-nicefrac.sty**

§ 348 Package nicefrac

(*Emulates or patches code by* Axel Reichert.)

Pkg nicefrac nicefrac is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{nicefrac}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@@UnitsNiceFrac}[3][]{%
    {% localize font selection
        #1{%
            \LWR@textcurrentfont{%
                \InlineClass{numerator}{#2}%
                /%
                \InlineClass{denominator}{#3}%
            }%
        }%
    }%
}

```

```
\LWR@formatted{@UnitsNiceFrac}

\DeclareRobustCommand*{\LWR@HTML@@UnitsUglyFrac}[3][]{%
    {% localize font selection
        #1{\LWR@textcurrentfont{#2/#3}}%
    }%
}

\LWR@formatted{@UnitsUglyFrac}
```

For Mathjax:

```
\CustomizeMathJax{\newcommand{\nicefrac}[3][]{#2/#3}}
```

File 251 **lwarp-niceframe.sty**

§ 349 Package niceframe

Pkg niceframe niceframe is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{niceframe}% the original date is in yyyy/dd/mm format

\newcommand{\LWR@niceframe}[3]{
    \setlength{\LWR@templengthone}{#1}
    \begin{BlockClass}[max-width:\LWR@printlength{\LWR@templengthone}]{#3}
    #2
    \end{BlockClass}
}

\newcommand{\niceframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{niceframe}}
\newcommand{\curlyframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{curlyframe}}
\newcommand{\artdecoframe}[2][\textwidth]{\LWR@niceframe{#1}{#2}{artdecoframe}}

\newcommand{\generalframe}[9]{\LWR@niceframe{\textwidth}{#9}{generalframe}}
```

File 252 **lwarp-nomencl.sty**

§ 350 Package nomencl

(*Emulates or patches code by* Boris Veytsman, Bernd Schandl, Lee Netherton, CV Radhakrishnan.)

Pkg nomencl nomencl is patched for use by lwarp.

To process the HTML nomenclature:

```
makeindex <project>_html.nlo -s nomencl.ist -o <project>_html.nls
```

for HTML output:

```
\LWR@ProvidesPackagePass{nomencl}[2005/09/22]
```

\BaseJobname is added to the label in case xr or xr-hyper are used.

```
\def\@@@nomenclature[#1]#2#3{%
 \def\@tempa{#2}\def\@tempb{#3}%
 \protected@write\@nomenclaturefile{}%
  {\string\nomenclatureentry{#1\nom@verb\@tempa @[{\nom@verb\@tempa}]%
      \begingroup\nom@verb\@tempb\protect\nomeqref{\theequation}%
        |nompageref}{\theLWR@previousautopagelabel}}%   lwarp
 \endgroup
 \@esphack}

\renewcommand*{\pagedeclaration}[1]{, \nameref{\BaseJobname-autopage-#1}}%
```

File 253 **lwarp-nonfloat.sty**

§ 351 Package nonfloat

(*Emulates or patches code by* Kai Rascher.)

Pkg nonfloat nonfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonfloat}[1999/07/05]
```

```
\LetLtxMacro\topcaption\caption
\newcommand{\figcaption}{\def\@captype{figure}\caption}
\newcommand{\tabcaption}{\def\@captype{table}\topcaption}
\newenvironment{narrow}[2]{}{}
```

File 254 **lwarp-nonumonpart.sty**

§ 352 Package nonumonpart

Pkg nonumonpart nonumonpart is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nonumonpart}[2011/04/15]
```

File 255 **lwarp-nopageno.sty**

§ 353 Package nopageno

Pkg nopageno nopageno is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{nopageno}[1989/01/01]
```

File 256 **lwarp-notes.sty**

§ 354 Package notes

Pkg notes notes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{notes}[2002/10/29]

\newcommand*{\LWR@notes@onenote}[2]{%
\newenvironment{#1}
    {
        \BlockClass{notes#1}
        \begin{BlockClass}{notesicon}\textcircled{~#2~}\end{BlockClass}
        \BlockClass{notescontents}
    }
    {\endBlockClass\endBlockClass}
}

\LWR@notes@onenote{importantnote}{!}

\LWR@notes@onenote{warningnote}{--}

\LWR@notes@onenote{informationnote}{i}
```

File 257 **lwarp-notespages.sty**

§ 355 Package notespages

Pkg notespages notespages is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{notespages}[2016/08/21]

\newcommand*{\npnotesname}{}
\newcommand*{\npnotestext}{}
\newcommand*{\remainingtextheight}{}
\newdimen\remainingtextheight
\newcommand*{\notestitletext}{}
\newcommand*{\notesareatext}{}
\newcommand*{\npnpinfo}[1]{}
\newcommand*{\tracingnpmarks}{}
\newcommand*{\notespage}[1][]{}
\newcommand*{\notespages}[1][]{}
\newcommand*{\notesfill}[1][]{}
\newcommand*{\setnotespages}[1]{}
\newcommand*{\definenotesoption}[2]{}
\newcommand{\definenotesstyle}[2]{}
\newcommand{\definetitlestyle}[2]{}
\newcommand{\nppatchchapter}[1]{}
```

```
\newcommand{\npunpatchchapter}{}
```

File 258 **lwarp-nowidow.sty**

§ 356 Package nowidow

(*Emulates or patches code by* Raphaël Pinson.)

Pkg nowidow nowidow is ignored.

Discard all options for lwarp-nowidow:

for HTML output:

```
\LWR@ProvidesPackageDrop{nowidow}[2011/09/20]
```

\nowidow [⟨*lines*⟩]

\setnowidow [⟨*lines*⟩]

```
\newcommand*{\nowidow}[1][]{}
\newcommand*{\setnowidow}[1][]{}
```

\noclub [⟨*lines*⟩]

\setnoclub [⟨*lines*⟩]

```
\newcommand*{\noclub}[1][]{}
\newcommand*{\setnoclub}[1][]{}
```

File 259 **lwarp-ntheorem.sty**

§ 357 Package ntheorem

(*Emulates or patches code by* Wolfgang May, Andreas Schedler.)

Pkg ntheorem ntheorem is patched for use by lwarp.

Table 15: Ntheorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader<style>

where <theoremstyle> is plain, break, etc.

§ 357.1 Limitations

⚠ Font control

This conversion is not total. Font control is via css, and the custom LaTeX font settings are ignored.

⚠ Equation numbering

ntheorem has a bug with equation numbering in $\mathcal{AMS}$ environmentswhen the option `thref` is used. lwarp does not share this bug, so equations with `\split`, etc, are numbered correctly with lwarp's HTML output, but not with the print output. It is recommended to use cleveref instead of ntheorem's `thref` option.

§ 357.2 Options

Options `amsthm` or `standard` choose which set of theorems and proofs to initialize.

⚠ Disabled options

The options `thmmarks` and `amsmath` are disabled, since they heavily modify the underlying math code. Theorem marks are emulated. The AMS-math modifications are not done.

Option `thref` is disabled because cleveref functions are used instead. `\thref` is emulated.

Option `hyperref` is disabled because lwarp emulated hyperref.

for HTML output:

Some disabled options:

```
\DeclareOption{thref}{}


\newbool{LWR@ntheoremmarks}
\boolfalse{LWR@ntheoremmarks}

\DeclareOption{thmmarks}{
\booltrue{LWR@ntheoremmarks}
\newif\ifsetendmark\setendmarktrue
}


\newbool{LWR@ntheoremamsthm}
\boolfalse{LWR@ntheoremamsthm}

\DeclareOption{amsthm}{\booltrue{LWR@ntheoremamsthm}}


\DeclareOption{amsmath}{}
\DeclareOption{hyperref}{}

\LWR@ProvidesPackagePass{ntheorem}[2011/08/15]
```

§ 357.3 Remembering the theorem style

Storage for the style being used for new theorems.

```
\newcommand{\LWR@newtheoremstyle}{plain}

\AtBeginDocument{
\@ifpackageloaded{cleveref}{
\gdef\@thm#1#2#3{%
   \if@thmmarks
     \stepcounter{end\InTheoType ctr}%
   \fi
   \renewcommand{\InTheoType}{#1}%
   \if@thmmarks
     \stepcounter{curr#1ctr}%
     \setcounter{end#1ctr}{0}%
   \fi
   \refstepcounter[#1]{#2}%  <<< cleveref modification
   \theorem@prework
    \LWR@forcenewpage% lwarp
    \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
   \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
   \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
     \ifthm@inframe
       \thm@topsep\theoreminframepreskipamount
       \thm@topsepadd\theoreminframepostskipamount
      \else
       \thm@topsep\theorempreskipamount
       \thm@topsepadd\theorempostskipamount
      \fi
    \else% oldframeskips
      \thm@topsep\theorempreskipamount
      \thm@topsepadd \theorempostskipamount
      \ifvmode\advance\thm@topsepadd\partopsep\fi
   \fi
   \@topsep\thm@topsep
   \@topsepadd\thm@topsepadd
   \advance\linewidth -\theorem@indent
   \advance\linewidth -\theorem@rightindent
   \advance\@totalleftmargin \theorem@indent
   \parshape \@ne \@totalleftmargin \linewidth
   \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}{% not @ifpackageloaded{cleveref}
\gdef\@thm#1#2#3{%
   \if@thmmarks
     \stepcounter{end\InTheoType ctr}%
   \fi
   \renewcommand{\InTheoType}{#1}%
   \if@thmmarks
     \stepcounter{curr#1ctr}%
     \setcounter{end#1ctr}{0}%
   \fi
   \refstepcounter{#2}%
   \theorem@prework
```

```
    \LWR@forcenewpage% lwarp
    \BlockClass{theorembody#1}%\LWR@thisthmstyle% lwarp
  \trivlist % latex's \trivlist, calling latex's \@trivlist unchanged
  \ifuse@newframeskips  % cf. latex.ltx for topsepadd: \@trivlist
    \ifthm@inframe
      \thm@topsep\theoreminframepreskipamount
      \thm@topsepadd\theoreminframepostskipamount
    \else
      \thm@topsep\theorempreskipamount
      \thm@topsepadd\theorempostskipamount
    \fi
   \else% oldframeskips
     \thm@topsep\theorempreskipamount
     \thm@topsepadd \theorempostskipamount
     \ifvmode\advance\thm@topsepadd\partopsep\fi
  \fi
  \@topsep\thm@topsep
  \@topsepadd\thm@topsepadd
  \advance\linewidth -\theorem@indent
  \advance\linewidth -\theorem@rightindent
  \advance\@totalleftmargin \theorem@indent
  \parshape \@ne \@totalleftmargin \linewidth
  \@ifnextchar[{\@ythm{#1}{#2}{#3}}{\@xthm{#1}{#2}{#3}}
}
}
}% AtBeginDocument
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
  \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle `#1'. Using `plain'}%
          \theorem@style{plain}
            \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
            }%
     {
       \theorem@style{#1}
       \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
       }
}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```

\gdef\@xnthm#1#2[#3]{%
 \ifthm@tempif
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \expandafter\@ifundefined{c@#1}%
       {\@definecounter{#1}}{}%
    \@newctr{#1}[#3]%
    \expandafter\xdef\csname the#1\endcsname{%
      \expandafter\noexpand\csname the#3\endcsname \@thmcountersep
         {\noexpand\csname\the\theoremnumbering\endcsname{#1}}}%
    \expandafter\gdef\csname mkheader@#1\endcsname
```

```
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@ynthm#1#2{%
  \ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \expandafter\@ifundefined{c@#1}%
        {\@definecounter{#1}}{}%
     \expandafter\xdef\csname the#1\endcsname
        {\noexpand\csname\the\theoremnumbering\endcsname{#1}}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
        \@thm{#1}{#1}{#2}
        }%
     \global\@namedef{end#1}{\@endtheorem}
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi
}

\gdef\@othm#1[#2]#3{%
  \@ifundefined{c@#2}{\@nocounterr{#2}}%
   {\ifthm@tempif
     \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
     \global\@namedef{the#1}{\@nameuse{the#2}}%
     \expandafter\protected@xdef\csname num@addtheoremline#1\endcsname{%
               \noexpand\@num@addtheoremline{#1}{#3}}%
     \expandafter\protected@xdef\csname nonum@addtheoremline#1\endcsname{%
               \noexpand\@nonum@addtheoremline{#1}{#3}}%
    \theoremkeyword{#3}%
    \expandafter\protected@xdef\csname #1Keyword\endcsname
             {\the\theoremkeyword}%
     \expandafter\gdef\csname mkheader@#1\endcsname
       {\csname setparms@#1\endcsname
                \@thm{#1}{#2}{#3}
        }%
     \global\@namedef{end#1}{\@endtheorem}
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
  \fi}
}
```

§ 357.4 HTML cross-referencing

Mimics a float by incrementing the float counter and generating an HTML anchor. These are used for list-of-theorem cross-references.

```
\newcommand{\LWR@inctheorem}{%
\addtocounter{LWR@thisautoid}{1}%
\LWR@stoppars%
\LWR@htmltag{a id="\LWR@print@mbox{autoid-\arabic{LWR@thisautoid}}"}\LWR@htmltag{/a}%
\LWR@startpars%
```

```
}
```

§ 357.5 \newtheoremstyle

The following are patched for css.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader<style>`.

```
\gdef\newtheoremstyle#1#2#3{%
  \expandafter\@ifundefined{th@#1}%
   {\expandafter\gdef\csname th@#1\endcsname{%
    \def\@begintheorem####1####2{%
    \LWR@inctheorem% lwarp
    #2}%
    \def\@opargbegintheorem####1####2####3{%
    \LWR@inctheorem% lwarp
    #3}%
}%
}%
{\PackageError{\basename}{Theorem style #1 already defined}\@eha}
}
```

§ 357.6 Standard styles

```
\renewtheoremstyle{plain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}

\renewtheoremstyle{break}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ ##2\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}%
        {##1\ ##2\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{change}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderchange}{##2\ ##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{changebreak}%
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\theorem@separator}\newline
    ]}%
```

```
  {\item[
        \InlineClass{theoremheaderchangebreak}%
            {##2\ ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{margin}%
  {\item[
        \InlineClass{theoremheadermargin}{##2 \qquad ##1\theorem@separator}
    ]}%
  {\item[
      \InlineClass{theoremheadermargin}{##2 \qquad ##1\ (##3)\theorem@separator}
    ]}

\renewtheoremstyle{marginbreak}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheadermarginbreak}%
        {##2 \qquad ##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{nonumberplain}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\theorem@separator}]}%
  {\item[
    \InlineClass{theoremheaderplain}{##1\ (##3)\theorem@separator}]}

\renewtheoremstyle{nonumberbreak}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\theorem@separator}\newline
    ]}%
  {\item[
    \InlineClass{theoremheaderbreak}{##1\ (##3)\theorem@separator}\newline
    ]}

\renewtheoremstyle{empty}%
  {\item[]}%
  {\item[
    \InlineClass{theoremheaderplain}{##3}]}

\renewtheoremstyle{emptybreak}%
  {\item[]}%
  {\item[
    \InlineClass{theoremheaderplain}{##3}] \ \newline}
```

§ 357.7 Additional objects

The following manually adjust the css for the standard configuration objects which are not a purely plain style:

```
\ifbool{LWR@ntheoremamsthm}{}{%
```

Upright text via CSS:

```
    \newtheoremstyle{plainupright}%
    {\item[
        \InlineClass{theoremheaderplain}{##1\ ##2\theorem@separator}]}%
    {\item[
        \InlineClass{theoremheaderplain}{##1\ ##2\ (##3)\theorem@separator}]}
```

Upright text and small caps header via CSS:

```
    \newtheoremstyle{nonumberplainuprightsc}%
    {\item[
        \InlineClass{theoremheadersc}{##1\theorem@separator}]}%
    {\item[
        \InlineClass{theoremheadersc}{##1\ (##3)\theorem@separator}]}
}% not amsthm
```

§ 357.8 Renewed standard configuration

The following standard configuration is renewed using the new CSS:

```
\ifbool{LWR@ntheoremamsthm}{}{%


\ifx\thm@usestd\@undefined
\else
    \theoremnumbering{arabic}
    \theoremstyle{plain}
    \RequirePackage{latexsym}
    \theoremsymbol{\Box}
    \theorembodyfont{\itshape}
    \theoremheaderfont{\normalfont\bfseries}
    \theoremseparator{}
    \renewtheorem{Theorem}{Theorem}
    \renewtheorem{theorem}{Theorem}
    \renewtheorem{Satz}{Satz}
    \renewtheorem{satz}{Satz}
    \renewtheorem{Proposition}{Proposition}
    \renewtheorem{proposition}{Proposition}
    \renewtheorem{Lemma}{Lemma}
    \renewtheorem{lemma}{Lemma}
    \renewtheorem{Korollar}{Korollar}
    \renewtheorem{korollar}{Korollar}
    \renewtheorem{Corollary}{Corollary}
    \renewtheorem{corollary}{Corollary}

    \theoremstyle{plainupright}
    \theorembodyfont{\upshape}
    \theoremsymbol{\HTMLunicode{25A1}}% UTF-8 white box
    \renewtheorem{Example}{Example}
    \renewtheorem{example}{Example}
    \renewtheorem{Beispiel}{Beispiel}
    \renewtheorem{beispiel}{Beispiel}
    \renewtheorem{Bemerkung}{Bemerkung}
    \renewtheorem{bemerkung}{Bemerkung}
```

```
    \renewtheorem{Anmerkung}{Anmerkung}
    \renewtheorem{anmerkung}{Anmerkung}
    \renewtheorem{Remark}{Remark}
    \renewtheorem{remark}{Remark}
    \renewtheorem{Definition}{Definition}
    \renewtheorem{definition}{Definition}

    \theoremstyle{nonumberplainuprightsc}
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \renewtheorem{Proof}{Proof}
    \renewtheorem{proof}{Proof}
    \renewtheorem{Beweis}{Beweis}
    \renewtheorem{beweis}{Beweis}
    \qedsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof

    \theoremsymbol{}
\fi
}% not amsthm
```

§ 357.9 amsthm option

Only if the amsthm option was given:

```
\ifbool{LWR@ntheoremamsthm}{

\gdef\th@plain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderplain}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberplain{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderplain}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderplain}{##1\ (##3).}
        ]}}

\gdef\th@definition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
```

```
      \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberdefinition{%
  \def\theorem@headerfont{\normalfont\bfseries}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderdefinition}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderdefinition}{##1\ (##3).}
        ]}}

\gdef\th@remark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1\ ##2.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ ##2\ (##3).}
        ]}}

\gdef\th@nonumberremark{%
  \def\theorem@headerfont{\itshape}\normalfont%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderremark}{##1.}
        ]}%
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderremark}{##1\ (##3).}
        ]}}

\gdef\th@proof{%
  \def\theorem@headerfont{\normalfont\bfseries}\itshape%
  \def\@begintheorem##1##2{%
        \LWR@inctheorem% lwarp
      \item[
  \InlineClass{theoremheaderproof}{##1.}
        ]}%
```

```
  \def\@opargbegintheorem##1##2##3{%
        \LWR@inctheorem% lwarp
     \item[
  \InlineClass{theoremheaderproof}{##1\ (##3).}
        ]}}



\newcounter{proof}%
\if@thmmarks
    \newcounter{currproofctr}%
    \newcounter{endproofctr}%
\fi

\gdef\proofSymbol{\openbox}

\newcommand{\proofname}{Proof}

\newenvironment{proof}[1][\proofname]{
    \th@proof
    \def\theorem@headerfont{\itshape}%
    \normalfont
    \theoremsymbol{\HTMLunicode{220E}}% UTF-8 end-of-proof
    \@thm{proof}{proof}{#1}
}%
{\@endtheorem}

}{}% amsthm option
```

§ 357.10 Ending a theorem

Patched for css:

```
\let\LWR@origendtheorem\@endtheorem
\renewcommand{\@endtheorem}{%
\ifbool{LWR@ntheoremmarks}{%
    \ifsetendmark%
    \InlineClass{theoremendmark}{\csname\InTheoType Symbol\endcsname}%
    \setendmarkfalse%
    \fi%
}{}%
\LWR@origendtheorem% also does \@endtrivlist
\ifbool{LWR@ntheoremmarks}{\global\setendmarktrue}{}%
\endBlockClass%
}
```

§ 357.11 \NoEndMark

```
\gdef\NoEndMark{\global\setendmarkfalse}
```

§ 357.12 List-of

Redefined to reuse the float mechanism to add list-of-theorem links:

\thm@thmline {⟨*1: printed type*⟩} {⟨*2: #*⟩} {⟨*3: optional*⟩} {⟨*4: page*⟩}

```
\renewcommand{\thm@@thmline@noname}[4]{%
\hypertocfloat{1}{theorem}{thm}{#2 #3}{}%
}

\renewcommand{\thm@@thmline@name}[4]{%
\hypertocfloat{1}{theorem}{thm}{#1 #2 #3}{}%
}
```

This was redefined by ntheorem when loaded, so it is now redefined for lwarp:

```
\def\thm@@thmline{\thm@@thmline@name}
```

Patch for css:

```
\def\listtheorems#1{
\LWR@htmlelementclass{nav}{lothm}%
\begingroup
\c@tocdepth=-2%
\def\thm@list{#1}\thm@processlist
\endgroup
\LWR@htmlelementclassend{nav}{lothm}%
}
```

§ 357.13 Symbols

Proof QED symbol:

```
\newcommand{\qed}{\qquad\the\qedsymbol}

\AtBeginDocument{
\@ifundefined{LWR@orig@openbox}{
\LetLtxMacro\LWR@orig@openbox\openbox
\LetLtxMacro\LWR@orig@blacksquare\blacksquare
\LetLtxMacro\LWR@orig@Box\Box

\def\openbox{\text{\HTMLunicode{25A1}}}% UTF-8 white box
\def\blacksquare{\text{\HTMLunicode{220E}}}% UTF-8 end-of-proof
\def\Box{\text{\HTMLunicode{25A1}}}% UTF-8 white box

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\openbox\LWR@orig@openbox%
\LetLtxMacro\blacksquare\LWR@orig@blacksquare%
\LetLtxMacro\Box\LWR@orig@Box%
}% appto
```

```
}{}% @ifundefined
}% AtBeginDocument
```

§ 357.14 Cross-referencing

\thref {⟨*label*⟩}

```
\newcommand*{\thref}[1]{\cref{#1}}%
```

File 260 **lwarp-octave.sty**

§ 358 Package octave

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg octave octave is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{octave}[2017/10/31]
```

Remove the leading 1pt kern:

```
\RenewDocumentCommand{\@PrintTicks}{ m }{%
\kern-1pt%  lwarp
\@TickNum = #1%
\loop
\@Tick{}%
\advance\@TickNum by -1
\ifnum\@TickNum > 0
\repeat
}
```

Use unicode for the prime character:

```
\RenewDocumentCommand{\@Tick}{}{\HTMLunicode{2032}}
```

Catch the inline font:

```
\RenewDocumentCommand{\pitch}{ m o m }{%
\if@OctaveNumber%
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \MakeUppercase{#1}%
            \IfValueTF{#2}{#2}{}\textsubscript{#3}%
        }%
    }%
}%
\else%
{%
    \pitchfont{%
        \LWR@textcurrentfont{%  lwarp
            \@GetOctaveTick{#1}[#2]{#3}%
```

```
        }%
    }%
}%
\fi%
}
```

The original was hard to adapt to lwarp's handling of &.

```
\StartDefiningTabulars
\renewcommand{\octavetable}{%
\begin{tabular}{ll}
\octaveprimes \pitch{C}{0} & \octavenumbers \pitch{C}{0} \\
\octaveprimes \pitch{C}{1} & \octavenumbers \pitch{C}{1} \\
\octaveprimes \pitch{C}{2} & \octavenumbers \pitch{C}{2} \\
\octaveprimes \pitch{C}{3} & \octavenumbers \pitch{C}{3} \\
\octaveprimes \pitch{C}{4} & \octavenumbers \pitch{C}{4} \\
\octaveprimes \pitch{C}{5} & \octavenumbers \pitch{C}{5} \\
\octaveprimes \pitch{C}{6} & \octavenumbers \pitch{C}{6} \\
\octaveprimes \pitch{C}{7} & \octavenumbers \pitch{C}{7} \\
\end{tabular}
}
\StopDefiningTabulars
```

File 261 **lwarp-overpic.sty**

§ 359 Package

overpic

(*Emulates or patches code by* Rolf Niepraschk.)

Pkg overpic overpic is patched for use by lwarp.

⚠ scaling The macros \overpicfontsize and \overpicfontskip are used during HTML generation. These are sent to \fontsize to adjust the font size for scaling differences between the print and HTML versions of the document. Renew these macros before using the overpic and Overpic environments.

See section 84.2 for the print-mode version of \overpicfontsize and \overpicfontskip.

for HTML output:

```
\LWR@ProvidesPackagePass{overpic}[2017/10/06]

\newcommand*{\overpicfontsize}{12}
\newcommand*{\overpicfontskip}{14}

\BeforeBeginEnvironment{overpic}{%
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}

\AfterEndEnvironment{overpic}{\end{lateximage}}

\BeforeBeginEnvironment{Overpic}{%
```

```
    \begin{lateximage}%
    \fontsize{\overpicfontsize}{\overpicfontskip}%
    \selectfont%
}

\AfterEndEnvironment{Overpic}{\end{lateximage}}
```

File 262 **lwarp-pagegrid.sty**

§ 360 Package pagegrid

Pkg pagegrid pagegrid is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pagegrid}[2016/05/16]

\newcommand*{\pagegridsetup}[1]{}
```

File 263 **lwarp-pagenote.sty**

§ 361 Package pagenote

Pkg pagenote pagenote works as-is, but the page option is disabled.

for HTML output:

```
\DeclareOption{page}{}
\LWR@ProvidesPackagePass{pagenote}[2009/09/03]
```

File 264 **lwarp-pagesel.sty**

§ 362 Package pagesel

Pkg pagesel pagesel is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pagesel}[2016/05/16]
```

File 265 **lwarp-paralist.sty**

§ 363 Package paralist

(*Emulates or patches code by* Bernd Schandl.)

Pkg paralist paralist is supported with minor changes.

for HTML output:

```
\LWR@ProvidesPackagePass{paralist}[2017/01/22]
```

The compact environments are identical to the regular ones:

```
\LetLtxMacro\compactitem\itemize
\LetLtxMacro\compactenum\enumerate
\LetLtxMacro\compactdesc\description
\LetLtxMacro\endcompactitem\enditemize
\LetLtxMacro\endcompactenum\endenumerate
\LetLtxMacro\endcompactdesc\enddescription
```

For the inline environments, revert `\item` to its original print-mode version:

```
\AtBeginEnvironment{inparaitem}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparaenum}{\LetLtxMacro\item\LWR@origitem}
\AtBeginEnvironment{inparadesc}{\LetLtxMacro\item\LWR@origitem}
```

Manual formatting of the description labels:

```
\def\paradescriptionlabel#1{{\normalfont\textbf{#1}}}
```

File 266 **lwarp-parnotes.sty**

§ 364 Package

parnotes

(*Emulates or patches code by* Chelsea Hughes.)

Pkg parnotes parnotes is supported with some patches.

for HTML output:

```
\LWR@ProvidesPackagePass{parnotes}[2016/08/15]

\long\def\PN@parnote@real#1#2{%
    \parnotemark{#1}%
    % Unless this is the first parnote in \PN@text, add a separator first
    \unless\ifx\PN@text\@empty\g@addto@macro\PN@text{\parnoteintercmd}\fi
    % Redefine \@currentlabel to the parnote label, so \label works
    \g@addto@macro\PN@text{%
%         \phantomsection%
        \def\@currentlabel{#1}%
        \def\cref@currentlabel{%        lwarp
            [parnotemark][\arabic{parnotemark}][]\theparnotemark%
        }%
    }%
    \g@addto@macro\PN@text{%
        \LWR@textcurrentfont{%          lwarp
            \parnotemark{#1}\nolinebreak\thinspace#2%
        }%
    }%
}

\def\PN@parnotes@real{%
    % We call \par later, so this avoids recursion with \PN@parnotes@auto
    \PN@inparnotestrue
    \unless\ifvmode\par\fi
```

```
    % Avoid page breaks between a paragraph and its parnotes
    \nopagebreak\addvspace{\parnotevskip}%
    \LWR@forcenewpage%                  lwarp
    \begin{BlockClass}{footnotes}%      lwarp
    {\parnotefmt{\PN@text}\par}%
    \end{BlockClass}%                   lwarp
    \global\def\PN@text{}%
    \addvspace{\parnotevskip}%
    %
    % These can be enabled or disabled by package options
    %
    \PN@disable@indent
    \PN@reset@optional
    \PN@inparnotesfalse
}

\AtBeginDocument{
\crefname{parnotemark}{paragraph note}{paragraph notes}%
\Crefname{parnotemark}{Paragraph note}{Paragraph notes}
}
```

File 267 **lwarp-parskip.sty**

§ 365 Package

parskip

Pkg parskip parskip is ignored.

for HTML output: Discard all options for lwarp-parskip.

```
\LWR@ProvidesPackageDrop{parskip}[2001/04/09]
```

File 268 **lwarp-pbox.sty**

§ 366 Package

pbox

(*Emulates or patches code by* Simon Law.)

Pkg pbox pbox is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{pbox}[2011/12/07]

\NewDocumentCommand{\pbox}{O{t} O{} O{t} m +m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox[#1][#2][#3]{#4}{#5}%
}

\newcommand{\settominwidth}[3][\columnwidth]{%
\settowidth{#2}{#3}%
}

```

```
\newcommand{\widthofpbox}[1]{%
\widthof{#1}%
}
```

File 269 **lwarp-pdfcomment.sty**

§ 367 Package pdfcomment

Pkg pdfcomment pdfcomment is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcomment}[2016/06/13]

\newenvironment{pdfsidelinecomment}[2][]{}{}
\newcommand{\pdfcomment}[2][]{}
\newcommand{\pdfmargincomment}[2][]{}
\newcommand{\pdfmarkupcomment}[3][]{#2}
\newcommand{\pdffreetextcomment}[2][]{}
\newcommand{\pdfsquarecomment}[2][]{}
\newcommand{\pdfcirclecomment}[2][]{}
\newcommand{\pdflinecomment}[2][]{}
\newcommand{\pdftooltip}[3][]{#2}
\newcommand{\pdfcommentsetup}[2][]{}
\newcommand{\listofpdfcomments}[1][]{}
\newcommand{\setliststyle}[1]{}
\newcommand{\defineliststyle}[2]{}
\newcommand{\defineavatar}[2]{}
\newcommand{\definestyle}[2]{}
```

File 270 **lwarp-pdfcrypt.sty**

§ 368 Package pdfcrypt

Pkg pdfcrypt pdfcrypt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfcrypt}[2016/05/16]

\newcommand*{\pdfcryptsetup}[1]{}
```

File 271 **lwarp-pdflscape.sty**

§ 369 Package pdflscape

Pkg pdflscape pdflscape is ignored.

for HTML output: Discard all options for lwarp-pdflscape:

```
\LWR@ProvidesPackageDrop{pdflscape}[2016/05/14]
```

File 272 **lwarp-pdfmarginpar.sty**

§ 370 Package pdfmarginpar

Pkg pdfmarginpar pdfmarginpar is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfmarginpar}[2011/08/05]

\newcommand{\pdfmarginpar}[2][]{}
\newcommand{\pdfmarginparset}[1]{}
```

File 273 **lwarp-pdfpages.sty**

§ 371 Package pdfpages

(*Emulates or patches code by* Andreas Matthias.)

Pkg pdfpages pdfpages is patched for use by lwarp.

Option `link` and `linkname` work:

```
\hyperlink{<filename>.pdf.<pagenubmer}}{some text}
\hyperlink{<linkname>.<pagenubmer}}{some text}
```

Options which make no sense in HTML are disabled.

for HTML output:

```
\LWR@ProvidesPackagePass{pdfpages}[2017-10-31]
```

Disable option which have no meaning for HTML output:

```
\define@key{pdfpages}{fitpaper}[false]{}
\define@key{pdfpages}{landscape}[false]{}
\define@key{pdfpages}{openright}[false]{}
\define@key{pdfpages}{signature}{}
\define@key{pdfpages}{signature*}{}
\define@key{pdfpages}{booklet}[false]{}
\define@key{pdfpages}{rotateoversize}[false]{}
\define@key{pdfpages}{doublepages}[false]{}
\define@key{pdfpages}{doublepagestwist}[false]{}
\define@key{pdfpages}{doublepagestwistodd}[false]{}
\define@key{pdfpages}{doublepagestwist*}[false]{}
\define@key{pdfpages}{doublepagestwistodd*}[false]{}
\define@key{pdfpages}{duplicatepages}[2]{}
\define@key{pdfpages}{thread}[false]{}
\define@key{pdfpages}{threadname}{}
```

```
\define@key{pdfpages}{linkfit}{}
\define@key{pdfpages}{linktodoc}[false]{}
\define@key{pdfpages}{linktodocfit}{}
\define@key{pdfpages}{linkfilename}{}
\define@key{pdfpages}{survey}[false]{}
\define@key{pdfpages}{survey-nolink}[false]{}
\define@key{pdfpages}{newwindow}[false]{}
```

Use print mode while measuring the page numbers:

```
\xpretocmd{\AM@getpagecount}{\LWR@restoreorigformatting}{}{}
```

Emulate a bit of eso-pic:

```
\newif\ifESO@texcoord

\newcommand{\ESO@HookIIBG}{}

\renewcommand{\AM@AddToShipoutPicture}{\g@addto@macro\ESO@HookIIBG}

\renewcommand{\ClearShipoutPicture}{}
```

`\LWR@esopic@newpage` At each `\newpage`.

```
\newcommand*{\LWR@esopic@newpage}{%
```

Is there something to draw?

```
\ifdefvoid{\ESO@HookIIBG}%
{}%
{%
```

If the `link` option was specified, add a hyper taraget:

```
    \ifAM@link%
        \hypertarget{\AM@linkname.\AM@page}{}%
    \fi%
```

Draw inside a picture environment of the size of a virtual page:

```
    \begingroup%
    \setlength{\unitlength}{1in}%
    \begin{picture}(8,10.5)%
    \ESO@HookIIBG%
    \end{picture}%
    \endgroup%
    \global\let\ESO@HookIIBG\@empty%
}
}
```

`\AM@output` Patched to use `\LWR@esopic@newpage`.

```
\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
```

```
    {\LWR@patcherror{pdfpages}{AM@output-1}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-2}}

\xpatchcmd{\AM@output}
    {\newpage}
    {\LWR@esopic@newpage}
    {}
    {\LWR@patcherror{pdfpages}{AM@output-3}}
```

`\includepdf` Patched to set a reasonable paper size.

```
\xpretocmd{\includepdf}{%
    \begingroup%
    \setlength{\paperwidth}{8in}%
    \setlength{\paperheight}{10.5in}%
}{}{}

\xapptocmd{\includepdf}{%
    \endgroup%
}{}{}
```

`\includepdfmerge` Patched to set a reasonable paper size.

```
\xpretocmd{\includepdfmerge}{%
    \begingroup%
    \setlength{\paperwidth}{8in}%
    \setlength{\paperheight}{10.5in}%
}{}{}

\xapptocmd{\includepdfmerge}{%
    \endgroup%
}{}{}
```

`\AM@hyper@begin@i` Hyper links are created by `\LWR@esopic@newpage`, so don't create them here:

```
\renewcommand{\AM@hyper@begin@i}{}
```

File 274 **lwarp-pdfprivacy.sty**

§ 372 Package pdfprivacy

`Pkg pdfprivacy` pdfprivacy is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfprivacy}[2017/12/03]
```

File 275 **lwarp-pdfrender.sty**

§ 373 Package pdfrender

Pkg pdfrender pdfrender is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfrender}[2016/05/17]

\newcommand*{\pdfrender}[1]{}
\newcommand{\textpdfrender}[2]{#2}
```

File 276 **lwarp-pdfsync.sty**

§ 374 Package pdfsync

(*Emulates or patches code by* J. Laurens.)

Pkg pdfsync pdfsync is ignored.

for HTML output: Discard all options for lwarp-pdfsync:

```
\LWR@ProvidesPackageDrop{pdfsync}[2008/01/26]

\newcommand*{\pdfsync}{}
\newcommand*{\pdfsyncstart}{}
\newcommand*{\pdfsyncstop}{}
```

File 277 **lwarp-pdftricks.sty**

§ 375 Package pdftricks

(*Emulates or patches code by* C. V. Radhakrishnan, C. V. Rajagopal, Antoine Chambert-Loir.)

Pkg pdftricks pdftricks is patched for use by lwarp.

⚠ convert image files The pdftricks image files `<jobname>-fig*.pdf` must be converted to `.svg`, or else a missing file error will occur. The image files must also be converted again whenever they change. To convert the images:

Enter ⇒ **lwarpmk pdftosvg <jobname>-fig*.pdf**

for HTML output:

```
\LWR@ProvidesPackagePass{pdftricks}[2003/08/10]
```

Reuse the print-mode images:

```
\def\PDFTfigname{\BaseJobname-fig\thepsfig}
```

If the .pdf images have not yet been converted to .svg then an error about a missing file will occur. Warn the user to convert the images.

```
\PackageWarning{lwarp-pdftricks}{
When the pdftricks images change,
remember to convert PDF images to SVG using 'lwarpmk pdftosvg *-fig.pdf',
}

\AfterEndDocument{\typeout{***}}
\AfterEndDocument{\typeout{*** Note: If pdftricks images are not found, new, or updated,}}
\AfterEndDocument{\typeout{*** \space use 'lwarpmk pdftosvg \BaseJobname-fig*.pdf'}}
\AfterEndDocument{\typeout{***}}
```

File 278 **lwarp-pdfx.sty**

§ 376 Package

pdfx

Pkg pdfx pdfx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pdfx}[2017/05/18]
```

File 279 **lwarp-perpage.sty**

§ 377 Package

perpage

(*Emulates or patches code by* David Kastrup.)

Pkg perpage perpage is mostly ignored, but support is added for footnote counters.

There is no page number in HTML, so most counters are not reset. If the document redefines \the<countername> to include \theperpage, it is necessary to place that redefininition inside a warpprint environment to avoid modifying the HTML defintions.

\AddAbsoluteCounter must not be inside warpprint, as the counter must be added for HTML also, although it is not incremented.

footnote numbering To have footnote numbers reset each time footnotes are printed:

```
\setcounter{footnoteReset}{1}
```

For bigfoot, manyfoot, or perpage:

```
\MakePerPage{footnoteX}
— or —
\MakeSortedPerPage{footnoteX}
```

The footnotes are reset when they are printed, according to section level as set by FootnoteDepth, which is not necessarily by HTML page. This is recommended for

\alph, \Alph, or \fnsymbol footnotes, due to the limited number of symbols which are available.

for HTML output:

```
\LWR@ProvidesPackageDrop{perpage}[2014/10/25]

\newcommand\AddAbsoluteCounter[1]
{
    \@ifundefined{c@abs#1}{%
        \expandafter\newcount\csname c@abs#1\endcsname
        \global\value{abs#1}\@ne
%         \global\expandafter\let\csname cl@abs#1\endcsname\@empty
        \expandafter\xdef\csname theabs#1\endcsname{%
%             \noexpand\number \csname c@abs#1\endcsname
        }%
%         \global\@namedef{c@pabs@#1}{\pp@cl@begin
%         \stepcounter{abs#1}%
%         \pp@cl@end}%
%         \@addtoreset{pabs@#1}{#1}
    }
    {}
}

\AddAbsoluteCounter{page}
\def\theabspage{1}

\newcommand*\MakePerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{

}%
}

\newcommand*\MakeSorted[1]{}

\newcommand*\MakeSortedPerPage[2][1]{%
    \ifltxcounter{#2Reset}{%
        \setcounter{#2Reset}{#1}%
    }{
}%
}

\newcommand*{\theperpage}{1}
```

File 280 **lwarp-pfnote.sty**

§ 378 Package

pfnote

Pkg pfnote pfnote is ignored.

pfnote

⚠ pfnote numbers While emulating pfnote, lwarp is not able to reset HTML footnote numbers per page number to match the printed version, as HTML has no concept of page numbers. lwarp therefore uses continuous footnote numbering even for pfnote.

for HTML output:
```
\LWR@ProvidesPackageDrop{pfnote}[1999/07/14]
```

File 281 **lwarp-phfqit.sty**

§ 379 Package
# phfqit

(*Emulates or patches code by* Philippe Faist.)

Pkg phfqit phfqit is patched for use by lwarp.

for HTML output:
```
\LWR@ProvidesPackagePass{phfqit}[2017/08/16]

\LetLtxMacro\LWR@origbitstring\bitstring

\renewcommand\bitstring[1]{%
\InlineClass[%
    text-decoration: overline underline ;
]{bitstring}{#1}%
% \phfqit@bitstring{#1}%
}

\appto\LWR@restoreorigformatting{%
\LetLtxMacro\bitstring\LWR@origbitstring%
}
```

File 282 **lwarp-pifont.sty**

§ 380 Package
# pifont

(*Emulates or patches code by* Walter Schmidt.)

Pkg pifont pifont is patched for use by lwarp.

Hashed inline images are used, as there may not be Unicode support for all icons.

for HTML output:
```
\LWR@ProvidesPackagePass{pifont}[2005/04/12]

\renewcommand{\Pisymbol}[2]{%
    \begin{lateximage}*[(Pisymbol)][pisymbol#1#2]%
    {\Pifont{#1}\char#2}%
    \end{lateximage}%
}

\newcommand{\LWR@HTML@Pifill}[2]{
    \Pisymbol{#1}{#2} \Pisymbol{#1}{#2} \Pisymbol{#1}{#2}
}
\LWR@formatted{Pifill}

\newcommand{\LWR@HTML@Piline}[2]{%
    \par\noindent\hspace*{0.5in}
```

```
    \Pifill{#1}{#2} \Pifill{#1}{#2} \Pifill{#1}{#2}
}
\LWR@formatted{Piline}
```

File 283 **lwarp-placeins.sty**

§ 381 Package placeins

(*Emulates or patches code by* Donald Arseneau.)

Pkg placeins placeins is ignored.

Discard all options for lwarp-placeins:

for HTML output:

```
\LWR@ProvidesPackageDrop{placeins}[2005/04/18]
\newcommand*{\FloatBarrier}{}
```

File 284 **lwarp-plarydshln.sty**

§ 382 Package plarydshln

Pkg plarydshln plarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plarydshln}[2018/10/20]
\LWR@origRequirePackage{lwarp-arydshln}
```

File 285 **lwarp-plext.sty**

§ 383 Package plext

Pkg plext plext is preloaded by jtarticle and related classes.

for HTML output:

```
\LWR@loadbefore{plext}

\LWR@ProvidesPackagePass{plext}[2017/07/21]

\let\tate\relax

\DeclareExpandableDocumentCommand{\rensuji}{s o m}{#3}

% \layoutfloat(width,height)[pos]#4
\DeclareDocumentCommand{\layoutfloat}{d() o m}{}

% \DeclareLayoutCaption{type} <dir>(width)[pos1pos2]
```

```
\DeclareDocumentCommand{\DeclareLayoutCaption}{m d<> d() o}{}

\LetLtxMacro\pcaption\caption

% \layoutcaption<dir>(width)[pos]
\DeclareDocumentCommand{\layoutcaption}{d<> d() o}{}

\let\captiondir\relax
```

Add the optional <t/y> direction:

```
\RenewDocumentEnvironment{LWR@HTML@minipage}{d<> O{t} O{} O{t} m}
    {\LWR@HTML@sub@minipage{#2}{#3}{#4}{#5}}
    {\endLWR@HTML@sub@minipage}

\RenewDocumentCommand{\LWR@HTML@parbox}{d<> O{t} O{} O{t} m +m}
{
\LWR@traceinfo{parbox of width #4}%
\begin{minipage}[#2][#3][#4]{#5}%
#6
\end{minipage}%
}

% \pbox <t/y> [width] [l/r] {contents}
\RenewDocumentCommand{\pbox}{d<> O{0pt} O{c} m}{%
\global\booltrue{LWR@minipagefullwidth}%
\parbox{#2}{#4}%
}
```

picture, as modified by pext, is encapsulated by the lwarp core.

File 286 **lwarp-plextarydshln.sty**

§ 384 Package plextarydshln

Pkg plextarydshln plextarydshln is emulated by lwarp-arydshln.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextarydshln}[2018/10/20]

\LWR@origRequirePackage{lwarp-arydshln}
```

File 287 **lwarp-plextcolortbl.sty**

§ 385 Package plextcolortbl

Pkg plextcolortbl plextcolortbl is emulated by lwarp-colortbl.

for HTML output:

```
\LWR@ProvidesPackageDrop{plextcolortbl}[2018/09/19]
```

```
\LWR@origRequirePackage{lwarp-colortbl}
```

File 288 **lwarp-prelim2e.sty**

§ 386 Package prelim2e

(*Emulates or patches code by* Martin Schröder.)

Pkg prelim2e prelim2e is ignored.

for HTML output: Discard all options for lwarp-prelim2e:

```
\LWR@ProvidesPackageDrop{prelim2e}[2009/05/29]

\newcommand{\PrelimText}{}
\newcommand{\PrelimTextStyle}{}
\newcommand{\PrelimWords}{}
```

File 289 **lwarp-prettyref.sty**

§ 387 Package prettyref

(*Emulates or patches code by* Kevin S. Ruland.)

Pkg prettyref prettyref is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{prettyref}[1998/07/09]

\newrefformat{fig}{Figure \ref{#1}}
\newrefformat{tab}{Table \ref{#1}}
```

File 290 **lwarp-preview.sty**

§ 388 Package preview

Pkg preview preview is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{preview}[2017/04/24]

\newenvironment{preview}{}{}
\newenvironment{nopreview}{}{}
\NewDocumentCommand{\PreviewMacro}{s o o +m}{}
\NewDocumentCommand{\PreviewEnvironment}{s o o +m}{}
\newcommand{\PreviewSnarfEnvironment}[2][]{}
\NewDocumentCommand{\PreviewOpen}{s o}{}
\NewDocumentCommand{\PreviewClose}{s o}{}
\let\ifPreview\iffalse% \fi for syntax highlighting
```

File 291 **lwarp-psfrag.sty**

§ 389 Package psfrag

(*Emulates or patches code by* Michael C. Grant, David Carlisle.)

Pkg psfrag psfrag is patched for use by lwarp.

⚠ use psfrags The psfrags environment is modified to use lateximage to encapsulate the image. Always use a psfrags environment to contain any local \psfrag macros and the associated \includegraphics or \epsfig calls. Outside of a psfrags environment, psfrags adjustments will not be seen by lwarp.

⚠ Tip: Use a mono-spaced font for the tags in the eps file.

for HTML output:

```
\LWR@ProvidesPackagePass{psfrag}[1998/04/11]
```

A lateximage captures the modified image from the document.

```
\BeforeBeginEnvironment{psfrags}{%
    \begin{lateximage}[(-psfrags-~\packagediagramname)]%
}

\AfterEndEnvironment{psfrags}{\end{lateximage}}
```

File 292 **lwarp-psfragx.sty**

§ 390 Package psfragx

(*Emulates or patches code by* Pascal Kockaert.)

Pkg psfragx psfragx is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{psfragx}[2012/05/02]
```

A lateximage captures the modified image from the document.

```
\def\pfx@includegraphicx#1#2{%
    \begin{lateximage}[(-psfragx-~\packagediagramname)]%
    \mbox{\pfx@overpix{#1}{#2}\endpfx@overpix}%
    \end{lateximage}%
}

\def\@@@overpix[#1]<#2>[#3]#4{%
    \begin{lateximage}[(-psfragx-~\packagediagramname)]%
    \pfx@overpix{#1,ovpfgd={#2},ovpbgd={#3}}{#4}%
}

```

```
\def\endoverpix{%
    \endpfx@overpix%
    \end{lateximage}%
}
```

File 293 **lwarp-pst-eps.sty**

§ 391 Package

pst-eps

(*Emulates or patches code by* Herbert Voss.)

Pkg pst-eps pst-eps is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{pst-eps}[2005/05/20]
```

```
\renewenvironment{TeXtoEPS}{}{}
\renewcommand{\PSTtoEPS}[3][]{}
```

File 294 **lwarp-pstool.sty**

§ 392 Package

pstool

(*Emulates or patches code by* Zebb Prime, Will Robertson.)

Pkg pstool pstool is patched for use by lwarp.

\graphicspath is ignored, and the file directory must be stated.

⚠ path and filename The filename must not have a file extension.

Use

Enter ⇒ **lwarpmk html**

followed by

Enter ⇒ **lwarpmk limages**

.

for HTML output:

```
\LWR@ProvidesPackagePass{pstool}[2018/01/20]
```

Each image is placed inside a lateximage to capture the results of psfrag.

```
\renewcommand\pstool@alwaysprocess[3][]{%
    \begin{lateximage}[(-pstool-~\packagediagramname)]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
\LetLtxMacro\pstool@neverprocess\pstool@alwaysprocess
```

```
\LetLtxMacro\pstool@maybeprocess\pstool@alwaysprocess

\renewcommand\pstool@@psfragfig[4]{%
    \begin{lateximage}[(-pstool-~\packagediagramname)]%
    \includegraphics{#2.pdf}%
    \end{lateximage}%
}
```

File 295 **lwarp-pstricks.sty**

§ 393 Package pstricks

(*Emulates or patches code by* Timothy Van Zandt.)

Pkg pstricks pstricks is patched for use by lwarp.

⚠ use pspicture All pstricks content should be contained inside a pspicture environment.

for HTML output:

```
\LWR@ProvidesPackagePass{pstricks}[2018/01/06]

\BeforeBeginEnvironment{pspicture}{\begin{lateximage}[(pspicture)]}
\AfterEndEnvironment{pspicture}{\end{lateximage}}
```

File 296 **lwarp-pxatbegshi.sty**

§ 394 Package pxatbegshi

Pkg pxatbegshi pxatbegshi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxatbegshi}[2017/11/04]

\LWR@origRequirePackage{lwarp-atbegshi}
```

File 297 **lwarp-pxeveryshi.sty**

§ 395 Package pxeveryshi

Pkg pxeveryshi pxeveryshi is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxeveryshi}[2012/05/19]

\LWR@origRequirePackage{lwarp-everyshi}
```

File 298 **lwarp-pxftnright.sty**

§ 396 Package pxftnright

Pkg pxftnright pxftnright is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxftnright}[2017/02/28]
\LWR@origRequirePackage{lwarp-ftnright}
```

File 299 **lwarp-pxjahyper.sty**

§ 397 Package pxjahyper

Pkg pxjahyper pxjahyper is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{pxjahyper}[2018/07/15]
```

File 300 **lwarp-quotchap.sty**

§ 398 Package quotchap

(*Emulates or patches code by* Karsten Tinnefeld, Jan Klever.)

Pkg quotchap quotchap is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{quotchap}[2012/10/20]

\newcommand{\@quotchap}{}
\newlength{\LWR@quotchapwidth}

\let\@printcites\relax

\newcommand*{\@iprintcites}{%
```

Place the quotes inside a of class quotchap, of the maximum selected width:

```
\begin{BlockClass}[max-width: \LWR@printlength{\LWR@quotchapwidth}]{quotchap}
%\begin{minipage}{\LWR@quotchapwidth}
\@quotchap
%\end{minipage}
\end{BlockClass}
```

Deactivate the quote printing:

```
\global\let\@printcites\relax
}

\NewEnviron{savequote}[1][\linewidth]{%
```

Remember the width, adjusted for HTML, and make the length assignment global, per:
https://tex.stackexchange.com/questions/300823/why-is-setlength-ineffective-inside-a-tabular-environment

```
\setlength{\LWR@quotchapwidth}{#1*2}%
\global\LWR@quotchapwidth=\LWR@quotchapwidth%
```

Remember the body, and activate the quote printing:

```
\global\let\@quotchap\BODY
\global\let\@printcites\@iprintcites%
}
```

The quotation author is placed inside a of class qauthor:

```
\newcommand{\qauthor}[1]{\begin{BlockClass}{qauthor}{#1}\end{BlockClass}}
```

\qsetcnfont is ignored:

```
\newcommand{\qsetcnfont}[1]{}
```

File 301 **lwarp-quoting.sty**

§ 399 Package

quoting

(*Emulates or patches code by* Thomas Titz.)

Pkg quoting quoting is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{quoting}[2014/01/28]

\xpatchcmd{\quoting}{\quo@begintext}
    {\begin{LWR@blocktextcurrentfont}\quo@begintext}
    {}
    {\LWR@patcherror{quoting}{quoting}}

\xpatchcmd{\endquoting}{\quo@endtext}
    {\quo@endtext\end{LWR@blocktextcurrentfont}}
    {}
    {\LWR@patcherror{imakeidx}{endquoting}}
```

File 302 **lwarp-ragged2e.sty**

§ 400 Package ragged2e

(*Emulates or patches code by* Martin Schröder.)

Pkg ragged2e ragged2e is emulated.

Discard all options for lwarp-ragged2e:

for HTML output:

```
\LWR@ProvidesPackageDrop{ragged2e}[2009/05/21]

\LetLtxMacro\Centering\centering
\LetLtxMacro\RaggedLeft\raggedleft
\LetLtxMacro\RaggedRight\raggedright
\newcommand*{\justifying}{}
\newlength{\CenteringLeftskip}
\newlength{\RaggedLeftLeftskip}
\newlength{\RaggedRightLeftskip}
\newlength{\CenteringRightskip}
\newlength{\RaggedLeftRightskip}
\newlength{\RaggedRightRightskip}
\newlength{\CenteringParfillskip}
\newlength{\RaggedLeftParfillskip}
\newlength{\RaggedRightParfillskip}
\newlength{\JustifyingParfillskip}
\newlength{\CenteringParindent}
\newlength{\RaggedLeftParindent}
\newlength{\RaggedRightParindent}
\newlength{\JustifyingParindent}
\newenvironment*{Center}{\center}{\endcenter}
\newenvironment*{FlushLeft}{\flushleft}{\endflushleft}
\newenvironment*{FlushRight}{\flushright}{\endflushright}
\newenvironment*{justify}{\justifying}{\endjustifying}
```

File 303 **lwarp-realscripts.sty**

§ 401 Package realscripts

(*Emulates or patches code by* Will Robertson.)

Pkg realscripts realscripts is emulated. See `lwarp.css` for the of class `supsubscript`.

for HTML output:

```
\LWR@ProvidesPackageDrop{realscripts}[2016/02/13]

\let\realsuperscript\textsuperscript
\let\realsubscript\textsubscript

```

```
\let\fakesuperscript\textsuperscript
\let\fakesubscript\textsubscript

\newlength{\subsupersep}

\newcommand*{\LWR@realscriptsalign}{}

\newcommand*{\LWR@setrealscriptsalign}[1]{%
    \renewcommand*{\LWR@realscriptsalign}{}%
    \ifthenelse{\equal{#1}{c}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:center} ; %
        }%
    }{}%
    \ifthenelse{\equal{#1}{r}}{%
        \renewcommand{\LWR@realscriptsalign}{%
            \LWR@print@mbox{text-align:right} ; %
        }%
    }{}%
}

\DeclareDocumentCommand \textsubsuperscript {s O{l} mm} {%
    \LWR@setrealscriptsalign{#2}%
    \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
        \textsuperscript{#4}\textsubscript{#3}%
    }%
}

\DeclareDocumentCommand \textsupersubscript {s O{l} mm} {%
    \LWR@setrealscriptsalign{#2}%
    \InlineClass[\LWR@realscriptsalign]{supsubscript}{%
        \textsubscript{#4}\textsuperscript{#3}%
    }%
}
```

File 304 **lwarp-refcheck.sty**

§ 402 Package

refcheck

Pkg refcheck refcheck is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{refcheck}[2013/02/14]

\def\showrefnames{}
\def\norefnames{}
\def\showcitenames{}
\def\nocitenames{}
\def\setonmsgs{}
\def\setoffmsgs{}
\def\checkunlbld{}
\def\ignoreunlbld{}
\newcommand*{\refcheckxrdoc}[2][]{}
```

File 305 **lwarp-register.sty**

§ 403 Package register

(*Emulates or patches code by* Matthew Lovell.)

Pkg register register is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{register}[2019/01/01]

\xpatchcmd{\register}
    {\centering}
    {\begin{center}\begin{lateximage}[(-register-~\packagediagramname)]}
    {}
    {\LWR@patcherror{register}{register}}

\xpatchcmd{\endregister}
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister}}

\expandafter\xapptocmd\csname register*\endcsname
    {\begin{center}\begin{lateximage}[(-register-~\packagediagramname)]}
    {}
    {\LWR@patcherror{register}{register*}}

\expandafter\xpatchcmd\csname endregister*\endcsname
    {\leftskip}
    {%
        \end{lateximage}\end{center}%
        \leftskip%
    }%
    {}
    {\LWR@patcherror{register}{endregister*}}

\setlength{\regWidth}{5in}
```

File 306 **lwarp-relsize.sty**

§ 404 Package relsize

(*Emulates or patches code by* Donald Arseneau, Bernie Cosell, Matt Swift.)

Pkg relsize relsize is patched for use by lwarp.

For HTML, only the inline macros are supported: `\textlarger`, `\textsmaller`, and `\textscale`. Each becomes an inline span of a modified `font-size`.

`\relsize`, `\larger`, `\smaller`, and `\relscale` are ignored.

While creating SVG math for HTML, the original definitions are temporarilty restored, and so should work as expected.

⚠ not small The HTML browser's setting for minumum font size may limit how small the output will be displayed.

for HTML output:

```
\LWR@ProvidesPackagePass{relsize}[2013/03/29]

\let\LWR@origrelsize\relsize
\LetLtxMacro\LWR@origlarger\larger
\LetLtxMacro\LWR@origsmaller\smaller
\let\LWR@relscale\relscale
\LetLtxMacro\LWR@origtextlarger\textlarger
\LetLtxMacro\LWR@origtextsmaller\textsmaller
\let\LWR@textscale\textscale

\appto\LWR@restoreorigformatting{%
\let\relsize\LWR@origrelsize%
\LetLtxMacro\larger\LWR@origlarger%
\LetLtxMacro\smaller\LWR@origsmaller%
\let\relscale\LWR@relscale%
\LetLtxMacro\textlarger\LWR@origtextlarger%
\LetLtxMacro\textsmaller\LWR@origtextsmaller%
\let\textscale\LWR@textscale%
}

\newcounter{LWR@relsizetemp}

\renewcommand*{\relsize}[1]{}
\renewcommand*{\larger}[1][]{}
\renewcommand*{\smaller}[1][]{}
\renewcommand*{\relscale}[1]{}

\renewcommand*{\textlarger}[2][1]{%
\setcounter{LWR@relsizetemp}{100+(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textlarger}{#2}%
}

\renewcommand*{\textsmaller}[2][1]{%
\setcounter{LWR@relsizetemp}{100-(#1*20)}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textsmaller}{#2}%
}

\renewcommand*{\textscale}[2]{%
\setcounter{LWR@relsizetemp}{100*\real{#1}}%
\InlineClass[font-size:\arabic{LWR@relsizetemp}\%]{textscale}{#2}%
}
```

File 307 **lwarp-repeatindex.sty**

§ 405 Package

repeatindex

Pkg repeatindex repeatindex is emulated for lwarp.

⚠ style file lwarp must be used with a special style file:

```
\usepackage[makeindex,makeindexStyle={lwarp_repeatindex}]{lwarp}
```

where lwarp_repeatindex.ist may be copied from the following modified version of lwarp.ist:

```
preamble
"\\begin{theindex}
  \\providecommand*\\lettergroupDefault[1]{}
  \\providecommand*\\lettergroup[1]{%
      \\par\\textbf{#1}\\par
      \\nopagebreak
  }
"
headings_flag 1
heading_prefix "
  \\lettergroup{"
heading_suffix "}"
delim_0 "], \\hyperindexref{"
delim_1 ", \\hyperindexref{"
delim_2 ", \\hyperindexref{"
delim_n "}, \\hyperindexref{"
delim_r "} -- \\hyperindexref{"
delim_t "}"

item_0 "\n  \\item ["
```

(The modifications are the delim_0 and item_0 entries.)

for HTML output:

```
\LWR@ProvidesPackageDrop{repeatindex}[2001/10/13]
```

In the lwarp core, \LWR@indexitem is modified to accept the optional \item argument.

```
\RequirePackage{makeidx}
\def\entryprefix{\itshape}
\def\entrypostfix{\dots}
```

File 308 **lwarp-resizegather.sty**

§ 406 Package resizegather

Pkg resizegather resizegather is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{resizegather}[2016/05/16]
\newcommand*{\resizegathersetup}[1]{}
```

File 309 **lwarp-rmpage.sty**

§ 407 Package rmpage

Pkg rmpage rmpage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{rmpage}[1997/09/29]
```

File 310 **lwarp-romanbar.sty**

§ 408 Package romanbar

(*Emulates or patches code by* H.-Martin Münch.)

Pkg romanbar romanbar is patched for use by lwarp.

An inline class with an overline and underline is used.

for HTML output:

```
\LWR@ProvidesPackagePass{romanbar}[2012/01/01]
\DeclareRobustCommand{\Roman@bar}[1]{% #1 is in Roman, i.e. MMXII
\InlineClass[%
    text-decoration: overline underline ;
]{romanbar}{#1}%
}
```

File 311 **lwarp-romanbarpagenumber.sty**

§ 409 Package romanbarpagenumber

Pkg romanbarpagenumber romanbarpagenumber is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{romanbarpagenumber}[2015/02/06]
```

File 312 **lwarp-rotating.sty**

§ 410 Package rotating

(*Emulates or patches code by* Robin Fairbairns, Sebastian Rahtz, Leonor Barroca.)

Pkg rotating rotating is emulated.

All rotations are ignored in HTML output.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotating}[2016/08/11]
\RequirePackage{graphicx}

\LetLtxMacro\sidewaystable\table
\let\endsidewaystable\endtable

\LetLtxMacro\sidewaysfigure\figure
\let\endsidewaysfigure\endfigure

\newenvironment*{sideways}{}{}
\newenvironment*{turn}[1]{}{}
\newenvironment*{rotate}[1]{}{}
\NewDocumentCommand{\turnbox}{m +m}{#2}
\let\rotcaption\caption
\let\@makerotcaption\@makecaption
```

File 313 **lwarp-rotfloat.sty**

§ 411 Package rotfloat

(*Emulates or patches code by* Axel Sommerfeldt.)

Pkg rotfloat rotfloat is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{rotfloat}[2004/01/04]

\RequirePackage{float}
```

\newfloat {⟨*1: type*⟩} {⟨*2: placement*⟩} {⟨*3: ext*⟩} [⟨*4: within*⟩]

Emulates the \newfloat command from the float package. Sideways floats are \let to the same as regular floats.

"placement" is ignored.

```
\RenewDocumentCommand{\newfloat}{m m m o}{%
\IfValueTF{#4}%
{%
```

```
    \DeclareFloatingEnvironment[fileext=#3,within=#4]{#1}%
}%
{%
    \DeclareFloatingEnvironment[fileext=#3]{#1}%
}%
\csletcs{sideways#1}{#1}%
\csletcs{endsideways#1}{end#1}%
```

Remember the float style:

```
\csedef{LWR@floatstyle@#1}{\LWR@floatstyle}%
\csedef{LWR@floatstyle@sideways#1}{\LWR@floatstyle}%
```

newfloat package automatically creates the `\listof` command for new floats, but float does not, so remove `\listof` here in case it is manually created later:

```
\cslet{listof#1s}\relax%
\cslet{listof#1es}\relax%
\cslet{listofsideways#1s}\relax%
\cslet{listofsideways#1es}\relax%
}
```

File 314 **lwarp-rviewport.sty**

§ 412 Package rviewport

Pkg rviewport

rviewport is honored inside a `lateximage`, and otherwise ignored for HTML output.

If rviewport is important for an image, enclose the image inside a `lateximage` environment.

for HTML output:

```
\LWR@ProvidesPackagePass{rviewport}[2011/08/27]
```

```
\define@key{igraph}{rviewport}{}
```

File 315 **lwarp-savetrees.sty**

§ 413 Package savetrees

Pkg savetrees

savetrees is ignored.

for HTML output:

Discard all options for lwarp-savetrees:

```
\LWR@ProvidesPackageDrop{savetrees}[2016/04/13]
```

File 316 **lwarp-scalefnt.sty**

§ 414 Package scalefnt

(*Emulates or patches code by* D. Carlisle.)

Pkg scalefnt scalefnt is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scalefnt}

\DeclareRobustCommand\scalefont[1]{}
```

File 317 **lwarp-schemata.sty**

§ 415 Package schemata

(*Emulates or patches code by* Charles P. Schaum.)

Pkg schemata schemata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{schemata}[2016/01/25]

\LetLtxMacro\LWR@schemata@origschema\schema
\LetLtxMacro\LWR@schemata@origSchema\Schema

\renewcommand{\schema}[3][open]{%
\begin{lateximage}%
\LWR@print@normalsize
\LWR@schemata@origschema[#1]{#2}{#3}%
\end{lateximage}%
}

\renewcommand{\Schema}[5][open]{%
\begin{lateximage}%
\LWR@print@normalsize
\LWR@schemata@origSchema[#1]{#2}{#3}{#4}{#5}%
\end{lateximage}%
}
```

File 318 **lwarp-scrextend.sty**

§ 416 Package scrextend

Pkg scrextend scrextend is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrextend}[2018/03/30]

\DeclareDocumentCommand{\setkomafont}{m m}{}
\DeclareDocumentCommand{\addkomafont}{m m}{}
\DeclareDocumentCommand{\usekomafont}{m}{}

\DeclareDocumentCommand{\usefontofkomafont}{m}{}
\DeclareDocumentCommand{\useencodingofkomafont}{m}{}
\DeclareDocumentCommand{\usesizeofkomafont}{m}{}
\DeclareDocumentCommand{\usefamilyofkomafont}{m}{}
\DeclareDocumentCommand{\useseriesofkomafont}{m}{}
\DeclareDocumentCommand{\useshapeofkomafont}{m}{}

\AtBeginDocument{
\let\LWR@maketitle\maketitle
\DeclareDocumentCommand{\maketitle}{o}{\LWR@maketitle}
}

\DeclareDocumentCommand{\extratitle}{m}{}
\DeclareDocumentCommand{\titlehead}{m}{}
\DeclareDocumentCommand{\subject}{m}{}
\DeclareDocumentCommand{\publishers}{m}{\published{#1}}
\DeclareDocumentCommand{\uppertitleback}{m}{}
\DeclareDocumentCommand{\lowertitleback}{m}{}
\DeclareDocumentCommand{\dedication}{m}{}

\DeclareDocumentCommand{\ifthispageodd}{m m}{#1}

\DeclareDocumentCommand{\titlepagestyle}{}{}

\DeclareDocumentCommand{\cleardoublepageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleplainpage}{}{}
\DeclareDocumentCommand{\cleardoublestandardpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddpageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleoddemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleoddplainpage}{}{}
\DeclareDocumentCommand{\cleardoubleoddstandardpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenpageusingstyle}{m}{}
\DeclareDocumentCommand{\cleardoubleevenemptypage}{}{}
\DeclareDocumentCommand{\cleardoubleevenplainpage}{}{}
\DeclareDocumentCommand{\cleardoubleevenstandardpage}{}{}

\DeclareDocumentCommand{\multiplefootnoteseparator}{}{%
  \begingroup\let\thefootnotemark\multfootsep\@makefnmark\endgroup
}

\DeclareDocumentCommand{\multfootsep}{}{,}

```

```
\DeclareDocumentCommand{\footref}{m}{%
  \begingroup
    \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
  \endgroup
  \@footnotemark
}

\DeclareDocumentCommand{\deffootnote}{o m m m}{}
\DeclareDocumentCommand{\deffootnotemark}{m}{}
\DeclareDocumentCommand{\setfootnoterule}{o m}{}
\DeclareDocumentCommand{\raggedfootnote}{}{}

\DeclareDocumentCommand{\dictum}{o m}{
\begin{LWR@BlockClassWP}{\LWR@print@mbox{text-align:right}}{}{dictum}
    #2
    \IfValueT{#1}
    {
        \ifbool{FormatWP}
     {\begin{BlockClass}[\LWR@print@mbox{border-top:} 1px solid gray]{dictumauthor}}
        {\begin{BlockClass}{dictumauthor}}
        \dictumauthorformat{#1}
        \end{BlockClass}
    }
\end{LWR@BlockClassWP}
}

\DeclareDocumentCommand{\dictumwidth}{}{}
\DeclareDocumentCommand{\dictumauthorformat}{m}{(#1)}
\DeclareDocumentCommand{\dictumrule}{}{}
\DeclareDocumentCommand{\raggeddictum}{}{}
\DeclareDocumentCommand{\raggeddictumtext}{}{}
\DeclareDocumentCommand{\raggeddictumauthor}{}{}

\DeclareDocumentEnvironment{labeling}{o m}
{%
\def\sc@septext{#1}%
\list{}{}%
\let\makelabel\labelinglabel%
}
{
\endlist
}

\DeclareDocumentCommand{\labelinglabel}{m}{%
#1 \qquad \sc@septext%
}

\let\addmargin\relax
\let\endaddmargin\relax
\cslet{addmargin*}{\relax}
\cslet{endaddmargin*}{\relax}

\NewDocumentEnvironment{addmargin}{s O{} m}
{
\setlength{\LWR@templengthtwo}{#3}
```

```
\ifblank{#2}
{
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthtwo}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
{
    \setlength{\LWR@templengthone}{#2}
    \begin{BlockClass}[
        \LWR@print@mbox{margin-left:\LWR@printlength{\LWR@templengthone}} ;
        \LWR@print@mbox{margin-right:\LWR@printlength{\LWR@templengthtwo}}
    ]{addmargin}
}
}
{\end{BlockClass}}
```

Ref to create a starred environment:
https://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment

```

\ExplSyntaxOn
\cs_new:cpn {addmargin*} {\addmargin*}
\cs_new_eq:cN {endaddmargin*} \endaddmargin
\ExplSyntaxOff

\DeclareDocumentCommand{\marginline}{m}{\marginpar{#1}}
```

File 319 **lwarp-scrhack.sty**

§ 417 Package scrhack

Pkg scrhack scrhack is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{scrhack}[2018/03/30]
```

File 320 **lwarp-scrlayer.sty**

§ 418 Package scrlayer

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer scrlayer is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer}[2018/03/30]
```

```
\newcommand*{\DeclareSectionNumberDepth}[2]{}
\newcommand*{\DeclareLayer}[2][]{}
\newcommand*{\DeclareNewLayer}[2][]{}
\newcommand*{\ProvideLayer}[2][]{}
\newcommand*{\RedeclareLayer}[2][]{}
\newcommand*{\ModifyLayer}[2][]{}
\newcommand*{\layerhalign}{}
\newcommand*{\layervalign}{}
\newcommand*{\layerxoffset}{}
\newcommand*{\layeryoffset}{}
\newcommand*{\layerwidth}{}
\newcommand*{\layerheight}{}
\providecommand*{\LenToUnit}[1]{\strip@pt\dimexpr#1*\p@/\unitlength}
\newcommand*{\putUL}[1]{}
\newcommand*{\putUR}[1]{}
\newcommand*{\putLL}[1]{}
\newcommand*{\putLR}[1]{}
\newcommand*{\putC}[1]{}
\newcommand*{\GetLayerContents}[1]{}
\newcommand{\IfLayerExists}[3]{#3}
\newcommand*{\DestroyLayer}[1]{}
\newcommand*{\layercontentsmeasure}{}
\newcommand*{\currentpagestyle}{}
\newcommand*{\BeforeSelectAnyPageStyle}[1]{}
\newcommand*{\AfterSelectAnyPageStyle}[1]{}
\newcommand*{\DeclarePageStyleAlias}[2]{}
\newcommand*{\DeclareNewPageStyleAlias}[2]{}
\newcommand*{\ProvidePageStyleAlias}[2]{}
\newcommand*{\RedeclarePageStyleAlias}[2]{}
\newcommand*{\DestroyPageStyleAlias}[1]{}
\newcommand*{\GetRealPageStyle}[1]{}
\newcommand*{\DeclarePageStyleByLayers}[3][]{}
\newcommand*{\DeclareNewPageStyleByLayers}[3][]{}
\newcommand*{\ProvidePageStyleByLayers}[3][]{}
\newcommand*{\RedeclarePageStyleByLayers}[3][]{}
\NewDocumentCommand{\ForEachLayerOfPageStyle}{s m m}{}
\newcommand*{\AddLayersToPageStyle}[2]{}
\newcommand*{\AddLayersAtBeginOfPageStyle}[2]{}
\newcommand*{\AddLayersAtEndOfPageStyle}[2]{}
\newcommand*{\RemoveLayersFromPageStyle}[2]{}
\newcommand*{\AddLayersToPageStyleBeforeLayer}[3]{}
\newcommand*{\AddLayersToPageStyleAfterLayer}[3]{}
\newcommand*{\UnifyLayersAtPageStyle}[1]{}
\newcommand*{\ModifyLayerPageStyleOptions}[2]{}
\newcommand*{\AddToLayerPageStyleOptions}[2]{}
\newcommand{\IfLayerPageStyleExists}[3]{#3}
\newcommand{\IfRealLayerPageStyleExists}[3]{#3}
\newcommand{\IfLayerAtPageStyle}[4]{#4}
\newcommand{\IfSomeLayerAtPageStyle}[4]{#4}
\newcommand{\IfLayersAtPageStyle}[4]{#4}
\newcommand*{\DestroyRealLayerPageStyle}[1]{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\automark}{s o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
```

```
\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\DeclareDocumentCommand{\GenericMarkFormat}{m}{}

\newcommand*{\@mkleft}[1]{}
\newcommand*{\@mkright}[1]{}
\newcommand*{\@mkdouble}[1]{}
\newcommand*{\@mkboth}[2]{}
\newcommand*{\scrlayerInitInterface}[1][]{}
\newcommand{\scrlayerAddToInterface}[3][]{}
\newcommand{\scrlayerAddCsToInterface}[3][]{}
\newcommand{\scrlayerOnAutoRemoveInterface}[2][]{}
```

File 321 **lwarp-scrlayer-notecolumn.sty**

§ 419 Package scrlayer-notecolumn

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-notecolumn scrlayer-notecolumn is emulated.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-notecolumn}[2018/02/02]

\newcommand*{\DeclareNoteColumn}[2][]{}
\newcommand*{\DeclareNewNoteColumn}[2][]{}
\newcommand*{\ProvideNoteColumn}[2][]{}
\newcommand*{\RedeclareNoteColumn}[2][]{}
\NewDocumentCommand{\makenote}{s o m}{\marginpar{#3}}
\newcommand*{\syncwithnotecolumn}[1][]{}
\newcommand*{\syncwithnotecolumns}[1][]{}
\newcommand*{\clearnotecolumn}[1][]{}
\newcommand*{\clearnotecolumns}[1][]{}
```

File 322 **lwarp-scrlayer-scrpage.sty**

§ 420 Package scrlayer-scrpage

(*Emulates or patches code by* Markus Kohm.)

Pkg scrlayer-scrpage scrlayer-scrpage is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrlayer-scrpage}[2018/03/30]
```

```
\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{s o m}{}
\NewDocumentCommand{\cehead}{s o m}{}
\NewDocumentCommand{\rehead}{s o m}{}
\NewDocumentCommand{\lohead}{s o m}{}
\NewDocumentCommand{\cohead}{s o m}{}
\NewDocumentCommand{\rohead}{s o m}{}
\NewDocumentCommand{\lefoot}{s o m}{}
\NewDocumentCommand{\cefoot}{s o m}{}
\NewDocumentCommand{\refoot}{s o m}{}
\NewDocumentCommand{\lofoot}{s o m}{}
\NewDocumentCommand{\cofoot}{s o m}{}
\NewDocumentCommand{\rofoot}{s o m}{}
\NewDocumentCommand{\ohead}{s o m}{}
\NewDocumentCommand{\chead}{s o m}{}
\NewDocumentCommand{\ihead}{s o m}{}
\NewDocumentCommand{\ofoot}{s o m}{}
\NewDocumentCommand{\cfoot}{s o m}{}
\NewDocumentCommand{\ifoot}{s o m}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\newcommand*{\defpairofpagestyles}[3][]{}
\newcommand*{\newpairofpagestyles}[3][]{}
\newcommand*{\renewpairofpagestyles}[3][]{}
\newcommand*{\providepairofpagestyles}[3][]{}

\newcommand*{\clearmainofpairofpagestyles}{}
\newcommand*{\clearplainofpairofpagestyles}{}
\newcommand*{\clearpairofpagestyles}{}
\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}

\NewDocumentCommand{\deftriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\newtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\renewtriplepagestyle}{m o o m m m m m m}{}
\NewDocumentCommand{\providetriplepagestyle}{m o o m m m m m m}{}
\newcommand*{\defpagestyle}[3]{}
\newcommand*{\newpagestyle}[3]{}
\newcommand*{\providepagestyle}[3]{}
\newcommand*{\renewpagestyle}[3]{}
```

File 323 **lwarp-scrpage2.sty**

§ 421 Package

scrpage2

(*Emulates or patches code by* Markus Kohm.)

Pkg scrpage2 scrpage2 is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{scrpage2}[2018/03/30]
```

```
\@ifundefined{footheight}{\newlength\footheight}{}
\NewDocumentCommand{\lehead}{o m}{}
\NewDocumentCommand{\cehead}{o m}{}
\NewDocumentCommand{\rehead}{o m}{}
\NewDocumentCommand{\lohead}{o m}{}
\NewDocumentCommand{\cohead}{o m}{}
\NewDocumentCommand{\rohead}{o m}{}
\NewDocumentCommand{\lefoot}{o m}{}
\NewDocumentCommand{\cefoot}{o m}{}
\NewDocumentCommand{\refoot}{o m}{}
\NewDocumentCommand{\lofoot}{o m}{}
\NewDocumentCommand{\cofoot}{o m}{}
\NewDocumentCommand{\rofoot}{o m}{}
\NewDocumentCommand{\ohead}{o m}{}
\NewDocumentCommand{\chead}{o m}{}
\NewDocumentCommand{\ihead}{o m}{}
\NewDocumentCommand{\ofoot}{o m}{}
\NewDocumentCommand{\cfoot}{o m}{}
\NewDocumentCommand{\ifoot}{o m}{}
\DeclareDocumentCommand{\automark}{o m}{}
\DeclareDocumentCommand{\manualmark}{}{}
\DeclareDocumentCommand{\MakeMarkcase}{m}{#1}
\NewDocumentCommand{\deftripstyle}{m o o m m m m m m}{}
\NewDocumentCommand{\defpagestyle}{s m m m}{}
\NewDocumentCommand{\newpagestyle}{s m m m}{}
\NewDocumentCommand{\renewpagestyle}{s m m m}{}
\NewDocumentCommand{\providepagestyle}{s m m m}{}
\newcommand{\partmarkformat}{}
\if@chapter
\newcommand{\chaptermarkformat}{}
\fi
\newcommand{\sectionmarkformat}{}
\newcommand{\subsectionmarkformat}{}
\newcommand{\subsubsectionmarkformat}{}
\newcommand{\paragraphmarkformat}{}
\newcommand{\subparagraphmarkformat}{}

\newcommand*{\clearscrheadings}{}
\newcommand*{\clearscrheadfoot}{}
\newcommand*{\clearscrplain}{}
```

File 324 **lwarp-section.sty**

§ 422 Package

section

Pkg section section is ignored.

(*Emulates or patches code by* Oliver Pretzel.)

for HTML output:

```
\LWR@ProvidesPackageDrop{section}

\ifx\chapter\undefined
 \def\chsize{\Large}\def\hdsize{\huge}\else
```

```
 \def\chsize{\huge}\def\hdsize{\Huge}
\fi
\let\ttsize\LARGE
\let\ausize\large
\let\dasize\large
\let\secsize\Large
\let\subsize\large
\let\hdpos\raggedright
\newcounter{hddepth}
\let\fpind\relax
\def\ttfnt{}
\def\hdfnt{}
\def\fefnt{}
\def\thfnt{}
\def\pgfnt{}
\def\hmkfnt{}
\let\mkcse\uppercase
\def\hddot{}
\def\cpdot{:}
\def\nmdot{}
\ifx\secindent\undefined
 \newdimen\secindent
 \newskip\secpreskp
 \newskip\secpstskp
 \newdimen\subindent
 \newskip\subpreskp
 \newskip\subpstskp
 \newskip\parpstskp
 \newcount\c@hddepth
\fi
```

File 325 **lwarp-sectionbreak.sty**

§ 423 Package sectionbreak

(*Emulates or patches code by* Michal Hoftich.)

Pkg sectionbreak sectionbreak is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{sectionbreak}[2018-01-03]

\renewcommand\asterism{\HTMLunicode{2042}}

\renewcommand\pre@sectionbreak{}
\renewcommand\post@sectionbreak{}

\renewcommand\print@sectionbreak[1]{%
\begin{center}
#1
\end{center}
}

```

File 326 **lwarp-sectsty.sty**

§ 424 Package

sectsty

(*Emulates or patches code by* Rowland McDonnell.)

Pkg sectsty sectsty is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{sectsty}[2002/02/25]

\newcommand*{\partfont}          [1] {}
\newcommand*{\partnumberfont}    [1] {}
\newcommand*{\parttitlefont}     [1] {}
\newcommand*{\chapterfont}       [1] {}
\newcommand*{\chapternumberfont} [1] {}
\newcommand*{\chaptertitlefont}  [1] {}
\newcommand*{\sectionfont}       [1] {}
\newcommand*{\subsectionfont}    [1] {}
\newcommand*{\subsubsectionfont} [1] {}
\newcommand*{\paragraphfont}     [1] {}
\newcommand*{\subparagraphfont}  [1] {}
\newcommand*{\minisecfont}  [1] {}
\newcommand*{\allsectionsfont}[1] {}
\newcommand{\nohang}{}
```

`\sectionrule` is only to be used in `*font` commands, thus it is ignored.

```
\newcommand*{\sectionrule}[5]{}

\def\ulemheading#1#2{}
```

File 327 **lwarp-semantic-markup.sty**

§ 425 Package

semantic-markup

(*Emulates or patches code by* Andrew A. Cashner.)

Pkg semantic-markup semantic-markup is patched for use by lwarp.

⚠ If using the `endnotes` option, add `\theendnotes` where desired.

for HTML output:

```
\LWR@ProvidesPackagePass{semantic-markup}[2018/05/21]
```

The endnotes must be printed by the user before the end of the document, since the end is after the HTML footer, etc.

```
\ifendnotes
\RenewDocumentCommand{\SetupEndnotes}{}{%
```

```
    \let\footnote=\endnote
%     \AtEndDocument{\DoBeforeEndnotes{\EndnoteFont\theendnotes}}%
}
\fi
```

HTML unicode characters from musicography are used.

```
\RequirePackage{musicography}

\let\fl\musFlat
\let\sh\musSharp
\let\na\musNatural
```

The `\musfig` is placed inside a hashed image, with a simple `alt` tag.

```
\RequirePackage{amsmath}

\RenewDocumentCommand{\musfig}{ m m }{%
    \LWR@subsingledollar*%
        {#1/#2}% alt tag
        {musfig}% addl' hashing
        {% contents
            \LWR@origensuredmath{%
                \genfrac{}{}{0pt}{1}{\text{#1}}{\text{#2}}%
            }%
        }%
}
```

The `\meter` is taken from musicography, and becomes a hashed image with a simple `alt` tag.

```
\RenewDocumentCommand{\meter}{ m m }{%
    \musMeter{#1}{#2}%
}
```

File 328 **lwarp-setspace.sty**

§ 426 Package

setspace

(*Emulates or patches code by* Robin Fairbairns.)

Pkg setspace setspace is emulated.

Discard all options for lwarp-setspace:

for HTML output:

```
\LWR@ProvidesPackageDrop{setspace}[2011/12/19]

\newcommand*{\setstretch}[1]{}
\newcommand*{\SetSinglespace}[1]{}
\newcommand*{\singlespacing}{}
\newcommand*{\onehalfspacing}{}
\newcommand*{\doublespacing}{}
```

```
8
9 \newenvironment*{singlespace}
10 {
11 \LWR@forcenewpage
12 \BlockClass{singlespace}
13 }
14 {\endBlockClass}
15
16 \newenvironment*{singlespace*}
17 {
18 \LWR@forcenewpage
19 \BlockClass{singlespace}
20 }
21 {\endBlockClass}
22
23 \newenvironment*{spacing}[1]{
24
25 }{
26
27 }
28
29 \newenvironment*{onehalfspace}
30 {
31 \LWR@forcenewpage
32 \BlockClass{onehalfspace}
33 }
34 {\endBlockClass}
35
36 \newenvironment*{doublespace}
37 {
38 \LWR@forcenewpage
39 \BlockClass{doublespace}
40 }
41 {\endBlockClass}
```

File 329 **lwarp-shadow.sty**

§ 427 Package

shadow

(*Emulates or patches code by* Mauro Orlandini.)

Pkg shadow shadow is emulated.

for HTML output: Discard all options for lwarp-shadow:

```
1 \LWR@ProvidesPackageDrop{shadow}[2003/02/19]

2 \newdimen\sboxsep
3 \newdimen\sboxrule
4 \newdimen\sdim
5
6 \newcommand{\shabox}[1]{%
7 \InlineClass{shabox}{#1}%
```

```
8 }
```

File 330 **lwarp-shapepar.sty**

§ 428 Package shapepar

(*Emulates or patches code by* Donald Arseneau.)

Pkg shapepar shapepar is patched for use by lwarp. Shapes appear in print mode, as well as inside a lateximage, but are ignored for HTML.

for HTML output:

```
1 \LWR@ProvidesPackagePass{shapepar}[2013/03/26]

2 \newcommand*{\LWR@HTML@shapepar}[2][]{}
3 \LWR@formatted{shapepar}
4
5 \NewDocumentCommand{\LWR@HTML@cutout}{m d()}{}
6 \LWR@formatted{cutout}
```

File 331 **lwarp-showidx.sty**

§ 429 Package showidx

Pkg showidx showidx is ignored.

for HTML output: Discard all options for lwarp-showidx:

```
1 \LWR@ProvidesPackageDrop{showidx}[2014/09/29]
```

\@wrindex is redefined \AtBeginDocument by the lwarp core.

File 332 **lwarp-showkeys.sty**

§ 430 Package showkeys

(*Emulates or patches code by* David Carlisle, Morten Høgholm.)

Pkg showkeys showkeys is ignored.

for HTML output: Discard all options for lwarp-showkeys:

```
1 \LWR@ProvidesPackageDrop{showkeys}[2014/10/28]

2 \NewDocumentCommand{\showkeys}{s}{}
```

File 333 **lwarp-showtags.sty**

§ 431 Package showtags

Pkg showtags showtags is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{showtags}% no version is given
\newcommand{\thecitetag}[1]{}
```

File 334 **lwarp-sidecap.sty**

§ 432 Package sidecap

(*Emulates or patches code by* Rolf Niepraschk, Hubert Gässlein.)

Pkg sidecap sidecap is emulated.

for HTML output: Discard all options for lwarp-sidecap.

```
\LWR@ProvidesPackageDrop{sidecap}[2003/06/06]
```

See:
http://tex.stackexchange.com/questions/45401/use-the-s-star-argument-with-newdocumentenvironment
regarding the creation of starred environments with xparse.

```
\NewDocumentEnvironment{SCtable}{soo}
{\IfValueTF{#3}{\table[#3]}{\table}}
{\endtable}

\ExplSyntaxOn
\cs_new:cpn {SCtable*} {\SCtable*}
\cs_new_eq:cN {endSCtable*} \endSCtable
\ExplSyntaxOff


\NewDocumentEnvironment{SCfigure}{soo}
{\IfValueTF{#3}{\figure[#3]}{\figure}}
{\endfigure}

\ExplSyntaxOn
\cs_new:cpn {SCfigure*} {\SCfigure*}
\cs_new_eq:cN {endSCfigure*} \endSCfigure
\ExplSyntaxOff


\newenvironment*{wide}{}{}
```

File 335 **lwarp-sidenotes.sty**

§ 433 Package

sidenotes

(*Emulates or patches code by* Andy Thomas, Oliver Schebaum.)

Pkg sidenotes Patched for lwarp.

for HTML output: Load the original package:

```
\LWR@ProvidesPackagePass{sidenotes}
```

The following patch sidenotes for use with lwarp:

\sidecaption * [⟨*entry*⟩] [⟨*offset*⟩] {⟨*text*⟩}

```
\RenewDocumentCommand \sidecaption {s o o +m}
{
    \LWR@stoppars
    \begingroup
  \captionsetup{style=sidecaption}
  \IfBooleanTF{#1}
  { % starred
    \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
    \caption*{#4}
    \end{BlockClass}
  }
  { % unstarred
  \IfNoValueOrEmptyTF{#2}
    {\def\@sidenotes@sidecaption@tof{#4}}
    {\def\@sidenotes@sidecaption@tof{#2}}
    \begin{BlockClass}[border:none ; box-shadow:none]{marginblock}
    \caption[\@sidenotes@sidecaption@tof]{#4}
    \end{BlockClass}
  }
    \endgroup
    \LWR@startpars
}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTsidenotes@marginfloat}{O{-1.2ex} m}
{% start
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}

\RenewDocumentEnvironment{marginfigure}{o}
```

```
  {\begin{KFLTsidenotes@marginfloat}{figure}}
  {\end{KFLTsidenotes@marginfloat}}

\RenewDocumentEnvironment{margintable}{o}
  {\begin{KFLTsidenotes@marginfloat}{table}}
  {\end{KFLTsidenotes@marginfloat}}
```

The following were changed by sidenotes, and now are reset back to their lwarp-supported originals:

Restoring the definition from the LaTeX 2_ε `article.cls` source:

```
\renewenvironment{figure*}
               {\@dblfloat{figure}}
               {\end@dblfloat}

\renewenvironment{table*}
               {\@dblfloat{table}}
               {\end@dblfloat}
```

File 336 **lwarp-SIunits.sty**

§ 434 Package

Slunits

(*Emulates or patches code by* Marcel Heldoorn.)

Pkg SIunits Slunits is patched for use by lwarp.

It is recommended to use `\unit` where possible, which combines the entire expression into a single `lateximage`, and adds the `alt` tag containing the LaTeX code, allowing for copy/paste. When units are used outside of the `\unit` macro, each unit macro will have its own `lateximage`, and each will have the `alt` tag set to "`(<\mathimagename>)`", which defaults to "`(math image)`".

for HTML output:

```
\LWR@ProvidesPackagePass{SIunits}[2007/12/02]
```

Patched for copy/paste with the HTML `alt` tag:

```
\DeclareRobustCommand{\unit}[2]{%
\@inunitcommandtrue%    original
\LWR@subsingledollar*%  lwarp
{% alt tag
    \textbackslash{}unit\{\LWR@HTMLsanitize{#1}\}%
        \{ \LWR@HTMLsanitize{#2}\}% extra space
}%
{SIunits}% add'l hashing
{%
    \LWR@origensuredmath{%  lwarp modification
        \SI@fstyle{#1\@qsk\period@active{#2}}%  original
    }%
}% contents
\@inunitcommandfalse%   original
```

```
16 }
```

File 337 **lwarp-siunitx.sty**

§ 435 Package

siunitx

(*Emulates or patches code by* Joseph Wright.)

Pkg siunitx siunitx is patched for use by lwarp.

fractions Due to *pdftotext* limitations, fraction output is replaced by symbol output for `per-mode` and `quotient-mode`.

⚠ math mode required Some units will require that the expression be placed inside math mode.

NOTE: As of this writing, the siunitx extension for MathJax is not currently hosted at any public CDN, thus siunitx is not usable with MathJax unless a local copy of this extension is created first. See `\MathJaxFilename` to select a custom MathJax script.

⚠ tabular Tabular `S` columns are rendered as simple `c` columns, and tabular `s` columns are not supported. These may be replaced by `c` columns with each cell contained in `\num` or `\si`.

for HTML output:

```
1 \RequirePackage{xcolor}% for \convertcolorspec
2
3 \LWR@ProvidesPackagePass{siunitx}[2018/05/17]


4 \AtBeginDocument{% in case textcomp was not loaded
5 \DeclareSIUnit\bohr{\textit{a}\textsubscript{0}}
6 \DeclareSIUnit\clight{\textit{c}\textsubscript{0}}
7 \DeclareSIUnit\elementarycharge{\textit{e}}
8 \DeclareSIUnit\electronmass{\textit{m}\textsubscript{e}}
9 \DeclareSIUnit\hartree{\textit{E}\textsubscript{h}}
10 \DeclareSIUnit\planckbar{\LWR@siunitx@textplanckbar}
11 }% AtBeginDocument
```

`\@ensuredmath` is not supported inside an `\hbox`, so it must temporarily be restored to its original. Similar for `\mbox`. SVG math is created explicitly when necessary, using `\LWR@subsingledollar`.

```
12
13 \ExplSyntaxOn
14 %
```

Modified to set set HTML `\textcolor` if not black:

```
15 \cs_undefine:N \__siunitx_print_aux:
16 \cs_new_protected:Npn \__siunitx_print_aux:
17   {
18     \text
19       {
```

```
        \__siunitx_ensure_ltr:n
          {
            \color@begingroup
            \__siunitx_print_color:
            \__siunitx_font_shape:
            \__siunitx_font_weight:
            \use:c
              {
                @@_ \l__siunitx_print_type_tl _
                text \l__siunitx_font_family_tl :
              }
            \bool_if:NTF \l__siunitx_font_math_mode_bool
              { \__siunitx_print_math: }
              {
                \LWR@findcurrenttextcolor% lwarp
                \ifdefstring{\LWR@tempcolor}{000000}% lwarp
                {\__siunitx_print_text:}% lwarp
                {% lwarp
                    \LWR@textcurrentcolor{% lwarp
                        \__siunitx_print_text:
                    }% lwarp
                }% lwarp
              }
            \color@endgroup
          }
      }
  }


\cs_undefine:N \__siunitx_set_math_fam:n
\cs_new_protected:Npn \__siunitx_set_math_fam:n #1 {
  \int_new:c { c__siunitx_math #1 _int }
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \hbox_set:Nn \l__siunitx_tmp_box
      {
        \ensuremath
          {
            \use:c { math #1 }
              {
                \int_gset:cn { c__siunitx_math #1 _int } { \fam }
              }
          }
      }
  \group_end:% lwarp
}

\cs_undefine:N \__siunitx_combined_output:n
\cs_new_protected:Npn \__siunitx_combined_output:n #1 {
    \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
  \bool_if:NTF \l__siunitx_number_parse_bool
    {
```

```
      \tl_clear:N \l__siunitx_number_out_tl
      \bool_set_false:N \l__siunitx_number_compound_bool
      \__siunitx_number_output_parse:n {#1}
    }
    {
      \__siunitx_unit_output_pre_print:
```

For parse-numbers=false:

```
%       \__siunitx_print:nn { number } { \ensuremath {#1} }
        \LWR@subsingledollar{% lwarp
            \textbackslash( \LWR@HTMLsanitize{#1} \textbackslash)% lwarp
        }{siunitx}{%
            \__siunitx_print:nn { number } {%
                \LWR@origensuredmath{#1}%
            }%
        }% lwarp

      \__siunitx_unit_output_print:
    }
    \group_end:% lwarp
}
%
```

For quotients, the fraction code is replaced by the symbol code:

```
\cs_undefine:N \__siunitx_number_output_quotient_fraction:
\cs_new_protected:Npn \__siunitx_number_output_quotient_fraction: {
  \bool_set_true:N \l__siunitx_number_compound_bool
  \__siunitx_number_output_quotient_aux_i:
  \tl_set_eq:NN \l__siunitx_number_out_tl
    \l__siunitx_number_numerator_tl
  \tl_put_right:NV \l__siunitx_number_out_tl \l__siunitx_output_quotient_tl
  \tl_put_right:NV \l__siunitx_number_out_tl
    \l__siunitx_number_denominator_tl
  \__siunitx_number_output_single_aux:
}
```

For units, the fraction code is replaced by the symbol code:

```
\cs_undefine:N \__siunitx_unit_format_fraction_fraction:
\cs_new_protected:Npn \__siunitx_unit_format_fraction_fraction: {
  \__siunitx_unit_format_fraction_symbol_aux:
  \int_compare:nNnT { \l__siunitx_unit_denominator_int } > { 1 }
    {
      \bool_if:NT \l__siunitx_unit_denominator_bracket_bool
        {
       \tl_put_left:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_open_tl
       \tl_put_right:NV \l__siunitx_unit_denominator_tl \l__siunitx_bracket_close_tl
        }
    }
  \tl_set_eq:NN \l__siunitx_unit_tl \l__siunitx_unit_numerator_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_per_symbol_tl
  \tl_put_right:NV \l__siunitx_unit_tl \l__siunitx_unit_denominator_tl
}
```

```
\cs_undefine:N \__siunitx_angle_print_astronomy_aux:
\cs_new_protected:Npn \__siunitx_angle_print_astronomy_aux: {
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-integer }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
 \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}% lwarp
 {% lateximage
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
    }
  \hbox_set:Nn \l__siunitx_angle_unit_box
    {
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \skip_horizontal:n { -\scriptspace }
    }
  \__siunitx_angle_print_astronomy_aux:n { marker }
  \__siunitx_angle_print_astronomy_aux:n { unit }
  \hbox_set:Nn \l__siunitx_angle_marker_box
    {
      \box_use:N \l__siunitx_angle_marker_box
      \box_use:N \l__siunitx_angle_unit_box
    }
  \dim_compare:nNnTF
    { \l__siunitx_angle_marker_dim } > { \l__siunitx_angle_unit_dim }
    { \__siunitx_angle_print_astronomy_marker: }
    { \__siunitx_angle_print_astronomy_unit: }
 }% lateximage
 {% not a lateximage
      \__siunitx_print:nV { unit } \l__siunitx_unit_tl
      \__siunitx_print:nn { number } { { \l__siunitx_output_decimal_tl } }
 }% not a lateximage
  \prop_get:NnNT \l__siunitx_number_out_prop { mantissa-decimal }
    \l__siunitx_tmpa_tl
    { \__siunitx_print:nV { number } \l__siunitx_tmpa_tl }
}

\RenewDocumentCommand \num { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_number_output:n {#2}
  \group_end:% lwarp
}

\RenewDocumentCommand \numrange { o m m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
```

```
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_range_numbers:nn {#2} {#3}
  \group_end:% lwarp
}

\RenewDocumentCommand \ang { o > { \SplitArgument { 2 } { ; } } m } {
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \IfNoValueF {#1}
      { \keys_set:nn { siunitx } {#1} }
    \__siunitx_angle_output:nnn #2
  \group_end:% lwarp
}

\RenewDocumentCommand \si { o m } {
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_unit_output:nn {#2} { } }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_unit_output:nn {#2} {#1}
      }
  \group_end:% lwarp
}


\RenewDocumentCommand{\SIrange}{o m m m}
{%
  \leavevmode
  \group_begin:% lwarp
    \LetLtxMacro\@ensuredmath\LWR@origensuredmath% lwarp
    \LetLtxMacro\mbox\LWR@print@mbox% lwarp
    \bool_set_false:N \l__siunitx_font_set_bool
    \IfNoValueTF {#1}
      { \__siunitx_range_unit:nnnn {#4} { } {#2} {#3} }
      {
        \keys_set:nn { siunitx } {#1}
        \__siunitx_range_unit:nnnn {#4} {#1} {#2} {#3}
      }
  \group_end:% lwarp
}

\ExplSyntaxOff
```

File 338 **lwarp-slantsc.sty**

§ 436 Package slantsc

(*Emulates or patches code by* Harald Harders.)

Pkg slantsc slantsc is emulated for HTML, and used as-is for print output.

for HTML output:

```
\LWR@ProvidesPackagePass{slantsc}[2012/01/01]

\newcommand*{\LWR@HTML@noscshape}{}
\LWR@formatted{noscshape}

\newcommand*{\LWR@null@noscshape}{}

\appto{\LWR@nullfonts}{%
\LetLtxMacro\noscshape\LWR@null@noscshape%
}
```

File 339 **lwarp-soul.sty**

§ 437 Package soul

(*Emulates or patches code by* Melchior FRANZ.)

Pkg soul soul is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{soul}[2003/11/17]
\RequirePackage{xcolor}% for \convertcolorspec
```

Storage for the colors to use:

```
\newcommand*{\LWR@soululcolor}{}

\newcommand*{\LWR@soulstcolor}{}

% \definecolor{LWR@soulhlcolordefault}{HTML}{F8E800}
% \newcommand*{\LWR@soulhlcolor}{LWR@soulhlcolordefault}
\newcommand*{\LWR@soulhlcolor}{}
```

\so {⟨*text*⟩}

Basic markup with CSS:

```
\newcommand{\so}[1]{%
\InlineClass(letter-spacing:.2ex){letterspacing}{#1}%
}
```

\caps {⟨*text*⟩}

```
\newcommand{\caps}[1]{%
    \InlineClass%
        (font-variant:small-caps;letter-spacing:.1ex)%
        {capsspacing}{#1}%
}
```

\LWR@soulcolor {⟨*text*⟩} {⟨*color*⟩} {⟨*class*⟩} {⟨*colorstyle*⟩} {⟨*FormatWPstyle*⟩}

Add colors if not empty:

```
\newcommand{\LWR@soulcolor}[5]{%
\ifcsempty{#2}%
{%
    \InlineClass(#5){#3}{#1}%
}%
{%
    \convertcolorspec{named}{\@nameuse{#2}}{HTML}\LWR@tempcolor%
    \LWR@htmlspanclass[#5;#4:\LWR@origpound\LWR@tempcolor]{#3}{#1}%
}%
}
```

```
\newcommand{\ul}[1]{%
\LWR@soulcolor{#1}{LWR@soululcolor}{uline}{text-decoration-color}%
    {text-decoration:underline; text-decoration-skip: auto;}%
}

\newcommand{\st}[1]{
\LWR@soulcolor{#1}{LWR@soulstcolor}{sout}{text-decoration-color}%
    {text-decoration:line-through}%
}

\newcommand{\hl}[1]{
\LWR@soulcolor{#1}{LWR@soulhlcolor}{highlight}{background-color}%
    {background:\LWR@origpound{}F8E800}
}
```

Nullified:

```
\newcommand*{\soulaccent}[1]{}
\newcommand*{\soulregister}[2]{}
\newcommand{\sloppyword}[1]{#1}
\newcommand*{\sodef}[5]{\DeclareRobustCommand*#1[1]{\so{##1}}}
\newcommand*{\resetso}{}
\newcommand*{\capsdef}[5]{}
\newcommand*{\capsreset}{}
\newcommand*{\capssave}[1]{}
\newcommand*{\capsselect}[1]{}
\newcommand*{\setul}[2]{}
\newcommand*{\resetul}{}
\newcommand*{\setuldepth}[1]{}
\newcommand*{\setuloverlap}[1]{}
```

Set colors:

```
\newcommand*{\setulcolor}[1]{\renewcommand{\LWR@soululcolor}{#1}}
\newcommand*{\setstcolor}[1]{\renewcommand{\LWR@soulstcolor}{#1}}
\newcommand*{\sethlcolor}[1]{\renewcommand{\LWR@soulhlcolor}{#1}}
```

Long versions of the user-level macros:

```
\let\textso\so
\let\textul\ul
\let\texthl\hl
\let\textcaps\caps
```

File 340 **lwarp-soulpos.sty**

§ 438 Package soulpos

(*Emulates or patches code by* Javier Bezos.)

Pkg soulpos soulpos is emulated.

for HTML output:

```
\RequirePackage{soul}
\RequirePackage{soulutf8}
\LWR@ProvidesPackageDrop{soulpos}[2012/02/25]

\NewDocumentCommand{\ulposdef}{m o m}{}

\newdimen\ulwidth

\newcommand\ifulstarttype[1]{%
\expandafter\@secondoftwo%
}

\newcommand\ifulendtype[1]{%
\expandafter\@secondoftwo%
}

\newcommand{\ulstarttype}{0}
\newcommand{\ulendtype}{0}
\newcommand\ulpostolerance{0}%
```

File 341 **lwarp-soulutf8.sty**

§ 439 Package soulutf8

Pkg soulutf8 soulutf8 is emulated.

lwarp's HTML output naturally supports UTF-8 encoding.

for HTML output:

```
\LWR@ProvidesPackageDrop{soulutf8}[2016/05/16]
\RequirePackage{soul}
```

File 342 **lwarp-splitidx.sty**

§ 440 Package

splitidx

(*Emulates or patches code by* Markus Kohm.)

Pkg splitidx splitidx is patched for use by lwarp.

If the latexmk option is selected for lwarp, *latexmk* will compile the document but will *not* compile the indexes. **lwarpmk printindex** and **lwarpmk htmlindex** will still be required.

⚠ \thepage When using \AtWriteToIndex or \AtNextWriteToIndex, the user must not refer to \thepage during HTML output, as the concept of a page number is meaningless. Instead, do

```
\addtocounter{LWR@autoindex}{1}
\LWR@new@label{LWRindex-\arabic{LWR@autoindex}}
```

where the \index-like action occurs, and then refer to \arabic{LWR@autoindex} instead of \thepage where the reference should occur.

See section 532.17 in the lwarp-patch-memoir package for the \@@wrspindexhyp macro as an example.

for HTML output:

```
\LWR@ProvidesPackagePass{splitidx}[2016/02/18]

\catcode`\_=12%
\xpatchcmd{\newindex}
    {\jobname-#2.idx}
    {\jobname-#2_html.idx}
    {}
    {\LWR@patcherror{splitidx}{@newindex}}
\catcode`\_=8%
```

Patched to use lwarp's automatic indexing counter instead of \thepage:

```
\renewcommand*{\@wrsindex}[2][]{%
  \ifx\relax#1\relax
    \if@splitidx
      \@wrsindex[idx]{#2}%
    \else
      \def\@tempa{#2}%
      \if@verbindex\@onelevel@sanitize\@tempa\fi
      \@wrindex{\@tempa}%
    \fi
  \else
    \def\@tempa{#2}%
```

```
    \csname index@#1@hook\endcsname
%     \expandafter\ifx\csname @@wrsindex\endcsname\relax
    \addtocounter{LWR@autoindex}{1}%                    lwarp
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%    lwarp
%       \@@@wrsindex{#1}{{\@tempa}{\thepage}}%
      \@@@wrsindex{#1}{{\@tempa}{\arabic{LWR@autoindex}}}%
%     \else
%       \def\@tempb{\@@wrsindex{#1}}%
%       \expandafter\@tempb\@tempa||\\%
%     \fi
    \endgroup
    \@esphack
  \fi
}
```

lwarp defines sectioning commands with xparse, so the below patches are done as temporary redefinitions instead of being `\let`.

```
\xpatchcmd{\printsubindex}
    {\let\section\subsection}
    {\renewcommand*{\section}{\subsection}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-section}}

\xpatchcmd{\printsubindex}
    {\let\chapter\section}
    {\renewcommand*{\chapter}{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}

\xpatchcmd{\printsubindex}
    {\let\@makechapterhead\section}
    {\def\@makechapterhead{\section}}
    {}
    {\LWR@patcherror{splitidx}{printsubindex-chapter}}
```

File 343 **lwarp-srcltx.sty**

§ 441 Package

srcltx

Pkg srcltx

srcltx is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{srcltx}[2006/11/12]

\newif\ifSRCOK \SRCOKfalse
\newcommand*\srcIncludeHook[1]{}
\newcommand*\srcInputHook[1]{}
\newcommand*\MainFile{}
\def\MainFile{\jobname.tex}
\newcommand*\CurrentInput{}
\gdef\CurrentInput{\MainFile}
\newcommand\Input{}
```

```
10 \let\Input\input
```

File 344 **lwarp-srctex.sty**

§ 442 Package srctex

Pkg srctex srctex is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{srctex}[2006/11/12]
2 \LWR@origRequirePackage{lwarp-srcltx}
```

File 345 **lwarp-stabular.sty**

§ 443 Package stabular

(*Emulates or patches code by* Sigitas Tolušis.)

Pkg stabular stabular is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{stabular}[2014/03/20]
```

Env stabular [⟨*vpos*⟩] {⟨*colspec*⟩}

```
2 \newenvironment{stabular}[2][c]
3 {
4 \begin{tabular}[#1]{#2}
5 \renewcommand{\noalign}[1]{}
6 }
7 {\end{tabular}}
```

Env stabular {⟨*width*⟩} [⟨*vpos*⟩] {⟨*colspec*⟩}

```
8 \NewDocumentEnvironment{stabular*}{m o m}
9 {
10 \begin{tabular}[#2]{#3}
11 \renewcommand{\noalign}[1]{}
12 }
13 {\end{tabular}}
```

File 346 **lwarp-stfloats.sty**

§ 444 Package stfloats

Pkg stfloats stfloats is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{stfloats}[2017/03/27]
```

stfloats may have been preloaded by a ltj* class.

The following are provided in case they have not yet been defined:

```
\providecommand*{\fnbelowfloat}{}
\providecommand*{\fnunderfloat}{}
\providecommand*{\setbaselinefloat}{}
\providecommand*{\setbaselinefixed}{}
```

Nullified for HTML:

```
\renewcommand*{\fnbelowfloat}{}
\renewcommand*{\fnunderfloat}{}
\renewcommand*{\setbaselinefloat}{}
\renewcommand*{\setbaselinefixed}{}
```

File 347 **lwarp-struktex.sty**

§ 445 Package struktex

(*Emulates or patches code by* JOBST HOFFMANN.)

Pkg struktex struktex is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{struktex}[2018/06/04]

\BeforeBeginEnvironment{struktogramm}{\begin{lateximage}[(struktogramm)]}
\AfterEndEnvironment{struktogramm}{\end{lateximage}}

\newenvironment{LWR@HTML@centernss}{\begin{center}}{\end{center}}
\LWR@formattedenv{centernss}

\newcommand{\LWR@HTML@CenterNssFile}[1]{%
    \begin{center}
    \input{#1.nss}
    \end{center}
}
\LWR@formatted{CenterNssFile}

\newcommand{\LWR@HTML@centernssfile}{\LWR@HTML@CenterNssFile}
\LWR@formatted{centernssfile}
```

File 348 **lwarp-subcaption.sty**

§ 446 Package subcaption

(*Emulates or patches code by* AXEL SOMMERFELDT.)

Pkg subcaption subcaption is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{subcaption}[2018/05/01]
```

Tells lwarp to ignore minipage widths inside a subfigure or subtable. In print mode the minipages are used to place the items next to each other. In HTML they are placed side-by-side automatically.

```
\ifdef{\subcaption@minipage}{
    \xpatchcmd{\subcaption@minipage}
        {\minipage}
        {\minipagefullwidth\minipage}
        {}
        {\LWR@patcherror{subcaption}{subcaption@minipage}}
}{}
```

Likewise for a \subcaptionbox:

```
\ifdef{\subcaptionbox}{
    \xpretocmd{\subcaptionbox}
        {\minipagefullwidth}
        {}
        {\LWR@patcherror{subcaption}{subcaptionbox}}
}{}
```

File 349 **lwarp-subfig.sty**

§ 447 Package

subfig

(*Emulates or patches code by* Steven Douglas Cochran.)

Pkg subfig

subfig is supported and patched by lwarp.

⚠ lof/lotdepth

At present, the package options for lofdepth and lotdepth are not working. These counters must be set separately after the package has been loaded.

In the document source, use \hfill and \hspace* subfig>inline between subfigures to spread them apart horizontally. The use of other forms of whitespace may cause paragraph tags to be generated, resulting in subfigures appearing on the following lines instead of all on a single line.

for HTML output:

Accept all options for lwarp-subfig:

```
\LWR@ProvidesPackagePass{subfig}[2005/06/28]
```

\sf@@@subfloat {⟨*1 type*⟩} [⟨*2 LOF entry*⟩] [⟨*3 caption*⟩] {⟨*4 contents*⟩}

The outer minipage allows side-by-side subfloats with \hfill between.

```
\long\def\sf@@@subfloat#1[#2][#3]#4{%
\begin{minipage}{\linewidth}% lwarp

\IfValueTF{#2}{%
    \LWR@setlatestname{#2}%
```

```
}{%
    \IfValueTF{#3}{%
        \LWR@setlatestname{#3}%
    }{}%
}%
\LWR@stoppars% lwarp
    \@ifundefined{FBsc@max}{}%
        {\FB@readaux{\let\FBsuboheight\relax}}%
    \@tempcnta=\@ne
    \if@minipage
      \@tempcnta=\z@
    \else\ifdim \lastskip=\z@ \else
      \@tempcnta=\tw@
    \fi\fi
    \ifmaincaptiontop
      \sf@top=\sf@nearskip
      \sf@bottom=\sf@farskip
    \else
      \sf@top=\sf@farskip
      \sf@bottom=\sf@nearskip
    \fi
    \leavevmode

%     \setbox\@tempboxa \hbox{#4}%
%     \@tempdima=\wd\@tempboxa
%     \@ifundefined{FBsc@max}{}%
%         {\global\advance\Xhsize-\wd\@tempboxa
%          \dimen@=\ht\@tempboxa
%          \advance\dimen@\dp\@tempboxa
%          \ifdim\dimen@>\FBso@max
%            \global\FBso@max\dimen@
%          \fi}%
```

Do not use boxes, which interfere with `lateximages`:

```
%     \vtop%
    \bgroup
%       \vbox%
      \bgroup
        \ifcase\@tempcnta
          \@minipagefalse
        \or
%           \vskip\sf@top
        \or
          \ifdim \lastskip=\z@ \else
%             \@tempskipb\sf@top\relax\@xaddvskip
          \fi
        \fi
        \sf@ifpositiontop{%
          \ifx \@empty#3\relax \else
            \sf@subcaption{#1}{#2}{#3}%
%             \vskip\sf@capskip
%             \vskip\sf@captopadj
          \fi\egroup
%           \hrule width0pt height0pt depth0pt
            \LWR@startpars% lwarp
```

```
% \box\@tempboxa
            #4
            \LWR@stoppars% lwarp
        }{%
        \LWR@startpars% lwarp
        \@ifundefined{FBsc@max}%
            {
% \box\@tempboxa
                #4
            }%
            {\ifx\FBsuboheight\relax
%                \box\@tempboxa
                #4
             \else
%                \vbox to \FBsuboheight{\FBafil\box\@tempboxa\FBbfil}%
                #4
             \fi}%
        \LWR@stoppars% lwarp
          \egroup
          \ifx \@empty#3\relax \else
%             \vskip\sf@capskip
%             \hrule width0pt height0pt depth0pt
            \sf@subcaption{#1}{#2}{#3}%
         \fi
        }%
%       \vskip\sf@bottom
    \egroup
    \@ifundefined{FBsc@max}{}%
        {\addtocounter{FRobj}{-1}%
         \ifnum\c@FRobj=0\else
           \subfloatrowsep
         \fi}%
    \ifmaincaptiontop\else
      \global\advance\@nameuse{c@\@captype}\m@ne
    \fi
\end{minipage}% lwarp
\LWR@startpars% lwarp
  \endgroup\ignorespaces%
}%
```

\sf@subcaption {⟨*1 type*⟩} {⟨*2* LOF *entry*⟩} {⟨*3 caption*⟩}

```
\long\def\sf@subcaption#1#2#3{%
\LWR@stoppars% lwarp
  \ifx \relax#2\relax \else
    \bgroup
      \let\label=\@gobble
      \let\protect=\string
      \def\@subcaplabel{%
        \caption@lstfmt{\@nameuse{p@#1}}{\@nameuse{the#1}}}%
      \sf@updatecaptionlist{#1}{#2}{\the\value{\@captype}}{\the\value{#1}}%
    \egroup
  \fi
  \bgroup
    \ifx \relax#3\relax
```

```
      \let\captionlabelsep=\relax
    \fi
%     \setbox0\vbox{%
%        \hb@xt@\the\@tempdima{%
%
% %          \hss
% %         \parbox[t]{\the\@tempdima}{%
%           \caption@make
%               {\@nameuse{sub\@captype name}}%
%               {\@nameuse{thesub\@captype}}%
%               {#3}
% %  }%
% %            \hss
%   }
%  }%
    \@ifundefined{FBsc@max}%
%         {\box0}%
        {
%  \parbox[t]{\the\@tempdima}{%
\LWR@traceinfo{sfsubcap B1}% lwarp
            \LWR@figcaption% lwarp
            \caption@make
                {\@nameuse{sub\@captype name}}%
                {\@nameuse{thesub\@captype}}%
                {\LWR@isolate{#3}}%

            \endLWR@figcaption% lwarp
\LWR@traceinfo{sfsubcap B2}% lwarp
%  }%
        }%
        {\dimen@\ht0%
         \advance\dimen@\dp0%
         \ifdim\dimen@>\FBsc@max
           \global\FBsc@max\dimen@
         \fi
         \FB@readaux{\let\FBsubcheight\relax}%
         \ifx\FBsubcheight\relax
           \def\next{
%  \parbox[t]{\the\@tempdima}
            }%
         \else
           \def\next{
%  \parbox[t][\FBsubcheight][t]{\the\@tempdima}
            }%
         \fi
%          \vbox{%
%            \hb@xt@\the\@tempdima{%
%
%              \hss
%              \next{%
\LWR@traceinfo{sfsubcap C1}% lwarp
                \caption@make
                    {\@nameuse{sub\@captype name}}%
                    {\@nameuse{thesub\@captype}}%
                    {#3}
\LWR@traceinfo{sfsubcap C1}% lwarp
```

```
%  }%
%               \hss
%
%  }
%            }
         }%
  \egroup
\LWR@startpars% lwarp
}
```

\subfloat@label Patches for \sf@sub@label:

```
\def\subfloat@label{%
\LWR@ensuredoingapar% lwarp
  \@ifnextchar(%   %) match left parenthesis
    {\sf@sub@label}
    {\sf@sub@label(Sub\@captype\space
                   \@ifundefined{thechapter}{}{\@nameuse{thechapter}\space}%
                   \@nameuse{p@sub\@captype}%
                   \@nameuse{thesub\@captype}.)}}
```

Patches for \subref.

\sf@subref {⟨*label*⟩}

The unstarred version uses a \ref link whose printed text comes from the sub@<label>:

```
\renewcommand{\sf@subref}[1]{%
\LWR@subnewref{#1}{sub@#1}%
}
```

\sf@@subref {⟨*label*⟩}

The starred version uses the printed sub@<label> which is stored as if it were a page number:

```
\renewcommand{\sf@@subref}[1]{\LWR@orig@pageref{sub@#1}}
```

Defining new subfloats. The l@sub<type> for each is redefined.

\@newsubfloat [⟨*keys/values*⟩] {⟨*float name*⟩}

```
\LetLtxMacro\LWR@orig@newsubfloat\@newsubfloat

\def\@newsubfloat[#1]#2{%
\LWR@orig@newsubfloat[#1]{#2}%
\renewcommand{\l@sub#2}[2]{\hypertocfloat{2}{sub#2}{\ext@sub#2}{##1}{##2}}%
}
```

Pre-defined for figures and tables:

\l@subfigure {⟨*text*⟩} {⟨*pagenum*⟩}

```
\renewcommand{\l@subfigure}[2]{\hypertocfloat{2}{subfigure}{lof}{#1}{#2}}
```

\l@subtable {⟨*text*⟩} {⟨*pagenum*⟩}

```
193 \renewcommand{\l@subtable}[2]{\hypertocfloat{2}{subtable}{lot}{#1}{#2}}
```

File 350 **lwarp-subfigure.sty**

§ 448 Package

subfigure

Pkg subfigure

subfigure is emulated by subfig.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{subfigure}[2002/03/15]
2 \RequirePackage{subfig}

3 \LetLtxMacro\subfigure\subfloat
4 \LetLtxMacro\subtable\subfloat
5 \LetLtxMacro\Subref\subref
6 \@ifundefined{figuretopcaptrue}{\newif\iffiguretopcap}{}
7 \newif\ifsubfiguretopcap
8 \newif\ifsubcaphang
9 \newif\ifsubcapcenter
10 \newif\ifsubcapcenterlast
11 \newif\ifsubcapnooneline
12 \newif\ifsubcapraggedright
13 \newskip\subfigtopskip
14 \newskip\subfigcapskip
15 \newdimen\subfigcaptopadj
16 \newskip\subfigbottomskip
17 \newdimen\subfigcapmargin
18 \newskip\subfiglabelskip
19 \newcommand*{\subcapsize}{}
20 \newcommand*{\subcaplabelfont}{}
21 \newcommand*{\subcapfont}{}
```

File 351 **lwarp-supertabular.sty**

§ 449 Package

supertabular

(*Emulates or patches code by* Johannes Braams, Theo Jurriens.)

Pkg supertabular

supertabular is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{supertabular}[2004/02/20]
```

⚠ Misplaced alignment tab character &

For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a lateximage.

```
\newcommand{\LWRST@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRST@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}
\newcommand{\tabletail}[1]{}

\newcommand{\LWRST@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRST@lasttail{#1}%
}


\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRST@caption{%
        \ifblank{#1}%
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption


\newcommand*{\LWRST@caption}{}

\newcommand*{\shrinkheight}[1]{}

\NewDocumentEnvironment{supertabular}{s o m}
{%
\LWR@traceinfo{supertabular}%
\begin{table}%
\LWRST@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRST@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRST@firsthead}%
}%
{%
\ifdefvoid{\LWRST@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRST@lasttail%
}%
\end{tabular}%
\end{table}%


\gdef\LWRST@caption{}%
```

```
\LWR@traceinfo{supertabular done}%
}

\NewDocumentEnvironment{mpsupertabular}{s o m}
{\minipage{\linewidth}\supertabular{#3}}
{\endsupertabular\endminipage}
```

File 352 **lwarp-syntonly.sty**

§ 450 Package syntonly

(*Emulates or patches code by* Frank Mittelbach, Rainer Schöpf.)

Pkg syntonly syntonly is ignored.

for HTML output: Discard all options for lwarp-syntonly:

```
\LWR@ProvidesPackageDrop{syntonly}[2017/06/30]

\newif\ifsyntax@
\syntax@false

\newcommand*{\syntaxonly}{}

\@onlypreamble\syntaxonly
```

File 353 **lwarp-tabfigures.sty**

§ 451 Package tabfigures

Pkg tabfigures tabfigures is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tabfigures}[2012/01/24]
```

File 354 **lwarp-tablefootnote.sty**

§ 452 Package tablefootnote

Pkg tablefootnote tablefootnote is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tablefootnote}[2014/01/26]
```

This works because in HTML tables are no longer floats.

```
\LetLtxMacro\tablefootnote\footnote
```

File 355 **lwarp-tabls.sty**

§ 453 Package tabls

(*Emulates or patches code by* Donald Arseneau.)

Pkg tabls tabls is emulated. \LWR@hline is used to handle the optional argument when tabls is loaded.

for HTML output:

```
\LWR@ProvidesPackageDrop{tabls}

\newdimen\tablinesep
\newdimen\arraylinesep
\newdimen\extrarulesep
```

File 356 **lwarp-tabularx.sty**

§ 454 Package tabularx

(*Emulates or patches code by* David Carlisle.)

Pkg tabularx tabularx is emulated by lwarp.

for HTML output: Discard all options for lwarp-tabularx:

```
\LWR@ProvidesPackageDrop{tabularx}[2016/02/03]
\RequirePackage{array}

\DeclareDocumentEnvironment{tabularx}{m o m}
{\tabular{#3}}
{\endtabular}

\DeclareDocumentEnvironment{tabularx*}{m o m}
{\tabular{#3}}
{\endtabular}
```

File 357 **lwarp-tabulary.sty**

§ 455 Package tabulary

(*Emulates or patches code by* David Carlisle.)

Pkg tabulary tabulary is emulated by lwarp.

for HTML output:

Discard all options for lwarp-tabulary.

Column types L, C, R, and J are emulated by lwarp core code.

```
\LWR@ProvidesPackageDrop{tabulary}[2014/06/11]
\RequirePackage{array}

\NewDocumentEnvironment{tabulary}{m o m}
{\tabular{#3}}
{\endtabular}

\NewDocumentEnvironment{tabulary*}{m o m}
{\tabular{#3}}
{\endtabular}

\newdimen\tymin
\newdimen\tymax
\def\tyformat{}
```

File 358 **lwarp-tascmac.sty**

§ 456 Package

tascmac

Pkg tascmac tascmac is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{tascmac}[2018/03/09]

\newenvironment*{boxnote}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            border-top: 1px dashed black ;
        ]{boxnote}
    }
    {\endBlockClass}

\newenvironment*{screen}[1][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
            border-radius: 8pt
        ]{boxnote}
    }
    {\endBlockClass}

\newenvironment*{itembox}[2][]
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid gray ;
```

```
            border-radius: 8pt
        ]{boxnote}
        \InlineClass{itemboxtitle}{#2}\par
    }
    {\endBlockClass}

\newenvironment*{shadebox}
    {
        \BlockClass[
            padding: .5ex ;
            border: 1px solid black ;
            box-shadow: 3px 3px 3px \#808080 ;
        ]{boxnote}
    }
    {\endBlockClass}

\newcommand*{\mask}[2]{%
    \InlineClass[background: lightgray]{mask}{#1}%
}

\newcommand*{\maskbox}[5]{%
    \InlineClass[background: lightgray]{mask}{#5}%
}

\newcommand*{\Maskbox}[6]{%
    \InlineClass[
        background: lightgray ;
        border: #5 solid black
    ]{mask}{#6}%
}

\newcommand*{\keytop}[2][]{%
    \InlineClass[%
        padding: .2ex ;
        border: 1px solid black ;
        border-radius: .7ex ;
    ]{keytop}{#2}%
}

\def\yen{\HTMLunicode{00A5}}

\def\return{\HTMLunicode{23CE}}

\def\Return{\HTMLunicode{23CE}}

\def\ascii{ASCII Corporation}

\def\Ascii{ASCII Corporation}

\def\ASCII{ASCII Corporation}
```

File 359 **lwarp-textarea.sty**

§ 457 Package textarea

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg textarea textarea is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{textarea}[2005/12/26]

\newcommand\StartFromTextArea{}
\newcommand\StartFromHeaderArea{}
\newcommand*\RestoreTextArea{}
\newcommand*\ExpandTextArea[1][*]{}
\let\NCC@restoretextarea\@empty
```

File 360 **lwarp-textcomp.sty**

§ 458 Package textcomp

(*Emulates or patches code by* Frank Mittelbach, Robin Fairbairns, Werner Lemberg.)

Pkg textcomp textcomp is patched for use by lwarp.

§ 458.1 Limitations

Some textcomp symbols do not have Unicode equivalents, and thus are not supported.

⚠ missing symbols Many textcomp symbols are not supported by many system / browser fonts. In the CSS try referencing fonts which are more complete, but expect to see gaps in coverage.

§ 458.2 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{textcomp}[2017/04/05]
```

§ 458.3 HTML symbols

For HTML, use HTML entities or direct Unicode, depending on the engine.

`\AtBeginDocument` improves support for LuaLaTeX and XeLaTeX.

§ 458.3.1 pdfLaTeX symbols

```
\AtBeginDocument{
\ifPDFTeX% pdflatex or dvi latex
\newcommand*{\LWR@HTML@textdegree}{\HTMLentity{deg}}
\newcommand*{\LWR@HTML@textcelsius}{\HTMLunicode{2103}}
\newcommand*{\LWR@HTML@textohm}{\HTMLunicode{2126}}
\newcommand*{\LWR@HTML@textmu}{\HTMLunicode{00B5}}
\newcommand*{\LWR@HTML@textlquill}{\HTMLunicode{2045}}
\newcommand*{\LWR@HTML@textrquill}{\HTMLunicode{2046}}
\newcommand*{\LWR@HTML@textcircledP}{\HTMLunicode{2117}}
\newcommand*{\LWR@HTML@texttwelveudash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{\HTMLunicode{2014}}% emdash
\newcommand*{\LWR@HTML@textmho}{\HTMLunicode{2127}}
\newcommand*{\LWR@HTML@textnaira}{\HTMLunicode{20A6}}
\newcommand*{\LWR@HTML@textpeso}{\HTMLunicode{20B1}}
\newcommand*{\LWR@HTML@textrecipe}{\HTMLunicode{211E}}
\newcommand*{\LWR@HTML@textinterrobang}{\HTMLunicode{203D}}
\newcommand*{\LWR@HTML@textinterrobangdown}{\HTMLunicode{2E18}}
\newcommand*{\LWR@HTML@textperthousand}{\HTMLunicode{2030}}
\newcommand*{\LWR@HTML@textpertenthousand}{\HTMLunicode{2031}}
\newcommand*{\LWR@HTML@textbaht}{\HTMLunicode{0E3F}}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{\HTMLunicode{2120}}
\else
```

§ 458.3.2 XeLaTeX and LuaLaTeX symbols

NOTE: Some of the following do not print well in the listing. Consult the .dtx or .sty file for the actual characters.

```
\newcommand*{\LWR@HTML@textdegree}{°}
\newcommand*{\LWR@HTML@textcelsius}{}
\newcommand*{\LWR@HTML@textohm}{}
\newcommand*{\LWR@HTML@textmu}{µ}
\newcommand*{\LWR@HTML@textlquill}{}
\newcommand*{\LWR@HTML@textrquill}{}
\newcommand*{\LWR@HTML@textcircledP}{}
\newcommand*{\LWR@HTML@texttwelveudash}{–}% emdash
\newcommand*{\LWR@HTML@textthreequartersemdash}{–}% emdash
\newcommand*{\LWR@HTML@textmho}{}
\newcommand*{\LWR@HTML@textnaira}{}
\newcommand*{\LWR@HTML@textpeso}{}
\newcommand*{\LWR@HTML@textrecipe}{}
\newcommand*{\LWR@HTML@textinterrobang}{}
\newcommand*{\LWR@HTML@textinterrobangdown}{}
\newcommand*{\LWR@HTML@textperthousand}{%}
\newcommand*{\LWR@HTML@textpertenthousand}{%}
\newcommand*{\LWR@HTML@textbaht}{}
\newcommand*{\LWR@HTML@textdiscount}{\%}
\newcommand*{\LWR@HTML@textservicemark}{}
\fi

\LWR@formatted{textdegree}
```

```
\LWR@formatted{textcelsius}
\LWR@formatted{textohm}
\LWR@formatted{textmu}
\LWR@formatted{textlquill}
\LWR@formatted{textrquill}
\LWR@formatted{textcircledP}
\LWR@formatted{texttwelveudash}
\LWR@formatted{textthreequartersemdash}
\LWR@formatted{textmho}
\LWR@formatted{textnaira}
\LWR@formatted{textpeso}
\LWR@formatted{textrecipe}
\LWR@formatted{textinterrobang}
\LWR@formatted{textinterrobangdown}
\LWR@formatted{textperthousand}
\LWR@formatted{textpertenthousand}
\LWR@formatted{textbaht}
\LWR@formatted{textdiscount}
\LWR@formatted{textservicemark}
```

§ 458.4 HTML diacritics

For HTML, Unicode diacritical marks are used:

```
\newcommand*{\LWR@HTML@capitalcedilla}[1]{#1\HTMLunicode{0327}}
\newcommand*{\LWR@HTML@capitalogonek}[1]{#1\HTMLunicode{0328}}
\newcommand*{\LWR@HTML@capitalgrave}[1]{#1\HTMLunicode{0300}}
\newcommand*{\LWR@HTML@capitalacute}[1]{#1\HTMLunicode{0301}}
\newcommand*{\LWR@HTML@capitalcircumflex}[1]{#1\HTMLunicode{0302}}
\newcommand*{\LWR@HTML@capitaltilde}[1]{#1\HTMLunicode{0303}}
\newcommand*{\LWR@HTML@capitaldieresis}[1]{#1\HTMLunicode{0308}}
\newcommand*{\LWR@HTML@capitalhungarumlaut}[1]{#1\HTMLunicode{30B}}
\newcommand*{\LWR@HTML@capitalring}[1]{#1\HTMLunicode{30A}}
\newcommand*{\LWR@HTML@capitalcaron}[1]{#1\HTMLunicode{30C}}
\newcommand*{\LWR@HTML@capitalbreve}[1]{#1\HTMLunicode{306}}
\newcommand*{\LWR@HTML@capitalmacron}[1]{#1\HTMLunicode{304}}
\newcommand*{\LWR@HTML@capitaldotaccent}[1]{#1\HTMLunicode{307}}
```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with xunicode.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
\InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{capitalcedilla}
\LWR@formatted{capitalogonek}
\LWR@formatted{capitalgrave}
\LWR@formatted{capitalacute}
\LWR@formatted{capitalcircumflex}
\LWR@formatted{capitaltilde}
\LWR@formatted{capitaldieresis}
\LWR@formatted{capitalhungarumlaut}
\LWR@formatted{capitalring}
\LWR@formatted{capitalcaron}
```

```
\LWR@formatted{capitalbreve}
\LWR@formatted{capitalmacron}
\LWR@formatted{capitaldotaccent}
\LWR@formatted{textcircled}
```

Nullify textcomp macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobang}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify

}% AtBeginDocument
```

File 361 **lwarp-textfit.sty**

§ 459 Package textfit

Pkg textfit textfit is emulated.

Text is placed into a of class textfit. Sizes are approximated, and also limited by browser min/max font-size settings.

for HTML output:

```
\LWR@ProvidesPackageDrop{textfit}[1994/04/15]

\newsavebox{\LWR@textfitbox}

\newcommand*{\LWR@textfitscale}[2]{%
\setlength{\LWR@templengthone}{#1}%
\setlength{\LWR@templengthone}{%
    1em*\ratio{\LWR@templengthone}{\LWR@templengthtwo}%
}%
\InlineClass[font-size:\LWR@printlength{\LWR@templengthone}]{textfit}{#2}%
}

\newcommand*{\scaletowidth}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settowidth{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}

\newcommand*{\scaletoheight}[2]{%
\sbox{\LWR@textfitbox}{#2}%
\settoheight{\LWR@templengthtwo}{\usebox{\LWR@textfitbox}}%
\LWR@textfitscale{#1}{#2}%
}
```

File 362 **lwarp-textpos.sty**

§ 460 Package

textpos

(*Emulates or patches code by* Norman Gray.)

Pkg textpos textpos is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{textpos}[2019/04/15]

\NewDocumentEnvironment{textblock}{m o r()}{}{}
\NewDocumentEnvironment{textblock*}{m o r()}{}{}
\newcommand*{\TPGrid}[3][]{}
\NewDocumentCommand{\TPMargin}{s o}{}
\newcommand*{\textblockcolour}[1]{}
\newcommand*{\textblockrulecolour}[1]{}
\newcommand*{\textblockcolor}[1]{}
\newcommand*{\textblockrulecolor}[1]{}
\newcommand*{\tekstblokkulur}[1]{}
\newcommand*{\tekstblokrulekulur}[1]{}
\newlength{\TPHorizModule}
\newlength{\TPVertModule}
\newlength{\TPboxrulesize}
\newcommand{\textblocklabel}[1]{}
\newcommand*{\showtextsize}{}
\newcommand{\textblockorigin}[2]{}
```

```
\newcommand*{\TPoptions}[1]{}
\newcommand*{\TPReferencePosition}[1]{}
```

File 363 **lwarp-theorem.sty**

§ 461 Package

theorem

(*Emulates or patches code by* Frank Mittelbach.)

Pkg theorem theorem is patched for use by lwarp.

Table 16: Theorem package — css styling of theorems and proofs

Theorem: of class theorembody<theoremstyle>

Theorem Header: of class theoremheader

where <theoremstyle> is plain, break, etc.

for HTML output:

```
\LWR@ProvidesPackagePass{theorem}[2014/10/28]
```

§ 461.1 Remembering the theorem style

Storage for the style being used for new theorems:

```
\newcommand{\LWR@newtheoremstyle}{plain}
```

Patched to remember the style being used for new theorems:

```
\gdef\theoremstyle#1{%
   \@ifundefined{th@#1}{\@warning
          {Unknown theoremstyle `#1'. Using `plain'}%
          \theorem@style{plain}%
           \renewcommand{\LWR@newtheoremstyle}{plain}% lwarp
          }%
      {%
          \theorem@style{#1}%
          \renewcommand{\LWR@newtheoremstyle}{#1}% lwarp
      }%
      \begingroup
        \csname th@\the\theorem@style \endcsname
      \endgroup}
```

Patched to remember the style for this theorem type, and set it later when the environment is started.

```
\gdef\@xnthm#1#2[#3]{%
   \expandafter\@ifdefinable\csname #1\endcsname
   {%
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
```

```
    \@definecounter{#1}\@newctr{#1}[#3]%
    \expandafter\xdef\csname the#1\endcsname
      {\expandafter \noexpand \csname the#3\endcsname
       \@thmcountersep \@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}%
    \expandafter \@tempa \expandafter{%
      \csname th@\the \theorem@style
            \expandafter \endcsname \the \theorem@bodyfont
     \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@ynthm#1#2{%
    \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \@definecounter{#1}%
    \expandafter\xdef\csname the#1\endcsname{\@thmcounter{#1}}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#1}{#2}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
   }}

\gdef\@othm#1[#2]#3{%
  \expandafter\ifx\csname c@#2\endcsname\relax
   \@nocounterr{#2}%
  \else
   \expandafter\@ifdefinable\csname #1\endcsname
   {
    \csedef{LWR@thmstyle#1}{\LWR@newtheoremstyle}% lwarp
    \expandafter \xdef \csname the#1\endcsname
     {\expandafter \noexpand \csname the#2\endcsname}%
    \def\@tempa{\global\@namedef{#1}}\expandafter \@tempa
     \expandafter{\csname th@\the \theorem@style \expandafter
     \endcsname \the\theorem@bodyfont \@thm{#2}{#3}}%
    \global \expandafter \let \csname end#1\endcsname \@endtheorem
   \AtBeginEnvironment{#1}{\edef\LWR@thisthmstyle{\@nameuse{LWR@thmstyle#1}}}% lwarp
    }%
  \fi}
```

§ 461.2 css patches

The following are patched for css.

These were in individual files `thp.sty` for plain, `thmb.sty` for margin break, etc. They are gathered together here.

Each theorem is encased in a `BlockClass` environment of class `theorembody<style>`.

Each header is encased in an `\InlineClass` of class `theoremheader`.

```
\gdef\th@plain{%
```

```
  \def\@begintheorem##1##2{%
        \item[
            \InlineClass{theoremheader}{##1\ ##2}
        ]
    }%
\def\@opargbegintheorem##1##2##3{%
   \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}
    ]
    }
}

\gdef\th@break{%
  \def\@begintheorem##1##2{%
    \item[
        \InlineClass{theoremheader}{##1\ ##2}\newline%
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
  \item[
        \InlineClass{theoremheader}{##1\ ##2\ (##3)}\newline
    ]
    }
}

\gdef\th@marginbreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}\newline
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@changebreak{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2\ ##1}\newline
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{ ##2\ ##1\ %
        (##3)}\newline
    ]
    }
}

\gdef\th@change{%
  \def\@begintheorem##1##2{
```

```
    \item[
        \InlineClass{theoremheader}{##2\ ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
        \InlineClass{theoremheader}{##2\ ##1\ (##3)}
    ]
    }
}

\gdef\th@margin{%
  \def\@begintheorem##1##2{
    \item[
        \InlineClass{theoremheader}{##2 \qquad ##1}
    ]
    }%
\def\@opargbegintheorem##1##2##3{%
    \item[
            \InlineClass{theoremheader}{##2 \qquad ##1\ (##3)}
    ]
    }
}
```

Patched for css:

```
\gdef\@thm#1#2{\refstepcounter{#1}%
\LWR@forcenewpage% lwarp
    \BlockClass{theorembody\LWR@thisthmstyle}% lwarp
   \trivlist
   \@topsep \theorempreskipamount               % used by first \item
   \@topsepadd \theorempostskipamount           % used by \@endparenv
   \@ifnextchar [%
   {\@ythm{#1}{#2}}%
   {\@begintheorem{#2}{\csname the#1\endcsname}\ignorespaces}}

\gdef\@endtheorem{%
\endtrivlist
\endBlockClass
}
```

File 364 **lwarp-thinsp.sty**

§ 462 Package

thinsp

Pkg thinsp thinsp is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{thinsp}[2016/10/02]

\AtBeginDocument{
\let\thinthinspace\relax% defined by some packages
\newcommand*{\thinthinspace}{\thinspace}
```

```
}

\newcommand*{\stretchthinspace}{\thinspace}
\newcommand*{\stretchthinthinspace}{\thinthinspace}
\newcommand*{\stretchnegthinspace}{\negthinspace}
```

File 365 **lwarp-threadcol.sty**

§ 463 Package

threadcol

Pkg threadcol threadcol is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{threadcol}[2013/01/06]

\newcommand{\setthreadname}[1]{}
```

File 366 **lwarp-threeparttable.sty**

§ 464 Package

threeparttable

(*Emulates or patches code by* Donald Arseneau.)

Pkg threeparttable threeparttable is emulated.

Table note are contained inside a CSS of class tnotes. If enumitem is used, the note item labels are also individually highlighted with an additional CSS of class tnoteitemheader, otherwise they are plain text.

for HTML output:

```
\LWR@ProvidesPackageDrop{threeparttable}[2003/06/13]
```

Env threeparttable [⟨*alignment*⟩] To emulate threeparttable:

```
\newenvironment*{threeparttable}[1][b]
    {\def\@captype{table}}
    {}
```

Env tablenotes [⟨*options*⟩]

```
\newenvironment*{tablenotes}[1][]
{%
\LWR@forcenewpage
\BlockClass{tnotes}%

\description%
}
{%
\enddescription%
\endBlockClass%
}
```

\tnote {⟨*text*⟩}

```
\newcommand{\tnote}[1]{\LWR@htmlspan{sup}{#1}}
```

File 367 **lwarp-threeparttablex.sty**

§ 465 Package

threeparttablex

Pkg threeparttablex threeparttablex is patched for use by lwarp.

threeparttablex is used with longtable and booktabs as follows:

```
\begin{longtable}{ [column specifiers] }
[ . . . ] \endfirsthead   % or \endhead, for print and HTML
\warpprintonly{          % not used in HTML
  [ . . . ] \endhead     % or \endfirsthead
  [ . . . ] \endfoot
  \bottomrule \insertTableNotes \endlastfoot
}
. . .  table contents . . .
\warpHTMLonly{   % HTML last footer
  \bottomrule
  \UseMinipageWidths     % optional
  \insertTableNotes
  \endlastfoot
}
\end{longtable}
```

table width The table notes are created using a \multicolumn. By default the width is not specified to the browser, so long table notes can cause the table to be spread out horizontally. For HTML output, lwarp guesses the width of the table depending on the number of columns, then restricts its guess to a min/max range. To use this guess for the width of the table notes, use \UseMinipageWidths before \insertTableNotes. The width is then specified, and in many cases the result is an improvement in overall table layout.

for HTML output:

```
\LWR@ProvidesPackagePass{threeparttablex}[2013/07/23]
```

The width is guessed depending on the number of columns, then limited to a min/max.

```
\renewcommand\insertTableNotes{%
   \setlength{\LWR@templengthone}{.375in*\value{LWR@tabletotalLaTeXcols}}%
   \setlength{\LWR@templengthone}{\minof{\textwidth}{\LWR@templengthone}}%
   \setlength{\LWR@templengthone}{\maxof{2.5in}{\LWR@templengthone}}%
 \multicolumn{\value{LWR@tabletotalLaTeXcols}}{c}{%
     \parbox{\LWR@templengthone}{%
       \begin{tablenotes}[\TPTL@optarg]%
         \TPTL@font%
         \TPTL@body%
```

```
        \end{tablenotes}%
      }%
  }%
}

\renewcommand\TPTL@tnotex[2]{\tnote{\nameref{#2}}}
```

File 368 **lwarp-thumb.sty**

§ 466 Package thumb

Pkg thumb thumb is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{thumb}[1997/12/24]

\newcommand*{\Overviewpage}{}
\newlength{\thumbheight}
\newlength{\thumbwidth}
```

File 369 **lwarp-thumbs.sty**

§ 467 Package thumbs

Pkg thumbs thumbs is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{thumbs}[2014/03/09]

\newcommand{\addthumb}[4]{}
\newcommand{\addtitlethumb}[5]{}
\newcommand{\stopthumb}{}
\newcommand{\continuethumb}{}
\newcommand{\thumbsoverview}[1]{}
\newcommand{\thumbsoverviewback}[1]{}
\newcommand{\thumbsoverviewverso}[1]{}
\newcommand{\thumbsoverviewdouble}[1]{}
\newcommand{\thumbnewcolumn}{}
\newcommand{\addthumbsoverviewtocontents}[2]{}
\newcommand{\thumbsnophantom}{}
```

File 370 **lwarp-tikz.sty**

§ 468 Package tikz

(*Emulates or patches code by* Till Tantau.)

Pkg tikz tikz is supported.

⚠ displaymath and matrices

If using display math with `tikzpicture` or `\tikz`, along with matrices with the `&` character, the document must be modified as follows:

```
\usepackage{tikz}
\tikzset{every picture/.style={ampersand replacement=\&}}
```

and each instance of `&` in the tikz expression must be replaced with `\&`.

Accept all options for lwarp-tikz:

```
\LWR@ProvidesPackagePass{tikz}[2015/08/07]
```

catcodes

lwarp changes the catcode of `$` for its own use. The Ti*k*z `babel` library temporarily changes catcodes back to normal for Ti*k*z's use. tikz v3.0.0 introduced the `babel` library which handles catcode changes. For older versions, lwarp must change `$`'s catcode itself.

Also see:
https://tex.stackexchange.com/questions/16199/test-if-a-package-or-package-option-is-loaded

```
\newbool{LWR@tikzbabel}

\@ifpackagelater{tikz}{2013/12/20}% Test for Tikz version v3.0.0
{\usetikzlibrary{babel}\booltrue{LWR@tikzbabel}}
{\boolfalse{LWR@tikzbabel}}
```

Env pgfpicture

The `\pgfpicture` environment is enclosed inside a `\lateximage`. Enclose the low-level `\pgfpicture` in a `lateximage`. This is also used by the higher-level `\tikz` and `tikzpicture`.

```
\preto\pgfpicture{%
    \begin{lateximage}%
    \ifbool{LWR@tikzbabel}% Test for Tikz version v3.0.0
    {}%
    {\catcode`\$=3}% dollar sign is math shift
}

\appto\endpgfpicture{\end{lateximage}}
```

Ti*k*z is placed inside an SVG image, so use the original meanings of the following:

```
\LetLtxMacro\pgfutil@minipage\LWR@print@minipage
\let\pgfutil@endminipage\endLWR@print@minipage

\let\pgfutil@raggedleft\LWR@print@raggedleft
\let\pgfutil@raggedright\LWR@print@raggedright

\def\pgfutil@font@tiny{\LWR@printtiny}
\def\pgfutil@font@scriptsize{\LWR@printscriptsize}
\def\pgfutil@font@footnotesize{\LWR@printfootnotesize}
\def\pgfutil@font@small{\LWR@print@small}
\def\pgfutil@font@normalsize{\LWR@print@normalsize}
```

```
\def\pgfutil@font@large{\LWR@printlarge}
\def\pgfutil@font@Large{\LWR@printLarge}
\def\pgfutil@font@huge{\LWR@printhuge}
\def\pgfutil@font@Huge{\LWR@printHuge}

\def\pgfutil@font@itshape{\LWR@origitshape}
\def\pgfutil@font@bfseries{\LWR@origbfseries}

\def\pgfutil@font@normalfont{\LWR@orignormalfont}
```

File 371 **lwarp-titleps.sty**

§ 469 Package

titleps

(*Emulates or patches code by* Javier Bezos.)

Pkg titleps

titleps is loaded and used by lwarp during HTML output. All user options and macros are ignored and disabled.

Discard all options for lwarp-titleps:

for HTML output:

```
\LWR@ProvidesPackageDrop{titleps}[2016/03/15]
```

\pagestyle and \thispagestyle are already disabled in the lwarp code.

\newpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\newpagestyle}{m o m}{}
```

\renewpagestyle {⟨*name*⟩} [⟨*style*⟩] {⟨*commands*⟩}

```
\NewDocumentCommand{\renewpagestyle}{m o m}{}
```

\sethead [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\sethead}{o o o m m m}{}
```

\setfoot [⟨*el*⟩] [⟨*ec*⟩] [⟨*er*⟩] {⟨*ol*⟩} {⟨*oc*⟩} {⟨*or*⟩}

```
\NewDocumentCommand{\setfoot}{o o o m m m}{}
```

\settitlemarks * {⟨*names*⟩}

```
\NewDocumentCommand{\settitlemarks}{s m}{}
```

\headrule

```
\newcommand*{\headrule}{}
```

\footrule

```
\newcommand*{\footrule}{}
```

\setheadrule {⟨*length*⟩}

```
\newcommand*{\setheadrule}[1]{}
```

\setfootrule {⟨*length*⟩}

```
\newcommand*{\setfootrule}[1]{}
```

\makeheadrule

```
\newcommand*{\makeheadrule}{}
```

\makefootrule

```
\newcommand*{\makefootrule}{}
```

\setmarkboth {⟨*code*⟩}

```
\newcommand{\setmarkboth}[1]{}
```

\widenhead

```
\NewDocumentCommand{\widenhead}{s o o m m}{}
```

\bottitlemarks

```
\newcommand*{\bottitlemarks}{}
```

\toptitlemarks

```
\newcommand*{\toptitlemarks}{}
```

\firsttitlemarks

```
\newcommand*{\firsttitlemarks}{}
```

\nexttitlemarks

```
\newcommand*{\nexttoptitlemarks}{}
```

\outertitlemarks

```
\newcommand*{\outertitlemarks}{}
```

\innertitlemarks

```
\newcommand*{\innertitlemarks}{}
```

\newtitlemark * {⟨*name*⟩}

```
21 \NewDocumentCommand{\newtitlemark}{s m}{}
```

\pretitlemark * {⟨*section*⟩} {⟨*text*⟩}

```
22 \NewDocumentCommand{\pretitlemark}{s m m}{}
```

\ifsamemark {⟨*group*⟩} {⟨*command*⟩} {⟨*true*⟩} {⟨*false*⟩}

```
23 \newcommand{\ifsamemark}[4]{}
```

\setfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
24 \NewDocumentCommand{\setfloathead}{s o o o m m m m m}{}
```

\setfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
25 \NewDocumentCommand{\setfloatfoot}{s o o o m m m m m}{}
```

\nextfloathead * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
26 \NewDocumentCommand{\nextfloathead}{s o o o m m m m m}{}
```

\nextfloatfoot * [⟨.⟩] [⟨.⟩] [⟨.⟩] {⟨.⟩} {⟨.⟩} {⟨.⟩} {⟨*extra*⟩} [⟨*which*⟩]

```
27 \NewDocumentCommand{\nextfloatfoot}{s o o o m m m m m}{}
```

\newmarkset {⟨*markset*⟩}

```
28 \newcommand{\newmarkset}[1]{}
```

\newextramark * {⟨*markset*⟩} {⟨*macro-name*⟩}

```
29 \NewDocumentCommand{\newextramarkset}{s m m}{}
```

\botextramarks {⟨*markset*⟩}

```
30 \newcommand{\botextramarks}[1]{}
```

\topextramarks {⟨*markset*⟩}

```
31 \newcommand{\topextramarks}[1]{}
```

\firstextramarks {⟨*markset*⟩}

```
32 \newcommand{\firstextramarks}[1]{}
```

\nextextramarks {⟨*markset*⟩}

```
33 \newcommand{\nexttopextramarks}[1]{}
```

\outerextramarks {⟨*markset*⟩}

```
\newcommand{\outerextramarks}[1]{}
```

\innerextramarks {⟨*markset*⟩}

```
\newcommand{\innerextramarks}[1]{}
```

File 372 **lwarp-titleref.sty**

§ 470 Package titleref

Pkg titleref titleref is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{titleref}[2001/04/05]

\LetLtxMacro\titleref\nameref

\providecounter{LWR@currenttitle}

\newcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\newcommand*{\theTitleReference}[2]{}
```

File 373 **lwarp-titlesec.sty**

§ 471 Package titlesec

(*Emulates or patches code by* Javier Bezos.)

Pkg titlesec titlesec is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titlesec:

for HTML output:

```
\LWR@ProvidesPackageDrop{titlesec}[2016/03/21]
```

\titlelabel {⟨*label-format*⟩}

```
\newcommand*{\titlelabel}[1]{}
```

\titleformat* {⟨*command*⟩} {⟨*format*⟩}

\titleformat {⟨*command*⟩} [⟨*shape*⟩] {⟨*format*⟩} {⟨*label*⟩} {⟨*sep*⟩} {⟨*befgore*⟩} [⟨*after*⟩]

```
\newcommand\titleformat{%
  \@ifstar{\ttl@format@s}%
          {\ttl@format@i}}
```

```
\newcommand{\ttl@format@s}[1]{}
\NewDocumentCommand{\ttl@format@i}{m o m m m m o}{}
```

\chaptertitlename

```
\@ifundefined{@chapapp}{\let\@chapapp\chaptername}{}
\newcommand\chaptertitlename{\@chapapp}
```

\titlespacing * {⟨*command*⟩} {⟨*left*⟩} {⟨*before*⟩} {⟨*after*⟩} [⟨*right*⟩]

```
\NewDocumentCommand{\titlespacing}{s m m m m o}{}
```

\filright

```
\newcommand*{\filright}{}
```

\filcenter

```
\newcommand*{\filcenter}{}
```

\filleft

```
\newcommand*{\filleft}{}
```

\fillast

```
\newcommand*{\fillast}{}
```

\filinner

```
\newcommand*{\filinner}{}
```

\filouter

```
\newcommand*{\filouter}{}
```

\wordsep

```
\newcommand\wordsep{\fontdimen\tw@\font \@plus
  \fontdimen\thr@@\font \@minus \fontdimen4\font}
```

\titleline * [⟨*align*⟩] {⟨*material*⟩}

```
\NewDocumentCommand{\titleline}{s o m}{}
```

\titlerule [⟨*height*⟩]

```
\providecommand*\titlerule{\@ifstar{\ttl@row}{\ttl@rule}}
\newcommand*{\ttl@rule}[1][]{}
\newcommand*{\ttl@row}[2][]{}
```

\iftitlemeasuring {⟨*true*⟩} {⟨*false*⟩}

```
23 \newcommand{\iftitlemeasuring}[2]{#2}
```

\assignpagestyle {⟨*command*⟩} {⟨*pagestyle*⟩}

```
24 \newcommand{\assignpagestyle}[2]{#2}
```

\titleclass {⟨*name*⟩} [⟨*startlevel*⟩] {⟨*class*⟩} [⟨*cmd*⟩]

```
25 \NewDocumentCommand{\titleclass}{m o m o}
```

File 374 **lwarp-titletoc.sty**

§ 472 Package

titletoc

(*Emulates or patches code by* Javier Bezos.)

Pkg titletoc titletoc is emulated. All user options and macros are ignored and disabled.

Discard all options for lwarp-titletoc:

for HTML output:

```
1 \LWR@ProvidesPackageDrop{titletoc}[2011/12/15]
```

\dottedcontents {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*label*⟩} {⟨*leader*⟩}

```
2 \NewDocumentCommand{\dottedcontents}{m o m m m}{}
```

\titlecontents * {⟨*section*⟩} [⟨*left*⟩] {⟨*above*⟩} {⟨*numbered*⟩} {⟨*numberless*⟩} {⟨*filler*⟩} [⟨*below or begin*⟩] [⟨*separator*⟩] [⟨*end*⟩]

```
3 \newcommand{\titlecontents}{\@ifstar{\ttl@tcstar}{\ttl@tcnostar}}
4 \NewDocumentCommand{\ttl@tcstar}{m o m m m m o o o}{}
5 \NewDocumentCommand{\ttl@tcnostar}{m o m m m m o}{}
```

\contentsmargin [⟨*correction*⟩] {⟨*right*⟩}

```
6 \newcommand{\contentsmargin}[2][]{}
```

\thecontentslabel

```
7 \newcommand*{\thecontentslabel}{thecontentslabel}
```

\thecontentspage

```
8 \newcommand*{\thecontentspage}{thecontentspage}
```

\contentslabel [⟨*format*⟩] {⟨*space*⟩}

```
9 \newcommand{\contentslabel}[2][]{\thecontentslabel}
```

\contentspage [⟨*format*⟩]

```
10 \newcommand{\contentspage}[1][]{\thecontentspage}
```

\contentspush {⟨*text*⟩}

```
11 \newcommand{\contentspush}[1]{}
```

\contentsuse {⟨*name*⟩} {⟨*text*⟩}

```
12 \newcommand{\contentsuse}[2]{}
```

\startcontents [⟨*name*⟩]

```
13 \newcommand*{\startcontents}[1][]{}
```

\stopcontents [⟨*name*⟩]

```
14 \newcommand*{\stopcontents}[1][]{}
```

\resumecontents [⟨*name*⟩]

```
15 \newcommand*{\resumecontents}[1][]{}
```

\printcontents [⟨*name*⟩] {⟨*prefix*⟩} {⟨*start*⟩} {⟨*code*⟩}

```
16 \newcommand{\printcontents}[4][]{}
```

\startlist [⟨*name*⟩] {⟨*list*⟩}

```
17 \newcommand{\startlist}[2][]{}
```

\stoplist [⟨*name*⟩] {⟨*list*⟩}

```
18 \newcommand{\stoplist}[2][]{}
```

\resumelist [⟨*name*⟩] {⟨*list*⟩}

```
19 \newcommand{\resumelist}[2][]{}
```

\printlist [⟨*name*⟩] {⟨*list*⟩} {⟨*prefix*⟩} {⟨*code*⟩}

```
20 \newcommand{\printlist}[4][]{}
```

File 375 **lwarp-titling.sty**

§ 473 Package

titling

(*Emulates or patches code by* Peter Wilson.)

Pkg titling

package support lwarp supports the native LaTeX titling commands, and also supports the packages

⚠ load order

authblk and titling. If both are used, authblk should be loaded before titling.

\published and \subtitle

If using the titling package, additional titlepage fields for \published and \subtitle may be added by using \AddSubtitlePublished in the preamble. See section 66.8.

The various titling footnote restyling commands have no effect.

Pass all options to lwarp-titling:

for HTML output:

```
\LWR@ProvidesPackagePass{titling}[2009/09/04]
```

\@bsmtitlempty

Patch \@bsmtitlempty:

```
\let\LWR@orig@bsmtitlempty\@bsmtitlempty
\renewcommand*{\@bsmtitlempty}{%
\LWR@orig@bsmtitlempty%
}
```

\keepthetitle

Patch \keepthetitle:

```
\let\LWR@origkeepthetitle\keepthetitle
\renewcommand*{\keepthetitle}{%
\LWR@orig@keepthetitle%
}
```

\killtitle

Patch \killtitle:

```
\let\LWR@origkilltitle\killtitle
\renewcommand*{\killtitle}{%
\LWR@orig@killtitle%
}
```

Env titlingpage

```
\renewenvironment*{titlingpage}
{%
```

Start an HTML titlepage div:

```
\LWR@printpendingfootnotes
\begin{titlepage}
```

Prepare for a custom version of \maketitle inside the titlingpage:

```
\LWR@maketitlesetup
\let\maketitle\LWR@titlingmaketitle
}
{
```

At the end of the environment, end the HTML titlepage div:

```
\end{titlepage}
}
```

Patch the pre/post title/author/date to add HTML tags, then initilize:

```
\pretitle{}
\posttitle{}

\preauthor{}
\postauthor{}

\predate{}
\postdate{}
```

`\LWR@maketitlesetup` Patches `\thanks` macros.

```
\renewcommand*{\LWR@maketitlesetup}{%
```

Redefine the footnote mark:

```
\def\@makefnmark{\textsuperscript{\@thefnmark}}
```

`\thefootnote` ⇒ `\nameuse{arabic}{footnote}`, or
`\thefootnote` ⇒ `\nameuse{fnsymbol}{footnote}`

Redefine the footnote text:

```
\long\def\@makefntext##1{%
```

Make the footnote mark and some extra horizontal space for the tags:

```
\makethanksmark~%
```

`\makethanksmark` ⇒ `\thanksfootmark` ⇒ `\tamark` ⇒
`\@thefnmark` ⇒ `\itshape` a (or similar)

Print the text:

```
##1%
}% \@makefntext
}
```

`\thanksfootmark`

```
\renewcommand{\thanksfootmark}{%
%   \hb@xt@\thanksmarkwidth{\hfil\normalfont%
        \thanksscript{%
            \thanksfootpre \tamark \thanksfootpost%
        }%
%   }%
}
```

\maketitle HTML mode. Creates an HTML titlepage div and typesets the title, etc.

Code from the titling package is adapted, simplified, and modified for HTML output.

```
\renewcommand*{\maketitle}{%
```

An HTML titlepage is used for all classes.

```
\begin{titlepage}
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any \thanks footnotes:

```
\@thanks
```

Close the HTML titlepage div:

```
\end{titlepage}
```

Reset the footnote counter:

```
\@bscontmark
}
```

\@maketitle Typesets the title, etc. Patched for HTML.

```
\DeclareDocumentCommand{\@maketitle}{}{%
    \maketitlehooka
    {
        \LWR@stoppars\LWR@htmltag{\LWR@tagtitle}%
        \@bspretitle \@title \@bsposttitle%
        \LWR@htmltag{\LWR@tagtitleend}\LWR@startpars%
    }
    \maketitlehookb
    {
        \begin{BlockClass}{author}
        \renewcommand{\and}{%
            \end{BlockClass}%
            \begin{BlockClass}{oneauthor}%
        }
        \begin{BlockClass}{oneauthor}%
```

```
        \@bspreauthor \@author  \@bspostauthor%
        \end{BlockClass}%
        \end{BlockClass}%
    }
    \maketitlehookc
    {
        \begin{BlockClass}{titledate}%
        \@bspredate \@date \@bspostdate%
        \end{BlockClass}%
    }
    \maketitlehookd
}
```

\LWR@titlingmaketitle `\maketitle` for use inside an HTML `titlingpage` environment.

```
\renewcommand*{\LWR@titlingmaketitle}{%
```

Keep pending footnotes out of the title block:

```
\@thanks
```

Select which kind of footnote marks to use:

```
\@bsmarkseries
```

Set up special patches:

```
\LWR@maketitlesetup
```

Typeset the title, etc:

```
\@maketitle
```

Immediately generate any `\thanks` footnotes:

```
\@thanks
```

Reset the footnote counter:

```
\@bscontmark
}
```

\thanksmarkseries {⟨*series*⟩}

Sets the type of footnote marks used by `\thanks`, where type is 'arabic', 'roman', 'fnsymbol', etc.

```
\renewcommand{\thanksmarkseries}[1]{%
\def\@bsmarkseries{\renewcommand{\thefootnote}{\@nameuse{#1}{footnote}}}%
}
```

Set default titlepage thanks footnote marks. See section 66.7.

```
\@ifclassloaded{memoir}{
   \thanksmarkseries{arabic}
}{% not memoir
\if@titlepage
   \thanksmarkseries{arabic}
\else
   \thanksmarkseries{fnsymbol}
\fi
}% not memoir
```

File 376 **lwarp-tocbasic.sty**

§ 474 Package

tocbasic

(*Emulates or patches code by* Markus Kohm.)

Pkg tocbasic tocbasic is nullified for lwarp.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackagePass{tocbasic}[2018/12/30]

\DeclareDocumentCommand{\usetocbasicnumberline}{o}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntry}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCStyleEntries}{o m m}{}
\DeclareDocumentCommand{\DeclareTOCEntryStyle}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryOption}{m o m}{}
\DeclareDocumentCommand{\DefineTOCEntryBooleanOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryCommandOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryIfOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryLengthOption}{m o m m m}{}
\DeclareDocumentCommand{\DefineTOCEntryNumberOption}{m o m m m}{}
\DeclareDocumentCommand{\CloneTOCEntryStyle}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleInitCode}{m m}{}
\DeclareDocumentCommand{\TOCEntryStyleStartInitCode}{m m}{}
```

File 377 **lwarp-tocbibind.sty**

§ 475 Package

tocbibind

(*Emulates or patches code by* Peter Wilson.)

Pkg tocbibind tocbibind is patched for use by lwarp.

placement and toc options An index may be placed inline with other HTML text, or on its own HTML page:

Pkg makeidx **Inline, with a manual TOC entry:**

A commonly-used method to introduce an index in a LaTeX document:

```
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\printindex
```

Pkg makeidx **On its own HTML page, with a manual TOC entry:**

```
\begin{warpprint}
\cleardoublepage
\phantomsection
\addcontentsline{toc}{section}{\indexname}% or chapter
\end{warpprint}
\ForceHTMLPage
\ForceHTMLTOC
\printindex
```

Pkg tocbibind **Inline, with an automatic TOC entry:**

The tocbibind package may be used to automatically place an entry in the TOC.

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\printindex
```

Pkg tocbibind **On its own HTML page, with an automatic TOC entry:**

```
\usepackage[nottoc]{tocbibind}
. . .
\cleardoublepage
\phantomsection % to fix print-version index link
\ForceHTMLPage
\printindex
```

Opt [tocbibind] numindex

numbered index section

Use the tocbibind numindex option to generate a numbered index. Without this option, the index heading has no number.

Other packages, such as imakeidx, may also have options for including the index in the Table of Contents.

for HTML output:

```
\let\simplechapterdelim\relax

\LWR@ProvidesPackagePass{tocbibind}[2010/10/13]


\renewenvironment{theindex}%
{%
     \if@bibchapter
        \if@donumindex
            \chapter{\indexname}
        \else
          \if@dotocind
            \chapter*{\indexname}
            \addcontentsline{toc}{chapter}{\LWR@isolate{\indexname}}
          \else
```

```
            \chapter*{\indexname}
          \fi
        \fi
     \else
        \if@donumindex
            \section{\indexname}
        \else
          \if@dotocind
            \section*{\indexname}
            \addcontentsline{toc}{\@tocextra}{\LWR@isolate{\indexname}}
          \else
            \section*{\indexname}
          \fi
        \fi
     \fi
\let\item\LWR@indexitem%
\let\subitem\LWR@indexsubitem%
\let\subsubitem\LWR@indexsubsubitem%
}{}
```

The following code is shared by anonchap.

```
\DeclareDocumentCommand{\simplechapter}{O{\@empty}}{%
    \def\@chapcntformat##1{%
        #1~\csname the##1\endcsname\simplechapterdelim\quad%
    }%
}

\DeclareDocumentCommand{\restorechapter}{}{%
\let\@chapcntformat\@seccntformat%
}
```

File 378 **lwarp-tocdata.sty**

§ 476 Package

tocdata

(*Emulates or patches code by* Brian Dunn.)

Pkg tocdata tocdata is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{tocdata}[2019/03/21]

\renewcommand*{\LWR@maybetocdata}{%
    \ifdefempty{\TD@thistocdata}{}{%
        \qquad --- \InlineClass{authorartist}{\TD@thistocdata}%
        \def\TD@thistocdata{}
    }
}

\renewrobustcmd{\tocdatapartprint}[4]
{%
    \LWR@htmltagc{br /}%
```

```
    \InlineClass{authorartist}{%
        \qquad --- %
        \TD@optionalname{#1}\TD@optionalname{#2}#3#4%
    }%
}

\@ifundefined{chapter}{}{
    \let\tocdatachapterprint\tocdatapartprint
}
\let\tocdatasectionprint\tocdatapartprint
\let\tocdatasubsectionprint\tocdatapartprint

\newcommand*{\LWR@TD@settextalign}[1]{%
    \def\LWR@TD@textalign{justify}%
    \ifcsstring{TD@#1align}{\centering}%
        {\def\LWR@TD@textalign{center}}%
        {}%
    \ifcsstring{TD@#1align}{\raggedleft}%
        {\def\LWR@TD@textalign{right}}%
        {}%
    \ifcsstring{TD@#1align}{\raggedright}%
        {\def\LWR@TD@textalign{left}}%
        {}%
}

\renewcommand{\TD@artistauthorprint}[5]{%
    \LWR@TD@settextalign{#1}%
    \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
    \InlineClass{authorartist}{\TD@optionalname{#2}\TD@optionalname{#3}#4#5}%
    \end{BlockClass}%
}

\newcommand*{\LWR@TD@setnamealign}[1]{%
    \def\LWR@TD@textalign{justify}%
    \ifcsstring{TD@#1textalign}{\centering}%
        {\def\LWR@TD@textalign{center}}%
        {}%
    \ifcsstring{TD@#1textalign}{\raggedleft}%
        {\def\LWR@TD@textalign{right}}%
        {}%
    \ifcsstring{TD@#1textalign}{\raggedright}%
        {\def\LWR@TD@textalign{left}}%
        {}%
}

\renewcommand{\TD@artistauthortextprint}[2]{%
    \LWR@TD@setnamealign{#1}%
    \begin{BlockClass}[text-align:\LWR@TD@textalign]{floatnotes}%
    #2%
    \end{BlockClass}%
}
```

File 379 **lwarp-tocenter.sty**

§ 477 Package

tocenter

Pkg tocenter tocenter is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{tocenter}[2004/12/09]

\NewDocumentCommand{\ToCenter}{s o m m}{}
\NewDocumentCommand{\FromMargins}{s o m m m m}{}
```

File 380 **lwarp-tocloft.sty**

§ 478 Package

tocloft

(*Emulates or patches code by* Peter Wilson.)

Pkg tocloft tocloft is emulated. Most user options and macros are ignored and disabled. \newlistof and \cftchapterprecis are supported.

Pkg tocloft

⚠ tocloft & other packages

If using tocloft with tocbibind, anonchap, fncychap, or other packages which change chapter title formatting, load tocloft with its titles option, which tells tocloft to use standard LaTeX commands to create the titles, allowing other packages to work with it.

Discard all options for lwarp-tocloft:

for HTML output:

```
\LWR@ProvidesPackageDrop{tocloft}[2017/08/31]
```

\tocloftpagestyle {⟨*style*⟩}

```
\newcommand{\tocloftpagestyle}[1]{}
```

\cftmarktoc

```
\newcommand*{\cftmarktoc}{}
```

\cfttoctitlefont

```
\newcommand*{\cfttoctitlefont}{}
```

\cftaftertoctitle

```
\newcommand*{\cftaftertoctitle}{}

\newlength{\cftbeforetoctitleskip}
\newlength{\cftaftertoctitleskip}
```

\cftmarklof

```
\newcommand*{\cftmarklof}{}
```

\cftloftitlefont

```
\newcommand*{\cftloftitlefont}{}
```

\cftafterloftitle

```
\newcommand*{\cftafterloftitle}{}

\newlength{\cftbeforeloftitleskip}
\newlength{\cftafterloftitleskip}
```

\cftmarklot

```
\newcommand*{\cftmarklot}{}
```

\cftlottitlefont

```
\newcommand*{\cftlottitlefont}{}
```

\cftafterlottitle

```
\newcommand*{\cftafterlottitle}{}

\newlength{\cftbeforelottitleskip}
\newlength{\cftafterlottitleskip}
```

\cftdot

```
\providecommand*{\cftdot}{.}
```

\cftdotsep

```
\providecommand*{\cftdotsep}{1}
```

\cftnodots

```
\providecommand*{\cftnodots}{5000}
```

\cftdotfill {⟨*sep*⟩}

```
\providecommand{\cftdotfill}[1]{}
```

\cftsetpnumwidth {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetpnumwidth}{m}{}
```

\cftsetrmarg {⟨*length*⟩}

```
\DeclareDocumentCommand{\cftsetrmarg}{m}{}
```

\cftpnumalign {⟨*alignment*⟩}

```
\DeclareDocumentCommand{\cftpnumalign}{m}{}

\LWR@providelength{\cftparskip}
```

The part-related items are also provided by memoir:

```
\LWR@providelength{\cftbeforepartskip}
\LWR@providelength{\cftpartindent}
\LWR@providelength{\cftpartnumwidth}
\providecommand*{\cftpartfont}{}
\providecommand*{\cftpartpresnum}{}
\providecommand*{\cftpartaftersnum}{}
\providecommand*{\cftpartaftersnumb}{}
\providecommand*{\cftpartleader}{}
\providecommand*{\cftpartdotsep}{1}
\providecommand*{\cftpartpagefont}{}
\providecommand*{\cftpartafterpnum}{}
```

memoir uses the full name “chapter” instead of “chap”:

```
\LWR@providelength{\cftbeforechapskip}
\LWR@providelength{\cftchapindent}
\LWR@providelength{\cftchapnumwidth}
\newcommand*{\cftchapfont}{}
\newcommand*{\cftchappresnum}{}
\newcommand*{\cftchapaftersnum}{}
\newcommand*{\cftchapaftersnumb}{}
\newcommand*{\cftchapleader}{}
\newcommand*{\cftchapdotsep}{1}
\newcommand*{\cftchappagefont}{}
\newcommand*{\cftchapafterpnum}{}
```

The following do not appear in memoir:

```
\LWR@providelength{\cftbeforesecskip}
\LWR@providelength{\cftsecindent}
\LWR@providelength{\cftsecnumwidth}
\newcommand*{\cftsecfont}{}
\newcommand*{\cftsecpresnum}{}
\newcommand*{\cftsecaftersnum}{}
\newcommand*{\cftsecaftersnumb}{}
\newcommand*{\cftsecleader}{}
\newcommand*{\cftsecdotsep}{1}
\newcommand*{\cftsecpagefont}{}
\newcommand*{\cftsecafterpnum}{}

\LWR@providelength{\cftbeforesubsecskip}
```

```
\LWR@providelength{\cftsubsecindent}
\LWR@providelength{\cftsubsecnumwidth}
\newcommand*{\cftsubsecfont}{}
\newcommand*{\cftsubsecpresnum}{}
\newcommand*{\cftsubsecaftersnum}{}
\newcommand*{\cftsubsecaftersnumb}{}
\newcommand*{\cftsubsecleader}{}
\newcommand*{\cftsubsecdotsep}{1}
\newcommand*{\cftsubsecpagefont}{}
\newcommand*{\cftsubsecafterpnum}{}

\LWR@providelength{\cftbeforesubsubsecskip}
\LWR@providelength{\cftsubsubsecindent}
\LWR@providelength{\cftsubsubsecnumwidth}
\newcommand*{\cftsubsubsecfont}{}
\newcommand*{\cftsubsubsecpresnum}{}
\newcommand*{\cftsubsubsecaftersnum}{}
\newcommand*{\cftsubsubsecaftersnumb}{}
\newcommand*{\cftsubsubsecleader}{}
\newcommand*{\cftsubsubsecdotsep}{1}
\newcommand*{\cftsubsubsecpagefont}{}
\newcommand*{\cftsubsubsecafterpnum}{}

\LWR@providelength{\cftbeforeparaskip}
\LWR@providelength{\cftparaindent}
\LWR@providelength{\cftparanumwidth}
\newcommand*{\cftparafont}{}
\newcommand*{\cftparapresnum}{}
\newcommand*{\cftparaaftersnum}{}
\newcommand*{\cftparaaftersnumb}{}
\newcommand*{\cftparaleader}{}
\newcommand*{\cftparadotsep}{1}
\newcommand*{\cftparapagefont}{}
\newcommand*{\cftparaafterpnum}{}

\LWR@providelength{\cftbeforesubparaskip}
\LWR@providelength{\cftsubparaindent}
\LWR@providelength{\cftsubparanumwidth}
\newcommand*{\cftsubparafont}{}
\newcommand*{\cftsubparapresnum}{}
\newcommand*{\cftsubparaaftersnum}{}
\newcommand*{\cftsubparaaftersnumb}{}
\newcommand*{\cftsubparaleader}{}
\newcommand*{\cftsubparadotsep}{1}
\newcommand*{\cftsubparapagefont}{}
\newcommand*{\cftsubparaafterpnum}{}

\LWR@providelength{\cftbeforefigskip}
\LWR@providelength{\cftfigindent}
\LWR@providelength{\cftfignumwidth}
\newcommand*{\cftfigfont}{}
\newcommand*{\cftfigpresnum}{}
\newcommand*{\cftfigaftersnum}{}
\newcommand*{\cftfigaftersnumb}{}
\newcommand*{\cftfigleader}{}
```

```
\newcommand*{\cftfigdotsep}{1}
\newcommand*{\cftfigpagefont}{}
\newcommand*{\cftfigafterpnum}{}

\LWR@providelength{\cftbeforesubfigskip}
\LWR@providelength{\cftsubfigindent}
\LWR@providelength{\cftsubfignumwidth}
\newcommand*{\cftsubfigfont}{}
\newcommand*{\cftsubfigpresnum}{}
\newcommand*{\cftsubfigaftersnum}{}
\newcommand*{\cftsubfigaftersnumb}{}
\newcommand*{\cftsubfigleader}{}
\newcommand*{\cftsubfigdotsep}{1}
\newcommand*{\cftsubfigpagefont}{}
\newcommand*{\cftsubfigafterpnum}{}

\LWR@providelength{\cftbeforetabskip}
\LWR@providelength{\cfttabindent}
\LWR@providelength{\cfttabnumwidth}
\newcommand*{\cfttabfont}{}
\newcommand*{\cfttabpresnum}{}
\newcommand*{\cfttabaftersnum}{}
\newcommand*{\cfttabaftersnumb}{}
\newcommand*{\cfttableader}{}
\newcommand*{\cfttabdotsep}{1}
\newcommand*{\cfttabpagefont}{}
\newcommand*{\cfttabafterpnum}{}

\LWR@providelength{\cftbeforesubtabskip}
\LWR@providelength{\cftsubtabindent}
\LWR@providelength{\cftsubtabnumwidth}
\newcommand*{\cftsubtabfont}{}
\newcommand*{\cftsubtabpresnum}{}
\newcommand*{\cftsubtabaftersnum}{}
\newcommand*{\cftsubtabaftersnumb}{}
\newcommand*{\cftsubtableader}{}
\newcommand*{\cftsubtabdotsep}{1}
\newcommand*{\cftsubtabpagefont}{}
\newcommand*{\cftsubtabafterpnum}{}

\DeclareDocumentCommand{\cftsetindents}{m m m}{}

\newcommand{\pagenumbersoff}[1]{}
\newcommand{\pagenumberson}[1]{}
```

\newlistentry [⟨*within*⟩] {⟨*counter*⟩} {⟨*ext*⟩} {⟨*level-1*⟩}

```
\DeclareDocumentCommand{\newlistentry}{o m m m}
{%
\LWR@traceinfo{newlistentry #2 #3 #4}%
\IfValueTF{#1}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}[#1]%
```

```
        \expandafter\edef\csname the#2\endcsname{%
            \expandafter\noexpand\csname the#1\endcsname.\noexpand\arabic{#2}%
        }%
    }{}%
}%
{%
    \@ifundefined{c@#2}{%
        \newcounter{#2}%
    }{}%
}%
\@namedef{l@#2}##1##2{%
    \hypertocfloat{1}{#2}{#3}{##1}{##2}%
    \def\cftwhatismyname{#2}% from memoir
}%
\expandafter\newlength\csname cftbefore#2skip\endcsname%
\expandafter\newlength\csname cft#2indent\endcsname%
\expandafter\newlength\csname cft#2numwidth\endcsname%
\@namedef{cft#2font}{}%
\@namedef{cft#2presnum}{}%
\@namedef{cft#2aftersnum}{}%
\@namedef{cft#2aftersnumb}{}%
\@namedef{cft#2leader}{}%
\@namedef{cft#2dotsep}{1}%
\@namedef{cft#2pagefont}{}%
\@namedef{cft#2afterpnum}{}%
\@namedef{toclevel@#2}{#4}%
\@namedef{cft#2fillnum}##1{}%
\LWR@traceinfo{newlistentry done}%
}
```

\newlistof [⟨*within*⟩] {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the \newfloat mechanism.

```
\DeclareDocumentCommand{\newlistof}{o m m m}
{%
\IfValueTF{#1}
{\newlistentry[#1]{#2}{#3}{0}}
{\newlistentry{#2}{#3}{0}}
\@namedef{ext@#2}{#3}
\@ifundefined{c@#3depth}{\newcounter{#3depth}}{}
\setcounter{#3depth}{1}
\@namedef{cftmark#3}{}
\@namedef{listof#2}{\listof{#2}{#4}}
\@namedef{@cftmake#3title}{}
\expandafter\newlength\csname cftbefore#3titleskip\endcsname
\expandafter\newlength\csname cftafter#3titleskip\endcsname
\@namedef{cft#3titlefont}{}
\@namedef{cftafter#3title}{}
\@namedef{cft#3prehook}{}
\@namedef{cft#3posthook}{}
}
```

\cftchapterprecis {⟨*text*⟩}

```
\newcommand{\cftchapterprecis}[1]{%
```

```
  \cftchapterprecishere{#1}
  \cftchapterprecistoc{#1}}
\newcommand{\cftchapterprecishere}[1]{%
  \begin{quote}\textit{#1}\end{quote}}
\newcommand{\cftchapterprecistoc}[1]{
  \addtocontents{toc}{%
  {
     \protect\begin{quote}#1\protect\end{quote}}
  }
}
```

File 381 **lwarp-tocstyle.sty**

§ 479 Package

tocstyle

Pkg tocstyle tocstyle is ignored.

⚠ Not fully tested! Please send bug reports!

for HTML output:

```
\LWR@ProvidesPackageDrop{tocstyle}[2017/02/23]

\newcommand*{\usetocstyle}[2][]{}
\newcommand*{\deactivatetocstyle}[1][]{}
\newcommand*{\reactivatetocstyle}[1][]{}
\NewDocumentCommand{\settocfeature}{o o m m}{}
\NewDocumentCommand{\settocstylefeature}{o m m}{}
\NewDocumentCommand{\newtocstyle}{o o m m}{}
\newcommand*{\aliastoc}[2]{}
\newcommand*{\showtoc}[2][]{}
\newcommand{\iftochasdepth}[4]{}
```

File 382 **lwarp-todo.sty**

§ 480 Package

todo

(*Emulates or patches code by* Federico Garcia.)

Pkg todo todo is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{todo}[2010/03/31]

\renewcommand\todoitem[2]{%
    \refstepcounter{todo}%
    \item[%
        \HTMLunicode{2610} \quad
        \ref{todopage:\thetodo}
     ] : {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
    \label{todolbl:\thetodo}%
}%

```

```
\renewcommand\doneitem[2]{%
    \stepcounter{todo}%
    \item[%
        \HTMLunicode{2611} \quad
        \ref{todopage:\thetodo}
    ] \@nameuse{@done\the\c@todo}:
        {\todoformat\ifx#1\todomark\else\textbf{#1} \fi}#2%
}

\xpatchcmd{\@displaytodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displaytodo.}}

\xpatchcmd{\@displayfulltodo}
    {\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch @displayfulltodo.}}

\patchcmd{\todoenv}{\itshape see text.}{\textit{see text.}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch todoenv.}}

\patchcmd{\astodos}{\todoformat #1}{\todoformat \textbf{#1}}{}
    {\PackageWarning{lwarp-todo}{Unable to patch astodos.}}

\AtBeginDocument{
    \crefname{todo}{todo}{todos}
    \Crefname{todo}{Todo}{Todos}
}
```

File 383 **lwarp-todonotes.sty**

§ 481 Package todonotes

(*Emulates or patches code by* Henrik Skov Midtiby.)

Pkg todonotes todonotes is emulated.

The documentation for todonotes and luatodonotes have an example with a todo inside a caption. If this example does not work it will be necessary to move the todo outside of the caption.

for HTML output:

```
\LWR@ProvidesPackagePass{todonotes}[2012/07/25]

\if@todonotes@disabled
\else

\newcommand{\ext@todo}{tdo}

\renewcommand{\l@todo}[2]{\hypertocfloat{1}{todo}{ldo}{#1}{#2}}


\let\LWRTODONOTES@orig@todototoc\todototoc

\renewcommand*{\todototoc}{%
```

```
\phantomsection%
\LWRTODONOTES@orig@todototoc%
}

\renewcommand{\@todonotes@drawMarginNoteWithLine}{
\fcolorbox
    {\@todonotes@currentbordercolor}
    {\@todonotes@currentbackgroundcolor}
    {\arabic{@todonotes@numberoftodonotes}}
\marginpar{\@todonotes@drawMarginNote}
}

\renewcommand{\@todonotes@drawInlineNote}{%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \if@todonotes@authorgiven%
        {\@todonotes@author:\,}%
        \fi%
        \@todonotes@text%
    }%
}

\renewcommand{\@todonotes@drawMarginNote}{%
    \if@todonotes@authorgiven%
        \@todonotes@author\par%
    \fi%
    \arabic{@todonotes@numberoftodonotes}: %
    \fcolorbox%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentbackgroundcolor}%
    {%
        \@todonotes@sizecommand%
        \@todonotes@text %
    }%
}%

\renewcommand{\@todonotes@drawLineToRightMargin}{}

\renewcommand{\@todonotes@drawLineToLeftMargin}{}

\renewcommand{\missingfigure}[2][]{%
\setkeys{todonotes}{#1}%
\addcontentsline{tdo}{todo}{\@todonotes@MissingFigureText: #2}%
\fcolorboxBlock%
    {\@todonotes@currentbordercolor}%
    {\@todonotes@currentfigcolor}%
    {%
        \setlength{\fboxrule}{4pt}%
        \fcolorbox{red}{white}{Missing figure} \quad #2%
    }
}

\LetLtxMacro\LWRTODONOTES@orig@todo\@todo
```

```
66
67 \RenewDocumentCommand{\@todo}{o m}{%
68 \begingroup%
69 \renewcommand*{\phantomsection}{}%
70 \IfValueTF{#1}{%
71     \LWRTODONOTES@orig@todo[#1]{#2}%
72 }{%
73     \LWRTODONOTES@orig@todo{#2}%
74 }
75 \endgroup%
76 }
77
78 \fi% \if@todonotes@disabled
```

File 384 **lwarp-topcapt.sty**

§ 482 Package topcapt

Pkg topcapt topcapt is emulated.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{topcapt}[2004/12/11]
2 \LetLtxMacro\topcaption\caption
```

File 385 **lwarp-tram.sty**

§ 483 Package tram

Pkg tram tram is emulated.

⚠ block only The HTML emulation uses a , which must not appear inside an HTML or an HTML paragraph. For this reason, the tram environment should only be used to contain paragraphs inside a \parbox or minipage. tram should not be used to mark up inline text.

To disable tram, allowing source compatibility with inline uses:

```
\begin{warpHTML}
\renewenvironment{tram}[1][]{}{}
\end{warpHTML}
```

for HTML output:

```
1 \LWR@ProvidesPackageDrop{tram}[2013/04/04]
2 \newenvironment{tram}[1][]%
3     {\BlockClass[background:lightgray]{tram}}
4     {\endBlockClass}
```

File 386 **lwarp-transparent.sty**

§ 484 Package transparent

(*Emulates or patches code by* Heiko Oberdiek.)

Pkg transparent transparent is emulated. \texttransparent works for inline objects. \transparent only works for \includegraphics.

⚠ Not XeLaTeX! Note that transparent does not work with XeLaTeX.

for HTML output: Discard all options for lwarp-transparent:

```
\LWR@ProvidesPackageDrop{transparent}[2016/05/16]

\newcommand*{\transparent}[1]{\edef\LWR@opacity{#1}}

\newcommand*{\texttransparent}[2]{%
\begingroup%
\transparent{#1}%
\InlineClass[opacity: #1]{transparent}{#2}%
\endgroup%
}
```

File 387 **lwarp-trimclip.sty**

§ 485 Package trimclip

Pkg trimclip trimclip is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{trimclip}[2018/04/08]
```

The third argument, the text, is not touched. This allows \bgroup / \egroup, and verbatim content.

```
\csdef{trimbox}{\@ifstar\@gobble\@gobble}
\csletcs{trimbox*}{trimbox}
\def\endtrimbox{}
\csletcs{endtrimbox*}{endtrimbox}

\csletcs{clipbox}{trimbox}
\csletcs{clipbox*}{trimbox}
\csletcs{endclipbox}{endtrimbox}
\csletcs{endclipbox*}{endtrimbox}

\csletcs{marginbox}{trimbox}
\csletcs{marginbox*}{trimbox}
\csletcs{endmarginbox}{endtrimbox}
```

```
\csletcs{endmarginbox*}{endtrimbox}
```

File 388 **lwarp-trivfloat.sty**

§ 486 Package

trivfloat

(*Emulates or patches code by* Joseph Wright.)

Pkg trivfloat trivfloat is forced to use the built-in lwarp emulation for floats.

To create a new float type and change its name:

```
\trivfloat{example}
\renewcommand{\examplename}{Example Name}
\crefname{example}{example}{examples}
\Crefname{example}{Example}{Examples}
```

Discard all options for lwarp-trivfloat. This tells trivfloat not to use floatrow or memoir.

```
\LWR@ProvidesPackageDrop{trivfloat}[2009/04/23]
\LWR@origRequirePackage{trivfloat}
```

\tfl@chapter@fix Nullified at the beginning of the document. Is used by trivfloat to correct float chapter numbers, but is not needed for lwarp.

for HTML output:

```
\begin{warpHTML}
\AtBeginDocument{\DeclareDocumentCommand{\tfl@chapter@fix}{m m}{}}
\end{warpHTML}
```

§ 486.1 Combining \newfloat, \trivfloat, and algorithmicx

for HTML & PRINT:

```
\begin{warpall}
```

For both print and HTML output:

⚠ When using float, trivfloat, or algorithmicx at the same time, be aware of conflicting file usage. algorithmicx uses .loa. trivfloat by default starts with .loa and goes up for additional floats, skipping .lof and .lot.

⚠ When using \newfloat, be sure to manually assign higher letters to the \newfloat files to avoid .loa used by algorithmicx, and any files used by trivfloat. Also avoid using .lof and .lot.

⚠ When using \trivfloat, you may force it to avoid conflicting with algorithmicx by starting trivfloat's file extensions with .lob:

```
\makeatletter
\setcounter{tfl@float@cnt}{1} % start trivfloats with .lob
\makeatletter
```

```
\end{warpall}
```

File 389 **lwarp-truncate.sty**

§ 487 Package truncate

Pkg truncate truncate is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{truncate}[2001/08/20]
```

```
\providecommand{\TruncateMarker}{}
\newcommand{\truncate}[3][\TruncateMarker]{#3}
```

File 390 **lwarp-turnthepage.sty**

§ 488 Package turnthepage

Pkg turnthepage turnthepage is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{turnthepage}[2011/03/24]
```

```
\newcommand{\turnthepage}{}
```

File 391 **lwarp-twoup.sty**

§ 489 Package twoup

Pkg twoup twoup is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{twoup}[2007/02/26]
```

```
\newcommand{\cleartolastpage}{}
```

File 392 **lwarp-typearea.sty**

§ 490 Package typearea

(*Emulates or patches code by* Markus Kohm.)

Pkg typearea typearea is emulated.

This package may be loaded standalone, but is also loaded automatically if koma-script classes are in use. \DeclareDocumentCommand is used to overwrite the koma-script definitions.

for HTML output:

```
\LWR@ProvidesPackageDrop{typearea}[2018/03/30]

\DeclareDocumentCommand{\typearea}{o m}{}
\DeclareDocumentCommand{\recalctypearea}{}{}
\@ifundefined{footheight}{\newlength\footheight}{}
\DeclareDocumentCommand{\areaset}{o m m}{}
\DeclareDocumentCommand{\activateareas}{}{}
\DeclareDocumentCommand{\storeareas}{m}{}
\DeclareDocumentCommand{\BeforeRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterRestoreareas}{s m}{}
\DeclareDocumentCommand{\AfterCalculatingTypearea}{s m}{}
\DeclareDocumentCommand{\AfterSettingArea}{s m}{}
```

File 393 **lwarp-typicons.sty**

§ 491 Package

typicons

(*Emulates or patches code by* Arthur Vigil, Xavier Danaux.)

Pkg typicons typicons is patched for use by lwarp.

If \ticon is used, the name of the icon is used in the alt tag. Otherwise, for each of the individual icon macros, a generic alt tag is used.

for HTML output:

```
\LWR@ProvidesPackagePass{typicons}[2015/05/20]

\LetLtxMacro\LWR@orig@symbol\symbol

\let\LWR@orig@typicon@TI\TI

\newcommand*{\LWR@typicon@symbol}[1]{%
    \begin{lateximage}*[(typicon)][typicon#1]%
    \begingroup%
    \LWR@orig@typicon@TI%
    \LWR@orig@symbol{#1}%
    \endgroup%
    \end{lateximage}%
}

\renewcommand*{\TI}{%
    \LetLtxMacro\symbol\LWR@typicon@symbol%
}

\renewcommand*{\ticon}[1]
{%
    \begin{lateximage}*[(#1 icon)][typicon#1]%
```

```
    \TI\csname ticon@#1\endcsname%
    \end{lateximage}%
}
```

File 394 **lwarp-ulem.sty**

§ 492 Package **ulem**

(*Emulates or patches code by* Donald Arseneau.)

Pkg ulem Patched for use by lwarp.

for HTML output: Use the original package:

```
\LWR@ProvidesPackagePass{ulem}[2012/05/18]
```

Basic markup commands, using CSS:

```
\NewDocumentCommand{\LWR@HTML@uline}{+m}{%
    \InlineClass%
        (text-decoration:underline; text-decoration-skip: auto)%
        {uline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uline}

\NewDocumentCommand{\LWR@HTML@uuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:double%
        )%
        {uuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{uuline}

\NewDocumentCommand{\LWR@HTML@uwave}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline; text-decoration-skip: auto;%
            text-decoration-style:wavy%
        )%
        {uwave}{\LWR@isolate{#1}}%
}
\LWR@formatted{uwave}

\NewDocumentCommand{\LWR@HTML@sout}{+m}{%
    \InlineClass%
        (text-decoration:line-through)%
        {sout}{\LWR@isolate{#1}}%
}
\LWR@formatted{sout}

\NewDocumentCommand{\LWR@HTML@xout}{+m}{%
```

```
    \InlineClass%
        (text-decoration:line-through)%
        {xout}{\LWR@isolate{#1}}%
}

\NewDocumentCommand{\LWR@HTML@dashuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style:dashed%
        )%
        {dashuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{xout}

\NewDocumentCommand{\LWR@HTML@dotuline}{+m}{%
    \InlineClass%
        (%
            text-decoration:underline;%
            text-decoration-skip: auto;%
            text-decoration-style: dotted%
        )%
        {dotuline}{\LWR@isolate{#1}}%
}
\LWR@formatted{dotuline}
```

Nullified/emulated macros:

```
\NewDocumentCommand{\LWR@HTML@markoverwith}{m}{}
\LWR@formatted{markoverwith}

\NewDocumentCommand{\LWR@HTML@ULon}{+m}{\uline{#1}\egroup}
\LWR@formatted{ULon}
```

File 395 **lwarp-umoline.sty**

§ 493 Package

umoline

(*Emulates or patches code by* Hiroshi Nakashima.)

Pkg umoline umoline is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{umoline}[2000/07/11]

\newcommand*{\LWR@HTML@Underline}[1]{%
    \InlineClass{uline}{#1}%
}
\LWR@formatted{Underline}

\newcommand*{\LWR@HTML@Midline}[1]{%
    \InlineClass{sout}{#1}%
}
```

```
\LWR@formatted{Midline}

\newcommand*{\LWR@HTML@Overline}[1]{%
    \InlineClass{oline}{#1}%
}
\LWR@formatted{Overline}

\newcommand*{\LWR@HTML@UMOline}[2]{%
    \InlineClass{uline}{#2}%
}
\LWR@formatted{UMOline}

\NewDocumentCommand{\LWR@HTML@UMOspace}{s m o}{\hspace*{#2}}
\LWR@formatted{UMOspace}

\NewDocumentCommand{\LWR@HTML@UMOnewline}{s}{\newline}
\LWR@formatted{UMOnewline}
```

File 396 **lwarp-underscore.sty**

§ 494 Package underscore

Pkg underscore underscore is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{underscore}[2006/09/13]
```

File 397 **lwarp-units.sty**

§ 495 Package units

(*Emulates or patches code by* Axel Reichert.)

Pkg units units is patched for use by lwarp.

Values are not styled by CSS, and take the style of the surrounding HTML text.

Units are styled according to the print version, so they will be forced to upright roman in HTML if the print version does so. It may be necessary to adjust the document's body CSS to match the print version.

for HTML output:

```
\LWR@ProvidesPackagePass{units}[1998/08/04]

\DeclareRobustCommand*{\LWR@HTML@unit}[2][]{%
\ifblank{#1}%
    {\LWR@textcurrentfont{#2}}%
    {%
        #1%
        \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
        \LWR@textcurrentfont{#2}%
    }%
```

```
}
\LWR@formatted{unit}

\DeclareRobustCommand*{\LWR@HTML@unitfrac}[3][]{%
\ifblank{#1}%
    {%
            \nicefrac{#2}{#3}%
    }%
    {%
            #1%
            \ifthenelse{\boolean{B@UnitsLoose}}{~}{\,}%
            \nicefrac{#2}{#3}%
    }%
}

\LWR@formatted{unitfrac}
```

For Mathjax:

```
\CustomizeMathJax{\newcommand{\unit}[2][]{#1 #2}}
\CustomizeMathJax{\newcommand{\unitfrac}[3][]{#1 #2/#3}}
```

File 398 **lwarp-unitsdef.sty**

§ 496 Package

unitsdef

(*Emulates or patches code by* Patrick Happel.)

Pkg unitsdef unitsdef is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{unitsdef}[2005/01/04]

\renewcommand{\unitvaluesep}{\,}

\renewcommand{\unittimes}{\@@setunitsepfalse\HTMLunicode{22c5}}% \cdot

\renewunit{\arcmin}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^\prime}}%
        {\HTMLunicode{2032}}% prime
}

\renewunit{\arcsec}{%
    \ifnumcomp{\value{LWR@lateximagedepth}}{>}{0}%
        {\ensuremath{{}^{\prime\prime}}}%
        {\HTMLunicode{2033}}% dbl prime
}

\renewrobustcmd{\SI}[2]{%
  \begingroup%
    \let\unit@@xspace\relax%
    \unitSIdef\selectfont%
```

```
      \LWR@textcurrentfont{#1#2}% lwarp
  \endgroup%
}
```

File 399 **lwarp-upref.sty**

§ 497 Package upref

Pkg upref upref is ignored.

for HTML output: Discard all options for lwarp-upref:

```
\LWR@ProvidesPackageDrop{upref}[2007/03/14]
```

File 400 **lwarp-url.sty**

§ 498 Package url

(*Emulates or patches code by* Donald Arseneau.)

Pkg url url is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{url}[2013/09/16]
```

url uses math mode to print its string inside a group, so the original meaning of math is restored first.

```
\LetLtxMacro\LWR@url@origUrl@FormatString\Url@FormatString

\renewcommand*{\Url@FormatString}{%
    \InlineClass{verbatim}{%
        \LWR@restoreorigformatting%
        \LWR@url@origUrl@FormatString%
    }%
}
```

File 401 **lwarp-uspace.sty**

§ 499 Package uspace

Pkg uspace uspace is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{uspace}[2016/11/06]
```

File 402 **lwarp-verse.sty**

§ 500 Package

verse

(*Emulates or patches code by* Peter Wilson.)

Pkg verse verse is supported and patched by lwarp.

for HTML output: Pass all options for lwarp-verse:

```
\LWR@ProvidesPackagePass{verse}[2009/09/04]
```

When using verse or memoir, always place a \\ after each line.

\attrib The documentation for the verse and memoir packages suggest defining an \attrib command, which may already exist in current documents, but it will only work for print output. lwarp provides \attribution, which works for both print and HTML output. To combine the two so that \attrib is used for print and \attribution is used for HTML:

```
\begin{warpHTML}
\let\attrib\attribution
\end{warpHTML}
```

Len \vleftskip
Len \vleftmargini
Len \HTMLvleftskip
Len \HTMLleftmargini

These lengths are used by verse and memoir to control the left margin, and they may already be set by the user for print output. New lengths \HTMLvleftskip and \HTMLleftmargini are provided to control the margins in HTML output. These new lengths may be set by the user before any verse environment, and persist until they are manually changed again. One reason to change \HTMLleftmargini is if there is a wide \flagverse in use, such as the word "Chorus", in which case the value of \HTMLleftmargini should be set to a wide enough length to contain "Chorus". The default is wide enough for a stanza number.

⚠ spacing Horizontal spacing relies on *pdftotext*'s ability to discern the layout (-layout option) of the text in the HTML-tagged PDF output. For some settings of \HTMLleftmargini or \HTMLleftskip the horizontal alignment may not work out exactly, in which case a label may be shifted by one space.

Env verse The verse environment will be placed inside a HTML <pre>.

```
\AfterEndPreamble{
\LWR@traceinfo{Patching verse.}
```

At the beginning of the verse environment:

```
\AtBeginEnvironment{verse}
{%
```

Use the original `list` environment inside a <pre> to attempt to preserve formatting.

```
\LWR@restoreoriglists%
```

Pkg verse
Cls memoir
\flagverse
Len \vleftskip

The verse or memoir packages can place stanza numbers to the left with their `\flagverse` command. Do not allow them to go into the left margin, which would cause *pdfcrop* to crop the entire page further to the left:

```
\ifdef{\vleftskip}{%
\setlength{\vleftskip}{\HTMLvleftskip}
\setlength{\leftmargini}{\HTMLleftmargini}
}{}
\LWR@forcenewpage
\LWR@atbeginverbatim{3}{verse}%
}
```

After the end of the `verse` environment, which places the <pre> tag at the regular left margin:

```
\AtEndEnvironment{verse}{%
\leavevmode%
\LWR@afterendverbatim{1}%
}
```

Patch to place poemtitle inside an HTML of class `poemtitle`:

```
\ifdef{\poemtitle}{
\DeclareDocumentCommand{\@vstypeptitle}{m}{%
   \vspace{\beforepoemtitleskip}%
   {\InlineClass{poemtitle}{\poemtitlefont #1}\par}%
   \vspace{\afterpoemtitleskip}%
 }
}{}

\LWR@traceinfo{Finished patching verse.}
}% AfterEndPreamble
```

File 403 **lwarp-versonotes.sty**

§ 501 Package

versonotes

(*Emulates or patches code by* Norman Gray.)

Pkg versonotes

versonotes is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{versonotes}[2015/12/08]
```

```
\newcommand{\versonote}[1]{\marginpar{#1}}
\newdimen\versotextwidth
\newdimen\versoleftmargin
\newcommand*{\versolayout}{}
```

File 404 **lwarp-vertbars.sty**

§ 502 Package vertbars

(*Emulates or patches code by* Peter Wilson.)

Pkg vertbars vertbars is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{vertbars}[2010/11/27]

\newlength{\barwidth}
\setlength{\barwidth}{0.4pt}
\newlength{\barspace}
\setlength{\barspace}{1em}

\newenvironment{vertbar}{
    \LWR@forcenewpage
    \LWR@forceminwidth{\barwidth}
    \begin{BlockClass}[%
        border-left: \LWR@printlength{\LWR@atleastonept} solid black ; %
        padding-left: \LWR@printlength{\barspace}%
    ]{vertbar}
}{
    \end{BlockClass}
}
```

File 405 **lwarp-vmargin.sty**

§ 503 Package vmargin

Pkg vmargin vmargin is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vmargin}[2004/07/15]

\newcommand*{\LWRVM@customsize}[2]{}
\newcommand*{\setpapersize}[2][]{\ifstrequal{#2}{custom}{\LWRVM@customsize}{}}
\newcommand*{\setmargins}[8]{}
\newcommand*{\setmarginsrb}[8]{}
\newcommand*{\setmargnohf}[4]{}
\newcommand*{\setmargnohfrb}[4]{}
\newcommand*{\setmarg}[4]{}
\newcommand*{\setmargrb}[4]{}
\newlength{\PaperWidth}
\setlength{\PaperWidth}{8.5in}
\newlength{\PaperHeight}
\setlength{\PaperHeight}{11in}
\newif\ifLandscape
```

File 406 **lwarp-vowel.sty**

§ 504 Package vowel

(*Emulates or patches code by* FUKUI REI.)

Pkg vowel vowel is patched for use by lwarp.

This package has been tested with *pdflatex* and the Type 1 TIPA fonts using the following package load sequence:

```
\usepackage[T3,T1]{fontenc}
\usepackage[utf8]{inputenc}
\usepackage[noenc]{tipa}
\usepackage{vowel}
```

for HTML output:

```
\LWR@ProvidesPackagePass{vowel}[2002/08/08]

\renewenvironment{vowel}[1][]
    {%
        \begin{lateximage}[(-vowel-~\packagediagramname)]%
        \@vowel[#1]%
    }
    {%
        \@@vowel%
        \end{lateximage}%
    }
```

File 407 **lwarp-vpe.sty**

§ 505 Package vpe

Pkg vpe vpe is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{vpe}[2012/04/18]
```

File 408 **lwarp-vwcol.sty**

§ 506 Package vwcol

(*Emulates or patches code by* WILL ROBERTSON.)

Pkg vwcol vwcol is patched for use with lwarp.

The `width` option is ignored. All `vwcol` environments adjust to 1–3 equal-width columns, depening on the width of the browser window.

The remaining options are supported, except for `lines` and `maxrecursion`.

for HTML output:

```
\LWR@ProvidesPackagePass{vwcol}[2015/02/10]
```

Factored from `\vwcol`. Each is given a style tag to append to the final style.

`\LWR@vwcol@addrule` {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addrule}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
     \LWR@printlength{\vwcol@rule} solid \LWR@origpound\LWR@vwcol@rulecolor ; %
    }%
}
```

`\LWR@vwcol@addrule` {⟨*style tag*⟩}

```
\newcommand*{\LWR@vwcol@addgap}[1]{%
    \appto{\LWR@vwcolstyle}{%
        #1: %
        \LWR@printlength{\vwcol@sep} ; %
    }%
}
```

Env `vwcol` {⟨*key/values*⟩}

Redefine the environment to add a HTML style. The style is built depending on the required options.

```
\renewenvironment*{vwcol}[1][]{%
```

New paragraph, and process the options:

```
\par\noindent%
\vwcolsetup{#1}%
```

Begin with no style:

```
\newcommand*{\LWR@vwcolstyle}{}
```

`presep` and `postsep` are created with HTML `margins`:

```
\if@vwcol@presep
    \appto{\LWR@vwcolstyle}{margin-left: 1em ; padding-left: .5em ; }
\fi
\if@vwcol@postsep
    \appto{\LWR@vwcolstyle}{margin-right: 1em ; padding-right: .5em ; }
\fi
```

`sep` becomes `column-gap`:

```
\ifdimgreater{\vwcol@sep}{1sp}{
    \LWR@vwcol@addgap{column-gap}
    \LWR@vwcol@addgap{-moz-column-gap}
    \LWR@vwcol@addgap{-webkit-column-gap}
}{}
```

`rule` become `column-rule`, while `prerule` and `postrule` become HTML borders:

```
\convertcolorspec{named}{\vwcol@rulecol}{HTML}\LWR@vwcol@rulecolor%
\ifdimgreater{\vwcol@rule}{0pt}{
    \ifdimless{\vwcol@rule}{1pt}{
        \setlength{\vwcol@rule}{1pt}
    }{}
    \LWR@vwcol@addrule{column-rule}
    \LWR@vwcol@addrule{-moz-column-rule}
    \LWR@vwcol@addrule{-webkit-column-rule}
    \if@vwcol@prerule\LWR@vwcol@addrule{border-left}\fi
    \if@vwcol@postrule\LWR@vwcol@addrule{border-right}\fi
}{}
```

Each of the justify options becomes a `text-align`. Indentation is added where appropriate.

```
\ifdefequal{\vwcol@justify}{\RaggedRight}{
    \appto{\LWR@vwcolstyle}{text-align: left ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}

\ifdefequal{\vwcol@justify}{\RaggedLeft}{
    \appto{\LWR@vwcolstyle}{text-align: right ; }
}{}

\ifdefequal{\vwcol@justify}{\Centering}{
    \appto{\LWR@vwcolstyle}{text-align: center ; }
}{}

\ifdefequal{\vwcol@justify}{\justifying}{
    \appto{\LWR@vwcolstyle}{text-align: justify ; }
    \ifdimgreater{\vwcol@parindent}{0pt}{
        \appto{\LWR@vwcolstyle}{%
            text-indent: \LWR@printlength{\vwcol@parindent} ; %
        }
    }{}
}{}
```

Create the `<div>` with the assembled style:

```
\BlockClass[\LWR@vwcolstyle]{multicols}
}
```

When the environment ends:

```
{
\endBlockClass
}
```

File 409 **lwarp-wallpaper.sty**

§ 507 Package

wallpaper

(*Emulates or patches code by* Michael H.F. Wilkinson.)

Pkg wallpaper wallpaper is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{wallpaper}[2005/01/18]

\newcommand*{\CenterWallPaper}[2]{}
\newcommand*{\ThisCenterWallPaper}[2]{}
\newcommand*{\TileWallPaper}[3]{}
\newcommand*{\ThisTileWallPaper}[3]{}
\newcommand*{\TileSquareWallPaper}[2]{}
\newcommand*{\ThisTileSquareWallPaper}[2]{}
\newcommand*{\ULCornerWallPaper}[2]{}
\newcommand*{\ThisULCornerWallPaper}[2]{}
\newcommand*{\LLCornerWallPaper}[2]{}
\newcommand*{\ThisLLCornerWallPaper}[2]{}
\newcommand*{\URCornerWallPaper}[2]{}
\newcommand*{\ThisURCornerWallPaper}[2]{}
\newcommand*{\LRCornerWallPaper}[2]{}
\newcommand*{\ThisLRCornerWallPaper}[2]{}
\newcommand*{\ClearWallPaper}{}
\newlength{\wpXoffset}
\newlength{\wpYoffset}
```

File 410 **lwarp-watermark.sty**

§ 508 Package watermark

(*Emulates or patches code by* Alexander I. Rozhenko.)

Pkg watermark watermark is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{watermark}[2004/12/09]

\newcommand{\watermark}[1]{}
\newcommand{\leftwatermark}[1]{}
\newcommand{\rightwatermark}[1]{}
\newcommand{\thiswatermark}[1]{}
\newcommand{\thispageheading}[1]{}
```

File 411 **lwarp-widows-and-orphans.sty**

§ 509 Package widows-and-orphans

Pkg widows-and-orphans widows-and-orphans is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{widows-and-orphans}[2018/09/01]

\NewDocumentCommand\WaOsetup{m}{}
\NewDocumentCommand\WaOparameters{}{}
\NewDocumentCommand\WaOignorenext{}{}
```

File 412 **lwarp-wrapfig.sty**

§ 510 Package wrapfig

(*Emulates or patches code by* Donald Arseneau.)

Pkg wrapfig wrapfig is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{wrapfig}[2003/01/31]


\newcommand*{\LWR@wrapposition}{}

\newcommand*{\LWR@subwrapfigure}[2]{%
\renewcommand*{\LWR@wrapposition}{}%
\ifthenelse{%
    \equal{#1}{r}\OR\equal{#1}{R}\OR%
    \equal{#1}{o}\OR\equal{#1}{O}%
}%
    {\renewcommand*{\LWR@wrapposition}{float:right}}%
    {\renewcommand*{\LWR@wrapposition}{float:left}}%
\setlength{\LWR@templengthone}{#2}%
\LWR@BlockClassWP{%
    width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition; %
    margin:10pt%
}%
{%
    width:\LWR@printlength{\LWR@templengthone}; \LWR@wrapposition%
}%
{marginblock}%
}


\NewDocumentEnvironment{wrapfigure}{o m o m}
{%
\LWR@subwrapfigure{#2}{#4}%
\captionsetup{type=figure}%
}
{%
\endLWR@BlockClassWP%
}


\NewDocumentEnvironment{wraptable}{o m o m}
{%
\LWR@subwrapfigure{#2}{#4}%
\captionsetup{type=table}%
}
{%
\endLWR@BlockClassWP%
}

```

```
43
44 \NewDocumentEnvironment{wrapfloat}{m o m o m}
45 {%
46 \LWR@subwrapfigure{#3}{#5}%
47 \captionsetup{type=#1}%
48 }
49 {%
50 \endLWR@BlockClassWP%
51 }
52
53 \newlength{\wrapoverhang}
```

File 413 **lwarp-xbmks.sty**

§ 511 Package xbmks

Pkg xbmks xbmks is ignored.

for HTML output:

```
1 \LWR@ProvidesPackageDrop{xbmks}[2018/07/04]

2 \newcommand{\xbmksetup}[1]{}
3 \NewDocumentCommand{\pdfbookmarkx}{o m o m}{}
4 \NewDocumentCommand{\currentpdfbookmarkx}{m o m}{}
5 \NewDocumentCommand{\subpdfbookmarkx}{m o m}{}
6 \NewDocumentCommand{\belowpdfbookmarkx}{m o m}{}
```

File 414 **lwarp-xcolor.sty**

§ 512 Package xcolor

(*Emulates or patches code by* Dr. Uwe Kern.)

Pkg xcolor xcolor is supported by lwarp.

§ 512.1 Limitations

\colorboxBlock and \fcolorboxBlock

\colorboxBlock and \fcolorboxBlock are provided for increased HTML compatibility, and they are identical to \colorbox and \fcolorbox in print mode. In HTML mode they place their contents into a instead of a . These s are set to display: inline-block so adjacent \colorboxBlocks appear side-by-side in HTML, although text is placed before or after each.

Print-mode definitions for \colorboxBlock and \fcolorboxBlock are created by lwarp's core if xcolor is loaded.

background: none

\fcolorbox and \fcolorboxBlock allow a background color of none, in which case only the frame is drawn, which can be useful for HTML.

color support

Color definitions, models, and mixing are fully supported without any changes re-

quired.

colored tables `\rowcolors` is supported, except that the optional argument is ignored so far.

colored text and boxes `\textcolor`, `\colorbox`, and `\fcolorbox` are supported.

`\color` and `\pagecolor` `\color` and `\pagecolor` are ignored. Use CSS or `\textcolor` where possible.

§ 512.2 xcolor definitions: location and timing

The lwarp core and its lwarp-xcolor package are tightly integrated to allow comparable results for print, HTML, and print inside an HTML `lateximage`. This requires a number of definitions and redefintions depending on whether each of xcolor and `lateximage` is being used, and whether print or HTML is being generated. Some of these actions are one-time when xcolor is loaded, and others are temporary as `lateximage` is used.

When xcolor is loaded in print mode: No special actions are taken at the time that xcolor is loaded in print mode, but see `\AtBeginDocument` below.

When lwarp-xcolor is loaded in HTML mode: xcolor's original definitions are saved for later restoration. `\LWR@restoreorigformatting` is appended to restore these definitions for use inside a `lateximage`. New HTML-mode definitions are created for `\textcolor`, `\pagecolor`, `\nopagecolor`, `\colorbox`, `\colorboxBlock`, `\fcolorbox`, `\fcolorboxBlock`, and `fcolorminipage`.

`\AtBeginDocument` in print or HTML mode: See Section 85. If xcolor has been loaded, the print-mode `\fcolorbox` is modified to accept a background color of `none`, and additional definitions are created for lwarp's new macros print-mode macros `\colorboxBlock`, `\fcolorboxBlock`, and `fcolorminipage`. The HTML versions of these macros will already have been created by lwarp-xcolor if it has been loaded.

For use inside an HTML `lateximage`, `\LWR@restoreorigformatting` is appended to temporarily set these functions to their print-mode versions.

In a `lateximage` in HTML mode: `\LWR@restoreorigformatting` temporarily restores the print-mode definitions of xcolor's functions. See `\LWR@restoreorigformatting` on page 485.

`\color`:

Print: Used as-is.

HTML: Ignored by *pdftotext*, and will not appear.

HTML `lateximage`: Colors will appear in a `lateximage`.

`\textcolor`:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 978.

HTML `lateximage`: Remembers and reuses the print version.

`\pagecolor`:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a `lateximage`.

`\nopagecolor`:

Print: Used as-is.

HTML: Ignored.

HTML lateximage: Colors will be picked up in a `lateximage`.

`\colorbox`:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 979.

HTML lateximage: Remembers and reuses the print version.

`\colorboxBlock`:

Print: Becomes `\colorbox`.

HTML: Newly defined by lwarp-xcolor to use a `<div>`, page 979.

HTML lateximage: Remembers and reuses the print version `\colorbox`.

`\fcolorbox`:

Print: Modified to allow a background of `none`.
`\LWR@print@fcolorbox` at section 85

HTML: Redefined by lwarp-xcolor, page 980.

HTML lateximage: Remembers and reuses the print version.

`\fcolorboxBlock`:

Print: Becomes `\fcolorbox`. Section 85

HTML: Newly defined by lwarp-xcolor to use a `<div>`, page 981.

HTML lateximage: Remembers and reuses the print version `\fcolorbox`.

`fcolorminipage`:

Print: Newly defined in the lwarp core.
`LWR@print@fcolorminipage` at section 85

HTML: Newly defined by lwarp-xcolor, page 981.

HTML lateximage: Uses the print version.

`\boxframe`:

Print: Used as-is.

HTML: Redefined by lwarp-xcolor, page 982.

HTML lateximage: Remembers and reuses the print version.

§ 512.3 Package loading

for HTML output:

```
\LWR@ProvidesPackagePass{xcolor}[2016/05/11]
\begin{warpHTML}
```

§ 512.4 Remembering and restoring original definitions

Remember the following print-mode actions to be restored when inside a `lateximage` environment:

```
\LetLtxMacro\LWR@print@pagecolor\pagecolor
\LetLtxMacro\LWR@print@nopagecolor\nopagecolor
```

`\LWR@restoreorigformatting` Inside a `lateximage` the following gets restored to their print-mode actions:

```
\appto\LWR@restoreorigformatting{%
\LetLtxMacro\pagecolor\LWR@print@pagecolor%
\LetLtxMacro\nopagecolor\LWR@print@nopagecolor%
}
```

§ 512.5 HTML color style

`\LWR@findcurrenttextcolor` Sets `\LWR@tempcolor` to the current color.

```
\renewcommand*{\LWR@findcurrenttextcolor}{%
\protect\colorlet{LWR@current@color}{.}%
\protect\convertcolorspec{named}{LWR@current@color}{HTML}\LWR@tempcolor%
}
```

`\LWR@currenttextcolorstyle` Prints a color style for the current color.

```
\newcommand*{\LWR@currenttextcolorstyle}{%
\LWR@findcurrenttextcolor%
\ifdefstring{\LWR@tempcolor}{000000}%
{}%
{color: \LWR@origpound\LWR@tempcolor ; }%
}
```

`\LWR@textcurrentcolor` {⟨*text*⟩} Like `\textcolor` but uses the current `\color` instead.

```
\DeclareDocumentCommand{\LWR@textcurrentcolor}{m}{%
\begingroup%
\LWR@FBcancel%
\LWR@findcurrenttextcolor%
\InlineClass[color:\LWR@origpound\LWR@tempcolor]{textcolor}{%
    \renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
    #1%
}%
\endgroup%
}
```

`\LWR@colorstyle` {⟨*2: model*⟩} {⟨*3: color*⟩}

For a color style, prints the color converted to HTML colors.

```
\NewDocumentCommand{\LWR@colorstyle}{m m}{%
\begingroup%
\LWR@FBcancel%
```

Use the xcolor package to convert to an HTML color space:

```
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
```

Print the converted color:

```
\LWR@origpound\LWR@tempcolor%
\endgroup%
}
```

\LWR@backgroundcolor [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Similar to \textcolor, but prints black text against a color background.

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@backgroundcolor}{O{named} m m}{%
\begingroup%
\LWR@FBcancel%
\InlineClass[background:\LWR@colorstyle{#1}{#2}]{backgroundcolor}{%
#3%
}%
\endgroup%
}
```

§ 512.6 HTML border

\LWR@borderpadding {⟨*colorstyle*⟩} {⟨*color*⟩} Prints the HTML attributes for a black border and padding. \LWR@forceminwidth must be used first in order to set the border width.

```
\newcommand*{\LWR@borderpadding}[2]{%
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
}
```

§ 512.7 High-level macros

\textcolor [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex color span.

```
\NewDocumentCommand{\LWR@HTML@textcolor}{o m m}{%
\begingroup%
```

Set the PDF color, to be picked up by SVG math if possible.

The print-mode \color command cannot accept the named option with color mixing, but it works with no option at all.

```
\IfValueTF{#1}{%
    \color[#1]{#2}%
}{%
    \color{#2}%
}%

\LWR@FBcancel%
\IfValueTF{#1}{%
\InlineClass[color:\LWR@colorstyle{#1}{#2}]{textcolor}{%
\renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
#3%
}%
}{%
\InlineClass[color:\LWR@colorstyle{named}{#2}]{textcolor}{%
\renewcommand*{\LWR@currenttextcolor}{\LWR@origpound\LWR@tempcolor}%
#3%
}%
}%
\endgroup%
}

\LWR@formatted{textcolor}
```

\pagecolor `[⟨model⟩] {⟨color⟩}`

Ignored. Use CSS instead.

```
\renewcommand*{\pagecolor}[2][named]{}
```

\nopagecolor Ignored.

```
\renewcommand*{\nopagecolor}{}
```

\colorbox `[⟨model⟩] {⟨color⟩} {⟨text⟩}`

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorbox}{O{named} m +m}{%
\begingroup%
\LWR@FBcancel%
\InlineClass[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorbox}{#3}%
\endgroup%
}

\AtBeginDocument{
\LWR@formatted{colorbox}
}
```

\colorboxBlock [⟨*model*⟩] {⟨*color*⟩} {⟨*text*⟩}

Converted into an HTML hex background color .

```
\NewDocumentCommand{\LWR@HTML@colorboxBlock}{O{named} m +m}{%
\begingroup%
\LWR@FBcancel%

\LWR@stoppars%

\begin{BlockClass}[%
background:\LWR@colorstyle{#1}{#2} ; %
padding:\LWR@printlength{\fboxsep}%
]{colorboxBlock}
#3
\end{BlockClass}%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formatted{colorboxBlock}
}
```

\fcolorbox [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorbox}{O{named} m O{named} m +m}{%
\LWR@traceinfo{HTML fcolorbox #2 #4}%
\begingroup%
\LWR@FBcancel%
\LWR@forceminwidth{\fboxrule}%
\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2}%
        ]{fcolorbox}{#5}%
    }%
    {% yes background color
        \InlineClass[%
        \LWR@borderpadding{#1}{#2} ; %
        background:\LWR@colorstyle{#3}{#4}%
        ]{fcolorbox}{#5}%
    }%
\endgroup%
```

```
}

\AtBeginDocument{
\LWR@formatted{fcolorbox}
}
```

\fcolorboxBlock [⟨*framemodel*⟩] {⟨*framecolor*⟩} [⟨*boxmodel*⟩] {⟨*boxcolor*⟩} {⟨*text*⟩}

Converted into a framed HTML hex background color span.

A background color of none creates a colored frame without a background color.

```
\NewDocumentCommand{\LWR@HTML@fcolorboxBlock}{O{named} m O{named} m +m}{%
\LWR@traceinfo{HTML fcolorboxBlock #2 #4}%
\begingroup%
\LWR@FBcancel%
\LWR@forceminwidth{\fboxrule}%

\LWR@stoppars%

\ifthenelse{\equal{#4}{none}}%
    {% no background color
        \begin{BlockClass}[%
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
    {% yes background color
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \begin{BlockClass}[%
            background:\LWR@origpound\LWR@tempcolortwo\ ; %
            \LWR@borderpadding{#1}{#2}%
        ]{fcolorboxBlock}
        #5
        \end{BlockClass}%
    }%
\endgroup%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
\global\booltrue{LWR@minipagethispar}%
\LWR@traceinfo{HTML fcolorboxBlock done}%
}

\AtBeginDocument{
\LWR@formatted{fcolorboxBlock}
}
```

Creates a framed HTML around its contents.

A print-output version is defined in the lwarp core: section 85

\LWR@subfcolorminipage {⟨*framemodel*⟩} {⟨*framecolor*⟩} {⟨*background tag*⟩} {⟨*height*⟩}

```
\NewDocumentCommand{\LWR@subfcolorminipage}{m m m m}{%
\LWR@stoppars%
\begin{BlockClass}[%
#3%
\LWR@borderpadding{#1}{#2} ; %
\IfValueT{#4}{height:\LWR@printlength{\LWR@tempheight} ; }%
width:\LWR@printlength{\LWR@tempwidth}%
]{fcolorminipage}%
}
```

Env fcolorminipage [⟨*1:framemodel*⟩] {⟨*2:framecolor*⟩} [⟨*3:boxmodel*⟩] {⟨*4:boxcolor*⟩} [⟨*5:align*⟩] [⟨*6:height*⟩] [⟨*7:inner-align*⟩] {⟨*8:width*⟩}

```
\NewDocumentEnvironment{LWR@HTML@fcolorminipage}{O{named} m O{named} m O{c} o o m}
{%
\LWR@FBcancel%
\setlength{\LWR@tempwidth}{#8}%
\IfValueT{#6}{\setlength{\LWR@tempheight}{#6}}%
\LWR@forceminwidth{\fboxrule}%
\convertcolorspec{#1}{#2}{HTML}\LWR@tempcolor%
\ifthenelse{\equal{#4}{none}}%
    {\LWR@subfcolorminipage{#1}{#2}{}{#6}}%
    {%
        \convertcolorspec{#3}{#4}{HTML}\LWR@tempcolortwo%
        \LWR@subfcolorminipage{#1}{#2}%
            {background:\LWR@origpound\LWR@tempcolortwo\ ; }%
            {#6}%
    }%
}%
{%
    \end{BlockClass}%
```

Prevent paragraph tags around horizontal white space until the start of the next paragraph:

```
    \global\booltrue{LWR@minipagethispar}%
}

\AtBeginDocument{
\LWR@formattedenv{fcolorminipage}
}
```

\boxframe {⟨*width*⟩} {⟨*height*⟩} {⟨*depth*⟩}

The depth is added to the height, but the box is not decended below by the depth. \textcolor is honored.

```
\newcommand*{\LWR@HTML@boxframe}[3]{%
{%
\setlength{\LWR@tempwidth}{#1}%
\setlength{\LWR@tempheight}{#2}%
\addtolength{\LWR@tempheight}{#3}%
\LWR@forceminwidth{\fboxrule}%
\LWR@findcurrenttextcolor%
\InlineClass[%
display:inline-block ; %
border:\LWR@printlength{\LWR@atleastonept} solid \LWR@currenttextcolor{} ; %
width:\LWR@printlength{\LWR@tempwidth} ; %
height:\LWR@printlength{\LWR@tempheight}%
]{boxframe}{}%
}%
}

\LWR@formatted{boxframe}
```

§ 512.8 Row colors

`\rowc@l@rs` `[⟨cmds⟩] {⟨startrow⟩} {⟨odd color⟩} {⟨even color⟩}`

```
\newcommand*{\LWR@xcolortempcolor}{}

\def\rowc@l@rs[#1]#2#3#4%
{
\global\rownum=1
   \global\@rowcolorstrue
   \@ifxempty{#3}%
     {\def\@oddrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#3}{HTML}\LWR@xcolortempcolor%
        \edef\@oddrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
     }%
   \@ifxempty{#4}%
     {\def\@evenrowcolor{\@norowcolor}}%
     {%
        \convertcolorspec{named}{#4}{HTML}\LWR@xcolortempcolor%
        \edef\@evenrowcolor{%
            \csdef{LWR@xcolorrowHTMLcolor}{\LWR@xcolortempcolor}%
        }%
     }%
   \if@rowcmd
     \def\@rowcolors
     {%
%          #1%
        \if@rowcolors
%         \noalign{%
            \relax\ifnum\rownum<#2\@norowcolor\else
            \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi\fi%
%          }%
        \fi%
     }%
   \else
```

```
    \def\@rowcolors
    {%
       \if@rowcolors
           \ifnum\rownum<#2%
            \noalign{%
               \@norowcolor
            }
           \else
            #1%
            \noalign{%
               \ifodd\rownum\@oddrowcolor\else\@evenrowcolor\fi%
            }%
           \fi
       \fi%
     }%
   \fi
   \ignorespaces%
}
```

`\@norowcolor` Turns off color for this row.

```
\def\@norowcolor{%
\renewcommand{\LWR@xcolorrowHTMLcolor}{}%
}
```

`\@rowc@lors` Executed at the end of each row.

```
\def\@rowc@lors{%
%   \noalign{%
        \global\advance\rownum\@ne%
%   }%
    \@rowcolors%
}

\end{warpHTML}
```

File 415 **lwarp-xechangebar.sty**

§ 513 Package xechangebar

Pkg xechangebar xechangebar is ignored

for HTML output:

```
\LWR@ProvidesPackageDrop{xechangebar}[2017/08/03]
\LWR@origRequirePackage{lwarp-changebar}
```

File 416 **lwarp-xellipsis.sty**

§ 514 Package xellipsis

(*Emulates or patches code by* Donald P. Goodman III.)

Pkg xellipsis xellipsis is patched for use by lwarp.

When non-zero, each of the spaces is converted to an HTML thin unbreakable space.

for HTML output:

```
\LWR@ProvidesPackagePass{xellipsis}[2015/11/01]

\newcommand*{\LWR@xellipsespace}[1]{%
\ifdim#1=0pt\else%
    \ifdim#1<\fontdimen2\font%
        \,%
    \else%
        ~%
    \fi%
\fi%
}

\def\xelip{%
\mbox{%
    \LWR@xellipsespace{\xelipprebef}%
    \xelipprechar%
    \LWR@xellipsespace{\xelippreaft}%
    \LWR@xellipsespace{\xelipbef}%
    \xelipchar%
    \xel@loopi = 1%
    \loop\ifnum\xelipnum>\xel@loopi%
        \advance\xel@loopi by1%
        \LWR@xellipsespace{\xelipgap}%
        \xelipchar%
    \repeat%
    \LWR@xellipsespace{\xelipaft}%
    \LWR@xellipsespace{\xelippostbef}%
    \xelippostchar%
    \LWR@xellipsespace{\xelippostaft}%
}%
}%
```

File 417 **lwarp-xetexko-vertical.sty**

§ 515 Package

xetexko-vertical

(*Emulates or patches code by* Dohyun Kim.)

Pkg xetexko-vertical xetexko-vertical is patched for use by lwarp.

for HTML output:

```
\LWR@loadbefore{xetexko-vertical}

\LWR@ProvidesPackagePass{xetexko-vertical}[2018/04/06]

\renewcommand{\verticaltypesetting}{}
\renewenvironment{vertical}[1]{\BlockClass{verticalrl}}{\endBlockClass}
\renewenvironment{horizontal}[1]{\BlockClass{horizontaltb}}{\endBlockClass}
\renewcommand{\vertlatin}[1]{#1}
```

File 418 **lwarp-xfakebold.sty**

§ 516 Package xfakebold

(*Emulates or patches code by* Herbert Voss.)

Pkg xfakebold xfakebold is patched for use by lwarp, and additional underlying support is found in the lwarp core.

⚠ page breaks Note that the print version resets to unbold at each page break, whereas the HTML version maintains the bold state until it is undone.

for HTML output:

```
\LWR@ProvidesPackagePass{xfakebold}[2018/07/25]

\let\LWR@orig@setBold\setBold
\let\LWR@orig@unsetBold\unsetBold
\renewcommand*{\setBold}{\booltrue{LWR@xfakebold}}
\renewcommand*{\unsetBold}{\boolfalse{LWR@xfakebold}}

\renewcommand*{\LWR@applyxfakebold}{%
    \ifbool{LWR@xfakebold}{\LWR@orig@setBold}{\LWR@orig@unsetBold}%
}
```

File 419 **lwarp-xfrac.sty**

§ 517 Package xfrac

(*Emulates or patches code by* The LaTeX3 Project.)

Pkg xfrac Supported by adding xfrac instances.

for HTML output:

```
\LWR@ProvidesPackagePass{xfrac}[2018-08-23]
```

⚠ font size In the user's document preamble, lwarp should be loaded after font-related setup. During HTML conversion, this font is used by lwarp to generate its initial PDF output containing HTML tags, later to be converted by *pdftotext* to a plain text file. While the text may be in any font which *pdftotext* can read, the math is directly converted into SVG images using this same user-selected font. xfrac below is set for the Latin Modern (lmr) font. If another font is used, it may be desirable to redefine \xfracHTMLfontsize with a different em size.

\sfrac [⟨*instance*⟩] {⟨*num*⟩} [⟨*sep*⟩] {⟨*denom*⟩}

A text-mode instance for the default font is provided below. The numerator and denominator formats are adjusted to encase everything in HTML tags. \scalebox is made null inside the numerator and denominator, since the HTML tags should not be scaled, and we do not want to introduce additional HTML tags for scaling.

In math mode, which will appear inside a `lateximage`, no adjustments are necessary.

for HTML & PRINT:

```
\begin{warpall}
```

`\xfracHTMLfontsize` User-redefinable macro which controls the font size of the fraction.

```
\newcommand*{\xfracHTMLfontsize}{.6em}
```

```
\end{warpall}
```

for HTML output:

```
\begin{warpHTML}
```

instances Instances of xfrac for various font choices:

Produce css for a small raised numerator and a small denominator.

Scaling is turned off so that *pdftotext* correctly reads the result.

```
\DeclareInstance{xfrac}{default}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmr}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmss}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}

\DeclareInstance{xfrac}{lmtt}{text}{
    numerator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{numerator}{#1}\,%
        \endgroup%
    },
    denominator-format = {%
        \begingroup%
        \RenewDocumentCommand{\scalebox}{m o m}{##3}%
        \InlineClass{denominator}{#1}%
        \endgroup%
    },
```

For *pdftotext*, do not scale the text:

```
    scaling = false
}


\end{warpHTML}
```

File 420 **lwarp-xltabular.sty**

§ 518 Package

xltabular

(*Emulates or patches code by* Rolf Niepraschk, Herbert Voss.)

Pkg xltabular xltabular is emulated by lwarp.

for HTML output: Relies on tabularx.

⚠ table numbering At present, an `xltabular` without a caption or with only a `\caption*` may be misnumbered in HTML, so it may be necessary to place at the end of the table:

```
\warpHTMLonly{\addtocounter{table}{-1}}
```

```
\RequirePackage{tabularx}

\LWR@ProvidesPackageDrop{xltabular}[2018/05/23]

\DeclareDocumentEnvironment{xltabular}{o m m}
{\longtable{#3}}
{\endlongtable}
```

File 421 **lwarp-xltxtra.sty**

§ 519 Package xltxtra

(*Emulates or patches code by* Will Robertson, Jonathan Kew.)

Pkg xltxtra xltxtra is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xltxtra}[2016/01/21]

\RequirePackage{realscripts}
\RequirePackage{metalogo}
\newcommand*\TeX@logo@spacing[6]{}

\newcommand*{\vfrac}[2]{%
\textsuperscript{#1}/\textsubscript{#2}%
}

\newcommand\namedglyph[1]{%
  \@tempcnta=\XeTeXglyphindex "#1"\relax
  \ifnum\@tempcnta>0
    \XeTeXglyph\@tempcnta
  \else
    \xxt@namedglyph@fallback{#1}%
  \fi}

\newcommand\xxt@namedglyph@fallback[1]{[#1]}

\DeclareDocumentCommand{\showhyphens}{m}{}
```

File 422 **lwarp-xmpincl.sty**

§ 520 Package xmpincl

(*Emulates or patches code by* Maarten Sneep.)

Pkg xmpincl xmpincl is ignored.

for HTML output: Discard all options for lwarp-xmpincl:

```
\LWR@ProvidesPackageDrop{xmpincl}[2008/05/10]
\newcommand*{\includexmp}[1]{}
```

File 423 **lwarp-xpiano.sty**

§ 521 Package xpiano

(*Emulates or patches code by* Enrico Gregorio.)

Pkg xpiano xpiano is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{xpiano}
\ExplSyntaxOn
\NewDocumentCommand{\LWR@print@keyboard}{ O{}m }
{
\xpiano_keyboard:nn { #1 } { #2 }
}

\NewDocumentCommand{\LWR@HTML@keyboard}{ O{}m }
{
\begin{lateximage}*
    [(-xpiano-~\packagediagramname{}: \detokenize\expandafter{#2})]
    [\detokenize\expandafter{#1}]
\xpiano_keyboard:nn { #1 } { #2 }
\end{lateximage}
}
\ExplSyntaxOff

\LWR@formatted{keyboard}
```

File 424 **lwarp-xpinyin.sty**

§ 522 Package xpinyin

(*Emulates or patches code by* Soben Lee.)

Pkg xpinyin xpinyin is partly supported. `\xpinyin` and `pinyinscope` are nullified, but `\pinyin` works.

for HTML output:

```
\LWR@ProvidesPackagePass{xpinyin}[2018/01/28]
\RenewDocumentEnvironment{pinyinscope}{O{}}{}{}

```

```
\RenewDocumentCommand{\xpinyin}{s O{} m}{%
    \IfBooleanTF{#1}{#3}{\@firstoftwo#3}%
}

\RenewDocumentCommand{\enablepinyin}{}{}
```

File 425 **lwarp-xr.sty**

§ 523 Package xr

(*Emulates or patches code by* Jean-Pierre Drucbert, David Carlisle.)

Pkg xr xr is patched for use by lwarp.

for HTML output: lwarp-xr-hyper also uses lwarp-xr to reuse the following definition. Only load xr if xr-hyper has not been loaded:

```
\ifdef{\externaldocument}{}{
    \LWR@ProvidesPackagePass{xr}[2019/01/05]
}

\LetLtxMacro\LWR@orig@externaldocument\externaldocument

\renewcommand*{\externaldocument}[2][]{%
    \ifblank{#1}{%
        \LWR@orig@externaldocument{#2_html}%
    }{%
        \LWR@orig@externaldocument[#1]{#2_html}%
    }%
}
```

File 426 **lwarp-xr-hyper.sty**

§ 524 Package xr-hyper

(*Emulates or patches code by* David Carlisle.)

Pkg xr-hyper xr-hyper is patched for use by lwarp.

for HTML output:

```
\LWR@ProvidesPackagePass{xr-hyper}[2000/03/22]

\LWR@origRequirePackage{lwarp-xr}
```

File 427 **lwarp-xtab.sty**

§ 525 Package xtab

(*Emulates or patches code by* Peter Wilson.)

Pkg xtab xtab is emulated.

for HTML output:

```
\LWR@ProvidesPackageDrop{xtab}[2011/07/31]
```

⚠ Misplaced alignment tab character &

For \tablefirsthead, etc., enclose them as follows:

```
\StartDefiningTabulars
\tablefirsthead
. . .
\StopDefiningTabulars
```

See section 8.10.1.

⚠ lateximage supertabular and xtab are not supported inside a lateximage.

```
\newcommand{\LWRXT@firsthead}{}

\newcommand{\tablefirsthead}[1]{%
    \long\gdef\LWRXT@firsthead{#1}%
}

\newcommand{\tablehead}[1]{}

\newcommand{\tablelasthead}[1]{}

\newcommand{\notablelasthead}{}

\newcommand{\tabletail}[1]{}

\newcommand{\LWRXT@lasttail}{}

\newcommand{\tablelasttail}[1]{%
    \long\gdef\LWRXT@lasttail{#1}%
}


\newcommand{\tablecaption}[2][]{%
    \long\gdef\LWRXT@caption{%
        \ifblank{#1}%
            {\caption{#2}}%
            {\caption[#1]{#2}}%
    }%
}

\let\topcaption\tablecaption
\let\bottomcaption\tablecaption


\newcommand*{\LWRXT@caption}{}

\newcommand*{\shrinkheight}[1]{}

\newcommand*{\xentrystretch}[1]{}

\NewDocumentEnvironment{xtabular}{s o m}
{%
\LWR@traceinfo{xtabular}%
```

```
\table%
\LWRXT@caption%
\begin{tabular}{#3}%
\TabularMacro\ifdefvoid{\LWRXT@firsthead}%
{\LWR@getmynexttoken}%
{\expandafter\LWR@getmynexttoken\LWRXT@firsthead}%
}%
{%
\ifdefvoid{\LWRXT@lasttail}%
{}%
{%
\TabularMacro\ResumeTabular%
\LWRXT@lasttail%
}%
\end{tabular}%
\endtable%


\gdef\LWRXT@caption{}%


\LWR@traceinfo{xtabular done}%
}

\NewDocumentEnvironment{mpxtabular}{s o m}
{\minipage{\linewidth}\xtabular{#3}}
{\endxtabular\endminipage}
```

File 428 **lwarp-xunicode.sty**

§ 526 Package

xunicode

Pkg xunicode

Error if xunicode is loaded after lwarp.

Patch lwarp-xunicode, but also verify that is was loaded before lwarp:

for HTML output:

```
\LWR@loadbefore{xunicode}%

\LWR@ProvidesPackagePass{xunicode}[2011/09/09]
```

`\textcircled` becomes a span with a rounded border. `\providecommand` is used to avoid conflict with textcomp.

```
\providecommand*{\LWR@HTML@textcircled}[1]{%
    \InlineClass[border: 1px solid \LWR@currenttextcolor]{textcircled}{#1}%
}

\LWR@formatted{textcircled}
```

Nullify xunicode macros when generating filenames:

```
\FilenameNullify{%
    \renewcommand*{\textdegree}{}%
```

```
    \renewcommand*{\textcelsius}{}%
    \renewcommand*{\textohm}{}%
    \renewcommand*{\textmu}{}%
    \renewcommand*{\textlquill}{}%
    \renewcommand*{\textrquill}{}%
    \renewcommand*{\textcircledP}{}%
    \renewcommand*{\texttwelveudash}{}%
    \renewcommand*{\textthreequartersemdash}{}%
    \renewcommand*{\textmho}{}%
    \renewcommand*{\textnaira}{}%
    \renewcommand*{\textpeso}{}%
    \renewcommand*{\textrecipe}{}%
    \renewcommand*{\textinterrobang}{}%
    \renewcommand*{\textinterrobangdown}{}%
    \renewcommand*{\textperthousand}{}%
    \renewcommand*{\textpertenthousand}{}%
    \renewcommand*{\textbaht}{}%
    \renewcommand*{\textdiscount}{}%
    \renewcommand*{\textservicemark}{}%
    \renewcommand*{\textcircled}[1]{#1}%
    \renewcommand*{\capitalcedilla}[1]{#1}%
    \renewcommand*{\capitalogonek}[1]{#1}%
    \renewcommand*{\capitalgrave}[1]{#1}%
    \renewcommand*{\capitalacute}[1]{#1}%
    \renewcommand*{\capitalcircumflex}[1]{#1}%
    \renewcommand*{\capitaltilde}[1]{#1}%
    \renewcommand*{\capitaldieresis}[1]{#1}%
    \renewcommand*{\capitalhungarumlaut}[1]{#1}%
    \renewcommand*{\capitalring}[1]{#1}%
    \renewcommand*{\capitalcaron}[1]{#1}%
    \renewcommand*{\capitalbreve}[1]{#1}%
    \renewcommand*{\capitalmacron}[1]{#1}%
    \renewcommand*{\capitaldotaccent}[1]{#1}%
}% FilenameNullify
```

File 429 **lwarp-xurl.sty**

§ 527 Package xurl

Pkg xurl xurl is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{xurl}[2018/06/02]
```

File 430 **lwarp-xy.sty**

§ 528 Package xy

(*Emulates or patches code by* Kristoffer H. Rose, Ross Moore.)

Pkg xy xy is patched for use by lwarp.

⚠ \xypolygon \xypolygon must be used inside the xy environment, or inside \xy ...\endxy.

for HTML output:

```
\LWR@ProvidesPackagePass{xy}[2013/10/06]

\AtBeginDocument{

\preto{\xy}{\begin{lateximage}[(-xy-~\packagediagramname)]}
\appto{\endxy}{\end{lateximage}}

\@ifundefined{xymatrix}{}{
\LetLtxMacro\LWR@origxymatrix\xymatrix

\renewcommand{\xymatrix}[1]{%
\begin{lateximage}[(-xy- xymatrix \packagediagramname)]
\LWR@origxymatrix{#1}
\end{lateximage}
}
}

\@ifundefined{xygraph}{}{
\LetLtxMacro\LWR@origxygraph\xygraph

\renewcommand{\xygraph}[1]{%
\begin{lateximage}[(-xy- xygraph \packagediagramname)]
\LWR@origxygraph{#1}
\end{lateximage}
}
}

}
```

File 431 **lwarp-zhlineskip.sty**

§ 529 Package zhlineskip

Pkg zhlineskip zhlineskip is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{zhlineskip}[2019/05/15]

\newcommand*\SetTextEnvironmentSinglespace[1]{}
\newcommand*\RestoreTextEnvironmentLeading[1]{}
\newcommand*\SetMathEnvironmentSinglespace[1]{}
\newcommand*\RestoreMathEnvironmentLeading[1]{}
```

File 432 **lwarp-zwpagelayout.sty**

§ 530 Package zwpagelayout

(*Emulates or patches code by* Zdeněk Wagner.)

Pkg zwpagelayout zwpagelayout is ignored.

for HTML output:

```
\LWR@ProvidesPackageDrop{zwpagelayout}[2013/01/13]

\def\noBboxes{}
\@onlypreamble\noBboxes

\expandafter\ifx\csname definecolor\endcsname\relax \else
  \definecolor{cmykblack}{cmyk}{0,0,0,1}
  \definecolor{grblack}{gray}{0}
%   \ifzwpl@redefineblack
%     \definecolor{black}{cmyk}{0,0,0,1}\color{black}
%   \fi
  \definecolor{cmykred}{cmyk}{0,1,1,0}
  \definecolor{cmykgreen}{cmyk}{1,0,1,0}
  \definecolor{cmykblue}{cmyk}{1,1,0,0}
  \definecolor{rgbred}{rgb}{1,0,0}
  \definecolor{rgbgreen}{rgb}{0,1,0}
  \definecolor{rgbblue}{rgb}{0,0,1}
%   \ifzwpl@redefinetocmyk
%     \definecolor{red}{cmyk}{0,1,1,0}
%     \definecolor{green}{cmyk}{1,0,1,0}
%     \definecolor{blue}{cmyk}{1,1,0,0}
%   \fi
\fi

\let\OverprintXeTeXExtGState\relax

\DeclareRobustCommand\SetOverprint{\ignorespaces}
\DeclareRobustCommand\SetKnockout{\ignorespaces}
\DeclareRobustCommand\textoverprint[1]{{\SetOverprint#1}}
\DeclareRobustCommand\textknockout[1]{{\SetKnockout#1}}

\def\SetPDFminorversion#1{}
\@onlypreamble\SetPDFminorversion

\newcommand*\Vcorr{}

\DeclareRobustCommand\vb[1][]{}
\NewDocumentCommand{\NewOddPage}{* o}{}
\NewDocumentCommand{\NewEvenPage}{* o}{}
\def\SetOddPageMessage#{\gdef\ZW@oddwarning}
\def\SetEvenPageMessage#{\gdef\Z@@evenwarning}
\def\ZW@oddwarning{Empty page inserted}\let\ZW@evenwarning\ZW@oddwarning

\def\clap#1{#1}

\def\CropFlap{2in}
\def\CropSpine{1in}
\def\CropXSpine{1in}
\def\CropXtrim{.25in}
\def\CropYtrim{.25in}
\def\UserWidth{5in}
\def\UserLeftMargin{1in}
\def\UserRightMargin{1in}
```

```
\def\UserTopMargin{1in}
\def\UserBotMargin{1in}
\def\thePageNumber{\LWR@origpound\,\arabic{page}}
\ifXeTeX
\def\ifcaseZWdriver{\ifcase2}
\else
\def\ifcaseZWdriver{\ifcase1}
\fi
\DeclareRobustCommand\ZWifdriver[2]{}
```

File 433 **lwarp-patch-komascript.sty**

§ 531 Package

patch-komascript

Pkg lwarp-patch-komascript

Patches for komascript classes.

lwarp loads this package when scrbook, scrartcl, or scrreprt classes are detected.

Many features are ignored during the HTML conversion. The goal is source-level compatibility.

\titlehead, \subject, \captionformat, \figureformat, and \tableformat are not yet emulated.

⚠ Not fully tested! Please send bug reports!

Some features have not yet been tested. Please contact the author with any bug reports.

for HTML output:

```
\ProvidesPackage{lwarp-patch-komascript}
```

typearea is emulated.

```
\RequirePackage{lwarp-typearea}
```

tocbasic is emulated.

```
\RequirePackage{lwarp-tocbasic}
```

scrextend patches most of the new macros.

```
\RequirePackage{lwarp-scrextend}
```

Indexing macros, simplified for lwarp:

```
\AtBeginDocument{

\renewcommand*{\idx@heading}{%
  \idx@@heading{\indexname}%
}

```

```
\renewenvironment{theindex}{%
  \idx@heading%
  \index@preamble\par\nobreak
    \let\item\LWR@indexitem%
    \let\subitem\LWR@indexsubitem%
    \let\subsubitem\LWR@indexsubsubitem%
}
{}

\renewcommand*\indexspace{}

}% AtBeginDocument
```

The `\minisec` is placed inside a `<div>` of class `minisec`.

```
\renewcommand*{\minisec}[1]{
\begin{BlockClass}{minisec}
#1
\end{BlockClass}
}
```

The part and chapter preambles are placed as plain text just after each heading.

```
\@ifundefined{setpartpreamble}{}{
\RenewDocumentCommand{\setpartpreamble}{o o +m}{%
\renewcommand{\part@preamble}{#3}%
}
}

\@ifundefined{setchapterpreamble}{}{
\RenewDocumentCommand{\setchapterpreamble}{o o +m}{%
\renewcommand{\chapter@preamble}{#3}%
}
}
```

Simple captions are used in all cases.

```
\LetLtxMacro\captionbelow\caption
\LetLtxMacro\captionabove\caption

\LetLtxMacro\captionofbelow\captionof
\LetLtxMacro\captionofabove\captionof

\RenewDocumentEnvironment{captionbeside}{o m o o o s}
{}
{%
\IfValueTF{#1}%
{\caption[#1]{#2}}%
{\caption{#2}}%
}

\RenewDocumentEnvironment{captionofbeside}{m o m o o o s}
{}
{%
\IfValueTF{#2}%
```

```
{\captionof{#1}[#2]{#3}}%
{\captionof{#1}{#3}}%
}

\RenewDocumentCommand{\setcapindent}{s m}{}
\renewcommand*{\setcaphanging}{}
\renewcommand*{\setcapwidth}[2][]{}
\renewcommand*{\setcapdynwidth}[2][]{}
\RenewDocumentCommand{\setcapmargin}{s o m}{}
```

File 434 **lwarp-patch-memoir.sty**

§ 532 Package

patch-memoir

(*Emulates or patches code by* Peter Wilson.)

Pkg lwarp-patch-memoir

Patches for memoir class.

⚠ Not fully tested!

Please send bug reports!

lwarp loads this package when the memoir class is detected.

⚠ options clash

While emulating memoir, lwarp pre-loads a number of packages (section 532.1). This can cause an options clash when the user's document later loads the same packages with options. To fix this problem, specify the options before loading lwarp:

```
\documentclass{memoir}
. . .
\PassOptionsToPackage{options_list}{package_name}
. . .
\usepackage{lwarp}
. . .
\usepackage{package_name}
```

⚠ version numbers

memoir emulates a number of packages, and declares a version date for each which often does not match the date of the corresponding freestanding package. This can cause warnings about incorrect version numbers. Since lwarp is intended to support the freestanding packages, which are often newer than the date declared by memoir, it is hoped that memoir will update and change its emulated version numbers to match.

`\verbfootnote` is not supported.

`\newfootnoteseries`, etc. are not supported.

lwarp loads pagenote to perform memoir's pagenote functions, but there are minor differences in `\pagenotesubhead` and related macros.

Poem numbering is not supported.

The `verbatim` environment does not yet support the memoir enhancements. It is currently recommended to load and use fancyvrb instead.

The memoir glossary system is not yet supported by *lwarpmk*. The glossaries package may be used instead, but does require the glossary entries be changed from the memoir syntax to the glossaries syntax.

for HTML output:

```
\ProvidesPackage{lwarp-patch-memoir}
```

§ 532.1 Packages

These are pre-loaded to provide emulation for many of memoir's functions. memoir pretends that abstract, etc. are already loaded, via its "emulated" package mechanism, but lwarp is directly loading the "`lwarp-`" version of each, which happens to avoid memoir's emulation system.

```
\RequirePackage{lwarp-abstract}% req'd
\RequirePackage{lwarp-array}% req'd
\RequirePackage{lwarp-booktabs}% req'd
% \RequirePackage{lwarp-ccaption}% emualated below
\RequirePackage{lwarp-changepage}% req'd
\RequirePackage{lwarp-crop}
\RequirePackage{lwarp-dcolumn}% req'd
\RequirePackage{lwarp-enumerate}% req'd
\RequirePackage{lwarp-epigraph}% req'd
\RequirePackage{lwarp-fancyvrb}% req'd
\RequirePackage{lwarp-footmisc}% req'd
\RequirePackage{lwarp-framed}% req'd
\RequirePackage{lwarp-hanging}% req'd
\RequirePackage{lwarp-makeidx}% req'd
\DisemulatePackage{moreverb}
\RequirePackage{lwarp-moreverb}
\RequirePackage{lwarp-mparhack}
\RequirePackage{lwarp-needspace}% req'd
\RequirePackage{lwarp-nextpage}% req'd
\RequirePackage{lwarp-pagenote}% req'd
\RequirePackage{lwarp-parskip}
\RequirePackage{lwarp-setspace}% req'd
\RequirePackage{lwarp-showidx}
\RequirePackage{lwarp-subfigure}% red'q
\makeindex
```

subfigure is emulated via subfig, which pre-defines `subfigure` and `subtable`, but memoir does not, so they must be tested for here:

```
\LetLtxMacro\LWR@memorignewsubfloat\newsubfloat
\RenewDocumentCommand{\newsubfloat}{O{} m}{%
    \@ifundefined{c@sub#2}{%
        \LWR@memorignewsubfloat[#1]{#2}%
    }{}%
}

\RequirePackage{lwarp-tabularx}% req'd
\RequirePackage{lwarp-titling}% req'd
% \RequirePackage{lwarp-tocbibind}% not emulated by memoir
\RequirePackage{lwarp-tocloft}% req'd
\RequirePackage{lwarp-verse}% req'd
```

§ 532.2 Preliminary setup

Bypass the memoir package mechanism:

```
\LetLtxMacro\LWR@orig@label\@mem@old@label
```

memoir already set the page size to a default, so it must be forced large for lwarp's use, to avoid tag overflows off the page.

```
\setstocksize{190in}{20in}
\setlrmarginsandblock{2in}{2in}{*}
\setulmarginsandblock{1in}{1in}{*}
```

§ 532.3 Laying out the page

```
\renewcommand*{\stockavi}{}
\renewcommand*{\stockav}{}
\renewcommand*{\stockaiv}{}
\renewcommand*{\stockaiii}{}
\renewcommand*{\stockbvi}{}
\renewcommand*{\stockbv}{}
\renewcommand*{\stockbiv}{}
\renewcommand*{\stockbiii}{}
% \renewcommand*{\stockmetriccrownvo}{}% in docs but not in the package
\renewcommand*{\stockmlargecrownvo}{}
\renewcommand*{\stockmdemyvo}{}
\renewcommand*{\stockmsmallroyalvo}{}
\renewcommand*{\pageavi}{}
\renewcommand*{\pageav}{}
\renewcommand*{\pageaiv}{}
\renewcommand*{\pageaiii}{}
\renewcommand*{\pagebvi}{}
\renewcommand*{\pagebv}{}
\renewcommand*{\pagebiv}{}
\renewcommand*{\pagebiii}{}
% \renewcommand*{\pagemetriccrownvo}{}% in docs but not in the package
\renewcommand*{\pagemlargecrownvo}{}
\renewcommand*{\pagemdemyvo}{}
\renewcommand*{\pagemsmallroyalvo}{}

\renewcommand*{\stockdbill}{}
\renewcommand*{\stockstatement}{}
\renewcommand*{\stockexecutive}{}
\renewcommand*{\stockletter}{}
\renewcommand*{\stockold}{}
\renewcommand*{\stocklegal}{}
\renewcommand*{\stockledger}{}
\renewcommand*{\stockbroadsheet}{}
\renewcommand*{\pagedbill}{}
\renewcommand*{\pagestatement}{}
\renewcommand*{\pageexecutive}{}
\renewcommand*{\pageletter}{}
\renewcommand*{\pageold}{}
\renewcommand*{\pagelegal}{}
\renewcommand*{\pageledger}{}
```

```
\renewcommand*{\pagebroadsheet}{}

\renewcommand*{\stockpottvo}{}
\renewcommand*{\stockfoolscapvo}{}
\renewcommand*{\stockcrownvo}{}
\renewcommand*{\stockpostvo}{}
\renewcommand*{\stocklargecrownvo}{}
\renewcommand*{\stocklargepostvo}{}
\renewcommand*{\stocksmalldemyvo}{}
\renewcommand*{\stockdemyvo}{}
\renewcommand*{\stockmediumvo}{}
\renewcommand*{\stocksmallroyalvo}{}
\renewcommand*{\stockroyalvo}{}
\renewcommand*{\stocksuperroyalvo}{}
\renewcommand*{\stockimperialvo}{}
\renewcommand*{\pagepottvo}{}
\renewcommand*{\pagefoolscapvo}{}
\renewcommand*{\pagecrownvo}{}
\renewcommand*{\pagepostvo}{}
\renewcommand*{\pagelargecrownvo}{}
\renewcommand*{\pagelargepostvo}{}
\renewcommand*{\pagesmalldemyvo}{}
\renewcommand*{\pagedemyvo}{}
\renewcommand*{\pagemediumvo}{}
\renewcommand*{\pagesmallroyalvo}{}
\renewcommand*{\pageroyalvo}{}
\renewcommand*{\pagesuperroyalvo}{}
\renewcommand*{\pageimperialvo}{}

\renewcommand*{\memfontfamily}{}
\renewcommand*{\memfontenc}{}
\renewcommand*{\memfontpack}{}

\renewcommand*{\anyptfilebase}{}
\renewcommand*{\anyptsize}{10}

\renewcommand*{\setstocksize}[2]{}
\renewcommand*{\settrimmedsize}[3]{}
\renewcommand*{\settrims}[2]{}

% \newlength{\lxvchars}
% \setlength{\lxvchars}{305pt}
% \newlength{\xlvchars}
% \setlength{\xlvchars}{190pt}
\renewcommand*{\setxlvchars}[1]{}
\renewcommand*{\setlxvchars}[1]{}

\renewcommand*{\settypeblocksize}[3]{}
\renewcommand*{\setlrmargins}[3]{}
\renewcommand*{\setlrmarginsandblock}[3]{}
\renewcommand*{\setbinding}[1]{}
\renewcommand*{\setulmargins}[3]{}
\renewcommand*{\setulmarginsandblock}[3]{}
\renewcommand*{\setcolsepandrule}[2]{}

```

```
\renewcommand*{\setheadfoot}[2]{}
\renewcommand*{\setheaderspaces}[3]{}
\renewcommand*{\setmarginnotes}[3]{}
\renewcommand*{\setfootins}[2]{}
\renewcommand*{\checkandfixthelayout}[1][]{}
\renewcommand*{\checkthelayout}[1]{}
\renewcommand*{\fixthelayout}{}
%
% \newlength{\stockheight}
% \newlength{\trimtop}
% \newlength{\trimedge}
% \newlength{\stockwidth}
% \newlength{\spinemargin}
% \newlength{\foremargin}
% \newlength{\uppermargin}
% \newlength{\headmargin}
%
\renewcommand*{\typeoutlayout}{}
\renewcommand*{\typeoutstandardlayout}{}
\renewcommand*{\settypeoutlayoutunit}[1]{}
\renewcommand*{\fixpdflayout}{}
\renewcommand*{\fixdvipslayout}{}

\renewcommand*{\medievalpage}[1][]{}
\renewcommand*{\isopage}[1][]{}
\renewcommand*{\semiisopage}[1][]{}

\renewcommand{\setpagebl}[3]{}
\renewcommand{\setpageml}[3]{}
\renewcommand{\setpagetl}[3]{}
\renewcommand{\setpagetm}[3]{}
\renewcommand{\setpagetr}[3]{}
\renewcommand{\setpagemr}[3]{}
\renewcommand{\setpagebr}[3]{}
\renewcommand{\setpagebm}[3]{}
\renewcommand{\setpagecc}[3]{}
```

§ 532.4 Text and fonts

```
\let\miniscule\tiny
\let\HUGE\Huge

\renewcommand*{\abnormalparskip}[1]{}
\renewcommand*{\nonzeroparskip}{}
\renewcommand*{\traditionalparskip}{}

\let\onelineskip\baselineskip

\let\OnehalfSpacing\onehalfspacing
\let\DoubleSpacing\doublespacing
\renewcommand*{\setPagenoteSpacing}[1]{}
\renewcommand*{\setFloatSpacing}[1]{}
\let\SingleSpacing\singlespacing
\let\setSingleSpace\SetSinglespace
\let\SingleSpace\singlespace
```

```
\let\endSingleSpace\endsinglespace
\let\Spacing\spacing
\let\endSpacing\endspacing
\let\OnehalfSpace\onehalfspace
\let\endOnehalfSpace\endonehalfspace
\csletcs{OnehalfSpace*}{onehalfspace}
\csletcs{endOnehalfSpace*}{endonehalfspace}
\let\DoubleSpace\doublespace
\let\endDoubleSpace\enddoublespace
\csletcs{DoubleSpace*}{doublespace}
\csletcs{endDoubleSpace*}{enddoublespace}
\renewcommand*{\setDisplayskipStretch}[1]{}
\renewcommand*{\memdskipstretch}{}
\renewcommand*{\noDisplayskipStretch}{}
\renewcommand*{\memdskips}{}

\renewcommand*{\midsloppy}{}
\renewenvironment*{midsloppypar}{}{}

\renewcommand*{\sloppybottom}{}
```

§ 532.5 Titles

```
\csletcs{titlingpage*}{titlingpage}
\csletcs{endtitlingpage*}{endtitlingpage}
\let\titlingpageend\relax
\newcommand{\titlingpageend}[2]{}
\let\andnext\and
\renewcommand*{\thanksmarkstyle}[1]{}
\renewcommand{\thanksfootmark}{%
\thanksscript{\tamark}%
}

% \newlength{\thanksmarksep}
```

§ 532.6 Abstracts

```
\renewcommand*{\abstractcol}{}
\renewcommand*{\abstractintoc}{}
\renewcommand*{\abstractnum}{}
\renewcommand*{\abstractrunin}{}
```

§ 532.7 Docment divisions

```

\def\@apppage{%
    \part*{\appendixpagename}
}
\renewcommand\mempreaddapppagetotochook{}
\renewcommand\mempostaddapppagetotochook{}

\def\@sapppage{%
    \part*{\appendixpagename}
}

```

```
\csletcs{frontmatter*}{frontmatter}
\csletcs{mainmatter*}{mainmatter}
\renewcommand*{\raggedbottomsection}{}
\renewcommand*{\normalbottomsection}{}
\renewcommand*{\bottomsectionskip}{}
\renewcommand*{\bottomsectionpenalty}{}
\csletcs{appendixpage*}{appendixpage}
\renewcommand*{\namedsubappendices}{}
\renewcommand*{\unnamedsubappendices}{}
\renewcommand*{\setsecnumdepth}[1]{}% todo tocvsec2
\renewcommand*{\maxsecnumdepth}[1]{}% todo tocvsec2
\renewcommand*{\beforebookskip}{}
\renewcommand*{\afterbookskip}{}
\renewcommand*{\beforepartskip}{}
\renewcommand*{\afterpartskip}{}
\renewcommand*{\midbookskip}{}
\renewcommand*{\midpartskip}{}
\renewcommand*{\printbookname}{}
\renewcommand*{\booknamefont}{}
\renewcommand*{\booknamenum}{}
\renewcommand*{\printbooknum}{}
\renewcommand*{\booknumfont}{}
\renewcommand*{\printpartname}{}
\renewcommand*{\partnamefont}{}
\renewcommand*{\partnamenum}{}
\renewcommand*{\printpartnum}{}
\renewcommand*{\partnumfont}{}
\renewcommand*{\printbooktitle}[1]{}
\renewcommand*{\booktitlefont}{}
\renewcommand{\printparttitle}[1]{}
\renewcommand*{\parttitlefont}{}
\renewcommand*{\bookpageend}{}
\renewcommand*{\bookblankpage}{}
\renewcommand*{\nobookblankpage}{}
\renewcommand*{\partpageend}{}
\renewcommand*{\partblankpage}{}
\renewcommand*{\nopartblankpage}{}
\RenewDocumentCommand{\newleadpage}{s o m m}{}% todo
\RenewDocumentCommand{\renewleadpage}{s o m m}{}% todo
\renewcommand*{\leadpagetoclevel}{chapter}

\renewcommand*{\openright}{}
\renewcommand*{\openleft}{}
\renewcommand*{\openany}{}
\renewcommand*{\clearforchapter}{}
\renewcommand*{\memendofchapterhook}{}
\renewcommand*{\chapterheadstart}{}
% \newlength{\beforechapskip}
\renewcommand*{\afterchapternum}{}
% \newlength{\midchapskip}
\renewcommand*{\afterchaptertitle}{}
% \newlength{\afterchapskip}
\renewcommand*{\printchaptername}{}
\renewcommand*{\chapnamefont}{}
\renewcommand*{\chapternamenum}{}
```

```
\renewcommand*{\printchapternum}{}
\renewcommand*{\chapnumfont}{}
\renewcommand{\printchaptertitle}[1]{}
\renewcommand*{\chaptitlefont}{}
\renewcommand*{\printchapternonum}{}
\renewcommand*{\indentafterchapter}{}
\renewcommand*{\noindentafterchapter}{}
\renewcommand*{\insertchapterspace}{}

\renewcommand*{\chapterstyle}[1]{}
\renewcommand{\makechapterstyle}[2]{}
\renewcommand*{\chapindent}{}
\let\chapterprecis\cftchapterprecis
\let\chapterprecishere\cftchapterprecishere
\let\chapterprecistoc\cftchapterprecistoc
\renewcommand*{\precisfont}{}
\renewcommand*{\prechapterprecis}{}
\renewcommand*{\postchapterprecis}{}
\renewcommand{\precistoctext}[1]{}
\renewcommand*{\precistocfont}{}
\renewcommand*{\precistocformat}{}
% \newlength{\prechapterprecisshift}

\renewcommand*{\setbeforesecskip}[1]{}
\renewcommand*{\setaftersecskip}[1]{}
\renewcommand*{\setsecindent}[1]{}
\renewcommand*{\setsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsecskip}[1]{}
\renewcommand*{\setaftersubsecskip}[1]{}
\renewcommand*{\setsubsecindent}[1]{}
\renewcommand*{\setsubsecheadstyle}[1]{}
\renewcommand*{\setbeforesubsubsecskip}[1]{}
\renewcommand*{\setaftersubsubsecskip}[1]{}
\renewcommand*{\setsubsubsecindent}[1]{}
\renewcommand*{\setsubsubsecheadstyle}[1]{}
\renewcommand*{\setbeforeparaskip}[1]{}
\renewcommand*{\setafterparaskip}[1]{}
\renewcommand*{\setparaindent}[1]{}
\renewcommand*{\setparaheadstyle}[1]{}
\renewcommand*{\setbeforesubparaskip}[1]{}
\renewcommand*{\setaftersubparaskip}[1]{}
\renewcommand*{\setsubparaindent}[1]{}
\renewcommand*{\setsubparaheadstyle}[1]{}
\renewcommand{\@hangfrom}[1]{#1}
\renewcommand{\sethangfrom}[1]{}
\renewcommand{\setsecnumformat}[1]{}

\renewcommand*{\hangsecnum}{}
\renewcommand*{\defaultsecnum}{}

\renewcommand*{\sechook}{}
\renewcommand{\setsechook}[1]{}
\renewcommand*{\subsechook}{}
\renewcommand{\setsubsechook}[1]{}
\renewcommand*{\subsubsechook}{}
```

```
\renewcommand{\setsubsubsechook}[1]{}
\renewcommand*{\parahook}{}
\renewcommand{\setparahook}[1]{}
\renewcommand*{\subparahook}{}
\renewcommand{\setsubparahook}[1]{}

\RenewDocumentCommand{\plainbreak}{s m}{\begin{center}~\end{center}}

\RenewDocumentCommand{\fancybreak}{s +m}{%
\begin{center}#2\end{center}%
}

\RenewDocumentCommand{\plainfancybreak}{s m m +m}{%
\begin{center}#4\end{center}%
}

\RenewDocumentCommand{\pfbreak}{s}{%
\begin{center}
\pfbreakdisplay
\end{center}
}

% \newlength{\pfbreakskip}
\renewcommand{\pfbreakdisplay}{*\quad*\quad*}

\renewcommand{\makeheadstyles}[2]{}
\renewcommand*{\headstyles}[1]{}
```

§ 532.8 Pagination and headers

```
\renewcommand*{\savepagenumber}{}
\renewcommand*{\restorepagenumber}{}
\renewcommand*{\uppercaseheads}{}
\renewcommand*{\nouppercaseheads}{}

\renewcommand*{\bookpagemark}[1]{}
\renewcommand*{\partmark}[1]{}
\renewcommand*{\bibmark}{}
\renewcommand*{\indexmark}{}
\renewcommand*{\glossarymark}{}

\LWR@origpagestyle{empty}
\renewcommand*{\ps@empty}{}
\renewcommand*{\makepagestyle}[1]{}
\renewcommand*{\emptypshook}{}%
% \renewcommand*{\empty@oddhead}{}
% \renewcommand*{\empty@oddfoot}{}
% \renewcommand*{\empty@evenhead}{}
% \renewcommand*{\empty@evenfoot}{}
\renewcommand*{\@oddhead}{}
\renewcommand*{\@oddfoot}{}
\renewcommand*{\@evenhead}{}
\renewcommand*{\@evenfoot}{}
\renewcommand*{\aliaspagestyle}[2]{}
\renewcommand*{\copypagestyle}[2]{}
```

```
\renewcommand*{\makeevenhead}[4]{}
\renewcommand*{\makeoddhead}[4]{}
\renewcommand*{\makeevenfoot}[4]{}
\renewcommand*{\makeoddfoot}[4]{}
\renewcommand*{\makerunningwidth}[3]{}
% \newlength{\headwidth}
\renewcommand*{\makeheadrule}[3]{}
\renewcommand*{\makefootrule}[3]{}
\renewcommand*{\makeheadfootruleprefix}[3]{}
% \newlength{\normalrulethickness}
% \setlength{\normalrulethickness}{.4pt}
% \newlength{\footruleheight}
% \newlength{\footruleskip}
\renewcommand*{\makeheadposition}[5]{}
\renewcommand{\makepsmarks}[2]{}
\renewcommand*{\makeheadfootstrut}[3]{}

\renewcommand{\createplainmark}[3]{}
\renewcommand{\memUChead}[1]{}
\renewcommand{\createmark}[5]{}
\renewcommand*{\clearplainmark}[1]{}
\renewcommand*{\clearmark}[1]{}
\renewcommand{\addtopsmarks}[3]{}
\renewcommand{\ifonlyfloats}[2]{#2}
\renewcommand*{\mergepagefloatstyle}[3]{}

\renewcommand*{\framepichead}{}
\renewcommand*{\framepictextfoot}{}
\renewcommand*{\framepichook}{}
\renewcommand*{\showheadfootlocoff}{}
\renewcommand*{\showtextblocklocoff}{}
```

§ 532.9 Paragraphs and lists

```
\renewcommand{\hangfrom}[1]{#1}
\let\centerfloat\centering
\renewcommand*{\raggedyright}[1][]{}
% \newlength{\ragrparindent}
\renewcommand{\sourceatright}[2][]{\attribution{#2}}
\let\memorigdbs\LWR@endofline
\let\memorigpar\par
\let\atcentercr\LWR@endofline

\renewcommand*{\linenottooshort}[1][]{}
\renewcommand*{\russianpar}{}
\renewcommand*{\lastlinerulefill}{}
\renewcommand*{\lastlineparrule}{}
\renewcommand*{\justlastraggedleft}{}
\renewcommand*{\raggedrightthenleft}{}
\renewcommand*{\leftcenterright}{}

\renewcommand{\leftspringright}[4]{%
\begin{minipage}{#1\linewidth}#3\end{minipage}\qquad%
\begin{minipage}{#2\linewidth}\begin{flushright}#4\end{flushright}\end{minipage}%
```

```
}

\renewenvironment*{blockdescription}
{\LWR@descriptionstart\LWR@origdescription}
{\enddescription}
\renewcommand*{\blockdescriptionlabel}[1]{\textbf{#1}}
\renewenvironment*{labelled}[1]{\begin{description}}{\end{description}}
\renewenvironment*{flexlabelled}[6]{\begin{description}}{\end{description}}
\renewcommand*{\tightlists}{}
\renewcommand*{\defaultlists}{}
\RenewDocumentCommand{\firmlists}{s}{}
\renewcommand*{\firmlist}{}
\renewcommand*{\tightlist}{}
\renewcommand*{\zerotrivseps}{}
\renewcommand*{\savetrivseps}{}
\renewcommand*{\restoretrivseps}{}
```

§ 532.10 Contents lists

```
\csletcs{tableofcontents*}{tableofcontents}
\csletcs{listoffigures*}{listoffigures}
\csletcs{listoftables*}{listoftables}
\renewenvironment{KeepFromToc}{}{}
\renewcommand*{\onecoltocetc}{}
\renewcommand*{\twocoltocetc}{}
\renewcommand*{\ensureonecol}{}
\renewcommand*{\restorefromonecol}{}
\renewcommand*{\doccoltocetc}{}
\renewcommand*{\maxtocdepth}[1]{}% tocvsec2
\renewcommand*{\settocdepth}[1]{}% tocvsec2

\renewcommand{\tocheadstart}{}
\renewcommand{\printtoctitle}[1]{}
\renewcommand{\tocmark}{}
\renewcommand{\aftertoctitle}{}
\renewcommand{\lofheadstart}{}
\renewcommand{\printloftitle}[1]{}
\renewcommand{\lofmark}{}
\renewcommand{\afterloftitle}{}
\renewcommand{\lotheadstart}{}
\renewcommand{\printlottitle}[1]{}
\renewcommand{\lotmark}{}
\renewcommand{\afterlottitle}{}

\renewcommand*{\setpnumwidth}[1]{}
\renewcommand*{\setrmarg}[1]{}
\renewcommand*{\cftbookbreak}{}
\renewcommand*{\cftpartbreak}{}
\renewcommand*{\cftchapterbreak}{}

% \newlength{\cftbeforebookskip}
% \newlength{\cftbookindent}
% \newlength{\cftbooknumwidth}
\renewcommand*{\cftbookfont}{}
\renewcommand*{\cftbookname}{}
```

```
\renewcommand*{\cftbookpresnum}{}
\renewcommand*{\cftbookaftersnum}{}
\renewcommand*{\cftbookaftersnumb}{}
\renewcommand*{\cftbookleader}{}
\renewcommand*{\cftbookdotsep}{1}
\renewcommand*{\cftbookpagefont}{}
\renewcommand*{\cftbookafterpnum}{}
\renewcommand*{\cftbookformatpnum}[1]{}
\renewcommand*{\cftbookformatpnumhook}[1]{}
```

Part is already defined by tocloft.

```
% \newlength{\cftbeforechapterskip}
% \newlength{\cftchapterindent}
% \newlength{\cftchapternumwidth}
\renewcommand*{\cftchapterfont}{}
\renewcommand*{\cftchaptername}{}
\renewcommand*{\cftchapterpresnum}{}
\renewcommand*{\cftchapteraftersnum}{}
\renewcommand*{\cftchapteraftersnumb}{}
\renewcommand*{\cftchapterleader}{}
\renewcommand*{\cftchapterdotsep}{1}
\renewcommand*{\cftchapterpagefont}{}
\renewcommand*{\cftchapterafterpnum}{}
\renewcommand*{\cftchapterformatpnum}[1]{}
\renewcommand*{\cftchapterformatpnumhook}[1]{}
```

```
% \newlength{\cftbeforesectionskip}
% \newlength{\cftsectionindent}
% \newlength{\cftsectionnumwidth}
\renewcommand*{\cftsectionfont}{}
\renewcommand*{\cftsectionname}{}
\renewcommand*{\cftsectionpresnum}{}
\renewcommand*{\cftsectionaftersnum}{}
\renewcommand*{\cftsectionaftersnumb}{}
\renewcommand*{\cftsectionleader}{}
\renewcommand*{\cftsectiondotsep}{1}
\renewcommand*{\cftsectionpagefont}{}
\renewcommand*{\cftsectionafterpnum}{}
\renewcommand*{\cftsectionformatpnum}[1]{}
\renewcommand*{\cftsectionformatpnumhook}[1]{}
```

```
% \newlength{\cftbeforesubsectionskip}
% \newlength{\cftsubsectionindent}
% \newlength{\cftsubsectionnumwidth}
\renewcommand*{\cftsubsectionfont}{}
\renewcommand*{\cftsubsectionname}{}
\renewcommand*{\cftsubsectionpresnum}{}
\renewcommand*{\cftsubsectionaftersnum}{}
\renewcommand*{\cftsubsectionaftersnumb}{}
\renewcommand*{\cftsubsectionleader}{}
\renewcommand*{\cftsubsectiondotsep}{1}
\renewcommand*{\cftsubsectionpagefont}{}
\renewcommand*{\cftsubsectionafterpnum}{}
\renewcommand*{\cftsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsectionformatpnumhook}[1]{}
```

```
% \newlength{\cftbeforesubsubsectionskip}
% \newlength{\cftsubsubsectionindent}
% \newlength{\cftsubsubsectionnumwidth}
\renewcommand*{\cftsubsubsectionfont}{}
\renewcommand*{\cftsubsubsectionname}{}
\renewcommand*{\cftsubsubsectionpresnum}{}
\renewcommand*{\cftsubsubsectionaftersnum}{}
\renewcommand*{\cftsubsubsectionaftersnumb}{}
\renewcommand*{\cftsubsubsectionleader}{}
\renewcommand*{\cftsubsubsectiondotsep}{1}
\renewcommand*{\cftsubsubsectionpagefont}{}
\renewcommand*{\cftsubsubsectionafterpnum}{}
\renewcommand*{\cftsubsubsectionformatpnum}[1]{}
\renewcommand*{\cftsubsubsectionformatpnumhook}[1]{}

% \newlength{\cftbeforeparagraphskip}
% \newlength{\cftparagraphindent}
% \newlength{\cftparagraphnumwidth}
\renewcommand*{\cftparagraphfont}{}
\renewcommand*{\cftparagraphname}{}
\renewcommand*{\cftparagraphpresnum}{}
\renewcommand*{\cftparagraphaftersnum}{}
\renewcommand*{\cftparagraphaftersnumb}{}
\renewcommand*{\cftparagraphleader}{}
\renewcommand*{\cftparagraphdotsep}{1}
\renewcommand*{\cftparagraphpagefont}{}
\renewcommand*{\cftparagraphafterpnum}{}
\renewcommand*{\cftparagraphformatpnum}[1]{}
\renewcommand*{\cftparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforesubparagraphskip}
% \newlength{\cftsubparagraphindent}
% \newlength{\cftsubparagraphnumwidth}
\renewcommand*{\cftsubparagraphfont}{}
\renewcommand*{\cftsubparagraphname}{}
\renewcommand*{\cftsubparagraphpresnum}{}
\renewcommand*{\cftsubparagraphaftersnum}{}
\renewcommand*{\cftsubparagraphaftersnumb}{}
\renewcommand*{\cftsubparagraphleader}{}
\renewcommand*{\cftsubparagraphdotsep}{1}
\renewcommand*{\cftsubparagraphpagefont}{}
\renewcommand*{\cftsubparagraphafterpnum}{}
\renewcommand*{\cftsubparagraphformatpnum}[1]{}
\renewcommand*{\cftsubparagraphformatpnumhook}[1]{}

% \newlength{\cftbeforefigureskip}
% \newlength{\cftfigureindent}
% \newlength{\cftfigurenumwidth}
\renewcommand*{\cftfigurefont}{}
\renewcommand*{\cftfigurename}{}
\renewcommand*{\cftfigurepresnum}{}
\renewcommand*{\cftfigureaftersnum}{}
\renewcommand*{\cftfigureaftersnumb}{}
\renewcommand*{\cftfigureleader}{}
\renewcommand*{\cftfiguredotsep}{1}
\renewcommand*{\cftfigurepagefont}{}
```

```
\renewcommand*{\cftfigureafterpnum}{}
\renewcommand*{\cftfigureformatpnum}[1]{}
\renewcommand*{\cftfigureformatpnumhook}[1]{}

% \newlength{\cftbeforesubfigureskip}
% \newlength{\cftsubfigureindent}
% \newlength{\cftsubfigurenumwidth}
\newcommand*{\cftsubfigurefont}{}
\newcommand*{\cftsubfigurename}{}
\newcommand*{\cftsubfigurepresnum}{}
\newcommand*{\cftsubfigureaftersnum}{}
\newcommand*{\cftsubfigureaftersnumb}{}
\newcommand*{\cftsubfigureleader}{}
\newcommand*{\cftsubfiguredotsep}{1}
\newcommand*{\cftsubfigurepagefont}{}
\newcommand*{\cftsubfigureafterpnum}{}
\newcommand*{\cftsubfigureformatpnum}[1]{}
\newcommand*{\cftsubfigureformatpnumhook}[1]{}

% \newlength{\cftbeforetableskip}
% \newlength{\cfttableindent}
% \newlength{\cfttablenumwidth}
\renewcommand*{\cfttablefont}{}
\renewcommand*{\cfttablename}{}
\renewcommand*{\cfttablepresnum}{}
\renewcommand*{\cfttableaftersnum}{}
\renewcommand*{\cfttableaftersnumb}{}
\renewcommand*{\cfttableleader}{}
\renewcommand*{\cfttabledotsep}{1}
\renewcommand*{\cfttablepagefont}{}
\renewcommand*{\cfttableafterpnum}{}
\renewcommand*{\cfttableformatpnum}[1]{}
\renewcommand*{\cfttableformatpnumhook}[1]{}

% \newlength{\cftbeforesubtableskip}
% \newlength{\cftsubtableindent}
% \newlength{\cftsubtablenumwidth}
\newcommand*{\cftsubtablefont}{}
\newcommand*{\cftsubtablename}{}
\newcommand*{\cftsubtablepresnum}{}
\newcommand*{\cftsubtableaftersnum}{}
\newcommand*{\cftsubtableaftersnumb}{}
\newcommand*{\cftsubtableleader}{}
\newcommand*{\cftsubtabledotsep}{1}
\newcommand*{\cftsubtablepagefont}{}
\newcommand*{\cftsubtableafterpnum}{}
\newcommand*{\cftsubtableformatpnum}[1]{}
\newcommand*{\cftsubtableformatpnumhook}[1]{}

\renewcommand*{\booknumberline}[1]{}
\renewcommand*{\partnumberline}[1]{}
\renewcommand*{\chapternumberline}[1]{}
\renewcommand*{\numberlinehook}[1]{}
% \renewcommand*{\cftwhatismyname}{}%
\renewcommand*{\booknumberlinehook}[1]{}
\renewcommand*{\partnumberlinehook}[1]{}
```

```
\renewcommand*{\chapternumberlinehook}[1]{}
\renewcommand{\numberlinebox}[2]{}
\renewcommand{\booknumberlinebox}[2]{}
\renewcommand{\partnumberlinebox}[2]{}
\renewcommand{\chapternumberlinebox}[2]{}
%
% \newlength{\cftparfillskip}
\renewcommand*{\cftpagenumbersoff}[1]{}
\renewcommand*{\cftpagenumberson}[1]{}
\renewcommand*{\cftlocalchange}[3]{}
\renewcommand*{\cftaddtitleline}[4]{}
\renewcommand*{\cftaddnumtitleline}[4]{}
\renewcommand{\cftinsertcode}[2]{}
\renewcommand{\cftinserthook}[2]{}
\renewcommand{\settocpreprocessor}[2]{}
\DeclareRobustCommand{\cftpagenumbersoff}[1]{}
\DeclareRobustCommand{\cftpagenumberson}[1]{}
```

§ 532.11 Floats and captions

\newfloat [⟨*1: within*⟩] {⟨*2: type*⟩} {⟨*3: ext*⟩} {⟨*4: capname*⟩}

```
\RenewDocumentCommand{\newfloat}{o m m m}{%
\IfValueTF{#1}%
{\DeclareFloatingEnvironment[fileext=#3,within=#1,name={#4}]{#2}}%
{\DeclareFloatingEnvironment[fileext=#3,name={#4}]{#2}}%
```

newfloat package automatically creates the \listof command for new floats, but float does not, so remove \listof here in case it is manually created later.

```
\cslet{listof#2s}\relax%
\cslet{listof#2es}\relax%
}
```

\newlistof [⟨*within*⟩] {⟨*type*⟩} {⟨*ext*⟩} {⟨*listofname*⟩}

Emulated through the \newfloat mechanism. Note that memoir uses a different syntax than tocloft for the name.

```
\RenewDocumentCommand{\newlistof}{o m m m}
{%
\IfValueTF{#1}
{\newlistentry[#1]{#2}{#3}{0}}
{\newlistentry{#2}{#3}{0}}
\@namedef{ext@#2}{#3}%
\@ifundefined{c@#3depth}{\newcounter{#3depth}}{}%
\setcounter{#3depth}{1}%
\@namedef{#3mark}{}%
\@namedef{#2}{\listof{#2}{#4}}
\@namedef{@cftmake#3title}{}
\@ifundefined{cftbefore#3titleskip}{
    \expandafter\newlength\csname cftbefore#3titleskip\endcsname
    \expandafter\newlength\csname cftafter#3titleskip\endcsname
}{}
\@namedef{cft#3titlefont}{}
\@namedef{cftafter#3title}{}
\@namedef{cft#3prehook}{}
```

```
\@namedef{cft#3posthook}{}
}

\renewcommand{\setfloatadjustment}[2]{}
```

Borrowed from the lwarp version of keyfloat:

```
\NewDocumentEnvironment{KFLTmemoir@marginfloat}{O{-1.2ex} m}
{% start
\LWR@BlockClassWP{float:right; width:2in; margin:10pt}{}{marginblock}%
\captionsetup{type=#2}%
}
{%
\endLWR@BlockClassWP%
}

\DeclareDocumentEnvironment{marginfigure}{o}
  {\begin{KFLTmemoir@marginfloat}{figure}}
  {\end{KFLTmemoir@marginfloat}}

\DeclareDocumentEnvironment{margintable}{o}
  {\begin{KFLTmemoir@marginfloat}{table}}
  {\end{KFLTmemoir@marginfloat}}

\renewcommand{\setmarginfloatcaptionadjustment}[2]{}
\renewcommand{\setmpjustification}[2]{}
\renewcommand*{\mpjustification}{}
\renewcommand*{\setfloatlocations}[2]{}
\DeclareDocumentCommand{\suppressfloats}{o}{}
\renewcommand*{\FloatBlock}{}
\renewcommand*{\FloatBlockAllowAbove}{}
\renewcommand*{\FloatBlockAllowBelow}{}
\renewcommand*{\setFloatBlockFor}{}

\renewcommand{\captiontitlefinal}[1]{}

\renewcommand{\flegtable}{\tablename}
\renewcommand{\flegfigure}{\figurename}
\renewcommand{\flegtoctable}{}
\renewcommand{\flegtocfigure}{}


\renewcommand{\subcaption}[2][]{%
\ifblank{#1}{\subfloat[#2]{}}{\subfloat[#1][#2]{}}%
}

\renewcommand{\contsubcaption}{\ContinuedFloat\subcaption}

\LetLtxMacro\subcaptionref\subref

\renewcommand*{\tightsubcaptions}{}
\renewcommand*{\loosesubcaptions}{}

\renewcommand*{\subcaptionsize}[1]{}
\renewcommand*{\subcaptionlabelfont}[1]{}
```

```
\renewcommand*{\subcaptionfont}[1]{}
\renewcommand*{\subcaptionstyle}[1]{}

\renewcommand*{\hangsubcaption}{}
\renewcommand*{\shortsubcaption}{}
\renewcommand*{\normalsubcaption}{}

\RenewDocumentEnvironment{sidecaption}{o m o}
{}
{
\IfValueTF{#1}{\caption[#1]{#2}}{\caption{#2}}%
\IfValueT{#3}{\label{#3}}%
}

% \newlength{\sidecapwidth}
% \newlength{\sidecapsep}
\renewcommand*{\setsidecaps}[2]{}
\renewcommand*{\sidecapmargin}[1]{}
% \newif\ifscapmargleft
\scapmargleftfalse
\renewcommand*{\setsidecappos}[1]{}

\RenewDocumentEnvironment{sidecontcaption}{m o}
{}
{%
\ContinuedFloat%
\caption{#1}%
```

Without \@captype, the section is referred to instead.

```
\IfValueT{#2}{\label[\@captype]{#2}}%
}
```

\sidenamedlegend does not appear to use the TOC argument.

```
\renewenvironment{sidenamedlegend}[2][]{
\begin{center}
\@nameuse{\@captype name}\CaptionSeparator#2
\end{center}
}
{}

\renewenvironment{sidelegend}[1]
{\begin{center}
#1

}
{\end{center}}

\renewcommand*{\sidecapstyle}{}
\renewcommand*{\overridescapmargin}[1]{}
% \newlength{\sidecapraise}
\renewcommand*{\sidecapfloatwidth}{\linewidth}

\LetLtxMacro\ctabular\tabular
```

```
\LetLtxMacro\endctabular\endtabular

\renewcommand{\autorows}[5][]{%
#5
}

\renewcommand{\autocols}[5][]{%
#5
}
```

§ 532.12 Page notes

```
\renewcommand*{\feetabovefloat}{}
\renewcommand*{\feetbelowfloat}{}
\renewcommand*{\feetatbottom}{}

\renewcommand*{\verbfootnote}[2][]{
\PackageError{lwarp,memoir}
{Verbatim footnotes are not yet supported by lwarp.}
{This may be improved some day.}
}

\renewcommand*{\plainfootnotes}{}
\renewcommand*{\twocolumnfootnotes}{}
\renewcommand*{\threecolumnfootnotes}{}
\renewcommand*{\paragraphfootnotes}{}
\renewcommand*{\footfudgefiddle}{}

\renewcommand*{\newfootnoteseries}[1]{
\PackageError{lwarp,memoir}
{Memoir footnote series are not yet supported by lwarp.}
{This may be improved some day.}
}

\renewcommand*{\plainfootstyle}[1]{}
\renewcommand*{\twocolumnfootstyle}[1]{}
\renewcommand*{\threecolumnfootstyle}[1]{}
\renewcommand*{\paragraphfootstyle}[1]{}

\renewcommand*{\footfootmark}{}
\renewcommand*{\footmarkstyle}[1]{}

% \newlength{\footmarkwidth}
% \newlength{\footmarksep}
% \newlength{\footparindent}

\renewcommand*{\foottextfont}{}

\renewcommand*{\marginparmargin}[1]{}
\renewcommand*{\sideparmargin}[1]{}

\LetLtxMacro\sidepar\marginpar
\renewcommand*{\sideparfont}{}
\renewcommand*{\sideparform}{}
\LWR@providelength{\sideparvshift}
```

```
\renewcommand*{\parnopar}{}

\renewcommand{\sidebar}[1]{\begin{quote}#1\end{quote}}
\renewcommand*{\sidebarmargin}[1]{}
\renewcommand*{\sidebarfont}{}
\renewcommand*{\sidebarform}{}
% \newlength{\sidebarhsep}
% \newlength{\sidebarvsep}
% \newlength{\sidebarwidth}
% \newlength{\sidebartopsep}
\renewcommand{\setsidebarheight}[1]{}
\renewcommand*{\setsidebars}[6]{}
\renewcommand*{\footnotesatfoot}{}
\renewcommand*{\footnotesinmargin}{}

\LetLtxMacro\sidefootnote\footnote
\LetLtxMacro\sidefootnotemark\footnotemark
\LetLtxMacro\sidefootnotetext\footnotetext

\renewcommand*{\sidefootmargin}[1]{}
% \newlength{\sidefoothsep}
% \newlength{\sidefootvsep}
% \newlength{\sidefootwidth}
% \newlength{\sidefootadjust}
% \newlength{\sidefootheight}
\renewcommand*{\setsidefootheight}[1]{}
% \renewcommand*{\sidefootfont}{}% in docs but not in the package
\renewcommand*{\setsidefeet}[6]{}
\renewcommand*{\sidefootmarkstyle}[1]{}
\renewcommand*{\sidefoottextfont}{}
\renewcommand*{\sidefootform}{}

\renewcommand*{\continuousnotenums}{\pncontopttrue}% from pagenote
\renewcommand*{\notepageref}{}
\renewcommand*{\prenotetext}{}
\renewcommand*{\postnotetext}{}
\renewcommand*{\idtextinnotes}[1]{}
\renewcommand*{\printpageinnotes}[1]{}
\renewcommand*{\printpageinnoteshyperref}[1]{}
\renewcommand*{\foottopagenote}{}
\renewcommand*{\pagetofootnote}{}
```

§ 532.13 Decorative text

```
\renewcommand*{\epigraphposition}[1]{}
\renewcommand*{\epigraphtextposition}[1]{}
\renewcommand*{\epigraphsourceposition}[1]{}
\renewcommand*{\epigraphfontsize}[1]{}
\renewcommand*{\epigraphforheader}[2][]{}
\renewcommand*{\epigraphpicture}{}
```

§ 532.14 Poetry

```
\renewcommand*{\vinphantom}{}
```

```
\renewcommand*{\vleftofline}[1]{#1}
% \let\linenumberfrequency\poemlines
% \renewcommand*{\linenumberfont}[1]{}

\DeclareDocumentCommand{\PoemTitle}{s o o m}{%
\IfValueTF{#2}%
{\poemtitle[#2]{#4}}%
{\poemtitle{#4}}%
}

\renewcommand*{\NumberPoemTitle}{}
\renewcommand*{\PlainPoemTitle}{}
\renewcommand*{\poemtitlepstyle}{}
\renewcommand*{\poemtitlestarmark}[1]{}
\renewcommand*{\poemtitlestarpstyle}{}
\renewcommand*{\PoemTitleheadstart}{}
\renewcommand*{\printPoemTitlenonum}{}
\renewcommand*{\printPoemTitlenum}{}
\renewcommand*{\afterPoemTitlenum}{}
\renewcommand*{\printPoemTitletitle}[1]{}
\renewcommand*{\afterPoemTitle}{}
\newlength{\midpoemtitleskip}
\renewcommand*{\PoemTitlenumfont}{}
\renewcommand*{\PoemTitlefont}{}
```

§ 532.15 Boxes, verbatims and files

```
\renewenvironment{qframe}{\framed}{\endframed}
\renewenvironment{qshade}{\shaded}{\endshaded}
```

Use the comment package:

```
\renewcommand*{\commentsoff}[1]{\includecomment{#1}}
\renewcommand*{\commentson}[1]{\excludecomment{#1}}
\LetLtxMacro\renewcomment\commentson

\renewcommand*{\setverbatimfont}[1]{}
\renewcommand*{\tabson}[1]{}
\renewcommand*{\tabsoff}{}
\renewcommand*{\wrappingon}{}
\renewcommand*{\wrappingoff}{}
\renewcommand*{\verbatimindent}{}
\renewcommand*{\verbatimbreakchar}[1]{}

\DefineVerbatimEnvironment{fboxverbatim}{Verbatim}{frame=single}
```

boxedverbatim is already defined by moreverb. boxedverbatim* does not appear to work at all, even in a minimal print memoir document.

```
\renewcommand*{\bvbox}{}
\renewcommand*{\bvtopandtail}{}
\renewcommand*{\bvsides}{}
\renewcommand*{\nobvbox}{}
% \newlength\bvboxsep
\renewcommand*{\bvtoprulehook}{}
```

```
\renewcommand*{\bvtopmidhook}{}
\renewcommand*{\bvendrulehook}{}
\renewcommand*{\bvleftsidehook}{}
\renewcommand*{\bvrightsidehook}{}
\renewcommand*{\bvperpagetrue}{}
\renewcommand*{\bvperpagefalse}{}
\renewcommand{\bvtopofpage}[1]{}
\renewcommand{\bvendofpage}[1]{}
\renewcommand*{\linenumberfrequency}[1]{}
\renewcommand*{\resetbvlinenumber}{}
\renewcommand*{\setbvlinenums}[2]{}
\renewcommand*{\linenumberfont}[1]{}
\renewcommand*{\bvnumbersinside}{}
\renewcommand*{\bvnumbersoutside}{}
```

§ 532.16 Cross referencing

```
\renewcommand*{\fref}[1]{\cref{#1}}
\renewcommand*{\tref}[1]{\cref{#1}}
\renewcommand*{\pref}[1]{\cpageref{#1}}
\renewcommand*{\Aref}[1]{\cref{#1}}
\renewcommand*{\Bref}[1]{\cref{#1}}
\renewcommand*{\Pref}[1]{\cref{#1}}
\renewcommand*{\Sref}[1]{\cref{#1}}
\renewcommand*{\figurerefname}{Figure}
\renewcommand*{\tablerefname}{Table}
\renewcommand*{\pagerefname}{page}
\renewcommand*{\bookrefname}{Book~}
\renewcommand*{\partrefname}{Part~}
\renewcommand*{\chapterrefname}{Chapter~}
\renewcommand*{\sectionrefname}{\S}
\renewcommand*{\appendixrefname}{Appendix~}
\LetLtxMacro\titleref\nameref
\renewcommand*{\headnameref}{}
\renewcommand*{\tocnameref}{}

\providecounter{LWR@currenttitle}

\renewcommand*{\currenttitle}{%
    \addtocounter{LWR@currenttitle}{1}%
    \label{currenttitle\arabic{LWR@currenttitle}}%
    \nameref{currenttitle\arabic{LWR@currenttitle}}%
}

\renewcommand*{\theTitleReference}[2]{}
\renewcommand*{\namerefon}{}
\renewcommand*{\namerefoff}{}
```

§ 532.17 Back matter

Redefined to write the LWR@autoindex counter instead of page. Note that memoir has two versions, depending on the use of hyperref.

```
\AtBeginDocument{

```

```
\def\@@wrindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
    {\string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}}%
    \endgroup
    \@esphack}%
```

\specialindex behaves like a regular \index, pointing to where \specialindex is used. If \specialindex is used inside a figure or table after the \caption, then the hyperlink will be given the name of that particular figure or table.

```
\def\@@wrspindexhyp#1||\\{%
    \addtocounter{LWR@autoindex}{1}%
    \LWR@new@label{LWRindex-\arabic{LWR@autoindex}}%
%     \ifshowindexmark\@showidx{#1}\fi
    \protected@write\@auxout{}%
    {%
%         \string\@@wrindexm@m{\@idxfile}{#1}{\@nameuse{the\@sptheidx}}%
        \string\@@wrindexm@m{\@idxfile}{#1}{\arabic{LWR@autoindex}}%
    }%
    \endgroup
    \@esphack}%

}% \AtBeginDocument
```

Patched to use _html filename and \BaseJobname:

```
\catcode`\_=12%
\renewcommand*{\makeindex}[1][\BaseJobname]{%
  \if@filesw
    \def\gindex{\@bsphack%
      \@ifnextchar [{\@index}{\@index[\BaseJobname]}}
    \def\specialindex{\@bsphack\@spindex}%
    \makememindexhook
    \expandafter\newwrite\csname #1@idxfile\endcsname
   \expandafter\immediate\openout \csname #1@idxfile\endcsname #1_html.idx\relax
    \typeout{Writing index file #1_html.idx }%
  \fi}
\catcode`\_=8%
```

Patched to use _html filename and \BaseJobname. This will later be patched by the lwarp core.

```
\catcode`\_=12%
\renewcommand{\printindex}[1][\BaseJobname]{\@input@{#1_html.ind}}
\catcode`\_=8%

\DeclareDocumentCommand{\newblock}{}{}
%
\renewcommand*{\showindexmarks}{}
\renewcommand*{\hideindexmarks}{}

\renewcommand*{\xindyindex}{}
```

§ 532.18 Miscellaneous

```
\renewcommand*{\changemarks}{}
\renewcommand*{\nochangemarks}{}
\renewcommand*{\added}[1]{}
\renewcommand*{\deleted}[1]{}
\renewcommand*{\changed}[1]{}

\renewcommand*{\showtrimsoff}{}
\renewcommand*{\showtrimson}{}
\renewcommand*{\trimXmarks}{}
\renewcommand*{\trimLmarks}{}
\renewcommand*{\trimFrame}{}
\renewcommand*{\trimNone}{}
\renewcommand*\trimmarkscolor{}
\renewcommand*{\trimmarks}{}
\renewcommand*{\tmarktl}{}
\renewcommand*{\tmarktr}{}
\renewcommand*{\tmarkbr}{}
\renewcommand*{\tmarkbl}{}
\renewcommand*{\tmarktm}{}
\renewcommand*{\tmarkmr}{}
\renewcommand*{\tmarkbm}{}
\renewcommand*{\tmarkml}{}
\renewcommand*{\trimmark}{}
\renewcommand*{\quarkmarks}{}
\renewcommand*{\registrationColour}[1]{}

\renewcommand*{\leavespergathering}[1]{}

\renewcommand*{\noprelistbreak}{}

\renewcommand*{\cleartorecto}{}
\renewcommand*{\cleartoverso}{}

\renewenvironment{vplace}[1][]{}{}
```

§ 532.19 ccaption emulation

```
\renewcommand*{\captiondelim}[1]{\renewcommand*{\CaptionSeparator}{#1}}
\renewcommand*{\captionnamefont}[1]{}
\renewcommand*{\captiontitlefont}[1]{}
\renewcommand*{\flushleftright}{}
\renewcommand*{\centerlastline}{}
\renewcommand*{\captionstyle}[2][]{}
\DeclareDocumentCommand{\captionwidth}{m}{}
\renewcommand*{\changecaptionwidth}{}
\renewcommand*{\normalcaptionwidth}{}
\renewcommand*{\hangcaption}{}
\renewcommand*{\indentcaption}[1]{}
\renewcommand*{\normalcaption}{}
\renewcommand{\precaption}[1]{}
\renewcommand{\postcaption}[1]{}
\renewcommand{\midbicaption}[1]{}
\renewcommand{\contcaption}[1]{%
```

```
% \ContinuedFloat%
% \caption{#1}%
\begin{LWR@figcaption}% later becomes \caption*
\LWR@isolate{\@nameuse{\@captype name}}~%
\thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#1}%
\end{LWR@figcaption}
}

\newlength{\abovelegendskip}
\setlength{\abovelegendskip}{0.5\baselineskip}
\newlength{\belowlegendskip}
\setlength{\belowlegendskip}{\abovelegendskip}
```

The extra \\ here forces a <br> in HTML when \legend is used in a \marginpar.

```
\renewcommand{\legend}[1]{\begin{center}#1\\\end{center}}

\renewcommand{\namedlegend}[2][]{
\begin{center}
\@nameuse{fleg\@captype}\CaptionSeparator#2\\
\end{center}
\@nameuse{flegtoc\@captype}{#1}
}

\renewcommand{\newfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\renewfixedcaption}[3][\caption]{%
  \renewcommand{#2}{\def\@captype{#3}#1}}
\renewcommand{\providefixedcaption}[3][\caption]{%
  \providecommand{#2}{\def\@captype{#3}#1}}

\renewcommand{\bitwonumcaption}[6][]{%
\ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
\addtocounter{\@captype}{-1}%
\begingroup%
\csdef{\@captype name}{#4}%
\ifblank{#5}{\caption{#6}}{\caption[#5]{#6}}%
\endgroup%
\ifblank{#1}{}{\label{#1}}%
}

\LetLtxMacro\bionenumcaption\bitwonumcaption% todo

\renewcommand{\bicaption}[5][]{%
\ifblank{#2}{\caption{#3}}{\caption[#2]{#3}}%
\begin{LWR@figcaption}% later becomes \caption*
\LWR@isolate{#4} \thechapter.\the\value{\@captype}\CaptionSeparator\LWR@isolate{#5}%
\end{LWR@figcaption}
\ifblank{#1}{}{\label{#1}}%
}

\renewcommand{\bicontcaption}[3]{%
\contcaption{#1}%
\begingroup%
\csdef{\@captype name}{#2}%
\contcaption{#3}%
```

```
\endgroup%
}

% only in ccaption, not in memoir:
% \LetLtxMacro\longbitwonumcaption\bitwonumcaption%
% \LetLtxMacro\longbionenumcaption\bitwonumcaption%
% \LetLtxMacro\longbicaption\bicaption%

\RenewDocumentCommand{\subtop}{O{} O{} m}{%
\subfloat[#1][#2]{#3}%
}

\RenewDocumentCommand{\subbottom}{O{} O{} m}{%
\subfloat[#1][#2]{#3}%
}

\renewcommand{\contsubtop}{%
\ContinuedFloat\addtocounter{\@captype}{1}%
\subtop}

\renewcommand{\contsubbottom}{%
\ContinuedFloat\addtocounter{\@captype}{1}%
\subbottom}

\renewcommand{\subconcluded}{}

\let\subfigure\subbottom
\let\subtable\subtop

\let\contsubtable\contsubtop
\let\contsubfigure\contsubbottom

\newcommand{\newfloatentry}[4][\@empty]{TODO: newfloatentry}
\newcommand{\newfloatlist}[5][\@empty]{TODO: newfloatlist}
\newcommand{\newfloatenv}[4][\@empty]{TODO: newfloatenv}
\DeclareRobustCommand{\newfloatpagesoff}[1]{}
\DeclareRobustCommand{\newfloatpageson}[1]{}
\newcommand{\setnewfloatindents}[3]{}
```

§ 532.20 Final patchwork

```
\newlistof{tableofcontents}{toc}{\contentsname}
\newlistof{listoffigures}{lof}{\listfigurename}
\newlistof{listoftables}{lot}{\listtablename}
```

File 435 **lwarp-common-multimedia.sty**

§ 533 Package common-multimedia

Pkg lwarp-common-multimedia

Common code for multimedia, movie15, and media9.

The packages multimedia, movie15, and media9 are supported.

HTML5 <audio> and <video> objects are created for .mp3 and .mp4 files.

HTML5 <embed> objects are created for http and ftp links.

\href links are created for other media types. (Unfortunately, there is not much overlap between the file types supported for print output and the file types supported by HTML5.)

For media9, a multimedia object is inserted for each addresource=, as well as each flashvars source= and src=. This may result in duplicate objects.

Undesired objects may be nullified by placing them inside \warpprintonly or the warpprint environment.

Each HTML multimedia object includes the poster text, except for <embed> objects. For movie15, the text option is supported to specify the poster text.

The width, height, and totalheight options are supported. The HTML object is scaled according to the display width, correctly compensating for either tall or wide viewports.

Other options are ignored.

media9 \addmediapath is supported. It is assumed that the same path structure will exist for the HTML document.

HTML5 media controls are always specified for each <audio> and <video> object.

media9 slideshows are not supported.

\hyperlinkmovie, \movieref, and \mediabutton are not supported.

3D objects are not supported.

If using a YouTube™ video, use an "embedded" URL with .../embed/... instead of .../v/...

for HTML output:

```
\ProvidesPackage{lwarp-common-multimedia}[2019/04/22]

\RequirePackage{xkeyval}

\define@key{LWR@multimedia}{width}{\setlength{\LWR@multimedia@width}{#1}}
\define@key{LWR@multimedia}{height}{\setlength{\LWR@multimedia@height}{#1}}
\define@key{LWR@multimedia}{totalheight}{\setlength{\LWR@multimedia@height}{#1}}

\newlength{\LWR@multimedia@width}
\newlength{\LWR@multimedia@height}
\newlength{\LWR@multimedia@maxdimension}
```

\LWR@multimedia@printsize

Proportional to \linewidth and the viewport's smaller dimension. This scales each object such that it will always fit on the screen, even if a tall or wide object inside a tall or wide viewport.

```
\newcommand*{\LWR@multimedia@printsize}{%
```

```
    \setlength{\LWR@multimedia@maxdimension}{%
        \maxof%
            {\linewidth}%
            {\maxof{\LWR@multimedia@width}{\LWR@multimedia@height}}%
    }%
    \setlength{\LWR@multimedia@maxdimension}{1.1\LWR@multimedia@maxdimension}%
    \ifdimgreater{\LWR@multimedia@width}{0pt}{%
        width:%
            \LWR@printpercentlength%
                {\LWR@multimedia@width}%
                {\LWR@multimedia@maxdimension}vmin ; % space
    }{}%
    \ifdimgreater{\LWR@multimedia@height}{0pt}{%
        height:%
            \LWR@printpercentlength%
                {\LWR@multimedia@height}%
                {\LWR@multimedia@maxdimension}vmin ; % space
    }{}%
}
```

\LWR@multimedia@fileAV {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates a video or audio from a file.

```
\newcommand*{\LWR@multimedia@fileAV}[4]{%
\filename@parse{#2}%
\IfFileExists{#2}{%
```

The container is sized as desired.

```
    \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
```

Paragraph tags are unnecessary for the A/V tags.

```
    \LWR@stoppars
```

The A/V element is 100% of the container.

```
    \LWR@htmltag{%
        #3\ % space
        width=\textquotedbl{}100\%\textquotedbl\ % space
        height=\textquotedbl{}100\%\textquotedbl\ % space
        controls%
    }\LWR@orignewline
```

The file source and type:

```
    \LWR@htmltag{%
        source % space
        src=\textquotedbl%
        \@filef@und\unskip\textquotedbl\ % space
        type=\textquotedbl{}#4\textquotedbl}
```

The poster text inside paragraph tags, along with a reference to the file.

```
    \LWR@startpars
    \href{\@filef@und}{#1}
    \LWR@stoppars
```

Finish.

```
    \LWR@htmltag{/#3}\LWR@orignewline
    \end{BlockClass}
}{%
    \PackageError{lwarp-common-multimedia}
    {File '#2' not found}
    {Perhaps an incorrect path?}
}%
}
```

`\LWR@multimedia@httpAV` {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates a video or audio from a URL link.

```
\newcommand*{\LWR@multimedia@httpAV}[4]{%
```

The container is sized as desired.

```
    \begin{BlockClass}[\LWR@multimedia@printsize\ margin:auto]{AVviewport}
```

Paragraph tags are unnecessary for the A/V tags.

```
    \LWR@stoppars
```

The A/V element is 100% of the container.

```
    \LWR@htmltag{%
        #3\ % space
        width=\textquotedbl{}100\%\textquotedbl\ % space
        height=\textquotedbl{}100\%\textquotedbl\ controls}\LWR@orignewline
```

The file source and type:

```
    \LWR@htmltag{%
        source % space
        src=\textquotedbl#2\textquotedbl\ % space
        type=\textquotedbl#4\textquotedbl}
```

The poster text inside paragraph tags, along with a reference to the URL.

```
    \LWR@startpars
    \href{#2}{#1}
    \LWR@stoppars
```

Finish.

```
    \LWR@htmltag{/#3}\LWR@orignewline
    \end{BlockClass}
}
```

`\LWR@multimedia@AV` {⟨*poster text*⟩} {⟨*filename*⟩} {⟨*audio/video*⟩} {⟨*mimetype*⟩}

Creates an audio or video from a file or a URL.

```
\newcommand*{\LWR@multimedia@AV}[4]{%
    \IfBeginWith{#2}{http}%
        {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
        {%
            \IfBeginWith{#2}{HTTP}%
                {\LWR@multimedia@httpAV{#1}{#2}{#3}{#4}}%
                {\LWR@multimedia@fileAV{#1}{#2}{#3}{#4}}%
        }%
}
```

\LWR@multimedia@embed {⟨*poster text*⟩} {⟨*URL or filename*⟩} {⟨*mime type*⟩}

Embeds multimedia of an arbitrary type. The poster text is not used, as it would appear along with the video if the <embed> element is supported.

```
\newcommand*{\LWR@multimedia@embed}[3]{%
    \begin{BlockClass}[width:100\%]{AVviewport}%
    \LWR@stoppars
        \LWR@htmltag{%
            embed % space
            \ifblank{#3}{}{type=\textquotedbl#3\textquotedbl\ }%
        style=\textquotedbl\LWR@multimedia@printsize\ margin:auto\textquotedbl\ % space
            src=\textquotedbl#2\textquotedbl\ % space
        }%
    \LWR@startpars
    \end{BlockClass}
}
```

\LWR@multimedia@percenterror

Error message if the comment character is used among the arguments of \LWR@multimediab.

```
\newcommand*{\LWR@multimedia@percenterror}{%
    \PackageError{lwarp-media9}
    {%
        Do not use a percent comment
        between\MessageBreak
        \protect\includemedia\space arguments%
    }
    {Percent is changed to a regular character to allow its use inside a URL.}
}
```

\LWR@multimediab [⟨*options*⟩] {⟨*poster text*⟩} {⟨*filename*⟩}

Creates multimedia. Examines the file extension to determine the type. If not a supported type, creates an embedded object if it has a URL. If neither, create a link to the unsupported object.

```
\newcommand*{\LWR@multimediab}[3][]{%
```

Error if the percent character appears among the arguments. This could happen since the comment character has been temporarily disabled, for use in a URL.

```
    \if#1\@percentchar\LWR@multimedia@percenterror\fi%
    \if#2\@percentchar\LWR@multimedia@percenterror\fi%
    \if#3\@percentchar\LWR@multimedia@percenterror\fi%
```

Record the desired size.

```
    \setlength{\LWR@multimedia@width}{0pt}%
    \setlength{\LWR@multimedia@height}{0pt}%
    \setkeys*{LWR@multimedia}{#1}%
```

If a known A/V type, create an HTML5 <video> or <audio>.

```
    \IfEndWith{#3}{.mp4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
    \IfEndWith{#3}{.MP4}{\LWR@multimedia@AV{#2}{#3}{video}{video/mp4}}{%
    \IfEndWith{#3}{.mp3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
    \IfEndWith{#3}{.MP3}{\LWR@multimedia@AV{#2}{#3}{audio}{audio/mpeg}}{%
```

If an arbitrary URL, embed it.

```
    \IfBeginWith{#3}{http}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{HTTP}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{ftp}{\LWR@multimedia@embed{#2}{#3}{}}{%
    \IfBeginWith{#3}{FTP}{\LWR@multimedia@embed{#2}{#3}{}}{%
```

If unknown, create a link to it.

```
        \href{#3}{#2}% unknown format
    }}}}}}}}%
    \endgroup%
}
```

Catcodes which may apper in a URL.

```
\newrobustcmd*{\LWR@multimedia}{%
    \begingroup%
    \catcode`\#=12%
    \catcode`\%=12%
    \catcode`\&=12%
    \catcode`\~=12%
    \catcode`\_=12%
    \LWR@multimediab%
}
```

Change History

§ 534 ## Chg Hist

For the most recent changes, see page 1056.

v0.10
General: 2016/03/08 Initial version . . 1
v0.11
General: 2016/03/11 1
Added section: Operating-System portability. 203
Added section: Selecting the operating system. 107
Test Suite: MS-WINDOWS in README.txt 1
Test Suite: limages and index in README.txt 1
v0.12
\LWR@newhtmlfile: Bugfix: TOC with numbered files. 348
General: 2016/03/14 1
Global: Uses \p@(type) in float captions. 1
Test Suite: Sub-figures 1
v0.13
\CaptionSeparator: Fix for newer babel package. 469
\LWR@LwarpStart: \up and \fup . . . 366
General: 2016/03/24 1
Fix dollar-redefined bug for newer package. 931
Removed package: subfig 1
Test Suite: Ordinals, Subcaption . . . 1
v0.14
\LWR@htmlsectionfilename: Fix: Links to home page. 309
General: 2016/03/31 1
floatrow: Added. 705
Docs: Commands for a successful HTML conversion. 111
Docs: Commands into a warpprint environment. 109
Docs: Newclude limitations. . . . 155
Docs: Table: Cross-referencing data structures. 455
Docs: Table: Float data structures. 465
Docs: Trademarks section. 182
Docs: Troubleshooting cross-references. 177
Test Suite: Assigned cleveref name for Test Float. 1
Test Suite: Floatrow 1
v0.15
General: 2016/04/06 1
Added. 710
Ampersand (&): Fixed handling when passed as an argument. . . 400
Docs: Added warning icons for items needing special attention. 185
Docs: Clarify print/HTML output. 108
Docs: Moved the supported features table to the introduction. 63
Files: lwarp_formal.css added. 1
Fix: steps counter 710
Fixed & handling. 708
Test Suite: test_suite_formal.css file added. 1
v0.16
General: 2016/04/11 1
\titlingpage: Improved print-output spacing. 374
xfrac: Adjusted for the use of any font: 987
Added XeLaTeX, LuaLaTeX support. 186
Docs: Font and UTF-8 support. . . 94
Docs: Moved location of \usepackage{lwarp}. 96
Docs: Text not converting. 177
Lwarp no longer selects fonts. 94, 212
Removed package: suffix 1
Test Suite: Improved titlingpage. 374
Test Suite: Lwarp no longer selects fonts. 1
Test Suite: Supports XeLaTeX, LuaLaTeX. 1
v0.17
\LWR@htmlsectionfilename: Fix: Links when entire doc is one HTML page. 309
General: 2016/04/14 1
mdframed: Added. 794

Test Suite: Fix: Print-version front-matter page numbers. 1
Test Suite: Mdframed 1
v0.18
\LWR@includegraphicsb: Add: svgz file extension. 733
em, ex, %, px dimensions preserved. 733
Fix: \linewidth, \textwidth, \textheight inside a minipage. 733
Improved HTML output linebreaks. 733
\LWR@myshorttoc: Reorganize \HomeHTMLFilename logic. 473
\LWR@newhtmlfile: sideTOC after title, improving responsive design. . . 347
\LWR@requesttoc: Reorganize \HomeHTMLFilename logic. 368
\LWR@subhyperref: Improved HTML output linebreaks. 462
\LWR@subhyperrefclass: Improved HTML output linebreaks. 462
\LWR@subinlineimage: Suppress extra space. 464
\hspace: \hspace supported. 562
General: 2016/05/19 1
File: lwarp.css: Improved TOC outline display. 1
Files: lwarp.css and lwarp_formal.css: Improved responsive design. 1
Microtype disabled during HTML generation 212
PDF Unicode input characters. . 200
Test Suite: Verse package 1
lateximage: pdfcrop: --hires added. 517
Reorganize \HomeHTMLFilename logic. 517
Suppress extra space. 517
verse: Supports verse, memoir packages. 966
minipage: Fix: \linewidth, \textwidth, \textheight inside a minipage. 538
v0.19
\HTMLFilename: Docs: Escape filename underscores. 309
\HomeHTMLFilename: Docs: Escape filename underscores. 309
\LWR@LwarpStart: Enabled \\ equal to \newline. 365
\LWR@doequation: MathJax support. 504
\LWR@doubledollar: MathJax support. 498
\LWR@filestart: lwarp_mathjax.txt loaded. 362
\LWR@minipagestartpars: Suppresses paragraph tags between minipages. 561
\LWR@subsingledollar: MathJax support. 493
\LateximageFontSizeName: Add: User-adjustable math/lateximage font size. 513
\hspace: Fix: \hspace length computations. 562
\minipagefullwidth: Added: No width tag for the next minipage in HTML. 537
\warpHTMLonly: Added. 211
\warpprintonly: Replaces \rowprintedonly. 211
\xfracHTMLfontsize: Added. 987
General: 2016/06/08 1
CSS for table note item. 928
MathJax support added. 501, 507, 509
multirow: Added optional args. . 818
Adapts to tikz version. 931
Avoids MathJax. 491
cleveref: Loaded \AtEndPreamble. 533
Docs: Math options. 96
Docs: Table: Cross-referencing data structures, updated. 455
File: lwarp.css: tnoteitemheader added. 1
File: lwarp_mathjax.txt added. . . 1
Introduction: MathJax support mentioned. 60
Options: mathsvg and mathjax . 206
Supports colored \rule. 977
titleps: null \pagestyle and \thispagestyle for HTML. 932
v0.20
\BlockClassSingle: Renamed from "LWR@htmldivclassline". 322
\HTMLDescription: Added \NewHTMLdescription. (Renamed in v0.30.) 333
\HTMLFilename: No longer escape underscores. 309
\HomeHTMLFilename: No longer escape underscores. 309
\InlineClass: Renamed from "inlineclass". 322
\LWR@LwarpStart: Fix: math cross references. 367
\LWR@closeparagraph: \unskip extra spaces. 326
No break tags in the start/end of a tabular. 326
\LWR@endofline: Fix: \\ 560

\LWR@filestart: Adds meta description. 362
\LWR@htmldivclass: Added optional style. 320
\LWR@htmlelementclass: Added optional style. 320
\LWR@htmlsectionfilename: HTMLFilename: removed additional trailing '-', and may be empty. 309
Sections called "Index" or "index" have an underscore prepended to their filenames if no prefix. 309
\LWR@includegraphicsb: Fix: \linewidth in a floatrow. 733
Fix: Expands filename. 733
\LWR@longtabledatacaptiontag: Fix: Pars in captions. 438
\LWR@section: Combined higher-level sections together into files. 354
\LWR@setOSWindows: Auto-detects operating system. 204
\LWR@subhtmlelementclass: Factored code. 320
\SetHTMLFileNumber: Add: Control file numbers. 309
\cpagerefFor: User-redefinable word for page references. 534
\dotfill: Inserts an ellipsis. 560
\hfill: Inserts a \qquad. 560
\hrulefill: Inserts a short rule. . . 560
\hspace: Add: Supports HTML thin breakable space. 562
\hyperindexref: Print mode provided in case hyperref not used. 483
\pageref: Added. 461
\tracinglwarp: Added. 224
General: 2017/02/09 1
afterpage: Added. 582
alltt: Added. 587
bookmark: Added. 617
caption and subcaption supported. 1
cleveref and referencing patches: Applied \AfterEndPreamble. . . . 533
draftwatermark: Added. 671
eso-pic: Added. 684
everypage: Added. 685
extramarks: Added. 685
fancyhdr: Added. 691
float: Improved float caption type handling. 703
hyperref: Additional user macros. 745
keyfloat: Added. 762
letterspace: User-interface emulated. 771
listings: Added. 775
ltcaption: Added. 784
lwarp-newproject: Added. 235
microtype: User-interface emulated. 809
needspace: Added. 826
nowidow: Added. 839
placeins: Added. 864
ragged2e: Added. 872
setspace: Improved support. . . 890
textpos: Added. 923
titleps: Added. 932
titlesec: Added. 935
titletoc: Added. 937
titling: Improved compatibility. . 939
tocloft: Added. 947
wallpaper: Added. 971
wrapfig: Added. 973
xetexko-vertical: Added. 985
Added @, <, > columns. 394
Added single-expansion data arrays. 305
Code factored into independent lwarp_html files. 573
Docs: Examples for generating HTML file names. 105
Docs: Improved index. 1
Enhanced titling support. 373
File: lwarp.css: Minor fixes for validation. 1
File: lwarpmk used to compile print, HTML, indexes, and latexmages. 1
Fix: \linewidth in a floatrow. . . 708
Moved sidebar and example code to test suite. 1
Page geometry set to 6in wide with large margins. 213
Parallel versions of aux files for print/HTML. 1
Removed reliance on make, grep, gawk. 1
Tabular: \unskip extra spaces. . . 394
Test Suite: HTML meta descriptions. 1
verbatim: Added. 383
BlockClass: Added optional style. . 322
Renamed from "blockclass". . . . 322
LWR@nestspan: Fix: Minipages inside a span. 317
v0.21
\LWR@LwarpStart: Changed latexmages to a .txt file. 365

\LWR@filestart: Skip title if not given. 362
\LWR@newhtmlfile: Skip title if not given. 347
\marginpar: Fixed source listing. . . 340
\marginparBlock: Fixed source listing. 340
General: 2017/02/23 1
fontenc: Added. 716
lwarpmk: Fix: **lwarpmk again** for WINDOWS. 285
lwarpmk: Fix: **lwarpmk limages** for WINDOWS. 285
lwarpmk: Fix: *lwarpmk* uses lateximages text file instead of shell script. 285
Add: Errors for misplaced packages. 186
Docs: Added internet class. 69
Docs: Added TeX2page, GladTeX. . 69
Docs: Installing on WINDOWS. . . . 75
File: lwarp_tutorial.txt added. . 79
v0.22
\LWR@parseDcolumn: Added tabular D column. 409
\LWR@parsebangcolumn: Added tabular ! column. 405
\LWR@parsetablecols: Unknown table column types become l. Added tabular D, !, X columns. . 413
\LWR@printmccoldata: Added tabular D, !, and X columns. 433
General: 2017/03/02 1
abstract: Added. 575
changepage: Added. 629
dcolumn: Added. 668
ftnright: Added. 722
geometry: Nullified commands. . 724
layout: Added. 768
lscape: Added. 783
mcaption: Added. 793
nameref: Added. 824
nextpage: Added. 826
parskip: Added. 855
showkeys: Added. 892
sidecap: Added. 893
tabularx: Added. 916
varioref: Supported. 119
verse: Added. 966
v0.23
\LWR@parsetablecols: Fix for vert bar column type. 413
\LWR@printmccoldata: Fix for vert bar column type. 433
General: 2017/03/02 1
v0.24
\LWR@htmlfileref: Fix: Index links while \tracinglwarp. 457
\hspace: Add: \hspace \fill converts to 2em 562
\hypertocfloat: List of floats responds to lofdepth, lotdepth. 479
General: 2017/03/15 1
floatrow: Support for subfig. . . . 705
subfig: Added. 908
tikz: For tikz v3.0.0 or later, auto-loads tikz babel library if necessary. 931
Docs: Filename underscore. 100, 113
Fix for inline images. 931
No longer preloads subcaption; conflicted with subfig. 215
picture: Fix for inline images. . . . 535
v0.25
\LWR@loadnever: Added the ability to prevent conflicting packages. . . 188
\addcontentsline: Handles theorems. 471
General: 2016/03/22 1
amsthm: Added. 590
ellipsis: Added. 674
emptypage: Added. 675
framed: Added. 720
lips: Added. 775
mdframed: Help avoid hyphenation. 795
ntheorem: Added. 839
showidx: Added. 892
theorem: Added. 924
Basic LaTeX theorems: improved css. 384
Docs: Adds credits for patched code. 1
Docs: Testing lwarp. 173
Fix: Allows XeLaTeX and LuaLaTeX to preload graphics and graphicx. 190
v0.26
General: 2017/03/31 1
lwarp.css: Improved responsive marginpar and marginblock. . . 243
cutwin: Added. 666
endnotes: Added. 677
floatflt: Added. 704
footmisc: Added. 716
footnotehyper: Added. 718
footnote: Added. 717
marginfix: Added. 791
marginnote: Added. 792
mparhack: Added. 814
pagenote: Supported as-is. 853

sidenotes: Added. 894
Docs: Improved MiKTEX install instructions. 74, 76
Dollar span avoided in a lateximage. 491
Footnotes now are LATEX boxes instead of pagenotes. 334
lateximage: Labels track page numbers of lateximages. 517
Print mode now uses a minipage of \linewidth. 517
picture: Fix for \makebox in picture. 535
v0.27
\LWR@@footnotetext: Fix for table footnote par tags. 336
General: 2017/04/04 1
lettrine: Added. 772
microtype: Fix with XeLATEX, LuaLATEX. 809
soul: Added. 901
ulem: Added. 961
Docs: Installing utilities for MACOS. 77
Docs: Limitations of saveboxes. . 114
Page geometry modified to reduce line overflow. 213
v0.28
\@wrindex: Improved indexing. . . . 482
\HTMLAuthor: Added \HTMLauthor. (Renamed in v0.30.) 333
\LWR@LwarpEnd: If FormatEPUB or FormatWP, no bottom nav. 368
\LWR@LwarpStart: FormatWordProcessor forces single-file output. 365
\LWR@filestart: Adds HTML meta author. 362
\LWR@forcenewpage: Forces new PDF page before major environments. 314
\LWR@htmlcomment: Breaks ligatures in HTML comments. 319
\LWR@includegraphicsb: Adapts to graphics syntax. 733
\LWR@newhtmlfile: If FormatEPUB or FormatWP: skips headers, footers, nav. 347
\LWR@parsetablecols: Added L, C, R, J column types. 413
\LWR@startref: Removed space. . . 459
\chapter: If EPUB, prints footnotes before each section. 360
\hyperindexref: Improved indexing. 483
\textup: Fixed span class. 549
General: 2017/04/14 1
glossaries: Added. 726
graphics: Added. 728
tabularx: Fix for optional pos. . . 916
tabulary: Added. 916
lwarpmk: Add: **printglossary** and **htmlglossary** commands. . . . 285
Added boolean FormatEPUB. . . . 229
Added boolean FormatWP. 229
Added boolean HTMLDebugComments. 224
Added boolean HTMLMarkFloats, changed to WPMarkFloats as of v0.42. 229
Docs: Modfying lwarpmk and index processing. 173
File: lwarp_mathjax.txt: Updated CDN repository. 283
Forced oneside to maintain large right margin. 213
v0.29
\LWR@includegraphicsb: Fix: Error when no optional arguments. . . 733
General: 2017/04/15 1
*.lwarpmkconf: Add: language option for config files. 242
lwarpmk.conf: Add: language option for config files. 242
lwarpmk: Add: language option for config files. 285
Add: lwarpmklang option for lwarp. 207
Docs: Using a glossary 90
v0.30
\CSSFilename: Renamed from \NewCSS. 331
\HTMLAuthor: Renamed from \HTMLauthor. 333
\HTMLDescription: Renamed from \NewHTMLdescription. 333
\HTMLFirstPageTop: Renamed from \SetFirstPageTop. 331
\HTMLLanguage: Renamed from \MetaLanguage. 361
\HTMLPageBottom: Renamed from \SetPageBottom. 331
\HTMLPageTop: Renamed from \SetPageTop. 331
General: 2017/04/29 1
lwarp-newproject removed, and combined with lwarp. 235
lwarpmk: Add: xdyfile configuration option. 285
lwarpmk: Fix: *xindy* and *texindy* adjusted for *pdflatex*, *xelatex* and *lualatex*. 285

lwarpmk: Fix: *xindy* now used for print index generation with *latexmk*. 285
lwarpmk: `language` now used for both index and glossary generation. 285
File: `lwarp_html.xdy` renamed to `lwarp.xdy`. 281
Fix: `*.css` files only written in print mode. 243
Fix: `lwarp.xdy` only written in print mode. 281
Fix: `lwarp_mathjax.txt`: Only written in print mode. 283
Option `lwarpmklang` changed to `IndexLanguage`. 207
Option `OSWindows` replaces macro `\warpOSwindows`. 207
Option `xdyFilename` added. 207
Option *latexmk* replaces macro `\UseLatexmk`. 209
Options `HomeHTMLFilename` and `HTMLFilename` replace macros `\HomeHTMLFilename` and `\HTMLFilename`. 208
v0.31
General: 2017/05/15 1
keyfloat: Improved compatibility. 762
v0.32
`\RequirePackage`: Fix: Ignores blanks in package list. 219
General: 2016/06/09 1
glossaries: Prevent error with `\glo@name` not defined. 484
lwarpmk: Fix: **`io.lines()`** changed to **`file:lines()`** due to *luatex* changes. 285
v0.33
`\HTMLAuthor`: Fix: Provides empty default author if none given. . . . 333
`\LWR@loadbefore`: Fix: No `\PackageError` if already loaded. 188
`\LWR@parseatcolumn`: Fix: Column alignment with leftmost `@`. 404
`\LWR@tabledatasinglecolumntag`: Fix: Macros in tabular could cause extra data cell. 420
`\LWR@vspace`: Add: `\vspace` nullified. 563
`\StartDefiningTabulars`: Add: Avoids error: `Misplaced alignment tab character &`. . . 306
General: 2017/07/10 1
amsmath: Removed `fleqn` option. 587
fancyhdr: Fix: Optional args for `\lhead`, etc. 691
Add: Tabular at and bang columns now have their own HTML columns. 394
cleveref: Fix: Loaded `\AtEndPreamble`. 533
Fix: Incorrectly-inline math environments. 509
New handling of `&` to localize catcode changes. 394
v0.34
`\@fnsymbol`: Text symbols instead of math. 376
`\InlineClass`: Moved optional argument in front of mandatory. 322
`\LWR@htmldivclass`: Moved optional argument in front of mandatory. 320
`\LWR@htmlelementclass`: Moved optional argument in front of mandatory. 320
`\LWR@htmlelementclassline`: Moved optional argument in front of mandatory. 321
`\LWR@htmlspanclass`: Moved optional argument in front of mandatory. 318
`\LWR@nullfonts`: Improved font control. 551
`\LWR@restoreorigformatting`:
booktabs: Works inside `lateximage`. 485
Improved font control. 485
`\LWR@subhtmlelementclass`: Moved optional argument in front of mandatory. 320
`\LWR@tabledatacolumntag`:
booktabs: Works inside `lateximage`. 445
`\fboxBlock`: Added. 544
`\makebox`: Fix: Handles paren arg. . 542
General: 2017/08/08 1
babel-french: Adds fixed-width HTML spaces to punctuation. . . 315
balance: Added. 608
booktabs: Works inside `lateximage`. 448, 618
boxedminipage2e: Added. . . . 620
crop: Added. 663
enumerate: Added. 677
enumitem: Added, no longer required. 677
everyshi: Added. 685
fancybox: Added. 687
fancyvrb: Added, no longer required. 693
figcaps: Added. 699

filecontents: Required. Patched for morewrites. 214
floatpag: Added. 705
flushend: Added. 711
fullpage: Added. 723
hyperxmp: Added. 750
idxlayout: Added. 751
marginfit: Added. 791
mdframed: Improved mdtheorem patch. 801
moreverb: Added. 811
paralist: Added. 853
pdflscape: Added. 856
pdfsync: Added. 860
prelim2e: Added. 866
rotfloat: Added. 878
savetrees: Added. 879
shadow: Added. 891
syntonly: Added. 915
titleps: No longer required. 932
titleref: Prevented. 935
xmpincl: Added. 990
Added. 982
Docs: Horizontal space limitations. 1
Docs: Misplaced alignment character. 177
File: lwarp_mathjax.txt: Version change. 283
File: README.txt: updated. 1
Fix: Added the eqnarray environments. 509
Improved font control. 547
Lists refactored to remove enumitem requirement. 386
Verbatim refactored to remove fancyvrb requirement. 382
tabular: booktabs: Works inside lateximage. 449
lateximage: Fix: lateximage with minipage, \parbox, \makebox, \fbox, \framebox, \raisebox, \scalebox, \reflectbox. 517
BlockClass: Moved optional argument in front of mandatory. 322
fminipage: Added. 544
LWR@nestspan: Fix: Minipages, BlocksClass, and lists inside a span. 317
v0.35
General: 2017/08/08 1
Fix: \textbf and related. 547
v0.36
\LWR@@footnotetext: Extra HTML source space after paragraphs. . 336
Force HTML superscripts. 336
\LWR@HTMLsanitize: Fix for babel-french. 514
\LWR@HTMLsanitizeexpand: Fix for babel-french. 514
\LWR@closeparagraph: Extra HTML source space after paragraphs. . 326
\LWR@currenttextcolor: Fix for \rule when xcolor not loaded. . 558
\LWR@nullfonts: Fix: Filenames while using MathJax. 551
\LWR@restoreorigformatting: siunitx: Improved super/subscripts in a lateximage. 485
\LWR@section: Improved spacing. . 354
\LWR@stoppars: Extra HTML source space after paragraphs. 329
\fbox: Fix: Uses \fboxrule and \fboxsep. 543
\framebox: Fix: Handles width and horiz position. 543
\makebox: Fix: Handles width and horiz position. 542
General: 2017/08/17 1
babel-french: Adjustements for French variants, load order, footnotes, ellipses. 315
footnote: Extra HTML source space after paragraphs. 717
siunitx: Fix for babel-french. . . . 526
siunitx: Improved symbol support. 896
transparent: Added. 957
upref: Added. 965
xcolor: Added \fcolorboxBlock, \colorboxBlock. 974
xcolor: Fix: Background none in print mode. 974
xcolor: Refactored \LWR@colorstyle. 977
xcolor: Uses \fboxrule and \fboxsep. 974
xcolor: \fcolorbox etc. now work inside lateximage. 974
Docs: Reorganized: Special cases and limitations. 111
Source: Improved formatting. . . . 1
tabular: Fix for babel-french. . . . 449
lateximage: Footnotes appear in regular text instead of the lateximage minipage. 517
v0.37
\include: Maintains independent aux files for HTML. 222
General: 2017/08/19 1
LaTeX accents: Added. 234

babel-french: Adjustment for load order. 315
color: Prevented. 660
comment: Maintains independent cutfiles for print, HTML. 211
siunitx: Improved symbol support. 896
textcomp: Improved support. . . 919
lwarpmk: Removes additional HTML aux files. 285
File handles reorganized. 221
v0.38
\@seccntformat: Added for appendix. 353
\ForceHTMLPage: Added. 351
\ForceHTMLTOC: Added. 351
\LWR@section: \part* starts a new HTML page, for appendix. 354
Modified spacing, uses \numberline. 354
\numberline: Added trailing \quad. 477
\part: Fix with article class. 360
General: 2017/08/27 1
appendix: Added. 595
arabicfront: Added. 597
chappg: Added. 632
color: Forces xcolor as well. . . . 660
fix2col: Added. 700
fncychap: Added. 711
grffile: Added. 741
metalogo: Added. 805
nonumonpart: Added. 837
nopageno: Added. 837
pagenote: Option page disabled. 853
realscripts: Added. 872
relsize: Added. 875
romanbarpagenumber: Added. . 877
romanbar: Added. 877
scalefnt: Added. 880
siunitx: Removed from lwarp core. 896
textcomp: Removed from lwarp core. 919
tocbibind: Added. 944
xltxtra: Added. 989
lwarpmk: Added **print1** and **html1** actions. 285
Added \markboth, \sloppy, etc. . 314
Docs: Enhanced *Supported Features* table. 63
Docs: Index, tocbibind. 125
Docs: Starred sections. 122
v0.39
\@maketitle: titling version. 941
Native LaTeX version. 377
Removed minipages. 377, 941
Supports authblk with s of class oneauthor instead of tabular. 377, 941
\AddSubtitlePublished: Added. . . 378
\LWR@domulticolumn: Add: Optional vpos and # rows. 435
\LWR@restoreorigformatting: Appended with \appto instead of calling various macros. 485
\LWR@tabledatacolumntag: Don't start a data cell if see \TabularMacro. 445
\ResumeTabular: Added. 444
\TabularMacro: Added. 444
\multicolumnrow: Added. . . . 442, 820
\printauthor: Removed minipages. 373
Supports authblk with s of class oneauthor instead of tabular. 373
\thanksmarkseries: Removed minipage footnotes. 942
General: 2017/09/05 1
a4wide: Added. 575
a4: Added. 574
a5comb: Added. 575
addlines: Added. 582
anysize: Added. 595
authblk: Added. 604
bigdelim: Added. 614
bigstrut: Added. 616
ebook: Added. 673
fullwidth: Added. 723
midpage: Added. 810
multirow: Add: New optional vpos argument. 818
multirow: Add: Supports left/right border for bigdelim. 818
multirow: Fix: Long text argument. 818
supertabular: Added. 913
textarea: Added. 919
titling: Improved compatibility. . 939
titling: Removed extraneous center environments. 940
typearea: Added. 960
xtabular: Added. 992
zwpagelayout: Added. 996
Docs: Reorganized tabular discussion. 146
Titlepage \published and \subtitle removed. \AddSubtitlePublished restores. 378
titlepage: Clear pending footnotes. 372
Removed minipages. 372
titlingpage: Clear pending footnotes. 939

v0.40
\@chapcntformat: Added for tocbibind, anonchap. 354
\LWR@HTMLhline: Added. 448
\LWR@includegraphicsb: Add: Full \graphicspath support. 733
\LWR@nullfonts: Fix: Long arguments for expandable command. . . . 551
\LWR@restoreorigformatting: Improved LaTeX logos inside a lateximage. 485
Improved symbols inside a lateximage. 485
Nullified \InlineClass, etc. inside a lateximage. 485
\LWR@tabledatacolumntag: Fix for bigdelim: \ldelim, \rdelim. . . . 445
\chapter: Added support for quotchap. 360
\multicolumnrow: Fix: Adapts to older multirow and xparse. 442
\simplechapterdelim: Added for tocbibind, anonchap. 353
\underline: Added. 558
General: 2017/09/25 1
adjmulticol: Added. 581
anonchap: Added. 594
bigdelim: Improved documentation. 614
cuted: Added. 666
dblfnote: Added. 667
fnpos: Added. 713
graphics: Moved out of the lwarp core. 728
graphics: Restores \includegraphics and \DeclareGraphicsExtensions in a lateximage. 728
graphicx: Moved out of the lwarp core. 740
grffile: Directly supported. 741
midfloat: Added. 810
multirow: Improved bigdelim borders. 818
pfnote: Added. 862
quotchap: Added. 870
sectsty: Added. 889
stabular: Added. 906
tabls: Added. 916
textcomp: Additional symbols, improved XeLaTeX and LuaLaTeX support. 919
tocbibind: Improved for \simplechapter. 944
xfrac: No longer preloaded. 215
xltxtra: Fix for \showhyphens with XeLaTeX. 989
v0.41
\LWR@addcmidruletrim: Add: \cmidrule trims. 425
\LWR@clearmidrules: Add: \cmidrule trims. 422
\LWR@closetabledatacell: Add: Mute > for \bottomrule. 398
Fix: At/bang column with \multirow. 399
Fix: Cancel < for \multicolumn. . 399
\LWR@domulticolumn: Add: \cmidrule trims. 435
Added vertical rules. 436
\LWR@nullifyNoAutoSpacing: Fix: \NoAutoSpacing in a tabular with babel-french. 449
\LWR@parsebarcolumn: Added vertical rules. 406
\LWR@printatbang: Add: \cmidrule trims. 418
Add: Mute at and bang columns for \bottomrule. 418
\LWR@printbartag: Added vertical rules. 418
\LWR@subaddcmidruletrim: Added. 424
\LWR@subcmidrule: Add: \cmidrule trims. 423
\LWR@tabledatasinglecolumntag: Add: \cmidrule trims. 420
Add: Mute < for \bottomrule. . . 420
\LWR@tabularfinishrow: Unfinished tabular rows automatically filled. 401
\mcolrowcell: Added for \multicolumnrow cells. 448
General: 2017/10/07 1
multirow: Add: \cmidrule trims. 818
Added vertical rules. 819
Fix: < spec. 819
Improved rules. 618
tabular: Fix: \NoAutoSpacing in a tabular with babel-french. . . . 450
v0.42
\@ensuredmath: Improved \ensuremath. 500
\@textsubscript: Added. 557
\@textsuperscript: Added. 557
\LWR@HTMLhline: If FormatWP force explicit border. 448
\LWR@addformatwpalignment: If FormatWP add explicit style for cell alignment. 427
\LWR@addrulewidth: If FormatWP force explicit border. 425

\LWR@amsmathbody: Fix: Numbering and naming AMS math environments. 516
\LWR@amsmathbodynumbered: Fix: Numbering and naming AMS math environments. 516
\LWR@doequation: If FormatWP print LaTeX expression. 504
\LWR@domulticolumn: If FormatWP add cell alignment. 437
\LWR@doubledollar: If FormatWP print LaTeX expression. 498
Improved \ensuremath. 498
Improved line spacing with mathjax. 498
\LWR@floatbegin: If FormatWP add a text frame. 466
\LWR@floatend: If FormatWP add a text frame. 467
\LWR@htmlmathlabel: If FormatWP print LaTeX expression. 508
\LWR@includegraphicsb: Fix: Filename expansion. 733
If FormatWP, use explicit size. . . . 734
\LWR@rememberbtag: Fix: Numbering and naming AMS math environments. 516
\LWR@restoreorigformatting: Improved \ensuremath. 486
\LWR@subaddcmidruletrim: 0pt if no rule given. 424
\LWR@subsingledollar: If FormatWP print LaTeX expression. 493
\LWR@tabledatasinglecolumntag: If FormatWP add cell alignment. . . 420
\LaTeX: If FormatWP use explicit style. 568
\TeX: If FormatWP use explicit style. 568
\hspace: If FormatWP add \quads. . . 563
\listoffigures: Added boolean WPMarkLOFT. 475
\listoftables: Added boolean WPMarkLOFT. 475
\marginpar: If FormatWP emulate a wrapfig. 340
\marginparBlock: If FormatWP emulate a wrapfig. 340
\rule: If FormatWP add \quads. . . . 566
\tableofcontents: Added boolean WPMarkTOC. 474
\underline: If FormatWP, use explicit styles for \underline, etc. 558
General: 2017/10/30 1
\textbf and related: If FormatWP, use explicit styles for \textsc, etc. 547
algorithmicx: If FormatWP add \quads. 586
epigraph: If FormatWP add HTML styles. 678
fancybox: If FormatWP add HTML styles. 687
floatflt: Added width. 704
includegraphics: Fix: Class key. . 732
keyfloat: If FormatWP add explicit HTML style. 767
moreverb: Simplified formatting of listings. 811
multirow: If FormatWP add cell alignment. 819
overpic: Added. 852
realscripts: Fix for subscripts in a lateximage. 872
sidenotes: If FormatWP add explicit HTML style. 894
siunitx: Improved \ensuremath. . 896
soul: If FormatWP, add explicit styles. 901
textcomp: Improved \interrobangdown. 919
wrapfig: If FormatWP add explicit HTML style. 973
Added boolean WPMarkLOFT. . . . 230
Added boolean WPMarkMath. . . . 230
Added boolean WPMarkMinipages. 230
Added boolean WPMarkTOC. 230
Added boolean WPTitleHeading. 230
Docs: Added support page. 2
Docs: Improper \prevdepth. . . . 177
Docs: Reorganized math limitations 137
File: lwarp_mathjax.txt: Updated siunitx script. 283
Fix: Numbering and naming AMS math environments. 515
If FormatWP force explicit border. 618
If FormatWP, shift section headings. 231
tabbing: Added. 384
lateximage: Fix: Numbering and naming AMS math environments. 518
center: If FormatWP use explicit text-align. 522
minipage: Added boolean WPMarkMinipages. 540
If FormatWP add a text frame. . . . 539
eqnarray: Fix: Numbering and naming AMS math environments. 510
If FormatWP print LaTeX expression. 509
LWR@BlockClassWP: Added to factor code. 323

LWR@figcaption: If FormatWP forces italic captions. 470
v0.43
\LWR@domulticolumn: Fix for vertical rules. 436
Fix: Multicolumn trim. 436
\LWR@maybeprintpendingfootnotes: Added FootnoteDepth. 339
\LWR@nullfonts: Fix: Nullify dollar inside filesnames. 551
\LWR@parsetablecols: Ignore spaces in col spec. 413
\LWR@printmccoltype: Added vertical rules. 431
\LWR@section: Fix: Expansion in comparison. 355
Fix: Math in section name. . 356, 358
Fix: Nullify fonts inside HTML comment. 356
\TabularMacro: \newcommand instead of \relax to fix supertabular and xtab. 444
\href: Made robust. 463
\nameref: Made robust. 461
\nolinkurl: Made robust. 463
\url: Made robust. 463
General: 2017/11/08 1
LWR@currentautosec: Added. . . . 354
breakurl: Added. 620
hyperref: Made robust. 746, 747, 749
hyperref: \Gauge added. 750
luatodonotes: Added. 786
todonotes: Added. 954
Added FootnoteDepth. 335
Docs: HTML settings table. 100
Docs: Reorganized HTML customization. 100
v0.44
\@currentlabelname: Adjustment for koma-script. 455
\HTMLTitle: Added. 333
\LWR@addformatwpalignment: Fix for multicolumn alignment if FormatWP. 427
\LWR@backgroundcolor: Added. . . . 978
\LWR@filestart: Add \HTMLTitle. . 364
Fix \HTMLAuthor. 363
\LWR@listitem: Added list and trivlist. 388
\LWR@patchlists: Added list and trivlist. 391
\LWR@strresult: Fix: \providecommand. 397
\LWR@textcurrentcolor: xcolor: Added \LWR@textcurrentcolor. 977
\addcontentsline: Automatic \LWR@newfloatanchor. 471
\chapter: Add preamble for koma-script. 360
\marginparBlock: Added. 340
\nopagecolor: xcolor: Fix for \nopagecolor. 979
\part: Add preamble for koma-script. 360
\title: Added \thetitle. 332
General: 2017/11/22 1
algorithmicx: Improved comment symbol. 586
atbegshi: Added. 601
cancel: Added. 623
changepage: Additional options. 629
easy-todo: Added. 672
fancyref: Added. 692
fixmetodonotes: Added. 702
fixme: Added. 701
fontenc: Allowed after lwarp. . . . 716
hang: Added. 742
ifoddpage: Added. 752
ltxtable: Added. 785
luatodonotes: Improved. 786
lwarp-patch-komascript: Added. 997
overpic: Fix: Groups for leximages. 852
pdfsync: Fixes. 860
preview: Added. 866
scrextend: Added. 881
scrhack: Added. 883
scrlayer-notecolumn: Added. . . 885
scrlayer-scrpage: Added. 885
scrlayer: Added. 883
section: Added. 887
soulpos: Added. 903
soulutf8: Added. 903
supertabular: Fix for caption. . . 914
tikz: Fix: Groups for leximages. 931
tocbasic: Added. 943
tocloft: Added \newlistentry. . 951
tocloft: Improved \newlistof. . . 952
tocstyle: Added. 953
todonotes: Improved. 954
todo: Added. 953
typearea: Added expert commands. 960
watermark: Added. 972
xcolor: Added \LWR@currenttextcolorstyle. . 977
xcolor: Added \LWR@findcurrenttextcolor. . . 977
xtab: Fix for caption. 992
Adjustment for koma-script. . . . 198

AMS environments: Fix: Groups for lateximages. 588
If pdfLaTeX, require T1 and UTF-8 encoding. 199
picture: overpic: Fix: Groups for lateximages. 535
list: Added list and trivlist. . . 389
LWR@nestspan: Added list and trivlist. 317
v0.45
\@currentHref: Added. 462
\@donoparitem: Modified for HTML. 386
\@item: Modified for HTML. 387
\@mklab: Modified for HTML. 386
\CSSFilename: Improved filenames with underscores. 331
\LWR@LwarpStart: Fix: Lateximages on incorrect pages with Mathjax. 367
\LWR@includegraphicsb: Improved URLs with underscores. 733
\LWR@newautoidanchor: Fix: No anchor if frozen autoid. 468
\LWR@notmemoirloadafter: Added. 187
\LWR@printpendingmpfootnotes: Added. 339
\LWR@startref: Fix: Labels with underscores. 460
\LWR@subhyperref: Improved URLs with underscores. 462
\LWR@subhyperrefclass: Improved URLs with underscores. 462
\LWR@sublabel: Fix: Labels with underscores. 458
\LWR@tabledatacolumntag: Fix: Empty line between rows. 447
\chapter: Add optional heading title for memoir. 360
\newpage: Added. 560
\nolinkurl: Fix: Underscore in URL. 463
\normalmarginpar: Added. 340
\reversemarginpar: Added. 340
\section: Add optional heading title for memoir. 361
\tableofcontents: Fix: Empty sidetoc. 474
Fix: Patch \AtBeginDocument. . . 474
\url: Improved URLs with underscores. 463
General: 2018/01/14 1
array: Added. 597
babel-french: Robust commands. 315
backref: Added. 608
breakurl: Fix: Underscore in URL. 620
changebar: Added. 628
cite: Added. 659
continue: Added. 662
endfloat: Added. 675
epigraph: Support for memoir. . 679
fancyvrb: Improvements. . . 693–695
flafter: Added. 702
fltrace: Added. 710
footnpag: Added. 719
fwlw: Added. 724
hanging: Added. 743
hyperref: Fix: Underscore in URL. 746
lwarp-patch-memoir: Added. . . 1000
memhfixc: Added. 805
memoir: Added. 571
natbib: Added. 824
pagesel: Added. 853
prettyref: Added. 866
subfigure: Added. 913
subfig: Fix for subcaption end tag. 911
subfig: Fix: Math in subcaptions. 909
textfit: Added. 923
titleref: Added. 935
turnthepage: Added. 959
Allows memoir's preloaded packages. 190
Docs: xparse warnings. 156
Docs: Fix for double hyphens. . . . 77
Docs: Improved install instructions. 78
Docs: Improved MiKTEX install instructions. 74
Docs: Moved table so doesn't interfere with install docs. 73
File: lwarp_mathjax.txt: Allow MathJax inside tabbing. 283
File: lwarp_mathjax.txt: Allow MathJax inside verse. 283
Fix: Empty sidetoc. 474
Improved: Robust \, \ , and \textellipsis commands. 559
Separate LWR@thisautoidWP for word processor s. 468
thebibliography: Patched to emphasize titles. 484
minipage: Fix: Improper \prevdepth. 538, 540
v0.46
\LWR@closeparagraph: Fix: Tabular empty lines. 327
\LWR@closeprevious: Fix: Stack unnesting. 313
\LWR@forcenewpage: Fix: Improper \prevdepth. 314
\LWR@lookforpackagename: Fix: Spaces in \usepackage. 218
\LWR@popclose: Fix: Stack unnesting. 304
\LWR@providelength: Added. 201

\LWR@pushclose: Fix: Stack unnesting. 304
\LWRPrintStack: Name changed from \PrintStack. 312
General: 2018/01/23 1
LWR@tabularpardepth added. . . 397
amsthm: Adapted to trivlist changes. 592
mdframed: Fixes for svg math or lateximage in title. 797
mdframed: Fixes for footnotes. . 798
ntheorem: Adapted to trivlist changes. 839
theorem: Adapt to trivlist changes. 925, 927
tabular: Fix: Tabular empty lines. . 453
list: Fix: Stack unnesting. 389
v0.47
\LWR@HTML@caption@begin: Fix: Argument passed to \LWR@origcaption@begin. 470
\LWR@LwarpStart: Fix for svg math in \nameref. 367
\LWR@WPcell: Fix: Line wrap at html hyphen. 426
\LWR@createautosec: Fix: Line wrap at html hyphen. 352
\LWR@domulticolumn: Fix: Line wrap at html hyphen. 436
\LWR@floatbegin: Fix: Line wrap at html hyphen. 466
\LWR@htmlclosecomment: Add \mbox to prevent line breaks. 319
\LWR@newautoidanchor: Fix: Line wrap at html hyphen. 468
\LWR@printopenlist: Fix: Line wrap at html hyphen. 386
\LWR@startref: Fix: Line wrap at html hyphen. 459
\LWR@sublabel: Fix: Line wrap at html hyphen. 458
\LWR@subsingledollar: Added svg math image baseline adjust and em sizing. 493
Fix: Line wrap at html hyphen. . 496
\captionlistentry: Fix: Line wrap at html hyphen. 471
\hypertoc: Fix: Line wrap at html hyphen. 478
\hypertocfloat: Fix: Line wrap at html hyphen. 479
General: 2018/01/30 1
adjmulticol: Fix: Line wrap at html hyphen. 581
blowup: Added. 616
caption: Added. 624
caption: Also loads lwarp-caption. 221
changepage: Fix for pagecheck macros. 629
endheads: Added. 676
epigraph: Fix: Line wrap at html hyphen. 678
hanging: Fix: Line wrap at html hyphen. 744
hang: Fix: Line wrap at html hyphen. 742
keyfloat: Fix for svg math in captions. 764
midpage: Fix: Line wrap at html hyphen. 810
multirow: Fix: Line wrap at html hyphen. 818
multitoc: Added. 821
ntheorem: Fix: Line wrap at html hyphen. 843
realscripts: Fix: Line wrap at html hyphen. 872
scrextend: Fix: Line wrap at html hyphen. 881
sectionbreak: Added. 888
sidenotes: Fix for svg math in captions. 894
subfig: Fix for svg math in captions. 909
subfig: Fix: Support \nameref. . . 908
xurl: Added. 994
lwarpmk: *pdfcrop*: Removed hires option for improved crop accuracy. 285
lateximage: Added css style option. 517
Fix: Line wrap at html hyphen. . 521
center: Fix: Line wrap at html hyphen. 522
minipage: Fix: Line wrap at html hyphen. 539
flushleft: Fix: Line wrap at html hyphen. 523
flushright: Fix: Line wrap at html hyphen. 522
enumerate: Fix: Line wrap at html hyphen. 390
itemize: Fix: Line wrap at html hyphen. 390
LWR@BlockClassWP: Fix: Line wrap at html hyphen. 323
v0.48
\@@@setcpageref: Fix for new v0.21 of cleveref. 534
\@@@setcref: Fix for new v0.21 of cleveref. 533

\@@@setcrefrange: Fix for new v0.21 of cleveref. 533
\@biblabel: Improved bibliography label. 484
\@item: Honors \makelabel. 387
\@maketitle: Fix: Errors with IEEEtran class. 377
\LWR@LwarpStart: Adjusted space around captions. 366
\LWR@ProvidesPackageDrop: Fix: Options with braces. 221
\LWR@addtabularhrulecolor: colortbl: Added. 427
\LWR@addtabularrulecolors: colortbl: Added. 428
\LWR@closetabledatacell: colortbl: Added. 399, 400
\LWR@includegraphicsb: Fix: Virtual page size limited to a group. 733, 736
\LWR@lookforpackagename: Fix: Parsing similar package names. . 218
\LWR@newautopagelabel: Fix: TOC, LOF, LOT links. 345
\LWR@newhtmlfile: Fix: TOC, LOF, LOT links. 349
\LWR@nullfonts: Fix: \newline in title. 551
\LWR@parsedrequirepackagenames: Fix: Parsing similar package names. 216
\LWR@parsetablecols: Fix: Ignore optional tabular column arguments. 414
\LWR@restoreorigformatting: Fix: Spacing in SVG math, lateximage, Ti*k*z. 485
\LWR@section: Fix: TOC, LOF, LOT links. 358
\LWR@tabledatasinglecolumntag: colortbl: Added. 421
\LWR@textcurrentfont: Added. Improves font control. 554
\bibliography: Fix: \BaseJobname for bibliography. 484
\centerline: Added. 524
\l@part: Adapts to classes without \part. 480
\leftline: Added. 524
\mbox: Nullified for HTML. 541
\rightline: Added. 524
\thempfootnote: Removed \itshape. 338
General: 2018/02/14 1
acronym: Added. 580
acro: Added. 578
chapterbib: Added. 632
colortbl: Added. 416, 427, 660
fancyref: Now directly supported. 692
hypcap: Added. 744
hypernat: Added. 745
hyperref: \texorpdfstring now uses the TEX string. 749
luatodonotes: Improved \todototoc. 787
siunitx: Changes fraction to symbol. 898
siunitx: Improved SVG math. 896, 898
siunitx: Improved color output. . 896
stfloats: Added. 906
todonotes: Improved \todototoc. 954
vmargin: Added. 968
xfrac: Fix: Added groups around super/subscripts to localize LWR@nestspan changes. 987
Docs: Converting an existing document. 93
Improved font control. 554, 555
tabular: colortbl: Added. 451
lateximage: Print mode boxed to natural width. 522
abstract: Allow optional name. . . . 379
v0.49
\LWR@addtabularcellcolor: xcolor: Added tabular row colors. 430
\LWR@domulticolumn: xcolor: Added tabular row colors. 437
\LWR@printlength: Fix: Group printlen changes. 215
\affiliation: Fix: Adapts to classes which already provide. 372
\href: Fix: Adapt to classes. 463
\noalign: Fix: \noalign inside tabular. 448
\url: Fix: Adapt to classes. 463
General: 2018/02/19 1
amsmath: Fix: Patches for \eqref. 587
eso-pic: Fix for \AddToShipoutPicture. 684
figsize: Added. 699
fnlineno: Added. 712
hypdestopt: Added. 745
hyphenat: Added. 751
lineno: Added. 772
luacolor: Added. 786
pagegrid: Added. 853
pdfrender: Added. 860
resizegather: Added. 877
vertbars: Added. 968
vwcol: Added. 969
xcolor: Added tabular row colors. 416, 983

Fix: Adapt to classes. 560
v0.50
\@ensuredmath: Fix: Use lateximage even if MathJax. 500
Improved SVG math alt tags. . . . 500
\LWR@@footnotetext: Robustify macros. 336
\LWR@atbeginverbatim: Improved column alignment. 382, 383
\LWR@doequation: Improved SVG math display. 504
\LWR@doubledollar: Improved SVG math alt tags. 498
Improved SVG math display. 498
\LWR@htmlrefsectionfilename: Fix: SVG math in a section name. . . 310
\LWR@newhtmlfile: Fix: SVG math in a section name. 349
\LWR@nullfonts: Fix: \underline in sectioning file name. 553
\LWR@overline: Added. 558
\LWR@subsingledollar: Fix: Use lateximage even if MathJax. . . . 493
Improved SVG math alt tags. . . . 493
MD5 hash avoids duplicate SVG math. 496
\LWR@vspace: Robustify macros. . . . 563
\newline: Robustify macros. 560
\textsubscript: Robustify macros. 557
\textsuperscript: Robustify macros. 557
General: 2018/03/03 1
lwarp.css: Improved SVG display math centering. 243
lwarp_one_limage.txt: Added. . 282
amsmath: Fix: Upright tags for SVGmath. 587
axodraw2: Added. 606
bytefield: Added. 623
dblfloatfix: Added. 667
diagbox: Added. 668
epstopdf: Added. 680
listings: Force flexible columns. . 775
morefloats: Added. 811
nonfloat: Added. 837
ntheorem: Fix: Not standard nor amsthm selected. 846
pbox: Added. 855
phfqit: Added. 863
schemata: Added. 880
siunitx: Fix: Loads xcolor. 896
siunitx: Improved SVG math alt tags. 898
siunitx: Improved units. 526, 896, 899
xy: Added. 995
lwarpmk: Error if lateximages.txt does not exist. 285
lwarpmk: Error if lwarpmk.conf points to lwarp. 285
lwarpmk: Improved error messages. 285
lwarpmk: MD5 hash avoids duplicate SVG math. 285
lwarpmk: Multiprocess support making lateximages. 285
AMS environments: Improved SVG math display. 588
Fix: Load fontspec if necessary. . 212
Robustify macros. 555
lateximage: Fix: SVG math in a section name. 520
MD5 hash avoids duplicate SVG math. 519, 521
eqnarray: Improved SVG math display. 510
v0.51
\@ensuredmath: Hashes \ensuremath. 500
\@item: Restored list label space. . . 388
\LWR@HTMLsanitize: Fix: Escapes double quotes. 514
\LWR@HTMLsanitizeexpand: Fix: Escapes double quotes. 514
\LWR@LwarpStart: MathJax: Nullifies \ensuremath. 367
\LWR@addbaselinemarker: Improved SVG math baseline. 491
\LWR@atbeginverbatim: Adds vertical offset. 382
\LWR@customizeMathJax: MathJax: Nullifies \ensuremath. 346
\LWR@doequation: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 504
\LWR@doubledollar: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 498
\LWR@findcurrenttextcolor: Added \LWR@findcurrenttextcolor when no xcolor. 558
\LWR@newautoidanchor: Fix: No autoid is inside a lateximage. . . 468
\LWR@newhtmlfile: MathJax: Nullifies \ensuremath. 350
\LWR@subsingledollar: Fix: \ensuredmath inside SVG image. 493
Fix: lateximage inside $\mathcal{AMS}$ \text. 494
Fix: Honors text font around SVG math. 494

Fix: SVG math with enclosed lateximage. 494
Improved SVG math baseline. . . . 495
SVG math baseline improved with invisible rule at corner. 497
Typeset SVG math only once during measurement. 494
\LWR@textcurrentcolor: xcolor: \LWR@textcurrentcolor if xcolor not loaded. 558
\addcontentsline: Add missing support for float mechanism if necessary. 472
No anchor ID if inside SVG image. 472
\displaymathnormal: Processing for complicated display math. . . . 506
\displaymathother: Processing for complicated display math. . . . 507
\textcolor: Fix: SVG math color. . . 978
General: 2018/03/24 1
HTML entity used for text dollar. . 491
lwarp_one_limage.txt: *pdftocairo* -noshrink added. 282
afterpackage: No longer required. 214
chemfig: Added. 633
chemformula: Added. 635
chemgreek: Added. 639
chemmacros: Added. 640
chemnum: Added. 657
epstopdf-base: Added. 680
fancybox: Fix: Optional tag for \item in a span. 690
grid: Added. 741
listings: Forces cleared options. . 776
ltxgrid: Added. 785
mhchem: Added. 807
tikz: Fix for \tikz macro. 931
tikz: Fix for tikz with optional argument. 931
titling: Fix for \thanks mark. . . . 940
lwarpmk: *pdfcrop*: Restored hires option. 285
lwarpmk: *pdftocairo* -noshrink added. 285
AMS environments: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 588
Docs: tikz limitations. 143
Docs: Multiple authors and affiliations. 121
Docs: Things to avoid. 111
Docs: Updated Converting an existing document. 93
Fix: Remember original \# in case is redefined. 232
lateximage: Added additional hashing option. 517
Fix: lateximage inside $\mathcal{AMS}$ \text. 518
Processing for complicated display math. 520
alignat: Fix: Added. 590
eqnarray: Fix: \addcontentsline inside SVG math. Provides an autoid anchor. 510
LWR@displaymathother: Processing for complicated display math. . . 501
LWR@equationother: Processing for complicated display math. . . . 501
v0.52
\@ensuredmath: Improved hashing expansion. 500
\@mpfootnotetext: Fix: Paragraph handling. 338
\CustomizeMathJax: Added. 346
\LWR@@footnotetext: Fix: Paragraph handling. 337
\LWR@addbaselinemarker: Warnings if lwarp_baseline_marker.png is not present or if graphicx/s not loaded. 491
\LWR@customizedMathJax: Added. . 346
\LWR@doequation: Fix: equation* now based on equation instead of displaymath. 504
Fix: equation* with split. . . . 504
\LWR@filenamenoblanks: Fix: \FileDepth with non-utf8 encoding. 344
\LWR@nullfonts: Fix: \texorpdfstring in section names. 554
\LWR@section: Fix: Footnote numbering: Limited HTML comment if starred. 356
Fix: Footnote numbering: Use short TOC entry for HTMLDebug comments. 356
\LWR@subsingledollar: Added user-adjustable SVG math font scaling. 495
\LateximageFontScale: Added user-adjustable SVG math font scaling. 513
\href: Fix: #, %, &, ~, _ in URL. . . . 463
\nolinkurl: Fix: #, %, &, ~, _ in URL. 463
\theHTMLTitleSeparator: Fix: \FileDepth with non-utf8 encoding. 362
\url: Fix: #, %, &, ~, _ in URL. 463

General: 2018/04/01 1
breakurl: Fix: #, %, &, ~, _ in URL. . 620
endfloat: Updated for v2.6. 675
fancyvrb: Initial support for \VerbatimFootnotes. 687, 693
hyperref: Fix: #, %, &, ~, _ in URL. 746–748
nicefrac: Added. 835
url: Added. 965
lwarpmk: Fix: Memory overflow when spawning tasks. 285
lwarpmk: Fix: Skip image generation if from page 0. 285
Changed FootnoteDepth default to \subsbusection. 335
Docs: Improved install instructions. 75
Fix: MathJax script line wraps. Reduced right margin. 213
If pdfLaTeX, allow other input encoding. 199
pkggraphics: Added defaults. 730, 731
pkggraphicx: Updated for v1.1a. . 731
pkggraphicx: Updated for v1.1b. . 731
Restore \kill in a lateximage. . 783
tabbing: Fix to allow inside lateximage. 384
lateximage: Fix for hash expansion. 519
v0.53
General: 2018/04/01 1
lwarpmk: Added **lwarpmk cleanlimages**. 285
lwarpmk: Added warning for corrupted images. 285
Docs: **lwarpmk cleanlimages**. . . . 91
Docs: **lwarpmk pdftohtml**. 91
v0.54
\LWR@afterendverbatim: Added vspace argument. 383
\LWR@atbeginverbatim: Improved column alignment. 383
\LWR@earlyloadnever: Added. 189
\LWR@endfloatalignment: Honor \centering, etc. in floats. 469
\LWR@floatalignment: Honor \centering, etc. in floats. 468
\LWR@floatbegin: Honor \centering, etc. in floats. 466
\LWR@floatend: Honor \centering, etc. in floats. 467
\LateximageFontSizeName: Defaults to normalsize. 513
\centering: Added debug comment. 523
\raggedleft: Added debug comment. 523
\raggedright: Added debug comment. 523
General: 2018/04/22 1
*.lwarpmkconf: Option IndexLanguage changed to xindyLanguage. 242
*.lwarpmkconf: Option pdftotextEnc added. 242
*.lwarpmkconf: Option xdyFilename changed to xindyStyle. 242
*.lwarpmkconf: Option xindyCodepage added. 242
lwarp.css: Fix: Text-decoration-skip: auto. . . . 243
lwarpmk.conf: Option IndexLanguage changed to xindyLanguage. 242
lwarpmk.conf: Option pdftotextEnc added. 242
lwarpmk.conf: Option xdyFilename changed to xindyStyle. 242
lwarpmk.conf: Option xindyCodepage added. 242
bibunits: Added. 614
chngpage: Added. 658
forest: Added. 719
glossaries: Fix when not using babel or polyglossia. 727
gridset: Added. 741
hyperref: Fix: \hyperref and \hyperlink with special chars in text. 747, 748
hyperref: Fix: \ref in \hyperref and \hyperlink caused nested link. 747, 748
lwarp-patch-memoir: Update for v3.7g. 1004
magaz: Added. 788
ragged2e: Fix: \centering, etc. . 872
textcomp: Fix for \textperthousand. 919
tikz: Fixes for \pgfpicture, minipages, fit, align, font. 931
lwarpmk: Added pdftotextenc. . 285
lwarpmk: Added xindycodepage. 285
lwarpmk: Changed language to xindylanguage. 285
lwarpmk: Changed xdyfile to xindystyle. 285
lwarpmk: Improved error if configuration file does not exist. 285
lwarpmk: Increased prominence for error for an unknown command. 285

lwarpmk: Verifies HTML version exists before `lwarpmk limages`. . 285
lwarpmk: Verifies image references before `lwarpmk limages`. 285
Add: `pdftotextEnc`. 207
Add: `xindyCodepage`. 207
Added early check for disallowed packages. 189
Docs: BibTeX. 123
Docs: Macros in sectioning names. 111
Never load aecompl. 189
Option `IndexLanguage` changed to `xindyLanguage`. 207
Option `xdyFilename` changed to `xindyStyle`. 207
`verse`: Fix: Line spacing. 381
v0.55
`\LWR@LwarpStart`: Fix: Overfull boxes in `lateximages`. 366
`\LWR@floatbegin`: Fix: Float optional args. 466
`\LWR@nullfonts`: Removed extraneous space which appeared in file links. 553
`\phantomsection`: Fix: `\ForceHTMLTOC` with `\phantomsection`. 566
General: 2018/04/26 1
clrdblpg: Added. 660
Fix: `\centering`, etc. for koma-script. 466
Fix: QED symbols in `lateximage`. 593, 850
v0.56
`\LWR@addcdashline`: arydshln: Added. 426
`\LWR@addmulticolvertrulecolor`: Adds support for dashed vertical rules. 434
Adds support for double vertical rules. 434
`\LWR@addtabularhrulecolor`: Adds support for arydshln dashed rules. 427
Adds support for double `\hlines` and `\midrules`. 427
`\LWR@addtabularrulecolors`: Adds support for dashed vertical rules. 428
Adds support for double vertical rules. 428
`\LWR@closeparagraph`: Added support for parnotes. 327
`\LWR@domulticolumn`: Adds support for dashed vertical rules. 436
Adds support for double vertical rules. 436
`\LWR@floatbegin`: Adds a `<class>` per float package style. 466
`\LWR@multicolpartext`: Fix: `\multicolumn` parameters. . . . 432
`\LWR@openparagraph`: Added support for parnotes. 326
`\LWR@parsebarcolumn`: Adds support for double vertical rules. 406
`\LWR@parsecoloncolumn`: arydshln: Added. 407
`\LWR@parsesemicoloncolumn`: arydshln: Added. 407
`\LWR@parsetablecols`: Added array `W` column. 415
`\LWR@printmccoldata`: Added array `W` column. 433
Fix: `\multicolumn` parameters. . . 433
`\LWR@printmccoltype`: Added array `W` column. 431
Adds support for dashed vertical rules. 431
Adds support for double vertical rules. 431
`\LWR@tabledatacolumntag`: Fix: `\morecmidrules` 446
`\LWR@textcurrentfont`: Added `span.textbf`, etc. 554
General: 2018/05/12 1
`*.lwarpmkconf`: Records `--shell-escape`. 242
`lwarp.css`: Added `div.textbf`, etc. 243
`lwarp.css`: Added `span.textbf`, etc. 243
`lwarpmk.conf`: Records `--shell-escape`. 242
arydshln: Added. 394, 598
lua-check-hyphen: Added. 785
paralist: Fixes for `compactenum`, `compactitem`, `compactdesc`. . . 853
parnotes: Added. 854
quoting: Added. 871
tocenter: Added. 947
underscore: Added. 963
lwarpmk: Added `lwarpmk pdftosvg`. 285
lwarpmk: Supports `--shell-escape`. 285
Added `\thinspace`. 559
Docs: **`lwarpmk pdftosvg`**. 91
`LWR@blocktextcurrentfont`: Added `div.textbf`, etc. 555

v0.57
\BlockClassSingle: Improved print/HTML output selection. . . 322
\InlineClass: Improved print/HTML output selection. 322
\LWR@customizeMathJax: MathJax: Supports \footnote, \footnotemark. 346
\LWR@ref@ignorestar: subcaption: Fix: \subref. 461
\LWR@subhyperref: Fix: Text catcodes. 462
\LWR@subhyperreftext: Fix: Text catcodes. 462
\LWR@subsingledollar: Fix: Dynamic inline math expressions. 493, 494, 496
\LWR@vspace: Improved print/HTML output selection. 563
\StartDefiningMath: Added. 306
\boxframe: xcolor: Fix: Colored \boxframe. 982
\colorbox: xcolor: New system for switching print and HTML outputs. 979
\colorboxBlock: xcolor: New system for switching print and HTML outputs. 980
\fboxBlock: Improved print/HTML output selection. 544
\fcolorbox: xcolor: New system for switching print and HTML outputs. 980
\framebox: Improved print/HTML output selection. 543
\href: Fix: Text catcodes. 463
\inlinemathother: Added. 307
\listof: Fix: Provide \l@name if not defined. 476
\makebox: Improved print/HTML output selection. 542
\mathimagename: Added. 490
\mbox: Improved print/HTML output selection. 541
\multicolumnrow: multirow: Improved print/HTML output selection. 820
Improved print/HTML output selection. 442
\newfloat: rotfloat: Added float styles. 879
rotfloat: Fix for listof sideways floats. 879
\packagediagramname: Added. 490
\parbox: Improved print/HTML output selection. 541
\raisebox: Improved print/HTML output selection. 546
\reflectbox: Improved print/HTML output selection. 740
\resizebox: Improved print/HTML output selection. 740
\rotatebox: Improved print/HTML output selection. 738
\rule: Fix: Colored rules. 565
\scalebox: Improved print/HTML output selection. 739
\textcolor: xcolor: New system for switching print and HTML outputs. 978
General: 2018/06/06 1
lwarp.css: Added ruled, boxed, boxruled floats. 243
lwarp.css: Increased float vertical margins. 243
algorithm2e: Added. 582
bigdelim: Improved print/HTML output selection. 614
breakurl: Fix: Text catcodes. 620
colortbl: New system for switching print and HTML outputs. 661
ellipsis: Added \midwordellipsis. 674
errata: Added. 682
float: Added float styles. 703
float: Fix: Do not pre-define \l@name. 703
ltablex: Added. 784
marginnote: Fix: Long optional argument. 792
multirow: Improved print/HTML output selection. 818
register: Added. 874
subcaption: Fix: \subref. 746
trimclip: Added. 957
vowel: Added. 969
xellipsis: Added. 985
xfrac: Improved print/HTML \scalebox control. 987
xltabular: Added. 988
xpiano: Added. 990
lwarpmk: Improved code factoring. 285
lwarpmk: Improved error handling. 285
Docs: Recompiling *lwarpmk* or CSS files. 173
Docs: Recreating the index for lwarp source. 170
New system for switching print and HTML outputs. 227

minipage: Improved print/HTML output selection. 538
BlockClass: Improved print/HTML output selection. 322
fminipage: Improved print/HTML output selection. 544
LWR@BlockClassWP: Improved print/HTML output selection. . . 323
v0.58
\LWR@HTML@caption@begin: Improved print/HTML output selection. . . 470
\LWR@HTML@caption@end: Improved print/HTML output selection. . . 471
\LWR@HTML@ref: Improved print/HTML output selection. 460
\LWR@doindexentry: Adds support for \see, \seealso, \emph, \textbf, etc. 482
\LWR@hyperindexrefnullified: Adds support for \see, \seealso, \emph, \textbf, etc. 482
\LWR@indexitem: Accepts optional arg for repeatindex. 481
\dotfill: Improved print/HTML output selection. 560
\hfill: Improved print/HTML output selection. 560
\hrulefill: Improved print/HTML output selection. 560
\hyperindexref: Adds support for \see, \seealso, \emph, \textbf, etc. 483
\printindex: Fix: Extra \newpage to flush pending \index writes. . . . 789
General: 2018/07/07 1
*.lwarpmkconf: Added option makeindexstyle. 242
*.lwarpmkconf: Added options makeindex and xindy. 242
*.lwarpmkconf: Generated \AtBeginDocument. 242
lwarp.xdy: Requires makeindex.xdy. 281
lwarp.xdy: Supports bold, italic. 281
lwarp_html.ist: Added. 281
lwarpmk.conf: Added option makeindexstyle. 242
lwarpmk.conf: Added options makeindex and xindy. 242
lwarpmk.conf: Generated \AtBeginDocument. 242
array: Improved print/HTML output selection. 597
attachfile2: Added. 602
attachfile: Added. 601
cases: Added. 627
imakeidx: Added. 753
index: Added. 757
intopdf: Added. 759
lwarp-patch-komascript: Modified indexing. 997
lwarp-patch-memoir: Fix for \specialindex. 1020
lwarp-patch-memoir: Fix for multiple indexes. 1020
makeidx: Added. Moved from lwarp core. 789
memoir: Fix for \firsthlline, \lasthline. 443
memoir: Fix for booktabs. 448
pdfpages: Added. 857
pdfx: Added. 861
repeatindex: Added. 876
splitidx: Added. 904
textcomp: Improved print/HTML output selection. 919
lwarpmk: Added makeindex and xindy options. 285
lwarpmk: Added -p option for project name. 285
lwarpmk: Added optional list of names for **lwarpmk printindex** and /cmdslwarpmk htmlindex. . 285
lwarpmk: Glossary generation now uses *makeglossaries*. 285
lwarpmk: **lwarpmk clean** removes all *.ind and *.idx files. 285
Added makeindex option. 208
Added xindy option. 208
Added option makeindexStyle. . 207
Docs: Index, *makeindex*, imakeidx. 125
Docs: Misplaced \omit. 177
Fix: memoir and ccaption. . . . 190
Improved print/HTML output selection. 559
Replaced each \csuse with \@nameuse to force error if undefined. 1
tabbing: Improved print/HTML output selection. 384
v0.59
\LWR@addbaselinemarker: Uses .eps if DVI *latex*. 491
\LWR@includegraphicsb: Fix: Expand filename. 734
Now works with .pdf and .eps filename extensions. 733
\LWR@latexmkcmd: Fix: --shell-escape with *latexmk*. . 237

\LWR@writeconf: Compilation commands now preassigned by lwarp instead of being computed by *lwarpmk*. 241
\[: Fix with \displaymathnormal. . 499
General: 2018/09/07 1
Slunits: Added. 895
accsupp: Added. 578
amsmath: Moved from the lwarp core. 587
asymptote: Added. 600
axessibility: Added. 606
breqn: Added. 621
bxpapersize: Added. 622
canoniclayout: Added. 624
chemformula: Fix for \NMR. 655
draftcopy: Added. 671
epstopdf-base: Improved. 680
epstopdf: Improved. 680
fnbreak: Added. 711
nccfancyhdr: Added. 825
pdftricks: Added. 860
pst-eps: Added. 868
pstricks: Added. 869
units: Added support for MathJax. 963
xunicode: Added. 993
lwarpmk: Added **lwarpmk epstopdf**. 285
lwarpmk: Consolidated compiling options into printlatexcmd and HTMLlatexcmd. 285
lwarpmk: Double insead of single-dashed --shell-escape option. 285
lwarpmk: Error if lwarpmk.conf format changed. 285
lwarpmk: Warning if operating system changed. 285
Added option dvipdfmx. 209
Added option dvipdfm. 209
Added option dvips. 209
Docs: **lwarpmk epstopdf**. 91
File: lwarp_mathjax.txt: Fix: Removed chapter number from tagged non-numeric MathJax equations. 283
File: lwarp_mathjax.txt: Updated to MathJax v2.7.4. 283
picture: Added an alt tag. 535
v0.60
\LWR@clearmidrules: tabular: Fix for midrules. 422
\LWR@parsenormalcolumn: tabular: Improved memory management: Not using xstring. 408
\LWR@tabledatasinglecolumntag: tabular: Improved memory management: Not using xstring. 420
\LWR@tabularendofline: Fix: Slowdown for long tables. 403
General: 2018/09/19 1
tabular: Improved memory management: Global boolean. . 395
tabular: Improved memory management: Not using xstring. 397, 819
2up: Added. 574
booklet: Added. 617
bophook: Added. 619
diagbox: Fix for par tags. 669
draftfigure: Added. 671
fancytabs: Added. 693
fullminipage: Added. 723
grid-system: Added. 741
layaureo: Added. 768
leading: Added. 771
listings: Fix for HTML entities. . . 776
listings: Fix if inside a list. . . 776, 779
thumbs: Added. 930
thumb: Added. 930
widows-and-orphans: Added. . . 972
v0.61
\DeclareGraphicsExtensions: Fix: EPS for DVI LaTeX. 728
\LWR@HTMLLatexCmd: Added HTMLLatexCmd option. 241
Added PrintLatexCmd option. . . 241
\LWR@addcompilecmd: Removed spaces. 237
\LWR@closetabledatacell: Fix: Par tags in tabular. 398
\LWR@hyperindexrefnullified: Made robust, ... 482
\LWR@includegraphicsb: Fix: EPS for DVI LaTeX. 734
Set keys before using filename, for epsfig. 734
\LWRopseq: Added spaces. 204
\RequirePackage: Support up to 20 packages. 219
\inlinemathnormal: Changed name from \StopDynamicMath to \inlinemathnormal. 307
\inlinemathother: Changed name from \StartDynamicMath to \inlinemathother. 307
\listof: Fix: newfloat lists. 476
\lwarpsetup: Added. 205
General: 2018/10/13 1

lwarp.css: Footnotes text align left. 243
lwarp.css: Minipage table and footnotes: tighter margin. 243
chkfloat: Added. 658
cmdtrack: Added. 660
copyrightbox: Added. 663
dprogress: Added. 670
epsfig: Added. 679
lua-visual-debug: Added. 786
pdfprivacy: Added. 859
psfragx: Added. 867
psfrag: Added. 867
pstool: Added. 868
refcheck: Added. 873
srcltx: Added. 905
srctex: Added. 906
supertabular: Fix for caption w/o opt arg. 914
thinsp: Added. 927
threadcol: Added. 928
uspace: Added. 965
vpe: Added. 969
xbmks: Added. 974
xtab: Fix for caption w/o opt arg. 992
Added HTMLLatexCmd option. . . . 208
Added PrintLatexCmd option. . . 208
Docs: \tracinglwarp 223
Docs: HTML entities. 112
Docs: Compiling using custom shell commands. 158
Docs: Fonts. 94
Docs: HTMLDebugComments 100, 223
Docs: Multiple indexes. 182
Don't write configuration files if processing pstool image. 235
Spaces redefined \AtBeginDocument. 559

v0.62

\@partcntformat: Added for ctex. . 354
\@partnameformat: Added for ctex. 354
\InlineClass: Added optional word-processing style. Replaces \LWR@HTMLtextstyle. 322
\LWR@PreloadedPackage: Added. . . 524
\LWR@ProvidesPackagePass: Fix: Unknown option error. 220
\LWR@endofline: Extra space if optional arg. 561
\LWR@filestart: Refactored. 364
\LWR@includegraphicsb: Fix: FormatWP. 734
Fix: Filename expansion. 735
\LWR@isolate: Added. 202
\LWR@textcurrentfont: Added print version. 558
Tracks depth to avoid nesting repeated font changes. 554
\colorboxBlock: Fix: Horiz white space. 980
\fcolorbox: Fix: No longer requires xifthen. 529
\fcolorboxBlock: Fix: Horiz white space. 981
\l@chapter: Don't define if no \chapter. Fix for algorithm2e. . 480
\slshape: Added. 556
\textup: Fixed WP span class. . . . 549
\theHTMLSection: Added. 362
\theHTMLTitleSection: Added. . . . 362
\theHTMLTitleSeparator: Refactored. 362
General: 2018/11/19 1
\textbf and related: Improved font detection. 547
lwarp.css: Added css for xfrac, nicefrac. 243
lwarp.css: Fixed css for \textup. 243
lwarp.css: Reduced margins in titlepage. 243
lwarp_formal.css: Fix: Font for verse. 276
2in1: Added. 574
CJKutf8: Prevented unless xeCJK. 659
CJK: Prevented unless xeCJK. . . 659
asymptote: Improved alt tags. . 600
bitpattern: Added. 616
calc: Fix: Required for print version. 214
chngpage: Fix: Loads lwarp-chngpage. 658
ctexpatch: Added patch. 572
flippdf: Added. 702
musicography: Added. 821
nicefrac: Improved font control and css, honors nice, ugly. . . . 835
notespages: Added. 838
octave: Added. 851
pdfcomment: Added. 856
pdfmarginpar: Added. 857
register: Updated to v1.8. 874
rviewport: Added. 879
semantic-markup: Added. 889
textcomp: Fix conflict with xunicode. 921
tram: Added. 956
twoup: Added. 959
ulem: Improved compatibility with CJKulem. 961

ulem: Now works in a lateximage. 961
unitsdef: Added. 964
units: Improved font control and css, honors loose, tight. 963
xechangebar: Added. 984
xfrac: Improved css. 987
xunicode: Fix conflict with textcomp. 993
Added early checks for CJK, CJKutf8. 189
Docs: asymptote. 145
Docs: miktex-poppler-bin-* 78
Docs: *MiKTeX Console* 74
Docs: Improved MiKTEX install instructions. 74
Docs: UTF-8 locale. 161
File: lwarp_mathjax.txt: Removed inoperable siunitx extension. . . 283
Fix for \em. 551
Fix: Horiz white space. 982
Logos: CSS instead of <sup>, <sub>. 567
Logos: Fix for XƎTEX logo if graphics is not loaded. 567
Logos: Improved CSS. 567
Logos: Made robust. 567
fcolorminipage: Fix: Horiz white space. 982
Fix: No longer requires xifthen. . 531
fminipage: Fix: Horiz white space. . 546
LWR@blocktextcurrentfont: Added print version. 558
v0.63
\LWR@HTMLLatexCmd: ujarticle and related: Compile options. 241
\LWR@LwarpStart: Fixes for xeCJK. 365
\LWR@atbeginverbatim: Fix for xeCJK. 382
\LWR@checkloadbefore: Added. . . . 188
\LWR@checkloadfilename: Added to reduce number of lwarp-* files. 217
\LWR@checkloadnever: Added. 188
\LWR@compileuplatex: Added. 238
\LWR@createautosec: Fix for xeCJK. 352
\LWR@earlyclassloadnever: Added. 189
\LWR@filestart: Fix: Break ligature for luatexko. 364
\LWR@firstoffour: Added. 202
\LWR@htmlclosecomment: Fix: Break ligature for luatexko. 319
\LWR@isolate: Fix for xeCJK. 202
\LWR@notltjloadafter: Added more classes. 187
Added. 187
\LWR@subhtmlelementclass: Fix for xeCJK. 320
\LinkHome: Fix: Print version. 311
\linkhomename: Added. 311
General: 2018/12/03 1
lwarp.css: Added css for vertical writing. 243
lwarp.css: Improved css for mdframed. 243
amsthm, mdframed: Fix for enforced load order. 590
emumitem: v3.6: Nullifiy \DrawEnumitemLabel. 677
everyhook: Fix for bxjs* classes. . 214
geometry: Fix for bxjs* classes. . 213
mdframed: Avoid thin rules. . . . 796
mdframed: Improved font control. 799–801
stfloats: Adapted to ltj* classes. . 906
xpinyin: Added. 990
zhlineskip: Added. 995
Added pTEXsupport. 186
Docs: \linkhomename. 100
Docs: \sidetocname. 102
Fix: Default \LWR@mdfive. 199
Improved titles. 798, 799
pTEX: Encoding. 199
pTEX: Load upquote. 201
pTEX: No newunicodechar. 200
LWR@BlockClassWP: Fix for xeCJK. . 323
v0.64
\LWR@HTMLLatexCmd: utarticle and related: Added. 241
\LWR@checkloadfilename: Prevented bitfield, doublespace, newthm, rplain, si. 217
\LWR@section: Support for ujarticle and related. 357
\enskip: Made robust. 561
\qquad: Made robust. 561
\quad: Made robust. 561
\theHTMLTitleSeparator: Added utarticle and related. 362
General: 2018/12/08 1
addlines: Updated to v0.3. 582
biblatex: Added patch for CTEX. . 613
bsheaders: Added. 622
gmeometric: Added. 727
marginal: Added. 791
rmpage: Added. 877
scrlayer-scrpage: Fixes. 886
scrlayer: Fixes. 885
scrpage2: Added. 886
ujarticle and related: Improved \today. 571

Added utarticle and related. . . . 571
v0.65
\LWR@LwarpEnd: Improved css for page layout. 368
\LWR@LwarpStart: Improved css for page layout. 367
\LWR@PreloadedPackage: \AtBeginDocument to avoid option clashes. 524
\LWR@hyperindexrefnullified: Added \textsi. 482
\LWR@includegraphicsb: graphics: Added \includegraphics alt key. 734, 736
\LWR@newhtmlfile: Error if duplicate file name. 348
Improved css for page layout. 347, 350
\LWR@nullfonts: Added \sishape. . 551
Added \textsi. 551
\LWR@restoreorigformatting: Fix: tabular*. 486
\enskip: Changed to Unicode EN SPACE. 561
\quad: Changed to Unicode EM SPACE. 561
\sishape: Added \sishape. 556
\textsi: Added. 550
General: 2018/12/22 1
lwarp.css: Added \sishape, \textsi. 243
lwarp.css: Improved css for page layout. 243
lwarp.css: Improved css for quotations. 243
lwarp.css: SideTOCto left for improved \marginpars. 243
lwarp_formal.css: SideTOCto left for improved \marginpars. . . . 276
lwarp_sagebrush.css: SideTOCto left for improved \marginpars. . 272
bounddvi: Added. 619
embrac: Added. 674
footnoterange: Added. 718
gentombow: Added. 724
geometry: Fix for bxjs* classes. . 213
graphics: Added \includegraphics alt key. 528, 729, 730, 732
lltjext: Added. 780
multicolrule: Added. 816
multicol: Added \docolaction. . 816
plarydshln: Added. 864
plextarydshln: Added. 865
plextcolortbl: Added. 865
plext: Added. 864
pxatbegshi: Added. 869
pxeveryshi: Added. 869
pxftnright: Added. 870
pxjahyper: Added. 870
tascmac: Added. 917
versonotes: Added. 967
Added early checks for jarticle, tarticle, and related. 189
Fix for \rensuji. 571
Fix space between class and id. . 323
tabular: Added support for plext. . 449
Fix: tabular*. 449
Fix: Rule color. 451
minipage: Refactored to later allow Japanese <t/y> argument. 538
LWR@figcaption: Uses <figurecaption> instead of <figcaption>. 470
v0.66
\@mpfootnotetext: Improved HTML formatting. 338
\IgnoreMinipageWidths: Added, . . 537
\LWR@@footnotetext: Improved HTML formatting. 336
\LWR@LwarpStart: Fix: TOC, LOF, LOT links. 368
\LWR@checkloadfilename: Prevented colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 217
\LWR@closeparagraph: Fix: Combined span, tabular, and lateximage. 327
Improved HTML formatting. . . . 327
\LWR@closeparagraph@br: Factored. 326
\LWR@fboxstyle: Use current text color. 543
\LWR@filenamenoblanks: Fix: Section names detokenized. 343
Fix: Section names with macros. 343
Fix: Section names with percent. 344
Improved file name generation. . 343
Limits filename length. 345
\LWR@findcurrenttextcolor: Fix: Color if xcolor not loaded. . . . 558
\LWR@htmlfileref: No longer use zref. 457
\LWR@htmlsectionfilename: Sanitize underscores. 309
\LWR@includegraphicsb: Improved HTML formatting. 733
\LWR@indentHTML: Added. 316
\LWR@lateximagedepthref: No longer use zref. 457
\LWR@lateximagenumberref: No longer use zref. 457

\LWR@lwarplabel: No longer use zref. 457
\LWR@nameref: No longer use zref. . 457
\LWR@nullfonts: Logos. 554
\LWR@openparagraph: Improved HTML formatting. 326
\LWR@section: Fix: TOC, LOF, LOT links. 358
Improved HTML formatting. 358
\LWR@setexparray: Fix with \par. . 305
\LWR@setref: No longer use zref. . . 457
\LWR@simplifyname: Added. 342
\LWR@startref: No longer use zref. 459
\LWR@stoppars: Improved HTML formatting. 329
\LWR@subhtmlelementclass: Improved HTML formatting. . . 320
\LWR@subhyperrefclass: Improved HTML formatting. 462
\LWR@subinlineimage: Improved HTML formatting. 464
\LWR@writeconf: Added ImagesDirectory and ImagesName. 241
\LinkHome: Fix: Document cross-references. 311
\UseMinipageWidths: Added, ... 537
\fbox: Fix: Removed extra space. . . 543
\hyperindexref: Fix: Long index entries. 483
\minipagefullwidth: Made \global. 537
\rotatebox: Improved HTML formatting. 738
\rule: Improved HTML formatting. . 565
\scalebox: Improved HTML formatting. 739
\textgreater: Made robust. 308
\textless: Made robust. 308
General: 2019/02/08 1
LWR@currentautosec: Fix for LOF, LOTfloat in home page. 354
lwarp.css: Added niceframe. . . 243
lwarp.css: Improved CSS for definition lists. 243
lwarp_formal.css: Improved CSS for table notes. 276
lwarp_one_limage.txt: Image directory and prefix. 282
acronym: Fix for acronym in caption. 580
acronym: No longer uses zref. . . 580
ar: Added. 596
caption: Fix for options clash. . . 221
ed: Added. 673
extramarks: Updated to v3.10. . . 685
fancyhdr: Updated to v3.10. . . . 691
kotexutf: Patch for references. . . 573
memoir: Docs re: version numbers. 153
multicolrule: Updated for v1.2. . 816
nameauth: Added. 823
register: Verified for v1.9. 874
subcaption: Added. 907
tocbasic: Updated to v3.26a. . . . 943
truncate: Added. 959
zref: No longer used. 215
lwarpmk: Added ImagesDirectory and ImagesName. 285
lwarpmk: Fix for **cleanlimages**. . 285
Added early checks for colortab, epsf, hyper, picinpar, picins, sistyle, ucs. 189
Added option ImagesDirectory. 206
Added option ImagesName. 206
Added support for indentfirst. . . 330
Docs: Updated Converting an existing document. 93
Fix: Minipages inside multicols. 815
Improved HTML formatting. . 688, 694
Package dates added where possible. 574
Sanitize filenames. 210
tabular: Fix: Minipages inside tabular. 452
lateximage: Adds \BaseJobname for multiple projects. 517
Improved HTML formatting. 519
minipage: Honor \LWR@forceminipagefullwidth. 539
v0.67
\FilenameNullify: Added. . . . 554, 559
\FilenameSimplify: Added. . . 342, 347
\LWR@doequation: xfakebold: Added support. 505
\LWR@doubledollar: xfakebold: Added support. 499
\LWR@filenamenoblanks: Improved file name generation. 343
\LWR@lookforpackagename: easyReview: Supported. 218
\LWR@nullfonts: Add'l symbols. . . 552
\LWR@simplifycustom: Added. . . . 342
\LWR@subsingledollar: xfakebold: Added support. 493, 497
General: 2019/02/23 1
academicons: Added. 577
bbding: Added. 608
changes: Added. 630
color: Fix for version number. . . 660
dingbat: Added. 670

eurosym: Added. 684
fitbox: Added. 700
fontawesome5: Added. 714
fontawesome: Added. 713
foreign: Added. 719
gloss: Added. 725
karnaugh-map: Added. 759
marvosym: Added. 792
multicap: Added. 814
nomencl: Added. 836
notes: Added. 838
pifont: Added. 863
struktex: Added. 907
textcomp: Nullify in filenames. . 922
typicons: Added. 960
umoline: Added. 962
xfakebold: Added support. . . . 491
xfakebold: Added. 986
xunicode: Nullify in filenames. . 993
AMS environments: Added xfakebold support. 588
eqnarray: xfakebold: Added support. 510, 511
v0.68
\LWR@@footnotetext: Factored for multiple foot boxes. 336
\LWR@checkloadfilename: Prevented alg, algorithmic, fncylab, pdfcprot. 217
\LWR@printpendingfootnotes: Factored for multiple footnote boxes. 339
\LWR@tabular@warpprintonly: Added. 449
General: 2019/03/05 1
bigfoot: Added. 615
fnpara: Added. 712
footnotebackref: Added. 718
hyperref: Fix for options with braces. 745
layouts: Added. 768
listings: Fix for listings v1.7. . . 779
longtable: Improved error handling. 782
manyfoot: Added. 789
niceframe: Added. 836
perpage: Added. 862
showtags: Added. 893
tablefootnote: Added. 915
threeparttablex: Added. 929
threeparttable: Fix for caption type. 928
lwarpmk: Improved error handling if incomplete compile. 285
Prevented alg, algorithmic, fncylab, pdfcprot. 189
tabular: Fix: \warpprintonly inside tabular. 451
v0.69
\LWR@maybetocdata: Added support for tocdata. 477
\framebox: Fix: Handle paren arg. . 543
\hypertoc: Added support for tocdata. 478
\hypertocfloat: Added support for tocdata. 479
\makebox: Fix: Handle paren arg. . . 542
\multicolumnrow: multirow: Error if \multirow without \mrowcell. . 820
General: 2019/03/21 1
array: Fix for \tabularnewline. 597, 783
ctable: Added. 663
eqlist: Added. 681
eqparbox: Added. 681
ftcap: Added. 722
graphics: Warning if using scale option. 730
keyfloat: Updated for v2.00. . . . 762
listliketab: Added. 779
minitoc: Added. 811
multirow: Error if \multirow without \mrowcell. 818
rotfloat: Requires graphicx. . . . 878
supertabular: Fix: Clear caption after use. 914
tabularx: Require array. 916
tabulary: Require array. 916
tocdata: Added. 945
topcapt: Added. 956
xtab: Fix: Clear caption after use. 993
tabular: Error if \multirow without \mrowcell. 450, 452, 454
lateximage: Fix for *pdftotext* errors from font size change. 521
fminipage: Honors \minipagefullwidth. 545
v0.70
\LWR@closeparagraph: Reduced underfull \hbox warnings. 327
\LWR@lookforpackagename: changes: Updated to v3.1.2. 218
\LWR@mathjaxfilename: Added. . . . 332
\LWR@restoreorigformatting: Fix: \& in a lateximage. 485
\MathJaxFilename: Added. 332
\enddocument: If labels changed, require recompile before making limages. 369

\framebox: Fix: Accept long arg. . . 543
\makebox: Fix: Accept long arg. . . . 542
Fix: Ignore width of 0pt. 542
Fix: No width given. 542
General: 2019/04/03 1
autonum: Added. 605
caption: Fix: Extra par tags. 626
changelayout: Added. 628
changes: Updated to v3.1.2. . . . 630
inputtrc: Added. 758
mathtools: Added. 793
metalogox: Added. 806
metalogo: Used in print mode. . 805
textcomp: Fix for \textinterrobang. 919
textpos: Added optional arg to textblock. 923
xunicode: Fix for \textinterrobang. 993
AMS environments: Refactored. . 588
Ensure vector font. 200
File: lwarp_mathjax.txt: Loads autoload-all.js extension. . . . 283
File: lwarp_mathjax.txt: Updated to MathJax v2.7.5. 283
Logos: Improved for metalogox, lateximages. 567
LWR@nestspan: Improved minipage, \parbox inside a span. 317
v0.71
\@mpfootnotetext: Improved HTML formatting. 338
Reduced underfull \hbox warnings. 338
\LWR@closeparagraph: Flush left captions. 327
\LWR@closetabledatacell: Fix: Tabular par tags. 398, 399
\LWR@stoppars: Reduced underfull \hbox warnings. 330
\expandcolspec: Added support for tabular '*' column. 410
General: 2019/04/29 1
chemfig: Updated for v1.4. . . . 633
endfloat: Updated for v2.7. . . . 675
lwarp-common-multimedia: Added. 1024
media9: Added. 803
movie15: Added. 813
multimedia: Added. 817
textpos: Updated for v1.9.1. . . 923
lwarpmk: If wrong lwarpmk.conf version, or wrong OS, displays the print command to recompile. . . 285
Docs: Error testing. 175
Fix: blockquotation tag. 380
Reduced underfull \hbox warnings. 627
v0.72
\LWR@newautopagelabel: Fix: References for xr, xr-hyper. . . . 345
\LWR@printmccoldata: Fix: \multicolumn parameters. . . . 433
\LWR@restoreorigformatting: Use \LWR@formatted for \bfseries, etc. 485
\chapter: Added support for hypbmsec. 360
\ebweight: nfssext-cfr: Added. . . 555
\hypertoc: Fix: References for xr, xr-hyper. 478
\hypertocfloat: Fix: References for xr, xr-hyper. 479
\lgweight: nfssext-cfr: Added. . . 555
\paragraph: Added support for hypbmsec. 361
\part: Added support for hypbmsec. 360
\section: Added support for hypbmsec. 361
\subparagraph: Added support for hypbmsec. 361
\subsection: Added support for hypbmsec. 361
\subsubsection: Added support for hypbmsec. 361
\texteb: nfssext-cfr: Added. 548
\textlg: nfssext-cfr: Added. 548
\textulc: fontaxes: Added. 550
\ulcshape: fontaxes: Added. 556
General: 2019/06/08 1
lwarp.css: Added backnaur. . . . 243
lwarp.css: Removed unneeded support for \sishape, \textsi. . 243
backnaur: Added. 607
boxedminipage2e: Added support for lateximages. 620
changes: Fix references for xr, xr-hyper. 630
fontaxes: Added. 554, 715
gloss: Fix references for xr, xr-hyper. 725
hypbmsec: Added. 744
minibox: Added. 810
nfssext-cfr: Added. 827
nomencl: Fix references for xr, xr-hyper. 837
pdfcrypt: Added. 856
shapepar: Added. 892
slantsc: Added. 901
soulutf8: Fix: Loads soul. 903
tabfigures: Added. 915
xr-hyper: Added. 991

xr: Added. 991
zhlineskip: Updated to v1.0e. . . . 995
Use \LWR@formatted for
\bfseries, etc. 232, 555

Index of Objects

This is an index of macros, environments, booleans, counters, lengths, packages, classes, options, keys, files, and various other programming objects. Each is listed by itself, and also by category. In some cases, they are further subdivided by [class].

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition.

Symbols

\$ ... *491*
\& ... *308*, 7228
\(... 9718
*-images.txt (file) ... *517*
*_html.aux (file) ... *345*, *454*, *455*, *517*
*_html.lof (file) ... *469*
*_html.lot (file) ... *469*
*_html.tex (file) ... *236*
\, ... *112*
--shell-escape (option) ... *94*
\@@@setcpageref ... 10501
\@@@setcref ... 10464
\@@@setcrefrange ... 10478
\@author ... *371*
\@begintheorem ... 6889
\@biblabel ... 9386
\@captype ... 8997
\@chapcntformat ... 6114
\@currentHref ... 8832
\@currentlabelname ... 8691
\@date ... *371*
\@dlbfloat ... 8963
\@donoparitem ... 6915
\@endtheorem ... 6901
\@ensuredmath ... 9728
\@float ... 8963
\@fnsymbol ... 6679
\@footnotetext ... 5689
\@include ... 1140
\@item ... 6928
\@makecaption ... 9018
\@makefnmark ... 5656
\@makefntext ... 5655
\@maketitle ... 56, 6702
\@mklab ... 6909
\@mpfootnotetext ... 5691
\@nbitem ... 6995
\@opargbegintheorem ... 6895
\@partcntformat ... 6115
\@partnameformat ... 6116
\@rowc@lors ... 7587
\@rowcolors ... 7586
\@seccntformat ... 6112
\@starttoc ... 9130
\@textsubscript ... 11260
\@textsuperscript ... 11256
\@title ... *371*
\@wrglossary ... 9327
\@wrindex ... 9316
\[... 9718
\\ ... *560*
$ ... *498*
$$ ... *498*
2in1 (package) ... *574*
2up (package) ... *574*

A

a4 (package) ... *574*
a4wide (package) ... *575*
a5comb (package) ... *575*
abstract (environment) ... 6765
abstract (package) ... *122*, *575*
\abstractname ... *103*, 6764
academicons (package) ... *577*
accsupp (package) ... *578*
acro (package) ... *578*
acronym (package) ... *580*
\addcontentsline ... 9081
addlines (package) ... *582*
\AddSubtitlePublished ... 6730
adjmulticol (package) ... *581*
Adobe (program) ... *70*
\affiliation ... 6582
afterpage (package) ... *582*
algorithm2e (package) ... *582*
algorithmicx (package) ... *151*, *586*
align (environment) ... 65
align* (environment) ... 68
alignat (environment) ... 77
alignat* (environment) ... 80
alltt (package) ... *587*
\AmS ... 11587

amsmath (package) 587
amsthm (package) 590
\and 370
anonchap (package) 594
anysize (package) 595
appendix (package) 123, 595
ar (package) 596
arabicfront (package) 597
array (package) 597
\arrayrulecolor 7594
\arrayrulecolornexttoken 7594
arydshln (package) 598
AsciiDoc (program) 70
AsciiDoctor (program) 70
Asciidoctor-LaTeX (program) 70
asymptote (package) 145, 600
atbegshi (package) 601
attachfile (package) 601
attachfile2 (package) 602
\attrib 154, 380, 966
\attribution 6775
authblk (package) 122, 604
\author 110, 370
autonum (package) 605
autosec 352
axessibility (package) 606
axodraw2 (package) 606

B

babel (package) 155
\backmatter 6090
backnaur (package) 607
backref (package) 608
balance (package) 608
\BaseJobname 4980
BaseJobname (option) 99, 206
bbding (package) 608
\bfseries 11219
biblatex (package) 613
\bibliography 9377
\BibTeX 11580
bibunits (package) 614
bigdelim (package) 151, 614
bigfoot (package) 615
bigstrut (package) 616
bitpattern (package) 616
BlockClass (environment) 5354
\BlockClassSingle 5368
blowup (package) 616
booklet (package) 617
bookmark (package) 617
booktabs (package) 618
boolean:
  CombineHigherDepths 102, 341
  FileSectionNames 103, 309
  FormatEPUB 162, 229
  FormatWP 164, 229
  HTMLDebugComments 103, 224
  LWR@amsmultline 507
  LWR@copiedsidetoc 474
  LWR@doingapar 325
  LWR@doingcmidrule 396
  LWR@doingstartpars 325
  LWR@doingtbrule 395
  LWR@dynamicmath 307
  LWR@emptyatbang 396
  LWR@exitingtabular 444
  LWR@forceminipagefullwidth 537
  LWR@foundmrowcell 396
  LWR@freezethisautoid 468
  LWR@indisplaymathimage 490
  LWR@infloatrow 732
  LWR@intabularmetadata 396
  LWR@isstartingequation 515
  LWR@mathmacro 306
  LWR@minipagefullwidth 537
  LWR@minipagethispar 538
  LWR@opttablecol 411
  LWR@origmathjax 205
  LWR@skipatbang 396
  LWR@skippingmcolrowcell 396
  LWR@skippingmrowcell 396
  LWR@starredlongtable 438
  LWR@startedrow 395
  LWR@tableparcell 396
  LWR@tabularcelladded 395
  LWR@tabularmutemods 445
  LWR@tracinglwarp 223
  LWR@usedmultirow 396
  LWR@validtablecol 411
  LWR@verbtags 382
  LWR@xfakebold 491
  mathjax 205
  usingOSWindows 204
  warpingHTML 205
  warpingprint 205
  WPMarkFloats 165, 229
  WPMarkLOFT 166, 230
  WPMarkMath 166, 230
  WPMarkMinipages 166, 230
  WPMarkTOC 166, 230
  WPTitleHeading 167, 230
bophook (package) 619
bounddvi (package) 619
boxedminipage2e (package) 620
\boxframe 190
breakurl (package) 620
breqn (package) 621
bsheaders (package) 622
BVerbatim (environment) 222
bxpapersize (package) 622

bytefield (package) 623

C

calc (package) 214
cancel (package) 623
canoniclayout (package) 624
capt-of (package) 472
caption (package) 151, 221, 472, 624
\caption@begin 9062
\caption@end 9062
\captionlistentry 9066
\captionof 9097
\CaptionSeparator 9017
cases (package) 627
center (environment) 10253
\centering 10277
\centerline 10296
changebar (package) 628
changelayout (package) 628
changepage (package) 629
changes (package) 630
chappg (package) 632
\chapter 6315
chapterbib (package) 632
chemfig (package) 633
chemformula (package) 634
chemgreek (package) 639
chemmacros (package) 640
chemnum (package) 657
chkfloat (package) 658
chngpage (package) 658
cite (package) 659
CJK (package) 659
CJKutf8 (package) 659
class (key) [Gin] 732
class:
  internet 69
  komascript 153
  memoir 153, 154, 967
\cleardoublepage 11420
\clearpage 11420
cleveref (package) 119, 532
clrdblpg (package) 660
cm-super (package) 94
cmap (package) 95
cmdtrack (package) 660
color (package) 143, 660
\colorbox 73
\colorboxBlock 86, 10361
colortbl (package) 150, 660
CombineHigherDepths (boolean) . . 102, 341
comment (package) 211
\ConTeXt 11575
continue (package) 662
copyrightbox (package) 662
counter:
  FileDepth 102, 341
  FootnoteDepth 103, 335
  footnoteReset 335
  lofdepth 478
  lotdepth 478
  LWR@cellcolordepth 430
  LWR@currentautosec 354
  LWR@externalfilecnt 490
  LWR@hdashedlines 395
  LWR@hlines 395
  LWR@htmlfilenumber 309
  LWR@latestautopage 470
  LWR@lateximagedepth 513
  LWR@lateximagenumber 513
  LWR@LIpage 513
  LWR@midrulecounter 422
  LWR@minipagedepth 536
  LWR@nextautoid 469
  LWR@nextautopage 469
  LWR@nextequation 501
  LWR@prevFileDepth 353
  LWR@previousautopagelabel 345
  LWR@spandepth 324
  LWR@splitstarcopies 410
  LWR@splitstarindex 410
  LWR@starcount 409
  LWR@startingequation 515
  LWR@tablecolspecindex 397
  LWR@tablecolspecwidth 397
  LWR@tableLaTeXcolindex 397
  LWR@tabletotalLaTeXcols 398
  LWR@tabletotalLaTeXcolsnext . . . 398
  LWR@tabularDepth 396
  LWR@tabularpardepth 397
  LWR@thisautoid 467
  LWR@thisautoidWP 468
  SideTOCDepth 102, 476
  tocdepth 102
\cpagerefFor 10500
crop (package) 663
\CSSFilename 103, 106, 5598
ctable (package) 663
\CustomizeMathJax 5934, 5959
cuted (package) 666
cutwin (package) 666

D

\date 110
dblfloatfix (package) 667
dblfnote (package) 667
dcolumn (package) 668
\DeclareGraphicsExtensions 2
dejavu (package) 94
description (environment) 7070
diagbox (package) 668

dingbat (package) *670*
\displaymathnormal . . *140*, *490*, *506*, 9911
\displaymathother . . . *140*, *490*, *506*, 9922
ditaa (package) *161*
\dotfill 11339
\doublerulesepcolor 7596
\doublerulesepcolornexttoken 7596
dprogress (package) *670*
draftcopy (package) *671*
draftfigure (package) *671*
draftwatermark (package) *672*
dvipdfm (option) *96*, *209*
dvipdfmx (option) *96*, *209*
dvips (option) *96*, *209*

E

easy-todo (package) *672*
ebook (package) *673*
\ebweight 11221
ed (package) *673*
ellipsis (package) *674*
embrac (package) *674*
\emph 10870
emptypage (package) *675*
\end@dlbfloat 8980
\end@float 8980
\enddocument 6547
endfloat (package) *675*
endheads (package) *676*
endnotes (package) *123*, *676*
\enlargethispage 11419
\enskip *561*, 11365
enumerate (environment) 7051
enumerate (package) *677*
enumitem (package) *677*
environ (package) *215*
environment:
  fminipage *115*
  lateximage *511*
  picture *535*
  titlepage *109*
  titlingpage *109*
  warpall *108*
  warpHTML *105*, *108*
  warpprint *105*, *108*
environments:
  abstract 6765
  align 65
  align* 68
  alignat 77
  alignat* 80
  BlockClass 5354
  BVerbatim 222
  center 10253
  description 7070
  enumerate 7051
  eqnarray 9971
  equation 9889
  equation* 9897
  fcolorminipage 166, 10402
  flalign 71
  flalign* 74
  flushleft 10269
  flushright 10261
  fminipage 10802
  gather 59
  gather* 62
  itemize 7045
  lateximage 10121, 10248
  list 7015
  longtable 4
  LWR@BlockClassWP 5395
  LWR@blocktextcurrentfont 11209, 11288
  LWR@displaymathnormal 9758
  LWR@displaymathother 9763
  LWR@equationother 9777
  LWR@figcaption 9032
  LWR@nestspan 5205
  math 9757
  minipage 10585
  multline 52
  multline* 55
  picture 10560
  quotation 6797
  quote 6791
  tabbing 6874
  tabular 8541
  thebibliography 9387
  theindex 9292
  titlepage 6599
  titlingpage 14
  verbatim 6864
  verse 2, 6805
  warpall 876
  warpHTML 877
  warpprint 877
epigraph (package) *678*
epsfig (package) *679*
epstopdf (package) *144*, *680*
epstopdf (program) *142*, *527*
epstopdf-base (package) *680*
eqlist (package) *681*
eqnarray (environment) 9971
eqparbox (package) *681*
equation (environment) 9889
equation* (environment) 9897
errata (package) *682*
eso-pic (package) *684*
\etalchar *123*
etoolbox (package) *186*
eurosym (package) *684*

everyhook (package) 214
everypage (package) 685
everyshi (package) 685
\expandcolspec 7470
expl3 (package) 214
extramarks (package) 685

F

fancybox (package) 116, 686
fancyhdr (package) 691
fancyref (package) 692
fancytabs (package) 693
fancyvrb (package) 693
\fbox 115, 10775
\fboxBlock 115, 10784
\fcolorbox 103, 10363
\fcolorboxBlock 126, 10400
fcolorminipage (environment) . 166, 10402
figcaps (package) 699
figsize (package) 699
file:
  *-images.txt 517
  *_html.aux 345, 454, 455, 517
  *_html.lof 469
  *_html.lot 469
  *_html.tex 236
  glyphtounicode.tex 95
  lwarp.css 107, 243
  lwarp.ist 134, 281
  lwarp.xdy 135, 281
  lwarp_baseline_marker.eps 491
  lwarp_baseline_marker.png 491
  lwarp_formal.css 276
  lwarp_mathjax.txt 283
  lwarp_one_limage.cmd 282
  lwarp_sagebrush.css 272
  lwarp_tutorial.txt 79
  lwarpmk.conf 242
  lwarpmk.lua 173
  project.css 107
  project.lwarpmkconf 242
  sample_project.css 107, 280
  tutorial.tex 79
filecontents (package) 214
FileDepth (counter) 102, 341
\FilenameLimit 103, 5800
\FilenameNullify 118, 11180, 11289
\FilenameSimplify 118, 5821, 5960
FileSectionNames (boolean) 103, 309
fitbox (package) 700
fix2col (package) 700
fixme (package) 156, 700
fixmetodonotes (package) 702
flafter (package) 702
\flagverse 967
flalign (environment) 71
flalign* (environment) 74
Flare (program) 70
flippdf (package) 702
float (package) 151, 703
floatflt (package) 704
floatpag (package) 705
floatrow (package) 152, 705
fltrace (package) 710
\flushbottom 5121
flushend (package) 711
flushleft (environment) 10269
flushright (environment) 10261
fminipage (environment) 115, 10802
fnbreak (package) 711
fncychap (package) 711
fnlineno (package) 712
fnpara (package) 712
fnpos (package) 713
fontawesome (package) 713
fontawesome5 (package) 714
fontaxes (package) 715
fontenc (package) 95, 716
fontspec (package) 95
footmisc (package) 716
footnote (package) 717
footnotebackref (package) 718
FootnoteDepth (counter) 103, 335
footnotehyper (package) 718
footnoterange (package) 718
footnoteReset (counter) 335
footnpag (package) 719
\ForceHTMLPage 122, 6065
\ForceHTMLTOC 122, 6071
foreign (package) 719
forest (package) 719
FormatEPUB (boolean) 162, 229
FormatWP (boolean) 164, 229
\framebox 10753
framed (package) 720
FrameMaker (program) 70
\frontmatter 6087
ftcap (package) 722
ftnright (package) 722
fullminipage (package) 723
fullpage (package) 723
fullwidth (package) 723
\fup 11264
\fussy 5123
fwlw (package) 724

G

gather (environment) 59
gather* (environment) 62
GELLMU (program) 69
gentombow (package) 724
geometry (package) 213, 724

gettitlestring (package) 214
[Gin]:
class (key) 732
GladTeX (program) 69
gloss (package) 124, 725
glossaries (package) 124, 725
GlossaryCmd (option) 99, 124, 208, 725
glyphtounicode.tex (file) 95
gmeometric (package) 727
graphics (package) 141, 728
graphicx (package) 141, 740
grffile (package) 143, 740
grid (package) 741
grid-system (package) 741
gridset (package) 741

H

hang (package) 742
hanging (package) 743
Hevea (program) 69
\hfill 11335
\HomeHTMLFilename 4982
HomeHTMLFilename (option) . . 96, 100, 208
\href 8860
\hrulefill 11337
\hskip 112
\hspace 112, 561, 11373, 11403, 11409
htlatex (program) 69
\HTMLAuthor 104, 111, 5635
HTMLDebugComments (boolean) 103, 224
\HTMLDescription 104, 110, 5640
\HTMLentity 4964
\HTMLFilename 4981
HTMLFilename (option) 96, 100, 208
\HTMLFirstPageTop 104, 5586
htmlglossary (option) [lwarpmk] . 124, 725
HTMLIndexCmd (option) 98, 208
\HTMLLanguage 103, 6348
HTMLLatexCmd (option) 96, 158, 208
\HTMLleftmargini (length) 154, 380, 381, 966
\HTMLPageBottom 104, 371, 5592
\HTMLPageTop 104, 5589
\HTMLTitle 103, 110, 5630
\HTMLTitleAfterSection 104, 6371
\HTMLTitleBeforeSection 104, 6366
\HTMLunicode 4972
\HTMLvleftskip (length) 154, 380, 381, 966
hypbmsec (package) 744
hypcap (package) 744
hypdestopt (package) 745
\hyperindexref 9355
hypernat (package) 745
hyperref (package) 120, 461, 745
\hypertoc 9227
\hypertocfloat 9250
hyperxmp (package) 750
hyphenat (package) 751

I

idxlayout (package) 751
\if@titlepage 6577
ifoddpage (package) 752
ifplatform (package) 186
\IgnoreMinipageWidths . . . 115, 536, 10575
ImagesDirectory (option) 206
ImagesName (option) 206
imakeidx (package) 753
\include 1140
\includegraphics 291
indentfirst (package) 330
InDesign (program) 70
index (package) 757
\InlineClass 5379
\inlinemathnormal 140, 489, 4957
\inlinemathother 140, 489, 4953
inputenc (package) 95
inputenx (package) 95
inputtrc (package) 758
internet (class) 69
intopdf (package) 759
itemize (environment) 7045
\itshape 11233

K

karnaugh-map (package) 759
\kern 112
key:
[Gin]:
class 732
keyfloat (package) 153, 762
komascript (class) 153
kotex (package) 157
kvoptions (package) 205

L

\l@chapter 9272
\l@figure 9283
\l@paragraph 9281
\l@part 9271
\l@section 9278
\l@subparagraph 9282
\l@subsection 9279
\l@subsubsection 9280
\l@table 9284
\LaTeX 11529
LaTeX2HTML (program) 69
\LaTeXe 11529
lateximage (environment) 511, 10121, 10248
\LateximageFontScale 10043
\LateximageFontSizeName 10042
latexmk (option) 96, 100, 209
latexmk (program) 159

LatexmkIndexCmd (option) *98*, *208*
LaTeXML (program) *69*
layaureo (package) *768*
layout (package) *768*
layouts (package) *768*
leading (package) *771*
\leftline 10295
length:
\HTMLleftmargini . . *154*, *380*, *381*, *966*
\HTMLvleftskip *154*, *380*, *381*, *966*
\LWR@cmidrulewidth *422*
\LWR@heavyrulewidth *422*
\LWR@lightrulewidth *422*
\LWR@minipageheight *537*
\LWR@minipagewidth *536*
\LWR@tempheight *562*
\LWR@tempraise *562*
\LWR@tempwidth *562*
\LWR@thiscmidrulewidth *422*
\VerbatimHTMLWidth *382*
\vleftmargini *154*, *380*, *966*
\vleftskip *154*, *380*, *966*, *967*
letltxmacro (package) *186*
letterspace (package) *771*
lettrine (package) *772*
\lgweight 11223
LibreOffice (program) *70*
\linebreak 11413
lineno (package) *772*
\LinkHome 5040, 5045
\linkhomename *100*, 5037
Linux (program) *107*, *203*
lips (package) *775*
list (environment) 7015
listings (package) *775*
listliketab (package) *779*
\listof 9184
\listoffigures 9158
\listoftables 9171
lltjext (package) *780*
lmodern (package) *94*, *95*
lofdepth (counter) *478*
longtable (environment) 4
longtable (package) *149*, *780*
lotdepth (counter) *478*
lscape (package) *783*
ltablex (package) *784*
ltcaption (package) *784*
ltxgrid (package) *785*
ltxtable (package) *785*
lua-check-hyphen (package) *785*
lua-visual-debug (package) *786*
luacolor (package) *786*
\LuaLaTeX 11558
LuaLaTeX (program) [requirement] *73*
\LuaTeX 11558
luatodonotes (package) *155*, *786*
lwarp (package) *96*
lwarp-common-multimedia (package) . *1023*
lwarp-patch-komascript (package) . . *997*
lwarp-patch-memoir (package) *999*
lwarp.css (file) *107*, *243*
lwarp.ist (file) *134*, *281*
lwarp.xdy (file) *135*, *281*
lwarp_baseline_marker.eps (file) *491*
lwarp_baseline_marker.png (file) *491*
lwarp_formal.css (file) *276*
lwarp_mathjax.txt (file) *283*
lwarp_one_limage.cmd (file) *282*
lwarp_sagebrush.css (file) *272*
lwarp_tutorial.txt (file) *79*
[lwarpmk]:
htmlglossary (option) *124*, *725*
printglossary (option) *124*, *725*
lwarpmk (option) *99*, *207*, *285*
lwarpmk (program) *173*, *285*
lwarpmk epstopdf (program) *142*, *527*
lwarpmk pdftosvg (program) *142*, *527*
lwarpmk.conf (file) *242*
lwarpmk.lua (file) *173*
\lwarpsetup 740
\LWR@@footnotetext 5659
\LWR@@makebox@align 10709
\LWR@@makebox@paren 10694
\LWR@@printpendingfootnotes 5725
\LWR@addbaselinemarker 9471
\LWR@addcdashline 7865
\LWR@addcmidruletrim 7831
\LWR@addcmidrulewidth 7862
\LWR@addcompilecmd 1517
\LWR@addformatwpalignment 7881
\LWR@addleftmostbartag 7666
\LWR@addmathjax 9826
\LWR@addmulticolvertrulecolor . . . 8140
\LWR@addrulewidth 7836
\LWR@addtabularcellcolor 8009
\LWR@addtabularhrulecolor 7909
\LWR@addtabularrowcolor 7894
\LWR@addtabularrulecolors 7955
\LWR@afterendverbatim 6847
\LWR@amsmathbody 10108
\LWR@amsmathbodynumbered 10114
LWR@amsmultline (boolean) *507*
\LWR@applyxfakebold 9463
\LWR@atbeginverbatim 6828
\LWR@backgroundcolor 36
\LWR@beginhideamsmath 9956
LWR@BlockClassWP (environment) . . . 5395
LWR@blocktextcurrentfont (environment) 11209, 11288

\LWR@botnavigation 5063
LWR@cdashlines 422
LWR@cellcolordepth (counter) 430
\LWR@cellHTMLcolor 7591
\LWR@checkloadbefore 64
\LWR@checkloadfilename 984
\LWR@checkloadnever 83
\LWR@clearmidrules 7746
\LWR@closeparagraph 5493
\LWR@closeparagraph@br 5483
\LWR@closeprevious 5090
\LWR@closetabledatacell 7184
\LWR@cmidrulewidth (length) 422
LWR@colafterspec 398
LWR@colatspec 398
LWR@colbangspec 398
LWR@colbarspec 398
LWR@colbeforespec 398
\LWR@columnHTMLcolor 7589
\LWR@columnspeclookahead 7306
\LWR@compilecmd 1514
\LWR@compileuplatex 1546
\LWR@convertto 675
LWR@copiedsidetoc (boolean) 474
\LWR@copyfile 1175
\LWR@createautosec 6096
LWR@currentautosec (counter) 354
\LWR@currentcss 5597
\LWR@currenttextcolor 11275
\LWR@customizedMathJax 5933
\LWR@customizeMathJax 5939
\LWR@descitem 7057
LWR@displaymathnormal (environment) 9758
LWR@displaymathother (environment) 9763
\LWR@docdashline 7795
\LWR@docmidrule 7779
\LWR@doequation 9839
\LWR@doindexentry 9335
LWR@doingapar (boolean) 325
LWR@doingcmidrule (boolean) 396
LWR@doingstartpars (boolean) 325
LWR@doingtbrule (boolean) 395
\LWR@domulticolumn 8178
\LWR@doubledollar 9672
LWR@dynamicmath (boolean) 307
\LWR@earlyclassloadnever 104
\LWR@earlyloadnever 89
LWR@emptyatbang (boolean) 396
\LWR@endfloatalignment 9013
\LWR@endhideamsmath 9964
\LWR@endofline 11346
\LWR@ensuredoingapar 5459
LWR@equationother (environment) . . 9777
\LWR@equationtag 10094
LWR@exitingtabular (boolean) 444
\LWR@expandableformatted 1237
\LWR@expandableformattedenv 1266
\LWR@expcolspec 7466
LWR@externalfilecnt (counter) 490
\LWR@fboxstyle 10769
LWR@figcaption (environment) 9032
\LWR@filenamenoblanks 5832
\LWR@filestart 6380
\LWR@findcurrenttextcolor 11278
\LWR@findword 981
\LWR@firstoffour 694
\LWR@floatalignment 8999
\LWR@floatalignmentname 8998
\LWR@floatbegin 8931
\LWR@floatend 8965
\LWR@floatstyle 2
\LWR@footnotebox 5654
\LWR@footnotetext 5688
LWR@forceminipagefullwidth (boolean) 537
\LWR@forceminwidth 10758
\LWR@forcenewpage 5110
\LWR@formatted 1222
\LWR@formattedenv 1252
\LWR@formatting 1221
LWR@foundmrowcell (boolean) 396
\LWR@fourthoffour 694
LWR@freezethisautoid (boolean) 468
\LWR@futurenonspacelet 7129
\LWR@FVstyle 56
\LWR@getexparray 4926
\LWR@getmynexttoken 7136
LWR@hdashedlines (counter) 395
\LWR@heavyrulewidth (length) 422
\LWR@hidelatexequation 9812
LWR@hlines (counter) 395
\LWR@HTML@caption@begin 9042
\LWR@HTML@caption@end 9053
\LWR@HTML@Gin@setfile 122
\LWR@HTML@ref 8803
\LWR@htmlblockcomment 5293
\LWR@htmlblocktag 5295
\LWR@HTMLcline 8522
\LWR@htmlclosecomment 5265
\LWR@htmlcomment 5286
\LWR@htmldivclass 5331
\LWR@htmldivclassend 5334
\LWR@htmlelement 5344
\LWR@htmlelementclass 5318
\LWR@htmlelementclassend 5323
\LWR@htmlelementclassline 5337
\LWR@htmlelementend 5347
LWR@htmlfilenumber (counter) 309
\LWR@htmlfileref 8710
\LWR@HTMLhline 8505
\LWR@HTMLLatexCmd 1556

\LWR@htmlmathlabel 9941
\LWR@htmlmulticolumn 8227
\LWR@htmlopencomment 5265
\LWR@htmlrefsectionfilename 5027
\LWR@HTMLsanitize 10046
\LWR@HTMLsanitizeexpand 10063
\LWR@htmlsectionfilename 4992
\LWR@htmlspan 5242
\LWR@htmlspanclass 5250
\LWR@htmltag 5260
\LWR@htmltagc 5195
\LWR@hyperindexrefnullified 9340
\LWR@imagesizebox 121
\LWR@includegraphicsb 140
\LWR@indentHTML 5192
\LWR@indexitem 9304
\LWR@indexnameref 9334
\LWR@indexsubitem 9308
\LWR@indexsubsubitem 9312
LWR@indisplaymathimage (boolean) . . *490*
LWR@infloatrow (boolean) *732*
\LWR@instertatbangcols 7176
LWR@intabularmetadata (boolean) . . . *396*
\LWR@isolate 685
LWR@isstartingequation (boolean) . . *515*
\LWR@itemizeitem 7038
LWR@latestautopage (counter) *470*
LWR@lateximagedepth (counter) *513*
\LWR@lateximagedepthref 8713
LWR@lateximagenumber (counter) *513*
\LWR@lateximagenumberref 8716
\LWR@lateximagesfile 1137
\LWR@latexmkcmd 1532
\LWR@latexmkdvipdfm 1537
\LWR@latexmkvar 1526
\LWR@lightrulewidth (length) *422*
LWR@LIpage (counter) *513*
\LWR@listitem 7000
\LWR@loadafter 23
\LWR@loadbefore 55
\LWR@loadnever 70
\LWR@longtabledatacaptiontag 8238
\LWR@lookforpackagename 1028
\LWR@lwarpconfversion 1508
\LWR@LwarpEnd 6524, 11606
\LWR@lwarplabel 8719
\LWR@LwarpStart 6460, 11606
\LWR@maketitlesetup 33, 6671
\LWR@mathjaxfilename 5608
LWR@mathmacro (boolean) *306*
\LWR@maybenewtablerow 7598
\LWR@maybeprintpendingfootnotes . 5744
\LWR@maybetocdata 9226
LWR@midrulecounter (counter) *422*
LWR@midrules *421*
LWR@minipagedepth (counter) *536*
LWR@minipagefullwidth (boolean) . . . *537*
\LWR@minipageheight (length) *537*
\LWR@minipagestartpars 11353
\LWR@minipagestoppars 11356
LWR@minipagethispar (boolean) *538*
\LWR@minipagewidth (length) *536*
\LWR@multicolother 8081
\LWR@multicolpartext 8075
\LWR@multicolskip 8087
\LWR@multirowborder 3
\LWR@mynexttoken 7128
\LWR@myshorttoc 9107
\LWR@nameref 8707
LWR@nestspan (environment) 5205
\LWR@new@label 8755
\LWR@newautoidanchor 8986
\LWR@newautopagelabel 5925
\LWR@newhtmlfile 5963
LWR@nextautoid (counter) *469*
LWR@nextautopage (counter) *469*
LWR@nextequation (counter) *501*
\LWR@notltjloadafter 42
\LWR@notmemoirloadafter 39
\LWR@nullfonts 11037
\LWR@nullifycomment 975
\LWR@nullifyNoAutoSpacing 8528
\LWR@nulllistfills 7007
\LWR@opacity 120
\LWR@openparagraph 5465
LWR@opttablecol (boolean) *411*
\LWR@orig@setBold 9461
\LWR@orig@unsetBold 9462
\LWR@origcolspec 7170
\LWR@originname 305
\LWR@originnames 312
LWR@origmathjax (boolean) *205*
\LWR@overline 11270
\LWR@parseaftercolumn 7376
\LWR@parseatcolumn 7316
\LWR@parsebangcolumn 7342
\LWR@parsebarcolumn 7387
\LWR@parsebeforecolumn 7365
\LWR@parsecoloncolumn 7412
\LWR@parseDcolumn 7461
\LWR@parsedrequirepackagenames . . . 974
\LWR@parsenormalcolumn 7437
\LWR@parsepcolumn 7449
\LWR@parsesemicoloncolumn 7433
\LWR@parsestarcolumn 7458
\LWR@parsetablecols 7500
\LWR@parsewcolumn 7453
\LWR@patcherror 680
\LWR@patchlists 7076
\LWR@pdfencoding 606

\LWR@popclose 4890
\LWR@PreloadedPackage 10300
LWR@prevFileDepth (counter) 353
LWR@previousautopagelabel (counter) 345
\LWR@printatbang 7641
\LWR@printbartag 7631
\LWR@printcloselist 6907
\LWR@PrintLatexCmd 1556
\LWR@printlength 956
\LWR@printmccoldata 8090
\LWR@printmccoltype 8033
\LWR@printopenlist 6908
\LWR@printpendingfootnotes 5741
\LWR@printpendingmpfootnotes 5753
\LWR@printpercentlength 676
\LWR@printthetitle 6623
\LWR@providelength 672
\LWR@ProvidesPackageDrop 1114
\LWR@ProvidesPackagePass 1099
\LWR@pushclose 4863
\LWR@pushoneclose 6102
\LWR@quickfile 1134
\LWR@ref@ignorestar 8811
\LWR@remembertag 10098
\LWR@replaceEPSSVG 129
\LWR@requesttoc 6517
\LWR@requirepackagenames 973
\LWR@restoreorigaccents 1463
\LWR@restoreorigformatting 9406
\LWR@restoreoriglists 7104
\LWR@rotboxorigin 304
\LWR@rotstyle 112
\LWR@rowHTMLcolor 7590
\LWR@ruleHTMLcolor 7592
\LWR@sanitize 811
\LWR@sanitized 810
\LWR@scalestyle 115
\LWR@secondoffour 694
\LWR@section 6119
\LWR@sectionnumber 6093
\LWR@select@html@hspace 11373
\LWR@select@html@nohspace 11403
\LWR@select@print@hspace 11406
\LWR@setexparray 4917
\LWR@setlatestname 8693
\LWR@setOSWindows 728
\LWR@setref 8701
\LWR@shellescapecmd 1509
\LWR@sidetoc 9200
\LWR@simplifycustom 5820
\LWR@simplifyname 5809
\LWR@singledollar 9697
LWR@skipatbang (boolean) 396
LWR@skippingmcolrowcell (boolean) . . 396
LWR@skippingmrowcell (boolean) 396
LWR@spandepth (counter) 324
\LWR@splitstarcontents 7469
LWR@splitstarcopies (counter) 410
LWR@splitstarindex (counter) 410
LWR@starcount (counter) 409
LWR@starredlongtable (boolean) 438
LWR@startedrow (boolean) 395
LWR@startingequation (counter) 515
\LWR@startingequationtag 10093
\LWR@startnewdepth 6106
\LWR@startpars 5535
\LWR@startref 8768
\LWR@stoppars 5553
\LWR@stripperiod 8692
\LWR@strresult 7168
\LWR@subaddcmidruletrim 7818
\LWR@subaddtabularcellcolor 8003
\LWR@subcdashline 7782
\LWR@subcmidrule 7764
\LWR@subhtmlelementclass 5300
\LWR@subhyperref 8837
\LWR@subhyperrefclass 8850
\LWR@subhyperreftext 8845
\LWR@subinlineimage 8910
\LWR@sublabel 8732
\LWR@subnewref 8797
\LWR@subsingledollar 9507
\LWR@subtableofcontents 9120
\LWR@subtabularhtmlcolumns 8310
\LWR@syncmathjax 9792
LWR@tablecolspec 397
LWR@tablecolspecindex (counter) . . . 397
LWR@tablecolspecwidth (counter) . . . 397
\LWR@tabledatacolumntag 8401
\LWR@tabledatasinglecolumntag . . . 7680
LWR@tableLaTeXcolindex (counter) . . . 397
LWR@tableparcell (boolean) 396
LWR@tabletotalLaTeXcols (counter) . . 398
LWR@tabletotalLaTeXcolsnext (counter) 398
\LWR@tabular@warpprintonly 8524
LWR@tabularcelladded (boolean) 395
LWR@tabularDepth (counter) 396
\LWR@tabularendofline 7286
\LWR@tabularfinishrow 7240
\LWR@tabularhtmlcolumns 8320
\LWR@tabularleftedge 7671
LWR@tabularmutemods (boolean) 445
LWR@tabularpardepth (counter) 397
\LWR@tdaddstyle 7806
\LWR@tdendstyles 7812
\LWR@tdstartstyles 7805
\LWR@tempcolor 11276
\LWR@tempcolortwo 11276
\LWR@tempheight (length) 562
\LWR@tempraise (length) 562

\LWR@tempwidth (length) *562*
\LWR@textcurrentcolor 19, 11281
\LWR@textcurrentfont 11187, 11287
\LWR@thirdoffour 694
LWR@thisautoid (counter) *467*
LWR@thisautoidWP (counter) *468*
\LWR@thiscmidrulewidth (length) *422*
\LWR@thiscolspec 7679
\LWR@thisfilename 5803
\LWR@thisnewfilename 5808
\LWR@titlingmaketitle 83, 6722
\LWR@topnavigation 5060
\LWR@traceinfo 1203
LWR@tracinglwarp (boolean) *223*
LWR@trimlrules *421*
LWR@trimrrules *422*
\LWR@unknownengine 1521
LWR@usedmultirow (boolean) *396*
LWR@validtablecol (boolean) *411*
LWR@verbtags (boolean) *382*
\LWR@vspace 11410
\LWR@WPcell 7877
\LWR@writeconf 1658
\LWR@xcolorrowHTMLcolor 7588
LWR@xfakebold (boolean) *491*
\LWRopquote 723
\LWRopseq 724
\LWRPrintStack 5068
\LWRsetnextfloat 9026
\LyX 11602

M

Mac OS (program) *107*, *203*
Madcap (program) *70*
magaz (package) *788*
\mainmatter 6083
make (program) *161*
\makebox 10718
makeidx (package) *136*, *789*, *943*, *944*
\MakeIndex 11580
makeindex (option) *96*, *100*, *208*
makeindex (program) *134*
makeindexStyle (option) *96*, *134*, *207*
\makelabel *386*
\maketitle 47, *109*, 6683
manyfoot (package) *789*
marginal (package) *791*
marginfit (package) *791*
marginfix (package) *791*
marginnote (package) *792*
\marginpar *114*, *340*, 5765
\marginparBlock *114*, *340*, 5776, 5793
\markboth 5118
\markright 5119
marvosym (package) *792*
math (environment) 9757
\mathimagename *104*, 9453
MathJax (program) *138*, *139*, *488*
MathJax (program) [requirement] *73*
mathjax (boolean) *205*
mathjax (option) *96*, *100*, *206*
\MathJaxFilename *103*, 5609
mathsvg (option) *96*, *100*, *206*
mathtools (package) *793*
\mbox 10691
mcaption (package) *793*
\mcolrowcell 8476
mdframed (package) *117*, *794*
\mdseries 11217
media9 (package) *145*, *803*
memhfixc (package) *805*
memoir (class) *153*, *154*, *967*
metalogo (package) *805*
metalogox (package) *806*
mhchem (package) *806*
microtype (package) *212*, *809*
midfloat (package) *810*
midpage (package) *810*
\MiKTeX 11600
minibox (package) *810*
minipage (environment) 10585
\minipagefullwidth 10573
minitoc (package) *811*
morefloats (package) *811*
moreverb (package) *811*
movie15 (package) *145*, *813*
mparhack (package) *814*
\mrowcell 8473
MS-Windows (program) *107*, *203*
multicap (package) *814*
multicol (package) *815*
multicolrule (package) *816*
\multicolumnrow 40, 8343
multimedia (package) *145*, *816*
\multirow *818*
multirow (package) *817*
multitoc (package) *821*
multline (environment) 52
multline* (environment) 55
musicography (package) *821*

N

nameauth (package) *823*
\Nameref 8829
\nameref 8820
nameref (package) *824*
natbib (package) *824*
nccfancyhdr (package) *825*
needspace (package) *826*
newclude (package) *155*
\newfloat 4
newfloat (package) *215*

\newline 11344
\newpage 11341
\newtheorem *384*
newtxmath (package) *141*
newunicodechar (package) *95*
nextpage (package) *826*
nfssext-cfr (package) *827*
nicefrac (package) *141*, *835*
niceframe (package) *836*
\noalign 8494
\nolinebreak 11414
\nolinkurl 8876
nomencl (package) *125*, *836*
nonfloat (package) *837*
nonumonpart (package) *837*
\nopagebreak 11418
\nopagecolor 72
nopageno (package) *837*
\normalfont 11252
\normalmarginpar 5790
notes (package) *838*
notespages (package) *838*
nowidow (package) *839*
ntheorem (package) *141*, *839*
\numberline 9221
numindex (option) [tocbibind] *137*, *944*

O

octave (package) *851*
OpenOffice (program) *70*
option:
  --shell-escape *94*
  [lwarpmk]:
    htmlglossary *124*, *725*
    printglossary *124*, *725*
  [tocbibind]:
    numindex *137*, *944*
  [tocloft]:
    titles *123*
  BaseJobname *99*, *206*
  dvipdfm *96*, *209*
  dvipdfmx *96*, *209*
  dvips *96*, *209*
  GlossaryCmd *99*, *124*, *208*, *725*
  HomeHTMLFilename *96*, *100*, *208*
  HTMLFilename *96*, *100*, *208*
  HTMLIndexCmd *98*, *208*
  HTMLLatexCmd *96*, *158*, *208*
  ImagesDirectory *206*
  ImagesName *206*
  latexmk *96*, *100*, *209*
  LatexmkIndexCmd *98*, *208*
  lwarpmk *99*, *207*, *285*
  makeindex *96*, *100*, *208*
  makeindexStyle *96*, *134*, *207*
  mathjax *96*, *100*, *206*
  mathsvg *96*, *100*, *206*
  OSWindows *99*, *107*, *203*, *207*
  pdftotextEnc *99*, *207*
  PrintIndexCmd *96*, *208*
  PrintLatexCmd *96*, *158*, *208*
  warpHTML *99*, *206*
  warpprint *99*, *205*
  xindy *96*, *100*, *208*
  xindyCodepage *96*, *207*
  xindyLanguage *96*, *207*
  xindyStyle *96*, *135*, *207*
\OSPathSymbol 727
OSWindows (option) *99*, *107*, *203*, *207*
overpic (package) *145*, *852*

P

package:
  2in1 . . . . . *574*
  2up *574*
  a4 . . . . . *574*
  a4wide *575*
  a5comb *575*
  abstract *122*, *575*
  academicons *577*
  accsupp *578*
  acro *578*
  acronym *580*
  addlines *582*
  adjmulticol *581*
  afterpage *582*
  algorithm2e *582*
  algorithmicx *151*, *586*
  alltt *587*
  amsmath *587*
  amsthm *590*
  anonchap *594*
  anysize *595*
  appendix *123*, *595*
  ar *596*
  arabicfront *597*
  array *597*
  arydshln *598*
  asymptote *145*, *600*
  atbegshi *601*
  attachfile *601*
  attachfile2 . . . . . *602*
  authblk *122*, *604*
  autonum *605*
  axessibility *606*
  axodraw2 . . . . . *606*
  babel *155*
  backnaur *607*
  backref *608*
  balance *608*
  bbding *608*
  biblatex *613*

bibunits 614
bigdelim 151, 614
bigfoot 615
bigstrut 616
bitpattern 616
blowup 616
booklet 617
bookmark 617
booktabs 618
bophook 619
bounddvi 619
boxedminipage2e 620
breakurl 620
breqn 621
bsheaders 622
bxpapersize 622
bytefield 623
calc 214
cancel 623
canoniclayout 624
capt-of 472
caption 151, 221, 472, 624
cases 627
changebar 628
changelayout 628
changepage 629
changes 630
chappg 632
chapterbib 632
chemfig 633
chemformula 634
chemgreek 639
chemmacros 640
chemnum 657
chkfloat 658
chngpage 658
cite 659
CJK 659
CJKutf8 659
cleveref 119, 532
clrdblpg 660
cm-super 94
cmap 95
cmdtrack 660
color 143, 660
colortbl 150, 660
comment 211
continue 662
copyrightbox 662
crop 663
ctable 663
cuted 666
cutwin 666
dblfloatfix 667
dblfnote 667
dcolumn 668
dejavu 94
diagbox 668
dingbat 670
ditaa 161
dprogress 670
draftcopy 671
draftfigure 671
draftwatermark 672
easy-todo 672
ebook 673
ed 673
ellipsis 674
embrac 674
emptypage 675
endfloat 675
endheads 676
endnotes 123, 676
enumerate 677
enumitem 677
environ 215
epigraph 678
epsfig 679
epstopdf 144, 680
epstopdf-base 680
eqlist 681
eqparbox 681
errata 682
eso-pic 684
etoolbox 186
eurosym 684
everyhook 214
everypage 685
everyshi 685
expl3 214
extramarks 685
fancybox 116, 686
fancyhdr 691
fancyref 692
fancytabs 693
fancyvrb 693
figcaps 699
figsize 699
filecontents 214
fitbox 700
fix2col 700
fixme 156, 700
fixmetodonotes 702
flafter 702
flippdf 702
float 151, 703
floatflt 704
floatpag 705
floatrow 152, 705
fltrace 710

flushend 711
fnbreak 711
fncychap 711
fnlineno 712
fnpara 712
fnpos 713
fontawesome 713
fontawesome5 714
fontaxes 715
fontenc 95, 716
fontspec 95
footmisc 716
footnote 717
footnotebackref 718
footnotehyper 718
footnoterange 718
footnpag 719
foreign 719
forest 719
framed 720
ftcap 722
ftnright 722
fullminipage 723
fullpage 723
fullwidth 723
fwlw 724
gentombow 724
geometry 213, 724
gettitlestring 214
gloss 124, 725
glossaries 124, 725
gmeometric 727
graphics 141, 728
graphicx 141, 740
grffile 143, 740
grid 741
grid-system 741
gridset 741
hang 742
hanging 743
hypbmsec 744
hypcap 744
hypdestopt 745
hypernat 745
hyperref 120, 461, 745
hyperxmp 750
hyphenat 751
idxlayout 751
ifoddpage 752
ifplatform 186
imakeidx 753
indentfirst 330
index 757
inputenc 95
inputenx 95
inputtrc 758
intopdf 759
karnaugh-map 759
keyfloat 153, 762
kotex 157
kvoptions 205
layaureo 768
layout 768
layouts 768
leading 771
letltxmacro 186
letterspace 771
lettrine 772
lineno 772
lips 775
listings 775
listliketab 779
lltjext 780
lmodern 94, 95
longtable 149, 780
lscape 783
ltablex 784
ltcaption 784
ltxgrid 785
ltxtable 785
lua-check-hyphen 785
lua-visual-debug 786
luacolor 786
luatodonotes 155, 786
lwarp 96
lwarp-common-multimedia 1023
lwarp-patch-komascript 997
lwarp-patch-memoir 999
magaz 788
makeidx 136, 789, 943, 944
manyfoot 789
marginal 791
marginfit 791
marginfix 791
marginnote 792
marvosym 792
mathtools 793
mcaption 793
mdframed 117, 794
media9 . . . . . 145, 803
memhfixc 805
metalogo 805
metalogox 806
mhchem 806
microtype 212, 809
midfloat 810
midpage 810
minibox 810
minitoc 811
morefloats 811

moreverb 811
movie15 . . . . . 145, 813
mparhack 814
multicap 814
multicol 815
multicolrule 816
multimedia 145, 816
multirow 817
multitoc 821
musicography 821
nameauth 823
nameref 824
natbib 824
nccfancyhdr 825
needspace 826
newclude 155
newfloat 215
newtxmath 141
newunicodechar 95
nextpage 826
nfssext-cfr 827
nicefrac 141, 835
niceframe 836
nomencl 125, 836
nonfloat 837
nonumonpart 837
nopageno 837
notes 838
notespages 838
nowidow 839
ntheorem 141, 839
octave 851
overpic 145, 852
pagegrid 853
pagenote 123, 853
pagesel 853
paralist 853
parnotes 854
parskip 855
pbox 855
pdfcomment 856
pdfcrypt 856
pdflscape 856
pdfmarginpar 857
pdfpages 857
pdfprivacy 859
pdfrender 860
pdfsync 860
pdftricks 144, 860
pdfx 861
perltex 160
perpage 861
pfnote 862
phfqit 863
pifont 863
placeins 864
plarydshln 864
plext 864
plextarydshln 865
plextcolortbl 865
polyglossia 155
prelim2e 866
prettyref 866
preview 866
printlen 215
psfrag 144, 867
psfragx 867
pst-eps 868
pstool 145, 868
pstricks 144, 869
pxatbegshi 869
pxeveryshi 869
pxftnright 870
pxjahyper 870
pythontex 160
quotchap 870
quoting 871
ragged2e 872
realscripts 872
refcheck 873
refcount 215
register 874
relsize 113, 874
repeatindex 876
resizegather 877
rmpage 877
romanbar 877
romanbarpagenumber 877
rotating 878
rotfloat 878
rterface 160
rviewport 879
sagetex 160
savetrees 879
scalefnt 880
schemata 880
scrextend 880
scrhack 883
scrlayer 883
scrlayer-notecolumn 885
scrlayer-scrpage 885
scrpage2 886
section 887
sectionbreak 888
sectsty 889
semantic-markup 889
setspace 890
shadow 891
shapepar 892
showidx 892

showkeys 892
showtags 893
sidecap 893
sidenotes 894
SIunits 895
siunitx 141, 525, 896
slantsc 901
soul 901
soulpos 903
soulutf8 903
splitidx 904
srcltx 905
srctex 906
stabular 906
stfloats 906
struktex 907
subcaption 151, 907
subfig 152, 908
subfigure 913
supertabular 150, 913
sympytex 160
syntonly 915
tabfigures 915
tablefootnote 915
tabls 916
tabularx 916
tabulary 916
tascmac 917
textarea 919
textcomp 95, 113, 919
textfit 922
textpos 923
theorem 924
thinsp 927
threadcol 928
threeparttable 928
threeparttablex 150, 929
thumb 930
thumbs 930
tikz 143, 930
titleps 932
titleref 935
titlesec 935
titletoc 937
titling 122, 938
tocbasic 943
tocbibind 136, 137, 943, 944
tocdata 945
tocenter 947
tocloft 123, 137, 594, 947
tocstyle 953
todo 953
todonotes 155, 954
topcapt 956
tram 956
transparent 957
trimclip 957
trivfloat 151, 958
truncate 959
turnthepage 959
twoup 959
typearea 960
typicons 960
ulem 961
umoline 962
underscore 963
units 141, 963
unitsdef 964
upref 965
url 120, 965
uspace 965
varioref 119
varwidth 216
verbatim 215
verse 154, 966, 967
versonotes 967
vertbars 968
vmargin 968
vowel 969
vpe 969
vwcol 969
wallpaper 972
watermark 972
widows-and-orphans 972
wrapfig 973
xbmks 974
xcolor 143, 528, 974
xechangebar 984
xellipsis 985
xetexko-vertical 985
xfakebold 986
xfrac 986
xifthen 215
xltabular 988
xltxtra 989
xmpincl 990
xparse 156, 213
xpatch 186
xpiano 990
xpinyin 990
xr 991
xr-hyper 991
xstring 215
xtab 150, 992
xunicode 993
xurl 994
xy 994
zhlineskip 995
zwpagelayout 996
\packagediagramname 105, 9454

\pagebreak 11415
\pagecolor 71
pagegrid (package) *853*
pagenote (package) *123*, *853*
\pagenumbering 5124
\pageref 8815
\pagerefPageFor 8814
pagesel (package) *853*
\pagestyle 5116
Pandoc (program) *70*
\paragraph 6340
paralist (package) *853*
\parbox 10682
parnotes (package) *854*
\parsemulticolumnalignment 8125
parskip (package) *855*
\part 6307
pbox (package) *855*
pdfcomment (package) *856*
pdfcrop (program) [requirement] *73*
pdfcrypt (package) *856*
pdfLaTeX (program) [requirement] *73*
pdflscape (package) *856*
pdfmarginpar (package) *857*
pdfpages (package) *857*
pdfprivacy (package) *859*
pdfrender (package) *860*
pdfseparate (program) [requirement] *73*, *78*
pdfsync (package) *860*
pdftocairo (program) *142*, *527*
pdftocairo (program) [requirement] *73*, *78*
pdftotext (program) [requirement] . *73*, *78*
pdftotextEnc (option) *99*, *207*
pdftricks (package) *144*, *860*
pdfx (package) *861*
perl (program) [requirement] *78*
perltex (package) *160*
perpage (package) *861*
pfnote (package) *862*
\phantomsection 11478
phfqit (package) *863*
picture (environment) *535*, 10560
pifont (package) *863*
placeins (package) *864*
plarydshln (package) *864*
Plastex (program) *69*
plext (package) *864*
plextarydshln (package) *865*
plextcolortbl (package) *865*
\PN@parnotes@auto 5464
polyglossia (package) *155*
\postchaptername 6291
\postpartname 6289
\postsectionname 6293
\prechaptername 6291
prelim2e (package) *866*
\prepartname 6289
\presectionname 6293
prettyref (package) *866*
preview (package) *866*
\printauthor *371*, 6631, 6650
\printdate *371*, 6642, 6652
printglossary (option) [lwarpmk] *124*, *725*
\printindex 2
PrintIndexCmd (option) *96*, *208*
PrintLatexCmd (option) *96*, *158*, *208*
printlen (package) *215*
\printthanks *370*, *373*
\printtitle *371*, 6615, 6649
program:
  [requirement]:
    LuaLaTeX *73*
    MathJax *73*
    pdfcrop *73*
    pdfLaTeX *73*
    pdfseparate *73*, *78*
    pdftocairo *73*, *78*
    pdftotext *73*, *78*
    perl *78*
    XeLaTeX *73*
  Adobe *70*
  AsciiDoc *70*
  AsciiDoctor *70*
  Asciidoctor-LaTeX *70*
  epstopdf *142*, *527*
  Flare *70*
  FrameMaker *70*
  GELLMU *69*
  GladTeX *69*
  Hevea *69*
  htlatex *69*
  InDesign *70*
  LaTeX2HTML *69*
  latexmk *159*
  LaTeXML *69*
  LibreOffice *70*
  Linux *107*, *203*
  lwarpmk *173*, *285*
  lwarpmk epstopdf *142*, *527*
  lwarpmk pdftosvg *142*, *527*
  Mac OS *107*, *203*
  Madcap *70*
  make *161*
  makeindex *134*
  MathJax *138*, *139*, *488*
  MS-Windows *107*, *203*
  OpenOffice *70*
  Pandoc *70*
  pdftocairo *142*, *527*
  Plastex *69*

TeX2page 69
TeX4ht 69
TeXMaths 166
TtH 69
Unix 107, 203
Windows 107, 203
Word 70
xindy 135
project.css (file) 107
project.lwarpmkconf (file) 242
psfrag (package) 144, 867
psfragx (package) 867
pst-eps (package) 868
pstool (package) 145, 868
pstricks (package) 144, 869
pxatbegshi (package) 869
pxeveryshi (package) 869
pxftnright (package) 870
pxjahyper (package) 870
pythontex (package) 160

Q

\qquad 561, 11364
\quad 561, 11359
quotation (environment) 6797
quotchap (package) 870
quote (environment) 6791
quoting (package) 871

R

ragged2e (package) 872
\raggedbottom 5120
\raggedleft 10283
\raggedright 10289
\raisebox 10863
realscripts (package) 872
\ref 8803
refcheck (package) 873
refcount (package) 215
\reflectbox 366
register (package) 874
relsize (package) 113, 874
repeatindex (package) 876
[requirement]:
LuaLaTeX (program) 73
MathJax (program) 73
pdfcrop (program) 73
pdfLaTeX (program) 73
pdfseparate (program) 73, 78
pdftocairo (program) 73, 78
pdftotext (program) 73, 78
perl (program) 78
XeLaTeX (program) 73
\RequirePackage 1061
\resizebox 375
resizegather (package) 877
\ResumeTabular 8388
\reversemarginpar 5789
\rightline 10297
\rmfamily 11225
rmpage (package) 877
romanbar (package) 877
romanbarpagenumber (package) 877
\rotatebox 324
rotating (package) 878
rotfloat (package) 878
\rowcolor 7593
\rownum 7585
rterface (package) 160
\rule 11422
rviewport (package) 879

S

sagetex (package) 160
sample_project.css (file) 107, 280
savetrees (package) 879
\sb 11254
\scalebox 347
scalefnt (package) 880
schemata (package) 880
scrextend (package) 880
scrhack (package) 883
scrlayer (package) 883
scrlayer-notecolumn (package) 885
scrlayer-scrpage (package) 885
scrpage2 (package) 886
\scshape 11235
\section 6331
section (package) 887
sectionbreak (package) 888
sectsty (package) 889
semantic-markup (package) 889
\SetHTMLFileNumber 4983
setspace (package) 890
\sffamily 11227
\sfrac 986
shadow (package) 891
shapepar (package) 892
showidx (package) 892
showkeys (package) 892
showtags (package) 893
sidecap (package) 893
sidenotes (package) 894
SideTOCDepth (counter) 102, 476
\sidetocname 102, 9197
\simplechapterdelim 6113
\sishape 11242
SIunits (package) 895
siunitx (package) 141, 525, 896
slantsc (package) 901
\sloppy 5122
\slshape 11250

soul (package) 901
soulpos (package) 903
soulutf8 (package) 903
\sp 11253
splitidx (package) 904
srcltx (package) 905
srctex (package) 906
stabular (package) 906
\StartDefiningMath 4941
\StartDefiningTabulars 4931
stfloats (package) 906
\StopDefiningMath 4945
\StopDefiningTabulars 4935
struktex (package) 907
subcaption (package) 151, 907
subfig (package) 152, 908
subfigure (package) 913
\subparagraph 6343
\subsection 6334
\subsubsection 6337
supertabular (package) 150, 913
sympytex (package) 160
syntonly (package) 915

T

tabbing (environment) 6874
tabfigures (package) 915
tablefootnote (package) 915
\tableofcontents 104, 9139
tabls (package) 916
tabular (environment) 8541
\TabularMacro 8386
tabularx (package) 916
tabulary (package) 916
tascmac (package) 917
\TeX 11516
TeX2page (program) 69
TeX4ht (program) 69
TeXMaths (program) 166
textarea (package) 919
\textbf 10890
\textcolor 48
textcomp (package) 95, 113, 919
\texteb 10900
textfit (package) 922
\textgreater 4976
\textit 10960
\textless 4974
\textlg 10910
\textmd 10880
\textnormal 11019
textpos (package) 923
\textrm 10920
\textsc 10970
\textsf 10930
\textsi 10990
\textsl 11009
\textsubscript 11257
\textsuperscript 11255
\texttt 10940
\textulc 10980
\textup 10950
\tfl@chapter@fix 958
\thanks 110
\thanksmarkseries 91
\theauthor 371
thebibliography (environment) 9387
\thedate 371
\theHTMLSection 6377
\theHTMLTitleSection 6376
\theHTMLTitleSeparator 6353
theindex (environment) 9292
\thempfootnote 5722
theorem (package) 924
\thetitle 371
thinsp (package) 927
\thispagestyle 5117
threadcol (package) 928
threeparttable (package) 928
threeparttablex (package) 150, 929
thumb (package) 930
thumbs (package) 930
tikz (package) 143, 930
\title 109, 5619
titlepage (environment) 109, 6599
titleps (package) 932
titleref (package) 935
titles (option) [tocloft] 123
titlesec (package) 935
titletoc (package) 937
titling (package) 122, 938
titlingpage (environment) 14, 109
tocbasic (package) 943
[tocbibind]:
    numindex (option) 137, 944
tocbibind (package) . . . 136, 137, 943, 944
tocdata (package) 945
tocdepth (counter) 102
tocenter (package) 947
[tocloft]:
    titles (option) 123
tocloft (package) 123, 137, 594, 947
tocstyle (package) 953
todo (package) 953
todonotes (package) 155, 954
topcapt (package) 956
\tracinglwarp 180, 1202
tram (package) 956
transparent (package) 957
trimclip (package) 957
trivfloat (package) 151, 958

truncate (package) 959
\ttfamily 11229
TtH (program) 69
turnthepage (package) 959
tutorial.tex (file) 79
twoup (package) 959
typearea (package) 960
typicons (package) 960

U

\ulcshape 11237
ulem (package) 961
umoline (package) 962
\underline 11265
underscore (package) 963
units (package) 141, 963
unitsdef (package) 964
Unix (program) 107, 203
\up 11263
upref (package) 965
\upshape 11231
\url 8893
url (package) 120, 965
\UseMinipageWidths 115, 536, 10574
usingOSWindows (boolean) 204
uspace (package) 965

V

varioref (package) 119
varwidth (package) 216
verbatim (environment) 6864
verbatim (package) 215
\VerbatimHTMLWidth (length) 382
\verbatiminput 6856
verse (environment) 2, 6805
verse (package) 154, 966, 967
versonotes (package) 967
vertbars (package) 968
\vleftmargini (length) 154, 380, 966
\vleftskip (length) 154, 380, 966, 967
vmargin (package) 968
vowel (package) 969
vpe (package) 969
vwcol (package) 969

W

wallpaper (package) 972
warpall (environment) 108, 876
warpHTML (environment) 105, 108, 877
warpHTML (option) 99, 206
\warpHTMLonly 105, 109, 867
warpingHTML (boolean) 205
warpingprint (boolean) 205
warpprint (environment) . . . 105, 108, 877
warpprint (option) 99, 205
\warpprintonly 105, 108, 866
watermark (package) 972
widows-and-orphans (package) 972
Windows (program) 107, 203
Word (program) 70
WPMarkFloats (boolean) 165, 229
WPMarkLOFT (boolean) 166, 230
WPMarkMath (boolean) 166, 230
WPMarkMinipages (boolean) 166, 230
WPMarkTOC (boolean) 166, 230
WPTitleHeading (boolean) 167, 230
wrapfig (package) 973

X

xbmks (package) 974
xcolor (package) 143, 528, 974
xechangebar (package) 984
\XeLaTeX 11563
XeLaTeX (program) [requirement] 73
xellipsis (package) 985
\XeTeX 11563
xetexko-vertical (package) 985
xfakebold (package) 986
xfrac (package) 986
\xfracHTMLfontsize 3
xifthen (package) 215
xindy (option) 96, 100, 208
xindy (program) 135
xindyCodepage (option) 96, 207
xindyLanguage (option) 96, 207
xindyStyle (option) 96, 135, 207
xltabular (package) 988
xltxtra (package) 989
xmpincl (package) 990
xparse (package) 156, 213
xpatch (package) 186
xpiano (package) 990
xpinyin (package) 990
xr (package) 991
xr-hyper (package) 991
xstring (package) 215
xtab (package) 150, 992
xunicode (package) 993
xurl (package) 994
xy (package) 994

Z

zhlineskip (package) 995
zwpagelayout (package) 996

General Index

This is an index of instructions and concepts. Look here when wondering how to do something, and check the Troubleshooting Index when something goes wrong.

Symbols

\, ... 112
~ 112

A

accents
  in section & file names 351
adapting
  class 173
  document 93
  package 171
affiliation
  multiple authors 121
algorithmicx
  with newfloat, trivfloat 958
array
  mhchem 807
audio 145
author
  HTML meta tag 111, 333
  multiple 121

B

baseline
  tabular 411
bibliography
  HTML page and TOC 122
bitmapped fonts 94
bugs 175

C

Calibre 162
chemistry
  Greek symbols 639
class
  modifying for lwarp 173
code listings 112
compiling
  custom 158
Computer Modern 94
converting
  class 173
  document 93
  package 171
CSS
  file selection 106
  lwarp.css 107
  per HTML page 106
  project-specific changes 107
ctable 151

D

danger icon 185
debugging 175
  HTML debug comments 223
  tracing log 223
Deja Vu 94
description
  HTML meta tag 110, 333
display math
  complicated objects 140
document
  convert existing 93
DVI LaTeX 89, 94
dynamic math 140
dynamic math expressions 307

E

endnotes
  HTML page and TOC 122
EPS image
  converting 91
  using 142, 526
EPUB
  conversion software 162
  HTML conversion settings 162, 229
error messages 175
export
  to word processor 164

F

FAQ 175
filename
  accent in 351
  hashed 492, 517
  international languages 154
  length 103
  simplify 118
  underscore in 100, 113
  unique 103
font
  Computer Modern 94

Deja Vu 94
ligatures 95
packages 95
selection 94
size
latexmage 138, 487, 512
math, SVG 138, 487, 512
xfrac 987
type 1 vector 94
type 3 bitmapped 94
footnotes 333
numbering 120
foreign
section names 154
framed objects 115
Frequently Asked Questions 175

G

generator
HTML meta tag 363
GIF images 142, 527
gloss 124
glossaries
HTML page and TOC 122
language 124
options 124
processing 90
graphics
formats 142, 526
Greek
chemistry symbols 639

H

hash
SVG image filename 492, 517
heading, word processor 167
horizontal space 112
between minipages 561
HTML
conversion settings 100
debug comments 223
EPUB 162, 229
word processor 164, 229
conversion suggestions 111
entities, conversion 112
filename generation 105
headings 184
meta tag
author 111, 333
description 110, 333
generator 363
title 103, 104, 110, 332, 333
viewport 364
selecting print/HTML definitions . . 224
tabular column conversion 412
verbatim, in 112
hyperref
and xindy 125

I

icon
warning 185
image
GIF 142, 527
graphicx package 526
hashed filename 492, 517
PDF or EPS
converting 91, 142, 527
using 142, 526
PNG and JPG 142, 527
processing 285
\includegraphics
using 142, 526
index
custom makeindex style file 134
custom xindy style file 135
custom display styles 136
formatting 482
HTML page and TOC 122
letter headings 753
placement and TOC options . . . 136, 943
processing 83, 84, 125
see, seealso, ranges 125
source code 125
table of contents 136, 943
UTF-8 95
xindy and hyperref 125
inline math
complicated objects 140
international
section names 154
item
empty 385

J

JAVASCRIPT
MATHJAX 137, 487
JPG images 142, 527

L

label
in HTML 367
math environment 508
language
glossaries 124
language HTML metadata 361
latexmage
font size 138, 487, 512
processing 285
Latin Modern font 94
LIBREOFFICE
conversion recommendations 167

import into . . . 164
section headings . . . 167
ligatures . . . 95, 212
line numbers . . . 185
list
empty item . . . 385
filename . . . 113
listings, program code . . . 112
locale . . . 161
LuaLaTeX
detection . . . 186
file & section names . . . 351
lwarp
loading . . . 96
options . . . 96
lwarp.ist
customizing . . . 134
lwarp.xdy
customizing . . . 135
lwarpmk
customizing . . . 173

M

make utility . . . 161
makeindex
customizing . . . 134
margin
numbers . . . 185
tags . . . 185
markup languages . . . 70
math
display with complicated objects . . . 140
dynamic . . . 140, 307
font size — SVG . . . 138, 487, 512
inline with complicated objects . . . 140
MathJax custom functions . . . 139, 488
MathJax summary . . . 138, 488
mathjax option . . . 206
mathsvg option . . . 206
mhchem . . . 807
SVG summary . . . 138, 487
word processor conversion . . . 167
MathJax
custom functions . . . 139, 488
custom script . . . 283
mathjax option . . . 206
summary . . . 138, 488
\mcolrowcell . . . 148
MD5 hash
SVG image filename . . . 492, 517
memoir
verse . . . 967
meta tag, HTML
author . . . 111, 333
description . . . 110, 333
generator . . . 363
title . . . 110, 332, 333
viewport . . . 364
minipage
framed . . . 115
horizontal space between . . . 561
modifying
class . . . 173
document . . . 93
package . . . 171
\mrowcell . . . 148
\multicolumn
with \multirow . . . 148
multimedia . . . 145
\multirow
with \multicolumn . . . 148
multirow
\mrowcell and \mcolrowcell . . . 148

N

newfloat
with trivfloat, algorithmicx . . . 958
nomencl . . . 125
numbers
left margin . . . 185

P

package
modifying for lwarp . . . 171
required . . . 212
\par
hooks . . . 329
PDF image
converting . . . 91
using . . . 142, 526
Perl . . . 78
PNG images . . . 142, 527
Poppler . . . 73, 78
print
selecting print/HTML definitions . . . 224
problems . . . 175
program listings . . . 112
programs
utility . . . 72
\published . . . 378

S

section
depths . . . 184
file names . . . 118
heading, word processor . . . 167
international languages . . . 154
settings
CSS project-specific . . . 107
CSS selection . . . 106
HTML conversion . . . 100
lwarp package options . . . 96

selecting output 108
title page 109
shell escape 94
siunitx
with *TeXMaths* 167
space
horizontal 112
between minipages 561
stack depths 184
\subtitle 378
SVG
converting from PDF or EPS 91
dynamic math 307
image processing 285
math summary 138, 487
mathsvg option 206

T

tabular
baseline 411
HTML columnn conversion 412
macros inside 147, 393
\multicolumn with \multirow 148
multirow \mrowcell and \mcolrowcell 148
tikz
catcodes 931
dollar redefined 931
title
HTML meta tag 110, 332, 333
titlepage
\subtitle and \published 378
tracing log 223
trivfloat
with newfloat, algorithmicx 958
troubleshooting 175
HTML debug comments 223
tracing log 223
type 1 vector fonts 94
type 3 bitmapped fonts 94

U

underscore
filename 100, 113
Unicode
enhanced coverage 94
file & section names 351
input characters 200
selection 94
UTF-8
enhanced coverage 94
file & section names 351
index 95
locale 161
selection 94
utility
programs 72

V

vector fonts 94
verbatim
code and HTML tags 112
video 145
viewport
HTML meta tag 364

W

warning icon 185
word processor
conversion recommendations 167
HTML conversion settings 164, 229
section headings 167

X

XeLaTeX
detection 186
file & section names 351
xindy
and hyperref 125
customizing 135
xparse
warnings 156

Troubleshooting Index

This index is a sorted reference of problems and solutions. In order to make it easier to locate a solution, the same issue may be addressed by more than one entry.

Entries with higher page numbers are often duplicates of entries with lower page numbers, as the same warning may occur within the user manual and again within the source code for a given package.

A

abstract
  missing TOC 122, 575
acronym
  multiply-defined labels 580
\AddSubtitlePublished 378
affiliation 371
alt tags 140, 178
AMSmath
  ntheorem
    numbering 141, 840
appendix
  incorrect TOC link 123, 595
array
  chemformula 156
audio 145
authblk
  \theauthor 370, 371
  titling 122, 370, 604, 939
author
  affiliation 371
  formatting 110
autonum 605

B

babel
  French 155
backref 608
backref 120
bibliography
  HTML page and TOC 122
bibtex
  \etalchar 123
  Improper \prevdepth 123
bigdelim 151, 614
bigfoot 121, 789
boxes 114
breqn
  darray 621
  MathJax 621

C

Calibre
  EPUB conversion 162
caption
  numbering 152
  options 151
cases
  MathJax 627
chemfig 156
chemformula
  MathJax 156, 635
chemgreek
  fontspec mapping 639
  text-mode symbols 639
chemmacros
  \makepolymerdelims 640
  redox reactions 640
colortbl 150, 660
cross reference
  incorrect link 179
  missing 178
CSS 180
ctable 151

D

ditaa 161
duplcate filename 119

E

\endhead, etc. 149
endnotes
  HTML page and TOC 122
\ensuremath 178
epstopdf 144, 680
EPUB
  encoding 162
  page order 162
  search order 162
  section breaks 163
error messages 175
\etalchar 123

F

fancybox
  \VerbatimFootnotes . . . 121, 687, 693
fancyvrb
  \VerbatimFootnotes . . . 121, 687, 693
figure
  macro in name . . . 178
file
  inaccessible . . . 102
filename
  accents . . . 351
  corrupted . . . 118, 154
  duplicate . . . 119
  international, UTF-8 . . . 154
  Korean . . . 157
  macro in name . . . 118
  math in . . . 93, 119, 137, 486
  Missing $ inserted . . . 177
fixme . . . 156, 701
float
  alignment . . . 112, 151
  out of sequence . . . 179
floatrow
  \FBwidth and \FBheight . . . 152, 706
  with subfig . . . 152, 706
floatrow
  \ttabbox . . . 147, 392
font
  ligatures . . . 95
  missing symbols . . . 113, 919
  monospace . . . 95
  package conflicts . . . 94
  selection . . . 94
  UTF-8 . . . 94
fontspec . . . 94
footmisc . . . 120, 334
footnote
  displaymath . . . 121, 687, 693
  in math . . . 121
  in sectioning command . . . 120
  memoir . . . 120, 334
  numbering . . . 120
  paragraph tags . . . 121, 687, 693
  sectioning, footmisc . . . 120, 334
  sectioning, verbatim . . . 121, 687, 693
  title . . . 370
  verbatim . . . 121
  \VerbatimFootnotes . . . 121, 687, 693
forest . . . 719
formatting
  \bfseries etc. . . . 112, 546
frames . . . 115

G

gloss . . . 124
glossaries
  HTML page and TOC . . . 122
  makeglossaries not found . . . 124, 725
  page numbers . . . 125, 726
  style . . . 124, 726
graphics
  \rotatebox, \scalebox, \reflectbox . . . 143, 528
  image format priorities . . . 142, 527
  images out of order . . . 85, 179
  multimedia . . . 145
  optional arguments . . . 142, 527
  scale option . . . 93, 141, 526
  scaled . . . 729
  viewport . . . 142, 527
Greek packages . . . 639
grffile . . . 143, 740

H

horizontal spacing . . . 152, 908
HTML
  &, <, > . . . 112, 546
  alt tags . . . 140
  author . . . 333
  corrupted . . . 110, 114, 177, 180
  entities . . . 112, 546
  image appear as HTML code . . . 85, 180
  inaccessible pages . . . 102, 104
    starred section . . . 122
  invalid . . . 112
  missing pages
    filename not unique . . . 103
    recompile . . . 180
    SideTOCDepth and FileDepth . . . 102
    SideTOCDepth and tocdepth . . . 102
  page did not update . . . 102, 180
  settings
    changed . . . 100
    undefined . . . 177
  validation . . . 112
\HTMLAuthor . . . 333
HTMLIndexCmd
  filenames . . . 98
hyperref
  backref . . . 120
  comments between arguments . . . 120
  incorrect link . . . 179

I

image
  appears as HTML code . . . 85, 180
  format priorities . . . 142, 527
  incorrect . . . 85, 179, 180
  viewport . . . 142, 527
Improper \prevdepth
  bibtex . . . 123

boxes 178
\includegraphics
optional arguments 142, 527
scale 93, 141, 526
index
empty 136
empty link 119, 179
formatting 482
HTML page and TOC 122
missing entries 125
numbers, not links 215
reference ranges 135
see and seealso 135
styling references 135
xindy and hyperref 135
xstring bug 215

K

keyfloat 153, 762

L

label
\nameref empty 119, 179
characters 119, 179
Label(s) may have changed 177
\LateximageFontSizeName 513
Leaders not followed by proper glue . . 177
LibreOffice
import 164
ligatures 95
LINUX 107, 203
list
empty item 113, 385
listings 179
lists
label formatting 386
locale 161
longtable
\endhead, etc. 149
lrbox 114
ltxtable
numbering 785
lualaTeX 94
\LWRbackslash 158
\LWRdollar 158
\LWRhash 158
\LWRopquote 158
\LWRopseq 158
\LWRpercent 158

M

MAC OS 107, 203
makeglossaries
not found 124, 725
\makelabel 386
manyfoot 121, 789
\marginpar 114, 340
math
alt tags 178
appears as HTML code 85, 180
chemformula 156
custom macros 178
dynamic 307
equation numbering
ntheorem 141, 840
file name 93, 119, 137, 486
footnote 121
in TeX boxes 138, 488
incorrect 85, 180, 307
non-math contents 178
section name 93, 119, 137, 486
slow or failed compile 178
subequations 139, 488
tabbing 146, 384
Ti*k*z 140
MATHJAX
breqn 621
cases 627
chemformula 156, 635
custom script 283
errors 140, 178, 307
mhchem 806
siunitx 139, 141, 489, 525, 896
subequations 139, 488
unsupported packages . . 140, 178, 489
mathtools 793
\mcolrowcell 148
media9 145
memoir
footmisc 120, 334
options clash 153, 999
version clash 153, 999
mhchem
MATHJAX 806
nested dollar signs 807
minipage
alignment 115, 536
horizontal space between 561
in a span 114, 536
inline 114, 536
multicols, width in 115, 536
size 114, 536
tabular, width in 115, 536
Misplaced \noalign 149, 781
tabular
rules 148, 394
Misplaced \omit
tabular 227
Misplaced alignment tab character &
ctable 151, 663
floatrow 152, 705

frames 116
supertabular 150, 913, 992
tabular
macros 147, 306, 392
Missing $ inserted
filename or URL 177
morewrites 177
morewrites 136
movie15 145
\mrowcell 148
MS-WINDOWS 107, 203
multimedia 145
multiply-defined labels
acronym 580
\multirow and \multicolumn 149, 818
multirow
\mrowcell and \mcolrowcell 148

N

newclude 155
newtxmath 141
nicefrac 141
No room for a new \write 177
nomencl 125
ntheorem 840
font 141, 840
numbering 141, 840

O

operating system 107, 203
options clash
memoir 153, 999
overpic 145, 852

P

package
version numbers with memoir . 153, 999
page
inacessible 102
page counter
references 119
SVG images 85, 180
page numbers 119, 179, 532
pdftricks 144, 860
perltex 160
pfnote
numbering 121, 862
polyglossia
Undefined control sequence 155
poppler
Syntax Warning (ligature) 713
PrintIndexCmd 98
psfrag 144
pstool 145, 868
pstricks 144, 869
pythontex 160

R

reference
% character between arguments . . 179
empty link 119, 179
incorrect link 179
label characters 119, 179
missing or incorrect 178
page number 119, 179, 532
repeatindex 876
rterface 161

S

sample_projects.css
overwritten 107
\savebox 114
\sbox 114
scale (\includegraphics option) 93, 141, 526
sectioning
accents 351
duplicate name 119
international language 154
macro in name 118, 178
math in name 93, 119, 137, 486
missing 102
starred section 122
word processor import 167
siunitx
MATHJAX 141, 525, 896
with TeXMaths 166
siunitx 141, 525, 896
MATHJAX 139, 489
S column 148, 394
tabular S and s columns . 141, 526, 896
splitidx
\thepage and \AtWriteToIndex 127, 904
subcaption
numbering 152
subfig
options 152, 908
with floatrow 152, 706
SVG image
appears as HTML code 85, 180
incorrect 85, 179, 180
math incorrect 307
out of order 85, 179
sympytex 161
Syntax Warning (ligature) 713

T

tabbing
math 146, 384
table
macro in name 178
numbering 785
Table of Contents
missing 104

tabular
baselines . . . 411
corrupt rows . . . 147, 393, 444
\endhead, \endfoot, \endlastfoot . . . 149, 781
inside an environment . . . 147, 393, 444
\kill . . . 149, 781
macro inside . . . 147, 393
Misplaced \noalign . . . 148, 394
Misplaced alignment tab character & . . . 147, 392
macros . . . 306
rules . . . 148
\multicolumn with \multirow . . . 148
multirow \mrowcell and \mcolrowcell . . . 148
\newcolumntype . . . 147, 393
numbering . . . 989
row corruption . . . 147, 393
rules . . . 148, 394
S column . . . 148, 394
TeXMaths . . . 166
text
&, <, > . . . 112, 546
\bfseries etc. . . . 112, 546
corrupted . . . 94
textcomp
missing symbols . . . 113, 919
\theauthor and authblk . . . 370, 371
threeparttablex . . . 150
tikz
in math . . . 140
matrices, & . . . 143, 931
title
affiliation . . . 371
newlines . . . 110
\thanks . . . 370
titling
authblk . . . 122, 370, 604, 939
hooks . . . 378
tocloft
chapter titles . . . 123, 137, 594, 947
todonotes . . . 155, 786, 954
tracing lwarp . . . 180
tram . . . 956
transparent . . . 957

U

Undefined control sequence
polyglossia . . . 155
Unicode
fonts . . . 94
UTF-8 locale . . . 161
units . . . 141
UNIX . . . 107, 203
URL
Missing $ inserted . . . 177
\usebox . . . 114
UTF-8
locale . . . 161

V

verbatim
footnote . . . 121
framed . . . 117, 686
VerbatimFootnotes . . . 121, 687, 693
verse
spacing . . . 154, 381, 966
version numbers
with memoir . . . 153, 999
video . . . 145
viewport . . . 142, 527

W

warning messages . . . 175
warpall . . . 177
warpHTML . . . 108, 177
warpprint . . . 108, 177
WINDOWS . . . 107, 203
word processor
import . . . 164
sectioning headings . . . 167

X

xeLaTeX . . . 94
xfakebold . . . 986
xfrac . . . 986
xindy
hyperref . . . 135
options
HTMLIndexCmd . . . 98
LatexmkIndexCmd . . . 99
PrintIndexCmd . . . 98
xltabular
numbering . . . 989
xparse . . . 156
xstring . . . 215
xy . . . 995

Index of Indexes

C

Change History 1029

G

General Index 1077

I

Index of Objects 1057

T

Troubleshooting Index 1081