LilyPond

The music typesetter

Internals Reference

The LilyPond development team

Copyright © 2000–2011 by the authors

For LilyPond version 2.14.2

Table of Contents

1 Music definitions 2

1.1 Music expressions 2

1.1.1 AbsoluteDynamicEvent 2
1.1.2 AnnotateOutputEvent 2
1.1.3 ApplyContext 2
1.1.4 ApplyOutputEvent 3
1.1.5 ArpeggioEvent 3
1.1.6 ArticulationEvent 3
1.1.7 AutoChangeMusic 4
1.1.8 BarCheck 4
1.1.9 BassFigureEvent 5
1.1.10 BeamEvent 5
1.1.11 BeamForbidEvent 5
1.1.12 BendAfterEvent 6
1.1.13 BreakDynamicSpanEvent 6
1.1.14 BreathingEvent 6
1.1.15 ClusterNoteEvent 7
1.1.16 CompletizeExtenderEvent 7
1.1.17 ContextChange 7
1.1.18 ContextSpeccedMusic 8
1.1.19 CrescendoEvent 8
1.1.20 DecrescendoEvent 9
1.1.21 DoublePercentEvent 9
1.1.22 EpisemaEvent 9
1.1.23 Event 10
1.1.24 EventChord 10
1.1.25 ExtenderEvent 10
1.1.26 FingeringEvent 11
1.1.27 FootnoteEvent 11
1.1.28 GlissandoEvent 11
1.1.29 GraceMusic 12
1.1.30 HarmonicEvent 12
1.1.31 HyphenEvent 12
1.1.32 KeyChangeEvent 13
1.1.33 LabelEvent 13
1.1.34 LaissezVibrerEvent 13
1.1.35 LigatureEvent 14
1.1.36 LineBreakEvent 14
1.1.37 LyricCombineMusic 14
1.1.38 LyricEvent 15
1.1.39 MarkEvent 15
1.1.40 MultiMeasureRestEvent 16
1.1.41 MultiMeasureRestMusic 16
1.1.42 MultiMeasureTextEvent 16
1.1.43 Music 17
1.1.44 NoteEvent 17
1.1.45 NoteGroupingEvent 17
1.1.46 OttavaMusic 18

1.1.47 OverrideProperty . . . 18
1.1.48 PageBreakEvent . . . 18
1.1.49 PageTurnEvent . . . 19
1.1.50 PartCombineForceEvent . . . 19
1.1.51 PartCombineMusic . . . 19
1.1.52 PartialSet . . . 20
1.1.53 PercentEvent . . . 20
1.1.54 PercentRepeatedMusic . . . 20
1.1.55 PesOrFlexaEvent . . . 21
1.1.56 PhrasingSlurEvent . . . 21
1.1.57 PropertySet . . . 22
1.1.58 PropertyUnset . . . 22
1.1.59 QuoteMusic . . . 22
1.1.60 RelativeOctaveCheck . . . 23
1.1.61 RelativeOctaveMusic . . . 23
1.1.62 RepeatSlashEvent . . . 24
1.1.63 RepeatTieEvent . . . 24
1.1.64 RepeatedChord . . . 24
1.1.65 RepeatedMusic . . . 25
1.1.66 RestEvent . . . 25
1.1.67 RevertProperty . . . 26
1.1.68 ScriptEvent . . . 26
1.1.69 SequentialMusic . . . 26
1.1.70 SimultaneousMusic . . . 27
1.1.71 SkipEvent . . . 28
1.1.72 SkipMusic . . . 28
1.1.73 SlurEvent . . . 28
1.1.74 SoloOneEvent . . . 29
1.1.75 SoloTwoEvent . . . 29
1.1.76 SostenutoEvent . . . 30
1.1.77 SpacingSectionEvent . . . 30
1.1.78 SpanEvent . . . 30
1.1.79 StaffSpanEvent . . . 31
1.1.80 StringNumberEvent . . . 31
1.1.81 StrokeFingerEvent . . . 31
1.1.82 SustainEvent . . . 32
1.1.83 TempoChangeEvent . . . 32
1.1.84 TextScriptEvent . . . 32
1.1.85 TextSpanEvent . . . 33
1.1.86 TieEvent . . . 33
1.1.87 TimeScaledMusic . . . 33
1.1.88 TimeSignatureMusic . . . 34
1.1.89 TransposedMusic . . . 34
1.1.90 TremoloEvent . . . 35
1.1.91 TremoloRepeatedMusic . . . 35
1.1.92 TremoloSpanEvent . . . 36
1.1.93 TrillSpanEvent . . . 36
1.1.94 TupletSpanEvent . . . 36
1.1.95 UnaCordaEvent . . . 37
1.1.96 UnfoldedRepeatedMusic . . . 37
1.1.97 UnisonoEvent . . . 37
1.1.98 UnrelativableMusic . . . 38
1.1.99 VoiceSeparator . . . 38
1.1.100 VoltaRepeatedMusic . . . 39

1.2 Music classes . . . 39
1.2.1 absolute-dynamic-event . . . 39
1.2.2 annotate-output-event . . . 39
1.2.3 apply-output-event . . . 39
1.2.4 arpeggio-event . . . 39
1.2.5 articulation-event . . . 40
1.2.6 bass-figure-event . . . 40
1.2.7 beam-event . . . 40
1.2.8 beam-forbid-event . . . 40
1.2.9 bend-after-event . . . 40
1.2.10 break-dynamic-span-event . . . 40
1.2.11 break-event . . . 40
1.2.12 break-span-event . . . 40
1.2.13 breathing-event . . . 40
1.2.14 cluster-note-event . . . 40
1.2.15 completize-extender-event . . . 41
1.2.16 crescendo-event . . . 41
1.2.17 decrescendo-event . . . 41
1.2.18 double-percent-event . . . 41
1.2.19 dynamic-event . . . 41
1.2.20 episema-event . . . 41
1.2.21 extender-event . . . 41
1.2.22 fingering-event . . . 41
1.2.23 footnote-event . . . 41
1.2.24 glissando-event . . . 41
1.2.25 harmonic-event . . . 42
1.2.26 hyphen-event . . . 42
1.2.27 key-change-event . . . 42
1.2.28 label-event . . . 42
1.2.29 laissez-vibrer-event . . . 42
1.2.30 layout-instruction-event . . . 42
1.2.31 ligature-event . . . 42
1.2.32 line-break-event . . . 42
1.2.33 lyric-event . . . 42
1.2.34 mark-event . . . 42
1.2.35 melodic-event . . . 43
1.2.36 multi-measure-rest-event . . . 43
1.2.37 multi-measure-text-event . . . 43
1.2.38 music-event . . . 43
1.2.39 note-event . . . 43
1.2.40 note-grouping-event . . . 44
1.2.41 page-break-event . . . 44
1.2.42 page-turn-event . . . 44
1.2.43 part-combine-event . . . 44
1.2.44 part-combine-force-event . . . 44
1.2.45 pedal-event . . . 44
1.2.46 percent-event . . . 44
1.2.47 pes-or-flexa-event . . . 44
1.2.48 phrasing-slur-event . . . 45
1.2.49 repeat-slash-event . . . 45
1.2.50 repeat-tie-event . . . 45
1.2.51 rest-event . . . 45
1.2.52 rhythmic-event . . . 45
1.2.53 script-event . . . 45

1.2.54 skip-event ... 45
1.2.55 slur-event ... 45
1.2.56 solo-one-event ... 45
1.2.57 solo-two-event ... 46
1.2.58 sostenuto-event ... 46
1.2.59 spacing-section-event ... 46
1.2.60 span-dynamic-event ... 46
1.2.61 span-event ... 46
1.2.62 staff-span-event ... 46
1.2.63 StreamEvent ... 46
1.2.64 string-number-event ... 47
1.2.65 stroke-finger-event ... 47
1.2.66 sustain-event ... 47
1.2.67 tempo-change-event ... 47
1.2.68 text-script-event ... 47
1.2.69 text-span-event ... 48
1.2.70 tie-event ... 48
1.2.71 tremolo-event ... 48
1.2.72 tremolo-span-event ... 48
1.2.73 trill-span-event ... 48
1.2.74 tuplet-span-event ... 48
1.2.75 una-corda-event ... 48
1.2.76 unisono-event ... 48
1.3 Music properties ... 48

2 Translation ... 54

2.1 Contexts ... 54
2.1.1 ChoirStaff ... 54
2.1.2 ChordNames ... 55
2.1.3 CueVoice ... 57
2.1.4 Devnull ... 70
2.1.5 DrumStaff ... 70
2.1.6 DrumVoice ... 76
2.1.7 Dynamics ... 88
2.1.8 FiguredBass ... 91
2.1.9 FretBoards ... 93
2.1.10 Global ... 95
2.1.11 GrandStaff ... 95
2.1.12 GregorianTranscriptionStaff ... 97
2.1.13 GregorianTranscriptionVoice ... 107
2.1.14 Lyrics ... 120
2.1.15 MensuralStaff ... 123
2.1.16 MensuralVoice ... 133
2.1.17 NoteNames ... 146
2.1.18 PianoStaff ... 147
2.1.19 RhythmicStaff ... 150
2.1.20 Score ... 153
2.1.21 Staff ... 164
2.1.22 StaffGroup ... 174
2.1.23 TabStaff ... 176
2.1.24 TabVoice ... 183
2.1.25 VaticanaStaff ... 197
2.1.26 VaticanaVoice ... 207
2.1.27 Voice ... 220

2.2 Engravers and Performers ... 233
2.2.1 Accidental_engraver ... 233
2.2.2 Ambitus_engraver ... 234
2.2.3 Arpeggio_engraver ... 234
2.2.4 Auto_beam_engraver ... 235
2.2.5 Axis_group_engraver ... 235
2.2.6 Balloon_engraver ... 236
2.2.7 Bar_engraver ... 236
2.2.8 Bar_number_engraver ... 236
2.2.9 Beam_collision_engraver ... 237
2.2.10 Beam_engraver ... 237
2.2.11 Beam_performer ... 237
2.2.12 Bend_engraver ... 238
2.2.13 Break_align_engraver ... 238
2.2.14 Breathing_sign_engraver ... 238
2.2.15 Chord_name_engraver ... 238
2.2.16 Chord_tremolo_engraver ... 239
2.2.17 Clef_engraver ... 239
2.2.18 Cluster_spanner_engraver ... 240
2.2.19 Collision_engraver ... 240
2.2.20 Completion_heads_engraver ... 240
2.2.21 Completion_rest_engraver ... 241
2.2.22 Control_track_performer ... 241
2.2.23 Cue_clef_engraver ... 241
2.2.24 Custos_engraver ... 242
2.2.25 Default_bar_line_engraver ... 242
2.2.26 Dot_column_engraver ... 243
2.2.27 Dots_engraver ... 243
2.2.28 Double_percent_repeat_engraver ... 243
2.2.29 Drum_note_performer ... 244
2.2.30 Drum_notes_engraver ... 244
2.2.31 Dynamic_align_engraver ... 244
2.2.32 Dynamic_engraver ... 245
2.2.33 Dynamic_performer ... 245
2.2.34 Engraver ... 245
2.2.35 Episema_engraver ... 245
2.2.36 Extender_engraver ... 246
2.2.37 Figured_bass_engraver ... 246
2.2.38 Figured_bass_position_engraver ... 247
2.2.39 Fingering_engraver ... 247
2.2.40 Font_size_engraver ... 247
2.2.41 Footnote_engraver ... 247
2.2.42 Forbid_line_break_engraver ... 248
2.2.43 Fretboard_engraver ... 248
2.2.44 Glissando_engraver ... 249
2.2.45 Grace_beam_engraver ... 249
2.2.46 Grace_engraver ... 250
2.2.47 Grace_spacing_engraver ... 250
2.2.48 Grid_line_span_engraver ... 250
2.2.49 Grid_point_engraver ... 250
2.2.50 Grob_pq_engraver ... 250
2.2.51 Hara_kiri_engraver ... 251
2.2.52 Horizontal_bracket_engraver ... 251
2.2.53 Hyphen_engraver ... 251

2.2.54 Instrument_name_engraver . . . 251
2.2.55 Instrument_switch_engraver . . . 252
2.2.56 Keep_alive_together_engraver . . . 252
2.2.57 Key_engraver . . . 252
2.2.58 Key_performer . . . 253
2.2.59 Laissez_vibrer_engraver . . . 254
2.2.60 Ledger_line_engraver . . . 254
2.2.61 Ligature_bracket_engraver . . . 254
2.2.62 Lyric_engraver . . . 254
2.2.63 Lyric_performer . . . 255
2.2.64 Mark_engraver . . . 255
2.2.65 Measure_grouping_engraver . . . 255
2.2.66 Melody_engraver . . . 256
2.2.67 Mensural_ligature_engraver . . . 256
2.2.68 Metronome_mark_engraver . . . 256
2.2.69 Multi_measure_rest_engraver . . . 257
2.2.70 New_dynamic_engraver . . . 257
2.2.71 New_fingering_engraver . . . 258
2.2.72 Note_head_line_engraver . . . 258
2.2.73 Note_heads_engraver . . . 259
2.2.74 Note_name_engraver . . . 259
2.2.75 Note_performer . . . 259
2.2.76 Note_spacing_engraver . . . 259
2.2.77 Ottava_spanner_engraver . . . 260
2.2.78 Output_property_engraver . . . 260
2.2.79 Page_turn_engraver . . . 260
2.2.80 Paper_column_engraver . . . 261
2.2.81 Parenthesis_engraver . . . 261
2.2.82 Part_combine_engraver . . . 261
2.2.83 Percent_repeat_engraver . . . 262
2.2.84 Phrasing_slur_engraver . . . 262
2.2.85 Piano_pedal_align_engraver . . . 263
2.2.86 Piano_pedal_engraver . . . 263
2.2.87 Piano_pedal_performer . . . 264
2.2.88 Pitch_squash_engraver . . . 264
2.2.89 Pitched_trill_engraver . . . 264
2.2.90 Repeat_acknowledge_engraver . . . 264
2.2.91 Repeat_tie_engraver . . . 265
2.2.92 Rest_collision_engraver . . . 265
2.2.93 Rest_engraver . . . 265
2.2.94 Rhythmic_column_engraver . . . 265
2.2.95 Scheme_engraver . . . 266
2.2.96 Script_column_engraver . . . 266
2.2.97 Script_engraver . . . 266
2.2.98 Script_row_engraver . . . 266
2.2.99 Separating_line_group_engraver . . . 266
2.2.100 Slash_repeat_engraver . . . 267
2.2.101 Slur_engraver . . . 267
2.2.102 Slur_performer . . . 267
2.2.103 Spacing_engraver . . . 268
2.2.104 Span_arpeggio_engraver . . . 268
2.2.105 Span_bar_engraver . . . 268
2.2.106 Spanner_break_forbid_engraver . . . 268
2.2.107 Staff_collecting_engraver . . . 269

2.2.108 Staff_performer ... 269
2.2.109 Staff_symbol_engraver ... 269
2.2.110 Stanza_number_align_engraver ... 269
2.2.111 Stanza_number_engraver ... 269
2.2.112 Stem_engraver ... 270
2.2.113 System_start_delimiter_engraver ... 270
2.2.114 Tab_note_heads_engraver ... 270
2.2.115 Tab_staff_symbol_engraver ... 271
2.2.116 Tab_tie_follow_engraver ... 272
2.2.117 Tempo_performer ... 272
2.2.118 Text_engraver ... 272
2.2.119 Text_spanner_engraver ... 272
2.2.120 Tie_engraver ... 272
2.2.121 Tie_performer ... 273
2.2.122 Time_signature_engraver ... 273
2.2.123 Time_signature_performer ... 273
2.2.124 Timing_translator ... 274
2.2.125 Translator ... 274
2.2.126 Trill_spanner_engraver ... 274
2.2.127 Tuplet_engraver ... 275
2.2.128 Tweak_engraver ... 275
2.2.129 Vaticana_ligature_engraver ... 275
2.2.130 Vertical_align_engraver ... 276
2.2.131 Volta_engraver ... 276
2.3 Tunable context properties ... 276
2.4 Internal context properties ... 287

3 Backend ... 289

3.1 All layout objects ... 289
3.1.1 Accidental ... 289
3.1.2 AccidentalCautionary ... 289
3.1.3 AccidentalPlacement ... 290
3.1.4 AccidentalSuggestion ... 291
3.1.5 Ambitus ... 292
3.1.6 AmbitusAccidental ... 293
3.1.7 AmbitusLine ... 294
3.1.8 AmbitusNoteHead ... 294
3.1.9 Arpeggio ... 295
3.1.10 BalloonTextItem ... 296
3.1.11 BarLine ... 297
3.1.12 BarNumber ... 298
3.1.13 BassFigure ... 300
3.1.14 BassFigureAlignment ... 300
3.1.15 BassFigureAlignmentPositioning ... 300
3.1.16 BassFigureBracket ... 301
3.1.17 BassFigureContinuation ... 301
3.1.18 BassFigureLine ... 302
3.1.19 Beam ... 302
3.1.20 BendAfter ... 304
3.1.21 BreakAlignGroup ... 304
3.1.22 BreakAlignment ... 305
3.1.23 BreathingSign ... 306
3.1.24 ChordName ... 307
3.1.25 Clef ... 307

3.1.26 ClusterSpanner . . . 309
3.1.27 ClusterSpannerBeacon . . . 309
3.1.28 CombineTextScript . . . 309
3.1.29 CueClef . . . 311
3.1.30 CueEndClef . . . 312
3.1.31 Custos . . . 313
3.1.32 DotColumn . . . 314
3.1.33 Dots . . . 315
3.1.34 DoublePercentRepeat . . . 315
3.1.35 DoublePercentRepeatCounter . . . 316
3.1.36 DoubleRepeatSlash . . . 317
3.1.37 DynamicLineSpanner . . . 318
3.1.38 DynamicText . . . 319
3.1.39 DynamicTextSpanner . . . 321
3.1.40 Episema . . . 322
3.1.41 Fingering . . . 323
3.1.42 FootnoteItem . . . 324
3.1.43 FootnoteSpanner . . . 325
3.1.44 FretBoard . . . 326
3.1.45 Glissando . . . 327
3.1.46 GraceSpacing . . . 328
3.1.47 GridLine . . . 329
3.1.48 GridPoint . . . 329
3.1.49 Hairpin . . . 330
3.1.50 HorizontalBracket . . . 331
3.1.51 InstrumentName . . . 332
3.1.52 InstrumentSwitch . . . 333
3.1.53 KeyCancellation . . . 334
3.1.54 KeySignature . . . 335
3.1.55 LaissezVibrerTie . . . 336
3.1.56 LaissezVibrerTieColumn . . . 337
3.1.57 LedgerLineSpanner . . . 337
3.1.58 LeftEdge . . . 338
3.1.59 LigatureBracket . . . 339
3.1.60 LyricExtender . . . 340
3.1.61 LyricHyphen . . . 340
3.1.62 LyricSpace . . . 341
3.1.63 LyricText . . . 342
3.1.64 MeasureGrouping . . . 343
3.1.65 MelodyItem . . . 344
3.1.66 MensuralLigature . . . 344
3.1.67 MetronomeMark . . . 344
3.1.68 MultiMeasureRest . . . 346
3.1.69 MultiMeasureRestNumber . . . 347
3.1.70 MultiMeasureRestText . . . 348
3.1.71 NonMusicalPaperColumn . . . 349
3.1.72 NoteCollision . . . 350
3.1.73 NoteColumn . . . 350
3.1.74 NoteHead . . . 351
3.1.75 NoteName . . . 352
3.1.76 NoteSpacing . . . 352
3.1.77 OctavateEight . . . 353
3.1.78 OttavaBracket . . . 354
3.1.79 PaperColumn . . . 355

3.1.80 ParenthesesItem . . . 356
3.1.81 PercentRepeat . . . 356
3.1.82 PercentRepeatCounter . . . 357
3.1.83 PhrasingSlur . . . 358
3.1.84 PianoPedalBracket . . . 359
3.1.85 RehearsalMark . . . 360
3.1.86 RepeatSlash . . . 362
3.1.87 RepeatTie . . . 362
3.1.88 RepeatTieColumn . . . 363
3.1.89 Rest . . . 364
3.1.90 RestCollision . . . 364
3.1.91 Script . . . 365
3.1.92 ScriptColumn . . . 365
3.1.93 ScriptRow . . . 366
3.1.94 Slur . . . 366
3.1.95 SostenutoPedal . . . 367
3.1.96 SostenutoPedalLineSpanner . . . 368
3.1.97 SpacingSpanner . . . 369
3.1.98 SpanBar . . . 370
3.1.99 StaffGrouper . . . 371
3.1.100 StaffSpacing . . . 372
3.1.101 StaffSymbol . . . 372
3.1.102 StanzaNumber . . . 373
3.1.103 Stem . . . 374
3.1.104 StemTremolo . . . 375
3.1.105 StringNumber . . . 376
3.1.106 StrokeFinger . . . 377
3.1.107 SustainPedal . . . 378
3.1.108 SustainPedalLineSpanner . . . 379
3.1.109 System . . . 380
3.1.110 SystemStartBar . . . 381
3.1.111 SystemStartBrace . . . 382
3.1.112 SystemStartBracket . . . 382
3.1.113 SystemStartSquare . . . 383
3.1.114 TabNoteHead . . . 384
3.1.115 TextScript . . . 385
3.1.116 TextSpanner . . . 387
3.1.117 Tie . . . 388
3.1.118 TieColumn . . . 389
3.1.119 TimeSignature . . . 390
3.1.120 TrillPitchAccidental . . . 391
3.1.121 TrillPitchGroup . . . 392
3.1.122 TrillPitchHead . . . 393
3.1.123 TrillSpanner . . . 393
3.1.124 TupletBracket . . . 395
3.1.125 TupletNumber . . . 396
3.1.126 UnaCordaPedal . . . 396
3.1.127 UnaCordaPedalLineSpanner . . . 397
3.1.128 VaticanaLigature . . . 398
3.1.129 VerticalAlignment . . . 399
3.1.130 VerticalAxisGroup . . . 399
3.1.131 VoiceFollower . . . 401
3.1.132 VoltaBracket . . . 401
3.1.133 VoltaBracketSpanner . . . 402

3.2 Graphical Object Interfaces . . . 403
3.2.1 accidental-interface . . . 403
3.2.2 accidental-placement-interface . . . 404
3.2.3 accidental-suggestion-interface . . . 405
3.2.4 align-interface . . . 405
3.2.5 ambitus-interface . . . 405
3.2.6 arpeggio-interface . . . 406
3.2.7 axis-group-interface . . . 406
3.2.8 balloon-interface . . . 408
3.2.9 bar-line-interface . . . 409
3.2.10 bass-figure-alignment-interface . . . 410
3.2.11 bass-figure-interface . . . 410
3.2.12 beam-interface . . . 410
3.2.13 bend-after-interface . . . 413
3.2.14 break-alignable-interface . . . 413
3.2.15 break-aligned-interface . . . 413
3.2.16 break-alignment-interface . . . 414
3.2.17 breathing-sign-interface . . . 415
3.2.18 chord-name-interface . . . 415
3.2.19 clef-interface . . . 415
3.2.20 cluster-beacon-interface . . . 416
3.2.21 cluster-interface . . . 416
3.2.22 custos-interface . . . 416
3.2.23 dot-column-interface . . . 417
3.2.24 dots-interface . . . 417
3.2.25 dynamic-interface . . . 417
3.2.26 dynamic-line-spanner-interface . . . 417
3.2.27 dynamic-text-interface . . . 418
3.2.28 dynamic-text-spanner-interface . . . 418
3.2.29 enclosing-bracket-interface . . . 418
3.2.30 episema-interface . . . 419
3.2.31 figured-bass-continuation-interface . . . 419
3.2.32 finger-interface . . . 419
3.2.33 font-interface . . . 419
3.2.34 footnote-interface . . . 421
3.2.35 footnote-spanner-interface . . . 421
3.2.36 fret-diagram-interface . . . 421
3.2.37 glissando-interface . . . 423
3.2.38 grace-spacing-interface . . . 423
3.2.39 gregorian-ligature-interface . . . 423
3.2.40 grid-line-interface . . . 424
3.2.41 grid-point-interface . . . 424
3.2.42 grob-interface . . . 424
3.2.43 hairpin-interface . . . 428
3.2.44 hara-kiri-group-spanner-interface . . . 428
3.2.45 horizontal-bracket-interface . . . 429
3.2.46 inline-accidental-interface . . . 430
3.2.47 instrument-specific-markup-interface . . . 430
3.2.48 item-interface . . . 432
3.2.49 key-cancellation-interface . . . 433
3.2.50 key-signature-interface . . . 433
3.2.51 ledger-line-spanner-interface . . . 434
3.2.52 ledgered-interface . . . 434
3.2.53 ligature-bracket-interface . . . 434

3.2.54 ligature-head-interface . . . 435
3.2.55 ligature-interface . . . 435
3.2.56 line-interface . . . 435
3.2.57 line-spanner-interface . . . 435
3.2.58 lyric-extender-interface . . . 436
3.2.59 lyric-hyphen-interface . . . 437
3.2.60 lyric-interface . . . 437
3.2.61 lyric-syllable-interface . . . 437
3.2.62 mark-interface . . . 437
3.2.63 measure-grouping-interface . . . 437
3.2.64 melody-spanner-interface . . . 438
3.2.65 mensural-ligature-interface . . . 438
3.2.66 metronome-mark-interface . . . 439
3.2.67 multi-measure-interface . . . 439
3.2.68 multi-measure-rest-interface . . . 439
3.2.69 note-collision-interface . . . 440
3.2.70 note-column-interface . . . 440
3.2.71 note-head-interface . . . 441
3.2.72 note-name-interface . . . 441
3.2.73 note-spacing-interface . . . 441
3.2.74 only-prebreak-interface . . . 442
3.2.75 ottava-bracket-interface . . . 442
3.2.76 paper-column-interface . . . 443
3.2.77 parentheses-interface . . . 444
3.2.78 percent-repeat-interface . . . 444
3.2.79 percent-repeat-item-interface . . . 445
3.2.80 piano-pedal-bracket-interface . . . 445
3.2.81 piano-pedal-interface . . . 446
3.2.82 piano-pedal-script-interface . . . 446
3.2.83 pitched-trill-interface . . . 446
3.2.84 rest-collision-interface . . . 446
3.2.85 rest-interface . . . 446
3.2.86 rhythmic-grob-interface . . . 447
3.2.87 rhythmic-head-interface . . . 447
3.2.88 script-column-interface . . . 447
3.2.89 script-interface . . . 447
3.2.90 self-alignment-interface . . . 448
3.2.91 semi-tie-column-interface . . . 449
3.2.92 semi-tie-interface . . . 449
3.2.93 separation-item-interface . . . 450
3.2.94 side-position-interface . . . 451
3.2.95 slur-interface . . . 452
3.2.96 spaceable-grob-interface . . . 454
3.2.97 spacing-interface . . . 455
3.2.98 spacing-options-interface . . . 455
3.2.99 spacing-spanner-interface . . . 455
3.2.100 span-bar-interface . . . 456
3.2.101 spanner-interface . . . 457
3.2.102 staff-grouper-interface . . . 458
3.2.103 staff-spacing-interface . . . 458
3.2.104 staff-symbol-interface . . . 459
3.2.105 staff-symbol-referencer-interface . . . 459
3.2.106 stanza-number-interface . . . 459
3.2.107 stem-interface . . . 459

3.2.108 stem-tremolo-interface . . . 462
3.2.109 string-number-interface . . . 462
3.2.110 stroke-finger-interface . . . 462
3.2.111 system-interface . . . 463
3.2.112 system-start-delimiter-interface . . . 463
3.2.113 system-start-text-interface . . . 464
3.2.114 tab-note-head-interface . . . 464
3.2.115 text-interface . . . 464
3.2.116 text-script-interface . . . 465
3.2.117 tie-column-interface . . . 466
3.2.118 tie-interface . . . 466
3.2.119 time-signature-interface . . . 467
3.2.120 trill-pitch-accidental-interface . . . 467
3.2.121 trill-spanner-interface . . . 468
3.2.122 tuplet-bracket-interface . . . 468
3.2.123 tuplet-number-interface . . . 469
3.2.124 unbreakable-spanner-interface . . . 470
3.2.125 vaticana-ligature-interface . . . 470
3.2.126 volta-bracket-interface . . . 470
3.2.127 volta-interface . . . 471
3.3 User backend properties . . . 471
3.4 Internal backend properties . . . 487

4 Scheme functions . . . 494

Appendix A Indices . . . 515
A.1 Concept index . . . 515
A.2 Function index . . . 515

This is the Internals Reference (IR) for version 2.14.2 of LilyPond, the GNU music typesetter.

1 Music definitions

1.1 Music expressions

1.1.1 AbsoluteDynamicEvent

Create a dynamic mark.

Syntax: *note*`\x`, where `\x` is a dynamic mark like `\ppp` or `\sfz`. A complete list is in file '`ly/dynamic-scripts-init.ly`'.

Event classes: Section 1.2.1 [absolute-dynamic-event], page 39, Section 1.2.19 [dynamic-event], page 41, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.32 [Dynamic_engraver], page 245, Section 2.2.33 [Dynamic_performer], page 245 and Section 2.2.70 [New_dynamic_engraver], page 257.

Properties:

`name` (symbol):
`'AbsoluteDynamicEvent`

Name of this music object.

`types` (list):
`'(general-music event dynamic-event absolute-dynamic-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.2 AnnotateOutputEvent

Print an annotation of an output element.

Event classes: Section 1.2.2 [annotate-output-event], page 39, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.6 [Balloon_engraver], page 236.

Properties:

`name` (symbol):
`'AnnotateOutputEvent`

Name of this music object.

`types` (list):
`'(general-music event annotate-output-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.3 ApplyContext

Call the argument with the current context during interpreting phase.

Properties:

`iterator-ctor` (procedure):
`ly:apply-context-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'ApplyContext`

Name of this music object.

`types` (list):
`'(general-music apply-context)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.4 ApplyOutputEvent

Call the argument with all current grobs during interpreting phase.

Syntax: `\applyOutput #'context func`

Arguments to *func* are 1. the grob, 2. the originating context, and 3. the context where *func* is called.

Event classes: Section 1.2.3 [apply-output-event], page 39, Section 1.2.30 [layout-instruction-event], page 42, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.78 [Output_property_engraver], page 260.

Properties:

`name` (symbol):
`'ApplyOutputEvent`
Name of this music object.

`types` (list):
`'(general-music event apply-output-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.5 ArpeggioEvent

Make an arpeggio on this note.

Syntax: *note*`-\arpeggio`

Event classes: Section 1.2.4 [arpeggio-event], page 39, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.3 [Arpeggio_engraver], page 234.

Properties:

`name` (symbol):
`'ArpeggioEvent`
Name of this music object.

`types` (list):
`'(general-music arpeggio-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.6 ArticulationEvent

Add an articulation marking to a note.

Syntax: *note*`xy`, where `x` is a direction (`^` for up or `_` for down), or LilyPond's choice (no direction specified), and where `y` is an articulation (such as `-.`, `->`, `\tenuto`, `\downbow`). See the Notation Reference for details.

Event classes: Section 1.2.5 [articulation-event], page 40, Section 1.2.38 [music-event], page 43, Section 1.2.53 [script-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.97 [Script_engraver], page 266.

Properties:

`name` (symbol):
`'ArticulationEvent`
Name of this music object.

`types` (list):
`'(general-music event articulation-event script-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.7 AutoChangeMusic

Used for making voices that switch between piano staves automatically.

Properties:

`iterator-ctor` (procedure):
`ly:auto-change-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-wrapper::length-callback`
How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'AutoChangeMusic`
Name of this music object.

`start-callback` (procedure):
`ly:music-wrapper::start-callback`
Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(general-music music-wrapper-music auto-change-instruction)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.8 BarCheck

Check whether this music coincides with the start of the measure.

Properties:

`iterator-ctor` (procedure):
`ly:bar-check-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'BarCheck`
Name of this music object.

`types` (list):
`'(general-music bar-check)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.9 BassFigureEvent

Print a bass-figure text.

Event classes: Section 1.2.6 [bass-figure-event], page 40, Section 1.2.38 [music-event], page 43, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.37 [Figured_bass_engraver], page 246.

Properties:

`name` (symbol):
`'BassFigureEvent`

Name of this music object.

`types` (list):
`'(general-music event rhythmic-event bass-figure-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.10 BeamEvent

Start or stop a beam.

Syntax for manual control: `c8-[ c c-] c8`

Event classes: Section 1.2.7 [beam-event], page 40, Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.10 [Beam_engraver], page 237, Section 2.2.11 [Beam_performer], page 237 and Section 2.2.45 [Grace_beam_engraver], page 249.

Properties:

`name` (symbol):
`'BeamEvent`

Name of this music object.

`types` (list):
`'(general-music event beam-event span-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.11 BeamForbidEvent

Specify that a note may not auto-beamed.

Event classes: Section 1.2.8 [beam-forbid-event], page 40, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.4 [Auto_beam_engraver], page 235.

Properties:

`name` (symbol):
`'BeamForbidEvent`

Name of this music object.

`types` (list):
`'(general-music event beam-forbid-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.12 BendAfterEvent

A drop/fall/doit jazz articulation.

Event classes: Section 1.2.9 [bend-after-event], page 40, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.12 [Bend_engraver], page 238.

Properties:

`name` (symbol):
`'BendAfterEvent`

Name of this music object.

`types` (list):
`'(general-music bend-after-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.13 BreakDynamicSpanEvent

End an alignment spanner for dynamics here.

Event classes: Section 1.2.10 [break-dynamic-span-event], page 40, Section 1.2.12 [break-span-event], page 40, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.31 [Dynamic_align_engraver], page 244.

Properties:

`name` (symbol):
`'BreakDynamicSpanEvent`

Name of this music object.

`types` (list):
`'(general-music break-span-event break-dynamic-span-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.14 BreathingEvent

Create a 'breath mark' or 'comma'.

Syntax: *note*`\breathe`

Event classes: Section 1.2.13 [breathing-event], page 40, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.14 [Breathing_sign_engraver], page 238.

Properties:

`name` (symbol):
`'BreathingEvent`

Name of this music object.

`types` (list):
`'(general-music event breathing-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.15 ClusterNoteEvent

A note that is part of a cluster.

Event classes: Section 1.2.14 [cluster-note-event], page 40, Section 1.2.35 [melodic-event], page 43, Section 1.2.38 [music-event], page 43, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.18 [Cluster_spanner_engraver], page 240.

Properties:

`name` (symbol):
`'ClusterNoteEvent`
Name of this music object.

`types` (list):
`'(general-music cluster-note-event melodic-event rhythmic-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.16 CompletizeExtenderEvent

Used internally to signal the end of a lyrics block to ensure extenders are completed correctly when a `Lyrics` context ends before its associated `Voice` context.

Event classes: Section 1.2.15 [completize-extender-event], page 41, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.36 [Extender_engraver], page 246.

Properties:

`name` (symbol):
`'CompletizeExtenderEvent`
Name of this music object.

`types` (list):
`'(general-music completize-extender-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.17 ContextChange

Change staves in Piano staff.

Syntax: `\change Staff = new-id`

Properties:

`iterator-ctor` (procedure):
`ly:change-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'ContextChange`
Name of this music object.

`types` (list):
`'(general-music translator-change-instruction)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.18 ContextSpeccedMusic

Interpret the argument music within a specific context.

Properties:

`iterator-ctor` (procedure):
`ly:context-specced-music-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-wrapper::length-callback`

How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'ContextSpeccedMusic`

Name of this music object.

`start-callback` (procedure):
`ly:music-wrapper::start-callback`

Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(context-specification general-music music-wrapper-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.19 CrescendoEvent

Begin or end a crescendo.

Syntax: *note*`\<` ... *note*`\!`

An alternative syntax is *note*`\cr` ... *note*`\endcr`.

Event classes: Section 1.2.16 [crescendo-event], page 41, Section 1.2.38 [music-event], page 43, Section 1.2.60 [span-dynamic-event], page 46, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.32 [Dynamic_engraver], page 245, Section 2.2.33 [Dynamic_performer], page 245 and Section 2.2.70 [New_dynamic_engraver], page 257.

Properties:

`name` (symbol):
`'CrescendoEvent`

Name of this music object.

`types` (list):
`'(general-music span-event span-dynamic-event crescendo-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.20 DecrescendoEvent

Begin or end a decrescendo.

Syntax: *note*`\>` ... *note*`\!`

An alternative syntax is *note*`\decr` ... *note*`\enddecr`.

Event classes: Section 1.2.17 [decrescendo-event], page 41, Section 1.2.38 [music-event], page 43, Section 1.2.60 [span-dynamic-event], page 46, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.32 [Dynamic_engraver], page 245, Section 2.2.33 [Dynamic_performer], page 245 and Section 2.2.70 [New_dynamic_engraver], page 257.

Properties:

`name` (symbol):
`'DecrescendoEvent`
Name of this music object.

`types` (list):
`'(general-music span-event span-dynamic-event decrescendo-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.21 DoublePercentEvent

Used internally to signal double percent repeats.

Event classes: Section 1.2.18 [double-percent-event], page 41, Section 1.2.38 [music-event], page 43, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.28 [Double_percent_repeat_engraver], page 243.

Properties:

`name` (symbol):
`'DoublePercentEvent`
Name of this music object.

`types` (list):
`'(general-music event double-percent-event rhythmic-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.22 EpisemaEvent

Begin or end an episema.

Event classes: Section 1.2.20 [episema-event], page 41, Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.35 [Episema_engraver], page 245.

Properties:

`name` (symbol):
`'EpisemaEvent`
Name of this music object.

`types` (list):
`'(general-music span-event event episema-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.23 Event

Atomic music event.

Properties:

`name` (symbol):
`'Event`
Name of this music object.

`types` (list):
`'(general-music event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.24 EventChord

Internally used to group a set of events.

Properties:

`iterator-ctor` (procedure):
`ly:event-chord-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-sequence::maximum-length-callback`
How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'EventChord`
Name of this music object.

`to-relative-callback` (procedure):
`ly:music-sequence::event-chord-relative-callback`
How to transform a piece of music to relative pitches.

`types` (list):
`'(general-music event-chord simultaneous-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.25 ExtenderEvent

Extend lyrics.

Event classes: Section 1.2.21 [extender-event], page 41, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.36 [Extender_engraver], page 246.

Properties:

`name` (symbol):
`'ExtenderEvent`
Name of this music object.

`types` (list):
`'(general-music extender-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.26 FingeringEvent

Specify what finger to use for this note.

Event classes: Section 1.2.22 [fingering-event], page 41, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.39 [Fingering_engraver], page 247, Section 2.2.43 [Fretboard_engraver], page 248 and Section 2.2.114 [Tab_note_heads_engraver], page 270.

Properties:

`name` (symbol):
`'FingeringEvent`

Name of this music object.

`types` (list):
`'(general-music fingering-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.27 FootnoteEvent

Footnote a grob.

Event classes: Section 1.2.23 [footnote-event], page 41, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.41 [Footnote_engraver], page 247.

Properties:

`name` (symbol):
`'FootnoteEvent`

Name of this music object.

`types` (list):
`'(general-music event footnote-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.28 GlissandoEvent

Start a glissando on this note.

Event classes: Section 1.2.24 [glissando-event], page 41, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.44 [Glissando_engraver], page 249.

Properties:

`name` (symbol):
`'GlissandoEvent`

Name of this music object.

`types` (list):
`'(general-music glissando-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.29 GraceMusic

Interpret the argument as grace notes.

Properties:

`iterator-ctor` (procedure):
`ly:grace-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length` (moment):
`#<Mom 0>`
The duration of this music.

`name` (symbol):
`'GraceMusic`
Name of this music object.

`start-callback` (procedure):
`ly:grace-music::start-callback`
Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(grace-music music-wrapper-music general-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.30 HarmonicEvent

Mark a note as harmonic.

Event classes: Section 1.2.25 [harmonic-event], page 42, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Not accepted by any engraver or performer.

Properties:

`name` (symbol):
`'HarmonicEvent`
Name of this music object.

`types` (list):
`'(general-music event harmonic-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.31 HyphenEvent

A hyphen between lyric syllables.

Event classes: Section 1.2.26 [hyphen-event], page 42, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.53 [Hyphen_engraver], page 251.

Properties:

`name` (symbol):
`'HyphenEvent`
Name of this music object.

`types` (list):
`'(general-music hyphen-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.32 KeyChangeEvent

Change the key signature.

Syntax: `\key` *name scale*

Event classes: Section 1.2.27 [key-change-event], page 42, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.57 [Key_engraver], page 252 and Section 2.2.58 [Key_performer], page 253.

Properties:

`name` (symbol):
`'KeyChangeEvent`
Name of this music object.

`to-relative-callback` (procedure):
`#<procedure #f (x p)>`
How to transform a piece of music to relative pitches.

`types` (list):
`'(general-music key-change-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.33 LabelEvent

Place a bookmarking label.

Event classes: Section 1.2.28 [label-event], page 42, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.80 [Paper_column_engraver], page 261.

Properties:

`name` (symbol):
`'LabelEvent`
Name of this music object.

`types` (list):
`'(general-music label-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.34 LaissezVibrerEvent

Don't damp this chord.

Syntax: *note*`\laissezVibrer`

Event classes: Section 1.2.29 [laissez-vibrer-event], page 42, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.59 [Laissez_vibrer_engraver], page 254.

Properties:

`name` (symbol):
`'LaissezVibrerEvent`
Name of this music object.

`types` (list):
`'(general-music event laissez-vibrer-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.35 LigatureEvent

Start or end a ligature.

Event classes: Section 1.2.31 [ligature-event], page 42, Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.61 [Ligature_bracket_engraver], page 254, Section 2.2.67 [Mensural_ligature_engraver], page 256 and Section 2.2.129 [Vaticana_ligature_engraver], page 275.

Properties:

`name` (symbol):
`'LigatureEvent`
Name of this music object.

`types` (list):
`'(general-music span-event ligature-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.36 LineBreakEvent

Allow, forbid or force a line break.

Event classes: Section 1.2.11 [break-event], page 40, Section 1.2.32 [line-break-event], page 42, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.79 [Page_turn_engraver], page 260 and Section 2.2.80 [Paper_column_engraver], page 261.

Properties:

`name` (symbol):
`'LineBreakEvent`
Name of this music object.

`types` (list):
`'(general-music line-break-event break-event event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.37 LyricCombineMusic

Align lyrics to the start of notes.

Syntax: `\lyricsto` *voicename lyrics*

Properties:

`iterator-ctor` (procedure):
`ly:lyric-combine-music-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length` (moment):
`#<Mom 0>`

The duration of this music.

`name` (symbol):
`'LyricCombineMusic`

Name of this music object.

`types` (list):
`'(general-music lyric-combine-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.38 LyricEvent

A lyric syllable. Must be entered in lyrics mode, i.e., `\lyrics { twinkle4 twinkle4 }` .

Event classes: Section 1.2.33 [lyric-event], page 42, Section 1.2.38 [music-event], page 43, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.62 [Lyric_engraver], page 254 and Section 2.2.63 [Lyric_performer], page 255.

Properties:

`name` (symbol):
`'LyricEvent`

Name of this music object.

`types` (list):
`'(general-music rhythmic-event lyric-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.39 MarkEvent

Insert a rehearsal mark.

Syntax: `\mark` *marker*

Example: `\mark "A"`

Event classes: Section 1.2.34 [mark-event], page 42, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.64 [Mark_engraver], page 255.

Properties:

`name` (symbol):
`'MarkEvent`

Name of this music object.

`types` (list):
`'(general-music mark-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.40 MultiMeasureRestEvent

Used internally by `MultiMeasureRestMusic` to signal rests.

Event classes: Section 1.2.36 [multi-measure-rest-event], page 43, Section 1.2.38 [music-event], page 43, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.69 [Multi_measure_rest_engraver], page 257.

Properties:

`name` (symbol):
`'MultiMeasureRestEvent`
Name of this music object.

`types` (list):
`'(general-music event rhythmic-event multi-measure-rest-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.41 MultiMeasureRestMusic

Rests that may be compressed into Multi rests.

Syntax: `R2.*4` for 4 measures in 3/4 time.

Properties:

`elements-callback` (procedure):
`mm-rest-child-list`
Return a list of children, for use by a sequential iterator. Takes a single music parameter.

`iterator-ctor` (procedure):
`ly:sequential-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'MultiMeasureRestMusic`
Name of this music object.

`types` (list):
`'(general-music multi-measure-rest)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.42 MultiMeasureTextEvent

Texts on multi measure rests.

Syntax: `R-\markup { \roman "bla" }`

Note the explicit font switch.

Event classes: Section 1.2.37 [multi-measure-text-event], page 43, Section 1.2.38 [music-event], page 43 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.69 [Multi_measure_rest_engraver], page 257.

Properties:

`name` (symbol):
`'MultiMeasureTextEvent`
Name of this music object.

`types` (list):
`'(general-music event multi-measure-text-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.43 Music

Generic type for music expressions.

Properties:

`name` (symbol):
`'Music`

Name of this music object.

`types` (list):
`'(general-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.44 NoteEvent

A note.

Event classes: Section 1.2.35 [melodic-event], page 43, Section 1.2.38 [music-event], page 43, Section 1.2.39 [note-event], page 43, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.15 [Chord_name_engraver], page 238, Section 2.2.20 [Completion_heads_engraver], page 240, Section 2.2.29 [Drum_note_performer], page 244, Section 2.2.30 [Drum_notes_engraver], page 244, Section 2.2.43 [Fretboard_engraver], page 248, Section 2.2.73 [Note_heads_engraver], page 259, Section 2.2.74 [Note_name_engraver], page 259, Section 2.2.75 [Note_performer], page 259, Section 2.2.82 [Part_combine_engraver], page 261 and Section 2.2.114 [Tab_note_heads_engraver], page 270.

Properties:

`name` (symbol):
`'NoteEvent`

Name of this music object.

`types` (list):
`'(general-music event note-event rhythmic-event melodic-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.45 NoteGroupingEvent

Start or stop grouping brackets.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.40 [note-grouping-event], page 44 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.52 [Horizontal_bracket_engraver], page 251.

Properties:

`name` (symbol):
`'NoteGroupingEvent`

Name of this music object.

`types` (list):
`'(general-music event note-grouping-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.46 OttavaMusic

Start or stop an ottava bracket.

Properties:

`elements-callback` (procedure):
`make-ottava-set`
Return a list of children, for use by a sequential iterator. Takes a single music parameter.

`iterator-ctor` (procedure):
`ly:sequential-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'OttavaMusic`
Name of this music object.

`types` (list):
`'(general-music ottava-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.47 OverrideProperty

Extend the definition of a graphical object.

Syntax: `\override` [*context* `.`] *object property* `=` *value*

Properties:

`iterator-ctor` (procedure):
`ly:push-property-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'OverrideProperty`
Name of this music object.

`types` (list):
`'(general-music layout-instruction-event override-property-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.48 PageBreakEvent

Allow, forbid or force a page break.

Event classes: Section 1.2.11 [break-event], page 40, Section 1.2.38 [music-event], page 43, Section 1.2.41 [page-break-event], page 44 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.79 [Page_turn_engraver], page 260 and Section 2.2.80 [Paper_column_engraver], page 261.

Properties:

`name` (symbol):
: `'PageBreakEvent`

  Name of this music object.

`types` (list):
: `'(general-music break-event page-break-event event)`

  The types of this music object; determines by what engraver this music expression is processed.

1.1.49 PageTurnEvent

Allow, forbid or force a page turn.

Event classes: Section 1.2.11 [break-event], page 40, Section 1.2.38 [music-event], page 43, Section 1.2.42 [page-turn-event], page 44 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.79 [Page_turn_engraver], page 260 and Section 2.2.80 [Paper_column_engraver], page 261.

Properties:

`name` (symbol):
: `'PageTurnEvent`

  Name of this music object.

`types` (list):
: `'(general-music break-event page-turn-event event)`

  The types of this music object; determines by what engraver this music expression is processed.

1.1.50 PartCombineForceEvent

Override the part-combiner's strategy.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.44 [part-combine-force-event], page 44 and Section 1.2.63 [StreamEvent], page 46.

Not accepted by any engraver or performer.

Properties:

`name` (symbol):
: `'PartCombineForceEvent`

  Name of this music object.

`types` (list):
: `'(general-music part-combine-force-event event)`

  The types of this music object; determines by what engraver this music expression is processed.

1.1.51 PartCombineMusic

Combine two parts on a staff, either merged or as separate voices.

Properties:

`iterator-ctor` (procedure):
: `ly:part-combine-iterator::constructor`

  Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
: `ly:music-sequence::maximum-length-callback`

  How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'PartCombineMusic`

Name of this music object.

`start-callback` (procedure):
`ly:music-sequence::minimum-start-callback`

Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(general-music part-combine-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.52 PartialSet

Create an anacrusis or upbeat (partial measure).

Properties:

`iterator-ctor` (procedure):
`ly:partial-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'PartialSet`

Name of this music object.

`types` (list):
`'(general-music partial-set)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.53 PercentEvent

Used internally to signal percent repeats.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.46 [percent-event], page 44, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.83 [Percent_repeat_engraver], page 262.

Properties:

`name` (symbol):
`'PercentEvent`

Name of this music object.

`types` (list):
`'(general-music event percent-event rhythmic-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.54 PercentRepeatedMusic

Repeats encoded by percents and slashes.

Properties:

`iterator-ctor` (procedure):
: `ly:percent-repeat-iterator::constructor`

  Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
: `ly:repeated-music::unfolded-music-length`

  How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
: `'PercentRepeatedMusic`

  Name of this music object.

`start-callback` (procedure):
: `ly:repeated-music::first-start`

  Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
: `'(general-music repeated-music percent-repeated-music)`

  The types of this music object; determines by what engraver this music expression is processed.

1.1.55 PesOrFlexaEvent

Within a ligature, mark the previous and the following note to form a pes (if melody goes up) or a flexa (if melody goes down).

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.47 [pes-or-flexa-event], page 44 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.129 [Vaticana_ligature_engraver], page 275.

Properties:

`name` (symbol):
: `'PesOrFlexaEvent`

  Name of this music object.

`types` (list):
: `'(general-music pes-or-flexa-event event)`

  The types of this music object; determines by what engraver this music expression is processed.

1.1.56 PhrasingSlurEvent

Start or end phrasing slur.

Syntax: *note*`\(` and *note*`\)`

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.48 [phrasing-slur-event], page 45, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.84 [Phrasing_slur_engraver], page 262.

Properties:

`name` (symbol):
: `'PhrasingSlurEvent`

  Name of this music object.

`spanner-id` (string):
`""`

Identifier to distinguish concurrent spanners.

`types` (list):
`'(general-music span-event event phrasing-slur-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.57 PropertySet

Set a context property.

Syntax: `\set` *`context.prop = scheme-val`*

Properties:

`iterator-ctor` (procedure):
`ly:property-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'PropertySet`

Name of this music object.

`types` (list):
`'(layout-instruction-event general-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.58 PropertyUnset

Restore the default setting for a context property. See Section 1.1.57 [PropertySet], page 22.

Syntax: `\unset` *`context.prop`*

Properties:

`iterator-ctor` (procedure):
`ly:property-unset-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'PropertyUnset`

Name of this music object.

`types` (list):
`'(layout-instruction-event general-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.59 QuoteMusic

Quote preprocessed snippets of music.

Properties:

`iterator-ctor` (procedure):
`ly:music-wrapper-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-wrapper::length-callback`

How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'QuoteMusic`

Name of this music object.

`start-callback` (procedure):
`ly:music-wrapper::start-callback`

Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(general-music music-wrapper-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.60 RelativeOctaveCheck

Check if a pitch is in the correct octave.

Properties:

`name` (symbol):
`'RelativeOctaveCheck`

Name of this music object.

`to-relative-callback` (procedure):
`ly:relative-octave-check::relative-callback`

How to transform a piece of music to relative pitches.

`types` (list):
`'(general-music relative-octave-check)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.61 RelativeOctaveMusic

Music that was entered in relative octave notation.

Properties:

`iterator-ctor` (procedure):
`ly:music-wrapper-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-wrapper::length-callback`

How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'RelativeOctaveMusic`

Name of this music object.

`start-callback` (procedure):
`ly:music-wrapper::start-callback`

Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`to-relative-callback` (procedure):
`ly:relative-octave-music::relative-callback`

How to transform a piece of music to relative pitches.

`types` (list):
`'(music-wrapper-music general-music relative-octave-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.62 RepeatSlashEvent

Used internally to signal beat repeats.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.49 [repeat-slash-event], page 45, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.100 [Slash_repeat_engraver], page 267.

Properties:

`name` (symbol):
`'RepeatSlashEvent`

Name of this music object.

`types` (list):
`'(general-music event repeat-slash-event rhythmic-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.63 RepeatTieEvent

Ties for starting a second volta bracket.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.50 [repeat-tie-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.91 [Repeat_tie_engraver], page 265.

Properties:

`name` (symbol):
`'RepeatTieEvent`

Name of this music object.

`types` (list):
`'(general-music event repeat-tie-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.64 RepeatedChord

A chord repetition

Properties:

`iterator-ctor` (procedure):
`ly:music-wrapper-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-wrapper::length-callback`
How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'RepeatedChord`
Name of this music object.

`start-callback` (procedure):
`ly:music-wrapper::start-callback`
Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`to-relative-callback` (procedure):
`ly:music-sequence::repeated-chord-relative-callback`
How to transform a piece of music to relative pitches.

`types` (list):
`'(general-music music-wrapper-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.65 RepeatedMusic

Repeat music in different ways.

Properties:

`name` (symbol):
`'RepeatedMusic`
Name of this music object.

`types` (list):
`'(general-music repeated-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.66 RestEvent

A Rest.

Syntax: `r4` for a quarter rest.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.51 [rest-event], page 45, Section 1.2.52 [rhythmic-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.15 [Chord_name_engraver], page 238, Section 2.2.21 [Completion_rest_engraver], page 241, Section 2.2.37 [Figured_bass_engraver], page 246 and Section 2.2.93 [Rest_engraver], page 265.

Properties:

`name` (symbol):
`'RestEvent`
Name of this music object.

`types` (list):
`'(general-music event rhythmic-event rest-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.67 RevertProperty

The opposite of Section 1.1.47 [OverrideProperty], page 18: remove a previously added property from a graphical object definition.

Properties:

`iterator-ctor` (procedure):
`ly:pop-property-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'RevertProperty`
Name of this music object.

`types` (list):
`'(general-music layout-instruction-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.68 ScriptEvent

Add an articulation mark to a note.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.53 [script-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Not accepted by any engraver or performer.

Properties:

`name` (symbol):
`'ScriptEvent`
Name of this music object.

`types` (list):
`'(general-music event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.69 SequentialMusic

Music expressions concatenated.

Syntax: `\sequential { ... }` or simply `{ ... }`

Properties:

`elements-callback` (procedure):
`#<procedure #f (m)>`
Return a list of children, for use by a sequential iterator. Takes a single music parameter.

`iterator-ctor` (procedure):
`ly:sequential-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-sequence::cumulative-length-callback`

How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'SequentialMusic`

Name of this music object.

`start-callback` (procedure):
`ly:music-sequence::first-start-callback`

Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(general-music sequential-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.70 SimultaneousMusic

Music playing together.

Syntax: `\simultaneous { ... }` or `<< ... >>`

Properties:

`iterator-ctor` (procedure):
`ly:simultaneous-music-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-sequence::maximum-length-callback`

How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'SimultaneousMusic`

Name of this music object.

`start-callback` (procedure):
`ly:music-sequence::minimum-start-callback`

Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`to-relative-callback` (procedure):
`ly:music-sequence::simultaneous-relative-callback`

How to transform a piece of music to relative pitches.

`types` (list):
`'(general-music simultaneous-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.71 SkipEvent

Filler that takes up duration, but does not print anything.

Syntax: `s4` for a skip equivalent to a quarter rest.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.52 [rhythmic-event], page 45, Section 1.2.54 [skip-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Not accepted by any engraver or performer.

Properties:

`name` (symbol):
`'SkipEvent`

Name of this music object.

`types` (list):
`'(general-music event rhythmic-event skip-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.72 SkipMusic

Filler that takes up duration, does not print anything, and also does not create staves or voices implicitly.

Syntax: `\skip` *duration*

Properties:

`iterator-ctor` (procedure):
`ly:simple-music-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-duration-length`

How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'SkipMusic`

Name of this music object.

`types` (list):
`'(general-music event rhythmic-event skip-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.73 SlurEvent

Start or end slur.

Syntax: *note*`(` and *note*`)`

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.55 [slur-event], page 45, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.101 [Slur_engraver], page 267 and Section 2.2.102 [Slur_performer], page 267.

Properties:

`name` (symbol):
`'SlurEvent`

Name of this music object.

`spanner-id` (string):
`""`

Identifier to distinguish concurrent spanners.

`types` (list):
`'(general-music span-event event slur-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.74 SoloOneEvent

Print 'Solo 1'.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.43 [part-combine-event], page 44, Section 1.2.56 [solo-one-event], page 45 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.82 [Part_combine_engraver], page 261.

Properties:

`name` (symbol):
`'SoloOneEvent`

Name of this music object.

`part-combine-status` (symbol):
`'solo1`

Change to what kind of state? Options are `solo1`, `solo2` and `unisono`.

`types` (list):
`'(general-music event part-combine-event solo-one-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.75 SoloTwoEvent

Print 'Solo 2'.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.43 [part-combine-event], page 44, Section 1.2.57 [solo-two-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.82 [Part_combine_engraver], page 261.

Properties:

`name` (symbol):
`'SoloTwoEvent`

Name of this music object.

`part-combine-status` (symbol):
`'solo2`

Change to what kind of state? Options are `solo1`, `solo2` and `unisono`.

`types` (list):
`'(general-music event part-combine-event solo-two-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.76 SostenutoEvent

Depress or release sostenuto pedal.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.45 [pedal-event], page 44, Section 1.2.58 [sostenuto-event], page 46, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.86 [Piano_pedal_engraver], page 263 and Section 2.2.87 [Piano_pedal_performer], page 264.

Properties:

`name` (symbol):
`'SostenutoEvent`

Name of this music object.

`types` (list):
`'(general-music event pedal-event sostenuto-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.77 SpacingSectionEvent

Start a new spacing section.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.59 [spacing-section-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.103 [Spacing_engraver], page 268.

Properties:

`name` (symbol):
`'SpacingSectionEvent`

Name of this music object.

`types` (list):
`'(general-music event spacing-section-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.78 SpanEvent

Event for anything that is started at a different time than stopped.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Not accepted by any engraver or performer.

Properties:

`name` (symbol):
`'SpanEvent`

Name of this music object.

`types` (list):
`'(general-music event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.79 StaffSpanEvent

Start or stop a staff symbol.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46, Section 1.2.62 [staff-span-event], page 46 and Section 1.2.63 [StreamEvent], page 46.

Accepted by: Section 2.2.109 [Staff_symbol_engraver], page 269.

Properties:

`name` (symbol):
`'StaffSpanEvent`

Name of this music object.

`types` (list):
`'(general-music event span-event staff-span-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.80 StringNumberEvent

Specify on which string to play this note.

Syntax: `\`*`number`*

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.64 [string-number-event], page 47.

Accepted by: Section 2.2.43 [Fretboard_engraver], page 248 and Section 2.2.114 [Tab_note_heads_engraver], page 270.

Properties:

`name` (symbol):
`'StringNumberEvent`

Name of this music object.

`types` (list):
`'(general-music string-number-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.81 StrokeFingerEvent

Specify with which finger to pluck a string.

Syntax: `\rightHandFinger` *text*

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.65 [stroke-finger-event], page 47.

Accepted by: Section 2.2.39 [Fingering_engraver], page 247.

Properties:

`name` (symbol):
`'StrokeFingerEvent`

Name of this music object.

`types` (list):
`'(general-music stroke-finger-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.82 SustainEvent

Depress or release sustain pedal.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.45 [pedal-event], page 44, Section 1.2.61 [span-event], page 46, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.66 [sustain-event], page 47.

Accepted by: Section 2.2.86 [Piano_pedal_engraver], page 263 and Section 2.2.87 [Piano_pedal_performer], page 264.

Properties:

`name` (symbol):
`'SustainEvent`

Name of this music object.

`types` (list):
`'(general-music event pedal-event sustain-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.83 TempoChangeEvent

A metronome mark or tempo indication.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.67 [tempo-change-event], page 47.

Accepted by: Section 2.2.68 [Metronome_mark_engraver], page 256.

Properties:

`name` (symbol):
`'TempoChangeEvent`

Name of this music object.

`types` (list):
`'(general-music event tempo-change-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.84 TextScriptEvent

Print text.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.53 [script-event], page 45, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.68 [text-script-event], page 47.

Accepted by: Section 2.2.118 [Text_engraver], page 272.

Properties:

`name` (symbol):
`'TextScriptEvent`

Name of this music object.

`types` (list):
`'(general-music script-event text-script-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.85 TextSpanEvent

Start a text spanner, for example, an octavation.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.69 [text-span-event], page 48.

Accepted by: Section 2.2.119 [Text_spanner_engraver], page 272.

Properties:

`name` (symbol):
`'TextSpanEvent`

Name of this music object.

`types` (list):
`'(general-music span-event event text-span-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.86 TieEvent

A tie.

Syntax: *note*`-~`

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.70 [tie-event], page 48.

Accepted by: Section 2.2.120 [Tie_engraver], page 272 and Section 2.2.121 [Tie_performer], page 273.

Properties:

`name` (symbol):
`'TieEvent`

Name of this music object.

`types` (list):
`'(general-music tie-event event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.87 TimeScaledMusic

Multiply durations, as in tuplets.

Syntax: `\times` *`fraction music`*, e.g., `\times 2/3 { ... }` for triplets.

Properties:

`iterator-ctor` (procedure):
`ly:tuplet-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-wrapper::length-callback`

How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'TimeScaledMusic`

Name of this music object.

`start-callback` (procedure):
`ly:music-wrapper::start-callback`
Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(time-scaled-music music-wrapper-music general-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.88 TimeSignatureMusic

Set a new time signature

Properties:

`elements-callback` (procedure):
`make-time-signature-set`
Return a list of children, for use by a sequential iterator. Takes a single music parameter.

`iterator-ctor` (procedure):
`ly:sequential-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`name` (symbol):
`'TimeSignatureMusic`
Name of this music object.

`types` (list):
`'(general-music time-signature-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.89 TransposedMusic

Music that has been transposed.

Properties:

`iterator-ctor` (procedure):
`ly:music-wrapper-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-wrapper::length-callback`
How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'TransposedMusic`
Name of this music object.

`start-callback` (procedure):
`ly:music-wrapper::start-callback`
Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`to-relative-callback` (procedure):
`ly:relative-octave-music::no-relative-callback`

How to transform a piece of music to relative pitches.

`types` (list):
`'(music-wrapper-music general-music transposed-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.90 TremoloEvent

Unmeasured tremolo.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.71 [tremolo-event], page 48.

Accepted by: Section 2.2.112 [Stem_engraver], page 270.

Properties:

`name` (symbol):
`'TremoloEvent`

Name of this music object.

`types` (list):
`'(general-music event tremolo-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.91 TremoloRepeatedMusic

Repeated notes denoted by tremolo beams.

Properties:

`iterator-ctor` (procedure):
`ly:chord-tremolo-iterator::constructor`

Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:repeated-music::folded-music-length`

How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'TremoloRepeatedMusic`

Name of this music object.

`start-callback` (procedure):
`ly:repeated-music::first-start`

Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(general-music repeated-music tremolo-repeated-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.92 TremoloSpanEvent

Tremolo over two stems.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.72 [tremolo-span-event], page 48.

Accepted by: Section 2.2.16 [Chord_tremolo_engraver], page 239.

Properties:

`name` (symbol):
`'TremoloSpanEvent`

Name of this music object.

`types` (list):
`'(general-music event span-event tremolo-span-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.93 TrillSpanEvent

Start a trill spanner.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.73 [trill-span-event], page 48.

Accepted by: Section 2.2.126 [Trill_spanner_engraver], page 274.

Properties:

`name` (symbol):
`'TrillSpanEvent`

Name of this music object.

`types` (list):
`'(general-music span-event event trill-span-event)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.94 TupletSpanEvent

Used internally to signal where tuplet brackets start and stop.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.61 [span-event], page 46, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.74 [tuplet-span-event], page 48.

Accepted by: Section 2.2.127 [Tuplet_engraver], page 275.

Properties:

`name` (symbol):
`'TupletSpanEvent`

Name of this music object.

`types` (list):
`'(tuplet-span-event span-event event general-music)`

The types of this music object; determines by what engraver this music expression is processed.

1.1.95 UnaCordaEvent

Depress or release una-corda pedal.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.45 [pedal-event], page 44, Section 1.2.61 [span-event], page 46, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.75 [una-corda-event], page 48.

Accepted by: Section 2.2.86 [Piano_pedal_engraver], page 263 and Section 2.2.87 [Piano_pedal_performer], page 264.

Properties:

`name` (symbol):
`'UnaCordaEvent`
Name of this music object.

`types` (list):
`'(general-music event pedal-event una-corda-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.96 UnfoldedRepeatedMusic

Repeated music which is fully written (and played) out.

Properties:

`iterator-ctor` (procedure):
`ly:unfolded-repeat-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:repeated-music::unfolded-music-length`
How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'UnfoldedRepeatedMusic`
Name of this music object.

`start-callback` (procedure):
`ly:repeated-music::first-start`
Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(general-music repeated-music unfolded-repeated-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.97 UnisonoEvent

Print 'a 2'.

Event classes: Section 1.2.38 [music-event], page 43, Section 1.2.43 [part-combine-event], page 44, Section 1.2.63 [StreamEvent], page 46 and Section 1.2.76 [unisono-event], page 48.

Accepted by: Section 2.2.82 [Part_combine_engraver], page 261.

Properties:

`name` (symbol):
`'UnisonoEvent`
Name of this music object.

`part-combine-status` (symbol):
`'unisono`
Change to what kind of state? Options are `solo1`, `solo2` and `unisono`.

`types` (list):
`'(general-music event part-combine-event unisono-event)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.98 UnrelativableMusic

Music that cannot be converted from relative to absolute notation. For example, transposed music.

Properties:

`iterator-ctor` (procedure):
`ly:music-wrapper-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:music-wrapper::length-callback`
How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'UnrelativableMusic`
Name of this music object.

`to-relative-callback` (procedure):
`ly:relative-octave-music::no-relative-callback`
How to transform a piece of music to relative pitches.

`types` (list):
`'(music-wrapper-music general-music unrelativable-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.99 VoiceSeparator

Separate polyphonic voices in simultaneous music.

Syntax: `\\`

Properties:

`name` (symbol):
`'VoiceSeparator`
Name of this music object.

`types` (list):
`'(separator general-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.1.100 VoltaRepeatedMusic

Repeats with alternatives placed sequentially.

Properties:

`iterator-ctor` (procedure):
`ly:volta-repeat-iterator::constructor`
Function to construct a `music-event-iterator` object for this music.

`length-callback` (procedure):
`ly:repeated-music::volta-music-length`
How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`name` (symbol):
`'VoltaRepeatedMusic`
Name of this music object.

`start-callback` (procedure):
`ly:repeated-music::first-start`
Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`types` (list):
`'(general-music repeated-music volta-repeated-music)`
The types of this music object; determines by what engraver this music expression is processed.

1.2 Music classes

1.2.1 absolute-dynamic-event

Music event type `absolute-dynamic-event` is in music objects of type Section 1.1.1 [AbsoluteDynamicEvent], page 2.

Accepted by: Section 2.2.32 [Dynamic_engraver], page 245, Section 2.2.33 [Dynamic_performer], page 245 and Section 2.2.70 [New_dynamic_engraver], page 257.

1.2.2 annotate-output-event

Music event type `annotate-output-event` is in music objects of type Section 1.1.2 [AnnotateOutputEvent], page 2.

Accepted by: Section 2.2.6 [Balloon_engraver], page 236.

1.2.3 apply-output-event

Music event type `apply-output-event` is in music objects of type Section 1.1.4 [ApplyOutputEvent], page 3.

Accepted by: Section 2.2.78 [Output_property_engraver], page 260.

1.2.4 arpeggio-event

Music event type `arpeggio-event` is in music objects of type Section 1.1.5 [ArpeggioEvent], page 3.

Accepted by: Section 2.2.3 [Arpeggio_engraver], page 234.

1.2.5 articulation-event

Music event type `articulation-event` is in music objects of type Section 1.1.6 [ArticulationEvent], page 3.

Accepted by: Section 2.2.97 [Script_engraver], page 266.

1.2.6 bass-figure-event

Music event type `bass-figure-event` is in music objects of type Section 1.1.9 [BassFigureEvent], page 5.

Accepted by: Section 2.2.37 [Figured_bass_engraver], page 246.

1.2.7 beam-event

Music event type `beam-event` is in music objects of type Section 1.1.10 [BeamEvent], page 5.

Accepted by: Section 2.2.10 [Beam_engraver], page 237, Section 2.2.11 [Beam_performer], page 237 and Section 2.2.45 [Grace_beam_engraver], page 249.

1.2.8 beam-forbid-event

Music event type `beam-forbid-event` is in music objects of type Section 1.1.11 [BeamForbidEvent], page 5.

Accepted by: Section 2.2.4 [Auto_beam_engraver], page 235.

1.2.9 bend-after-event

Music event type `bend-after-event` is in music objects of type Section 1.1.12 [BendAfterEvent], page 6.

Accepted by: Section 2.2.12 [Bend_engraver], page 238.

1.2.10 break-dynamic-span-event

Music event type `break-dynamic-span-event` is in music objects of type Section 1.1.13 [BreakDynamicSpanEvent], page 6.

Not accepted by any engraver or performer.

1.2.11 break-event

Music event type `break-event` is in music objects of type Section 1.1.36 [LineBreakEvent], page 14, Section 1.1.48 [PageBreakEvent], page 18 and Section 1.1.49 [PageTurnEvent], page 19.

Accepted by: Section 2.2.79 [Page_turn_engraver], page 260 and Section 2.2.80 [Paper_column_engraver], page 261.

1.2.12 break-span-event

Music event type `break-span-event` is in music objects of type Section 1.1.13 [BreakDynamicSpanEvent], page 6.

Accepted by: Section 2.2.31 [Dynamic_align_engraver], page 244.

1.2.13 breathing-event

Music event type `breathing-event` is in music objects of type Section 1.1.14 [BreathingEvent], page 6.

Accepted by: Section 2.2.14 [Breathing_sign_engraver], page 238.

1.2.14 cluster-note-event

Music event type `cluster-note-event` is in music objects of type Section 1.1.15 [ClusterNoteEvent], page 7.

Accepted by: Section 2.2.18 [Cluster_spanner_engraver], page 240.

1.2.15 completize-extender-event

Music event type `completize-extender-event` is in music objects of type Section 1.1.16 [CompletizeExtenderEvent], page 7.

Accepted by: Section 2.2.36 [Extender_engraver], page 246.

1.2.16 crescendo-event

Music event type `crescendo-event` is in music objects of type Section 1.1.19 [CrescendoEvent], page 8.

Accepted by: Section 2.2.33 [Dynamic_performer], page 245.

1.2.17 decrescendo-event

Music event type `decrescendo-event` is in music objects of type Section 1.1.20 [DecrescendoEvent], page 9.

Accepted by: Section 2.2.33 [Dynamic_performer], page 245.

1.2.18 double-percent-event

Music event type `double-percent-event` is in music objects of type Section 1.1.21 [DoublePercentEvent], page 9.

Accepted by: Section 2.2.28 [Double_percent_repeat_engraver], page 243.

1.2.19 dynamic-event

Music event type `dynamic-event` is in music objects of type Section 1.1.1 [AbsoluteDynamicEvent], page 2.

Not accepted by any engraver or performer.

1.2.20 episema-event

Music event type `episema-event` is in music objects of type Section 1.1.22 [EpisemaEvent], page 9.

Accepted by: Section 2.2.35 [Episema_engraver], page 245.

1.2.21 extender-event

Music event type `extender-event` is in music objects of type Section 1.1.25 [ExtenderEvent], page 10.

Accepted by: Section 2.2.36 [Extender_engraver], page 246.

1.2.22 fingering-event

Music event type `fingering-event` is in music objects of type Section 1.1.26 [FingeringEvent], page 11.

Accepted by: Section 2.2.39 [Fingering_engraver], page 247, Section 2.2.43 [Fretboard_engraver], page 248 and Section 2.2.114 [Tab_note_heads_engraver], page 270.

1.2.23 footnote-event

Music event type `footnote-event` is in music objects of type Section 1.1.27 [FootnoteEvent], page 11.

Accepted by: Section 2.2.41 [Footnote_engraver], page 247.

1.2.24 glissando-event

Music event type `glissando-event` is in music objects of type Section 1.1.28 [GlissandoEvent], page 11.

Accepted by: Section 2.2.44 [Glissando_engraver], page 249.

1.2.25 harmonic-event

Music event type `harmonic-event` is in music objects of type Section 1.1.30 [HarmonicEvent], page 12.

Not accepted by any engraver or performer.

1.2.26 hyphen-event

Music event type `hyphen-event` is in music objects of type Section 1.1.31 [HyphenEvent], page 12.

Accepted by: Section 2.2.53 [Hyphen_engraver], page 251.

1.2.27 key-change-event

Music event type `key-change-event` is in music objects of type Section 1.1.32 [KeyChangeEvent], page 13.

Accepted by: Section 2.2.57 [Key_engraver], page 252 and Section 2.2.58 [Key_performer], page 253.

1.2.28 label-event

Music event type `label-event` is in music objects of type Section 1.1.33 [LabelEvent], page 13.

Accepted by: Section 2.2.80 [Paper_column_engraver], page 261.

1.2.29 laissez-vibrer-event

Music event type `laissez-vibrer-event` is in music objects of type Section 1.1.34 [LaissezVibrerEvent], page 13.

Accepted by: Section 2.2.59 [Laissez_vibrer_engraver], page 254.

1.2.30 layout-instruction-event

Music event type `layout-instruction-event` is in music objects of type Section 1.1.4 [ApplyOutputEvent], page 3.

Not accepted by any engraver or performer.

1.2.31 ligature-event

Music event type `ligature-event` is in music objects of type Section 1.1.35 [LigatureEvent], page 14.

Accepted by: Section 2.2.61 [Ligature_bracket_engraver], page 254, Section 2.2.67 [Mensural_ligature_engraver], page 256 and Section 2.2.129 [Vaticana_ligature_engraver], page 275.

1.2.32 line-break-event

Music event type `line-break-event` is in music objects of type Section 1.1.36 [LineBreakEvent], page 14.

Not accepted by any engraver or performer.

1.2.33 lyric-event

Music event type `lyric-event` is in music objects of type Section 1.1.38 [LyricEvent], page 15.

Accepted by: Section 2.2.62 [Lyric_engraver], page 254 and Section 2.2.63 [Lyric_performer], page 255.

1.2.34 mark-event

Music event type `mark-event` is in music objects of type Section 1.1.39 [MarkEvent], page 15.

Accepted by: Section 2.2.64 [Mark_engraver], page 255.

1.2.35 melodic-event

Music event type `melodic-event` is in music objects of type Section 1.1.15 [ClusterNoteEvent], page 7 and Section 1.1.44 [NoteEvent], page 17.

Not accepted by any engraver or performer.

1.2.36 multi-measure-rest-event

Music event type `multi-measure-rest-event` is in music objects of type Section 1.1.40 [MultiMeasureRestEvent], page 16.

Accepted by: Section 2.2.69 [Multi_measure_rest_engraver], page 257.

1.2.37 multi-measure-text-event

Music event type `multi-measure-text-event` is in music objects of type Section 1.1.42 [MultiMeasureTextEvent], page 16.

Accepted by: Section 2.2.69 [Multi_measure_rest_engraver], page 257.

1.2.38 music-event

Music event type `music-event` is in music objects of type Section 1.1.1 [AbsoluteDynamicEvent], page 2, Section 1.1.2 [AnnotateOutputEvent], page 2, Section 1.1.4 [ApplyOutputEvent], page 3, Section 1.1.5 [ArpeggioEvent], page 3, Section 1.1.6 [ArticulationEvent], page 3, Section 1.1.9 [BassFigureEvent], page 5, Section 1.1.10 [BeamEvent], page 5, Section 1.1.11 [BeamForbidEvent], page 5, Section 1.1.12 [BendAfterEvent], page 6, Section 1.1.13 [BreakDynamicSpanEvent], page 6, Section 1.1.14 [BreathingEvent], page 6, Section 1.1.15 [ClusterNoteEvent], page 7, Section 1.1.16 [CompletizeExtenderEvent], page 7, Section 1.1.19 [CrescendoEvent], page 8, Section 1.1.20 [DecrescendoEvent], page 9, Section 1.1.21 [DoublePercentEvent], page 9, Section 1.1.22 [EpisemaEvent], page 9, Section 1.1.25 [ExtenderEvent], page 10, Section 1.1.26 [FingeringEvent], page 11, Section 1.1.27 [FootnoteEvent], page 11, Section 1.1.28 [GlissandoEvent], page 11, Section 1.1.30 [HarmonicEvent], page 12, Section 1.1.31 [HyphenEvent], page 12, Section 1.1.32 [KeyChangeEvent], page 13, Section 1.1.33 [LabelEvent], page 13, Section 1.1.34 [LaissezVibrerEvent], page 13, Section 1.1.35 [LigatureEvent], page 14, Section 1.1.36 [LineBreakEvent], page 14, Section 1.1.38 [LyricEvent], page 15, Section 1.1.39 [MarkEvent], page 15, Section 1.1.40 [MultiMeasureRestEvent], page 16, Section 1.1.42 [MultiMeasureTextEvent], page 16, Section 1.1.44 [NoteEvent], page 17, Section 1.1.45 [NoteGroupingEvent], page 17, Section 1.1.48 [PageBreakEvent], page 18, Section 1.1.49 [PageTurnEvent], page 19, Section 1.1.50 [PartCombineForceEvent], page 19, Section 1.1.53 [PercentEvent], page 20, Section 1.1.55 [PesOrFlexaEvent], page 21, Section 1.1.56 [PhrasingSlurEvent], page 21, Section 1.1.62 [RepeatSlashEvent], page 24, Section 1.1.63 [RepeatTieEvent], page 24, Section 1.1.66 [RestEvent], page 25, Section 1.1.68 [ScriptEvent], page 26, Section 1.1.71 [SkipEvent], page 28, Section 1.1.73 [SlurEvent], page 28, Section 1.1.74 [SoloOneEvent], page 29, Section 1.1.75 [SoloTwoEvent], page 29, Section 1.1.76 [SostenutoEvent], page 30, Section 1.1.77 [SpacingSectionEvent], page 30, Section 1.1.78 [SpanEvent], page 30, Section 1.1.79 [StaffSpanEvent], page 31, Section 1.1.80 [StringNumberEvent], page 31, Section 1.1.81 [StrokeFingerEvent], page 31, Section 1.1.82 [SustainEvent], page 32, Section 1.1.83 [TempoChangeEvent], page 32, Section 1.1.84 [TextScriptEvent], page 32, Section 1.1.85 [TextSpanEvent], page 33, Section 1.1.86 [TieEvent], page 33, Section 1.1.90 [TremoloEvent], page 35, Section 1.1.92 [TremoloSpanEvent], page 36, Section 1.1.93 [TrillSpanEvent], page 36, Section 1.1.94 [TupletSpanEvent], page 36, Section 1.1.95 [UnaCordaEvent], page 37 and Section 1.1.97 [UnisonoEvent], page 37.

Not accepted by any engraver or performer.

1.2.39 note-event

Music event type `note-event` is in music objects of type Section 1.1.44 [NoteEvent], page 17.

Accepted by: Section 2.2.15 [Chord_name_engraver], page 238, Section 2.2.20 [Completion_heads_engraver], page 240, Section 2.2.29 [Drum_note_performer], page 244, Section 2.2.30 [Drum_notes_engraver], page 244, Section 2.2.43 [Fretboard_engraver], page 248, Section 2.2.73 [Note_heads_engraver], page 259, Section 2.2.74 [Note_name_engraver], page 259, Section 2.2.75 [Note_performer], page 259, Section 2.2.82 [Part_combine_engraver], page 261 and Section 2.2.114 [Tab_note_heads_engraver], page 270.

1.2.40 note-grouping-event

Music event type `note-grouping-event` is in music objects of type Section 1.1.45 [NoteGroupingEvent], page 17.

Accepted by: Section 2.2.52 [Horizontal_bracket_engraver], page 251.

1.2.41 page-break-event

Music event type `page-break-event` is in music objects of type Section 1.1.48 [PageBreakEvent], page 18.

Not accepted by any engraver or performer.

1.2.42 page-turn-event

Music event type `page-turn-event` is in music objects of type Section 1.1.49 [PageTurnEvent], page 19.

Not accepted by any engraver or performer.

1.2.43 part-combine-event

Music event type `part-combine-event` is in music objects of type Section 1.1.74 [SoloOneEvent], page 29, Section 1.1.75 [SoloTwoEvent], page 29 and Section 1.1.97 [UnisonoEvent], page 37.

Accepted by: Section 2.2.82 [Part_combine_engraver], page 261.

1.2.44 part-combine-force-event

Music event type `part-combine-force-event` is in music objects of type Section 1.1.50 [PartCombineForceEvent], page 19.

Not accepted by any engraver or performer.

1.2.45 pedal-event

Music event type `pedal-event` is in music objects of type Section 1.1.76 [SostenutoEvent], page 30, Section 1.1.82 [SustainEvent], page 32 and Section 1.1.95 [UnaCordaEvent], page 37.

Not accepted by any engraver or performer.

1.2.46 percent-event

Music event type `percent-event` is in music objects of type Section 1.1.53 [PercentEvent], page 20.

Accepted by: Section 2.2.83 [Percent_repeat_engraver], page 262.

1.2.47 pes-or-flexa-event

Music event type `pes-or-flexa-event` is in music objects of type Section 1.1.55 [PesOrFlexaEvent], page 21.

Accepted by: Section 2.2.129 [Vaticana_ligature_engraver], page 275.

1.2.48 phrasing-slur-event

Music event type `phrasing-slur-event` is in music objects of type Section 1.1.56 [PhrasingSlurEvent], page 21.

Accepted by: Section 2.2.84 [Phrasing_slur_engraver], page 262.

1.2.49 repeat-slash-event

Music event type `repeat-slash-event` is in music objects of type Section 1.1.62 [RepeatSlashEvent], page 24.

Accepted by: Section 2.2.100 [Slash_repeat_engraver], page 267.

1.2.50 repeat-tie-event

Music event type `repeat-tie-event` is in music objects of type Section 1.1.63 [RepeatTieEvent], page 24.

Accepted by: Section 2.2.91 [Repeat_tie_engraver], page 265.

1.2.51 rest-event

Music event type `rest-event` is in music objects of type Section 1.1.66 [RestEvent], page 25.

Accepted by: Section 2.2.15 [Chord_name_engraver], page 238, Section 2.2.21 [Completion_rest_engraver], page 241, Section 2.2.37 [Figured_bass_engraver], page 246 and Section 2.2.93 [Rest_engraver], page 265.

1.2.52 rhythmic-event

Music event type `rhythmic-event` is in music objects of type Section 1.1.9 [BassFigureEvent], page 5, Section 1.1.15 [ClusterNoteEvent], page 7, Section 1.1.21 [DoublePercentEvent], page 9, Section 1.1.38 [LyricEvent], page 15, Section 1.1.40 [MultiMeasureRestEvent], page 16, Section 1.1.44 [NoteEvent], page 17, Section 1.1.53 [PercentEvent], page 20, Section 1.1.62 [RepeatSlashEvent], page 24, Section 1.1.66 [RestEvent], page 25 and Section 1.1.71 [SkipEvent], page 28.

Not accepted by any engraver or performer.

1.2.53 script-event

Music event type `script-event` is in music objects of type Section 1.1.6 [ArticulationEvent], page 3, Section 1.1.68 [ScriptEvent], page 26 and Section 1.1.84 [TextScriptEvent], page 32.

Not accepted by any engraver or performer.

1.2.54 skip-event

Music event type `skip-event` is in music objects of type Section 1.1.71 [SkipEvent], page 28.

Not accepted by any engraver or performer.

1.2.55 slur-event

Music event type `slur-event` is in music objects of type Section 1.1.73 [SlurEvent], page 28.

Accepted by: Section 2.2.101 [Slur_engraver], page 267 and Section 2.2.102 [Slur_performer], page 267.

1.2.56 solo-one-event

Music event type `solo-one-event` is in music objects of type Section 1.1.74 [SoloOneEvent], page 29.

Not accepted by any engraver or performer.

1.2.57 solo-two-event

Music event type `solo-two-event` is in music objects of type Section 1.1.75 [SoloTwoEvent], page 29.

Not accepted by any engraver or performer.

1.2.58 sostenuto-event

Music event type `sostenuto-event` is in music objects of type Section 1.1.76 [SostenutoEvent], page 30.

Accepted by: Section 2.2.86 [Piano_pedal_engraver], page 263 and Section 2.2.87 [Piano_pedal_performer], page 264.

1.2.59 spacing-section-event

Music event type `spacing-section-event` is in music objects of type Section 1.1.77 [SpacingSectionEvent], page 30.

Accepted by: Section 2.2.103 [Spacing_engraver], page 268.

1.2.60 span-dynamic-event

Music event type `span-dynamic-event` is in music objects of type Section 1.1.19 [CrescendoEvent], page 8 and Section 1.1.20 [DecrescendoEvent], page 9.

Accepted by: Section 2.2.32 [Dynamic_engraver], page 245 and Section 2.2.70 [New_dynamic_engraver], page 257.

1.2.61 span-event

Music event type `span-event` is in music objects of type Section 1.1.10 [BeamEvent], page 5, Section 1.1.19 [CrescendoEvent], page 8, Section 1.1.20 [DecrescendoEvent], page 9, Section 1.1.22 [EpisemaEvent], page 9, Section 1.1.35 [LigatureEvent], page 14, Section 1.1.56 [PhrasingSlurEvent], page 21, Section 1.1.73 [SlurEvent], page 28, Section 1.1.76 [SostenutoEvent], page 30, Section 1.1.78 [SpanEvent], page 30, Section 1.1.79 [StaffSpanEvent], page 31, Section 1.1.82 [SustainEvent], page 32, Section 1.1.85 [TextSpanEvent], page 33, Section 1.1.92 [TremoloSpanEvent], page 36, Section 1.1.93 [TrillSpanEvent], page 36, Section 1.1.94 [TupletSpanEvent], page 36 and Section 1.1.95 [UnaCordaEvent], page 37.

Not accepted by any engraver or performer.

1.2.62 staff-span-event

Music event type `staff-span-event` is in music objects of type Section 1.1.79 [StaffSpanEvent], page 31.

Accepted by: Section 2.2.109 [Staff_symbol_engraver], page 269.

1.2.63 StreamEvent

Music event type `StreamEvent` is in music objects of type Section 1.1.1 [AbsoluteDynamicEvent], page 2, Section 1.1.2 [AnnotateOutputEvent], page 2, Section 1.1.4 [ApplyOutputEvent], page 3, Section 1.1.5 [ArpeggioEvent], page 3, Section 1.1.6 [ArticulationEvent], page 3, Section 1.1.9 [BassFigureEvent], page 5, Section 1.1.10 [BeamEvent], page 5, Section 1.1.11 [BeamForbidEvent], page 5, Section 1.1.12 [BendAfterEvent], page 6, Section 1.1.13 [BreakDynamicSpanEvent], page 6, Section 1.1.14 [BreathingEvent], page 6, Section 1.1.15 [ClusterNoteEvent], page 7, Section 1.1.16 [CompletizeExtenderEvent], page 7, Section 1.1.19 [CrescendoEvent], page 8, Section 1.1.20 [DecrescendoEvent], page 9, Section 1.1.21 [DoublePercentEvent], page 9, Section 1.1.22 [EpisemaEvent], page 9, Section 1.1.25 [ExtenderEvent], page 10, Section 1.1.26 [FingeringEvent], page 11, Section 1.1.27 [FootnoteEvent], page 11, Section 1.1.28 [GlissandoEvent], page 11, Section 1.1.30 [HarmonicEvent],

page 12, Section 1.1.31 [HyphenEvent], page 12, Section 1.1.32 [KeyChangeEvent], page 13, Section 1.1.33 [LabelEvent], page 13, Section 1.1.34 [LaissezVibrerEvent], page 13, Section 1.1.35 [LigatureEvent], page 14, Section 1.1.36 [LineBreakEvent], page 14, Section 1.1.38 [LyricEvent], page 15, Section 1.1.39 [MarkEvent], page 15, Section 1.1.40 [MultiMeasureRestEvent], page 16, Section 1.1.42 [MultiMeasureTextEvent], page 16, Section 1.1.44 [NoteEvent], page 17, Section 1.1.45 [NoteGroupingEvent], page 17, Section 1.1.48 [PageBreakEvent], page 18, Section 1.1.49 [PageTurnEvent], page 19, Section 1.1.50 [PartCombineForceEvent], page 19, Section 1.1.53 [PercentEvent], page 20, Section 1.1.55 [PesOrFlexaEvent], page 21, Section 1.1.56 [PhrasingSlurEvent], page 21, Section 1.1.62 [RepeatSlashEvent], page 24, Section 1.1.63 [RepeatTieEvent], page 24, Section 1.1.66 [RestEvent], page 25, Section 1.1.68 [ScriptEvent], page 26, Section 1.1.71 [SkipEvent], page 28, Section 1.1.73 [SlurEvent], page 28, Section 1.1.74 [SoloOneEvent], page 29, Section 1.1.75 [SoloTwoEvent], page 29, Section 1.1.76 [SostenutoEvent], page 30, Section 1.1.77 [SpacingSectionEvent], page 30, Section 1.1.78 [SpanEvent], page 30, Section 1.1.79 [StaffSpanEvent], page 31, Section 1.1.80 [StringNumberEvent], page 31, Section 1.1.81 [StrokeFingerEvent], page 31, Section 1.1.82 [SustainEvent], page 32, Section 1.1.83 [TempoChangeEvent], page 32, Section 1.1.84 [TextScriptEvent], page 32, Section 1.1.85 [TextSpanEvent], page 33, Section 1.1.86 [TieEvent], page 33, Section 1.1.90 [TremoloEvent], page 35, Section 1.1.92 [TremoloSpanEvent], page 36, Section 1.1.93 [TrillSpanEvent], page 36, Section 1.1.94 [TupletSpanEvent], page 36, Section 1.1.95 [UnaCordaEvent], page 37 and Section 1.1.97 [UnisonoEvent], page 37.

Not accepted by any engraver or performer.

1.2.64 string-number-event

Music event type `string-number-event` is in music objects of type Section 1.1.80 [StringNumberEvent], page 31.

Accepted by: Section 2.2.43 [Fretboard_engraver], page 248 and Section 2.2.114 [Tab_note_heads_engraver], page 270.

1.2.65 stroke-finger-event

Music event type `stroke-finger-event` is in music objects of type Section 1.1.81 [StrokeFingerEvent], page 31.

Accepted by: Section 2.2.39 [Fingering_engraver], page 247.

1.2.66 sustain-event

Music event type `sustain-event` is in music objects of type Section 1.1.82 [SustainEvent], page 32.

Accepted by: Section 2.2.86 [Piano_pedal_engraver], page 263 and Section 2.2.87 [Piano_pedal_performer], page 264.

1.2.67 tempo-change-event

Music event type `tempo-change-event` is in music objects of type Section 1.1.83 [TempoChangeEvent], page 32.

Accepted by: Section 2.2.68 [Metronome_mark_engraver], page 256.

1.2.68 text-script-event

Music event type `text-script-event` is in music objects of type Section 1.1.84 [TextScriptEvent], page 32.

Accepted by: Section 2.2.118 [Text_engraver], page 272.

1.2.69 text-span-event

Music event type `text-span-event` is in music objects of type Section 1.1.85 [TextSpanEvent], page 33.

Accepted by: Section 2.2.119 [Text_spanner_engraver], page 272.

1.2.70 tie-event

Music event type `tie-event` is in music objects of type Section 1.1.86 [TieEvent], page 33.

Accepted by: Section 2.2.120 [Tie_engraver], page 272 and Section 2.2.121 [Tie_performer], page 273.

1.2.71 tremolo-event

Music event type `tremolo-event` is in music objects of type Section 1.1.90 [TremoloEvent], page 35.

Accepted by: Section 2.2.112 [Stem_engraver], page 270.

1.2.72 tremolo-span-event

Music event type `tremolo-span-event` is in music objects of type Section 1.1.92 [TremoloSpanEvent], page 36.

Accepted by: Section 2.2.16 [Chord_tremolo_engraver], page 239.

1.2.73 trill-span-event

Music event type `trill-span-event` is in music objects of type Section 1.1.93 [TrillSpanEvent], page 36.

Accepted by: Section 2.2.126 [Trill_spanner_engraver], page 274.

1.2.74 tuplet-span-event

Music event type `tuplet-span-event` is in music objects of type Section 1.1.94 [TupletSpanEvent], page 36.

Accepted by: Section 2.2.127 [Tuplet_engraver], page 275.

1.2.75 una-corda-event

Music event type `una-corda-event` is in music objects of type Section 1.1.95 [UnaCordaEvent], page 37.

Accepted by: Section 2.2.86 [Piano_pedal_engraver], page 263 and Section 2.2.87 [Piano_pedal_performer], page 264.

1.2.76 unisono-event

Music event type `unisono-event` is in music objects of type Section 1.1.97 [UnisonoEvent], page 37.

Not accepted by any engraver or performer.

1.3 Music properties

`absolute-octave` (integer)
: The absolute octave for a octave check note.

`alteration` (number)
: Alteration for figured bass.

`articulation-type` (string)
: Key for script definitions alist.

  TODO: Consider making type into symbol.

`articulations` (list of music objects)
: Articulation events specifically for this note.

`associated-context` (string)
: Name of the Voice context associated with this `\lyricsto` section.

`augmented` (boolean)
: This figure is for an augmented figured bass (with `+` sign).

`augmented-slash` (boolean)
: This figure is for an augmented figured bass (back-slashed number).

`autosplit-end` (boolean)
: Duration of event was truncated by automatic splitting in `Completion_heads_engraver`.

`bass` (boolean)
: Set if this note is a bass note in a chord.

`beat-structure` (list)
: A beatStructure to be used in autobeaming.

`bracket-start` (boolean)
: Start a bracket here.

  TODO: Use SpanEvents?

`bracket-stop` (boolean)
: Stop a bracket here.

`break-penalty` (number)
: Penalty for line break hint.

`break-permission` (symbol)
: Whether to allow, forbid or force a line break.

`cautionary` (boolean)
: If set, this alteration needs a cautionary accidental.

`change-to-id` (string)
: Name of the context to change to.

`change-to-type` (symbol)
: Type of the context to change to.

`compress-procedure` (procedure)
: Compress this music expression. Arg 1: the music, arg 2: factor.

`context-id` (string)
: Name of context.

`context-type` (symbol)
: Type of context.

`create-new` (boolean)
: Create a fresh context.

`delta-step` (number)
: How much should a fall change pitch?

`denominator` (integer)
: Denominator in a time signature.

`descend-only` (boolean)
: If set, this `\context` only descends in the context tree.

`digit` (integer)
: Digit for fingering.

`diminished` (boolean)
: This bass figure should be slashed.

`direction` (direction)
: Print this up or down?

`drum-type` (symbol)
: Which percussion instrument to play this note on.

`duration` (duration)
: Duration of this note or lyric.

`element` (music)
: The single child of a Music_wrapper music object, or the body of a repeat.

`elements` (list of music objects)
: A list of elements for sequential of simultaneous music, or the alternatives of repeated music.

`elements-callback` (procedure)
: Return a list of children, for use by a sequential iterator. Takes a single music parameter.

`error-found` (boolean)
: If true, a parsing error was found in this expression.

`figure` (integer)
: A bass figure.

`footnote-text` (markup)
: Text to appear in a footnote.

`force-accidental` (boolean)
: If set, a cautionary accidental should always be printed on this note.

`forced-type` (symbol)
: Override for the part-combiner.

`grob-property` (symbol)
: The symbol of the grob property to set.

`grob-property-path` (list)
: A list of symbols, locating a nested grob property, e.g., `(beamed-lengths details)`.

`grob-value` (any type)
: The value of the grob property to set.

`input-tag` (any type)
: Arbitrary marker to relate input and output.

`inversion` (boolean)
: If set, this chord note is inverted.

`iterator-ctor` (procedure)
: Function to construct a `music-event-iterator` object for this music.

`label` (markup)
: Label of a mark.

`last-pitch` (pitch)
: The last pitch after relativization.

`length` (moment)
: The duration of this music.

`length-callback` (procedure)
: How to compute the duration of this music. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`line-break-permission` (symbol)
: When the music is at top-level, whether to allow, forbid or force a line break.

`metronome-count` (number or pair)
: How many beats in a minute?

`name` (symbol)
: Name of this music object.

`no-continuation` (boolean)
: If set, disallow continuation lines.

`numerator` (integer)
: Numerator of a time signature.

`octavation` (integer)
: This pitch was octavated by how many octaves? For chord inversions, this is negative.

`once` (boolean)
: Apply this operation only during one time step?

`origin` (input location)
: Where was this piece of music defined?

`original-chord` (music)
: Original chord of a repeated chord. Used by repeated chords in \relative mode, to determine the first note octave

`ottava-number` (integer)
: The octavation for `\ottava`.

`page-break-permission` (symbol)
: When the music is at top-level, whether to allow, forbid or force a page break.

`page-label` (symbol)
: The label of a page marker.

`page-marker` (boolean)
: If true, and the music expression is found at top-level, a page marker object is instanciated instead of a score.

`page-turn-permission` (symbol)
: When the music is at top-level, whether to allow, forbid or force a page turn.

`parenthesize` (boolean)
: Enclose resulting objects in parentheses?

`part-combine-status` (symbol)
: Change to what kind of state? Options are `solo1`, `solo2` and `unisono`.

`partial-duration` (duration)
: The length of a partial measure as a duration.

`pitch` (pitch)
: The pitch of this note.

`pitch-alist` (list)
: A list of pitches jointly forming the scale of a key signature.

`pop-first` (boolean)
: Do a revert before we try to do a override on some grob property.

`prob-property` (symbol)
: The symbol of the prob property to set.

`procedure` (procedure)
: The function to run with `\applycontext`. It must take a single argument, being the context.

`property-operations` (list)
: Do these operations for instantiating the context.

`quoted-context-id` (string)
: The ID of the context to direct quotes to, e.g., `cue`.

`quoted-context-type` (symbol)
: The name of the context to direct quotes to, e.g., `Voice`.

`quoted-events` (vector)
: A vector of with `moment` and `event-list` entries.

`quoted-music-clef` (string)
: The clef of the voice to quote.

`quoted-music-name` (string)
: The name of the voice to quote.

`quoted-transposition` (pitch)
: The pitch used for the quote, overriding `\transposition`.

`quoted-voice-direction` (direction)
: Should the quoted voice be up-stem or down-stem?

`repeat-count` (integer)
: Do a `\repeat` how often?

`slash-count` (integer)
: The number of slashes in a single-beat repeat. If zero, signals a beat containing varying durations.

`span-direction` (direction)
: Does this start or stop a spanner?

`span-text` (markup)
: The displayed text for dynamic text spanners (e.g., cresc.)

`span-type` (symbol)
: What kind of dynamic spanner should be created? Options are `'text` and `'hairpin`.

`spanner-id` (string)
: Identifier to distinguish concurrent spanners.

`split-list` (list)
: Splitting moments for part combiner.

`start-callback` (procedure)
: Function to compute the negative length of starting grace notes. This property can only be defined as initializer in '`scm/define-music-types.scm`'.

`string-number` (integer)
: The number of the string in a `StringNumberEvent`.

`symbol` (symbol)
: Grob name to perform an override or revert on.

`tags` (list)
: List of symbols that for denoting extra details, e.g., `\tag #'part ...` could tag a piece of music as only being active in a part.

`tempo-unit` (duration)
: The unit for the metronome count.

`text` (markup)
: Markup expression to be printed.

`to-relative-callback` (procedure)
: How to transform a piece of music to relative pitches.

`tonic` (pitch)
: Base of the scale.

`tremolo-type` (integer)
: Speed of tremolo, e.g., 16 for `c4:16`.

`trill-pitch` (pitch)
: Pitch of other note of the trill.

`tweaks` (list)
: An alist of properties to override in the backend for the grob made of this event.

`type` (symbol)
: The type of this music object. Determines iteration in some cases.

`types` (list)
: The types of this music object; determines by what engraver this music expression is processed.

`untransposable` (boolean)
: If set, this music is not transposed.

`value` (any type)
: Assignment value for a translation property.

`void` (boolean)
: If this property is `#t`, then the music expression is to be discarded by the toplevel music handler.

`what` (symbol)
: What to change for auto-change.

  FIXME: Naming.

`X-offset` (number)
: Offset of resulting grob; only used for balloon texts.

`Y-offset` (number)
: Offset of resulting grob; only used for balloon texts.

2 Translation

2.1 Contexts

2.1.1 ChoirStaff

Identical to `StaffGroup` except that the contained staves are not connected vertically.

This context creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332, Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383 and Section 3.1.129 [VerticalAlignment], page 399.

This context sets the following properties:

- Set translator property `instrumentName` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.
- Set translator property `shortVocalName` to `'()`.
- Set translator property `systemStartDelimiter` to `'SystemStartBracket`.
- Set translator property `topLevelAlignment` to `#f`.
- Set translator property `vocalName` to `'()`.

Context ChoirStaff can contain Section 2.1.1 [ChoirStaff], page 54, Section 2.1.2 [ChordNames], page 55, Section 2.1.5 [DrumStaff], page 70, Section 2.1.8 [FiguredBass], page 91, Section 2.1.11 [GrandStaff], page 95, Section 2.1.14 [Lyrics], page 120, Section 2.1.18 [PianoStaff], page 147, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164 and Section 2.1.22 [StaffGroup], page 174.

This context is built from the following engraver(s):

Section 2.2.54 [Instrument_name_engraver], page 251

Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
: See `instrumentName`.

`shortVocalName` (markup)
: Name of a vocal line, short version.

`vocalName` (markup)
: Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

Section 2.2.113 [System_start_delimiter_engraver], page 270
: Create a system start delimiter (i.e., a `SystemStartBar`, `SystemStartBrace`, `SystemStartBracket` or `SystemStartSquare` spanner).

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  `systemStartDelimiter` (symbol)
  : Which grob to make for the start of the system/staff? Set to `SystemStartBrace`, `SystemStartBracket` or `SystemStartBar`.

  `systemStartDelimiterHierarchy` (pair)
  : A nested list, indicating the nesting of a start delimiters.

  This engraver creates the following layout object(s):

  Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382 and Section 3.1.113 [SystemStartSquare], page 383.

Section 2.2.130 [Vertical_align_engraver], page 276
: Catch groups (staves, lyrics lines, etc.) and stack them vertically.

  Properties (read)

  `alignAboveContext` (string)
  : Where to insert newly created context in vertical alignment.

  `alignBelowContext` (string)
  : Where to insert newly created context in vertical alignment.

  This engraver creates the following layout object(s):

  Section 3.1.129 [VerticalAlignment], page 399.

2.1.2 ChordNames

Typesets chord names.

This context creates the following layout object(s):

Section 3.1.24 [ChordName], page 307, Section 3.1.100 [StaffSpacing], page 372 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `nonstaff-nonstaff-spacing padding` in Section 3.1.130 [VerticalAxisGroup], page 399 to `0.5`.
- Set grob-property `nonstaff-relatedstaff-spacing padding` in Section 3.1.130 [VerticalAxisGroup], page 399 to `0.5`.
- Set grob-property `remove-empty` in Section 3.1.130 [VerticalAxisGroup], page 399 to `#t`.
- Set grob-property `remove-first` in Section 3.1.130 [VerticalAxisGroup], page 399 to `#t`.
- Set grob-property `staff-affinity` in Section 3.1.130 [VerticalAxisGroup], page 399 to `-1`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.15 [Chord_name_engraver], page 238
: Catch note and rest events and generate the appropriate chordname.

  Music types accepted:

  Section 1.2.39 [note-event], page 43 and Section 1.2.51 [rest-event], page 45

  Properties (read)

  `chordChanges` (boolean)
  : Only show changes in chords scheme?

  `chordNameExceptions` (list)
  : An alist of chord exceptions. Contains `(`*`chord . markup`*`)` entries.

  `chordNameExceptions` (list)
  : An alist of chord exceptions. Contains `(`*`chord . markup`*`)` entries.

  `chordNameFunction` (procedure)
  : The function that converts lists of pitches to chord names.

  `chordNoteNamer` (procedure)
  : A function that converts from a pitch object to a text markup. Used for single pitches.

  `chordRootNamer` (procedure)
  : A function that converts from a pitch object to a text markup. Used for chords.

  `majorSevenSymbol` (markup)
  : How should the major 7th be formatted in a chord name?

  `noChordSymbol` (markup)
  : Markup to be displayed for rests in a ChordNames context.

  This engraver creates the following layout object(s):

  Section 3.1.24 [ChordName], page 307.

Section 2.2.51 [Hara_kiri_engraver], page 251
: Like `Axis_group_engraver`, but make a hara-kiri spanner, and add interesting items (i.e., note heads, lyric syllables, and normal rests).

  Properties (read)

  `keepAliveInterfaces` (list)
  : A list of symbols, signifying grob interfaces that are worth keeping a staff with `remove-empty` set around for.

  This engraver creates the following layout object(s):

  Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.99 [Separating_line_group_engraver], page 266
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

2.1.3 CueVoice

Corresponds to a voice on a staff. This context handles the conversion of dynamic signs, stems, beams, super- and subscripts, slurs, ties, and rests.

You have to instantiate this explicitly if you want to have multiple voices on the same staff.

This context also accepts commands for the following context(s):

Voice.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.23 [BreathingSign], page 306, Section 3.1.26 [ClusterSpanner], page 309, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.45 [Glissando], page 327, Section 3.1.49 [Hairpin], page 330, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.59 [LigatureBracket], page 339, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.73 [NoteColumn], page 350, Section 3.1.74 [NoteHead], page 351, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83 [PhrasingSlur], page 358, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.91 [Script], page 365, Section 3.1.92 [ScriptColumn], page 365, Section 3.1.94 [Slur], page 366, Section 3.1.103 [Stem], page 374, Section 3.1.104 [StemTremolo], page 375, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead],

page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.125 [TupletNumber], page 396 and Section 3.1.131 [VoiceFollower], page 401.

This context sets the following properties:

- Set grob-property `beam-thickness` in Section 3.1.19 [Beam], page 302 to `0.35`.
- Set grob-property `length-fraction` in Section 3.1.19 [Beam], page 302 to `0.629960524947437`.
- Set grob-property `length-fraction` in Section 3.1.103 [Stem], page 374 to `0.629960524947437`.
- Set translator property `fontSize` to `-4`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.3 [Arpeggio_engraver], page 234
: Generate an Arpeggio symbol.

  Music types accepted:

  Section 1.2.4 [arpeggio-event], page 39

  This engraver creates the following layout object(s):

  Section 3.1.9 [Arpeggio], page 295.

Section 2.2.4 [Auto_beam_engraver], page 235
: Generate beams based on measure characteristics and observed Stems. Uses `baseMoment`, `beatStructure`, `beamExceptions`, `measureLength`, and `measurePosition` to decide when to start and stop a beam. Overriding beaming is done through Section 2.2.112 [Stem_engraver], page 270 properties `stemLeftBeamCount` and `stemRightBeamCount`.

  Music types accepted:

  Section 1.2.8 [beam-forbid-event], page 40

  Properties (read)

  `autoBeaming` (boolean)
  : If set to true then beams are generated automatically.

  `baseMoment` (moment)
  : Smallest unit of time that will stand on its own as a subdivided section.

  `beamExceptions` (list)
  : An alist of exceptions to autobeam rules that normally end on beats.

  `beatStructure` (list)
  : List of `baseMoments` that are combined to make beats.

  `subdivideBeams` (boolean)
  : If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

  This engraver creates the following layout object(s):

  Section 3.1.19 [Beam], page 302.

Section 2.2.10 [Beam_engraver], page 237
: Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams.

  Music types accepted:

  Section 1.2.7 [beam-event], page 40

  Properties (read)

  `baseMoment` (moment)
  : Smallest unit of time that will stand on its own as a subdivided section.

  `beamMelismaBusy` (boolean)
  : Signal if a beam is present.

  `beatStructure` (list)
  : List of `baseMoments` that are combined to make beats.

  `subdivideBeams` (boolean)
  : If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

  Properties (write)

  `forbidBreak` (boolean)
  : If set to `##t`, prevent a line break at this point.

  This engraver creates the following layout object(s):

  Section 3.1.19 [Beam], page 302.

Section 2.2.12 [Bend_engraver], page 238
: Create fall spanners.

  Music types accepted:

  Section 1.2.9 [bend-after-event], page 40

  This engraver creates the following layout object(s):

  Section 3.1.20 [BendAfter], page 304.

Section 2.2.14 [Breathing_sign_engraver], page 238
: Create a breathing sign.

  Music types accepted:

  Section 1.2.13 [breathing-event], page 40

  This engraver creates the following layout object(s):

  Section 3.1.23 [BreathingSign], page 306.

Section 2.2.16 [Chord_tremolo_engraver], page 239
: Generate beams for tremolo repeats.

  Music types accepted:

  Section 1.2.72 [tremolo-span-event], page 48

  This engraver creates the following layout object(s):

  Section 3.1.19 [Beam], page 302.

Section 2.2.18 [Cluster_spanner_engraver], page 240
: Engrave a cluster using `Spanner` notation.

Music types accepted:

Section 1.2.14 [cluster-note-event], page 40

This engraver creates the following layout object(s):

Section 3.1.26 [ClusterSpanner], page 309 and Section 3.1.27 [ClusterSpannerBeacon], page 309.

`Section 2.2.27 [Dots_engraver], page 243`
Create Section 3.1.33 [Dots], page 315 objects for Section 3.2.87 [rhythmic-head-interface], page 447s.

This engraver creates the following layout object(s):

Section 3.1.33 [Dots], page 315.

`Section 2.2.28 [Double_percent_repeat_engraver], page 243`
Make double measure repeats.

Music types accepted:

Section 1.2.18 [double-percent-event], page 41

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`measureLength` (moment)
: Length of one measure in the current time signature.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.34 [DoublePercentRepeat], page 315 and Section 3.1.35 [DoublePercentRepeatCounter], page 316.

`Section 2.2.31 [Dynamic_align_engraver], page 244`
Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

Section 2.2.39 [Fingering_engraver], page 247
Create fingering scripts.

Music types accepted:

Section 1.2.22 [fingering-event], page 41 and Section 1.2.65 [stroke-finger-event], page 47

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323.

Section 2.2.40 [Font_size_engraver], page 247
Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
The relative size of all grobs in a context.

Section 2.2.41 [Footnote_engraver], page 247
Create footnote texts.

Music types accepted:

Section 1.2.23 [footnote-event], page 41

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

Section 2.2.42 [Forbid_line_break_engraver], page 248
Forbid line breaks when note heads are still playing at some point.

Properties (read)

`busyGrobs` (list)
A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`forbidBreak` (boolean)
If set to `##t`, prevent a line break at this point.

Section 2.2.44 [Glissando_engraver], page 249
Engrave glissandi.

Music types accepted:

Section 1.2.24 [glissando-event], page 41

Properties (read)

`glissandoMap` (list)
A map in the form of '((source1 . target1) (source2 . target2) (sourcen . targetn)) showing the glissandi to be drawn for note columns.

The value '() will default to '((0 . 0) (1 . 1) (n . n)), where n is the minimal number of noteheads in the two note columns between which the glissandi occur.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327.

Section 2.2.45 [Grace_beam_engraver], page 249

Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams. Only engraves beams when we are at grace points in time.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.46 [Grace_engraver], page 250

Set font size and other properties for grace notes.

Properties (read)

`graceSettings` (list)
: Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

Section 2.2.50 [Grob_pq_engraver], page 250

Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.55 [Instrument_switch_engraver], page 252
: Create a cue text for taking instrument.

  Properties (read)

  `instrumentCueName` (markup)
  : The name to print if another instrument is to be taken.

  This engraver creates the following layout object(s):

  Section 3.1.52 [InstrumentSwitch], page 333.

Section 2.2.59 [Laissez_vibrer_engraver], page 254
: Create laissez vibrer items.

  Music types accepted:

  Section 1.2.29 [laissez-vibrer-event], page 42

  This engraver creates the following layout object(s):

  Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.56 [LaissezVibrerTieColumn], page 337.

Section 2.2.61 [Ligature_bracket_engraver], page 254
: Handle `Ligature_events` by engraving `Ligature` brackets.

  Music types accepted:

  Section 1.2.31 [ligature-event], page 42

  This engraver creates the following layout object(s):

  Section 3.1.59 [LigatureBracket], page 339.

Section 2.2.69 [Multi_measure_rest_engraver], page 257
: Engrave multi-measure rests that are produced with '`R`'. It reads `measurePosition` and `internalBarNumber` to determine what number to print over the Section 3.1.68 [MultiMeasureRest], page 346. Reads `measureLength` to determine whether it should use a whole rest or a breve rest to represent one measure.

  Music types accepted:

  Section 1.2.36 [multi-measure-rest-event], page 43 and Section 1.2.37 [multi-measure-text-event], page 43

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  `internalBarNumber` (integer)
  : Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`restNumberThreshold` (number)
: If a multimeasure rest has more measures than this, a number is printed.

This engraver creates the following layout object(s):

Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

`Section 2.2.70 [New_dynamic_engraver], page 257`

Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

`Section 2.2.71 [New_fingering_engraver], page 258`

Create fingering scripts for notes in a new chord. This engraver is ill-named, since it also takes care of articulations and harmonic note heads.

Properties (read)

`fingeringOrientations` (list)
: A list of symbols, containing '`left`', '`right`', '`up`' and/or '`down`'. This list determines where fingerings are put relative to the chord being fingered.

`harmonicDots` (boolean)
: If set, harmonic notes in dotted chords get dots.

`stringNumberOrientations` (list)
: See `fingeringOrientations`.

`strokeFingerOrientations` (list)
: See `fingeringOrientations`.

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323, Section 3.1.91 [Script], page 365, Section 3.1.105 [StringNumber], page 376 and Section 3.1.106 [StrokeFinger], page 377.

`Section 2.2.72 [Note_head_line_engraver], page 258`
Engrave a line between two note heads, for example a glissando. If `followVoice` is set, staff switches also generate a line.

Properties (read)

`followVoice` (boolean)
: If set, note heads are tracked across staff switches by a thin line.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327 and Section 3.1.131 [VoiceFollower], page 401.

`Section 2.2.73 [Note_heads_engraver], page 259`
Generate note heads.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`staffLineLayoutFunction` (procedure)
: Layout of staff lines, `traditional`, or `semitone`.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351.

`Section 2.2.76 [Note_spacing_engraver], page 259`
Generate `NoteSpacing`, an object linking horizontal lines for use in spacing.

This engraver creates the following layout object(s):

Section 3.1.76 [NoteSpacing], page 352.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.82 [Part_combine_engraver], page 261
Part combine engraver for orchestral scores: Print markings 'a2', 'Solo', 'Solo II', and 'unisono'.

Music types accepted:

Section 1.2.39 [note-event], page 43 and Section 1.2.43 [part-combine-event], page 44

Properties (read)

`aDueText` (markup)
Text to print at a unisono passage.

`partCombineTextsOnNote` (boolean)
Print part-combine texts only on the next note rather than immediately on rests or skips.

`printPartCombineTexts` (boolean)
Set 'Solo' and 'A due' texts in the part combiner?

`soloIIText` (markup)
The text for the start of a solo for voice 'two' when part-combining.

`soloText` (markup)
The text for the start of a solo when part-combining.

This engraver creates the following layout object(s):

Section 3.1.28 [CombineTextScript], page 309.

Section 2.2.83 [Percent_repeat_engraver], page 262
Make whole measure repeats.

Music types accepted:

Section 1.2.46 [percent-event], page 44

Properties (read)

`countPercentRepeats` (boolean)
If set, produce counters for percent repeats.

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`repeatCountVisibility` (procedure)
A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

This engraver creates the following layout object(s):

Section 3.1.81 [PercentRepeat], page 356 and Section 3.1.82 [PercentRepeatCounter], page 357.

Section 2.2.84 [Phrasing_slur_engraver], page 262
: Print phrasing slurs. Similar to Section 2.2.101 [Slur_engraver], page 267.

  Music types accepted:

  Section 1.2.48 [phrasing-slur-event], page 45

  This engraver creates the following layout object(s):

  Section 3.1.83 [PhrasingSlur], page 358.

Section 2.2.89 [Pitched_trill_engraver], page 264
: Print the bracketed note head after a note head with trill.

  This engraver creates the following layout object(s):

  Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392 and Section 3.1.122 [TrillPitchHead], page 393.

Section 2.2.91 [Repeat_tie_engraver], page 265
: Create repeat ties.

  Music types accepted:

  Section 1.2.50 [repeat-tie-event], page 45

  This engraver creates the following layout object(s):

  Section 3.1.87 [RepeatTie], page 362 and Section 3.1.88 [RepeatTieColumn], page 363.

Section 2.2.93 [Rest_engraver], page 265
: Engrave rests.

  Music types accepted:

  Section 1.2.51 [rest-event], page 45

  Properties (read)

  `middleCPosition` (number)
  : The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

  This engraver creates the following layout object(s):

  Section 3.1.89 [Rest], page 364.

Section 2.2.94 [Rhythmic_column_engraver], page 265
: Generate `NoteColumn`, an object that groups stems, note heads, and rests.

  This engraver creates the following layout object(s):

  Section 3.1.73 [NoteColumn], page 350.

Section 2.2.96 [Script_column_engraver], page 266
: Find potentially colliding scripts and put them into a `ScriptColumn` object; that will fix the collisions.

  This engraver creates the following layout object(s):

  Section 3.1.92 [ScriptColumn], page 365.

Section 2.2.97 [Script_engraver], page 266
: Handle note scripted articulations.

  Music types accepted:

  Section 1.2.5 [articulation-event], page 40

  Properties (read)

`scriptDefinitions` (list)
: The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

This engraver creates the following layout object(s):

Section 3.1.91 [Script], page 365.

`Section 2.2.100 [Slash_repeat_engraver], page 267`
: Make beat repeats.

Music types accepted:

Section 1.2.49 [repeat-slash-event], page 45

This engraver creates the following layout object(s):

Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

`Section 2.2.101 [Slur_engraver], page 267`
: Build slur grobs from slur events.

Music types accepted:

Section 1.2.55 [slur-event], page 45

Properties (read)

`doubleSlurs` (boolean)
: If set, two slurs are created for every slurred note, one above and one below the chord.

`slurMelismaBusy` (boolean)
: Signal if a slur is present.

This engraver creates the following layout object(s):

Section 3.1.94 [Slur], page 366.

`Section 2.2.106 [Spanner_break_forbid_engraver], page 268`
: Forbid breaks in certain spanners.

`Section 2.2.112 [Stem_engraver], page 270`
: Create stems and single-stem tremolos. It also works together with the beam engraver for overriding beaming.

Music types accepted:

Section 1.2.71 [tremolo-event], page 48

Properties (read)

`stemLeftBeamCount` (integer)
: Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.

`stemRightBeamCount` (integer)
: See `stemLeftBeamCount`.

`tremoloFlags` (integer)
: The number of tremolo flags to add if no number is specified.

This engraver creates the following layout object(s):

Section 3.1.103 [Stem], page 374 and Section 3.1.104 [StemTremolo], page 375.

`Section 2.2.118 [Text_engraver], page 272`

Create text scripts.

Music types accepted:

Section 1.2.68 [text-script-event], page 47

This engraver creates the following layout object(s):

Section 3.1.115 [TextScript], page 385.

`Section 2.2.119 [Text_spanner_engraver], page 272`

Create text spanner from an event.

Music types accepted:

Section 1.2.69 [text-span-event], page 48

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.116 [TextSpanner], page 387.

`Section 2.2.120 [Tie_engraver], page 272`

Generate ties between note heads of equal pitch.

Music types accepted:

Section 1.2.70 [tie-event], page 48

Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

`Section 2.2.126 [Trill_spanner_engraver], page 274`

Create trill spanner from an event.

Music types accepted:

Section 1.2.73 [trill-span-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.123 [TrillSpanner], page 393.

Section 2.2.127 [Tuplet_engraver], page 275
: Catch tuplet events and generate appropriate bracket.

Music types accepted:

Section 1.2.74 [tuplet-span-event], page 48

Properties (read)

`tupletFullLength` (boolean)
: If set, the tuplet is printed up to the start of the next note.

`tupletFullLengthNote` (boolean)
: If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

This engraver creates the following layout object(s):

Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

Section 2.2.128 [Tweak_engraver], page 275
: Read the `tweaks` property from the originating event, and set properties.

2.1.4 Devnull

Silently discards all musical information given to this context.

This context also accepts commands for the following context(s):

Staff and Voice.

This context creates the following layout object(s):

none.

This context is a 'bottom' context; it cannot contain other contexts.

2.1.5 DrumStaff

Handles typesetting for percussion.

This context also accepts commands for the following context(s):

Staff.

This context creates the following layout object(s):

Section 3.1.11 [BarLine], page 297, Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.32 [DotColumn], page 314, Section 3.1.51 [InstrumentName], page 332, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.72 [NoteCollision], page 350, Section 3.1.77 [OctavateEight], page 353, Section 3.1.90

[RestCollision], page 364, Section 3.1.93 [ScriptRow], page 366, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.119 [TimeSignature], page 390, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `staff-padding` in Section 3.1.91 [Script], page 365 to `0.75`.
- Set translator property `clefGlyph` to `"clefs.percussion"`.
- Set translator property `clefPosition` to `0`.
- Set translator property `createSpacing` to `#t`.
- Set translator property `ignoreFiguredBassRest` to `#f`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `localKeySignature` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.

Context DrumStaff can contain Section 2.1.3 [CueVoice], page 57 and Section 2.1.6 [DrumVoice], page 76.

This context is built from the following engraver(s):

Section 2.2.5 [Axis_group_engraver], page 235
: Group all objects created in this context in a `VerticalAxisGroup` spanner.

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  This engraver creates the following layout object(s):

  Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.7 [Bar_engraver], page 236
: Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

  Properties (read)

  `whichBar` (string)
  : This property is read to determine what type of bar line to create.

    Example:

    ```
    \set Staff.whichBar = "|:"
    ```

    This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

  Properties (write)

  `forbidBreak` (boolean)
  : If set to `##t`, prevent a line break at this point.

  This engraver creates the following layout object(s):

  Section 3.1.11 [BarLine], page 297.

Section 2.2.9 [Beam_collision_engraver], page 237
: Help beams avoid colliding with notes and clefs in other voices.

Section 2.2.17 [Clef_engraver], page 239
: Determine and set reference point for pitches.

  Properties (read)

  `clefGlyph` (string)
  : Name of the symbol within the music font.

  `clefOctavation` (integer)
  : Add this much extra octavation. Values of 7 and -7 are common.

  `clefPosition` (number)
  : Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

  `explicitClefVisibility` (vector)
  : '`break-visibility`' function for clef changes.

  `forceClef` (boolean)
  : Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

  This engraver creates the following layout object(s):

  Section 3.1.25 [Clef], page 307 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.19 [Collision_engraver], page 240
: Collect `NoteColumns`, and as soon as there are two or more, put them in a `NoteCollision` object.

  This engraver creates the following layout object(s):

  Section 3.1.72 [NoteCollision], page 350.

Section 2.2.23 [Cue_clef_engraver], page 241
: Determine and set reference point for pitches in cued voices.

  Properties (read)

  `clefOctavation` (integer)
  : Add this much extra octavation. Values of 7 and -7 are common.

  `cueClefGlyph` (string)
  : Name of the symbol within the music font.

  `cueClefOctavation` (integer)
  : Add this much extra octavation. Values of 7 and -7 are common.

  `cueClefPosition` (number)
  : Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

  `explicitCueClefVisibility` (vector)
  : '`break-visibility`' function for cue clef changes.

`middleCCuePosition` (number)
: The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

This engraver creates the following layout object(s):

Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312 and Section 3.1.77 [OctavateEight], page 353.

`Section 2.2.26 [Dot_column_engraver], page 243`
: Engrave dots on dotted notes shifted to the right of the note. If omitted, then dots appear on top of the notes.

This engraver creates the following layout object(s):

Section 3.1.32 [DotColumn], page 314.

`Section 2.2.37 [Figured_bass_engraver], page 246`
: Make figured bass numbers.

Music types accepted:

Section 1.2.6 [bass-figure-event], page 40 and Section 1.2.51 [rest-event], page 45

Properties (read)

`figuredBassAlterationDirection` (direction)
: Where to put alterations relative to the main figure.

`figuredBassCenterContinuations` (boolean)
: Whether to vertically center pairs of extender lines. This does not work with three or more lines.

`figuredBassFormatter` (procedure)
: A routine generating a markup for a bass figure.

`ignoreFiguredBassRest` (boolean)
: Don't swallow rest events.

`implicitBassFigures` (list)
: A list of bass figures that are not printed as numbers, but only as extender lines.

`useBassFigureExtenders` (boolean)
: Whether to use extender lines for repeated bass figures.

This engraver creates the following layout object(s):

Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301 and Section 3.1.18 [BassFigureLine], page 302.

`Section 2.2.38 [Figured_bass_position_engraver], page 247`
: Position figured bass alignments over notes.

This engraver creates the following layout object(s):

Section 3.1.15 [BassFigureAlignmentPositioning], page 300.

Section 2.2.40 [Font_size_engraver], page 247

Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

Section 2.2.50 [Grob_pq_engraver], page 250

Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.54 [Instrument_name_engraver], page 251

Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
: See `instrumentName`.

`shortVocalName` (markup)
: Name of a vocal line, short version.

`vocalName` (markup)
: Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

Section 2.2.60 [Ledger_line_engraver], page 254

Create the spanner to draw ledger lines, and notices objects that need ledger lines.

This engraver creates the following layout object(s):

Section 3.1.57 [LedgerLineSpanner], page 337.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.85 [Piano_pedal_align_engraver], page 263
Align piano pedal symbols and brackets.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.108 [SustainPedalLineSpanner], page 379 and Section 3.1.127 [UnaCordaPedalLineSpanner], page 397.

Section 2.2.92 [Rest_collision_engraver], page 265
Handle collisions of rests.

Properties (read)

`busyGrobs` (list)
A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

This engraver creates the following layout object(s):

Section 3.1.90 [RestCollision], page 364.

Section 2.2.98 [Script_row_engraver], page 266
Determine order in horizontal side position elements.

This engraver creates the following layout object(s):

Section 3.1.93 [ScriptRow], page 366.

Section 2.2.99 [Separating_line_group_engraver], page 266
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

Section 2.2.107 [Staff_collecting_engraver], page 269
Maintain the `stavesFound` variable.

Properties (read)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Properties (write)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

`Section 2.2.109 [Staff_symbol_engraver], page 269`
Create the constellation of five (default) staff lines.

Music types accepted:

Section 1.2.62 [staff-span-event], page 46

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

`Section 2.2.122 [Time_signature_engraver], page 273`
Create a Section 3.1.119 [TimeSignature], page 390 whenever `timeSignatureFraction` changes.

Properties (read)

`implicitTimeSignatureVisibility` (vector)
break visibility for the default time signature.

`timeSignatureFraction` (pair of numbers)
A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

This engraver creates the following layout object(s):

Section 3.1.119 [TimeSignature], page 390.

2.1.6 DrumVoice

A voice on a percussion staff.

This context also accepts commands for the following context(s):

Voice.

This context creates the following layout object(s):

Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.23 [BreathingSign], page 306, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.49 [Hairpin], page 330, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.73 [NoteColumn], page 350, Section 3.1.74 [NoteHead], page 351, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83 [PhrasingSlur], page 358, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.91 [Script], page 365, Section 3.1.92 [ScriptColumn], page 365, Section 3.1.94 [Slur], page 366, Section 3.1.103 [Stem], page 374, Section 3.1.104 [StemTremolo], page 375, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387,

Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.4 [Auto_beam_engraver], page 235
: Generate beams based on measure characteristics and observed Stems. Uses `baseMoment`, `beatStructure`, `beamExceptions`, `measureLength`, and `measurePosition` to decide when to start and stop a beam. Overriding beaming is done through Section 2.2.112 [Stem_engraver], page 270 properties `stemLeftBeamCount` and `stemRightBeamCount`.

  Music types accepted:

  Section 1.2.8 [beam-forbid-event], page 40

  Properties (read)

  `autoBeaming` (boolean)
  : If set to true then beams are generated automatically.

  `baseMoment` (moment)
  : Smallest unit of time that will stand on its own as a subdivided section.

  `beamExceptions` (list)
  : An alist of exceptions to autobeam rules that normally end on beats.

  `beatStructure` (list)
  : List of `baseMoments` that are combined to make beats.

  `subdivideBeams` (boolean)
  : If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

  This engraver creates the following layout object(s):

  Section 3.1.19 [Beam], page 302.

Section 2.2.10 [Beam_engraver], page 237
: Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams.

  Music types accepted:

  Section 1.2.7 [beam-event], page 40

  Properties (read)

  `baseMoment` (moment)
  : Smallest unit of time that will stand on its own as a subdivided section.

  `beamMelismaBusy` (boolean)
  : Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.12 [Bend_engraver], page 238`
Create fall spanners.

Music types accepted:

Section 1.2.9 [bend-after-event], page 40

This engraver creates the following layout object(s):

Section 3.1.20 [BendAfter], page 304.

`Section 2.2.14 [Breathing_sign_engraver], page 238`
Create a breathing sign.

Music types accepted:

Section 1.2.13 [breathing-event], page 40

This engraver creates the following layout object(s):

Section 3.1.23 [BreathingSign], page 306.

`Section 2.2.16 [Chord_tremolo_engraver], page 239`
Generate beams for tremolo repeats.

Music types accepted:

Section 1.2.72 [tremolo-span-event], page 48

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.27 [Dots_engraver], page 243`
Create Section 3.1.33 [Dots], page 315 objects for Section 3.2.87 [rhythmic-head-interface], page 447s.

This engraver creates the following layout object(s):

Section 3.1.33 [Dots], page 315.

`Section 2.2.28 [Double_percent_repeat_engraver], page 243`
Make double measure repeats.

Music types accepted:

Section 1.2.18 [double-percent-event], page 41

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`measureLength` (moment)
: Length of one measure in the current time signature.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.34 [DoublePercentRepeat], page 315 and Section 3.1.35 [DoublePercentRepeatCounter], page 316.

`Section 2.2.30 [Drum_notes_engraver], page 244`

Generate drum note heads.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`drumStyleTable` (hash table)
: A hash table which maps drums to layout settings. Predefined values: '`drums-style`', '`timbales-style`', '`congas-style`', '`bongos-style`', and '`percussion-style`'.

  The layout style is a hash table, containing the drum-pitches (e.g., the symbol '`hihat`') as keys, and a list `(`*`notehead-style script vertical-position`*`)` as values.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351 and Section 3.1.91 [Script], page 365.

`Section 2.2.31 [Dynamic_align_engraver], page 244`

Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

`Section 2.2.40 [Font_size_engraver], page 247`

Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

Section 2.2.41 [Footnote_engraver], page 247
: Create footnote texts.

Music types accepted:

Section 1.2.23 [footnote-event], page 41

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

Section 2.2.42 [Forbid_line_break_engraver], page 248
: Forbid line breaks when note heads are still playing at some point.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

Section 2.2.45 [Grace_beam_engraver], page 249
: Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams. Only engraves beams when we are at grace points in time.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.46 [Grace_engraver], page 250

Set font size and other properties for grace notes.

Properties (read)

`graceSettings` (list)
: Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

Section 2.2.50 [Grob_pq_engraver], page 250

Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.50 [Grob_pq_engraver], page 250

Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.55 [Instrument_switch_engraver], page 252

Create a cue text for taking instrument.

Properties (read)

`instrumentCueName` (markup)
: The name to print if another instrument is to be taken.

This engraver creates the following layout object(s):

Section 3.1.52 [InstrumentSwitch], page 333.

Section 2.2.59 [Laissez_vibrer_engraver], page 254
Create laissez vibrer items.

Music types accepted:

Section 1.2.29 [laissez-vibrer-event], page 42

This engraver creates the following layout object(s):

Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.56 [LaissezVibrerTieColumn], page 337.

Section 2.2.69 [Multi_measure_rest_engraver], page 257
Engrave multi-measure rests that are produced with 'R'. It reads `measurePosition` and `internalBarNumber` to determine what number to print over the Section 3.1.68 [MultiMeasureRest], page 346. Reads `measureLength` to determine whether it should use a whole rest or a breve rest to represent one measure.

Music types accepted:

Section 1.2.36 [multi-measure-rest-event], page 43 and Section 1.2.37 [multi-measure-text-event], page 43

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`internalBarNumber` (integer)
Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
Length of one measure in the current time signature.

`measurePosition` (moment)
How much of the current measure have we had. This can be set manually to create incomplete measures.

`restNumberThreshold` (number)
If a multimeasure rest has more measures than this, a number is printed.

This engraver creates the following layout object(s):

Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

Section 2.2.70 [New_dynamic_engraver], page 257
Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

Section 2.2.76 [Note_spacing_engraver], page 259
: Generate `NoteSpacing`, an object linking horizontal lines for use in spacing.

  This engraver creates the following layout object(s):

  Section 3.1.76 [NoteSpacing], page 352.

Section 2.2.78 [Output_property_engraver], page 260
: Apply a procedure to any grob acknowledged.

  Music types accepted:

  Section 1.2.3 [apply-output-event], page 39

Section 2.2.82 [Part_combine_engraver], page 261
: Part combine engraver for orchestral scores: Print markings 'a2', 'Solo', 'Solo II', and 'unisono'.

  Music types accepted:

  Section 1.2.39 [note-event], page 43 and Section 1.2.43 [part-combine-event], page 44

  Properties (read)

  `aDueText` (markup)
  : Text to print at a unisono passage.

  `partCombineTextsOnNote` (boolean)
  : Print part-combine texts only on the next note rather than immediately on rests or skips.

  `printPartCombineTexts` (boolean)
  : Set 'Solo' and 'A due' texts in the part combiner?

`soloIIText` (markup)
: The text for the start of a solo for voice 'two' when part-combining.

`soloText` (markup)
: The text for the start of a solo when part-combining.

This engraver creates the following layout object(s):

Section 3.1.28 [CombineTextScript], page 309.

`Section 2.2.83 [Percent_repeat_engraver], page 262`

Make whole measure repeats.

Music types accepted:

Section 1.2.46 [percent-event], page 44

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

This engraver creates the following layout object(s):

Section 3.1.81 [PercentRepeat], page 356 and Section 3.1.82 [PercentRepeatCounter], page 357.

`Section 2.2.84 [Phrasing_slur_engraver], page 262`

Print phrasing slurs. Similar to Section 2.2.101 [Slur_engraver], page 267.

Music types accepted:

Section 1.2.48 [phrasing-slur-event], page 45

This engraver creates the following layout object(s):

Section 3.1.83 [PhrasingSlur], page 358.

`Section 2.2.89 [Pitched_trill_engraver], page 264`

Print the bracketed note head after a note head with trill.

This engraver creates the following layout object(s):

Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392 and Section 3.1.122 [TrillPitchHead], page 393.

`Section 2.2.91 [Repeat_tie_engraver], page 265`

Create repeat ties.

Music types accepted:

Section 1.2.50 [repeat-tie-event], page 45

This engraver creates the following layout object(s):

Section 3.1.87 [RepeatTie], page 362 and Section 3.1.88 [RepeatTieColumn], page 363.

Section 2.2.93 [Rest_engraver], page 265
Engrave rests.

Music types accepted:

Section 1.2.51 [rest-event], page 45

Properties (read)

`middleCPosition` (number)
The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

This engraver creates the following layout object(s):

Section 3.1.89 [Rest], page 364.

Section 2.2.94 [Rhythmic_column_engraver], page 265
Generate `NoteColumn`, an object that groups stems, note heads, and rests.

This engraver creates the following layout object(s):

Section 3.1.73 [NoteColumn], page 350.

Section 2.2.96 [Script_column_engraver], page 266
Find potentially colliding scripts and put them into a `ScriptColumn` object; that will fix the collisions.

This engraver creates the following layout object(s):

Section 3.1.92 [ScriptColumn], page 365.

Section 2.2.97 [Script_engraver], page 266
Handle note scripted articulations.

Music types accepted:

Section 1.2.5 [articulation-event], page 40

Properties (read)

`scriptDefinitions` (list)
The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

This engraver creates the following layout object(s):

Section 3.1.91 [Script], page 365.

Section 2.2.100 [Slash_repeat_engraver], page 267
Make beat repeats.

Music types accepted:

Section 1.2.49 [repeat-slash-event], page 45

This engraver creates the following layout object(s):

Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

Section 2.2.101 [Slur_engraver], page 267
Build slur grobs from slur events.

Music types accepted:

Section 1.2.55 [slur-event], page 45

Properties (read)

`doubleSlurs` (boolean)
: If set, two slurs are created for every slurred note, one above and one below the chord.

`slurMelismaBusy` (boolean)
: Signal if a slur is present.

This engraver creates the following layout object(s):

Section 3.1.94 [Slur], page 366.

`Section 2.2.106 [Spanner_break_forbid_engraver], page 268`
: Forbid breaks in certain spanners.

`Section 2.2.112 [Stem_engraver], page 270`
: Create stems and single-stem tremolos. It also works together with the beam engraver for overriding beaming.

Music types accepted:

Section 1.2.71 [tremolo-event], page 48

Properties (read)

`stemLeftBeamCount` (integer)
: Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.

`stemRightBeamCount` (integer)
: See `stemLeftBeamCount`.

`tremoloFlags` (integer)
: The number of tremolo flags to add if no number is specified.

This engraver creates the following layout object(s):

Section 3.1.103 [Stem], page 374 and Section 3.1.104 [StemTremolo], page 375.

`Section 2.2.118 [Text_engraver], page 272`
: Create text scripts.

Music types accepted:

Section 1.2.68 [text-script-event], page 47

This engraver creates the following layout object(s):

Section 3.1.115 [TextScript], page 385.

`Section 2.2.119 [Text_spanner_engraver], page 272`
: Create text spanner from an event.

Music types accepted:

Section 1.2.69 [text-span-event], page 48

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.116 [TextSpanner], page 387.

Section 2.2.120 [Tie_engraver], page 272

Generate ties between note heads of equal pitch.

Music types accepted:

Section 1.2.70 [tie-event], page 48

Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

Section 2.2.126 [Trill_spanner_engraver], page 274

Create trill spanner from an event.

Music types accepted:

Section 1.2.73 [trill-span-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.123 [TrillSpanner], page 393.

Section 2.2.127 [Tuplet_engraver], page 275

Catch tuplet events and generate appropriate bracket.

Music types accepted:

Section 1.2.74 [tuplet-span-event], page 48

Properties (read)

`tupletFullLength` (boolean)
: If set, the tuplet is printed up to the start of the next note.

`tupletFullLengthNote` (boolean)
: If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

This engraver creates the following layout object(s):

Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

Section 2.2.128 [Tweak_engraver], page 275

Read the `tweaks` property from the originating event, and set properties.

2.1.7 Dynamics

Holds a single line of dynamics, which will be centered between the staves surrounding this context.

This context also accepts commands for the following context(s):

Voice.

This context creates the following layout object(s):

Section 3.1.11 [BarLine], page 297, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.49 [Hairpin], page 330, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.91 [Script], page 365, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.126 [UnaCordaPedal], page 396 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `font-shape` in Section 3.1.115 [TextScript], page 385 to `'italic`.
- Set grob-property `nonstaff-relatedstaff-spacing` in Section 3.1.130 [VerticalAxisGroup], page 399 to `'((basic-distance . 5) (padding . 0.5))`.
- Set grob-property `staff-affinity` in Section 3.1.130 [VerticalAxisGroup], page 399 to `0`.
- Set grob-property `Y-offset` in Section 3.1.37 [DynamicLineSpanner], page 318 to `0`.
- Set translator property `pedalSustainStrings` to `'(Ped. *Ped. *)`.
- Set translator property `pedalUnaCordaStrings` to `'(una corda tre corde)`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.5 [Axis_group_engraver], page 235

Group all objects created in this context in a `VerticalAxisGroup` spanner.

Properties (read)

`currentCommandColumn` (graphical (layout) object)

Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.7 [Bar_engraver], page 236

Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

Properties (read)

`whichBar` (string)

This property is read to determine what type of bar line to create.

Example:

```
\set Staff.whichBar = "|:"
```

This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.11 [BarLine], page 297.

Section 2.2.31 [Dynamic_align_engraver], page 244

Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

Section 2.2.70 [New_dynamic_engraver], page 257

Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

`Section 2.2.78 [Output_property_engraver], page 260`
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

`Section 2.2.86 [Piano_pedal_engraver], page 263`
Engrave piano pedal symbols and brackets.

Music types accepted:

Section 1.2.58 [sostenuto-event], page 46, Section 1.2.66 [sustain-event], page 47 and Section 1.2.75 [una-corda-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`pedalSostenutoStrings` (list)
: See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)
: See `pedalSustainStyle`.

`pedalSustainStrings` (list)
: A list of strings to print for sustain-pedal. Format is `(up updown down)`, where each of the three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)
: A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)
: See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)
: See `pedalSustainStyle`.

This engraver creates the following layout object(s):

Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378 and Section 3.1.126 [UnaCordaPedal], page 396.

`Section 2.2.97 [Script_engraver], page 266`
Handle note scripted articulations.

Music types accepted:

Section 1.2.5 [articulation-event], page 40

Properties (read)

`scriptDefinitions` (list)
: The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

This engraver creates the following layout object(s):

Section 3.1.91 [Script], page 365.

`Section 2.2.118 [Text_engraver], page 272`
: Create text scripts.

Music types accepted:

Section 1.2.68 [text-script-event], page 47

This engraver creates the following layout object(s):

Section 3.1.115 [TextScript], page 385.

`Section 2.2.119 [Text_spanner_engraver], page 272`
: Create text spanner from an event.

Music types accepted:

Section 1.2.69 [text-span-event], page 48

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.116 [TextSpanner], page 387.

`Section 2.2.128 [Tweak_engraver], page 275`
: Read the `tweaks` property from the originating event, and set properties.

2.1.8 FiguredBass

A context for printing a figured bass line.

This context creates the following layout object(s):

Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.100 [StaffSpacing], page 372 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `nonstaff-nonstaff-spacing padding` in Section 3.1.130 [VerticalAxisGroup], page 399 to `0.5`.
- Set grob-property `nonstaff-relatedstaff-spacing padding` in Section 3.1.130 [VerticalAxisGroup], page 399 to `0.5`.
- Set grob-property `remove-empty` in Section 3.1.130 [VerticalAxisGroup], page 399 to `#t`.
- Set grob-property `remove-first` in Section 3.1.130 [VerticalAxisGroup], page 399 to `#t`.
- Set grob-property `staff-affinity` in Section 3.1.130 [VerticalAxisGroup], page 399 to `1`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.37 [Figured_bass_engraver], page 246
: Make figured bass numbers.

  Music types accepted:

  Section 1.2.6 [bass-figure-event], page 40 and Section 1.2.51 [rest-event], page 45

  Properties (read)

  `figuredBassAlterationDirection` (direction)
  : Where to put alterations relative to the main figure.

  `figuredBassCenterContinuations` (boolean)
  : Whether to vertically center pairs of extender lines. This does not work with three or more lines.

  `figuredBassFormatter` (procedure)
  : A routine generating a markup for a bass figure.

  `ignoreFiguredBassRest` (boolean)
  : Don't swallow rest events.

  `implicitBassFigures` (list)
  : A list of bass figures that are not printed as numbers, but only as extender lines.

  `useBassFigureExtenders` (boolean)
  : Whether to use extender lines for repeated bass figures.

  This engraver creates the following layout object(s):

  Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301 and Section 3.1.18 [BassFigureLine], page 302.

Section 2.2.51 [Hara_kiri_engraver], page 251
: Like `Axis_group_engraver`, but make a hara-kiri spanner, and add interesting items (i.e., note heads, lyric syllables, and normal rests).

  Properties (read)

  `keepAliveInterfaces` (list)
  : A list of symbols, signifying grob interfaces that are worth keeping a staff with `remove-empty` set around for.

  This engraver creates the following layout object(s):

  Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.99 [Separating_line_group_engraver], page 266
: Generate objects for computing spacing parameters.

  Properties (read)

  `createSpacing` (boolean)
  : Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
: True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

2.1.9 FretBoards

A context for displaying fret diagrams.

This context creates the following layout object(s):

Section 3.1.44 [FretBoard], page 326, Section 3.1.51 [InstrumentName], page 332, Section 3.1.100 [StaffSpacing], page 372 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set translator property `handleNegativeFrets` to `'recalculate`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `predefinedDiagramTable` to `#<hash-table 0/113>`.
- Set translator property `shortInstrumentName` to `'()`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.40 [Font_size_engraver], page 247
: Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

Section 2.2.43 [Fretboard_engraver], page 248
: Generate fret diagram from one or more events of type `NoteEvent`.

Music types accepted:

Section 1.2.22 [fingering-event], page 41, Section 1.2.39 [note-event], page 43 and Section 1.2.64 [string-number-event], page 47

Properties (read)

`chordChanges` (boolean)
: Only show changes in chords scheme?

`defaultStrings` (list)
: A list of strings to use in calculating frets for tablatures and fretboards if no strings are provided in the notes for the current moment.

`highStringOne` (boolean)
: Whether the first string is the string with highest pitch on the instrument. This used by the automatic string selector for tablature notation.

`maximumFretStretch` (number)
: Don't allocate frets further than this from specified frets.

`minimumFret` (number)
: The tablature auto string-selecting mechanism selects the highest string with a fret at least `minimumFret`.

`noteToFretFunction` (procedure)
: Convert list of notes and list of defined strings to full list of strings and fret numbers. Parameters: The context, a list of note events, a list of tabstring events, and the fretboard grob if a fretboard is desired.

`predefinedDiagramTable` (hash table)
: The hash table of predefined fret diagrams to use in FretBoards.

`stringTunings` (list)
: The tablature strings tuning. It is a list of the pitches of each string (starting with the lowest numbered one).

`tablatureFormat` (procedure)
: A function formatting a tablature note head. Called with three arguments: context, string number and, fret number. It returns the text as a markup.

This engraver creates the following layout object(s):

Section 3.1.44 [FretBoard], page 326.

Section 2.2.51 [Hara_kiri_engraver], page 251
: Like `Axis_group_engraver`, but make a hara-kiri spanner, and add interesting items (i.e., note heads, lyric syllables, and normal rests).

Properties (read)

`keepAliveInterfaces` (list)
: A list of symbols, signifying grob interfaces that are worth keeping a staff with `remove-empty` set around for.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.54 [Instrument_name_engraver], page 251
: Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
See `instrumentName`.

`shortVocalName` (markup)
Name of a vocal line, short version.

`vocalName` (markup)
Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.99 [Separating_line_group_engraver], page 266
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

2.1.10 Global

Hard coded entry point for LilyPond. Cannot be tuned.

This context creates the following layout object(s):

none.

Context Global can contain Section 2.1.20 [Score], page 153.

2.1.11 GrandStaff

A group of staves, with a brace on the left side, grouping the staves together. The bar lines of the contained staves are connected vertically.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.51 [InstrumentName], page 332, Section 3.1.98 [SpanBar], page 370, Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383 and Section 3.1.129 [VerticalAlignment], page 399.

This context sets the following properties:

- Set translator property `instrumentName` to `'()`.
- Set translator property `localKeySignature` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.
- Set translator property `systemStartDelimiter` to `'SystemStartBrace`.

- Set translator property `topLevelAlignment` to `#f`.

Context GrandStaff can contain Section 2.1.2 [ChordNames], page 55, Section 2.1.5 [DrumStaff], page 70, Section 2.1.7 [Dynamics], page 88, Section 2.1.8 [FiguredBass], page 91, Section 2.1.14 [Lyrics], page 120, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164 and Section 2.1.23 [TabStaff], page 176.

This context is built from the following engraver(s):

`Section 2.2.54 [Instrument_name_engraver], page 251`
Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
See `instrumentName`.

`shortVocalName` (markup)
Name of a vocal line, short version.

`vocalName` (markup)
Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

`Section 2.2.104 [Span_arpeggio_engraver], page 268`
Make arpeggios that span multiple staves.

Properties (read)

`connectArpeggios` (boolean)
If set, connect arpeggios across piano staff.

This engraver creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295.

`Section 2.2.105 [Span_bar_engraver], page 268`
Make cross-staff bar lines: It catches all normal bar lines and draws a single span bar across them.

This engraver creates the following layout object(s):

Section 3.1.98 [SpanBar], page 370.

`Section 2.2.113 [System_start_delimiter_engraver], page 270`
Create a system start delimiter (i.e., a `SystemStartBar`, `SystemStartBrace`, `SystemStartBracket` or `SystemStartSquare` spanner).

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`systemStartDelimiter` (symbol)
: Which grob to make for the start of the system/staff? Set to `SystemStartBrace`, `SystemStartBracket` or `SystemStartBar`.

`systemStartDelimiterHierarchy` (pair)
: A nested list, indicating the nesting of a start delimiters.

This engraver creates the following layout object(s):

Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382 and Section 3.1.113 [SystemStartSquare], page 383.

`Section 2.2.130 [Vertical_align_engraver], page 276`
: Catch groups (staves, lyrics lines, etc.) and stack them vertically.

Properties (read)

`alignAboveContext` (string)
: Where to insert newly created context in vertical alignment.

`alignBelowContext` (string)
: Where to insert newly created context in vertical alignment.

This engraver creates the following layout object(s):

Section 3.1.129 [VerticalAlignment], page 399.

2.1.12 GregorianTranscriptionStaff

Handles clefs, bar lines, keys, accidentals. It can contain `Voice` contexts.

This context also accepts commands for the following context(s):

Staff.

This context creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290, Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.11 [BarLine], page 297, Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.32 [DotColumn], page 314, Section 3.1.51 [InstrumentName], page 332, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.72 [NoteCollision], page 350, Section 3.1.77 [OctavateEight], page 353, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.90 [RestCollision], page 364, Section 3.1.93 [ScriptRow], page 366, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.107 [SustainPedal], page 378, Section 3.1.108 [SustainPedalLineSpanner],

page 379, Section 3.1.119 [TimeSignature], page 390, Section 3.1.126 [UnaCordaPedal], page 396, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `transparent` in Section 3.1.11 [BarLine], page 297 to `#t`.
- Set translator property `createSpacing` to `#t`.
- Set translator property `ignoreFiguredBassRest` to `#f`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `localKeySignature` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.

Context GregorianTranscriptionStaff can contain Section 2.1.3 [CueVoice], page 57 and Section 2.1.13 [GregorianTranscriptionVoice], page 107.

This context is built from the following engraver(s):

Section 2.2.1 [Accidental_engraver], page 233

Make accidentals. Catch note heads, ties and notices key-change events. This engraver usually lives at Staff level, but reads the settings for Accidental at `Voice` level, so you can `\override` them at `Voice`.

Properties (read)

`autoAccidentals` (list)

List of different ways to typeset an accidental.

For determining when to print an accidental, several different rules are tried. The rule that gives the highest number of accidentals is used.

Each entry in the list is either a symbol or a procedure.

symbol The symbol is the name of the context in which the following rules are to be applied. For example, if *context* is Section "Score" in *Internals Reference* then all staves share accidentals, and if *context* is Section "Staff" in *Internals Reference* then all voices in the same staff share accidentals, but staves do not.

procedure The procedure represents an accidental rule to be applied to the previously specified context.

The procedure takes the following arguments:

`context` The current context to which the rule should be applied.

`pitch` The pitch of the note to be evaluated.

`barnum` The current bar number.

`measurepos`
: The current measure position.

The procedure returns a pair of booleans. The first states whether an extra natural should be added. The second states whether an accidental should be printed. `(#t . #f)` does not make sense.

`autoCautionaries` (list)
: List similar to `autoAccidentals`, but it controls cautionary accidentals rather than normal ones. Both lists are tried, and the one giving the most accidentals wins. In case of draw, a normal accidental is typeset.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`harmonicAccidentals` (boolean)
: If set, harmonic notes in chords get accidentals.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step`*` . `*`alter`*`)` or `((`*`octave`*` . `*`step`*`) . `*`alter`*`)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((`*`octave`*` . `*`name`*`) . (`*`alter barnumber`*` . `*`measureposition`*`))` pairs.

Properties (write)

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((`*`octave`*` . `*`name`*`) . (`*`alter barnumber`*` . `*`measureposition`*`))` pairs.

This engraver creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290 and Section 3.1.4 [AccidentalSuggestion], page 291.

Section 2.2.5 [Axis_group_engraver], page 235
Group all objects created in this context in a `VerticalAxisGroup` spanner.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.7 [Bar_engraver], page 236
Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

Properties (read)

`whichBar` (string)
This property is read to determine what type of bar line to create.

Example:

```
\set Staff.whichBar = "|:"
```

This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`forbidBreak` (boolean)
If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.11 [BarLine], page 297.

Section 2.2.9 [Beam_collision_engraver], page 237
Help beams avoid colliding with notes and clefs in other voices.

Section 2.2.17 [Clef_engraver], page 239
Determine and set reference point for pitches.

Properties (read)

`clefGlyph` (string)
Name of the symbol within the music font.

`clefOctavation` (integer)
Add this much extra octavation. Values of 7 and -7 are common.

`clefPosition` (number)
Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitClefVisibility` (vector)
'`break-visibility`' function for clef changes.

`forceClef` (boolean)
: Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

This engraver creates the following layout object(s):

Section 3.1.25 [Clef], page 307 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.19 [Collision_engraver], page 240
: Collect `NoteColumns`, and as soon as there are two or more, put them in a `NoteCollision` object.

This engraver creates the following layout object(s):

Section 3.1.72 [NoteCollision], page 350.

Section 2.2.23 [Cue_clef_engraver], page 241
: Determine and set reference point for pitches in cued voices.

Properties (read)

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefGlyph` (string)
: Name of the symbol within the music font.

`cueClefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitCueClefVisibility` (vector)
: '`break-visibility`' function for cue clef changes.

`middleCCuePosition` (number)
: The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

This engraver creates the following layout object(s):

Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.26 [Dot_column_engraver], page 243
: Engrave dots on dotted notes shifted to the right of the note. If omitted, then dots appear on top of the notes.

This engraver creates the following layout object(s):

Section 3.1.32 [DotColumn], page 314.

Section 2.2.37 [Figured_bass_engraver], page 246
: Make figured bass numbers.

Music types accepted:

Section 1.2.6 [bass-figure-event], page 40 and Section 1.2.51 [rest-event], page 45

Properties (read)

`figuredBassAlterationDirection` (direction)
: Where to put alterations relative to the main figure.

`figuredBassCenterContinuations` (boolean)
: Whether to vertically center pairs of extender lines. This does not work with three or more lines.

`figuredBassFormatter` (procedure)
: A routine generating a markup for a bass figure.

`ignoreFiguredBassRest` (boolean)
: Don't swallow rest events.

`implicitBassFigures` (list)
: A list of bass figures that are not printed as numbers, but only as extender lines.

`useBassFigureExtenders` (boolean)
: Whether to use extender lines for repeated bass figures.

This engraver creates the following layout object(s):

Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301 and Section 3.1.18 [BassFigureLine], page 302.

`Section 2.2.38 [Figured_bass_position_engraver], page 247`
Position figured bass alignments over notes.

This engraver creates the following layout object(s):

Section 3.1.15 [BassFigureAlignmentPositioning], page 300.

`Section 2.2.40 [Font_size_engraver], page 247`
Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

`Section 2.2.50 [Grob_pq_engraver], page 250`
Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.54 [Instrument_name_engraver], page 251

Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
: See `instrumentName`.

`shortVocalName` (markup)
: Name of a vocal line, short version.

`vocalName` (markup)
: Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

Section 2.2.57 [Key_engraver], page 252

Engrave a key signature.

Music types accepted:

Section 1.2.27 [key-change-event], page 42

Properties (read)

`createKeyOnClefChange` (boolean)
: Print a key signature whenever the clef is changed.

`explicitKeySignatureVisibility` (vector)
: '`break-visibility`' function for explicit key changes. '`\override`' of the `break-visibility` property will set the visibility for normal (i.e., at the start of the line) key signatures.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`keyAlterationOrder` (list)
: An alist that defines in what order alterations should be printed. The format is `(step . alter)`, where *step* is a number from 0 to 6 and *alter* from -2 (sharp) to 2 (flat).

`keySignature` (list)
: The current key signature. This is an alist containing `(step . alter)` or `((octave . step) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`middleCClefPosition` (number)
: The position of the middle C, as determined only by the clef. This can be calculated by looking at `clefPosition` and `clefGlyph`.

`printKeyCancellation` (boolean)
: Print restoration alterations before a key signature change.

Properties (write)

`keySignature` (list)
: The current key signature. This is an alist containing `(step . alter)` or `((octave . step) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`tonic` (pitch)
: The tonic of the current scale.

This engraver creates the following layout object(s):

Section 3.1.53 [KeyCancellation], page 334 and Section 3.1.54 [KeySignature], page 335.

`Section 2.2.60 [Ledger_line_engraver], page 254`
: Create the spanner to draw ledger lines, and notices objects that need ledger lines.

This engraver creates the following layout object(s):

Section 3.1.57 [LedgerLineSpanner], page 337.

`Section 2.2.77 [Ottava_spanner_engraver], page 260`
: Create a text spanner when the ottavation property changes.

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`middleCOffset` (number)
: The offset of middle C from the position given by `middleCClefPosition` This is used for ottava brackets.

`ottavation` (markup)
: If set, the text for an ottava spanner. Changing this creates a new text spanner.

This engraver creates the following layout object(s):

Section 3.1.78 [OttavaBracket], page 354.

`Section 2.2.78 [Output_property_engraver], page 260`
: Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

`Section 2.2.85 [Piano_pedal_align_engraver], page 263`
: Align piano pedal symbols and brackets.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.108 [SustainPedalLineSpanner], page 379 and Section 3.1.127 [UnaCordaPedalLineSpanner], page 397.

`Section 2.2.86 [Piano_pedal_engraver], page 263`
: Engrave piano pedal symbols and brackets.

Music types accepted:

Section 1.2.58 [sostenuto-event], page 46, Section 1.2.66 [sustain-event], page 47 and Section 1.2.75 [una-corda-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`pedalSostenutoStrings` (list)
: See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)
: See `pedalSustainStyle`.

`pedalSustainStrings` (list)
: A list of strings to print for sustain-pedal. Format is `(up updown down)`, where each of the

three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)
: A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)
: See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)
: See `pedalSustainStyle`.

This engraver creates the following layout object(s):

Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378 and Section 3.1.126 [UnaCordaPedal], page 396.

`Section 2.2.92 [Rest_collision_engraver], page 265`
Handle collisions of rests.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

This engraver creates the following layout object(s):

Section 3.1.90 [RestCollision], page 364.

`Section 2.2.98 [Script_row_engraver], page 266`
Determine order in horizontal side position elements.

This engraver creates the following layout object(s):

Section 3.1.93 [ScriptRow], page 366.

`Section 2.2.99 [Separating_line_group_engraver], page 266`
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
: Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
: True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

`Section 2.2.107 [Staff_collecting_engraver], page 269`
Maintain the `stavesFound` variable.

Properties (read)

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

Properties (write)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

`Section 2.2.109 [Staff_symbol_engraver], page 269`
Create the constellation of five (default) staff lines.

Music types accepted:

Section 1.2.62 [staff-span-event], page 46

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

`Section 2.2.122 [Time_signature_engraver], page 273`
Create a Section 3.1.119 [TimeSignature], page 390 whenever `timeSignatureFraction` changes.

Properties (read)

`implicitTimeSignatureVisibility` (vector)
break visibility for the default time signature.

`timeSignatureFraction` (pair of numbers)
A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

This engraver creates the following layout object(s):

Section 3.1.119 [TimeSignature], page 390.

2.1.13 GregorianTranscriptionVoice

Corresponds to a voice on a staff. This context handles the conversion of dynamic signs, stems, beams, super- and subscripts, slurs, ties, and rests.

You have to instantiate this explicitly if you want to have multiple voices on the same staff.

This context also accepts commands for the following context(s):

Voice.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.23 [BreathingSign], page 306, Section 3.1.26 [ClusterSpanner], page 309, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.40 [Episema], page 322, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.45 [Glissando], page 327, Section 3.1.49 [Hairpin], page 330, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.59 [LigatureBracket], page 339, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.73 [NoteColumn], page 350, Section 3.1.74 [NoteHead], page 351, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83 [PhrasingSlur], page 358, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.91 [Script], page 365,

Section 3.1.92 [ScriptColumn], page 365, Section 3.1.94 [Slur], page 366, Section 3.1.103 [Stem], page 374, Section 3.1.104 [StemTremolo], page 375, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.125 [TupletNumber], page 396 and Section 3.1.131 [VoiceFollower], page 401.

This context sets the following properties:

- Set grob-property `padding` in Section 3.1.91 [Script], page 365 to `0.5`.
- Set grob-property `transparent` in Section 3.1.59 [LigatureBracket], page 339 to `#t`.
- Set translator property `autoBeaming` to `#f`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.3 [Arpeggio_engraver], page 234
: Generate an Arpeggio symbol.

  Music types accepted:

  Section 1.2.4 [arpeggio-event], page 39

  This engraver creates the following layout object(s):

  Section 3.1.9 [Arpeggio], page 295.

Section 2.2.4 [Auto_beam_engraver], page 235
: Generate beams based on measure characteristics and observed Stems. Uses `baseMoment`, `beatStructure`, `beamExceptions`, `measureLength`, and `measurePosition` to decide when to start and stop a beam. Overriding beaming is done through Section 2.2.112 [Stem_engraver], page 270 properties `stemLeftBeamCount` and `stemRightBeamCount`.

  Music types accepted:

  Section 1.2.8 [beam-forbid-event], page 40

  Properties (read)

  `autoBeaming` (boolean)
  : If set to true then beams are generated automatically.

  `baseMoment` (moment)
  : Smallest unit of time that will stand on its own as a subdivided section.

  `beamExceptions` (list)
  : An alist of exceptions to autobeam rules that normally end on beats.

  `beatStructure` (list)
  : List of `baseMoments` that are combined to make beats.

  `subdivideBeams` (boolean)
  : If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.10 [Beam_engraver], page 237

Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.12 [Bend_engraver], page 238

Create fall spanners.

Music types accepted:

Section 1.2.9 [bend-after-event], page 40

This engraver creates the following layout object(s):

Section 3.1.20 [BendAfter], page 304.

Section 2.2.14 [Breathing_sign_engraver], page 238

Create a breathing sign.

Music types accepted:

Section 1.2.13 [breathing-event], page 40

This engraver creates the following layout object(s):

Section 3.1.23 [BreathingSign], page 306.

Section 2.2.16 [Chord_tremolo_engraver], page 239

Generate beams for tremolo repeats.

Music types accepted:

Section 1.2.72 [tremolo-span-event], page 48

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.18 [Cluster_spanner_engraver], page 240
Engrave a cluster using `Spanner` notation.

Music types accepted:

Section 1.2.14 [cluster-note-event], page 40

This engraver creates the following layout object(s):

Section 3.1.26 [ClusterSpanner], page 309 and Section 3.1.27 [ClusterSpannerBeacon], page 309.

Section 2.2.27 [Dots_engraver], page 243
Create Section 3.1.33 [Dots], page 315 objects for Section 3.2.87 [rhythmic-head-interface], page 447s.

This engraver creates the following layout object(s):

Section 3.1.33 [Dots], page 315.

Section 2.2.28 [Double_percent_repeat_engraver], page 243
Make double measure repeats.

Music types accepted:

Section 1.2.18 [double-percent-event], page 41

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`measureLength` (moment)
: Length of one measure in the current time signature.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.34 [DoublePercentRepeat], page 315 and Section 3.1.35 [DoublePercentRepeatCounter], page 316.

Section 2.2.31 [Dynamic_align_engraver], page 244
Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

Section 2.2.35 [Episema_engraver], page 245
Create an *Editio Vaticana*-style episema line.

Music types accepted:

Section 1.2.20 [episema-event], page 41

This engraver creates the following layout object(s):

Section 3.1.40 [Episema], page 322.

Section 2.2.39 [Fingering_engraver], page 247
Create fingering scripts.

Music types accepted:

Section 1.2.22 [fingering-event], page 41 and Section 1.2.65 [stroke-finger-event], page 47

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323.

Section 2.2.40 [Font_size_engraver], page 247
Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
The relative size of all grobs in a context.

Section 2.2.41 [Footnote_engraver], page 247
Create footnote texts.

Music types accepted:

Section 1.2.23 [footnote-event], page 41

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

Section 2.2.42 [Forbid_line_break_engraver], page 248
Forbid line breaks when note heads are still playing at some point.

Properties (read)

`busyGrobs` (list)
A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`forbidBreak` (boolean)
If set to `##t`, prevent a line break at this point.

Section 2.2.44 [Glissando_engraver], page 249
Engrave glissandi.

Music types accepted:

Section 1.2.24 [glissando-event], page 41

Properties (read)

`glissandoMap` (list)
: A map in the form of '((source1 . target1) (source2 . target2) (sourcen . targetn)) showing the glissandi to be drawn for note columns. The value '() will default to '((0 . 0) (1 . 1) (n . n)), where n is the minimal number of noteheads in the two note columns between which the glissandi occur.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327.

`Section 2.2.45 [Grace_beam_engraver], page 249`
: Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams. Only engraves beams when we are at grace points in time.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.46 [Grace_engraver], page 250`
: Set font size and other properties for grace notes.

Properties (read)

`graceSettings` (list)
: Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

`Section 2.2.50 [Grob_pq_engraver], page 250`
: Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.55 [Instrument_switch_engraver], page 252
: Create a cue text for taking instrument.

Properties (read)

`instrumentCueName` (markup)
: The name to print if another instrument is to be taken.

This engraver creates the following layout object(s):

Section 3.1.52 [InstrumentSwitch], page 333.

Section 2.2.59 [Laissez_vibrer_engraver], page 254
: Create laissez vibrer items.

Music types accepted:

Section 1.2.29 [laissez-vibrer-event], page 42

This engraver creates the following layout object(s):

Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.56 [LaissezVibrerTieColumn], page 337.

Section 2.2.61 [Ligature_bracket_engraver], page 254
: Handle `Ligature_events` by engraving `Ligature` brackets.

Music types accepted:

Section 1.2.31 [ligature-event], page 42

This engraver creates the following layout object(s):

Section 3.1.59 [LigatureBracket], page 339.

Section 2.2.69 [Multi_measure_rest_engraver], page 257
: Engrave multi-measure rests that are produced with '`R`'. It reads `measurePosition` and `internalBarNumber` to determine what number to print over the Section 3.1.68 [MultiMeasureRest], page 346. Reads `measureLength` to determine whether it should use a whole rest or a breve rest to represent one measure.

Music types accepted:

Section 1.2.36 [multi-measure-rest-event], page 43 and Section 1.2.37 [multi-measure-text-event], page 43

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`restNumberThreshold` (number)
: If a multimeasure rest has more measures than this, a number is printed.

This engraver creates the following layout object(s):

Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

`Section 2.2.70 [New_dynamic_engraver], page 257`

Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

Section 2.2.71 [New_fingering_engraver], page 258
Create fingering scripts for notes in a new chord. This engraver is ill-named, since it also takes care of articulations and harmonic note heads.

Properties (read)

`fingeringOrientations` (list)
A list of symbols, containing '`left`', '`right`', '`up`' and/or '`down`'. This list determines where fingerings are put relative to the chord being fingered.

`harmonicDots` (boolean)
If set, harmonic notes in dotted chords get dots.

`stringNumberOrientations` (list)
See `fingeringOrientations`.

`strokeFingerOrientations` (list)
See `fingeringOrientations`.

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323, Section 3.1.91 [Script], page 365, Section 3.1.105 [StringNumber], page 376 and Section 3.1.106 [StrokeFinger], page 377.

Section 2.2.72 [Note_head_line_engraver], page 258
Engrave a line between two note heads, for example a glissando. If `followVoice` is set, staff switches also generate a line.

Properties (read)

`followVoice` (boolean)
If set, note heads are tracked across staff switches by a thin line.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327 and Section 3.1.131 [VoiceFollower], page 401.

Section 2.2.73 [Note_heads_engraver], page 259
Generate note heads.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`middleCPosition` (number)
The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`staffLineLayoutFunction` (procedure)
Layout of staff lines, `traditional`, or `semitone`.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351.

Section 2.2.76 [Note_spacing_engraver], page 259
: Generate `NoteSpacing`, an object linking horizontal lines for use in spacing.

  This engraver creates the following layout object(s):

  Section 3.1.76 [NoteSpacing], page 352.

Section 2.2.78 [Output_property_engraver], page 260
: Apply a procedure to any grob acknowledged.

  Music types accepted:

  Section 1.2.3 [apply-output-event], page 39

Section 2.2.82 [Part_combine_engraver], page 261
: Part combine engraver for orchestral scores: Print markings 'a2', 'Solo', 'Solo II', and 'unisono'.

  Music types accepted:

  Section 1.2.39 [note-event], page 43 and Section 1.2.43 [part-combine-event], page 44

  Properties (read)

  `aDueText` (markup)
  : Text to print at a unisono passage.

  `partCombineTextsOnNote` (boolean)
  : Print part-combine texts only on the next note rather than immediately on rests or skips.

  `printPartCombineTexts` (boolean)
  : Set 'Solo' and 'A due' texts in the part combiner?

  `soloIIText` (markup)
  : The text for the start of a solo for voice 'two' when part-combining.

  `soloText` (markup)
  : The text for the start of a solo when part-combining.

  This engraver creates the following layout object(s):

  Section 3.1.28 [CombineTextScript], page 309.

Section 2.2.83 [Percent_repeat_engraver], page 262
: Make whole measure repeats.

  Music types accepted:

  Section 1.2.46 [percent-event], page 44

  Properties (read)

  `countPercentRepeats` (boolean)
  : If set, produce counters for percent repeats.

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

This engraver creates the following layout object(s):

Section 3.1.81 [PercentRepeat], page 356 and Section 3.1.82 [PercentRepeatCounter], page 357.

`Section 2.2.84 [Phrasing_slur_engraver], page 262`
: Print phrasing slurs. Similar to Section 2.2.101 [Slur_engraver], page 267.

Music types accepted:

Section 1.2.48 [phrasing-slur-event], page 45

This engraver creates the following layout object(s):

Section 3.1.83 [PhrasingSlur], page 358.

`Section 2.2.89 [Pitched_trill_engraver], page 264`
: Print the bracketed note head after a note head with trill.

This engraver creates the following layout object(s):

Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392 and Section 3.1.122 [TrillPitchHead], page 393.

`Section 2.2.91 [Repeat_tie_engraver], page 265`
: Create repeat ties.

Music types accepted:

Section 1.2.50 [repeat-tie-event], page 45

This engraver creates the following layout object(s):

Section 3.1.87 [RepeatTie], page 362 and Section 3.1.88 [RepeatTieColumn], page 363.

`Section 2.2.93 [Rest_engraver], page 265`
: Engrave rests.

Music types accepted:

Section 1.2.51 [rest-event], page 45

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

This engraver creates the following layout object(s):

Section 3.1.89 [Rest], page 364.

`Section 2.2.94 [Rhythmic_column_engraver], page 265`
: Generate `NoteColumn`, an object that groups stems, note heads, and rests.

This engraver creates the following layout object(s):

Section 3.1.73 [NoteColumn], page 350.

Section 2.2.96 [Script_column_engraver], page 266
: Find potentially colliding scripts and put them into a `ScriptColumn` object; that will fix the collisions.

  This engraver creates the following layout object(s):

  Section 3.1.92 [ScriptColumn], page 365.

Section 2.2.97 [Script_engraver], page 266
: Handle note scripted articulations.

  Music types accepted:

  Section 1.2.5 [articulation-event], page 40

  Properties (read)

  `scriptDefinitions` (list)
  : The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

  This engraver creates the following layout object(s):

  Section 3.1.91 [Script], page 365.

Section 2.2.100 [Slash_repeat_engraver], page 267
: Make beat repeats.

  Music types accepted:

  Section 1.2.49 [repeat-slash-event], page 45

  This engraver creates the following layout object(s):

  Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

Section 2.2.101 [Slur_engraver], page 267
: Build slur grobs from slur events.

  Music types accepted:

  Section 1.2.55 [slur-event], page 45

  Properties (read)

  `doubleSlurs` (boolean)
  : If set, two slurs are created for every slurred note, one above and one below the chord.

  `slurMelismaBusy` (boolean)
  : Signal if a slur is present.

  This engraver creates the following layout object(s):

  Section 3.1.94 [Slur], page 366.

Section 2.2.106 [Spanner_break_forbid_engraver], page 268
: Forbid breaks in certain spanners.

Section 2.2.112 [Stem_engraver], page 270
: Create stems and single-stem tremolos. It also works together with the beam engraver for overriding beaming.

  Music types accepted:

  Section 1.2.71 [tremolo-event], page 48

  Properties (read)

`stemLeftBeamCount` (integer)
: Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.

`stemRightBeamCount` (integer)
: See `stemLeftBeamCount`.

`tremoloFlags` (integer)
: The number of tremolo flags to add if no number is specified.

This engraver creates the following layout object(s):

Section 3.1.103 [Stem], page 374 and Section 3.1.104 [StemTremolo], page 375.

`Section 2.2.118 [Text_engraver], page 272`

Create text scripts.

Music types accepted:

Section 1.2.68 [text-script-event], page 47

This engraver creates the following layout object(s):

Section 3.1.115 [TextScript], page 385.

`Section 2.2.119 [Text_spanner_engraver], page 272`

Create text spanner from an event.

Music types accepted:

Section 1.2.69 [text-span-event], page 48

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.116 [TextSpanner], page 387.

`Section 2.2.120 [Tie_engraver], page 272`

Generate ties between note heads of equal pitch.

Music types accepted:

Section 1.2.70 [tie-event], page 48

Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

Section 2.2.126 [Trill_spanner_engraver], page 274
: Create trill spanner from an event.

  Music types accepted:

  Section 1.2.73 [trill-span-event], page 48

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  `currentMusicalColumn` (graphical (layout) object)
  : Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

  This engraver creates the following layout object(s):

  Section 3.1.123 [TrillSpanner], page 393.

Section 2.2.127 [Tuplet_engraver], page 275
: Catch tuplet events and generate appropriate bracket.

  Music types accepted:

  Section 1.2.74 [tuplet-span-event], page 48

  Properties (read)

  `tupletFullLength` (boolean)
  : If set, the tuplet is printed up to the start of the next note.

  `tupletFullLengthNote` (boolean)
  : If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

  This engraver creates the following layout object(s):

  Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

Section 2.2.128 [Tweak_engraver], page 275
: Read the `tweaks` property from the originating event, and set properties.

2.1.14 Lyrics

Corresponds to a voice with lyrics. Handles the printing of a single line of lyrics.

This context creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332, Section 3.1.60 [LyricExtender], page 340, Section 3.1.61 [LyricHyphen], page 340, Section 3.1.62 [LyricSpace], page 341, Section 3.1.63 [LyricText], page 342, Section 3.1.102 [StanzaNumber], page 373 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `bar-extent` in Section 3.1.11 [BarLine], page 297 to `'(-0.05 . 0.05)`.
- Set grob-property `font-size` in Section 3.1.51 [InstrumentName], page 332 to `1.0`.
- Set grob-property `nonstaff-nonstaff-spacing` in Section 3.1.130 [VerticalAxisGroup], page 399 to `'((basic-distance . 0) (minimum-distance . 2.8) (padding . 0.2) (stretchability . 0))`.

- Set grob-property `nonstaff-relatedstaff-spacing` in Section 3.1.130 [VerticalAxisGroup], page 399 to `'((basic-distance . 5.5) (padding . 0.5) (stretchability . 1))`.
- Set grob-property `nonstaff-unrelatedstaff-spacing padding` in Section 3.1.130 [VerticalAxisGroup], page 399 to `1.5`.
- Set grob-property `remove-empty` in Section 3.1.130 [VerticalAxisGroup], page 399 to `#t`.
- Set grob-property `remove-first` in Section 3.1.130 [VerticalAxisGroup], page 399 to `#t`.
- Set grob-property `self-alignment-Y` in Section 3.1.51 [InstrumentName], page 332 to `#f`.
- Set grob-property `staff-affinity` in Section 3.1.130 [VerticalAxisGroup], page 399 to `1`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `searchForVoice` to `#f`.
- Set translator property `shortInstrumentName` to `'()`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.36 [Extender_engraver], page 246
: Create lyric extenders.

  Music types accepted:

  Section 1.2.15 [completize-extender-event], page 41 and Section 1.2.21 [extender-event], page 41

  Properties (read)

  `extendersOverRests` (boolean)
  : Whether to continue extenders as they cross a rest.

  `includeGraceNotes` (boolean)
  : Do not ignore grace notes for Section "Lyrics" in *Internals Reference*.

  This engraver creates the following layout object(s):

  Section 3.1.60 [LyricExtender], page 340.

Section 2.2.40 [Font_size_engraver], page 247
: Put `fontSize` into `font-size` grob property.

  Properties (read)

  `fontSize` (number)
  : The relative size of all grobs in a context.

Section 2.2.51 [Hara_kiri_engraver], page 251
: Like `Axis_group_engraver`, but make a hara-kiri spanner, and add interesting items (i.e., note heads, lyric syllables, and normal rests).

  Properties (read)

  `keepAliveInterfaces` (list)
  : A list of symbols, signifying grob interfaces that are worth keeping a staff with `remove-empty` set around for.

  This engraver creates the following layout object(s):

  Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.53 [Hyphen_engraver], page 251
Create lyric hyphens and distance constraints between words.

Music types accepted:

Section 1.2.26 [hyphen-event], page 42

This engraver creates the following layout object(s):

Section 3.1.61 [LyricHyphen], page 340 and Section 3.1.62 [LyricSpace], page 341.

Section 2.2.54 [Instrument_name_engraver], page 251
Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
See `instrumentName`.

`shortVocalName` (markup)
Name of a vocal line, short version.

`vocalName` (markup)
Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

Section 2.2.62 [Lyric_engraver], page 254
Engrave text for lyrics.

Music types accepted:

Section 1.2.33 [lyric-event], page 42

Properties (read)

`ignoreMelismata` (boolean)
Ignore melismata for this Section "Lyrics" in *Internals Reference* line.

`includeGraceNotes` (boolean)
Do not ignore grace notes for Section "Lyrics" in *Internals Reference*.

`lyricMelismaAlignment` (direction)
Alignment to use for a melisma syllable.

`searchForVoice` (boolean)
Signal whether a search should be made of all contexts in the context hierarchy for a voice to provide rhythms for the lyrics.

This engraver creates the following layout object(s):

Section 3.1.63 [LyricText], page 342.

`Section 2.2.111 [Stanza_number_engraver], page 269`

Engrave stanza numbers.

Properties (read)

`stanza` (markup)

Stanza 'number' to print before the start of a verse. Use in `Lyrics` context.

This engraver creates the following layout object(s):

Section 3.1.102 [StanzaNumber], page 373.

2.1.15 MensuralStaff

Same as `Staff` context, except that it is accommodated for typesetting a piece in mensural style.

This context also accepts commands for the following context(s):

Staff.

This context creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290, Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.11 [BarLine], page 297, Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.31 [Custos], page 313, Section 3.1.32 [DotColumn], page 314, Section 3.1.51 [InstrumentName], page 332, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.72 [NoteCollision], page 350, Section 3.1.77 [OctavateEight], page 353, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.90 [RestCollision], page 364, Section 3.1.93 [ScriptRow], page 366, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.107 [SustainPedal], page 378, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.119 [TimeSignature], page 390, Section 3.1.126 [UnaCordaPedal], page 396, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `glyph-name-alist` in Section 3.1.1 [Accidental], page 289 to `'((-1/2 . accidentals.mensuralM1) (0 . accidentals.vaticana0) (1/2 . accidentals.mensural1))`.
- Set grob-property `glyph-name-alist` in Section 3.1.54 [KeySignature], page 335 to `'((-1/2 . accidentals.mensuralM1) (0 . accidentals.vaticana0) (1/2 . accidentals.mensural1))`.
- Set grob-property `neutral-direction` in Section 3.1.31 [Custos], page 313 to `-1`.
- Set grob-property `neutral-position` in Section 3.1.31 [Custos], page 313 to `3`.
- Set grob-property `style` in Section 3.1.31 [Custos], page 313 to `'mensural`.
- Set grob-property `style` in Section 3.1.119 [TimeSignature], page 390 to `'mensural`.
- Set grob-property `thickness` in Section 3.1.101 [StaffSymbol], page 372 to `0.6`.
- Set grob-property `transparent` in Section 3.1.11 [BarLine], page 297 to `#t`.

- Set translator property `autoAccidentals` to `'(Staff #<procedure #f (context pitch barnum measurepos)>)`.
- Set translator property `autoCautionaries` to `'()`.
- Set translator property `clefGlyph` to `"clefs.mensural.g"`.
- Set translator property `clefOctavation` to `0`.
- Set translator property `clefPosition` to `-2`.
- Set translator property `createSpacing` to `#t`.
- Set translator property `extraNatural` to `#f`.
- Set translator property `ignoreFiguredBassRest` to `#f`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `localKeySignature` to `'()`.
- Set translator property `middleCClefPosition` to `-6`.
- Set translator property `middleCPosition` to `-6`.
- Set translator property `printKeyCancellation` to `#f`.
- Set translator property `shortInstrumentName` to `'()`.

Context MensuralStaff can contain Section 2.1.3 [CueVoice], page 57 and Section 2.1.16 [MensuralVoice], page 133.

This context is built from the following engraver(s):

Section 2.2.1 [Accidental_engraver], page 233

Make accidentals. Catch note heads, ties and notices key-change events. This engraver usually lives at Staff level, but reads the settings for Accidental at `Voice` level, so you can `\override` them at `Voice`.

Properties (read)

`autoAccidentals` (list)

List of different ways to typeset an accidental.

For determining when to print an accidental, several different rules are tried. The rule that gives the highest number of accidentals is used.

Each entry in the list is either a symbol or a procedure.

symbol The symbol is the name of the context in which the following rules are to be applied. For example, if *context* is Section "Score" in *Internals Reference* then all staves share accidentals, and if *context* is Section "Staff" in *Internals Reference* then all voices in the same staff share accidentals, but staves do not.

procedure The procedure represents an accidental rule to be applied to the previously specified context.

The procedure takes the following arguments:

`context` The current context to which the rule should be applied.

`pitch` The pitch of the note to be evaluated.

`barnum` The current bar number.

`measurepos` The current measure position.

The procedure returns a pair of booleans. The first states whether an extra natural should be added. The second states whether an accidental should be printed. `(#t . #f)` does not make sense.

`autoCautionaries` (list)
: List similar to `autoAccidentals`, but it controls cautionary accidentals rather than normal ones. Both lists are tried, and the one giving the most accidentals wins. In case of draw, a normal accidental is typeset.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`harmonicAccidentals` (boolean)
: If set, harmonic notes in chords get accidentals.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step . alter`*`)` or `((`*`octave . step`*`) . `*`alter`*`)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((`*`octave . name`*`) . (`*`alter barnumber . measureposition`*`))` pairs.

Properties (write)

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`,

but can also contain `((octave . name) . (alter barnumber . measureposition))` pairs.

This engraver creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290 and Section 3.1.4 [AccidentalSuggestion], page 291.

Section 2.2.5 [Axis_group_engraver], page 235

Group all objects created in this context in a `VerticalAxisGroup` spanner.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.7 [Bar_engraver], page 236

Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

Properties (read)

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

  ```
  \set Staff.whichBar = "|:"
  ```

  This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.11 [BarLine], page 297.

Section 2.2.9 [Beam_collision_engraver], page 237

Help beams avoid colliding with notes and clefs in other voices.

Section 2.2.17 [Clef_engraver], page 239

Determine and set reference point for pitches.

Properties (read)

`clefGlyph` (string)
: Name of the symbol within the music font.

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`clefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitClefVisibility` (vector)
: '`break-visibility`' function for clef changes.

`forceClef` (boolean)
: Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

This engraver creates the following layout object(s):

Section 3.1.25 [Clef], page 307 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.19 [Collision_engraver], page 240
: Collect `NoteColumns`, and as soon as there are two or more, put them in a `NoteCollision` object.

This engraver creates the following layout object(s):

Section 3.1.72 [NoteCollision], page 350.

Section 2.2.23 [Cue_clef_engraver], page 241
: Determine and set reference point for pitches in cued voices.

Properties (read)

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefGlyph` (string)
: Name of the symbol within the music font.

`cueClefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitCueClefVisibility` (vector)
: '`break-visibility`' function for cue clef changes.

`middleCCuePosition` (number)
: The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

This engraver creates the following layout object(s):

Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.24 [Custos_engraver], page 242
: Engrave custodes.

  This engraver creates the following layout object(s):

  Section 3.1.31 [Custos], page 313.

Section 2.2.26 [Dot_column_engraver], page 243
: Engrave dots on dotted notes shifted to the right of the note. If omitted, then dots appear on top of the notes.

  This engraver creates the following layout object(s):

  Section 3.1.32 [DotColumn], page 314.

Section 2.2.37 [Figured_bass_engraver], page 246
: Make figured bass numbers.

  Music types accepted:

  Section 1.2.6 [bass-figure-event], page 40 and Section 1.2.51 [rest-event], page 45

  Properties (read)

  `figuredBassAlterationDirection` (direction)
  : Where to put alterations relative to the main figure.

  `figuredBassCenterContinuations` (boolean)
  : Whether to vertically center pairs of extender lines. This does not work with three or more lines.

  `figuredBassFormatter` (procedure)
  : A routine generating a markup for a bass figure.

  `ignoreFiguredBassRest` (boolean)
  : Don't swallow rest events.

  `implicitBassFigures` (list)
  : A list of bass figures that are not printed as numbers, but only as extender lines.

  `useBassFigureExtenders` (boolean)
  : Whether to use extender lines for repeated bass figures.

  This engraver creates the following layout object(s):

  Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301 and Section 3.1.18 [BassFigureLine], page 302.

Section 2.2.38 [Figured_bass_position_engraver], page 247
: Position figured bass alignments over notes.

  This engraver creates the following layout object(s):

  Section 3.1.15 [BassFigureAlignmentPositioning], page 300.

Section 2.2.40 [Font_size_engraver], page 247
: Put `fontSize` into `font-size` grob property.

  Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

Section 2.2.50 [Grob_pq_engraver], page 250
: Administrate when certain grobs (e.g., note heads) stop playing.

  Properties (read)

  `busyGrobs` (list)
  : A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

  Properties (write)

  `busyGrobs` (list)
  : A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.54 [Instrument_name_engraver], page 251
: Create a system start text for instrument or vocal names.

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  `instrumentName` (markup)
  : The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

  `shortInstrumentName` (markup)
  : See `instrumentName`.

  `shortVocalName` (markup)
  : Name of a vocal line, short version.

  `vocalName` (markup)
  : Name of a vocal line.

  This engraver creates the following layout object(s):

  Section 3.1.51 [InstrumentName], page 332.

Section 2.2.57 [Key_engraver], page 252
: Engrave a key signature.

  Music types accepted:

  Section 1.2.27 [key-change-event], page 42

  Properties (read)

  `createKeyOnClefChange` (boolean)
  : Print a key signature whenever the clef is changed.

`explicitKeySignatureVisibility` (vector)
: '`break-visibility`' function for explicit key changes. '`\override`' of the `break-visibility` property will set the visibility for normal (i.e., at the start of the line) key signatures.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`keyAlterationOrder` (list)
: An alist that defines in what order alterations should be printed. The format is `(`*`step . alter`*`)`, where *step* is a number from 0 to 6 and *alter* from -2 (sharp) to 2 (flat).

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step . alter`*`)` or `((`*`octave . step`*`) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`middleCClefPosition` (number)
: The position of the middle C, as determined only by the clef. This can be calculated by looking at `clefPosition` and `clefGlyph`.

`printKeyCancellation` (boolean)
: Print restoration alterations before a key signature change.

Properties (write)

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step . alter`*`)` or `((`*`octave . step`*`) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`tonic` (pitch)
: The tonic of the current scale.

This engraver creates the following layout object(s):

Section 3.1.53 [KeyCancellation], page 334 and Section 3.1.54 [KeySignature], page 335.

Section 2.2.60 [Ledger_line_engraver], page 254
Create the spanner to draw ledger lines, and notices objects that need ledger lines.

This engraver creates the following layout object(s):

Section 3.1.57 [LedgerLineSpanner], page 337.

Section 2.2.77 [Ottava_spanner_engraver], page 260
Create a text spanner when the ottavation property changes.

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`middleCOffset` (number)
The offset of middle C from the position given by `middleCClefPosition` This is used for ottava brackets.

`ottavation` (markup)
If set, the text for an ottava spanner. Changing this creates a new text spanner.

This engraver creates the following layout object(s):

Section 3.1.78 [OttavaBracket], page 354.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.85 [Piano_pedal_align_engraver], page 263
Align piano pedal symbols and brackets.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.108 [SustainPedalLineSpanner], page 379 and Section 3.1.127 [UnaCordaPedalLineSpanner], page 397.

Section 2.2.86 [Piano_pedal_engraver], page 263
Engrave piano pedal symbols and brackets.

Music types accepted:

Section 1.2.58 [sostenuto-event], page 46, Section 1.2.66 [sustain-event], page 47 and Section 1.2.75 [una-corda-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`pedalSostenutoStrings` (list)
: See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)
: See `pedalSustainStyle`.

`pedalSustainStrings` (list)
: A list of strings to print for sustain-pedal. Format is `(up updown down)`, where each of the three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)
: A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)
: See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)
: See `pedalSustainStyle`.

This engraver creates the following layout object(s):

Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378 and Section 3.1.126 [UnaCordaPedal], page 396.

`Section 2.2.92 [Rest_collision_engraver], page 265`
Handle collisions of rests.

Properties (read)

`busyGrobs` (list)
: A queue of `(end-moment . GROB)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

This engraver creates the following layout object(s):

Section 3.1.90 [RestCollision], page 364.

`Section 2.2.98 [Script_row_engraver], page 266`
Determine order in horizontal side position elements.

This engraver creates the following layout object(s):

Section 3.1.93 [ScriptRow], page 366.

`Section 2.2.99 [Separating_line_group_engraver], page 266`
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
: Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
: True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

Section 2.2.107 [Staff_collecting_engraver], page 269
Maintain the `stavesFound` variable.

Properties (read)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Properties (write)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Section 2.2.109 [Staff_symbol_engraver], page 269
Create the constellation of five (default) staff lines.

Music types accepted:

Section 1.2.62 [staff-span-event], page 46

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

Section 2.2.122 [Time_signature_engraver], page 273
Create a Section 3.1.119 [TimeSignature], page 390 whenever `timeSignatureFraction` changes.

Properties (read)

`implicitTimeSignatureVisibility` (vector)
break visibility for the default time signature.

`timeSignatureFraction` (pair of numbers)
A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

This engraver creates the following layout object(s):

Section 3.1.119 [TimeSignature], page 390.

2.1.16 MensuralVoice

Same as `Voice` context, except that it is accommodated for typesetting a piece in mensural style.

This context also accepts commands for the following context(s):

Voice.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.23 [BreathingSign], page 306, Section 3.1.26 [ClusterSpanner], page 309, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.45 [Glissando], page 327, Section 3.1.49 [Hairpin], page 330, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.66 [MensuralLigature], page 344,

Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.73 [NoteColumn], page 350, Section 3.1.74 [NoteHead], page 351, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83 [PhrasingSlur], page 358, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.91 [Script], page 365, Section 3.1.92 [ScriptColumn], page 365, Section 3.1.103 [Stem], page 374, Section 3.1.104 [StemTremolo], page 375, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.125 [TupletNumber], page 396 and Section 3.1.131 [VoiceFollower], page 401.

This context sets the following properties:

- Set grob-property `style` in Section 3.1.74 [NoteHead], page 351 to `'mensural`.
- Set grob-property `style` in Section 3.1.89 [Rest], page 364 to `'mensural`.
- Set translator property `autoBeaming` to `#f`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

`Section 2.2.3 [Arpeggio_engraver], page 234`

Generate an Arpeggio symbol.

Music types accepted:

Section 1.2.4 [arpeggio-event], page 39

This engraver creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295.

`Section 2.2.4 [Auto_beam_engraver], page 235`

Generate beams based on measure characteristics and observed Stems. Uses `baseMoment`, `beatStructure`, `beamExceptions`, `measureLength`, and `measurePosition` to decide when to start and stop a beam. Overriding beaming is done through Section 2.2.112 [Stem_engraver], page 270 properties `stemLeftBeamCount` and `stemRightBeamCount`.

Music types accepted:

Section 1.2.8 [beam-forbid-event], page 40

Properties (read)

`autoBeaming` (boolean)
: If set to true then beams are generated automatically.

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamExceptions` (list)
: An alist of exceptions to autobeam rules that normally end on beats.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.10 [Beam_engraver], page 237
: Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.12 [Bend_engraver], page 238
: Create fall spanners.

Music types accepted:

Section 1.2.9 [bend-after-event], page 40

This engraver creates the following layout object(s):

Section 3.1.20 [BendAfter], page 304.

Section 2.2.14 [Breathing_sign_engraver], page 238
: Create a breathing sign.

Music types accepted:

Section 1.2.13 [breathing-event], page 40

This engraver creates the following layout object(s):

Section 3.1.23 [BreathingSign], page 306.

Section 2.2.16 [Chord_tremolo_engraver], page 239
: Generate beams for tremolo repeats.

Music types accepted:

Section 1.2.72 [tremolo-span-event], page 48

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.18 [Cluster_spanner_engraver], page 240`

Engrave a cluster using `Spanner` notation.

Music types accepted:

Section 1.2.14 [cluster-note-event], page 40

This engraver creates the following layout object(s):

Section 3.1.26 [ClusterSpanner], page 309 and Section 3.1.27 [ClusterSpannerBeacon], page 309.

`Section 2.2.27 [Dots_engraver], page 243`

Create Section 3.1.33 [Dots], page 315 objects for Section 3.2.87 [rhythmic-head-interface], page 447s.

This engraver creates the following layout object(s):

Section 3.1.33 [Dots], page 315.

`Section 2.2.28 [Double_percent_repeat_engraver], page 243`

Make double measure repeats.

Music types accepted:

Section 1.2.18 [double-percent-event], page 41

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`measureLength` (moment)
: Length of one measure in the current time signature.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.34 [DoublePercentRepeat], page 315 and Section 3.1.35 [DoublePercentRepeatCounter], page 316.

`Section 2.2.31 [Dynamic_align_engraver], page 244`

Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

Section 2.2.39 [Fingering_engraver], page 247

Create fingering scripts.

Music types accepted:

Section 1.2.22 [fingering-event], page 41 and Section 1.2.65 [stroke-finger-event], page 47

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323.

Section 2.2.40 [Font_size_engraver], page 247

Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

Section 2.2.41 [Footnote_engraver], page 247

Create footnote texts.

Music types accepted:

Section 1.2.23 [footnote-event], page 41

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

Section 2.2.42 [Forbid_line_break_engraver], page 248

Forbid line breaks when note heads are still playing at some point.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

Section 2.2.44 [Glissando_engraver], page 249

Engrave glissandi.

Music types accepted:

Section 1.2.24 [glissando-event], page 41

Properties (read)

`glissandoMap` (list)
: A map in the form of '((source1 . target1) (source2 . target2) (sourcen . targetn)) showing the glissandi to be drawn for note columns. The value '() will default to '((0 . 0) (1 . 1) (n . n)), where n is the minimal number of noteheads in the two note columns between which the glissandi occur.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327.

`Section 2.2.45 [Grace_beam_engraver], page 249`
: Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams. Only engraves beams when we are at grace points in time.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.46 [Grace_engraver], page 250`
: Set font size and other properties for grace notes.

Properties (read)

`graceSettings` (list)
: Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

`Section 2.2.50 [Grob_pq_engraver], page 250`
: Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

`Section 2.2.55 [Instrument_switch_engraver], page 252`
Create a cue text for taking instrument.

Properties (read)

`instrumentCueName` (markup)
: The name to print if another instrument is to be taken.

This engraver creates the following layout object(s):

Section 3.1.52 [InstrumentSwitch], page 333.

`Section 2.2.59 [Laissez_vibrer_engraver], page 254`
Create laissez vibrer items.

Music types accepted:

Section 1.2.29 [laissez-vibrer-event], page 42

This engraver creates the following layout object(s):

Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.56 [LaissezVibrerTieColumn], page 337.

`Section 2.2.67 [Mensural_ligature_engraver], page 256`
Handle `Mensural_ligature_events` by glueing special ligature heads together.

Music types accepted:

Section 1.2.31 [ligature-event], page 42

This engraver creates the following layout object(s):

Section 3.1.66 [MensuralLigature], page 344.

`Section 2.2.69 [Multi_measure_rest_engraver], page 257`
Engrave multi-measure rests that are produced with '`R`'. It reads `measurePosition` and `internalBarNumber` to determine what number to print over the Section 3.1.68 [MultiMeasureRest], page 346. Reads `measureLength` to determine whether it should use a whole rest or a breve rest to represent one measure.

Music types accepted:

Section 1.2.36 [multi-measure-rest-event], page 43 and Section 1.2.37 [multi-measure-text-event], page 43

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`restNumberThreshold` (number)
: If a multimeasure rest has more measures than this, a number is printed.

This engraver creates the following layout object(s):

Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

`Section 2.2.70 [New_dynamic_engraver], page 257`

Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

`Section 2.2.71 [New_fingering_engraver], page 258`

Create fingering scripts for notes in a new chord. This engraver is ill-named, since it also takes care of articulations and harmonic note heads.

Properties (read)

`fingeringOrientations` (list)
: A list of symbols, containing '`left`', '`right`', '`up`' and/or '`down`'. This list determines where fingerings are put relative to the chord being fingered.

`harmonicDots` (boolean)
: If set, harmonic notes in dotted chords get dots.

`stringNumberOrientations` (list)
: See `fingeringOrientations`.

`strokeFingerOrientations` (list)
: See `fingeringOrientations`.

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323, Section 3.1.91 [Script], page 365, Section 3.1.105 [StringNumber], page 376 and Section 3.1.106 [StrokeFinger], page 377.

Section 2.2.72 [Note_head_line_engraver], page 258
: Engrave a line between two note heads, for example a glissando. If `followVoice` is set, staff switches also generate a line.

Properties (read)

`followVoice` (boolean)
: If set, note heads are tracked across staff switches by a thin line.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327 and Section 3.1.131 [VoiceFollower], page 401.

Section 2.2.73 [Note_heads_engraver], page 259
: Generate note heads.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`staffLineLayoutFunction` (procedure)
: Layout of staff lines, `traditional`, or `semitone`.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351.

Section 2.2.76 [Note_spacing_engraver], page 259
: Generate `NoteSpacing`, an object linking horizontal lines for use in spacing.

This engraver creates the following layout object(s):

Section 3.1.76 [NoteSpacing], page 352.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.82 [Part_combine_engraver], page 261
Part combine engraver for orchestral scores: Print markings 'a2', 'Solo', 'Solo II', and 'unisono'.

Music types accepted:

Section 1.2.39 [note-event], page 43 and Section 1.2.43 [part-combine-event], page 44

Properties (read)

`aDueText` (markup)
Text to print at a unisono passage.

`partCombineTextsOnNote` (boolean)
Print part-combine texts only on the next note rather than immediately on rests or skips.

`printPartCombineTexts` (boolean)
Set 'Solo' and 'A due' texts in the part combiner?

`soloIIText` (markup)
The text for the start of a solo for voice 'two' when part-combining.

`soloText` (markup)
The text for the start of a solo when part-combining.

This engraver creates the following layout object(s):

Section 3.1.28 [CombineTextScript], page 309.

Section 2.2.83 [Percent_repeat_engraver], page 262
Make whole measure repeats.

Music types accepted:

Section 1.2.46 [percent-event], page 44

Properties (read)

`countPercentRepeats` (boolean)
If set, produce counters for percent repeats.

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`repeatCountVisibility` (procedure)
A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

This engraver creates the following layout object(s):

Section 3.1.81 [PercentRepeat], page 356 and Section 3.1.82 [PercentRepeatCounter], page 357.

Section 2.2.84 [Phrasing_slur_engraver], page 262
: Print phrasing slurs. Similar to Section 2.2.101 [Slur_engraver], page 267.

  Music types accepted:

  Section 1.2.48 [phrasing-slur-event], page 45

  This engraver creates the following layout object(s):

  Section 3.1.83 [PhrasingSlur], page 358.

Section 2.2.89 [Pitched_trill_engraver], page 264
: Print the bracketed note head after a note head with trill.

  This engraver creates the following layout object(s):

  Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392 and Section 3.1.122 [TrillPitchHead], page 393.

Section 2.2.91 [Repeat_tie_engraver], page 265
: Create repeat ties.

  Music types accepted:

  Section 1.2.50 [repeat-tie-event], page 45

  This engraver creates the following layout object(s):

  Section 3.1.87 [RepeatTie], page 362 and Section 3.1.88 [RepeatTieColumn], page 363.

Section 2.2.93 [Rest_engraver], page 265
: Engrave rests.

  Music types accepted:

  Section 1.2.51 [rest-event], page 45

  Properties (read)

  `middleCPosition` (number)
  : The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

  This engraver creates the following layout object(s):

  Section 3.1.89 [Rest], page 364.

Section 2.2.94 [Rhythmic_column_engraver], page 265
: Generate `NoteColumn`, an object that groups stems, note heads, and rests.

  This engraver creates the following layout object(s):

  Section 3.1.73 [NoteColumn], page 350.

Section 2.2.96 [Script_column_engraver], page 266
: Find potentially colliding scripts and put them into a `ScriptColumn` object; that will fix the collisions.

  This engraver creates the following layout object(s):

  Section 3.1.92 [ScriptColumn], page 365.

Section 2.2.97 [Script_engraver], page 266
: Handle note scripted articulations.

  Music types accepted:

  Section 1.2.5 [articulation-event], page 40

  Properties (read)

`scriptDefinitions` (list)
: The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

This engraver creates the following layout object(s):

Section 3.1.91 [Script], page 365.

`Section 2.2.100 [Slash_repeat_engraver], page 267`
: Make beat repeats.

Music types accepted:

Section 1.2.49 [repeat-slash-event], page 45

This engraver creates the following layout object(s):

Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

`Section 2.2.106 [Spanner_break_forbid_engraver], page 268`
: Forbid breaks in certain spanners.

`Section 2.2.112 [Stem_engraver], page 270`
: Create stems and single-stem tremolos. It also works together with the beam engraver for overriding beaming.

Music types accepted:

Section 1.2.71 [tremolo-event], page 48

Properties (read)

`stemLeftBeamCount` (integer)
: Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.

`stemRightBeamCount` (integer)
: See `stemLeftBeamCount`.

`tremoloFlags` (integer)
: The number of tremolo flags to add if no number is specified.

This engraver creates the following layout object(s):

Section 3.1.103 [Stem], page 374 and Section 3.1.104 [StemTremolo], page 375.

`Section 2.2.118 [Text_engraver], page 272`
: Create text scripts.

Music types accepted:

Section 1.2.68 [text-script-event], page 47

This engraver creates the following layout object(s):

Section 3.1.115 [TextScript], page 385.

`Section 2.2.119 [Text_spanner_engraver], page 272`
: Create text spanner from an event.

Music types accepted:

Section 1.2.69 [text-span-event], page 48

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.116 [TextSpanner], page 387.

`Section 2.2.120 [Tie_engraver], page 272`

Generate ties between note heads of equal pitch.

Music types accepted:

Section 1.2.70 [tie-event], page 48

Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

`Section 2.2.126 [Trill_spanner_engraver], page 274`

Create trill spanner from an event.

Music types accepted:

Section 1.2.73 [trill-span-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.123 [TrillSpanner], page 393.

`Section 2.2.127 [Tuplet_engraver], page 275`

Catch tuplet events and generate appropriate bracket.

Music types accepted:

Section 1.2.74 [tuplet-span-event], page 48

Properties (read)

`tupletFullLength` (boolean)
: If set, the tuplet is printed up to the start of the next note.

`tupletFullLengthNote` (boolean)
: If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

This engraver creates the following layout object(s):

Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

`Section 2.2.128 [Tweak_engraver], page 275`
: Read the `tweaks` property from the originating event, and set properties.

2.1.17 NoteNames

A context for printing the names of notes.

This context creates the following layout object(s):

Section 3.1.75 [NoteName], page 352, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `nonstaff-nonstaff-spacing` in Section 3.1.130 [VerticalAxisGroup], page 399 to `'((basic-distance . 0) (minimum-distance . 2.8) (padding . 0.2) (stretchability . 0))`.
- Set grob-property `nonstaff-relatedstaff-spacing` in Section 3.1.130 [VerticalAxisGroup], page 399 to `'((basic-distance . 5.5) (padding . 0.5) (stretchability . 1))`.
- Set grob-property `nonstaff-unrelatedstaff-spacing padding` in Section 3.1.130 [VerticalAxisGroup], page 399 to `1.5`.
- Set grob-property `staff-affinity` in Section 3.1.130 [VerticalAxisGroup], page 399 to `1`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

`Section 2.2.5 [Axis_group_engraver], page 235`
: Group all objects created in this context in a `VerticalAxisGroup` spanner.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

`Section 2.2.74 [Note_name_engraver], page 259`
: Print pitches as words.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`printOctaveNames` (boolean)
: Print octave marks for the `NoteNames` context.

This engraver creates the following layout object(s):

Section 3.1.75 [NoteName], page 352.

Section 2.2.99 [Separating_line_group_engraver], page 266
: Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
: Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
: True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

Section 2.2.120 [Tie_engraver], page 272
: Generate ties between note heads of equal pitch.

Music types accepted:

Section 1.2.70 [tie-event], page 48

Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

2.1.18 PianoStaff

Just like `GrandStaff`, but the staves are only removed together, never separately.

This context also accepts commands for the following context(s):

GrandStaff.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.51 [InstrumentName], page 332, Section 3.1.98 [SpanBar], page 370, Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383 and Section 3.1.129 [VerticalAlignment], page 399.

This context sets the following properties:

- Set translator property `instrumentName` to `'()`.
- Set translator property `instrumentName` to `'()`.

- Set translator property `localKeySignature` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.
- Set translator property `systemStartDelimiter` to `'SystemStartBrace`.
- Set translator property `topLevelAlignment` to `#f`.
- Set translator property `topLevelAlignment` to `#f`.

Context PianoStaff can contain Section 2.1.2 [ChordNames], page 55, Section 2.1.5 [DrumStaff], page 70, Section 2.1.7 [Dynamics], page 88, Section 2.1.8 [FiguredBass], page 91, Section 2.1.14 [Lyrics], page 120, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164 and Section 2.1.23 [TabStaff], page 176.

This context is built from the following engraver(s):

Section 2.2.54 [Instrument_name_engraver], page 251
: Create a system start text for instrument or vocal names.

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  `instrumentName` (markup)
  : The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

  `shortInstrumentName` (markup)
  : See `instrumentName`.

  `shortVocalName` (markup)
  : Name of a vocal line, short version.

  `vocalName` (markup)
  : Name of a vocal line.

  This engraver creates the following layout object(s):

  Section 3.1.51 [InstrumentName], page 332.

Section 2.2.56 [Keep_alive_together_engraver], page 252
: This engraver collects all `Hara_kiri_group_spanner`s that are created in contexts at or below its own. These spanners are then tied together so that one will be removed only if all are removed. For example, if a `StaffGroup` uses this engraver, then the staves in the group will all be visible as long as there is a note in at least one of them.

Section 2.2.104 [Span_arpeggio_engraver], page 268
: Make arpeggios that span multiple staves.

  Properties (read)

  `connectArpeggios` (boolean)
  : If set, connect arpeggios across piano staff.

  This engraver creates the following layout object(s):

  Section 3.1.9 [Arpeggio], page 295.

Section 2.2.105 [Span_bar_engraver], page 268
: Make cross-staff bar lines: It catches all normal bar lines and draws a single span bar across them.

  This engraver creates the following layout object(s):

  Section 3.1.98 [SpanBar], page 370.

Section 2.2.113 [System_start_delimiter_engraver], page 270
: Create a system start delimiter (i.e., a `SystemStartBar`, `SystemStartBrace`, `SystemStartBracket` or `SystemStartSquare` spanner).

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  `systemStartDelimiter` (symbol)
  : Which grob to make for the start of the system/staff? Set to `SystemStartBrace`, `SystemStartBracket` or `SystemStartBar`.

  `systemStartDelimiterHierarchy` (pair)
  : A nested list, indicating the nesting of a start delimiters.

  This engraver creates the following layout object(s):

  Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382 and Section 3.1.113 [SystemStartSquare], page 383.

Section 2.2.130 [Vertical_align_engraver], page 276
: Catch groups (staves, lyrics lines, etc.) and stack them vertically.

  Properties (read)

  `alignAboveContext` (string)
  : Where to insert newly created context in vertical alignment.

  `alignBelowContext` (string)
  : Where to insert newly created context in vertical alignment.

  This engraver creates the following layout object(s):

  Section 3.1.129 [VerticalAlignment], page 399.

Section 2.2.130 [Vertical_align_engraver], page 276
: Catch groups (staves, lyrics lines, etc.) and stack them vertically.

  Properties (read)

  `alignAboveContext` (string)
  : Where to insert newly created context in vertical alignment.

  `alignBelowContext` (string)
  : Where to insert newly created context in vertical alignment.

This engraver creates the following layout object(s):

Section 3.1.129 [VerticalAlignment], page 399.

2.1.19 RhythmicStaff

A context like `Staff` but for printing rhythms. Pitches are ignored; the notes are printed on one line.

This context also accepts commands for the following context(s):

Staff.

This context creates the following layout object(s):

Section 3.1.11 [BarLine], page 297, Section 3.1.32 [DotColumn], page 314, Section 3.1.51 [InstrumentName], page 332, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.119 [TimeSignature], page 390 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `bar-extent` in Section 3.1.11 [BarLine], page 297 to `'(-2 . 2)`.
- Set grob-property `line-count` in Section 3.1.101 [StaffSymbol], page 372 to `1`.
- Set grob-property `neutral-direction` in Section 3.1.19 [Beam], page 302 to `1`.
- Set grob-property `neutral-direction` in Section 3.1.103 [Stem], page 374 to `1`.
- Set grob-property `staff-padding` in Section 3.1.132 [VoltaBracket], page 401 to `3`.
- Set translator property `createSpacing` to `#t`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `localKeySignature` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.
- Set translator property `squashedPosition` to `0`.

Context RhythmicStaff can contain Section 2.1.3 [CueVoice], page 57 and Section 2.1.27 [Voice], page 220.

This context is built from the following engraver(s):

Section 2.2.5 [Axis_group_engraver], page 235

Group all objects created in this context in a `VerticalAxisGroup` spanner.

Properties (read)

`currentCommandColumn` (graphical (layout) object)

Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.7 [Bar_engraver], page 236

Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

Properties (read)

`whichBar` (string)

This property is read to determine what type of bar line to create.

Example:

```
\set Staff.whichBar = "|:"
```

This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.11 [BarLine], page 297.

Section 2.2.26 [Dot_column_engraver], page 243

Engrave dots on dotted notes shifted to the right of the note. If omitted, then dots appear on top of the notes.

This engraver creates the following layout object(s):

Section 3.1.32 [DotColumn], page 314.

Section 2.2.40 [Font_size_engraver], page 247

Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

Section 2.2.54 [Instrument_name_engraver], page 251

Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
: See `instrumentName`.

`shortVocalName` (markup)
: Name of a vocal line, short version.

`vocalName` (markup)
: Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

Section 2.2.60 [Ledger_line_engraver], page 254

Create the spanner to draw ledger lines, and notices objects that need ledger lines.

This engraver creates the following layout object(s):

Section 3.1.57 [LedgerLineSpanner], page 337.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.88 [Pitch_squash_engraver], page 264
Set the vertical position of note heads to `squashedPosition`, if that property is set. This can be used to make a single-line staff demonstrating the rhythm of a melody.

Properties (read)

`squashedPosition` (integer)
Vertical position of squashing for Section "Pitch_squash_engraver" in *Internals Reference*.

Section 2.2.99 [Separating_line_group_engraver], page 266
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

Section 2.2.109 [Staff_symbol_engraver], page 269
Create the constellation of five (default) staff lines.

Music types accepted:

Section 1.2.62 [staff-span-event], page 46

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

Section 2.2.122 [Time_signature_engraver], page 273
Create a Section 3.1.119 [TimeSignature], page 390 whenever `timeSignatureFraction` changes.

Properties (read)

`implicitTimeSignatureVisibility` (vector)
break visibility for the default time signature.

`timeSignatureFraction` (pair of numbers)
A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

This engraver creates the following layout object(s):

Section 3.1.119 [TimeSignature], page 390.

2.1.20 Score

This is the top level notation context. No other context can contain a `Score` context. This context handles the administration of time signatures. It also makes sure that items such as clefs, time signatures, and key-signatures are aligned across staves.

You cannot explicitly instantiate a `Score` context (since it is not contained in any other context). It is instantiated automatically when an output definition (a `\score` or `\layout` block) is processed.

This context creates the following layout object(s):

Section 3.1.12 [BarNumber], page 298, Section 3.1.21 [BreakAlignGroup], page 304, Section 3.1.22 [BreakAlignment], page 305, Section 3.1.46 [GraceSpacing], page 328, Section 3.1.58 [LeftEdge], page 338, Section 3.1.67 [MetronomeMark], page 344, Section 3.1.71 [NonMusicalPaperColumn], page 349, Section 3.1.79 [PaperColumn], page 355, Section 3.1.80 [ParenthesesItem], page 356, Section 3.1.85 [RehearsalMark], page 360, Section 3.1.97 [SpacingSpanner], page 369, Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383, Section 3.1.129 [VerticalAlignment], page 399, Section 3.1.132 [VoltaBracket], page 401 and Section 3.1.133 [VoltaBracketSpanner], page 402.

This context sets the following properties:

- Set translator property `aDueText` to `"a2"`.
- Set translator property `autoAccidentals` to `'(Staff #<procedure #f (context pitch barnum measurepos)>)`.
- Set translator property `autoBeamCheck` to `default-auto-beam-check`.
- Set translator property `autoBeaming` to `#t`.
- Set translator property `autoCautionaries` to `'()`.
- Set translator property `automaticBars` to `#t`.
- Set translator property `barCheckSynchronize` to `#f`.
- Set translator property `barNumberVisibility` to `first-bar-number-invisible`.
- Set translator property `baseMoment` to `#<Mom 1/4>`.
- Set translator property `bassStaffProperties` to `'((assign clefGlyph clefs.F) (assign clefPosition 2) (assign middleCPosition 6) (assign middleCClefPosition 6))`.
- Set translator property `beamExceptions` to `'((end ((1 . 8) 4 4) ((1 . 12) 3 3 3 3)))`.
- Set translator property `beatStructure` to `'(1 1 1 1)`.
- Set translator property `chordNameExceptionsFull` to `'(((#<Pitch c' > #<Pitch e' > #<Pitch gis' >) (#<procedure line-markup (layout props args)> (+))) ((#<Pitch c' > #<Pitch ees' > #<Pitch ges' >) (#<procedure line-markup (layout props args)> ((#<procedure super-markup (layout props arg)> o)))) ((#<Pitch c' > #<Pitch ees' > #<Pitch ges' > #<Pitch bes' >) (#<procedure line-markup (layout props args)> ((#<procedure super-markup (layout props arg)>)))) ((#<Pitch c' > #<Pitch ees' > #<Pitch ges' > #<Pitch beses' >) (#<procedure line-markup (layout props args)> ((#<procedure super-markup (layout props arg)> o7)))))`.
- Set translator property `chordNameExceptionsPartial` to `'(((#<Pitch c' > #<Pitch d' >) (#<procedure line-markup (layout props args)> ((#<procedure normal-size-super-markup (layout props arg)> 2)))) ((#<Pitch c' > #<Pitch ees' >) (#<procedure line-markup (layout props args)> (m))) ((#<Pitch c' > #<Pitch f' >) (#<procedure line-markup (layout props args)> ((#<procedure normal-size-super-markup (layout props arg)> sus4)))) ((#<Pitch c' > #<Pitch`

g' >) (#<procedure line-markup (layout props args)> ((#<procedure normal-size-super-markup (layout props arg)> 5)))) ((#<Pitch c' > #<Pitch ees' > #<Pitch f' >) (#<procedure line-markup (layout props args)> (m)) (#<procedure line-markup (layout props args)> ((#<procedure normal-size-super-markup (layout props arg)> sus4)))) ((#<Pitch c' > #<Pitch d' > #<Pitch ees' >) (#<procedure line-markup (layout props args)> (m)) (#<procedure line-markup (layout props args)> ((#<procedure normal-size-super-markup (layout props arg)> sus2))))).

- Set translator property chordNameExceptions to '(((#<Pitch e' > #<Pitch gis' >) #<procedure line-markup (layout props args)> (+)) ((#<Pitch ees' > #<Pitch ges' >) #<procedure line-markup (layout props args)> ((#<procedure super-markup (layout props arg)> o))) ((#<Pitch ees' > #<Pitch ges' > #<Pitch bes' >) #<procedure line-markup (layout props args)> ((#<procedure super-markup (layout props arg)>))) ((#<Pitch ees' > #<Pitch ges' > #<Pitch beses' >) #<procedure line-markup (layout props args)> ((#<procedure super-markup (layout props arg)> o7)))).
- Set translator property chordNameFunction to ignatzek-chord-names.
- Set translator property chordNameLowercaseMinor to #f.
- Set translator property chordNameSeparator to '(#<procedure simple-markup (layout props str)> /).
- Set translator property chordNoteNamer to '().
- Set translator property chordPrefixSpacer to 0.
- Set translator property chordRootNamer to note-name->markup.
- Set translator property clefGlyph to "clefs.G".
- Set translator property clefPosition to -2.
- Set translator property crescendoSpanner to 'hairpin.
- Set translator property decrescendoSpanner to 'hairpin.
- Set translator property defaultBarType to "|".
- Set translator property doubleRepeatType to ":|:".
- Set translator property drumStyleTable to #<hash-table 29/61>.
- Set translator property explicitClefVisibility to #(#t #t #t).
- Set translator property explicitCueClefVisibility to #(#f #t #t).
- Set translator property explicitKeySignatureVisibility to #(#t #t #t).
- Set translator property extraNatural to #t.
- Set translator property figuredBassFormatter to format-bass-figure.
- Set translator property fingeringOrientations to '(up down).
- Set translator property firstClef to #t.
- Set translator property graceSettings to '((Voice Stem direction 1) (Voice Stem font-size -3) (Voice NoteHead font-size -3) (Voice TabNoteHead font-size -4) (Voice Dots font-size -3) (Voice Stem length-fraction 0.8) (Voice Stem no-stem-extend #t) (Voice Beam beam-thickness 0.384) (Voice Beam length-fraction 0.8) (Voice Accidental font-size -4) (Voice AccidentalCautionary font-size -4) (Voice Slur direction -1) (Voice Script font-size -3) (Voice Fingering font-size -8) (Voice StringNumber font-size -8)).
- Set translator property harmonicAccidentals to #t.
- Set translator property highStringOne to #t.
- Set translator property implicitTimeSignatureVisibility to #(#f #t #t).

- Set translator property instrumentTransposition to #<Pitch c' >.
- Set translator property keepAliveInterfaces to '(bass-figure-interface chord-name-interface cluster-beacon-interface fret-diagram-interface lyric-syllable-interface note-head-interface tab-note-head-interface lyric-interface percent-repeat-item-interface percent-repeat-interface stanza-number-interface).
- Set translator property keyAlterationOrder to '((6 . -1/2) (2 . -1/2) (5 . -1/2) (1 . -1/2) (4 . -1/2) (0 . -1/2) (3 . -1/2) (3 . 1/2) (0 . 1/2) (4 . 1/2) (1 . 1/2) (5 . 1/2) (2 . 1/2) (6 . 1/2) (6 . -1) (2 . -1) (5 . -1) (1 . -1) (4 . -1) (0 . -1) (3 . -1) (3 . 1) (0 . 1) (4 . 1) (1 . 1) (5 . 1) (2 . 1) (6 . 1)).
- Set translator property lyricMelismaAlignment to -1.
- Set translator property majorSevenSymbol to '(#<procedure line-markup (layout props args)> ((#<procedure triangle-markup (layout props filled)> #f))).
- Set translator property markFormatter to format-mark-letters.
- Set translator property measureLength to #<Mom 1>.
- Set translator property melismaBusyProperties to '(melismaBusy slurMelismaBusy tieMelismaBusy beamMelismaBusy completionBusy).
- Set translator property metronomeMarkFormatter to format-metronome-markup.
- Set translator property middleCClefPosition to -6.
- Set translator property middleCPosition to -6.
- Set translator property noChordSymbol to '(#<procedure simple-markup (layout props str)> N.C.).
- Set translator property noteToFretFunction to determine-frets.
- Set translator property partCombineTextsOnNote to #t.
- Set translator property pedalSostenutoStrings to '(Sost. Ped. *Sost. Ped. *).
- Set translator property pedalSostenutoStyle to 'mixed.
- Set translator property pedalSustainStrings to '(Ped. *Ped. *).
- Set translator property pedalSustainStyle to 'text.
- Set translator property pedalUnaCordaStrings to '(una corda tre corde).
- Set translator property pedalUnaCordaStyle to 'text.
- Set translator property predefinedDiagramTable to #f.
- Set translator property printKeyCancellation to #t.
- Set translator property printPartCombineTexts to #t.
- Set translator property quotedCueEventTypes to '(note-event rest-event tie-event beam-event tuplet-span-event).
- Set translator property quotedEventTypes to '(StreamEvent).
- Set translator property rehearsalMark to 1.
- Set translator property repeatCountVisibility to all-repeat-counts-visible.
- Set translator property scriptDefinitions to '((accent (avoid-slur . around) (padding . 0.2) (script-stencil feta sforzato . sforzato) (side-relative-direction . -1)) (accentus (script-stencil feta uaccentus . uaccentus) (side-relative-direction . -1) (avoid-slur . ignore) (padding . 0.2) (quantize-position . #t) (script-priority . -100) (direction . 1)) (circulus (script-stencil feta circulus . circulus) (side-relative-direction . -1) (avoid-slur . ignore) (padding . 0.2) (quantize-position . #t) (script-priority . -100) (direction . 1)) (coda (script-stencil feta coda . coda)

(padding . 0.2) (avoid-slur . outside) (direction . 1)) (comma (script-stencil feta lcomma . rcomma) (quantize-position . #t) (padding . 0.2) (avoid-slur . ignore) (direction . 1)) (downbow (script-stencil feta downbow . downbow) (padding . 0.2) (avoid-slur . around) (direction . 1) (script-priority . 150)) (downmordent (script-stencil feta downmordent . downmordent) (padding . 0.2) (avoid-slur . around) (direction . 1)) (downprall (script-stencil feta downprall . downprall) (padding . 0.2) (avoid-slur . around) (direction . 1)) (espressivo (avoid-slur . around) (padding . 0.2) (script-stencil feta espr . espr) (side-relative-direction . -1)) (fermata (script-stencil feta dfermata . ufermata) (padding . 0.2) (avoid-slur . around) (script-priority . 4000) (direction . 1)) (flageolet (script-stencil feta flageolet . flageolet) (padding . 0.2) (avoid-slur . around) (direction . 1)) (halfopen (avoid-slur . outside) (padding . 0.2) (script-stencil feta halfopen . halfopen) (direction . 1)) (ictus (script-stencil feta ictus . ictus) (side-relative-direction . -1) (quantize-position . #t) (avoid-slur . ignore) (padding . 0.2) (script-priority . -100) (direction . -1)) (lheel (script-stencil feta upedalheel . upedalheel) (padding . 0.2) (avoid-slur . around) (direction . -1)) (lineprall (script-stencil feta lineprall . lineprall) (padding . 0.2) (avoid-slur . around) (direction . 1)) (longfermata (script-stencil feta dlongfermata . ulongfermata) (padding . 0.2) (avoid-slur . around) (direction . 1)) (ltoe (script-stencil feta upedaltoe . upedaltoe) (padding . 0.2) (avoid-slur . around) (direction . -1)) (marcato (script-stencil feta dmarcato . umarcato) (padding . 0.2) (avoid-slur . inside) (quantize-position . #t) (side-relative-direction . -1)) (mordent (script-stencil feta mordent . mordent) (padding . 0.2) (avoid-slur . around) (direction . 1)) (open (avoid-slur . outside) (padding . 0.2) (script-stencil feta open . open) (direction . 1)) (portato (script-stencil feta uportato . dportato) (avoid-slur . around) (slur-padding . 0.3) (padding . 0.45) (side-relative-direction . -1)) (prall (script-stencil feta prall . prall) (padding . 0.2) (avoid-slur . around) (direction . 1)) (pralldown (script-stencil feta pralldown . pralldown) (padding . 0.2) (avoid-slur . around) (direction . 1)) (prallmordent (script-stencil feta prallmordent . prallmordent) (padding . 0.2) (avoid-slur . around) (direction . 1)) (prallprall (script-stencil feta prallprall . prallprall) (padding . 0.2) (avoid-slur . around) (direction . 1)) (prallup (script-stencil feta prallup . prallup) (padding . 0.2) (avoid-slur . around) (direction . 1)) (reverseturn (script-stencil feta reverseturn . reverseturn) (padding . 0.2) (avoid-slur . inside) (direction . 1)) (rheel (script-stencil feta dpedalheel . dpedalheel) (padding . 0.2) (avoid-slur . around) (direction . 1)) (rtoe (script-stencil feta dpedaltoe . dpedaltoe) (padding . 0.2) (avoid-slur . around) (direction . 1)) (segno (script-stencil feta segno . segno) (padding . 0.2) (avoid-slur . outside) (direction . 1)) (semicirculus (script-stencil feta dsemicirculus . dsemicirculus) (side-relative-direction . -1) (quantize-position . #t) (avoid-slur . ignore) (padding . 0.2) (script-priority . -100) (direction . 1)) (shortfermata (script-stencil feta dshortfermata . ushortfermata) (padding . 0.2) (avoid-slur . around) (direction . 1)) (signumcongruentiae (script-stencil feta dsignumcongruentiae . usignumcongruentiae) (padding . 0.2) (avoid-slur . outside) (direction . 1)) (snappizzicato (script-stencil feta snappizzicato . snappizzicato) (padding . 0.2) (avoid-slur . outside) (direction . 1)) (staccatissimo (avoid-slur . inside) (quantize-position . #t) (script-stencil feta dstaccatissimo . ustaccatissimo) (padding . 0.2) (side-relative-direction . -1)) (staccato (script-stencil feta staccato . staccato) (side-relative-direction . -1) (quantize-position . #t) (avoid-

slur . inside) (toward-stem-shift . 0.5) (padding . 0.2) (script-priority . -100)) (stopped (script-stencil feta stopped . stopped) (avoid-slur . inside) (padding . 0.2) (direction . 1)) (tenuto (script-stencil feta tenuto . tenuto) (quantize-position . #t) (avoid-slur . inside) (padding . 0.2) (side-relative-direction . -1)) (thumb (script-stencil feta thumb . thumb) (avoid-slur . around) (padding . 0.5) (direction . 1) (slur-padding . 0.2) (staff-padding . 0.5)) (trill (script-stencil feta trill . trill) (direction . 1) (padding . 0.2) (avoid-slur . outside) (script-priority . 2000)) (turn (script-stencil feta turn . turn) (avoid-slur . inside) (padding . 0.2) (direction . 1)) (upbow (script-stencil feta upbow . upbow) (avoid-slur . around) (padding . 0.2) (direction . 1) (script-priority . 150)) (upmordent (script-stencil feta upmordent . upmordent) (padding . 0.2) (avoid-slur . around) (direction . 1)) (upprall (script-stencil feta upprall . upprall) (padding . 0.2) (avoid-slur . around) (direction . 1)) (varcoda (script-stencil feta varcoda . varcoda) (padding . 0.2) (avoid-slur . outside) (direction . 1)) (varcomma (script-stencil feta lvarcomma . rvarcomma) (quantize-position . #t) (padding . 0.2) (avoid-slur . ignore) (direction . 1)) (verylongfermata (script-stencil feta dverylongfermata . uverylongfermata) (padding . 0.2) (avoid-slur . around) (direction . 1))).

- Set translator property `soloIIText` to `"Solo II"`.
- Set translator property `soloText` to `"Solo"`.
- Set translator property `stringNumberOrientations` to `'(up down)`.
- Set translator property `stringOneTopmost` to `#t`.
- Set translator property `stringTunings` to `'(#<Pitch e' > #<Pitch b > #<Pitch g > #<Pitch d > #<Pitch a, > #<Pitch e, >)`.
- Set translator property `strokeFingerOrientations` to `'(right)`.
- Set translator property `subdivideBeams` to `#f`.
- Set translator property `systemStartDelimiter` to `'SystemStartBar`.
- Set translator property `tablatureFormat` to `fret-number-tablature-format`.
- Set translator property `tabStaffLineLayoutFunction` to `tablature-position-on-lines`.
- Set translator property `tieWaitForNote` to `#f`.
- Set translator property `timeSignatureFraction` to `'(4 . 4)`.
- Set translator property `timeSignatureSettings` to `'(((2 . 2) (beamExceptions (end ((1 . 32) 8 8 8 8)))) ((3 . 2) (beamExceptions (end ((1 . 32) 8 8 8 8 8 8)))) ((3 . 4) (beamExceptions (end ((1 . 8) 6) ((1 . 12) 3 3 3)))) ((3 . 8) (beamExceptions (end ((1 . 8) 3)))) ((4 . 2) (beamExceptions (end ((1 . 16) 4 4 4 4 4 4 4 4)))) ((4 . 4) (beamExceptions (end ((1 . 8) 4 4) ((1 . 12) 3 3 3 3)))) ((4 . 8) (beatStructure 2 2)) ((6 . 4) (beamExceptions (end ((1 . 16) 4 4 4 4 4 4)))) ((9 . 4) (beamExceptions (end ((1 . 32) 8 8 8 8 8 8 8 8)))) ((12 . 4) (beamExceptions (end ((1 . 32) 8 8 8 8 8 8 8 8 8 8 8 8)))) ((5 . 8) (beatStructure 3 2)) ((8 . 8) (beatStructure 3 3 2))).`
- Set translator property `timing` to `#t`.
- Set translator property `topLevelAlignment` to `#t`.

Context Score can contain Section 2.1.1 [ChoirStaff], page 54, Section 2.1.2 [ChordNames], page 55, Section 2.1.4 [Devnull], page 70, Section 2.1.5 [DrumStaff], page 70, Section 2.1.8 [FiguredBass], page 91, Section 2.1.9 [FretBoards], page 93, Section 2.1.11 [GrandStaff], page 95, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.14 [Lyrics], page 120, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.17 [NoteNames], page 146, Section 2.1.18

[PianoStaff], page 147, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.22 [StaffGroup], page 174, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

This context is built from the following engraver(s):

Section 2.2.8 [Bar_number_engraver], page 236
: A bar number is created whenever `measurePosition` is zero and when there is a bar line (i.e., when `whichBar` is set). It is put on top of all staves, and appears only at the left side of the staff. The staves are taken from `stavesFound`, which is maintained by Section 2.2.107 [Staff_collecting_engraver], page 269.

  Properties (read)

  `barNumberVisibility` (procedure)
  : A Procedure that takes an integer and returns whether the corresponding bar number should be printed.

  `currentBarNumber` (integer)
  : Contains the current barnumber. This property is incremented at every bar line.

  `stavesFound` (list of grobs)
  : A list of all staff-symbols found.

  `whichBar` (string)
  : This property is read to determine what type of bar line to create.

    Example:

    ```
    \set Staff.whichBar = "|:"
    ```

    This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

  This engraver creates the following layout object(s):

  Section 3.1.12 [BarNumber], page 298.

Section 2.2.13 [Break_align_engraver], page 238
: Align grobs with corresponding `break-align-symbols` into groups, and order the groups according to `breakAlignOrder`. The left edge of the alignment gets a separate group, with a symbol `left-edge`.

  This engraver creates the following layout object(s):

  Section 3.1.21 [BreakAlignGroup], page 304, Section 3.1.22 [BreakAlignment], page 305 and Section 3.1.58 [LeftEdge], page 338.

Section 2.2.25 [Default_bar_line_engraver], page 242
: This engraver determines what kind of automatic bar lines should be produced, and sets `whichBar` accordingly. It should be at the same level as Section 2.2.124 [Timing_translator], page 274.

  Properties (read)

  `automaticBars` (boolean)
  : If set to false then bar lines will not be printed automatically; they must be explicitly created with a `\bar` command. Unlike the `\cadenzaOn`

keyword, measures are still counted. Bar line generation will resume according to that count if this property is unset.

`barAlways` (boolean)
: If set to true a bar line is drawn after each note.

`defaultBarType` (string)
: Set the default type of bar line. See `whichBar` for information on available bar types.

  This variable is read by Section "Timing_translator" in *Internals Reference* at Section "Score" in *Internals Reference* level.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

```
\set Staff.whichBar = "|:"
```

  This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`automaticBars` (boolean)
: If set to false then bar lines will not be printed automatically; they must be explicitly created with a `\bar` command. Unlike the `\cadenzaOn` keyword, measures are still counted. Bar line generation will resume according to that count if this property is unset.

Section 2.2.47 [Grace_spacing_engraver], page 250
: Bookkeeping of shortest starting and playing notes in grace note runs.

  Properties (read)

  `currentMusicalColumn` (graphical (layout) object)
  : Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

  This engraver creates the following layout object(s):

  Section 3.1.46 [GraceSpacing], page 328.

Section 2.2.64 [Mark_engraver], page 255
: Create `RehearsalMark` objects. It puts them on top of all staves (which is taken from the property `stavesFound`). If moving this engraver to

a different context, Section 2.2.107 [Staff_collecting_engraver], page 269 must move along, otherwise all marks end up on the same Y location.

Music types accepted:

Section 1.2.34 [mark-event], page 42

Properties (read)

`markFormatter` (procedure)
: A procedure taking as arguments the context and the rehearsal mark. It should return the formatted mark as a markup object.

`rehearsalMark` (integer)
: The last rehearsal mark printed.

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

This engraver creates the following layout object(s):

Section 3.1.85 [RehearsalMark], page 360.

`Section 2.2.68 [Metronome_mark_engraver], page 256`

Engrave metronome marking. This delegates the formatting work to the function in the `metronomeMarkFormatter` property. The mark is put over all staves. The staves are taken from the `stavesFound` property, which is maintained by Section 2.2.107 [Staff_collecting_engraver], page 269.

Music types accepted:

Section 1.2.67 [tempo-change-event], page 47

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`metronomeMarkFormatter` (procedure)
: How to produce a metronome markup. Called with two arguments: a `TempoChangeEvent` and context.

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

`tempoHideNote` (boolean)
: Hide the note = count in tempo marks.

This engraver creates the following layout object(s):

Section 3.1.67 [MetronomeMark], page 344.

`Section 2.2.78 [Output_property_engraver], page 260`

Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.80 [Paper_column_engraver], page 261

Take care of generating columns.

This engraver decides whether a column is breakable. The default is that a column is always breakable. However, every `Bar_engraver` that does not have a barline at a certain point will set `forbidBreaks` in the score context to stop line breaks. In practice, this means that you can make a break point by creating a bar line (assuming that there are no beams or notes that prevent a break point).

Music types accepted:

Section 1.2.11 [break-event], page 40 and Section 1.2.28 [label-event], page 42

Properties (read)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

Properties (write)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.71 [NonMusicalPaperColumn], page 349 and Section 3.1.79 [PaperColumn], page 355.

Section 2.2.81 [Parenthesis_engraver], page 261

Parenthesize objects whose music cause has the `parenthesize` property.

This engraver creates the following layout object(s):

Section 3.1.80 [ParenthesesItem], page 356.

Section 2.2.90 [Repeat_acknowledge_engraver], page 264

Acknowledge repeated music, and convert the contents of `repeatCommands` into an appropriate setting for `whichBar`.

Properties (read)

`doubleRepeatType` (string)
: Set the default bar line for double repeats.

`repeatCommands` (list)
: This property is a list of commands of the form `(list 'volta` *x*`)`, where *x* is a string or `#f`. `'end-repeat` is also accepted as a command.

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

```
\set Staff.whichBar = "|:"
```

This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Section 2.2.103 [Spacing_engraver], page 268

Make a `SpacingSpanner` and do bookkeeping of shortest starting and playing notes.

Music types accepted:

Section 1.2.59 [spacing-section-event], page 46

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`proportionalNotationDuration` (moment)
: Global override for shortest-playing duration. This is used for switching on proportional notation.

This engraver creates the following layout object(s):

Section 3.1.97 [SpacingSpanner], page 369.

Section 2.2.107 [Staff_collecting_engraver], page 269

Maintain the `stavesFound` variable.

Properties (read)

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

Properties (write)

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

Section 2.2.110 [Stanza_number_align_engraver], page 269

This engraver ensures that stanza numbers are neatly aligned.

Section 2.2.113 [System_start_delimiter_engraver], page 270

Create a system start delimiter (i.e., a `SystemStartBar`, `SystemStartBrace`, `SystemStartBracket` or `SystemStartSquare` spanner).

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`systemStartDelimiter` (symbol)
: Which grob to make for the start of the system/staff? Set to `SystemStartBrace`, `SystemStartBracket` or `SystemStartBar`.

`systemStartDelimiterHierarchy` (pair)
: A nested list, indicating the nesting of a start delimiters.

This engraver creates the following layout object(s):

Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382 and Section 3.1.113 [SystemStartSquare], page 383.

`Section 2.2.124 [Timing_translator], page 274`
: This engraver adds the alias `Timing` to its containing context. Responsible for synchronizing timing information from staves. Normally in `Score`. In order to create polyrhythmic music, this engraver should be removed from `Score` and placed in `Staff`.

Properties (read)

`currentBarNumber` (integer)
: Contains the current barnumber. This property is incremented at every bar line.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

Properties (write)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`currentBarNumber` (integer)
: Contains the current barnumber. This property is incremented at every bar line.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`timeSignatureFraction` (pair of numbers)
: A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

Section 2.2.130 [Vertical_align_engraver], page 276
: Catch groups (staves, lyrics lines, etc.) and stack them vertically.

Properties (read)

`alignAboveContext` (string)
: Where to insert newly created context in vertical alignment.

`alignBelowContext` (string)
: Where to insert newly created context in vertical alignment.

This engraver creates the following layout object(s):

Section 3.1.129 [VerticalAlignment], page 399.

Section 2.2.131 [Volta_engraver], page 276
: Make volta brackets.

Properties (read)

`repeatCommands` (list)
: This property is a list of commands of the form `(list 'volta` *x*`)`, where *x* is a string or `#f`. `'end-repeat` is also accepted as a command.

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

`voltaSpannerDuration` (moment)
: This specifies the maximum duration to use for the brackets printed for `\alternative`. This can be used to shrink the length of brackets in the situation where one alternative is very large.

This engraver creates the following layout object(s):

Section 3.1.132 [VoltaBracket], page 401 and Section 3.1.133 [VoltaBracketSpanner], page 402.

2.1.21 Staff

Handles clefs, bar lines, keys, accidentals. It can contain `Voice` contexts.

This context creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290, Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.11 [BarLine], page 297, Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation],

page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.32 [DotColumn], page 314, Section 3.1.51 [InstrumentName], page 332, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.72 [NoteCollision], page 350, Section 3.1.77 [OctavateEight], page 353, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.90 [RestCollision], page 364, Section 3.1.93 [ScriptRow], page 366, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.107 [SustainPedal], page 378, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.119 [TimeSignature], page 390, Section 3.1.126 [UnaCordaPedal], page 396, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set translator property `createSpacing` to `#t`.
- Set translator property `ignoreFiguredBassRest` to `#f`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `localKeySignature` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.

Context Staff can contain Section 2.1.3 [CueVoice], page 57 and Section 2.1.27 [Voice], page 220.

This context is built from the following engraver(s):

`Section 2.2.1 [Accidental_engraver], page 233`

Make accidentals. Catch note heads, ties and notices key-change events. This engraver usually lives at Staff level, but reads the settings for Accidental at `Voice` level, so you can `\override` them at `Voice`.

Properties (read)

`autoAccidentals` (list)

List of different ways to typeset an accidental.

For determining when to print an accidental, several different rules are tried. The rule that gives the highest number of accidentals is used.

Each entry in the list is either a symbol or a procedure.

symbol The symbol is the name of the context in which the following rules are to be applied. For example, if *context* is Section "Score" in *Internals Reference* then all staves share accidentals, and if *context* is Section "Staff" in *Internals Reference* then all voices in the same staff share accidentals, but staves do not.

procedure The procedure represents an accidental rule to be applied to the previously specified context.

The procedure takes the following arguments:

`context` The current context to which the rule should be applied.

`pitch` The pitch of the note to be evaluated.

`barnum` The current bar number.

`measurepos` The current measure position.

The procedure returns a pair of booleans. The first states whether an extra natural should be added. The second states whether an accidental should be printed. `(#t . #f)` does not make sense.

`autoCautionaries` (list)
: List similar to `autoAccidentals`, but it controls cautionary accidentals rather than normal ones. Both lists are tried, and the one giving the most accidentals wins. In case of draw, a normal accidental is typeset.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`harmonicAccidentals` (boolean)
: If set, harmonic notes in chords get accidentals.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step . alter`*`)` or `((`*`octave . step`*`) . `*`alter`*`)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((`*`octave . name`*`) . (`*`alter barnumber . measureposition`*`))` pairs.

Properties (write)

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`,

but can also contain `((`*`octave . name`*`) . (`*`alter barnumber . measureposition`*`))` pairs.

This engraver creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290 and Section 3.1.4 [AccidentalSuggestion], page 291.

Section 2.2.5 [Axis_group_engraver], page 235

Group all objects created in this context in a `VerticalAxisGroup` spanner.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.7 [Bar_engraver], page 236

Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

Properties (read)

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

  ```
  \set Staff.whichBar = "|:"
  ```

  This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.11 [BarLine], page 297.

Section 2.2.9 [Beam_collision_engraver], page 237

Help beams avoid colliding with notes and clefs in other voices.

Section 2.2.17 [Clef_engraver], page 239

Determine and set reference point for pitches.

Properties (read)

`clefGlyph` (string)
: Name of the symbol within the music font.

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`clefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitClefVisibility` (vector)
: '`break-visibility`' function for clef changes.

`forceClef` (boolean)
: Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

This engraver creates the following layout object(s):

Section 3.1.25 [Clef], page 307 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.19 [Collision_engraver], page 240
: Collect `NoteColumns`, and as soon as there are two or more, put them in a `NoteCollision` object.

This engraver creates the following layout object(s):

Section 3.1.72 [NoteCollision], page 350.

Section 2.2.23 [Cue_clef_engraver], page 241
: Determine and set reference point for pitches in cued voices.

Properties (read)

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefGlyph` (string)
: Name of the symbol within the music font.

`cueClefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitCueClefVisibility` (vector)
: '`break-visibility`' function for cue clef changes.

`middleCCuePosition` (number)
: The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

This engraver creates the following layout object(s):

Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.26 [Dot_column_engraver], page 243
: Engrave dots on dotted notes shifted to the right of the note. If omitted, then dots appear on top of the notes.

  This engraver creates the following layout object(s):

  Section 3.1.32 [DotColumn], page 314.

Section 2.2.37 [Figured_bass_engraver], page 246
: Make figured bass numbers.

  Music types accepted:

  Section 1.2.6 [bass-figure-event], page 40 and Section 1.2.51 [rest-event], page 45

  Properties (read)

  `figuredBassAlterationDirection` (direction)
  : Where to put alterations relative to the main figure.

  `figuredBassCenterContinuations` (boolean)
  : Whether to vertically center pairs of extender lines. This does not work with three or more lines.

  `figuredBassFormatter` (procedure)
  : A routine generating a markup for a bass figure.

  `ignoreFiguredBassRest` (boolean)
  : Don't swallow rest events.

  `implicitBassFigures` (list)
  : A list of bass figures that are not printed as numbers, but only as extender lines.

  `useBassFigureExtenders` (boolean)
  : Whether to use extender lines for repeated bass figures.

  This engraver creates the following layout object(s):

  Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301 and Section 3.1.18 [BassFigureLine], page 302.

Section 2.2.38 [Figured_bass_position_engraver], page 247
: Position figured bass alignments over notes.

  This engraver creates the following layout object(s):

  Section 3.1.15 [BassFigureAlignmentPositioning], page 300.

Section 2.2.40 [Font_size_engraver], page 247
: Put `fontSize` into `font-size` grob property.

  Properties (read)

  `fontSize` (number)
  : The relative size of all grobs in a context.

Section 2.2.50 [Grob_pq_engraver], page 250
: Administrate when certain grobs (e.g., note heads) stop playing.

  Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.54 [Instrument_name_engraver], page 251

Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
: See `instrumentName`.

`shortVocalName` (markup)
: Name of a vocal line, short version.

`vocalName` (markup)
: Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

Section 2.2.57 [Key_engraver], page 252

Engrave a key signature.

Music types accepted:

Section 1.2.27 [key-change-event], page 42

Properties (read)

`createKeyOnClefChange` (boolean)
: Print a key signature whenever the clef is changed.

`explicitKeySignatureVisibility` (vector)
: '`break-visibility`' function for explicit key changes. '`\override`' of the `break-visibility` property will set the visibility for normal (i.e., at the start of the line) key signatures.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`keyAlterationOrder` (list)
: An alist that defines in what order alterations should be printed. The format is `(step . alter)`, where *step* is a number from 0 to 6 and *alter* from -2 (sharp) to 2 (flat).

`keySignature` (list)
: The current key signature. This is an alist containing `(step . alter)` or `((octave . step) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`middleCClefPosition` (number)
: The position of the middle C, as determined only by the clef. This can be calculated by looking at `clefPosition` and `clefGlyph`.

`printKeyCancellation` (boolean)
: Print restoration alterations before a key signature change.

Properties (write)

`keySignature` (list)
: The current key signature. This is an alist containing `(step . alter)` or `((octave . step) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`tonic` (pitch)
: The tonic of the current scale.

This engraver creates the following layout object(s):

Section 3.1.53 [KeyCancellation], page 334 and Section 3.1.54 [KeySignature], page 335.

`Section 2.2.60 [Ledger_line_engraver], page 254`
: Create the spanner to draw ledger lines, and notices objects that need ledger lines.

This engraver creates the following layout object(s):

Section 3.1.57 [LedgerLineSpanner], page 337.

Section 2.2.77 [Ottava_spanner_engraver], page 260
Create a text spanner when the ottavation property changes.

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`middleCOffset` (number)
The offset of middle C from the position given by `middleCClefPosition` This is used for ottava brackets.

`ottavation` (markup)
If set, the text for an ottava spanner. Changing this creates a new text spanner.

This engraver creates the following layout object(s):

Section 3.1.78 [OttavaBracket], page 354.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.85 [Piano_pedal_align_engraver], page 263
Align piano pedal symbols and brackets.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.108 [SustainPedalLineSpanner], page 379 and Section 3.1.127 [UnaCordaPedalLineSpanner], page 397.

Section 2.2.86 [Piano_pedal_engraver], page 263
Engrave piano pedal symbols and brackets.

Music types accepted:

Section 1.2.58 [sostenuto-event], page 46, Section 1.2.66 [sustain-event], page 47 and Section 1.2.75 [una-corda-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`pedalSostenutoStrings` (list)
See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)
See `pedalSustainStyle`.

`pedalSustainStrings` (list)
: A list of strings to print for sustain-pedal. Format is `(up updown down)`, where each of the three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)
: A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)
: See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)
: See `pedalSustainStyle`.

This engraver creates the following layout object(s):

Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378 and Section 3.1.126 [UnaCordaPedal], page 396.

Section 2.2.92 [Rest_collision_engraver], page 265
Handle collisions of rests.

Properties (read)

`busyGrobs` (list)
: A queue of `(end-moment . GROB)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

This engraver creates the following layout object(s):

Section 3.1.90 [RestCollision], page 364.

Section 2.2.98 [Script_row_engraver], page 266
Determine order in horizontal side position elements.

This engraver creates the following layout object(s):

Section 3.1.93 [ScriptRow], page 366.

Section 2.2.99 [Separating_line_group_engraver], page 266
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
: Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
: True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

Section 2.2.107 [Staff_collecting_engraver], page 269
Maintain the `stavesFound` variable.

Properties (read)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Properties (write)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

`Section 2.2.109 [Staff_symbol_engraver], page 269`
Create the constellation of five (default) staff lines.

Music types accepted:

Section 1.2.62 [staff-span-event], page 46

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

`Section 2.2.122 [Time_signature_engraver], page 273`
Create a Section 3.1.119 [TimeSignature], page 390 whenever `timeSignatureFraction` changes.

Properties (read)

`implicitTimeSignatureVisibility` (vector)
break visibility for the default time signature.

`timeSignatureFraction` (pair of numbers)
A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

This engraver creates the following layout object(s):

Section 3.1.119 [TimeSignature], page 390.

2.1.22 StaffGroup

Groups staves while adding a bracket on the left side, grouping the staves together. The bar lines of the contained staves are connected vertically. `StaffGroup` only consists of a collection of staves, with a bracket in front and spanning bar lines.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.51 [InstrumentName], page 332, Section 3.1.98 [SpanBar], page 370, Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383 and Section 3.1.129 [VerticalAlignment], page 399.

This context sets the following properties:

- Set translator property `instrumentName` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.
- Set translator property `systemStartDelimiter` to `'SystemStartBracket`.
- Set translator property `topLevelAlignment` to `#f`.

Context StaffGroup can contain Section 2.1.1 [ChoirStaff], page 54, Section 2.1.2 [ChordNames], page 55, Section 2.1.5 [DrumStaff], page 70, Section 2.1.8 [FiguredBass], page 91, Section 2.1.11 [GrandStaff], page 95, Section 2.1.14 [Lyrics], page 120, Section 2.1.18 [PianoStaff], page 147, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.22 [StaffGroup], page 174 and Section 2.1.23 [TabStaff], page 176.

This context is built from the following engraver(s):

Section 2.2.54 [Instrument_name_engraver], page 251
Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
See `instrumentName`.

`shortVocalName` (markup)
Name of a vocal line, short version.

`vocalName` (markup)
Name of a vocal line.

This engraver creates the following layout object(s):
Section 3.1.51 [InstrumentName], page 332.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:
Section 1.2.3 [apply-output-event], page 39

Section 2.2.104 [Span_arpeggio_engraver], page 268
Make arpeggios that span multiple staves.

Properties (read)

`connectArpeggios` (boolean)
If set, connect arpeggios across piano staff.

This engraver creates the following layout object(s):
Section 3.1.9 [Arpeggio], page 295.

Section 2.2.105 [Span_bar_engraver], page 268
Make cross-staff bar lines: It catches all normal bar lines and draws a single span bar across them.

This engraver creates the following layout object(s):
Section 3.1.98 [SpanBar], page 370.

Section 2.2.113 [System_start_delimiter_engraver], page 270
Create a system start delimiter (i.e., a `SystemStartBar`, `SystemStartBrace`, `SystemStartBracket` or `SystemStartSquare` spanner).

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`systemStartDelimiter` (symbol)
: Which grob to make for the start of the system/staff? Set to `SystemStartBrace`, `SystemStartBracket` or `SystemStartBar`.

`systemStartDelimiterHierarchy` (pair)
: A nested list, indicating the nesting of a start delimiters.

This engraver creates the following layout object(s):

Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382 and Section 3.1.113 [SystemStartSquare], page 383.

`Section 2.2.130 [Vertical_align_engraver], page 276`
: Catch groups (staves, lyrics lines, etc.) and stack them vertically.

Properties (read)

`alignAboveContext` (string)
: Where to insert newly created context in vertical alignment.

`alignBelowContext` (string)
: Where to insert newly created context in vertical alignment.

This engraver creates the following layout object(s):

Section 3.1.129 [VerticalAlignment], page 399.

2.1.23 TabStaff

Context for generating tablature. It accepts only `TabVoice` contexts and handles the line spacing, the tablature clef etc. properly.

This context also accepts commands for the following context(s):

Staff.

This context creates the following layout object(s):

Section 3.1.11 [BarLine], page 297, Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.32 [DotColumn], page 314, Section 3.1.51 [InstrumentName], page 332, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.72 [NoteCollision], page 350, Section 3.1.77 [OctavateEight], page 353, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.90 [RestCollision], page 364, Section 3.1.93 [ScriptRow], page 366, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.107 [SustainPedal], page 378, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.119 [TimeSignature], page 390, Section 3.1.126 [UnaCordaPedal], page 396, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `avoid-note-head` in Section 3.1.103 [Stem], page 374 to `#t`.
- Set grob-property `ignore-collision` in Section 3.1.73 [NoteColumn], page 350 to `#t`.
- Set grob-property `staff-space` in Section 3.1.101 [StaffSymbol], page 372 to `1.5`.

- Set grob-property `stencil` in Section 3.1.9 [Arpeggio], page 295 to `#f`.
- Set grob-property `stencil` in Section 3.1.25 [Clef], page 307 to `clef::print-modern-tab-if-set`.
- Set grob-property `stencil` in Section 3.1.119 [TimeSignature], page 390 to `#f`.
- Set translator property `clefGlyph` to `"clefs.tab"`.
- Set translator property `clefPosition` to `0`.
- Set translator property `createSpacing` to `#t`.
- Set translator property `handleNegativeFrets` to `'recalculate`.
- Set translator property `ignoreFiguredBassRest` to `#f`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `localKeySignature` to `'()`.
- Set translator property `shortInstrumentName` to `'()`.

Context TabStaff can contain Section 2.1.3 [CueVoice], page 57 and Section 2.1.24 [TabVoice], page 183.

This context is built from the following engraver(s):

Section 2.2.5 [Axis_group_engraver], page 235
: Group all objects created in this context in a `VerticalAxisGroup` spanner.

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  This engraver creates the following layout object(s):

  Section 3.1.130 [VerticalAxisGroup], page 399.

Section 2.2.7 [Bar_engraver], page 236
: Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

  Properties (read)

  `whichBar` (string)
  : This property is read to determine what type of bar line to create.

    Example:

    ```
    \set Staff.whichBar = "|:"
    ```

    This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

  Properties (write)

  `forbidBreak` (boolean)
  : If set to `##t`, prevent a line break at this point.

  This engraver creates the following layout object(s):

  Section 3.1.11 [BarLine], page 297.

Section 2.2.9 [Beam_collision_engraver], page 237
: Help beams avoid colliding with notes and clefs in other voices.

Section 2.2.17 [Clef_engraver], page 239
Determine and set reference point for pitches.

Properties (read)

`clefGlyph` (string)
Name of the symbol within the music font.

`clefOctavation` (integer)
Add this much extra octavation. Values of 7 and -7 are common.

`clefPosition` (number)
Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitClefVisibility` (vector)
'`break-visibility`' function for clef changes.

`forceClef` (boolean)
Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

This engraver creates the following layout object(s):

Section 3.1.25 [Clef], page 307 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.19 [Collision_engraver], page 240
Collect `NoteColumns`, and as soon as there are two or more, put them in a `NoteCollision` object.

This engraver creates the following layout object(s):

Section 3.1.72 [NoteCollision], page 350.

Section 2.2.23 [Cue_clef_engraver], page 241
Determine and set reference point for pitches in cued voices.

Properties (read)

`clefOctavation` (integer)
Add this much extra octavation. Values of 7 and -7 are common.

`cueClefGlyph` (string)
Name of the symbol within the music font.

`cueClefOctavation` (integer)
Add this much extra octavation. Values of 7 and -7 are common.

`cueClefPosition` (number)
Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitCueClefVisibility` (vector)
'`break-visibility`' function for cue clef changes.

`middleCCuePosition` (number)
: The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

This engraver creates the following layout object(s):

Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312 and Section 3.1.77 [OctavateEight], page 353.

`Section 2.2.26 [Dot_column_engraver], page 243`
: Engrave dots on dotted notes shifted to the right of the note. If omitted, then dots appear on top of the notes.

This engraver creates the following layout object(s):

Section 3.1.32 [DotColumn], page 314.

`Section 2.2.37 [Figured_bass_engraver], page 246`
: Make figured bass numbers.

Music types accepted:

Section 1.2.6 [bass-figure-event], page 40 and Section 1.2.51 [rest-event], page 45

Properties (read)

`figuredBassAlterationDirection` (direction)
: Where to put alterations relative to the main figure.

`figuredBassCenterContinuations` (boolean)
: Whether to vertically center pairs of extender lines. This does not work with three or more lines.

`figuredBassFormatter` (procedure)
: A routine generating a markup for a bass figure.

`ignoreFiguredBassRest` (boolean)
: Don't swallow rest events.

`implicitBassFigures` (list)
: A list of bass figures that are not printed as numbers, but only as extender lines.

`useBassFigureExtenders` (boolean)
: Whether to use extender lines for repeated bass figures.

This engraver creates the following layout object(s):

Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301 and Section 3.1.18 [BassFigureLine], page 302.

`Section 2.2.38 [Figured_bass_position_engraver], page 247`
: Position figured bass alignments over notes.

This engraver creates the following layout object(s):

Section 3.1.15 [BassFigureAlignmentPositioning], page 300.

Section 2.2.40 [Font_size_engraver], page 247
Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
The relative size of all grobs in a context.

Section 2.2.50 [Grob_pq_engraver], page 250
Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.54 [Instrument_name_engraver], page 251
Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
See `instrumentName`.

`shortVocalName` (markup)
Name of a vocal line, short version.

`vocalName` (markup)
Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

Section 2.2.60 [Ledger_line_engraver], page 254
Create the spanner to draw ledger lines, and notices objects that need ledger lines.

This engraver creates the following layout object(s):

Section 3.1.57 [LedgerLineSpanner], page 337.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.85 [Piano_pedal_align_engraver], page 263
Align piano pedal symbols and brackets.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.108 [SustainPedalLineSpanner], page 379 and Section 3.1.127 [UnaCordaPedalLineSpanner], page 397.

Section 2.2.86 [Piano_pedal_engraver], page 263
Engrave piano pedal symbols and brackets.

Music types accepted:

Section 1.2.58 [sostenuto-event], page 46, Section 1.2.66 [sustain-event], page 47 and Section 1.2.75 [una-corda-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`pedalSostenutoStrings` (list)
See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)
See `pedalSustainStyle`.

`pedalSustainStrings` (list)
A list of strings to print for sustain-pedal. Format is `(up updown down)`, where each of the three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)
A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)
See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)
See `pedalSustainStyle`.

This engraver creates the following layout object(s):

Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378 and Section 3.1.126 [UnaCordaPedal], page 396.

Section 2.2.92 [Rest_collision_engraver], page 265
Handle collisions of rests.

Properties (read)

`busyGrobs` (list)
A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

This engraver creates the following layout object(s):

Section 3.1.90 [RestCollision], page 364.

Section 2.2.98 [Script_row_engraver], page 266
Determine order in horizontal side position elements.

This engraver creates the following layout object(s):

Section 3.1.93 [ScriptRow], page 366.

Section 2.2.99 [Separating_line_group_engraver], page 266
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

Section 2.2.107 [Staff_collecting_engraver], page 269
Maintain the `stavesFound` variable.

Properties (read)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Properties (write)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Section 2.2.109 [Staff_symbol_engraver], page 269
Create the constellation of five (default) staff lines.

Music types accepted:

Section 1.2.62 [staff-span-event], page 46

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

Section 2.2.115 [Tab_staff_symbol_engraver], page 271
Create a tablature staff symbol, but look at `stringTunings` for the number of lines.

Properties (read)

`stringTunings` (list)
: The tablature strings tuning. It is a list of the pitches of each string (starting with the lowest numbered one).

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

`Section 2.2.122 [Time_signature_engraver], page 273`
Create a Section 3.1.119 [TimeSignature], page 390 whenever `timeSignatureFraction` changes.

Properties (read)

`implicitTimeSignatureVisibility` (vector)
: break visibility for the default time signature.

`timeSignatureFraction` (pair of numbers)
: A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

This engraver creates the following layout object(s):

Section 3.1.119 [TimeSignature], page 390.

2.1.24 TabVoice

Context for drawing notes in a Tab staff.

This context also accepts commands for the following context(s):

Voice.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.23 [BreathingSign], page 306, Section 3.1.26 [ClusterSpanner], page 309, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.45 [Glissando], page 327, Section 3.1.49 [Hairpin], page 330, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.59 [LigatureBracket], page 339, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.73 [NoteColumn], page 350, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83 [PhrasingSlur], page 358, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.91 [Script], page 365, Section 3.1.92 [ScriptColumn], page 365, Section 3.1.94 [Slur], page 366, Section 3.1.103 [Stem], page 374, Section 3.1.104 [StemTremolo], page 375, Section 3.1.114 [TabNoteHead], page 384, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.125 [TupletNumber], page 396 and Section 3.1.131 [VoiceFollower], page 401.

This context sets the following properties:

- Set grob-property `after-line-breaking` in Section 3.1.87 [RepeatTie], page 362 to `repeat-tie::handle-tab-note-head`.
- Set grob-property `after-line-breaking` in Section 3.1.117 [Tie], page 388 to `tie::handle-tab-note-head`.
- Set grob-property `beam-thickness` in Section 3.1.19 [Beam], page 302 to `0.32`.
- Set grob-property `beam-thickness` in Section 3.1.104 [StemTremolo], page 375 to `0.32`.
- Set grob-property `beam-width` in Section 3.1.104 [StemTremolo], page 375 to `stem-tremolo::calc-tab-width`.
- Set grob-property `bound-details left` in Section 3.1.45 [Glissando], page 327 to `'((attach-dir . 1) (padding . 0.3))`.
- Set grob-property `bound-details right` in Section 3.1.45 [Glissando], page 327 to `'((attach-dir . -1) (padding . 0.3))`.
- Set grob-property `details` in Section 3.1.103 [Stem], page 374 to `'((lengths 0 0 0 0 0 0) (beamed-lengths 0 0 0) (beamed-minimum-free-lengths 0 0 0) (beamed-extreme-minimum-free-lengths 0 0) (stem-shorten 0 0))`.
- Set grob-property `extra-dy` in Section 3.1.45 [Glissando], page 327 to `glissando::calc-tab-extra-dy`.
- Set grob-property `flag-style` in Section 3.1.103 [Stem], page 374 to `'no-flag`.
- Set grob-property `glyph-name` in Section 3.1.114 [TabNoteHead], page 384 to `tab-note-head::calc-glyph-name`.
- Set grob-property `length-fraction` in Section 3.1.19 [Beam], page 302 to `0.62`.
- Set grob-property `length-fraction` in Section 3.1.104 [StemTremolo], page 375 to `#<procedure #f (grob)>`.
- Set grob-property `length` in Section 3.1.103 [Stem], page 374 to `0`.
- Set grob-property `no-stem-extend` in Section 3.1.103 [Stem], page 374 to `#t`.
- Set grob-property `stencil` in Section 3.1.19 [Beam], page 302 to `#f`.
- Set grob-property `stencil` in Section 3.1.33 [Dots], page 315 to `#f`.
- Set grob-property `stencil` in Section 3.1.39 [DynamicTextSpanner], page 321 to `#f`.
- Set grob-property `stencil` in Section 3.1.45 [Glissando], page 327 to `glissando::draw-tab-glissando`.
- Set grob-property `stencil` in Section 3.1.55 [LaissezVibrerTie], page 336 to `#f`.
- Set grob-property `stencil` in Section 3.1.68 [MultiMeasureRest], page 346 to `#f`.
- Set grob-property `stencil` in Section 3.1.83 [PhrasingSlur], page 358 to `#f`.
- Set grob-property `stencil` in Section 3.1.87 [RepeatTie], page 362 to `#f`.
- Set grob-property `stencil` in Section 3.1.89 [Rest], page 364 to `#f`.
- Set grob-property `stencil` in Section 3.1.91 [Script], page 365 to `#f`.
- Set grob-property `stencil` in Section 3.1.94 [Slur], page 366 to `slur::draw-tab-slur`.
- Set grob-property `stencil` in Section 3.1.104 [StemTremolo], page 375 to `#f`.
- Set grob-property `stencil` in Section 3.1.114 [TabNoteHead], page 384 to `tab-note-head::whiteout-if-style-set`.
- Set grob-property `stencil` in Section 3.1.115 [TextScript], page 385 to `#f`.
- Set grob-property `stencil` in Section 3.1.116 [TextSpanner], page 387 to `#f`.
- Set grob-property `stencil` in Section 3.1.117 [Tie], page 388 to `#f`.
- Set grob-property `stencil` in Section 3.1.124 [TupletBracket], page 395 to `#f`.

- Set grob-property `stencil` in Section 3.1.125 [TupletNumber], page 396 to `#f`.
- Set grob-property `transparent` in Section 3.1.38 [DynamicText], page 319 to `#t`.
- Set grob-property `transparent` in Section 3.1.49 [Hairpin], page 330 to `#t`.
- Set grob-property `transparent` in Section 3.1.69 [MultiMeasureRestNumber], page 347 to `#t`.
- Set grob-property `transparent` in Section 3.1.70 [MultiMeasureRestText], page 348 to `#t`.
- Set grob-property `transparent` in Section 3.1.103 [Stem], page 374 to `#t`.
- Set translator property `autoBeaming` to `#f`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.3 [Arpeggio_engraver], page 234
: Generate an Arpeggio symbol.

  Music types accepted:

  Section 1.2.4 [arpeggio-event], page 39

  This engraver creates the following layout object(s):

  Section 3.1.9 [Arpeggio], page 295.

Section 2.2.4 [Auto_beam_engraver], page 235
: Generate beams based on measure characteristics and observed Stems. Uses `baseMoment`, `beatStructure`, `beamExceptions`, `measureLength`, and `measurePosition` to decide when to start and stop a beam. Overriding beaming is done through Section 2.2.112 [Stem_engraver], page 270 properties `stemLeftBeamCount` and `stemRightBeamCount`.

  Music types accepted:

  Section 1.2.8 [beam-forbid-event], page 40

  Properties (read)

  `autoBeaming` (boolean)
  : If set to true then beams are generated automatically.

  `baseMoment` (moment)
  : Smallest unit of time that will stand on its own as a subdivided section.

  `beamExceptions` (list)
  : An alist of exceptions to autobeam rules that normally end on beats.

  `beatStructure` (list)
  : List of `baseMoments` that are combined to make beats.

  `subdivideBeams` (boolean)
  : If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

  This engraver creates the following layout object(s):

  Section 3.1.19 [Beam], page 302.

Section 2.2.10 [Beam_engraver], page 237
Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
Signal if a beam is present.

`beatStructure` (list)
List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

Properties (write)

`forbidBreak` (boolean)
If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.12 [Bend_engraver], page 238
Create fall spanners.

Music types accepted:

Section 1.2.9 [bend-after-event], page 40

This engraver creates the following layout object(s):

Section 3.1.20 [BendAfter], page 304.

Section 2.2.14 [Breathing_sign_engraver], page 238
Create a breathing sign.

Music types accepted:

Section 1.2.13 [breathing-event], page 40

This engraver creates the following layout object(s):

Section 3.1.23 [BreathingSign], page 306.

Section 2.2.16 [Chord_tremolo_engraver], page 239
Generate beams for tremolo repeats.

Music types accepted:

Section 1.2.72 [tremolo-span-event], page 48

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.18 [Cluster_spanner_engraver], page 240
Engrave a cluster using `Spanner` notation.

Music types accepted:

Section 1.2.14 [cluster-note-event], page 40

This engraver creates the following layout object(s):

Section 3.1.26 [ClusterSpanner], page 309 and Section 3.1.27 [ClusterSpannerBeacon], page 309.

`Section 2.2.27 [Dots_engraver], page 243`

Create Section 3.1.33 [Dots], page 315 objects for Section 3.2.87 [rhythmic-head-interface], page 447s.

This engraver creates the following layout object(s):

Section 3.1.33 [Dots], page 315.

`Section 2.2.28 [Double_percent_repeat_engraver], page 243`

Make double measure repeats.

Music types accepted:

Section 1.2.18 [double-percent-event], page 41

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`measureLength` (moment)
: Length of one measure in the current time signature.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.34 [DoublePercentRepeat], page 315 and Section 3.1.35 [DoublePercentRepeatCounter], page 316.

`Section 2.2.31 [Dynamic_align_engraver], page 244`

Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

`Section 2.2.40 [Font_size_engraver], page 247`

Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

Section 2.2.41 [Footnote_engraver], page 247
: Create footnote texts.

Music types accepted:

Section 1.2.23 [footnote-event], page 41

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

Section 2.2.42 [Forbid_line_break_engraver], page 248
: Forbid line breaks when note heads are still playing at some point.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

Section 2.2.44 [Glissando_engraver], page 249
: Engrave glissandi.

Music types accepted:

Section 1.2.24 [glissando-event], page 41

Properties (read)

`glissandoMap` (list)
: A map in the form of '((source1 . target1) (source2 . target2) (sourcen . targetn)) showing the glissandi to be drawn for note columns. The value '() will default to '((0 . 0) (1 . 1) (n . n)), where n is the minimal number of noteheads in the two note columns between which the glissandi occur.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327.

Section 2.2.45 [Grace_beam_engraver], page 249
: Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams. Only engraves beams when we are at grace points in time.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.46 [Grace_engraver], page 250`

Set font size and other properties for grace notes.

Properties (read)

`graceSettings` (list)
: Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

`Section 2.2.50 [Grob_pq_engraver], page 250`

Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

`Section 2.2.55 [Instrument_switch_engraver], page 252`

Create a cue text for taking instrument.

Properties (read)

`instrumentCueName` (markup)
: The name to print if another instrument is to be taken.

This engraver creates the following layout object(s):

Section 3.1.52 [InstrumentSwitch], page 333.

Section 2.2.59 [Laissez_vibrer_engraver], page 254
: Create laissez vibrer items.

  Music types accepted:

  Section 1.2.29 [laissez-vibrer-event], page 42

  This engraver creates the following layout object(s):

  Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.56 [LaissezVibrerTieColumn], page 337.

Section 2.2.61 [Ligature_bracket_engraver], page 254
: Handle `Ligature_events` by engraving `Ligature` brackets.

  Music types accepted:

  Section 1.2.31 [ligature-event], page 42

  This engraver creates the following layout object(s):

  Section 3.1.59 [LigatureBracket], page 339.

Section 2.2.69 [Multi_measure_rest_engraver], page 257
: Engrave multi-measure rests that are produced with 'R'. It reads `measurePosition` and `internalBarNumber` to determine what number to print over the Section 3.1.68 [MultiMeasureRest], page 346. Reads `measureLength` to determine whether it should use a whole rest or a breve rest to represent one measure.

  Music types accepted:

  Section 1.2.36 [multi-measure-rest-event], page 43 and Section 1.2.37 [multi-measure-text-event], page 43

  Properties (read)

  `currentCommandColumn` (graphical (layout) object)
  : Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

  `internalBarNumber` (integer)
  : Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

  `measureLength` (moment)
  : Length of one measure in the current time signature.

  `measurePosition` (moment)
  : How much of the current measure have we had. This can be set manually to create incomplete measures.

  `restNumberThreshold` (number)
  : If a multimeasure rest has more measures than this, a number is printed.

  This engraver creates the following layout object(s):

  Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

Section 2.2.70 [New_dynamic_engraver], page 257
Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

Section 2.2.72 [Note_head_line_engraver], page 258
Engrave a line between two note heads, for example a glissando. If `followVoice` is set, staff switches also generate a line.

Properties (read)

`followVoice` (boolean)
If set, note heads are tracked across staff switches by a thin line.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327 and Section 3.1.131 [VoiceFollower], page 401.

Section 2.2.76 [Note_spacing_engraver], page 259
Generate `NoteSpacing`, an object linking horizontal lines for use in spacing.

This engraver creates the following layout object(s):

Section 3.1.76 [NoteSpacing], page 352.

Section 2.2.78 [Output_property_engraver], page 260
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.82 [Part_combine_engraver], page 261

Part combine engraver for orchestral scores: Print markings 'a2', 'Solo', 'Solo II', and 'unisono'.

Music types accepted:

Section 1.2.39 [note-event], page 43 and Section 1.2.43 [part-combine-event], page 44

Properties (read)

`aDueText` (markup)
: Text to print at a unisono passage.

`partCombineTextsOnNote` (boolean)
: Print part-combine texts only on the next note rather than immediately on rests or skips.

`printPartCombineTexts` (boolean)
: Set 'Solo' and 'A due' texts in the part combiner?

`soloIIText` (markup)
: The text for the start of a solo for voice 'two' when part-combining.

`soloText` (markup)
: The text for the start of a solo when part-combining.

This engraver creates the following layout object(s):

Section 3.1.28 [CombineTextScript], page 309.

Section 2.2.83 [Percent_repeat_engraver], page 262

Make whole measure repeats.

Music types accepted:

Section 1.2.46 [percent-event], page 44

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

This engraver creates the following layout object(s):

Section 3.1.81 [PercentRepeat], page 356 and Section 3.1.82 [PercentRepeatCounter], page 357.

Section 2.2.84 [Phrasing_slur_engraver], page 262
: Print phrasing slurs. Similar to Section 2.2.101 [Slur_engraver], page 267.

  Music types accepted:

  Section 1.2.48 [phrasing-slur-event], page 45

  This engraver creates the following layout object(s):

  Section 3.1.83 [PhrasingSlur], page 358.

Section 2.2.89 [Pitched_trill_engraver], page 264
: Print the bracketed note head after a note head with trill.

  This engraver creates the following layout object(s):

  Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392 and Section 3.1.122 [TrillPitchHead], page 393.

Section 2.2.91 [Repeat_tie_engraver], page 265
: Create repeat ties.

  Music types accepted:

  Section 1.2.50 [repeat-tie-event], page 45

  This engraver creates the following layout object(s):

  Section 3.1.87 [RepeatTie], page 362 and Section 3.1.88 [RepeatTieColumn], page 363.

Section 2.2.93 [Rest_engraver], page 265
: Engrave rests.

  Music types accepted:

  Section 1.2.51 [rest-event], page 45

  Properties (read)

  `middleCPosition` (number)
  : The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

  This engraver creates the following layout object(s):

  Section 3.1.89 [Rest], page 364.

Section 2.2.94 [Rhythmic_column_engraver], page 265
: Generate `NoteColumn`, an object that groups stems, note heads, and rests.

  This engraver creates the following layout object(s):

  Section 3.1.73 [NoteColumn], page 350.

Section 2.2.96 [Script_column_engraver], page 266
: Find potentially colliding scripts and put them into a `ScriptColumn` object; that will fix the collisions.

  This engraver creates the following layout object(s):

  Section 3.1.92 [ScriptColumn], page 365.

Section 2.2.97 [Script_engraver], page 266
: Handle note scripted articulations.

  Music types accepted:

  Section 1.2.5 [articulation-event], page 40

  Properties (read)

`scriptDefinitions` (list)
: The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

This engraver creates the following layout object(s):

Section 3.1.91 [Script], page 365.

`Section 2.2.100 [Slash_repeat_engraver], page 267`
: Make beat repeats.

Music types accepted:

Section 1.2.49 [repeat-slash-event], page 45

This engraver creates the following layout object(s):

Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

`Section 2.2.101 [Slur_engraver], page 267`
: Build slur grobs from slur events.

Music types accepted:

Section 1.2.55 [slur-event], page 45

Properties (read)

`doubleSlurs` (boolean)
: If set, two slurs are created for every slurred note, one above and one below the chord.

`slurMelismaBusy` (boolean)
: Signal if a slur is present.

This engraver creates the following layout object(s):

Section 3.1.94 [Slur], page 366.

`Section 2.2.106 [Spanner_break_forbid_engraver], page 268`
: Forbid breaks in certain spanners.

`Section 2.2.112 [Stem_engraver], page 270`
: Create stems and single-stem tremolos. It also works together with the beam engraver for overriding beaming.

Music types accepted:

Section 1.2.71 [tremolo-event], page 48

Properties (read)

`stemLeftBeamCount` (integer)
: Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.

`stemRightBeamCount` (integer)
: See `stemLeftBeamCount`.

`tremoloFlags` (integer)
: The number of tremolo flags to add if no number is specified.

This engraver creates the following layout object(s):

Section 3.1.103 [Stem], page 374 and Section 3.1.104 [StemTremolo], page 375.

`Section 2.2.114 [Tab_note_heads_engraver], page 270`

Generate one or more tablature note heads from event of type `NoteEvent`.

Music types accepted:

Section 1.2.22 [fingering-event], page 41, Section 1.2.39 [note-event], page 43 and Section 1.2.64 [string-number-event], page 47

Properties (read)

`defaultStrings` (list)
: A list of strings to use in calculating frets for tablatures and fretboards if no strings are provided in the notes for the current moment.

`fretLabels` (list)
: A list of strings or Scheme-formatted markups containing, in the correct order, the labels to be used for lettered frets in tablature.

`highStringOne` (boolean)
: Whether the first string is the string with highest pitch on the instrument. This used by the automatic string selector for tablature notation.

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`minimumFret` (number)
: The tablature auto string-selecting mechanism selects the highest string with a fret at least `minimumFret`.

`noteToFretFunction` (procedure)
: Convert list of notes and list of defined strings to full list of strings and fret numbers. Parameters: The context, a list of note events, a list of tabstring events, and the fretboard grob if a fretboard is desired.

`stringOneTopmost` (boolean)
: Whether the first string is printed on the top line of the tablature.

`stringTunings` (list)
: The tablature strings tuning. It is a list of the pitches of each string (starting with the lowest numbered one).

`tablatureFormat` (procedure)
: A function formatting a tablature note head. Called with three arguments: context, string number and, fret number. It returns the text as a markup.

`tabStaffLineLayoutFunction` (procedure)
: A function determining the staff position of a tablature note head. Called with two arguments: the context and the string.

This engraver creates the following layout object(s):

Section 3.1.114 [TabNoteHead], page 384.

Section 2.2.116 [Tab_tie_follow_engraver], page 272
: Adjust TabNoteHead properties when a tie is followed by a slur or glissando.

Section 2.2.118 [Text_engraver], page 272
: Create text scripts.

Music types accepted:

Section 1.2.68 [text-script-event], page 47

This engraver creates the following layout object(s):

Section 3.1.115 [TextScript], page 385.

Section 2.2.119 [Text_spanner_engraver], page 272
: Create text spanner from an event.

Music types accepted:

Section 1.2.69 [text-span-event], page 48

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.116 [TextSpanner], page 387.

Section 2.2.120 [Tie_engraver], page 272
: Generate ties between note heads of equal pitch.

Music types accepted:

Section 1.2.70 [tie-event], page 48

Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

Section 2.2.126 [Trill_spanner_engraver], page 274
: Create trill spanner from an event.

Music types accepted:

Section 1.2.73 [trill-span-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.123 [TrillSpanner], page 393.

`Section 2.2.127 [Tuplet_engraver], page 275`

Catch tuplet events and generate appropriate bracket.

Music types accepted:

Section 1.2.74 [tuplet-span-event], page 48

Properties (read)

`tupletFullLength` (boolean)
: If set, the tuplet is printed up to the start of the next note.

`tupletFullLengthNote` (boolean)
: If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

This engraver creates the following layout object(s):

Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

`Section 2.2.128 [Tweak_engraver], page 275`

Read the `tweaks` property from the originating event, and set properties.

2.1.25 VaticanaStaff

Same as `Staff` context, except that it is accommodated for typesetting Gregorian Chant in the notational style of Editio Vaticana.

This context also accepts commands for the following context(s):

Staff.

This context creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290, Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.11 [BarLine], page 297, Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.31 [Custos], page 313, Section 3.1.32 [DotColumn], page 314, Section 3.1.51 [InstrumentName], page 332, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.72 [NoteCollision],

page 350, Section 3.1.77 [OctavateEight], page 353, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.90 [RestCollision], page 364, Section 3.1.93 [ScriptRow], page 366, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.107 [SustainPedal], page 378, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.126 [UnaCordaPedal], page 396, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397 and Section 3.1.130 [VerticalAxisGroup], page 399.

This context sets the following properties:

- Set grob-property `glyph-name-alist` in Section 3.1.1 [Accidental], page 289 to `'((-1/2 . accidentals.vaticanaM1) (0 . accidentals.vaticana0) (1/2 . accidentals.mensural1))`.
- Set grob-property `glyph-name-alist` in Section 3.1.54 [KeySignature], page 335 to `'((-1/2 . accidentals.vaticanaM1) (0 . accidentals.vaticana0) (1/2 . accidentals.mensural1))`.
- Set grob-property `line-count` in Section 3.1.101 [StaffSymbol], page 372 to `4`.
- Set grob-property `neutral-direction` in Section 3.1.31 [Custos], page 313 to `-1`.
- Set grob-property `neutral-position` in Section 3.1.31 [Custos], page 313 to `3`.
- Set grob-property `style` in Section 3.1.31 [Custos], page 313 to `'vaticana`.
- Set grob-property `style` in Section 3.1.33 [Dots], page 315 to `'vaticana`.
- Set grob-property `thickness` in Section 3.1.101 [StaffSymbol], page 372 to `0.6`.
- Set grob-property `transparent` in Section 3.1.11 [BarLine], page 297 to `#t`.
- Set translator property `clefGlyph` to `"clefs.vaticana.do"`.
- Set translator property `clefOctavation` to `0`.
- Set translator property `clefPosition` to `1`.
- Set translator property `createSpacing` to `#t`.
- Set translator property `ignoreFiguredBassRest` to `#f`.
- Set translator property `instrumentName` to `'()`.
- Set translator property `localKeySignature` to `'()`.
- Set translator property `middleCClefPosition` to `1`.
- Set translator property `middleCPosition` to `1`.
- Set translator property `shortInstrumentName` to `'()`.

Context VaticanaStaff can contain Section 2.1.3 [CueVoice], page 57 and Section 2.1.26 [VaticanaVoice], page 207.

This context is built from the following engraver(s):

Section 2.2.1 [Accidental_engraver], page 233

Make accidentals. Catch note heads, ties and notices key-change events. This engraver usually lives at Staff level, but reads the settings for Accidental at `Voice` level, so you can `\override` them at `Voice`.

Properties (read)

`autoAccidentals` (list)

List of different ways to typeset an accidental.

For determining when to print an accidental, several different rules are tried. The rule that gives the highest number of accidentals is used.

Each entry in the list is either a symbol or a procedure.

symbol The symbol is the name of the context in which the following rules are to be applied. For example, if *context* is Section "Score" in *Internals Reference* then all staves share accidentals, and if *context* is Section "Staff" in *Internals Reference* then all voices in the same staff share accidentals, but staves do not.

procedure The procedure represents an accidental rule to be applied to the previously specified context.

The procedure takes the following arguments:

`context` The current context to which the rule should be applied.

`pitch` The pitch of the note to be evaluated.

`barnum` The current bar number.

`measurepos` The current measure position.

The procedure returns a pair of booleans. The first states whether an extra natural should be added. The second states whether an accidental should be printed. `(#t . #f)` does not make sense.

`autoCautionaries` (list)
List similar to `autoAccidentals`, but it controls cautionary accidentals rather than normal ones. Both lists are tried, and the one giving the most accidentals wins. In case of draw, a normal accidental is typeset.

`extraNatural` (boolean)
Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`harmonicAccidentals` (boolean)
If set, harmonic notes in chords get accidentals.

`internalBarNumber` (integer)
Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step`*` . `*`alter`*`)` or `((`*`octave`*` . `*`step`*`) . `*`alter`*`)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((`*`octave`*` . `*`name`*`) . (`*`alter barnumber`*` . `*`measureposition`*`))` pairs.

Properties (write)

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((`*`octave`*` . `*`name`*`) . (`*`alter barnumber`*` . `*`measureposition`*`))` pairs.

This engraver creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290 and Section 3.1.4 [AccidentalSuggestion], page 291.

`Section 2.2.5 [Axis_group_engraver], page 235`
Group all objects created in this context in a `VerticalAxisGroup` spanner.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

`Section 2.2.7 [Bar_engraver], page 236`
Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

Properties (read)

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

```
\set Staff.whichBar = "|:"
```

  This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.11 [BarLine], page 297.

Section 2.2.9 [Beam_collision_engraver], page 237
: Help beams avoid colliding with notes and clefs in other voices.

Section 2.2.17 [Clef_engraver], page 239
: Determine and set reference point for pitches.

Properties (read)

`clefGlyph` (string)
: Name of the symbol within the music font.

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`clefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitClefVisibility` (vector)
: '`break-visibility`' function for clef changes.

`forceClef` (boolean)
: Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

This engraver creates the following layout object(s):

Section 3.1.25 [Clef], page 307 and Section 3.1.77 [OctavateEight], page 353.

Section 2.2.19 [Collision_engraver], page 240
: Collect `NoteColumns`, and as soon as there are two or more, put them in a `NoteCollision` object.

This engraver creates the following layout object(s):

Section 3.1.72 [NoteCollision], page 350.

Section 2.2.23 [Cue_clef_engraver], page 241
: Determine and set reference point for pitches in cued voices.

Properties (read)

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefGlyph` (string)
: Name of the symbol within the music font.

`cueClefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitCueClefVisibility` (vector)
: '`break-visibility`' function for cue clef changes.

`middleCCuePosition` (number)
: The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

This engraver creates the following layout object(s):

Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312 and Section 3.1.77 [OctavateEight], page 353.

`Section 2.2.24 [Custos_engraver], page 242`
Engrave custodes.

This engraver creates the following layout object(s):

Section 3.1.31 [Custos], page 313.

`Section 2.2.26 [Dot_column_engraver], page 243`
Engrave dots on dotted notes shifted to the right of the note. If omitted, then dots appear on top of the notes.

This engraver creates the following layout object(s):

Section 3.1.32 [DotColumn], page 314.

`Section 2.2.37 [Figured_bass_engraver], page 246`
Make figured bass numbers.

Music types accepted:

Section 1.2.6 [bass-figure-event], page 40 and Section 1.2.51 [rest-event], page 45

Properties (read)

`figuredBassAlterationDirection` (direction)
: Where to put alterations relative to the main figure.

`figuredBassCenterContinuations` (boolean)
: Whether to vertically center pairs of extender lines. This does not work with three or more lines.

`figuredBassFormatter` (procedure)
: A routine generating a markup for a bass figure.

`ignoreFiguredBassRest` (boolean)
: Don't swallow rest events.

`implicitBassFigures` (list)
: A list of bass figures that are not printed as numbers, but only as extender lines.

`useBassFigureExtenders` (boolean)
: Whether to use extender lines for repeated bass figures.

This engraver creates the following layout object(s):

Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301 and Section 3.1.18 [BassFigureLine], page 302.

`Section 2.2.38 [Figured_bass_position_engraver], page 247`
: Position figured bass alignments over notes.

This engraver creates the following layout object(s):

Section 3.1.15 [BassFigureAlignmentPositioning], page 300.

`Section 2.2.40 [Font_size_engraver], page 247`
: Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

`Section 2.2.50 [Grob_pq_engraver], page 250`
: Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

`Section 2.2.54 [Instrument_name_engraver], page 251`
: Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
: See `instrumentName`.

`shortVocalName` (markup)
: Name of a vocal line, short version.

`vocalName` (markup)
: Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

`Section 2.2.57 [Key_engraver], page 252`

Engrave a key signature.

Music types accepted:

Section 1.2.27 [key-change-event], page 42

Properties (read)

`createKeyOnClefChange` (boolean)
: Print a key signature whenever the clef is changed.

`explicitKeySignatureVisibility` (vector)
: '`break-visibility`' function for explicit key changes. '`\override`' of the `break-visibility` property will set the visibility for normal (i.e., at the start of the line) key signatures.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`keyAlterationOrder` (list)
: An alist that defines in what order alterations should be printed. The format is `(`*`step . alter`*`)`, where *step* is a number from 0 to 6 and *alter* from -2 (sharp) to 2 (flat).

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step . alter`*`)` or `((`*`octave . step`*`) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`middleCClefPosition` (number)
: The position of the middle C, as determined only by the clef. This can be calculated by looking at `clefPosition` and `clefGlyph`.

`printKeyCancellation` (boolean)
: Print restoration alterations before a key signature change.

Properties (write)

`keySignature` (list)
: The current key signature. This is an alist containing `(step . alter)` or `((octave . step) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`tonic` (pitch)
: The tonic of the current scale.

This engraver creates the following layout object(s):

Section 3.1.53 [KeyCancellation], page 334 and Section 3.1.54 [KeySignature], page 335.

`Section 2.2.60 [Ledger_line_engraver], page 254`
Create the spanner to draw ledger lines, and notices objects that need ledger lines.

This engraver creates the following layout object(s):

Section 3.1.57 [LedgerLineSpanner], page 337.

`Section 2.2.77 [Ottava_spanner_engraver], page 260`
Create a text spanner when the ottavation property changes.

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`middleCOffset` (number)
: The offset of middle C from the position given by `middleCClefPosition` This is used for ottava brackets.

`ottavation` (markup)
: If set, the text for an ottava spanner. Changing this creates a new text spanner.

This engraver creates the following layout object(s):

Section 3.1.78 [OttavaBracket], page 354.

`Section 2.2.78 [Output_property_engraver], page 260`
Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

`Section 2.2.85 [Piano_pedal_align_engraver], page 263`
Align piano pedal symbols and brackets.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.108 [SustainPedalLineSpanner], page 379 and Section 3.1.127 [UnaCordaPedalLineSpanner], page 397.

Section 2.2.86 [Piano_pedal_engraver], page 263
Engrave piano pedal symbols and brackets.

Music types accepted:

Section 1.2.58 [sostenuto-event], page 46, Section 1.2.66 [sustain-event], page 47 and Section 1.2.75 [una-corda-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`pedalSostenutoStrings` (list)
: See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)
: See `pedalSustainStyle`.

`pedalSustainStrings` (list)
: A list of strings to print for sustain-pedal. Format is `(up updown down)`, where each of the three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)
: A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)
: See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)
: See `pedalSustainStyle`.

This engraver creates the following layout object(s):

Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378 and Section 3.1.126 [UnaCordaPedal], page 396.

Section 2.2.92 [Rest_collision_engraver], page 265
Handle collisions of rests.

Properties (read)

`busyGrobs` (list)
: A queue of `(end-moment . GROB)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

This engraver creates the following layout object(s):

Section 3.1.90 [RestCollision], page 364.

Section 2.2.98 [Script_row_engraver], page 266
Determine order in horizontal side position elements.

This engraver creates the following layout object(s):

Section 3.1.93 [ScriptRow], page 366.

Section 2.2.99 [Separating_line_group_engraver], page 266
Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

Section 2.2.107 [Staff_collecting_engraver], page 269
Maintain the `stavesFound` variable.

Properties (read)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Properties (write)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Section 2.2.109 [Staff_symbol_engraver], page 269
Create the constellation of five (default) staff lines.

Music types accepted:

Section 1.2.62 [staff-span-event], page 46

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

2.1.26 VaticanaVoice

Same as `Voice` context, except that it is accommodated for typesetting Gregorian Chant in the notational style of Editio Vaticana.

This context also accepts commands for the following context(s):

Voice.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.23 [BreathingSign], page 306, Section 3.1.26 [ClusterSpanner], page 309, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.32 [DotColumn], page 314, Section 3.1.33 [Dots],

page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.40 [Episema], page 322, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.45 [Glissando], page 327, Section 3.1.49 [Hairpin], page 330, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.73 [NoteColumn], page 350, Section 3.1.74 [NoteHead], page 351, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83 [PhrasingSlur], page 358, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.91 [Script], page 365, Section 3.1.92 [ScriptColumn], page 365, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.115 [TextScript], page 385, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.125 [TupletNumber], page 396, Section 3.1.128 [VaticanaLigature], page 398 and Section 3.1.131 [VoiceFollower], page 401.

This context sets the following properties:

- Set grob-property `padding` in Section 3.1.91 [Script], page 365 to `0.5`.
- Set grob-property `style` in Section 3.1.74 [NoteHead], page 351 to `'vaticana.punctum`.
- Set translator property `autoBeaming` to `#f`.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

`Section 2.2.3 [Arpeggio_engraver], page 234`

Generate an Arpeggio symbol.

Music types accepted:

Section 1.2.4 [arpeggio-event], page 39

This engraver creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295.

`Section 2.2.4 [Auto_beam_engraver], page 235`

Generate beams based on measure characteristics and observed Stems. Uses `baseMoment`, `beatStructure`, `beamExceptions`, `measureLength`, and `measurePosition` to decide when to start and stop a beam. Overriding beaming is done through Section 2.2.112 [Stem_engraver], page 270 properties `stemLeftBeamCount` and `stemRightBeamCount`.

Music types accepted:

Section 1.2.8 [beam-forbid-event], page 40

Properties (read)

`autoBeaming` (boolean)

If set to true then beams are generated automatically.

`baseMoment` (moment)

Smallest unit of time that will stand on its own as a subdivided section.

`beamExceptions` (list)
: An alist of exceptions to autobeam rules that normally end on beats.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.10 [Beam_engraver], page 237`

Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.12 [Bend_engraver], page 238`

Create fall spanners.

Music types accepted:

Section 1.2.9 [bend-after-event], page 40

This engraver creates the following layout object(s):

Section 3.1.20 [BendAfter], page 304.

`Section 2.2.14 [Breathing_sign_engraver], page 238`

Create a breathing sign.

Music types accepted:

Section 1.2.13 [breathing-event], page 40

This engraver creates the following layout object(s):

Section 3.1.23 [BreathingSign], page 306.

`Section 2.2.16 [Chord_tremolo_engraver], page 239`
Generate beams for tremolo repeats.

Music types accepted:

Section 1.2.72 [tremolo-span-event], page 48

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.18 [Cluster_spanner_engraver], page 240`
Engrave a cluster using `Spanner` notation.

Music types accepted:

Section 1.2.14 [cluster-note-event], page 40

This engraver creates the following layout object(s):

Section 3.1.26 [ClusterSpanner], page 309 and Section 3.1.27 [ClusterSpannerBeacon], page 309.

`Section 2.2.27 [Dots_engraver], page 243`
Create Section 3.1.33 [Dots], page 315 objects for Section 3.2.87 [rhythmic-head-interface], page 447s.

This engraver creates the following layout object(s):

Section 3.1.33 [Dots], page 315.

`Section 2.2.28 [Double_percent_repeat_engraver], page 243`
Make double measure repeats.

Music types accepted:

Section 1.2.18 [double-percent-event], page 41

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`measureLength` (moment)
: Length of one measure in the current time signature.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.34 [DoublePercentRepeat], page 315 and Section 3.1.35 [DoublePercentRepeatCounter], page 316.

Section 2.2.31 [Dynamic_align_engraver], page 244
Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

Section 2.2.35 [Episema_engraver], page 245
Create an *Editio Vaticana*-style episema line.

Music types accepted:

Section 1.2.20 [episema-event], page 41

This engraver creates the following layout object(s):

Section 3.1.40 [Episema], page 322.

Section 2.2.39 [Fingering_engraver], page 247
Create fingering scripts.

Music types accepted:

Section 1.2.22 [fingering-event], page 41 and Section 1.2.65 [stroke-finger-event], page 47

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323.

Section 2.2.40 [Font_size_engraver], page 247
Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
The relative size of all grobs in a context.

Section 2.2.41 [Footnote_engraver], page 247
Create footnote texts.

Music types accepted:

Section 1.2.23 [footnote-event], page 41

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

Section 2.2.42 [Forbid_line_break_engraver], page 248
Forbid line breaks when note heads are still playing at some point.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

Section 2.2.44 [Glissando_engraver], page 249
Engrave glissandi.

Music types accepted:

Section 1.2.24 [glissando-event], page 41

Properties (read)

`glissandoMap` (list)
: A map in the form of '((source1 . target1) (source2 . target2) (sourcen . targetn)) showing the glissandi to be drawn for note columns. The value '() will default to '((0 . 0) (1 . 1) (n . n)), where n is the minimal number of noteheads in the two note columns between which the glissandi occur.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327.

Section 2.2.45 [Grace_beam_engraver], page 249
Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams. Only engraves beams when we are at grace points in time.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.46 [Grace_engraver], page 250
Set font size and other properties for grace notes.

Properties (read)

`graceSettings` (list)
Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

Section 2.2.50 [Grob_pq_engraver], page 250
Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
A queue of (*end-moment* . *GROB*) cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
A queue of (*end-moment* . *GROB*) cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.55 [Instrument_switch_engraver], page 252
Create a cue text for taking instrument.

Properties (read)

`instrumentCueName` (markup)
The name to print if another instrument is to be taken.

This engraver creates the following layout object(s):

Section 3.1.52 [InstrumentSwitch], page 333.

Section 2.2.59 [Laissez_vibrer_engraver], page 254
Create laissez vibrer items.

Music types accepted:

Section 1.2.29 [laissez-vibrer-event], page 42

This engraver creates the following layout object(s):

Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.56 [LaissezVibrerTieColumn], page 337.

Section 2.2.69 [Multi_measure_rest_engraver], page 257
Engrave multi-measure rests that are produced with 'R'. It reads `measurePosition` and `internalBarNumber` to determine what number to print over the Section 3.1.68 [MultiMeasureRest], page 346. Reads `measureLength` to determine whether it should use a whole rest or a breve rest to represent one measure.

Music types accepted:

Section 1.2.36 [multi-measure-rest-event], page 43 and Section 1.2.37 [multi-measure-text-event], page 43

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`restNumberThreshold` (number)
: If a multimeasure rest has more measures than this, a number is printed.

This engraver creates the following layout object(s):

Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

`Section 2.2.70 [New_dynamic_engraver], page 257`
: Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

Section 2.2.71 [New_fingering_engraver], page 258

Create fingering scripts for notes in a new chord. This engraver is ill-named, since it also takes care of articulations and harmonic note heads.

Properties (read)

`fingeringOrientations` (list)
: A list of symbols, containing '`left`', '`right`', '`up`' and/or '`down`'. This list determines where fingerings are put relative to the chord being fingered.

`harmonicDots` (boolean)
: If set, harmonic notes in dotted chords get dots.

`stringNumberOrientations` (list)
: See `fingeringOrientations`.

`strokeFingerOrientations` (list)
: See `fingeringOrientations`.

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323, Section 3.1.91 [Script], page 365, Section 3.1.105 [StringNumber], page 376 and Section 3.1.106 [StrokeFinger], page 377.

Section 2.2.72 [Note_head_line_engraver], page 258

Engrave a line between two note heads, for example a glissando. If `followVoice` is set, staff switches also generate a line.

Properties (read)

`followVoice` (boolean)
: If set, note heads are tracked across staff switches by a thin line.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327 and Section 3.1.131 [VoiceFollower], page 401.

Section 2.2.73 [Note_heads_engraver], page 259

Generate note heads.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`staffLineLayoutFunction` (procedure)
: Layout of staff lines, `traditional`, or `semitone`.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351.

Section 2.2.76 [Note_spacing_engraver], page 259

Generate `NoteSpacing`, an object linking horizontal lines for use in spacing.

This engraver creates the following layout object(s):

Section 3.1.76 [NoteSpacing], page 352.

Section 2.2.78 [Output_property_engraver], page 260

Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.82 [Part_combine_engraver], page 261

Part combine engraver for orchestral scores: Print markings 'a2', 'Solo', 'Solo II', and 'unisono'.

Music types accepted:

Section 1.2.39 [note-event], page 43 and Section 1.2.43 [part-combine-event], page 44

Properties (read)

`aDueText` (markup)
: Text to print at a unisono passage.

`partCombineTextsOnNote` (boolean)
: Print part-combine texts only on the next note rather than immediately on rests or skips.

`printPartCombineTexts` (boolean)
: Set 'Solo' and 'A due' texts in the part combiner?

`soloIIText` (markup)
: The text for the start of a solo for voice 'two' when part-combining.

`soloText` (markup)
: The text for the start of a solo when part-combining.

This engraver creates the following layout object(s):

Section 3.1.28 [CombineTextScript], page 309.

Section 2.2.83 [Percent_repeat_engraver], page 262

Make whole measure repeats.

Music types accepted:

Section 1.2.46 [percent-event], page 44

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

This engraver creates the following layout object(s):

Section 3.1.81 [PercentRepeat], page 356 and Section 3.1.82 [PercentRepeatCounter], page 357.

`Section 2.2.84 [Phrasing_slur_engraver], page 262`
: Print phrasing slurs. Similar to Section 2.2.101 [Slur_engraver], page 267.

Music types accepted:

Section 1.2.48 [phrasing-slur-event], page 45

This engraver creates the following layout object(s):

Section 3.1.83 [PhrasingSlur], page 358.

`Section 2.2.89 [Pitched_trill_engraver], page 264`
: Print the bracketed note head after a note head with trill.

This engraver creates the following layout object(s):

Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392 and Section 3.1.122 [TrillPitchHead], page 393.

`Section 2.2.91 [Repeat_tie_engraver], page 265`
: Create repeat ties.

Music types accepted:

Section 1.2.50 [repeat-tie-event], page 45

This engraver creates the following layout object(s):

Section 3.1.87 [RepeatTie], page 362 and Section 3.1.88 [RepeatTieColumn], page 363.

`Section 2.2.93 [Rest_engraver], page 265`
: Engrave rests.

Music types accepted:

Section 1.2.51 [rest-event], page 45

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

This engraver creates the following layout object(s):

Section 3.1.89 [Rest], page 364.

`Section 2.2.94 [Rhythmic_column_engraver], page 265`
: Generate `NoteColumn`, an object that groups stems, note heads, and rests.

This engraver creates the following layout object(s):

Section 3.1.73 [NoteColumn], page 350.

Section 2.2.96 [Script_column_engraver], page 266
: Find potentially colliding scripts and put them into a `ScriptColumn` object; that will fix the collisions.

  This engraver creates the following layout object(s):

  Section 3.1.92 [ScriptColumn], page 365.

Section 2.2.97 [Script_engraver], page 266
: Handle note scripted articulations.

  Music types accepted:

  Section 1.2.5 [articulation-event], page 40

  Properties (read)

  `scriptDefinitions` (list)
  : The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

  This engraver creates the following layout object(s):

  Section 3.1.91 [Script], page 365.

Section 2.2.100 [Slash_repeat_engraver], page 267
: Make beat repeats.

  Music types accepted:

  Section 1.2.49 [repeat-slash-event], page 45

  This engraver creates the following layout object(s):

  Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

Section 2.2.106 [Spanner_break_forbid_engraver], page 268
: Forbid breaks in certain spanners.

Section 2.2.118 [Text_engraver], page 272
: Create text scripts.

  Music types accepted:

  Section 1.2.68 [text-script-event], page 47

  This engraver creates the following layout object(s):

  Section 3.1.115 [TextScript], page 385.

Section 2.2.120 [Tie_engraver], page 272
: Generate ties between note heads of equal pitch.

  Music types accepted:

  Section 1.2.70 [tie-event], page 48

  Properties (read)

  `tieWaitForNote` (boolean)
  : If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

  Properties (write)

  `tieMelismaBusy` (boolean)
  : Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

Section 2.2.126 [Trill_spanner_engraver], page 274

Create trill spanner from an event.

Music types accepted:

Section 1.2.73 [trill-span-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.123 [TrillSpanner], page 393.

Section 2.2.127 [Tuplet_engraver], page 275

Catch tuplet events and generate appropriate bracket.

Music types accepted:

Section 1.2.74 [tuplet-span-event], page 48

Properties (read)

`tupletFullLength` (boolean)
: If set, the tuplet is printed up to the start of the next note.

`tupletFullLengthNote` (boolean)
: If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

This engraver creates the following layout object(s):

Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

Section 2.2.128 [Tweak_engraver], page 275

Read the `tweaks` property from the originating event, and set properties.

Section 2.2.129 [Vaticana_ligature_engraver], page 275

Handle ligatures by glueing special ligature heads together.

Music types accepted:

Section 1.2.31 [ligature-event], page 42 and Section 1.2.47 [pes-or-flexa-event], page 44

This engraver creates the following layout object(s):

Section 3.1.32 [DotColumn], page 314 and Section 3.1.128 [VaticanaLigature], page 398.

2.1.27 Voice

Corresponds to a voice on a staff. This context handles the conversion of dynamic signs, stems, beams, super- and subscripts, slurs, ties, and rests.

You have to instantiate this explicitly if you want to have multiple voices on the same staff.

This context creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295, Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.23 [BreathingSign], page 306, Section 3.1.26 [ClusterSpanner], page 309, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.45 [Glissando], page 327, Section 3.1.49 [Hairpin], page 330, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.59 [LigatureBracket], page 339, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.73 [NoteColumn], page 350, Section 3.1.74 [NoteHead], page 351, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83 [PhrasingSlur], page 358, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.91 [Script], page 365, Section 3.1.92 [ScriptColumn], page 365, Section 3.1.94 [Slur], page 366, Section 3.1.103 [Stem], page 374, Section 3.1.104 [StemTremolo], page 375, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.125 [TupletNumber], page 396 and Section 3.1.131 [VoiceFollower], page 401.

This context is a 'bottom' context; it cannot contain other contexts.

This context is built from the following engraver(s):

Section 2.2.3 [Arpeggio_engraver], page 234
: Generate an Arpeggio symbol.

  Music types accepted:

  Section 1.2.4 [arpeggio-event], page 39

  This engraver creates the following layout object(s):

  Section 3.1.9 [Arpeggio], page 295.

Section 2.2.4 [Auto_beam_engraver], page 235
: Generate beams based on measure characteristics and observed Stems. Uses `baseMoment`, `beatStructure`, `beamExceptions`, `measureLength`, and `measurePosition` to decide when to start and stop a beam. Overriding beaming is done through Section 2.2.112 [Stem_engraver], page 270 properties `stemLeftBeamCount` and `stemRightBeamCount`.

  Music types accepted:

  Section 1.2.8 [beam-forbid-event], page 40

  Properties (read)

`autoBeaming` (boolean)
: If set to true then beams are generated automatically.

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamExceptions` (list)
: An alist of exceptions to autobeam rules that normally end on beats.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.10 [Beam_engraver], page 237
Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.12 [Bend_engraver], page 238
Create fall spanners.

Music types accepted:

Section 1.2.9 [bend-after-event], page 40

This engraver creates the following layout object(s):

Section 3.1.20 [BendAfter], page 304.

`Section 2.2.14 [Breathing_sign_engraver], page 238`
Create a breathing sign.

Music types accepted:

Section 1.2.13 [breathing-event], page 40

This engraver creates the following layout object(s):

Section 3.1.23 [BreathingSign], page 306.

`Section 2.2.16 [Chord_tremolo_engraver], page 239`
Generate beams for tremolo repeats.

Music types accepted:

Section 1.2.72 [tremolo-span-event], page 48

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Section 2.2.18 [Cluster_spanner_engraver], page 240`
Engrave a cluster using `Spanner` notation.

Music types accepted:

Section 1.2.14 [cluster-note-event], page 40

This engraver creates the following layout object(s):

Section 3.1.26 [ClusterSpanner], page 309 and Section 3.1.27 [ClusterSpannerBeacon], page 309.

`Section 2.2.27 [Dots_engraver], page 243`
Create Section 3.1.33 [Dots], page 315 objects for Section 3.2.87 [rhythmic-head-interface], page 447s.

This engraver creates the following layout object(s):

Section 3.1.33 [Dots], page 315.

`Section 2.2.28 [Double_percent_repeat_engraver], page 243`
Make double measure repeats.

Music types accepted:

Section 1.2.18 [double-percent-event], page 41

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`measureLength` (moment)
: Length of one measure in the current time signature.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.34 [DoublePercentRepeat], page 315 and Section 3.1.35 [DoublePercentRepeatCounter], page 316.

`Section 2.2.31 [Dynamic_align_engraver], page 244`
Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

`Section 2.2.39 [Fingering_engraver], page 247`
Create fingering scripts.

Music types accepted:

Section 1.2.22 [fingering-event], page 41 and Section 1.2.65 [stroke-finger-event], page 47

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323.

`Section 2.2.40 [Font_size_engraver], page 247`
Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

`Section 2.2.41 [Footnote_engraver], page 247`
Create footnote texts.

Music types accepted:

Section 1.2.23 [footnote-event], page 41

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

`Section 2.2.42 [Forbid_line_break_engraver], page 248`
Forbid line breaks when note heads are still playing at some point.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

Section 2.2.44 [Glissando_engraver], page 249
Engrave glissandi.

Music types accepted:

Section 1.2.24 [glissando-event], page 41

Properties (read)

`glissandoMap` (list)
: A map in the form of '((source1 . target1) (source2 . target2) (sourcen . targetn)) showing the glissandi to be drawn for note columns. The value '() will default to '((0 . 0) (1 . 1) (n . n)), where n is the minimal number of noteheads in the two note columns between which the glissandi occur.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327.

Section 2.2.45 [Grace_beam_engraver], page 249
Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams. Only engraves beams when we are at grace points in time.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

Section 2.2.46 [Grace_engraver], page 250
Set font size and other properties for grace notes.

Properties (read)

`graceSettings` (list)
Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

Section 2.2.50 [Grob_pq_engraver], page 250
Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Section 2.2.55 [Instrument_switch_engraver], page 252
Create a cue text for taking instrument.

Properties (read)

`instrumentCueName` (markup)
The name to print if another instrument is to be taken.

This engraver creates the following layout object(s):

Section 3.1.52 [InstrumentSwitch], page 333.

Section 2.2.59 [Laissez_vibrer_engraver], page 254
Create laissez vibrer items.

Music types accepted:

Section 1.2.29 [laissez-vibrer-event], page 42

This engraver creates the following layout object(s):

Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.56 [LaissezVibrerTieColumn], page 337.

Section 2.2.61 [Ligature_bracket_engraver], page 254
Handle `Ligature_events` by engraving `Ligature` brackets.

Music types accepted:

Section 1.2.31 [ligature-event], page 42

This engraver creates the following layout object(s):

Section 3.1.59 [LigatureBracket], page 339.

Section 2.2.69 [Multi_measure_rest_engraver], page 257
Engrave multi-measure rests that are produced with '`R`'. It reads `measurePosition` and `internalBarNumber` to determine what number

to print over the Section 3.1.68 [MultiMeasureRest], page 346. Reads `measureLength` to determine whether it should use a whole rest or a breve rest to represent one measure.

Music types accepted:

Section 1.2.36 [multi-measure-rest-event], page 43 and Section 1.2.37 [multi-measure-text-event], page 43

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`restNumberThreshold` (number)
: If a multimeasure rest has more measures than this, a number is printed.

This engraver creates the following layout object(s):

Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

`Section 2.2.70 [New_dynamic_engraver], page 257`
: Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

Section 2.2.71 [New_fingering_engraver], page 258

Create fingering scripts for notes in a new chord. This engraver is ill-named, since it also takes care of articulations and harmonic note heads.

Properties (read)

`fingeringOrientations` (list)
: A list of symbols, containing '`left`', '`right`', '`up`' and/or '`down`'. This list determines where fingerings are put relative to the chord being fingered.

`harmonicDots` (boolean)
: If set, harmonic notes in dotted chords get dots.

`stringNumberOrientations` (list)
: See `fingeringOrientations`.

`strokeFingerOrientations` (list)
: See `fingeringOrientations`.

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323, Section 3.1.91 [Script], page 365, Section 3.1.105 [StringNumber], page 376 and Section 3.1.106 [StrokeFinger], page 377.

Section 2.2.72 [Note_head_line_engraver], page 258

Engrave a line between two note heads, for example a glissando. If `followVoice` is set, staff switches also generate a line.

Properties (read)

`followVoice` (boolean)
: If set, note heads are tracked across staff switches by a thin line.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327 and Section 3.1.131 [VoiceFollower], page 401.

Section 2.2.73 [Note_heads_engraver], page 259

Generate note heads.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`staffLineLayoutFunction` (procedure)
: Layout of staff lines, `traditional`, or `semitone`.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351.

Section 2.2.76 [Note_spacing_engraver], page 259
: Generate `NoteSpacing`, an object linking horizontal lines for use in spacing.

This engraver creates the following layout object(s):

Section 3.1.76 [NoteSpacing], page 352.

Section 2.2.78 [Output_property_engraver], page 260
: Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

Section 2.2.82 [Part_combine_engraver], page 261
: Part combine engraver for orchestral scores: Print markings 'a2', 'Solo', 'Solo II', and 'unisono'.

Music types accepted:

Section 1.2.39 [note-event], page 43 and Section 1.2.43 [part-combine-event], page 44

Properties (read)

`aDueText` (markup)
: Text to print at a unisono passage.

`partCombineTextsOnNote` (boolean)
: Print part-combine texts only on the next note rather than immediately on rests or skips.

`printPartCombineTexts` (boolean)
: Set 'Solo' and 'A due' texts in the part combiner?

`soloIIText` (markup)
: The text for the start of a solo for voice 'two' when part-combining.

`soloText` (markup)
: The text for the start of a solo when part-combining.

This engraver creates the following layout object(s):

Section 3.1.28 [CombineTextScript], page 309.

Section 2.2.83 [Percent_repeat_engraver], page 262
: Make whole measure repeats.

Music types accepted:

Section 1.2.46 [percent-event], page 44

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

This engraver creates the following layout object(s):

Section 3.1.81 [PercentRepeat], page 356 and Section 3.1.82 [PercentRepeatCounter], page 357.

`Section 2.2.84 [Phrasing_slur_engraver], page 262`
Print phrasing slurs. Similar to Section 2.2.101 [Slur_engraver], page 267.

Music types accepted:

Section 1.2.48 [phrasing-slur-event], page 45

This engraver creates the following layout object(s):

Section 3.1.83 [PhrasingSlur], page 358.

`Section 2.2.89 [Pitched_trill_engraver], page 264`
Print the bracketed note head after a note head with trill.

This engraver creates the following layout object(s):

Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392 and Section 3.1.122 [TrillPitchHead], page 393.

`Section 2.2.91 [Repeat_tie_engraver], page 265`
Create repeat ties.

Music types accepted:

Section 1.2.50 [repeat-tie-event], page 45

This engraver creates the following layout object(s):

Section 3.1.87 [RepeatTie], page 362 and Section 3.1.88 [RepeatTieColumn], page 363.

`Section 2.2.93 [Rest_engraver], page 265`
Engrave rests.

Music types accepted:

Section 1.2.51 [rest-event], page 45

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

This engraver creates the following layout object(s):

Section 3.1.89 [Rest], page 364.

Section 2.2.94 [Rhythmic_column_engraver], page 265
Generate `NoteColumn`, an object that groups stems, note heads, and rests.

This engraver creates the following layout object(s):

Section 3.1.73 [NoteColumn], page 350.

Section 2.2.96 [Script_column_engraver], page 266
Find potentially colliding scripts and put them into a `ScriptColumn` object; that will fix the collisions.

This engraver creates the following layout object(s):

Section 3.1.92 [ScriptColumn], page 365.

Section 2.2.97 [Script_engraver], page 266
Handle note scripted articulations.

Music types accepted:

Section 1.2.5 [articulation-event], page 40

Properties (read)

`scriptDefinitions` (list)
The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

This engraver creates the following layout object(s):

Section 3.1.91 [Script], page 365.

Section 2.2.100 [Slash_repeat_engraver], page 267
Make beat repeats.

Music types accepted:

Section 1.2.49 [repeat-slash-event], page 45

This engraver creates the following layout object(s):

Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

Section 2.2.101 [Slur_engraver], page 267
Build slur grobs from slur events.

Music types accepted:

Section 1.2.55 [slur-event], page 45

Properties (read)

`doubleSlurs` (boolean)
If set, two slurs are created for every slurred note, one above and one below the chord.

`slurMelismaBusy` (boolean)
Signal if a slur is present.

This engraver creates the following layout object(s):

Section 3.1.94 [Slur], page 366.

Section 2.2.106 [Spanner_break_forbid_engraver], page 268
: Forbid breaks in certain spanners.

Section 2.2.112 [Stem_engraver], page 270
: Create stems and single-stem tremolos. It also works together with the beam engraver for overriding beaming.

  Music types accepted:

  Section 1.2.71 [tremolo-event], page 48

  Properties (read)

  `stemLeftBeamCount` (integer)
  : Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.

  `stemRightBeamCount` (integer)
  : See `stemLeftBeamCount`.

  `tremoloFlags` (integer)
  : The number of tremolo flags to add if no number is specified.

  This engraver creates the following layout object(s):

  Section 3.1.103 [Stem], page 374 and Section 3.1.104 [StemTremolo], page 375.

Section 2.2.118 [Text_engraver], page 272
: Create text scripts.

  Music types accepted:

  Section 1.2.68 [text-script-event], page 47

  This engraver creates the following layout object(s):

  Section 3.1.115 [TextScript], page 385.

Section 2.2.119 [Text_spanner_engraver], page 272
: Create text spanner from an event.

  Music types accepted:

  Section 1.2.69 [text-span-event], page 48

  Properties (read)

  `currentMusicalColumn` (graphical (layout) object)
  : Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

  This engraver creates the following layout object(s):

  Section 3.1.116 [TextSpanner], page 387.

Section 2.2.120 [Tie_engraver], page 272
: Generate ties between note heads of equal pitch.

  Music types accepted:

  Section 1.2.70 [tie-event], page 48

  Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

`Section 2.2.126 [Trill_spanner_engraver], page 274`
Create trill spanner from an event.

Music types accepted:

Section 1.2.73 [trill-span-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.123 [TrillSpanner], page 393.

`Section 2.2.127 [Tuplet_engraver], page 275`
Catch tuplet events and generate appropriate bracket.

Music types accepted:

Section 1.2.74 [tuplet-span-event], page 48

Properties (read)

`tupletFullLength` (boolean)
: If set, the tuplet is printed up to the start of the next note.

`tupletFullLengthNote` (boolean)
: If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

This engraver creates the following layout object(s):

Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

`Section 2.2.128 [Tweak_engraver], page 275`
Read the `tweaks` property from the originating event, and set properties.

2.2 Engravers and Performers

See Section "Modifying context plug-ins" in *Notation Reference*.

2.2.1 Accidental_engraver

Make accidentals. Catch note heads, ties and notices key-change events. This engraver usually lives at Staff level, but reads the settings for Accidental at `Voice` level, so you can `\override` them at `Voice`.

Properties (read)

`autoAccidentals` (list)
: List of different ways to typeset an accidental.

  For determining when to print an accidental, several different rules are tried. The rule that gives the highest number of accidentals is used.

  Each entry in the list is either a symbol or a procedure.

  symbol
  : The symbol is the name of the context in which the following rules are to be applied. For example, if *context* is Section "Score" in *Internals Reference* then all staves share accidentals, and if *context* is Section "Staff" in *Internals Reference* then all voices in the same staff share accidentals, but staves do not.

  procedure
  : The procedure represents an accidental rule to be applied to the previously specified context.

    The procedure takes the following arguments:

    `context`
    : The current context to which the rule should be applied.

    `pitch`
    : The pitch of the note to be evaluated.

    `barnum`
    : The current bar number.

    `measurepos`
    : The current measure position.

    The procedure returns a pair of booleans. The first states whether an extra natural should be added. The second states whether an accidental should be printed. `(#t . #f)` does not make sense.

`autoCautionaries` (list)
: List similar to `autoAccidentals`, but it controls cautionary accidentals rather than normal ones. Both lists are tried, and the one giving the most accidentals wins. In case of draw, a normal accidental is typeset.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`harmonicAccidentals` (boolean)
: If set, harmonic notes in chords get accidentals.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`keySignature` (list)
: The current key signature. This is an alist containing `(step . alter)` or `((octave . step) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((octave . name) . (alter barnumber . measureposition))` pairs.

Properties (write)

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((octave . name) . (alter barnumber . measureposition))` pairs.

This engraver creates the following layout object(s):

Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290 and Section 3.1.4 [AccidentalSuggestion], page 291.

`Accidental_engraver` is part of the following context(s): Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.2 Ambitus_engraver

Create an ambitus.

Properties (read)

`keySignature` (list)
: The current key signature. This is an alist containing `(step . alter)` or `((octave . step) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

This engraver creates the following layout object(s):

Section 3.1.3 [AccidentalPlacement], page 290, Section 3.1.5 [Ambitus], page 292, Section 3.1.6 [AmbitusAccidental], page 293, Section 3.1.7 [AmbitusLine], page 294 and Section 3.1.8 [AmbitusNoteHead], page 294.

`Ambitus_engraver` is not part of any context.

2.2.3 Arpeggio_engraver

Generate an Arpeggio symbol.

Music types accepted:

Section 1.2.4 [arpeggio-event], page 39

This engraver creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295.

`Arpeggio_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice],

page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.4 Auto_beam_engraver

Generate beams based on measure characteristics and observed Stems. Uses `baseMoment`, `beatStructure`, `beamExceptions`, `measureLength`, and `measurePosition` to decide when to start and stop a beam. Overriding beaming is done through Section 2.2.112 [Stem_engraver], page 270 properties `stemLeftBeamCount` and `stemRightBeamCount`.

Music types accepted:

Section 1.2.8 [beam-forbid-event], page 40

Properties (read)

`autoBeaming` (boolean)
: If set to true then beams are generated automatically.

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamExceptions` (list)
: An alist of exceptions to autobeam rules that normally end on beats.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Auto_beam_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.5 Axis_group_engraver

Group all objects created in this context in a `VerticalAxisGroup` spanner.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

`Axis_group_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.7 [Dynamics], page 88, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.17 [NoteNames], page 146, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.6 Balloon_engraver

Create balloon texts.

Music types accepted:

Section 1.2.2 [annotate-output-event], page 39

This engraver creates the following layout object(s):

Section 3.1.10 [BalloonTextItem], page 296.

`Balloon_engraver` is not part of any context.

2.2.7 Bar_engraver

Create barlines. This engraver is controlled through the `whichBar` property. If it has no bar line to create, it will forbid a linebreak at this point.

Properties (read)

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

  ```
  \set Staff.whichBar = "|:"
  ```

  This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.11 [BarLine], page 297.

`Bar_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.7 [Dynamics], page 88, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.8 Bar_number_engraver

A bar number is created whenever `measurePosition` is zero and when there is a bar line (i.e., when `whichBar` is set). It is put on top of all staves, and appears only at the left side of the staff. The staves are taken from `stavesFound`, which is maintained by Section 2.2.107 [Staff_collecting_engraver], page 269.

Properties (read)

`barNumberVisibility` (procedure)
: A Procedure that takes an integer and returns whether the corresponding bar number should be printed.

`currentBarNumber` (integer)
: Contains the current barnumber. This property is incremented at every bar line.

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

```
\set Staff.whichBar = "|:"
```

This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

This engraver creates the following layout object(s):

Section 3.1.12 [BarNumber], page 298.

`Bar_number_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.9 Beam_collision_engraver

Help beams avoid colliding with notes and clefs in other voices.

`Beam_collision_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.10 Beam_engraver

Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Beam_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.11 Beam_performer

Music types accepted:

Section 1.2.7 [beam-event], page 40

`Beam_performer` is not part of any context.

2.2.12 Bend_engraver

Create fall spanners.

Music types accepted:

Section 1.2.9 [bend-after-event], page 40

This engraver creates the following layout object(s):

Section 3.1.20 [BendAfter], page 304.

`Bend_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.13 Break_align_engraver

Align grobs with corresponding `break-align-symbols` into groups, and order the groups according to `breakAlignOrder`. The left edge of the alignment gets a separate group, with a symbol `left-edge`.

This engraver creates the following layout object(s):

Section 3.1.21 [BreakAlignGroup], page 304, Section 3.1.22 [BreakAlignment], page 305 and Section 3.1.58 [LeftEdge], page 338.

`Break_align_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.14 Breathing_sign_engraver

Create a breathing sign.

Music types accepted:

Section 1.2.13 [breathing-event], page 40

This engraver creates the following layout object(s):

Section 3.1.23 [BreathingSign], page 306.

`Breathing_sign_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.15 Chord_name_engraver

Catch note and rest events and generate the appropriate chordname.

Music types accepted:

Section 1.2.39 [note-event], page 43 and Section 1.2.51 [rest-event], page 45

Properties (read)

`chordChanges` (boolean)
: Only show changes in chords scheme?

`chordNameExceptions` (list)
: An alist of chord exceptions. Contains `(`*`chord . markup`*`)` entries.

`chordNameExceptions` (list)
: An alist of chord exceptions. Contains `(`*`chord . markup`*`)` entries.

`chordNameFunction` (procedure)
: The function that converts lists of pitches to chord names.

`chordNoteNamer` (procedure)
: A function that converts from a pitch object to a text markup. Used for single pitches.

`chordRootNamer` (procedure)
: A function that converts from a pitch object to a text markup. Used for chords.

`majorSevenSymbol` (markup)
: How should the major 7th be formatted in a chord name?

`noChordSymbol` (markup)
: Markup to be displayed for rests in a ChordNames context.

This engraver creates the following layout object(s):

Section 3.1.24 [ChordName], page 307.

`Chord_name_engraver` is part of the following context(s): Section 2.1.2 [ChordNames], page 55.

2.2.16 Chord_tremolo_engraver

Generate beams for tremolo repeats.

Music types accepted:

Section 1.2.72 [tremolo-span-event], page 48

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Chord_tremolo_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.17 Clef_engraver

Determine and set reference point for pitches.

Properties (read)

`clefGlyph` (string)
: Name of the symbol within the music font.

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`clefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitClefVisibility` (vector)
: '`break-visibility`' function for clef changes.

`forceClef` (boolean)
: Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

This engraver creates the following layout object(s):

Section 3.1.25 [Clef], page 307 and Section 3.1.77 [OctavateEight], page 353.

`Clef_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.18 Cluster_spanner_engraver

Engrave a cluster using `Spanner` notation.

Music types accepted:

Section 1.2.14 [cluster-note-event], page 40

This engraver creates the following layout object(s):

Section 3.1.26 [ClusterSpanner], page 309 and Section 3.1.27 [ClusterSpannerBeacon], page 309.

`Cluster_spanner_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.19 Collision_engraver

Collect `NoteColumns`, and as soon as there are two or more, put them in a `NoteCollision` object.

This engraver creates the following layout object(s):

Section 3.1.72 [NoteCollision], page 350.

`Collision_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.20 Completion_heads_engraver

This engraver replaces `Note_heads_engraver`. It plays some trickery to break long notes and automatically tie them into the next measure.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`timing` (boolean)
: Keep administration of measure length, position, bar number, etc.? Switch off for cadenzas.

Properties (write)

`completionBusy` (boolean)
: Whether a completion-note head is playing.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351, Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

`Completion_heads_engraver` is not part of any context.

2.2.21 Completion_rest_engraver

This engraver replaces `Rest_engraver`. It plays some trickery to break long rests into the next measure.

Music types accepted:

Section 1.2.51 [rest-event], page 45

Properties (read)

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

Properties (write)

`restCompletionBusy` (boolean)
: Signal whether a completion-rest is active.

This engraver creates the following layout object(s):

Section 3.1.89 [Rest], page 364.

`Completion_rest_engraver` is not part of any context.

2.2.22 Control_track_performer

`Control_track_performer` is not part of any context.

2.2.23 Cue_clef_engraver

Determine and set reference point for pitches in cued voices.

Properties (read)

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefGlyph` (string)
: Name of the symbol within the music font.

`cueClefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`explicitCueClefVisibility` (vector)
: '`break-visibility`' function for cue clef changes.

`middleCCuePosition` (number)
: The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

This engraver creates the following layout object(s):

Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312 and Section 3.1.77 [OctavateEight], page 353.

`Cue_clef_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.24 Custos_engraver

Engrave custodes.

This engraver creates the following layout object(s):

Section 3.1.31 [Custos], page 313.

`Custos_engraver` is part of the following context(s): Section 2.1.15 [MensuralStaff], page 123 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.25 Default_bar_line_engraver

This engraver determines what kind of automatic bar lines should be produced, and sets `whichBar` accordingly. It should be at the same level as Section 2.2.124 [Timing_translator], page 274.

Properties (read)

`automaticBars` (boolean)
: If set to false then bar lines will not be printed automatically; they must be explicitly created with a `\bar` command. Unlike the `\cadenzaOn` keyword, measures are still counted. Bar line generation will resume according to that count if this property is unset.

`barAlways` (boolean)
: If set to true a bar line is drawn after each note.

`defaultBarType` (string)
: Set the default type of bar line. See `whichBar` for information on available bar types.

  This variable is read by Section "Timing_translator" in *Internals Reference* at Section "Score" in *Internals Reference* level.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

```
\set Staff.whichBar = "|:"
```

  This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

Properties (write)

`automaticBars` (boolean)
: If set to false then bar lines will not be printed automatically; they must be explicitly created with a `\bar` command. Unlike the `\cadenzaOn` keyword, measures are still counted. Bar line generation will resume according to that count if this property is unset.

`Default_bar_line_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.26 Dot_column_engraver

Engrave dots on dotted notes shifted to the right of the note. If omitted, then dots appear on top of the notes.

This engraver creates the following layout object(s):

Section 3.1.32 [DotColumn], page 314.

`Dot_column_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.27 Dots_engraver

Create Section 3.1.33 [Dots], page 315 objects for Section 3.2.87 [rhythmic-head-interface], page 447s.

This engraver creates the following layout object(s):

Section 3.1.33 [Dots], page 315.

`Dots_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.28 Double_percent_repeat_engraver

Make double measure repeats.

Music types accepted:

Section 1.2.18 [double-percent-event], page 41

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`measureLength` (moment)
: Length of one measure in the current time signature.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.34 [DoublePercentRepeat], page 315 and Section 3.1.35 [DoublePercentRepeatCounter], page 316.

`Double_percent_repeat_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.29 Drum_note_performer

Play drum notes.

Music types accepted:

Section 1.2.39 [note-event], page 43

`Drum_note_performer` is not part of any context.

2.2.30 Drum_notes_engraver

Generate drum note heads.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`drumStyleTable` (hash table)
: A hash table which maps drums to layout settings. Predefined values: '`drums-style`', '`timbales-style`', '`congas-style`', '`bongos-style`', and '`percussion-style`'.

  The layout style is a hash table, containing the drum-pitches (e.g., the symbol '`hihat`') as keys, and a list `(`*`notehead-style script vertical-position`*`)` as values.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351 and Section 3.1.91 [Script], page 365.

`Drum_notes_engraver` is part of the following context(s): Section 2.1.6 [DrumVoice], page 76.

2.2.31 Dynamic_align_engraver

Align hairpins and dynamic texts on a horizontal line.

Music types accepted:

Section 1.2.12 [break-span-event], page 40

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318.

`Dynamic_align_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.7 [Dynamics], page 88, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.32 Dynamic_engraver

Create hairpins, dynamic texts, and their vertical alignments. The symbols are collected onto a `DynamicLineSpanner` grob which takes care of vertical positioning.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

This engraver creates the following layout object(s):

Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

`Dynamic_engraver` is not part of any context.

2.2.33 Dynamic_performer

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39, Section 1.2.16 [crescendo-event], page 41 and Section 1.2.17 [decrescendo-event], page 41

Properties (read)

`dynamicAbsoluteVolumeFunction` (procedure)
: A procedure that takes one argument, the text value of a dynamic event, and returns the absolute volume of that dynamic event.

`instrumentEqualizer` (procedure)
: A function taking a string (instrument name), and returning a `(`*`min . max`*`)` pair of numbers for the loudness range of the instrument.

`midiInstrument` (string)
: Name of the MIDI instrument to use.

`midiMaximumVolume` (number)
: Analogous to `midiMinimumVolume`.

`midiMinimumVolume` (number)
: Set the minimum loudness for MIDI. Ranges from 0 to 1.

`Dynamic_performer` is not part of any context.

2.2.34 Engraver

Base class for engravers. Does nothing, so it is not used.

`Engraver` is not part of any context.

2.2.35 Episema_engraver

Create an *Editio Vaticana*-style episema line.

Music types accepted:

Section 1.2.20 [episema-event], page 41

This engraver creates the following layout object(s):

Section 3.1.40 [Episema], page 322.

`Episema_engraver` is part of the following context(s): Section 2.1.13 [GregorianTranscriptionVoice], page 107 and Section 2.1.26 [VaticanaVoice], page 207.

2.2.36 Extender_engraver

Create lyric extenders.

Music types accepted:

Section 1.2.15 [completize-extender-event], page 41 and Section 1.2.21 [extender-event], page 41

Properties (read)

`extendersOverRests` (boolean)
: Whether to continue extenders as they cross a rest.

`includeGraceNotes` (boolean)
: Do not ignore grace notes for Section "Lyrics" in *Internals Reference*.

This engraver creates the following layout object(s):

Section 3.1.60 [LyricExtender], page 340.

`Extender_engraver` is part of the following context(s): Section 2.1.14 [Lyrics], page 120.

2.2.37 Figured_bass_engraver

Make figured bass numbers.

Music types accepted:

Section 1.2.6 [bass-figure-event], page 40 and Section 1.2.51 [rest-event], page 45

Properties (read)

`figuredBassAlterationDirection` (direction)
: Where to put alterations relative to the main figure.

`figuredBassCenterContinuations` (boolean)
: Whether to vertically center pairs of extender lines. This does not work with three or more lines.

`figuredBassFormatter` (procedure)
: A routine generating a markup for a bass figure.

`ignoreFiguredBassRest` (boolean)
: Don't swallow rest events.

`implicitBassFigures` (list)
: A list of bass figures that are not printed as numbers, but only as extender lines.

`useBassFigureExtenders` (boolean)
: Whether to use extender lines for repeated bass figures.

This engraver creates the following layout object(s):

Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301 and Section 3.1.18 [BassFigureLine], page 302.

`Figured_bass_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.8 [FiguredBass], page 91, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.38 Figured_bass_position_engraver

Position figured bass alignments over notes.

This engraver creates the following layout object(s):

Section 3.1.15 [BassFigureAlignmentPositioning], page 300.

`Figured_bass_position_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.39 Fingering_engraver

Create fingering scripts.

Music types accepted:

Section 1.2.22 [fingering-event], page 41 and Section 1.2.65 [stroke-finger-event], page 47

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323.

`Fingering_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.40 Font_size_engraver

Put `fontSize` into `font-size` grob property.

Properties (read)

`fontSize` (number)
: The relative size of all grobs in a context.

`Font_size_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.5 [DrumStaff], page 70, Section 2.1.6 [DrumVoice], page 76, Section 2.1.9 [FretBoards], page 93, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.14 [Lyrics], page 120, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176, Section 2.1.24 [TabVoice], page 183, Section 2.1.25 [VaticanaStaff], page 197, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.41 Footnote_engraver

Create footnote texts.

Music types accepted:

Section 1.2.23 [footnote-event], page 41

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

`Footnote_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.42 Forbid_line_break_engraver

Forbid line breaks when note heads are still playing at some point.

Properties (read)

`busyGrobs` (list)
: A queue of `(end-moment . GROB)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

`Forbid_line_break_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.43 Fretboard_engraver

Generate fret diagram from one or more events of type `NoteEvent`.

Music types accepted:

Section 1.2.22 [fingering-event], page 41, Section 1.2.39 [note-event], page 43 and Section 1.2.64 [string-number-event], page 47

Properties (read)

`chordChanges` (boolean)
: Only show changes in chords scheme?

`defaultStrings` (list)
: A list of strings to use in calculating frets for tablatures and fretboards if no strings are provided in the notes for the current moment.

`highStringOne` (boolean)
: Whether the first string is the string with highest pitch on the instrument. This used by the automatic string selector for tablature notation.

`maximumFretStretch` (number)
: Don't allocate frets further than this from specified frets.

`minimumFret` (number)
: The tablature auto string-selecting mechanism selects the highest string with a fret at least `minimumFret`.

`noteToFretFunction` (procedure)
: Convert list of notes and list of defined strings to full list of strings and fret numbers. Parameters: The context, a list of note events, a list of tabstring events, and the fretboard grob if a fretboard is desired.

`predefinedDiagramTable` (hash table)
: The hash table of predefined fret diagrams to use in FretBoards.

`stringTunings` (list)
: The tablature strings tuning. It is a list of the pitches of each string (starting with the lowest numbered one).

`tablatureFormat` (procedure)
: A function formatting a tablature note head. Called with three arguments: context, string number and, fret number. It returns the text as a markup.

This engraver creates the following layout object(s):

Section 3.1.44 [FretBoard], page 326.

`Fretboard_engraver` is part of the following context(s): Section 2.1.9 [FretBoards], page 93.

2.2.44 Glissando_engraver

Engrave glissandi.

Music types accepted:

Section 1.2.24 [glissando-event], page 41

Properties (read)

`glissandoMap` (list)
: A map in the form of '((source1 . target1) (source2 . target2) (sourcen . targetn)) showing the glissandi to be drawn for note columns. The value '() will default to '((0 . 0) (1 . 1) (n . n)), where n is the minimal number of note-heads in the two note columns between which the glissandi occur.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327.

`Glissando_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.45 Grace_beam_engraver

Handle `Beam` events by engraving beams. If omitted, then notes are printed with flags instead of beams. Only engraves beams when we are at grace points in time.

Music types accepted:

Section 1.2.7 [beam-event], page 40

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

This engraver creates the following layout object(s):

Section 3.1.19 [Beam], page 302.

`Grace_beam_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.46 Grace_engraver

Set font size and other properties for grace notes.

Properties (read)

`graceSettings` (list)
: Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

`Grace_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.47 Grace_spacing_engraver

Bookkeeping of shortest starting and playing notes in grace note runs.

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.46 [GraceSpacing], page 328.

`Grace_spacing_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.48 Grid_line_span_engraver

This engraver makes cross-staff lines: It catches all normal lines and draws a single span line across them.

This engraver creates the following layout object(s):

Section 3.1.47 [GridLine], page 329.

`Grid_line_span_engraver` is not part of any context.

2.2.49 Grid_point_engraver

Generate grid points.

Properties (read)

`gridInterval` (moment)
: Interval for which to generate `GridPoints`.

This engraver creates the following layout object(s):

Section 3.1.48 [GridPoint], page 329.

`Grid_point_engraver` is not part of any context.

2.2.50 Grob_pq_engraver

Administrate when certain grobs (e.g., note heads) stop playing.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

Properties (write)

`busyGrobs` (list)
: A queue of `(end-moment . GROB)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

`Grob_pq_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.5 [DrumStaff], page 70, Section 2.1.6 [DrumVoice], page 76, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176, Section 2.1.24 [TabVoice], page 183, Section 2.1.25 [VaticanaStaff], page 197, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.51 Hara_kiri_engraver

Like `Axis_group_engraver`, but make a hara-kiri spanner, and add interesting items (i.e., note heads, lyric syllables, and normal rests).

Properties (read)

`keepAliveInterfaces` (list)
: A list of symbols, signifying grob interfaces that are worth keeping a staff with `remove-empty` set around for.

This engraver creates the following layout object(s):

Section 3.1.130 [VerticalAxisGroup], page 399.

`Hara_kiri_engraver` is part of the following context(s): Section 2.1.2 [ChordNames], page 55, Section 2.1.8 [FiguredBass], page 91, Section 2.1.9 [FretBoards], page 93 and Section 2.1.14 [Lyrics], page 120.

2.2.52 Horizontal_bracket_engraver

Create horizontal brackets over notes for musical analysis purposes.

Music types accepted:

Section 1.2.40 [note-grouping-event], page 44

This engraver creates the following layout object(s):

Section 3.1.50 [HorizontalBracket], page 331.

`Horizontal_bracket_engraver` is not part of any context.

2.2.53 Hyphen_engraver

Create lyric hyphens and distance constraints between words.

Music types accepted:

Section 1.2.26 [hyphen-event], page 42

This engraver creates the following layout object(s):

Section 3.1.61 [LyricHyphen], page 340 and Section 3.1.62 [LyricSpace], page 341.

`Hyphen_engraver` is part of the following context(s): Section 2.1.14 [Lyrics], page 120.

2.2.54 Instrument_name_engraver

Create a system start text for instrument or vocal names.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`shortInstrumentName` (markup)
: See `instrumentName`.

`shortVocalName` (markup)
: Name of a vocal line, short version.

`vocalName` (markup)
: Name of a vocal line.

This engraver creates the following layout object(s):

Section 3.1.51 [InstrumentName], page 332.

`Instrument_name_engraver` is part of the following context(s): Section 2.1.1 [ChoirStaff], page 54, Section 2.1.5 [DrumStaff], page 70, Section 2.1.9 [FretBoards], page 93, Section 2.1.11 [GrandStaff], page 95, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.14 [Lyrics], page 120, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.18 [PianoStaff], page 147, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.22 [StaffGroup], page 174, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.55 Instrument_switch_engraver

Create a cue text for taking instrument.

Properties (read)

`instrumentCueName` (markup)
: The name to print if another instrument is to be taken.

This engraver creates the following layout object(s):

Section 3.1.52 [InstrumentSwitch], page 333.

`Instrument_switch_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.56 Keep_alive_together_engraver

This engraver collects all `Hara_kiri_group_spanner`s that are created in contexts at or below its own. These spanners are then tied together so that one will be removed only if all are removed. For example, if a `StaffGroup` uses this engraver, then the staves in the group will all be visible as long as there is a note in at least one of them.

`Keep_alive_together_engraver` is part of the following context(s): Section 2.1.18 [PianoStaff], page 147.

2.2.57 Key_engraver

Engrave a key signature.

Music types accepted:

Section 1.2.27 [key-change-event], page 42

Properties (read)

`createKeyOnClefChange` (boolean)
: Print a key signature whenever the clef is changed.

`explicitKeySignatureVisibility` (vector)
: '`break-visibility`' function for explicit key changes. '`\override`' of the `break-visibility` property will set the visibility for normal (i.e., at the start of the line) key signatures.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`keyAlterationOrder` (list)
: An alist that defines in what order alterations should be printed. The format is `(`*`step . alter`*`)`, where *step* is a number from 0 to 6 and *alter* from -2 (sharp) to 2 (flat).

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step . alter`*`)` or `((`*`octave . step`*`) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`middleCClefPosition` (number)
: The position of the middle C, as determined only by the clef. This can be calculated by looking at `clefPosition` and `clefGlyph`.

`printKeyCancellation` (boolean)
: Print restoration alterations before a key signature change.

Properties (write)

`keySignature` (list)
: The current key signature. This is an alist containing `(`*`step . alter`*`)` or `((`*`octave . step`*`) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction, denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`tonic` (pitch)
: The tonic of the current scale.

This engraver creates the following layout object(s):

Section 3.1.53 [KeyCancellation], page 334 and Section 3.1.54 [KeySignature], page 335.

`Key_engraver` is part of the following context(s): Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.58 Key_performer

Music types accepted:

Section 1.2.27 [key-change-event], page 42

`Key_performer` is not part of any context.

2.2.59 Laissez_vibrer_engraver

Create laissez vibrer items.

Music types accepted:

Section 1.2.29 [laissez-vibrer-event], page 42

This engraver creates the following layout object(s):

Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.56 [LaissezVibrerTieColumn], page 337.

`Laissez_vibrer_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.60 Ledger_line_engraver

Create the spanner to draw ledger lines, and notices objects that need ledger lines.

This engraver creates the following layout object(s):

Section 3.1.57 [LedgerLineSpanner], page 337.

`Ledger_line_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.61 Ligature_bracket_engraver

Handle `Ligature_events` by engraving `Ligature` brackets.

Music types accepted:

Section 1.2.31 [ligature-event], page 42

This engraver creates the following layout object(s):

Section 3.1.59 [LigatureBracket], page 339.

`Ligature_bracket_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.24 [TabVoice], page 183 and Section 2.1.27 [Voice], page 220.

2.2.62 Lyric_engraver

Engrave text for lyrics.

Music types accepted:

Section 1.2.33 [lyric-event], page 42

Properties (read)

`ignoreMelismata` (boolean)
: Ignore melismata for this Section "Lyrics" in *Internals Reference* line.

`includeGraceNotes` (boolean)
: Do not ignore grace notes for Section "Lyrics" in *Internals Reference*.

`lyricMelismaAlignment` (direction)
: Alignment to use for a melisma syllable.

`searchForVoice` (boolean)
: Signal whether a search should be made of all contexts in the context hierarchy for a voice to provide rhythms for the lyrics.

This engraver creates the following layout object(s):

Section 3.1.63 [LyricText], page 342.

`Lyric_engraver` is part of the following context(s): Section 2.1.14 [Lyrics], page 120.

2.2.63 Lyric_performer

Music types accepted:

Section 1.2.33 [lyric-event], page 42

`Lyric_performer` is not part of any context.

2.2.64 Mark_engraver

Create `RehearsalMark` objects. It puts them on top of all staves (which is taken from the property `stavesFound`). If moving this engraver to a different context, Section 2.2.107 [Staff_collecting_engraver], page 269 must move along, otherwise all marks end up on the same Y location.

Music types accepted:

Section 1.2.34 [mark-event], page 42

Properties (read)

`markFormatter` (procedure)
: A procedure taking as arguments the context and the rehearsal mark. It should return the formatted mark as a markup object.

`rehearsalMark` (integer)
: The last rehearsal mark printed.

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

This engraver creates the following layout object(s):

Section 3.1.85 [RehearsalMark], page 360.

`Mark_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.65 Measure_grouping_engraver

Create `MeasureGrouping` to indicate beat subdivision.

Properties (read)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`beatStructure` (list)
: List of `baseMoments` that are combined to make beats.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

This engraver creates the following layout object(s):

Section 3.1.64 [MeasureGrouping], page 343.

`Measure_grouping_engraver` is not part of any context.

2.2.66 Melody_engraver

Create information for context dependent typesetting decisions.

This engraver creates the following layout object(s):

Section 3.1.65 [MelodyItem], page 344.

`Melody_engraver` is not part of any context.

2.2.67 Mensural_ligature_engraver

Handle `Mensural_ligature_events` by glueing special ligature heads together.

Music types accepted:

Section 1.2.31 [ligature-event], page 42

This engraver creates the following layout object(s):

Section 3.1.66 [MensuralLigature], page 344.

`Mensural_ligature_engraver` is part of the following context(s): Section 2.1.16 [MensuralVoice], page 133.

2.2.68 Metronome_mark_engraver

Engrave metronome marking. This delegates the formatting work to the function in the `metronomeMarkFormatter` property. The mark is put over all staves. The staves are taken from the `stavesFound` property, which is maintained by Section 2.2.107 [Staff_collecting_engraver], page 269.

Music types accepted:

Section 1.2.67 [tempo-change-event], page 47

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`metronomeMarkFormatter` (procedure)
: How to produce a metronome markup. Called with two arguments: a `TempoChangeEvent` and context.

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

`tempoHideNote` (boolean)
: Hide the note = count in tempo marks.

This engraver creates the following layout object(s):

Section 3.1.67 [MetronomeMark], page 344.

`Metronome_mark_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.69 Multi_measure_rest_engraver

Engrave multi-measure rests that are produced with 'R'. It reads `measurePosition` and `internalBarNumber` to determine what number to print over the Section 3.1.68 [MultiMeasureRest], page 346. Reads `measureLength` to determine whether it should use a whole rest or a breve rest to represent one measure.

Music types accepted:

Section 1.2.36 [multi-measure-rest-event], page 43 and Section 1.2.37 [multi-measure-text-event], page 43

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`restNumberThreshold` (number)
: If a multimeasure rest has more measures than this, a number is printed.

This engraver creates the following layout object(s):

Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

`Multi_measure_rest_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.70 New_dynamic_engraver

Create hairpins, dynamic texts and dynamic text spanners.

Music types accepted:

Section 1.2.1 [absolute-dynamic-event], page 39 and Section 1.2.60 [span-dynamic-event], page 46

Properties (read)

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

This engraver creates the following layout object(s):

Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

`New_dynamic_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.7 [Dynamics], page 88, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.71 New_fingering_engraver

Create fingering scripts for notes in a new chord. This engraver is ill-named, since it also takes care of articulations and harmonic note heads.

Properties (read)

`fingeringOrientations` (list)
: A list of symbols, containing '`left`', '`right`', '`up`' and/or '`down`'. This list determines where fingerings are put relative to the chord being fingered.

`harmonicDots` (boolean)
: If set, harmonic notes in dotted chords get dots.

`stringNumberOrientations` (list)
: See `fingeringOrientations`.

`strokeFingerOrientations` (list)
: See `fingeringOrientations`.

This engraver creates the following layout object(s):

Section 3.1.41 [Fingering], page 323, Section 3.1.91 [Script], page 365, Section 3.1.105 [StringNumber], page 376 and Section 3.1.106 [StrokeFinger], page 377.

`New_fingering_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.72 Note_head_line_engraver

Engrave a line between two note heads, for example a glissando. If `followVoice` is set, staff switches also generate a line.

Properties (read)

`followVoice` (boolean)
: If set, note heads are tracked across staff switches by a thin line.

This engraver creates the following layout object(s):

Section 3.1.45 [Glissando], page 327 and Section 3.1.131 [VoiceFollower], page 401.

`Note_head_line_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.73 Note_heads_engraver

Generate note heads.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`staffLineLayoutFunction` (procedure)
: Layout of staff lines, `traditional`, or `semitone`.

This engraver creates the following layout object(s):

Section 3.1.74 [NoteHead], page 351.

`Note_heads_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.74 Note_name_engraver

Print pitches as words.

Music types accepted:

Section 1.2.39 [note-event], page 43

Properties (read)

`printOctaveNames` (boolean)
: Print octave marks for the `NoteNames` context.

This engraver creates the following layout object(s):

Section 3.1.75 [NoteName], page 352.

`Note_name_engraver` is part of the following context(s): Section 2.1.17 [NoteNames], page 146.

2.2.75 Note_performer

Music types accepted:

Section 1.2.39 [note-event], page 43

`Note_performer` is not part of any context.

2.2.76 Note_spacing_engraver

Generate `NoteSpacing`, an object linking horizontal lines for use in spacing.

This engraver creates the following layout object(s):

Section 3.1.76 [NoteSpacing], page 352.

`Note_spacing_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.77 Ottava_spanner_engraver

Create a text spanner when the ottavation property changes.

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`middleCOffset` (number)
: The offset of middle C from the position given by `middleCClefPosition` This is used for ottava brackets.

`ottavation` (markup)
: If set, the text for an ottava spanner. Changing this creates a new text spanner.

This engraver creates the following layout object(s):

Section 3.1.78 [OttavaBracket], page 354.

`Ottava_spanner_engraver` is part of the following context(s): Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.78 Output_property_engraver

Apply a procedure to any grob acknowledged.

Music types accepted:

Section 1.2.3 [apply-output-event], page 39

`Output_property_engraver` is part of the following context(s): Section 2.1.2 [ChordNames], page 55, Section 2.1.3 [CueVoice], page 57, Section 2.1.5 [DrumStaff], page 70, Section 2.1.6 [DrumVoice], page 76, Section 2.1.7 [Dynamics], page 88, Section 2.1.9 [FretBoards], page 93, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.20 [Score], page 153, Section 2.1.21 [Staff], page 164, Section 2.1.22 [StaffGroup], page 174, Section 2.1.23 [TabStaff], page 176, Section 2.1.24 [TabVoice], page 183, Section 2.1.25 [VaticanaStaff], page 197, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.79 Page_turn_engraver

Decide where page turns are allowed to go.

Music types accepted:

Section 1.2.11 [break-event], page 40

Properties (read)

`minimumPageTurnLength` (moment)
: Minimum length of a rest for a page turn to be allowed.

`minimumRepeatLengthForPageTurn` (moment)
: Minimum length of a repeated section for a page turn to be allowed within that section.

`Page_turn_engraver` is not part of any context.

2.2.80 Paper_column_engraver

Take care of generating columns.

This engraver decides whether a column is breakable. The default is that a column is always breakable. However, every `Bar_engraver` that does not have a barline at a certain point will set `forbidBreaks` in the score context to stop line breaks. In practice, this means that you can make a break point by creating a bar line (assuming that there are no beams or notes that prevent a break point).

Music types accepted:

Section 1.2.11 [break-event], page 40 and Section 1.2.28 [label-event], page 42

Properties (read)

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

Properties (write)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

This engraver creates the following layout object(s):

Section 3.1.71 [NonMusicalPaperColumn], page 349 and Section 3.1.79 [PaperColumn], page 355.

`Paper_column_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.81 Parenthesis_engraver

Parenthesize objects whose music cause has the `parenthesize` property.

This engraver creates the following layout object(s):

Section 3.1.80 [ParenthesesItem], page 356.

`Parenthesis_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.82 Part_combine_engraver

Part combine engraver for orchestral scores: Print markings ‘a2’, ‘Solo’, ‘Solo II’, and ‘unisono’.

Music types accepted:

Section 1.2.39 [note-event], page 43 and Section 1.2.43 [part-combine-event], page 44

Properties (read)

`aDueText` (markup)
: Text to print at a unisono passage.

`partCombineTextsOnNote` (boolean)
: Print part-combine texts only on the next note rather than immediately on rests or skips.

`printPartCombineTexts` (boolean)
: Set ‘Solo’ and ‘A due’ texts in the part combiner?

`soloIIText` (markup)
: The text for the start of a solo for voice 'two' when part-combining.

`soloText` (markup)
: The text for the start of a solo when part-combining.

This engraver creates the following layout object(s):

Section 3.1.28 [CombineTextScript], page 309.

`Part_combine_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.83 Percent_repeat_engraver

Make whole measure repeats.

Music types accepted:

Section 1.2.46 [percent-event], page 44

Properties (read)

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

This engraver creates the following layout object(s):

Section 3.1.81 [PercentRepeat], page 356 and Section 3.1.82 [PercentRepeatCounter], page 357.

`Percent_repeat_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.84 Phrasing_slur_engraver

Print phrasing slurs. Similar to Section 2.2.101 [Slur_engraver], page 267.

Music types accepted:

Section 1.2.48 [phrasing-slur-event], page 45

This engraver creates the following layout object(s):

Section 3.1.83 [PhrasingSlur], page 358.

`Phrasing_slur_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.85 Piano_pedal_align_engraver

Align piano pedal symbols and brackets.

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

This engraver creates the following layout object(s):

Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.108 [SustainPedalLineSpanner], page 379 and Section 3.1.127 [UnaCordaPedalLineSpanner], page 397.

`Piano_pedal_align_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.86 Piano_pedal_engraver

Engrave piano pedal symbols and brackets.

Music types accepted:

Section 1.2.58 [sostenuto-event], page 46, Section 1.2.66 [sustain-event], page 47 and Section 1.2.75 [una-corda-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`pedalSostenutoStrings` (list)
: See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)
: See `pedalSustainStyle`.

`pedalSustainStrings` (list)
: A list of strings to print for sustain-pedal. Format is `(up updown down)`, where each of the three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)
: A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)
: See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)
: See `pedalSustainStyle`.

This engraver creates the following layout object(s):

Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378 and Section 3.1.126 [UnaCordaPedal], page 396.

`Piano_pedal_engraver` is part of the following context(s): Section 2.1.7 [Dynamics], page 88, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.87 Piano_pedal_performer

Music types accepted:

Section 1.2.58 [sostenuto-event], page 46, Section 1.2.66 [sustain-event], page 47 and Section 1.2.75 [una-corda-event], page 48

`Piano_pedal_performer` is not part of any context.

2.2.88 Pitch_squash_engraver

Set the vertical position of note heads to `squashedPosition`, if that property is set. This can be used to make a single-line staff demonstrating the rhythm of a melody.

Properties (read)

`squashedPosition` (integer)
: Vertical position of squashing for Section "Pitch_squash_engraver" in *Internals Reference*.

`Pitch_squash_engraver` is part of the following context(s): Section 2.1.19 [RhythmicStaff], page 150.

2.2.89 Pitched_trill_engraver

Print the bracketed note head after a note head with trill.

This engraver creates the following layout object(s):

Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392 and Section 3.1.122 [TrillPitchHead], page 393.

`Pitched_trill_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.90 Repeat_acknowledge_engraver

Acknowledge repeated music, and convert the contents of `repeatCommands` into an appropriate setting for `whichBar`.

Properties (read)

`doubleRepeatType` (string)
: Set the default bar line for double repeats.

`repeatCommands` (list)
: This property is a list of commands of the form `(list 'volta x)`, where *x* is a string or `#f`. `'end-repeat` is also accepted as a command.

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

```
\set Staff.whichBar = "|:"
```

  This will create a start-repeat bar in this staff only. Valid values are described in Section "bar-line-interface" in *Internals Reference*.

`Repeat_acknowledge_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.91 Repeat_tie_engraver

Create repeat ties.

Music types accepted:

Section 1.2.50 [repeat-tie-event], page 45

This engraver creates the following layout object(s):

Section 3.1.87 [RepeatTie], page 362 and Section 3.1.88 [RepeatTieColumn], page 363.

`Repeat_tie_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.92 Rest_collision_engraver

Handle collisions of rests.

Properties (read)

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

This engraver creates the following layout object(s):

Section 3.1.90 [RestCollision], page 364.

`Rest_collision_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.93 Rest_engraver

Engrave rests.

Music types accepted:

Section 1.2.51 [rest-event], page 45

Properties (read)

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

This engraver creates the following layout object(s):

Section 3.1.89 [Rest], page 364.

`Rest_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.94 Rhythmic_column_engraver

Generate `NoteColumn`, an object that groups stems, note heads, and rests.

This engraver creates the following layout object(s):

Section 3.1.73 [NoteColumn], page 350.

`Rhythmic_column_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.95 Scheme_engraver

Implement engravers in Scheme. Interprets arguments to `\consists` as callbacks.

`Scheme_engraver` is not part of any context.

2.2.96 Script_column_engraver

Find potentially colliding scripts and put them into a `ScriptColumn` object; that will fix the collisions.

This engraver creates the following layout object(s):

Section 3.1.92 [ScriptColumn], page 365.

`Script_column_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.97 Script_engraver

Handle note scripted articulations.

Music types accepted:

Section 1.2.5 [articulation-event], page 40

Properties (read)

`scriptDefinitions` (list)
: The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

This engraver creates the following layout object(s):

Section 3.1.91 [Script], page 365.

`Script_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.7 [Dynamics], page 88, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.98 Script_row_engraver

Determine order in horizontal side position elements.

This engraver creates the following layout object(s):

Section 3.1.93 [ScriptRow], page 366.

`Script_row_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.99 Separating_line_group_engraver

Generate objects for computing spacing parameters.

Properties (read)

`createSpacing` (boolean)
: Create `StaffSpacing` objects? Should be set for staves.

Properties (write)

`hasStaffSpacing` (boolean)
: True if the current `CommandColumn` contains items that will affect spacing.

This engraver creates the following layout object(s):

Section 3.1.100 [StaffSpacing], page 372.

`Separating_line_group_engraver` is part of the following context(s): Section 2.1.2 [ChordNames], page 55, Section 2.1.5 [DrumStaff], page 70, Section 2.1.8 [FiguredBass], page 91, Section 2.1.9 [FretBoards], page 93, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.17 [NoteNames], page 146, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.100 Slash_repeat_engraver

Make beat repeats.

Music types accepted:

Section 1.2.49 [repeat-slash-event], page 45

This engraver creates the following layout object(s):

Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

`Slash_repeat_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.101 Slur_engraver

Build slur grobs from slur events.

Music types accepted:

Section 1.2.55 [slur-event], page 45

Properties (read)

`doubleSlurs` (boolean)
: If set, two slurs are created for every slurred note, one above and one below the chord.

`slurMelismaBusy` (boolean)
: Signal if a slur is present.

This engraver creates the following layout object(s):

Section 3.1.94 [Slur], page 366.

`Slur_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.24 [TabVoice], page 183 and Section 2.1.27 [Voice], page 220.

2.2.102 Slur_performer

Music types accepted:

Section 1.2.55 [slur-event], page 45

`Slur_performer` is not part of any context.

2.2.103 Spacing_engraver

Make a `SpacingSpanner` and do bookkeeping of shortest starting and playing notes.

Music types accepted:

Section 1.2.59 [spacing-section-event], page 46

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`proportionalNotationDuration` (moment)
: Global override for shortest-playing duration. This is used for switching on proportional notation.

This engraver creates the following layout object(s):

Section 3.1.97 [SpacingSpanner], page 369.

`Spacing_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.104 Span_arpeggio_engraver

Make arpeggios that span multiple staves.

Properties (read)

`connectArpeggios` (boolean)
: If set, connect arpeggios across piano staff.

This engraver creates the following layout object(s):

Section 3.1.9 [Arpeggio], page 295.

`Span_arpeggio_engraver` is part of the following context(s): Section 2.1.11 [GrandStaff], page 95, Section 2.1.18 [PianoStaff], page 147 and Section 2.1.22 [StaffGroup], page 174.

2.2.105 Span_bar_engraver

Make cross-staff bar lines: It catches all normal bar lines and draws a single span bar across them.

This engraver creates the following layout object(s):

Section 3.1.98 [SpanBar], page 370.

`Span_bar_engraver` is part of the following context(s): Section 2.1.11 [GrandStaff], page 95, Section 2.1.18 [PianoStaff], page 147 and Section 2.1.22 [StaffGroup], page 174.

2.2.106 Spanner_break_forbid_engraver

Forbid breaks in certain spanners.

`Spanner_break_forbid_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.107 Staff_collecting_engraver

Maintain the `stavesFound` variable.

Properties (read)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

Properties (write)

`stavesFound` (list of grobs)
A list of all staff-symbols found.

`Staff_collecting_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.20 [Score], page 153, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.108 Staff_performer

`Staff_performer` is not part of any context.

2.2.109 Staff_symbol_engraver

Create the constellation of five (default) staff lines.

Music types accepted:

Section 1.2.62 [staff-span-event], page 46

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

`Staff_symbol_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164, Section 2.1.23 [TabStaff], page 176 and Section 2.1.25 [VaticanaStaff], page 197.

2.2.110 Stanza_number_align_engraver

This engraver ensures that stanza numbers are neatly aligned.

`Stanza_number_align_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.111 Stanza_number_engraver

Engrave stanza numbers.

Properties (read)

`stanza` (markup)
Stanza 'number' to print before the start of a verse. Use in `Lyrics` context.

This engraver creates the following layout object(s):

Section 3.1.102 [StanzaNumber], page 373.

`Stanza_number_engraver` is part of the following context(s): Section 2.1.14 [Lyrics], page 120.

2.2.112 Stem_engraver

Create stems and single-stem tremolos. It also works together with the beam engraver for overriding beaming.

Music types accepted:

Section 1.2.71 [tremolo-event], page 48

Properties (read)

`stemLeftBeamCount` (integer)
: Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.

`stemRightBeamCount` (integer)
: See `stemLeftBeamCount`.

`tremoloFlags` (integer)
: The number of tremolo flags to add if no number is specified.

This engraver creates the following layout object(s):

Section 3.1.103 [Stem], page 374 and Section 3.1.104 [StemTremolo], page 375.

`Stem_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183 and Section 2.1.27 [Voice], page 220.

2.2.113 System_start_delimiter_engraver

Create a system start delimiter (i.e., a `SystemStartBar`, `SystemStartBrace`, `SystemStartBracket` or `SystemStartSquare` spanner).

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`systemStartDelimiter` (symbol)
: Which grob to make for the start of the system/staff? Set to `SystemStartBrace`, `SystemStartBracket` or `SystemStartBar`.

`systemStartDelimiterHierarchy` (pair)
: A nested list, indicating the nesting of a start delimiters.

This engraver creates the following layout object(s):

Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382 and Section 3.1.113 [SystemStartSquare], page 383.

`System_start_delimiter_engraver` is part of the following context(s): Section 2.1.1 [ChoirStaff], page 54, Section 2.1.11 [GrandStaff], page 95, Section 2.1.18 [PianoStaff], page 147, Section 2.1.20 [Score], page 153 and Section 2.1.22 [StaffGroup], page 174.

2.2.114 Tab_note_heads_engraver

Generate one or more tablature note heads from event of type `NoteEvent`.

Music types accepted:

Section 1.2.22 [fingering-event], page 41, Section 1.2.39 [note-event], page 43 and Section 1.2.64 [string-number-event], page 47

Properties (read)

`defaultStrings` (list)
: A list of strings to use in calculating frets for tablatures and fretboards if no strings are provided in the notes for the current moment.

`fretLabels` (list)
: A list of strings or Scheme-formatted markups containing, in the correct order, the labels to be used for lettered frets in tablature.

`highStringOne` (boolean)
: Whether the first string is the string with highest pitch on the instrument. This used by the automatic string selector for tablature notation.

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`minimumFret` (number)
: The tablature auto string-selecting mechanism selects the highest string with a fret at least `minimumFret`.

`noteToFretFunction` (procedure)
: Convert list of notes and list of defined strings to full list of strings and fret numbers. Parameters: The context, a list of note events, a list of tabstring events, and the fretboard grob if a fretboard is desired.

`stringOneTopmost` (boolean)
: Whether the first string is printed on the top line of the tablature.

`stringTunings` (list)
: The tablature strings tuning. It is a list of the pitches of each string (starting with the lowest numbered one).

`tablatureFormat` (procedure)
: A function formatting a tablature note head. Called with three arguments: context, string number and, fret number. It returns the text as a markup.

`tabStaffLineLayoutFunction` (procedure)
: A function determining the staff position of a tablature note head. Called with two arguments: the context and the string.

This engraver creates the following layout object(s):

Section 3.1.114 [TabNoteHead], page 384.

`Tab_note_heads_engraver` is part of the following context(s): Section 2.1.24 [TabVoice], page 183.

2.2.115 Tab_staff_symbol_engraver

Create a tablature staff symbol, but look at `stringTunings` for the number of lines.

Properties (read)

`stringTunings` (list)
: The tablature strings tuning. It is a list of the pitches of each string (starting with the lowest numbered one).

This engraver creates the following layout object(s):

Section 3.1.101 [StaffSymbol], page 372.

`Tab_staff_symbol_engraver` is part of the following context(s): Section 2.1.23 [TabStaff], page 176.

2.2.116 Tab_tie_follow_engraver

Adjust TabNoteHead properties when a tie is followed by a slur or glissando.

`Tab_tie_follow_engraver` is part of the following context(s): Section 2.1.24 [TabVoice], page 183.

2.2.117 Tempo_performer

Properties (read)

`tempoWholesPerMinute` (moment)
: The tempo in whole notes per minute.

`Tempo_performer` is not part of any context.

2.2.118 Text_engraver

Create text scripts.

Music types accepted:

Section 1.2.68 [text-script-event], page 47

This engraver creates the following layout object(s):

Section 3.1.115 [TextScript], page 385.

`Text_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.7 [Dynamics], page 88, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.119 Text_spanner_engraver

Create text spanner from an event.

Music types accepted:

Section 1.2.69 [text-span-event], page 48

Properties (read)

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.116 [TextSpanner], page 387.

`Text_spanner_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.7 [Dynamics], page 88, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183 and Section 2.1.27 [Voice], page 220.

2.2.120 Tie_engraver

Generate ties between note heads of equal pitch.

Music types accepted:

Section 1.2.70 [tie-event], page 48

Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

This engraver creates the following layout object(s):

Section 3.1.117 [Tie], page 388 and Section 3.1.118 [TieColumn], page 389.

`Tie_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.17 [NoteNames], page 146, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.121 Tie_performer

Generate ties between note heads of equal pitch.

Music types accepted:

Section 1.2.70 [tie-event], page 48

Properties (read)

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

Properties (write)

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

`Tie_performer` is not part of any context.

2.2.122 Time_signature_engraver

Create a Section 3.1.119 [TimeSignature], page 390 whenever `timeSignatureFraction` changes.

Properties (read)

`implicitTimeSignatureVisibility` (vector)
: break visibility for the default time signature.

`timeSignatureFraction` (pair of numbers)
: A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

This engraver creates the following layout object(s):

Section 3.1.119 [TimeSignature], page 390.

`Time_signature_engraver` is part of the following context(s): Section 2.1.5 [DrumStaff], page 70, Section 2.1.12 [GregorianTranscriptionStaff], page 97, Section 2.1.15 [MensuralStaff], page 123, Section 2.1.19 [RhythmicStaff], page 150, Section 2.1.21 [Staff], page 164 and Section 2.1.23 [TabStaff], page 176.

2.2.123 Time_signature_performer

`Time_signature_performer` is not part of any context.

2.2.124 Timing_translator

This engraver adds the alias `Timing` to its containing context. Responsible for synchronizing timing information from staves. Normally in `Score`. In order to create polyrhythmic music, this engraver should be removed from `Score` and placed in `Staff`.

Properties (read)

`currentBarNumber` (integer)
: Contains the current barnumber. This property is incremented at every bar line.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

Properties (write)

`baseMoment` (moment)
: Smallest unit of time that will stand on its own as a subdivided section.

`currentBarNumber` (integer)
: Contains the current barnumber. This property is incremented at every bar line.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`timeSignatureFraction` (pair of numbers)
: A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

`Timing_translator` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.2.125 Translator

Base class. Not instantiated.

`Translator` is not part of any context.

2.2.126 Trill_spanner_engraver

Create trill spanner from an event.

Music types accepted:

Section 1.2.73 [trill-span-event], page 48

Properties (read)

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

This engraver creates the following layout object(s):

Section 3.1.123 [TrillSpanner], page 393.

`Trill_spanner_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.127 Tuplet_engraver

Catch tuplet events and generate appropriate bracket.

Music types accepted:

Section 1.2.74 [tuplet-span-event], page 48

Properties (read)

`tupletFullLength` (boolean)
: If set, the tuplet is printed up to the start of the next note.

`tupletFullLengthNote` (boolean)
: If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

This engraver creates the following layout object(s):

Section 3.1.124 [TupletBracket], page 395 and Section 3.1.125 [TupletNumber], page 396.

`Tuplet_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.128 Tweak_engraver

Read the `tweaks` property from the originating event, and set properties.

`Tweak_engraver` is part of the following context(s): Section 2.1.3 [CueVoice], page 57, Section 2.1.6 [DrumVoice], page 76, Section 2.1.7 [Dynamics], page 88, Section 2.1.13 [GregorianTranscriptionVoice], page 107, Section 2.1.16 [MensuralVoice], page 133, Section 2.1.24 [TabVoice], page 183, Section 2.1.26 [VaticanaVoice], page 207 and Section 2.1.27 [Voice], page 220.

2.2.129 Vaticana_ligature_engraver

Handle ligatures by glueing special ligature heads together.

Music types accepted:

Section 1.2.31 [ligature-event], page 42 and Section 1.2.47 [pes-or-flexa-event], page 44

This engraver creates the following layout object(s):

Section 3.1.32 [DotColumn], page 314 and Section 3.1.128 [VaticanaLigature], page 398.

`Vaticana_ligature_engraver` is part of the following context(s): Section 2.1.26 [VaticanaVoice], page 207.

2.2.130 Vertical_align_engraver

Catch groups (staves, lyrics lines, etc.) and stack them vertically.

Properties (read)

`alignAboveContext` (string)
: Where to insert newly created context in vertical alignment.

`alignBelowContext` (string)
: Where to insert newly created context in vertical alignment.

This engraver creates the following layout object(s):

Section 3.1.129 [VerticalAlignment], page 399.

`Vertical_align_engraver` is part of the following context(s): Section 2.1.1 [ChoirStaff], page 54, Section 2.1.11 [GrandStaff], page 95, Section 2.1.18 [PianoStaff], page 147, Section 2.1.20 [Score], page 153 and Section 2.1.22 [StaffGroup], page 174.

2.2.131 Volta_engraver

Make volta brackets.

Properties (read)

`repeatCommands` (list)
: This property is a list of commands of the form `(list 'volta` *x*`)`, where *x* is a string or `#f`. `'end-repeat` is also accepted as a command.

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

`voltaSpannerDuration` (moment)
: This specifies the maximum duration to use for the brackets printed for `\alternative`. This can be used to shrink the length of brackets in the situation where one alternative is very large.

This engraver creates the following layout object(s):

Section 3.1.132 [VoltaBracket], page 401 and Section 3.1.133 [VoltaBracketSpanner], page 402.

`Volta_engraver` is part of the following context(s): Section 2.1.20 [Score], page 153.

2.3 Tunable context properties

`aDueText` (markup)
: Text to print at a unisono passage.

`alignAboveContext` (string)
: Where to insert newly created context in vertical alignment.

`alignBassFigureAccidentals` (boolean)
: If true, then the accidentals are aligned in bass figure context.

`alignBelowContext` (string)
: Where to insert newly created context in vertical alignment.

`associatedVoice` (string)
: Name of the `Voice` that has the melody for this `Lyrics` line.

`autoAccidentals` (list)
: List of different ways to typeset an accidental.

  For determining when to print an accidental, several different rules are tried. The rule that gives the highest number of accidentals is used.

  Each entry in the list is either a symbol or a procedure.

symbol The symbol is the name of the context in which the following rules are to be applied. For example, if *context* is Section "Score" in *Internals Reference* then all staves share accidentals, and if *context* is Section "Staff" in *Internals Reference* then all voices in the same staff share accidentals, but staves do not.

procedure The procedure represents an accidental rule to be applied to the previously specified context.

The procedure takes the following arguments:

`context` The current context to which the rule should be applied.

`pitch` The pitch of the note to be evaluated.

`barnum` The current bar number.

`measurepos` The current measure position.

The procedure returns a pair of booleans. The first states whether an extra natural should be added. The second states whether an accidental should be printed. `(#t . #f)` does not make sense.

`autoBeamCheck` (procedure)
A procedure taking three arguments, *context*, *dir* [start/stop (-1 or 1)], and *test* [shortest note in the beam]. A non-`#f` return value starts or stops the auto beam.

`autoBeaming` (boolean)
If set to true then beams are generated automatically.

`autoCautionaries` (list)
List similar to `autoAccidentals`, but it controls cautionary accidentals rather than normal ones. Both lists are tried, and the one giving the most accidentals wins. In case of draw, a normal accidental is typeset.

`automaticBars` (boolean)
If set to false then bar lines will not be printed automatically; they must be explicitly created with a `\bar` command. Unlike the `\cadenzaOn` keyword, measures are still counted. Bar line generation will resume according to that count if this property is unset.

`barAlways` (boolean)
If set to true a bar line is drawn after each note.

`barCheckSynchronize` (boolean)
If true then reset `measurePosition` when finding a bar check.

`barNumberVisibility` (procedure)
A Procedure that takes an integer and returns whether the corresponding bar number should be printed.

`baseMoment` (moment)
Smallest unit of time that will stand on its own as a subdivided section.

`bassFigureFormatFunction` (procedure)
A procedure that is called to produce the formatting for a `BassFigure` grob. It takes a list of `BassFigureEvent`s, a context, and the grob to format.

`bassStaffProperties` (list)
An alist of property settings to apply for the down staff of `PianoStaff`. Used by `\autochange`.

`beamExceptions` (list)
: An alist of exceptions to autobeam rules that normally end on beats.

`beatStructure` (list)
: List of `baseMoment`s that are combined to make beats.

`chordChanges` (boolean)
: Only show changes in chords scheme?

`chordNameExceptions` (list)
: An alist of chord exceptions. Contains `(`*`chord . markup`*`)` entries.

`chordNameExceptionsFull` (list)
: An alist of full chord exceptions. Contains `(`*`chord . markup`*`)` entries.

`chordNameExceptionsPartial` (list)
: An alist of partial chord exceptions. Contains `(`*`chord . (prefix-markup suffix-markup`*`))` entries.

`chordNameFunction` (procedure)
: The function that converts lists of pitches to chord names.

`chordNameLowercaseMinor` (boolean)
: Downcase roots of minor chords?

`chordNameSeparator` (markup)
: The markup object used to separate parts of a chord name.

`chordNoteNamer` (procedure)
: A function that converts from a pitch object to a text markup. Used for single pitches.

`chordPrefixSpacer` (number)
: The space added between the root symbol and the prefix of a chord name.

`chordRootNamer` (procedure)
: A function that converts from a pitch object to a text markup. Used for chords.

`clefGlyph` (string)
: Name of the symbol within the music font.

`clefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`clefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`completionBusy` (boolean)
: Whether a completion-note head is playing.

`connectArpeggios` (boolean)
: If set, connect arpeggios across piano staff.

`countPercentRepeats` (boolean)
: If set, produce counters for percent repeats.

`createKeyOnClefChange` (boolean)
: Print a key signature whenever the clef is changed.

`createSpacing` (boolean)
: Create `StaffSpacing` objects? Should be set for staves.

`crescendoSpanner` (symbol)
: The type of spanner to be used for crescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin crescendo is used.

`crescendoText` (markup)
: The text to print at start of non-hairpin crescendo, i.e., '`cresc.`'.

`cueClefGlyph` (string)
: Name of the symbol within the music font.

`cueClefOctavation` (integer)
: Add this much extra octavation. Values of 7 and -7 are common.

`cueClefPosition` (number)
: Where should the center of the clef symbol go, measured in half staff spaces from the center of the staff.

`currentBarNumber` (integer)
: Contains the current barnumber. This property is incremented at every bar line.

`decrescendoSpanner` (symbol)
: The type of spanner to be used for decrescendi. Available values are '`hairpin`' and '`text`'. If unset, a hairpin decrescendo is used.

`decrescendoText` (markup)
: The text to print at start of non-hairpin decrescendo, i.e., '`dim.`'.

`defaultBarType` (string)
: Set the default type of bar line. See `whichBar` for information on available bar types.

  This variable is read by Section "Timing_translator" in *Internals Reference* at Section "Score" in *Internals Reference* level.

`defaultStrings` (list)
: A list of strings to use in calculating frets for tablatures and fretboards if no strings are provided in the notes for the current moment.

`doubleRepeatType` (string)
: Set the default bar line for double repeats.

`doubleSlurs` (boolean)
: If set, two slurs are created for every slurred note, one above and one below the chord.

`drumPitchTable` (hash table)
: A table mapping percussion instruments (symbols) to pitches.

`drumStyleTable` (hash table)
: A hash table which maps drums to layout settings. Predefined values: '`drums-style`', '`timbales-style`', '`congas-style`', '`bongos-style`', and '`percussion-style`'.

  The layout style is a hash table, containing the drum-pitches (e.g., the symbol '`hihat`') as keys, and a list `(notehead-style script vertical-position)` as values.

`explicitClefVisibility` (vector)
: '`break-visibility`' function for clef changes.

`explicitCueClefVisibility` (vector)
: '`break-visibility`' function for cue clef changes.

`explicitKeySignatureVisibility` (vector)
: '`break-visibility`' function for explicit key changes. '`\override`' of the `break-visibility` property will set the visibility for normal (i.e., at the start of the line) key signatures.

`extendersOverRests` (boolean)
: Whether to continue extenders as they cross a rest.

`extraNatural` (boolean)
: Whether to typeset an extra natural sign before accidentals changing from a non-natural to another non-natural.

`figuredBassAlterationDirection` (direction)
: Where to put alterations relative to the main figure.

`figuredBassCenterContinuations` (boolean)
: Whether to vertically center pairs of extender lines. This does not work with three or more lines.

`figuredBassFormatter` (procedure)
: A routine generating a markup for a bass figure.

`figuredBassPlusDirection` (direction)
: Where to put plus signs relative to the main figure.

`fingeringOrientations` (list)
: A list of symbols, containing '`left`', '`right`', '`up`' and/or '`down`'. This list determines where fingerings are put relative to the chord being fingered.

`firstClef` (boolean)
: If true, create a new clef when starting a staff.

`followVoice` (boolean)
: If set, note heads are tracked across staff switches by a thin line.

`fontSize` (number)
: The relative size of all grobs in a context.

`forbidBreak` (boolean)
: If set to `##t`, prevent a line break at this point.

`forceClef` (boolean)
: Show clef symbol, even if it has not changed. Only active for the first clef after the property is set, not for the full staff.

`fretLabels` (list)
: A list of strings or Scheme-formatted markups containing, in the correct order, the labels to be used for lettered frets in tablature.

`glissandoMap` (list)
: A map in the form of '((source1 . target1) (source2 . target2) (sourcen . targetn)) showing the glissandi to be drawn for note columns. The value '() will default to '((0 . 0) (1 . 1) (n . n)), where n is the minimal number of note-heads in the two note columns between which the glissandi occur.

`gridInterval` (moment)
: Interval for which to generate `GridPoint`s.

`handleNegativeFrets` (symbol)
: How the automatic fret calculator should handle calculated negative frets. Values include `'ignore`, to leave them out of the diagram completely, `'include`, to include

them as calculated, and `'recalculate`, to ignore the specified string and find a string where they will fit with a positive fret number.

`harmonicAccidentals` (boolean)
: If set, harmonic notes in chords get accidentals.

`harmonicDots` (boolean)
: If set, harmonic notes in dotted chords get dots.

`highStringOne` (boolean)
: Whether the first string is the string with highest pitch on the instrument. This used by the automatic string selector for tablature notation.

`ignoreBarChecks` (boolean)
: Ignore bar checks.

`ignoreFiguredBassRest` (boolean)
: Don't swallow rest events.

`ignoreMelismata` (boolean)
: Ignore melismata for this Section "Lyrics" in *Internals Reference* line.

`implicitBassFigures` (list)
: A list of bass figures that are not printed as numbers, but only as extender lines.

`implicitTimeSignatureVisibility` (vector)
: break visibility for the default time signature.

`includeGraceNotes` (boolean)
: Do not ignore grace notes for Section "Lyrics" in *Internals Reference*.

`instrumentCueName` (markup)
: The name to print if another instrument is to be taken.

`instrumentEqualizer` (procedure)
: A function taking a string (instrument name), and returning a `(min . max)` pair of numbers for the loudness range of the instrument.

`instrumentName` (markup)
: The name to print left of a staff. The `instrumentName` property labels the staff in the first system, and the `shortInstrumentName` property labels following lines.

`instrumentTransposition` (pitch)
: Define the transposition of the instrument. Its value is the pitch that sounds like middle C. This is used to transpose the MIDI output, and `\quote`s.

`internalBarNumber` (integer)
: Contains the current barnumber. This property is used for internal timekeeping, among others by the `Accidental_engraver`.

`keepAliveInterfaces` (list)
: A list of symbols, signifying grob interfaces that are worth keeping a staff with `remove-empty` set around for.

`keyAlterationOrder` (list)
: An alist that defines in what order alterations should be printed. The format is `(step . alter)`, where *step* is a number from 0 to 6 and *alter* from -2 (sharp) to 2 (flat).

`keySignature` (list)
: The current key signature. This is an alist containing `(step . alter)` or `((octave . step) . alter)`, where *step* is a number in the range 0 to 6 and *alter* a fraction,

denoting alteration. For alterations, use symbols, e.g. `keySignature = #`((6 . ,FLAT))`.

`lyricMelismaAlignment` (direction)
: Alignment to use for a melisma syllable.

`majorSevenSymbol` (markup)
: How should the major 7th be formatted in a chord name?

`markFormatter` (procedure)
: A procedure taking as arguments the context and the rehearsal mark. It should return the formatted mark as a markup object.

`maximumFretStretch` (number)
: Don't allocate frets further than this from specified frets.

`measureLength` (moment)
: Length of one measure in the current time signature.

`measurePosition` (moment)
: How much of the current measure have we had. This can be set manually to create incomplete measures.

`melismaBusyProperties` (list)
: A list of properties (symbols) to determine whether a melisma is playing. Setting this property will influence how lyrics are aligned to notes. For example, if set to `#'(melismaBusy beamMelismaBusy)`, only manual melismata and manual beams are considered. Possible values include `melismaBusy`, `slurMelismaBusy`, `tieMelismaBusy`, and `beamMelismaBusy`.

`metronomeMarkFormatter` (procedure)
: How to produce a metronome markup. Called with two arguments: a `TempoChangeEvent` and context.

`middleCClefPosition` (number)
: The position of the middle C, as determined only by the clef. This can be calculated by looking at `clefPosition` and `clefGlyph`.

`middleCCuePosition` (number)
: The position of the middle C, as determined only by the clef of the cue notes. This can be calculated by looking at `cueClefPosition` and `cueClefGlyph`.

`middleCOffset` (number)
: The offset of middle C from the position given by `middleCClefPosition` This is used for ottava brackets.

`middleCPosition` (number)
: The place of the middle C, measured in half staff-spaces. Usually determined by looking at `middleCClefPosition` and `middleCOffset`.

`midiChannelMapping` (symbol)
: How to map MIDI channels: per `instrument` (default), `staff` or `voice`.

`midiInstrument` (string)
: Name of the MIDI instrument to use.

`midiMaximumVolume` (number)
: Analogous to `midiMinimumVolume`.

`midiMergeUnisons` (boolean)
: If true, output only one MIDI note-on event when notes with the same pitch, in the same MIDI-file track, overlap.

`midiMinimumVolume` (number)
: Set the minimum loudness for MIDI. Ranges from 0 to 1.

`minimumFret` (number)
: The tablature auto string-selecting mechanism selects the highest string with a fret at least `minimumFret`.

`minimumPageTurnLength` (moment)
: Minimum length of a rest for a page turn to be allowed.

`minimumRepeatLengthForPageTurn` (moment)
: Minimum length of a repeated section for a page turn to be allowed within that section.

`noChordSymbol` (markup)
: Markup to be displayed for rests in a ChordNames context.

`noteToFretFunction` (procedure)
: Convert list of notes and list of defined strings to full list of strings and fret numbers. Parameters: The context, a list of note events, a list of tabstring events, and the fretboard grob if a fretboard is desired.

`ottavation` (markup)
: If set, the text for an ottava spanner. Changing this creates a new text spanner.

`output` (music output)
: The output produced by a score-level translator during music interpretation.

`partCombineTextsOnNote` (boolean)
: Print part-combine texts only on the next note rather than immediately on rests or skips.

`pedalSostenutoStrings` (list)
: See `pedalSustainStrings`.

`pedalSostenutoStyle` (symbol)
: See `pedalSustainStyle`.

`pedalSustainStrings` (list)
: A list of strings to print for sustain-pedal. Format is `(up updown down)`, where each of the three is the string to print when this is done with the pedal.

`pedalSustainStyle` (symbol)
: A symbol that indicates how to print sustain pedals: `text`, `bracket` or `mixed` (both).

`pedalUnaCordaStrings` (list)
: See `pedalSustainStrings`.

`pedalUnaCordaStyle` (symbol)
: See `pedalSustainStyle`.

`predefinedDiagramTable` (hash table)
: The hash table of predefined fret diagrams to use in FretBoards.

`printKeyCancellation` (boolean)
: Print restoration alterations before a key signature change.

`printOctaveNames` (boolean)
: Print octave marks for the `NoteNames` context.

`printPartCombineTexts` (boolean)
: Set ‘Solo’ and ‘A due’ texts in the part combiner?

`proportionalNotationDuration` (moment)
: Global override for shortest-playing duration. This is used for switching on proportional notation.

`rehearsalMark` (integer)
: The last rehearsal mark printed.

`repeatCommands` (list)
: This property is a list of commands of the form `(list 'volta x)`, where *x* is a string or `#f`. `'end-repeat` is also accepted as a command.

`repeatCountVisibility` (procedure)
: A procedure taking as arguments an integer and context, returning whether the corresponding percent repeat number should be printed when `countPercentRepeats` is set.

`restCompletionBusy` (boolean)
: Signal whether a completion-rest is active.

`restNumberThreshold` (number)
: If a multimeasure rest has more measures than this, a number is printed.

`searchForVoice` (boolean)
: Signal whether a search should be made of all contexts in the context hierarchy for a voice to provide rhythms for the lyrics.

`shapeNoteStyles` (vector)
: Vector of symbols, listing style for each note head relative to the tonic (qv.) of the scale.

`shortInstrumentName` (markup)
: See `instrumentName`.

`shortVocalName` (markup)
: Name of a vocal line, short version.

`skipBars` (boolean)
: If set to true, then skip the empty bars that are produced by multimeasure notes and rests. These bars will not appear on the printed output. If not set (the default), multimeasure notes and rests expand into their full length, printing the appropriate number of empty bars so that synchronization with other voices is preserved.

```
{
  r1 r1*3 R1*3
  \set Score.skipBars= ##t
  r1*3 R1*3
}
```

`skipTypesetting` (boolean)
: If true, no typesetting is done, speeding up the interpretation phase. Useful for debugging large scores.

`soloIIText` (markup)
: The text for the start of a solo for voice ‘two’ when part-combining.

`soloText` (markup)
: The text for the start of a solo when part-combining.

`squashedPosition` (integer)
: Vertical position of squashing for Section “Pitch_squash_engraver” in *Internals Reference*.

`staffLineLayoutFunction` (procedure)
: Layout of staff lines, `traditional`, or `semitone`.

`stanza` (markup)
: Stanza 'number' to print before the start of a verse. Use in `Lyrics` context.

`stemLeftBeamCount` (integer)
: Specify the number of beams to draw on the left side of the next note. Overrides automatic beaming. The value is only used once, and then it is erased.

`stemRightBeamCount` (integer)
: See `stemLeftBeamCount`.

`stringNumberOrientations` (list)
: See `fingeringOrientations`.

`stringOneTopmost` (boolean)
: Whether the first string is printed on the top line of the tablature.

`stringTunings` (list)
: The tablature strings tuning. It is a list of the pitches of each string (starting with the lowest numbered one).

`strokeFingerOrientations` (list)
: See `fingeringOrientations`.

`subdivideBeams` (boolean)
: If set, multiple beams will be subdivided at `baseMoment` positions by only drawing one beam over the beat.

`suggestAccidentals` (boolean)
: If set, accidentals are typeset as cautionary suggestions over the note.

`systemStartDelimiter` (symbol)
: Which grob to make for the start of the system/staff? Set to `SystemStartBrace`, `SystemStartBracket` or `SystemStartBar`.

`systemStartDelimiterHierarchy` (pair)
: A nested list, indicating the nesting of a start delimiters.

`tablatureFormat` (procedure)
: A function formatting a tablature note head. Called with three arguments: context, string number and, fret number. It returns the text as a markup.

`tabStaffLineLayoutFunction` (procedure)
: A function determining the staff position of a tablature note head. Called with two arguments: the context and the string.

`tempoHideNote` (boolean)
: Hide the note = count in tempo marks.

`tempoWholesPerMinute` (moment)
: The tempo in whole notes per minute.

`tieWaitForNote` (boolean)
: If true, tied notes do not have to follow each other directly. This can be used for writing out arpeggios.

`timeSignatureFraction` (pair of numbers)
: A pair of numbers, signifying the time signature. For example, `#'(4 . 4)` is a 4/4 time signature.

`timeSignatureSettings` (list)
: A nested alist of settings for time signatures. Contains elements for various time signatures. The element for each time signature contains entries for `baseMoment`, `beatStructure`, and `beamExceptions`.

`timing` (boolean)
: Keep administration of measure length, position, bar number, etc.? Switch off for cadenzas.

`tonic` (pitch)
: The tonic of the current scale.

`topLevelAlignment` (boolean)
: If true, the *Vertical_align_engraver* will create a *VerticalAlignment*; otherwise, it will create a *StaffGrouper*

`trebleStaffProperties` (list)
: An alist of property settings to apply for the up staff of `PianoStaff`. Used by `\autochange`.

`tremoloFlags` (integer)
: The number of tremolo flags to add if no number is specified.

`tupletFullLength` (boolean)
: If set, the tuplet is printed up to the start of the next note.

`tupletFullLengthNote` (boolean)
: If set, end at the next note, otherwise end on the matter (time signatures, etc.) before the note.

`tupletSpannerDuration` (moment)
: Normally, a tuplet bracket is as wide as the `\times` expression that gave rise to it. By setting this property, you can make brackets last shorter.

```
{
  \set tupletSpannerDuration = #(ly:make-moment 1 4)
  \times 2/3 { c8 c c c c c }
}
```

`useBassFigureExtenders` (boolean)
: Whether to use extender lines for repeated bass figures.

`vocalName` (markup)
: Name of a vocal line.

`voltaSpannerDuration` (moment)
: This specifies the maximum duration to use for the brackets printed for `\alternative`. This can be used to shrink the length of brackets in the situation where one alternative is very large.

`whichBar` (string)
: This property is read to determine what type of bar line to create.

  Example:

```
\set Staff.whichBar = "|:"
```

  This will create a start-repeat bar in this staff only. Valid values are described in Section “bar-line-interface” in *Internals Reference*.

2.4 Internal context properties

`associatedVoiceContext` (context)
: The context object of the `Voice` that has the melody for this `Lyrics`.

`barCheckLastFail` (moment)
: Where in the measure did the last barcheck fail?

`beamMelismaBusy` (boolean)
: Signal if a beam is present.

`busyGrobs` (list)
: A queue of `(`*`end-moment . GROB`*`)` cons cells. This is for internal (C++) use only. This property contains the grobs which are still busy (e.g. note heads, spanners, etc.).

`currentCommandColumn` (graphical (layout) object)
: Grob that is X-parent to all current breakable (clef, key signature, etc.) items.

`currentMusicalColumn` (graphical (layout) object)
: Grob that is X-parent to all non-breakable items (note heads, lyrics, etc.).

`dynamicAbsoluteVolumeFunction` (procedure)
: A procedure that takes one argument, the text value of a dynamic event, and returns the absolute volume of that dynamic event.

`finalizations` (list)
: A list of expressions to evaluate before proceeding to next time step. This is an internal variable.

`graceSettings` (list)
: Overrides for grace notes. This property should be manipulated through the `add-grace-property` function.

`hasStaffSpacing` (boolean)
: True if the current `CommandColumn` contains items that will affect spacing.

`lastKeySignature` (list)
: Last key signature before a key signature change.

`localKeySignature` (list)
: The key signature at this point in the measure. The format is the same as for `keySignature`, but can also contain `((`*`octave . name`*`) . (`*`alter barnumber . measureposition`*`))` pairs.

`melismaBusy` (boolean)
: Signifies whether a melisma is active. This can be used to signal melismas on top of those automatically detected.

`quotedCueEventTypes` (list)
: A list of symbols, representing the event types that should be duplicated for `\cueDuring` commands.

`quotedEventTypes` (list)
: A list of symbols, representing the event types that should be duplicated for `\quoteDuring` commands. This is also a fallback for `\cueDuring` if `quotedCueEventTypes` is not set

`rootSystem` (graphical (layout) object)
: The System object.

`scriptDefinitions` (list)
: The description of scripts. This is used by the `Script_engraver` for typesetting note-superscripts and subscripts. See '`scm/script.scm`' for more information.

`slurMelismaBusy` (boolean)
: Signal if a slur is present.

`stavesFound` (list of grobs)
: A list of all staff-symbols found.

`tieMelismaBusy` (boolean)
: Signal whether a tie is present.

3 Backend

3.1 All layout objects

3.1.1 Accidental

Accidental objects are created by: Section 2.2.1 [Accidental_engraver], page 233.

Standard settings:

`alteration` (number):
`accidental-interface::calc-alteration`
Alteration numbers for accidental.

`avoid-slur` (symbol):
`'inside`
Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`glyph-name-alist` (list):
`'((0 . accidentals.natural) (-1/2 . accidentals.flat) (1/2 . accidentals.sharp) (1 . accidentals.doublesharp) (-1 . accidentals.flatflat) (3/4 . accidentals.sharp.slashslash.stemstemstem) (1/4 . accidentals.sharp.slashslash.stem) (-1/4 . accidentals.mirroredflat) (-3/4 . accidentals.mirroredflat.flat))`
An alist of key-string pairs.

`stencil` (stencil):
`ly:accidental-interface::print`
The symbol to print.

`X-extent` (pair of numbers):
`ly:accidental-interface::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:accidental-interface::height`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.1 [accidental-interface], page 403, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.46 [inline-accidental-interface], page 430 and Section 3.2.48 [item-interface], page 432.

3.1.2 AccidentalCautionary

AccidentalCautionary objects are created by: Section 2.2.1 [Accidental_engraver], page 233.

Standard settings:

`alteration` (number):
`accidental-interface::calc-alteration`
Alteration numbers for accidental.

`avoid-slur` (symbol):
`'inside`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`glyph-name-alist` (list):
`'((0 . accidentals.natural) (-1/2 . accidentals.flat) (1/2 . accidentals.sharp) (1 . accidentals.doublesharp) (-1 . accidentals.flatflat) (3/4 . accidentals.sharp.slashslash.stemstemstem) (1/4 . accidentals.sharp.slashslash.stem) (-1/4 . accidentals.mirroredflat) (-3/4 . accidentals.mirroredflat.flat))`

An alist of key-string pairs.

`parenthesized` (boolean):
`#t`

Parenthesize this grob.

`stencil` (stencil):
`ly:accidental-interface::print`

The symbol to print.

`Y-extent` (pair of numbers):
`ly:accidental-interface::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.1 [accidental-interface], page 403, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.46 [inline-accidental-interface], page 430 and Section 3.2.48 [item-interface], page 432.

3.1.3 AccidentalPlacement

AccidentalPlacement objects are created by: Section 2.2.1 [Accidental_engraver], page 233 and Section 2.2.2 [Ambitus_engraver], page 234.

Standard settings:

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`right-padding` (dimension, in staff space):
`0.15`

Space to insert on the right side of an object (e.g., between note and its accidentals).

`script-priority` (number):
`-100`

A sorting key that determines in what order a script is within a stack of scripts.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

This object supports the following interface(s): Section 3.2.2 [accidental-placement-interface], page 404, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.4 AccidentalSuggestion

AccidentalSuggestion objects are created by: Section 2.2.1 [Accidental_engraver], page 233.

Standard settings:

`alteration` (number):
`accidental-interface::calc-alteration`

Alteration numbers for accidental.

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-size` (number):
`-2`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`glyph-name-alist` (list):
```
'((0 . accidentals.natural) (-1/2 . accidentals.flat) (1/2
. accidentals.sharp) (1 . accidentals.doublesharp) (-1 .
accidentals.flatflat) (3/4 . accidentals.sharp.slashslash.stemstemstem)
(1/4 . accidentals.sharp.slashslash.stem)
(-1/4 . accidentals.mirroredflat) (-3/4 .
accidentals.mirroredflat.flat))
```

An alist of key-string pairs.

`outside-staff-priority` (number):
`0`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`script-priority` (number):
`0`

A sorting key that determines in what order a script is within a stack of scripts.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`0.25`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:accidental-interface::print`

The symbol to print.

`X-extent` (pair of numbers):
`ly:accidental-interface::width`

Hard coded extent in X direction.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:self-alignment-interface::centered-on-x-parent>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) >) >`

The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers):
`ly:accidental-interface::height`

Hard coded extent in Y direction.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.1 [accidental-interface], page 403, Section 3.2.3 [accidental-suggestion-interface], page 405, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.89 [script-interface], page 447, Section 3.2.90 [self-alignment-interface], page 448 and Section 3.2.94 [side-position-interface], page 451.

3.1.5 Ambitus

Ambitus objects are created by: Section 2.2.2 [Ambitus_engraver], page 234.

Standard settings:

`axes` (list):
`'(0 1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`break-align-symbol` (symbol):
`'ambitus`
This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#f #f #t)`
A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`non-musical` (boolean):
`#t`
True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
`'((cue-end-clef extra-space . 0.5) (clef extra-space . 0.5) (cue-clef extra-space . 0.5) (key-signature extra-space . 0.0) (staff-bar extra-space . 0.0) (time-signature extra-space . 0.0) (first-note fixed-space . 0.0))`
A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.5 [ambitus-interface], page 405, Section 3.2.7 [axis-group-interface], page 406, Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.6 AmbitusAccidental

AmbitusAccidental objects are created by: Section 2.2.2 [Ambitus_engraver], page 234.

Standard settings:

`direction` (direction):
`-1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=1, `#DOWN`=-1, `#LEFT`=-1, `#RIGHT`=1, `#CENTER`=0.

`glyph-name-alist` (list):
`'((0 . accidentals.natural) (-1/2 . accidentals.flat) (1/2 . accidentals.sharp) (1 . accidentals.doublesharp) (-1 . accidentals.flatflat) (3/4 . accidentals.sharp.slashslash.stemstemstem) (1/4 . accidentals.sharp.slashslash.stem) (-1/4 . accidentals.mirroredflat) (-3/4 . accidentals.mirroredflat.flat))`
An alist of key-string pairs.

`padding` (dimension, in staff space):
`0.5`

Add this much extra space between objects that are next to each other.

`side-axis` (number):
`0`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`stencil` (stencil):
`ly:accidental-interface::print`

The symbol to print.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`

The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers):
`ly:accidental-interface::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.1 [accidental-interface], page 403, Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.94 [side-position-interface], page 451.

3.1.7 AmbitusLine

AmbitusLine objects are created by: Section 2.2.2 [Ambitus_engraver], page 234.

Standard settings:

`gap` (dimension, in staff space):
`0.35`

Size of a gap in a variable symbol.

`stencil` (stencil):
`ambitus::print`

The symbol to print.

`thickness` (number):
`2`

Line thickness, generally measured in `line-thickness`.

`X-offset` (number):
`ly:self-alignment-interface::centered-on-x-parent`

The horizontal amount that this object is moved relative to its X-parent.

This object supports the following interface(s): Section 3.2.5 [ambitus-interface], page 405, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.8 AmbitusNoteHead

AmbitusNoteHead objects are created by: Section 2.2.2 [Ambitus_engraver], page 234.

Standard settings:

`duration-log` (integer):
`2`
The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

`glyph-name` (string):
`note-head::calc-glyph-name`
The glyph name within the font.

`stencil` (stencil):
`ly:note-head::print`
The symbol to print.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.5 [ambitus-interface], page 405, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.52 [ledgered-interface], page 434, Section 3.2.71 [note-head-interface], page 441, Section 3.2.87 [rhythmic-head-interface], page 447 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.9 Arpeggio

Arpeggio objects are created by: Section 2.2.3 [Arpeggio_engraver], page 234 and Section 2.2.104 [Span_arpeggio_engraver], page 268.

Standard settings:

`direction` (direction):
`-1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`padding` (dimension, in staff space):
`0.5`
Add this much extra space between objects that are next to each other.

`positions` (pair of numbers):
`ly:arpeggio::calc-positions`
Pair of staff coordinates `(`*`left . right`*`)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

`script-priority` (number):
`0`
A sorting key that determines in what order a script is within a stack of scripts.

`side-axis` (number):
`0`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-position` (number):
`0.0`
Vertical position, measured in half staff spaces, counted from the middle line.

`stencil` (stencil):
`ly:arpeggio::print`
The symbol to print.

`X-extent` (pair of numbers):
`ly:arpeggio::width`
Hard coded extent in X direction.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.6 [arpeggio-interface], page 406, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.10 BalloonTextItem

BalloonTextItem objects are created by: Section 2.2.6 [Balloon_engraver], page 236.

Standard settings:

`annotation-balloon` (boolean):
`#t`
Print the balloon around an annotation.

`annotation-line` (boolean):
`#t`
Print the line from an annotation to the grob that it annotates.

`stencil` (stencil):
`ly:balloon-interface::print`
The symbol to print.

`text` (markup):
`#<procedure #f (grob)>`
Text markup. See Section “Formatting text” in *Notation Reference*.

`X-offset` (number):
`#<procedure #f (grob)>`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`#<procedure #f (grob)>`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.8 [balloon-interface], page 408, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.115 [text-interface], page 464.

3.1.11 BarLine

BarLine objects are created by: Section 2.2.7 [Bar_engraver], page 236.

Standard settings:

`allow-span-bar` (boolean):
`#t`
If false, no inter-staff bar line will be created below this bar line.

`break-align-anchor` (number):
`ly:bar-line::calc-anchor`
Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-symbol` (symbol):
`'staff-bar`
This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`bar-line::calc-break-visibility`
A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`gap` (dimension, in staff space):
`0.4`
Size of a gap in a variable symbol.

`glyph` (string):
`"|"`
A string determining what 'style' of glyph is typeset. Valid choices depend on the function that is reading this property.

`glyph-name` (string):
`bar-line::calc-glyph-name`
The glyph name within the font.

`hair-thickness` (number):
`1.9`
Thickness of the thin line in a bar line.

`kern` (dimension, in staff space):
`3.0`
Amount of extra white space to add. For bar lines, this is the amount of space after a thick line.

`layer` (integer):
`0`
An integer which determines the order of printing objects. Objects with the lowest value of layer are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a layer value of 1.

`non-musical` (boolean):
`#t`
True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
: `'((time-signature extra-space . 0.75) (custos minimum-space . 2.0) (clef minimum-space . 1.0) (key-signature extra-space . 1.0) (key-cancellation extra-space . 1.0) (first-note fixed-space . 1.3) (next-note semi-fixed-space . 0.9) (right-edge extra-space . 0.0))`

A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
: `ly:bar-line::print`

The symbol to print.

`thick-thickness` (number):
: `6.0`

Bar line thickness, measured in `line-thickness`.

`thin-kern` (number):
: `3.0`

The space after a hair-line in a bar line.

This object supports the following interface(s): Section 3.2.9 [bar-line-interface], page 409, Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.12 BarNumber

BarNumber objects are created by: Section 2.2.8 [Bar_number_engraver], page 236.

Standard settings:

`after-line-breaking` (boolean):
: `ly:side-position-interface::move-to-extremal-staff`

Dummy property, used to trigger callback for `after-line-breaking`.

`break-align-symbols` (list):
: `'(left-edge staff-bar)`

A list of symbols that determine which break-aligned grobs to align this to. If the grob selected by the first symbol in the list is invisible due to break-visibility, we will align to the next grob (and so on). Choices are `left-edge`, `ambitus`, `breathing-sign`, `clef`, `staff-bar`, `key-cancellation`, `key-signature`, `time-signature`, and `custos`.

`break-visibility` (vector):
: `#(#f #f #t)`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`direction` (direction):
: `1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-family` (symbol):
`'roman`

The font family is the broadest category for selecting text fonts. Options include: `sans`, `roman`.

`font-size` (number):
`-2`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`outside-staff-priority` (number):
`100`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`1.0`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`1`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:break-alignable-interface::self-align-callback>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) >) >`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.14 [break-alignable-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.115 [text-interface], page 464.

3.1.13 BassFigure

BassFigure objects are created by: Section 2.2.37 [Figured_bass_engraver], page 246.

Standard settings:

`stencil` (stencil):
`ly:text-interface::print`
The symbol to print.

This object supports the following interface(s): Section 3.2.11 [bass-figure-interface], page 410, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.86 [rhythmic-grob-interface], page 447 and Section 3.2.115 [text-interface], page 464.

3.1.14 BassFigureAlignment

BassFigureAlignment objects are created by: Section 2.2.37 [Figured_bass_engraver], page 246.

Standard settings:

`axes` (list):
`'(1)`
List of axis numbers. In the case of alignment grobs, this should contain only one number.

`padding` (dimension, in staff space):
`0.2`
Add this much extra space between objects that are next to each other.

`stacking-dir` (direction):
`-1`
Stack objects in which direction?

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.4 [align-interface], page 405, Section 3.2.7 [axis-group-interface], page 406, Section 3.2.10 [bass-figure-alignment-interface], page 410, Section 3.2.42 [grob-interface], page 424 and Section 3.2.101 [spanner-interface], page 457.

3.1.15 BassFigureAlignmentPositioning

BassFigureAlignmentPositioning objects are created by: Section 2.2.38 [Figured_bass_position_engraver], page 247.

Standard settings:

`axes` (list):
`'(1)`
List of axis numbers. In the case of alignment grobs, this should contain only one number.

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or

`#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`padding` (dimension, in staff space):
`0.5`

Add this much extra space between objects that are next to each other.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`1.0`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`

Hard coded extent in Y direction.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.16 BassFigureBracket

BassFigureBracket objects are created by: Section 2.2.37 [Figured_bass_engraver], page 246.

Standard settings:

`edge-height` (pair):
`'(0.2 . 0.2)`

A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`stencil` (stencil):
`ly:enclosing-bracket::print`

The symbol to print.

`X-extent` (pair of numbers):
`ly:enclosing-bracket::width`

Hard coded extent in X direction.

This object supports the following interface(s): Section 3.2.29 [enclosing-bracket-interface], page 418, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.17 BassFigureContinuation

BassFigureContinuation objects are created by: Section 2.2.37 [Figured_bass_engraver], page 246.

Standard settings:

`stencil` (stencil):
`ly:figured-bass-continuation::print`
The symbol to print.

`Y-offset` (number):
`ly:figured-bass-continuation::center-on-figures`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.31 [figured-bass-continuation-interface], page 419, Section 3.2.42 [grob-interface], page 424 and Section 3.2.101 [spanner-interface], page 457.

3.1.18 BassFigureLine

BassFigureLine objects are created by: Section 2.2.37 [Figured_bass_engraver], page 246.

Standard settings:

`axes` (list):
`'(1)`
List of axis numbers. In the case of alignment grobs, this should contain only one number.

`vertical-skylines` (pair of skylines):
`ly:axis-group-interface::calc-skylines`
Two skylines, one above and one below this grob.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424 and Section 3.2.101 [spanner-interface], page 457.

3.1.19 Beam

Beam objects are created by: Section 2.2.4 [Auto_beam_engraver], page 235, Section 2.2.10 [Beam_engraver], page 237, Section 2.2.16 [Chord_tremolo_engraver], page 239 and Section 2.2.45 [Grace_beam_engraver], page 249.

Standard settings:

`auto-knee-gap` (dimension, in staff space):
`5.5`
If a gap is found between note heads where a horizontal beam fits that is larger than this number, make a kneed beam.

`beam-thickness` (dimension, in staff space):
`0.48`
Beam thickness, measured in `staff-space` units.

`beamed-stem-shorten` (list):
`'(1.0 0.5 0.25)`
How much to shorten beamed stems, when their direction is forced. It is a list, since the value is different depending on the number of flags and beams.

`beaming` (pair):
`ly:beam::calc-beaming`

Pair of number lists. Each number list specifies which beams to make. `0` is the central beam, `1` is the next beam toward the note, etc. This information is used to determine how to connect the beaming patterns from stem to stem inside a beam.

`clip-edges` (boolean):
`#t`
Allow outward pointing beamlets at the edges of beams?

`collision-interfaces` (list):
`'(beam-interface clef-interface inline-accidental-interface key-signature-interface note-head-interface stem-interface time-signature-interface)`
A list of interfaces for which automatic beam-collision resolution is run.

`concaveness` (number):
`ly:beam::calc-concaveness`
A beam is concave if its inner stems are closer to the beam than the two outside stems. This number is a measure of the closeness of the inner stems. It is used for damping the slope of the beam.

`damping` (number):
`1`
Amount of beam slope damping.

`details` (list):
`'((secondary-beam-demerit . 10) (stem-length-demerit-factor . 5) (region-size . 2) (beam-eps . 0.001) (stem-length-limit-penalty . 5000) (damping-direction-penalty . 800) (hint-direction-penalty . 20) (musical-direction-factor . 400) (ideal-slope-factor . 10) (collision-penalty . 500) (collision-padding . 0.35) (round-to-zero-slope . 0.02))`
Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction):
`ly:beam::calc-direction`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-family` (symbol):
`'roman`
The font family is the broadest category for selecting text fonts. Options include: `sans`, `roman`.

`gap` (dimension, in staff space):
`0.8`
Size of a gap in a variable symbol.

`neutral-direction` (direction):
`-1`
Which direction to take in the center of the staff.

`normalized-endpoints` (pair):
`ly:spanner::calc-normalized-endpoints`

Represents left and right placement over the total spanner, where the width of the spanner is normalized between 0 and 1.

`positions` (pair of numbers):
`#<simple-closure #<simple-closure (#<procedure chain-grob-member-functions (grob value . funcs)> (#<primitive-procedure cons> 0 0) #<primitive-procedure ly:beam::calc-least-squares-positions> #<primitive-procedure ly:beam::slope-damping> #<primitive-procedure ly:beam::shift-region-to-valid> #<primitive-procedure ly:beam::quanting>) > >`

Pair of staff coordinates (*`left . right`*), where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

`stencil` (stencil):
`ly:beam::print`

The symbol to print.

This object supports the following interface(s): Section 3.2.12 [beam-interface], page 410, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457, Section 3.2.105 [staff-symbol-referencer-interface], page 459 and Section 3.2.124 [unbreakable-spanner-interface], page 470.

3.1.20 BendAfter

BendAfter objects are created by: Section 2.2.12 [Bend_engraver], page 238.

Standard settings:

`minimum-length` (dimension, in staff space):
`0.5`

Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`stencil` (stencil):
`bend::print`

The symbol to print.

`thickness` (number):
`2.0`

Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.13 [bend-after-interface], page 413, Section 3.2.42 [grob-interface], page 424 and Section 3.2.101 [spanner-interface], page 457.

3.1.21 BreakAlignGroup

BreakAlignGroup objects are created by: Section 2.2.13 [Break_align_engraver], page 238.

Standard settings:

`axes` (list):
`'(0)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`break-align-anchor` (number):
`ly:break-aligned-interface::calc-average-anchor`

Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-visibility` (vector):
`ly:break-aligned-interface::calc-break-visibility`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.22 BreakAlignment

BreakAlignment objects are created by: Section 2.2.13 [Break_align_engraver], page 238.

Standard settings:

`axes` (list):
`'(0)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`break-align-orders` (vector):
`#((left-edge cue-end-clef ambitus breathing-sign clef cue-clef staff-bar key-cancellation key-signature time-signature custos) (left-edge cue-end-clef ambitus breathing-sign clef cue-clef staff-bar key-cancellation key-signature time-signature custos) (left-edge ambitus breathing-sign clef key-cancellation key-signature staff-bar time-signature cue-clef custos))`

Defines the order in which prefatory matter (clefs, key signatures) appears. The format is a vector of length 3, where each element is one order for end-of-line, middle of line, and start-of-line, respectively. An order is a list of symbols.

For example, clefs are put after key signatures by setting

```
\override Score.BreakAlignment #'break-align-orders =
  #(make-vector 3 '(span-bar
                    breathing-sign
                    staff-bar
                    key
                    clef
                    time-signature))
```

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`stacking-dir` (direction):
`1`

Stack objects in which direction?

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.16 [break-alignment-interface], page 414, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.23 BreathingSign

BreathingSign objects are created by: Section 2.2.14 [Breathing_sign_engraver], page 238.

Standard settings:

`break-align-symbol` (symbol):
`'breathing-sign`

This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#t #t #f)`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
`'((ambitus extra-space . 2.0) (custos minimum-space . 1.0) (key-signature minimum-space . 1.5) (time-signature minimum-space . 1.5) (staff-bar minimum-space . 1.5) (clef minimum-space . 2.0) (cue-clef minimum-space . 2.0) (cue-end-clef minimum-space . 2.0) (first-note fixed-space . 1.0) (right-edge extra-space . 0.1))`

A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`text` (markup):
`'(#<procedure musicglyph-markup (layout props glyph-name)> scripts.rcomma)`

Text markup. See Section “Formatting text” in *Notation Reference*.

`Y-offset` (number):
`ly:breathing-sign::offset-callback`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.17 [breathing-sign-interface], page 415, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.115 [text-interface], page 464.

3.1.24 ChordName

ChordName objects are created by: Section 2.2.15 [Chord_name_engraver], page 238.

Standard settings:

`after-line-breaking` (boolean):
`ly:chord-name::after-line-breaking`

Dummy property, used to trigger callback for `after-line-breaking`.

`extra-spacing-height` (pair of numbers):
`'(0.2 . -0.2)`

In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`font-family` (symbol):
`'sans`

The font family is the broadest category for selecting text fonts. Options include: `sans`, `roman`.

`font-size` (number):
`1.5`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`word-space` (dimension, in staff space):
`0.0`

Space to insert between words in texts.

This object supports the following interface(s): Section 3.2.18 [chord-name-interface], page 415, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.86 [rhythmic-grob-interface], page 447 and Section 3.2.115 [text-interface], page 464.

3.1.25 Clef

Clef objects are created by: Section 2.2.17 [Clef_engraver], page 239.

Standard settings:

`avoid-slur` (symbol):
`'inside`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`break-align-anchor` (number):
`ly:break-aligned-interface::calc-extent-aligned-anchor`

Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-symbol` (symbol):
`'clef`

This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#f #f #t)`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`glyph-name` (string):
`ly:clef::calc-glyph-name`

The glyph name within the font.

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
`'((cue-clef extra-space . 2.0) (staff-bar extra-space . 0.7) (key-cancellation minimum-space . 3.5) (key-signature minimum-space . 3.5) (time-signature minimum-space . 4.2) (first-note minimum-fixed-space . 5.0) (next-note extra-space . 0.5) (right-edge extra-space . 0.5))`

A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
`ly:clef::print`

The symbol to print.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.19 [clef-interface], page 415, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.26 ClusterSpanner

ClusterSpanner objects are created by: Section 2.2.18 [Cluster_spanner_engraver], page 240.

Standard settings:

`minimum-length` (dimension, in staff space):
`0.0`

Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`padding` (dimension, in staff space):
`0.25`

Add this much extra space between objects that are next to each other.

`springs-and-rods` (boolean):
`ly:spanner::set-spacing-rods`

Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:cluster::print`

The symbol to print.

`style` (symbol):
`'ramp`

This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

This object supports the following interface(s): Section 3.2.21 [cluster-interface], page 416, Section 3.2.42 [grob-interface], page 424 and Section 3.2.101 [spanner-interface], page 457.

3.1.27 ClusterSpannerBeacon

ClusterSpannerBeacon objects are created by: Section 2.2.18 [Cluster_spanner_engraver], page 240.

Standard settings:

`Y-extent` (pair of numbers):
`ly:cluster-beacon::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.20 [cluster-beacon-interface], page 416, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.86 [rhythmic-grob-interface], page 447.

3.1.28 CombineTextScript

CombineTextScript objects are created by: Section 2.2.82 [Part_combine_engraver], page 261.

Standard settings:

`avoid-slur` (symbol):
`'outside`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur

only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`baseline-skip` (dimension, in staff space):
`2`
Distance between base lines of multiple lines of text.

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`
In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`font-series` (symbol):
`'bold`
Select the series of a font. Choices include `medium`, `bold`, `bold-narrow`, etc.

`outside-staff-priority` (number):
`450`
If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.5`
Add this much extra space between objects that are next to each other.

`script-priority` (number):
`200`
A sorting key that determines in what order a script is within a stack of scripts.

`side-axis` (number):
`1`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`0.5`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`
The symbol to print.

`X-offset` (number):
`ly:self-alignment-interface::x-aligned-on-self`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.94 [side-position-interface], page 451, Section 3.2.115 [text-interface], page 464 and Section 3.2.116 [text-script-interface], page 465.

3.1.29 CueClef

CueClef objects are created by: Section 2.2.23 [Cue_clef_engraver], page 241.

Standard settings:

`avoid-slur` (symbol):
`'inside`
Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`break-align-anchor` (number):
`ly:break-aligned-interface::calc-extent-aligned-anchor`
Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-symbol` (symbol):
`'cue-clef`
This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#f #f #t)`
A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`font-size` (number):
`-4`
The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`full-size-change` (boolean):
`#t`
Don't make a change clef smaller.

`glyph-name` (string):
`ly:clef::calc-glyph-name`
The glyph name within the font.

`non-musical` (boolean):
: `#t`

  True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
: `'((staff-bar minimum-space . 2.7) (key-cancellation minimum-space . 3.5) (key-signature minimum-space . 3.5) (time-signature minimum-space . 4.2) (custos minimum-space . 0.0) (first-note minimum-fixed-space . 3.0) (next-note extra-space . 0.5) (right-edge extra-space . 0.5))`

  A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
: `ly:clef::print`

  The symbol to print.

`Y-offset` (number):
: `ly:staff-symbol-referencer::callback`

  The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.19 [clef-interface], page 415, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.30 CueEndClef

CueEndClef objects are created by: Section 2.2.23 [Cue_clef_engraver], page 241.

Standard settings:

`avoid-slur` (symbol):
: `'inside`

  Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`break-align-anchor` (number):
: `ly:break-aligned-interface::calc-extent-aligned-anchor`

  Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-symbol` (symbol):
: `'cue-end-clef`

  This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
: `#(#t #t #f)`

A vector of 3 booleans, `#(end-of-line unbroken begin-of-line)`. `#t` means visible, `#f` means killed.

`font-size` (number):
`-4`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`full-size-change` (boolean):
`#t`

Don't make a change clef smaller.

`glyph-name` (string):
`ly:clef::calc-glyph-name`

The glyph name within the font.

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
`'((clef extra-space . 0.7) (cue-clef extra-space . 0.7) (staff-bar extra-space . 0.7) (key-cancellation minimum-space . 3.5) (key-signature minimum-space . 3.5) (time-signature minimum-space . 4.2) (first-note minimum-fixed-space . 5.0) (next-note extra-space . 0.5) (right-edge extra-space . 0.5))`

A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(break-align-symbol type . distance)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
`ly:clef::print`

The symbol to print.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.19 [clef-interface], page 415, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.31 Custos

Custos objects are created by: Section 2.2.24 [Custos_engraver], page 242.

Standard settings:

`break-align-symbol` (symbol):
`'custos`

This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#t #f #f)`
A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`neutral-direction` (direction):
`-1`
Which direction to take in the center of the staff.

`non-musical` (boolean):
`#t`
True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
`'((first-note minimum-fixed-space . 0.0) (right-edge extra-space . 0.1))`
A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
`ly:custos::print`
The symbol to print.

`style` (symbol):
`'vaticana`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.22 [custos-interface], page 416, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.32 DotColumn

DotColumn objects are created by: Section 2.2.26 [Dot_column_engraver], page 243 and Section 2.2.129 [Vaticana_ligature_engraver], page 275.

Standard settings:

`axes` (list):
`'(0)`
List of axis numbers. In the case of alignment grobs, this should contain only one number.

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`
Hard coded extent in X direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.23 [dot-column-interface], page 417, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.33 Dots

Dots objects are created by: Section 2.2.27 [Dots_engraver], page 243.

Standard settings:

`dot-count` (integer):
`dots::calc-dot-count`
The number of dots.

`extra-spacing-height` (pair of numbers):
`'(-0.5 . 0.5)`
In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`staff-position` (number):
`dots::calc-staff-position`
Vertical position, measured in half staff spaces, counted from the middle line.

`stencil` (stencil):
`ly:dots::print`
The symbol to print.

This object supports the following interface(s): Section 3.2.24 [dots-interface], page 417, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.34 DoublePercentRepeat

DoublePercentRepeat objects are created by: Section 2.2.28 [Double_percent_repeat_engraver], page 243.

Standard settings:

`break-align-symbol` (symbol):
`'staff-bar`
This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#t #t #f)`
A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`dot-negative-kern` (number):
`0.75`
The space to remove between a dot and a slash in percent repeat glyphs. Larger values bring the two elements closer together.

`font-encoding` (symbol):
`'fetaMusic`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`slash-negative-kern` (number):
`1.6`

The space to remove between slashes in percent repeat glyphs. Larger values bring the two elements closer together.

`slope` (number):
`1.0`

The slope of this object.

`stencil` (stencil):
`ly:percent-repeat-item-interface::double-percent`

The symbol to print.

`thickness` (number):
`0.48`

Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.78 [percent-repeat-interface], page 444 and Section 3.2.79 [percent-repeat-item-interface], page 445.

3.1.35 DoublePercentRepeatCounter

DoublePercentRepeatCounter objects are created by: Section 2.2.28 [Double_percent_repeat_engraver], page 243.

Standard settings:

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-encoding` (symbol):
`'fetaText`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`font-size` (number):
`-2`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`padding` (dimension, in staff space):
`0.2`
Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`
Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`side-axis` (number):
`1`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`0.25`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`
The symbol to print.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:self-alignment-interface::centered-on-y-parent>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) >) >`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.78 [percent-repeat-interface], page 444, Section 3.2.79 [percent-repeat-item-interface], page 445, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.115 [text-interface], page 464.

3.1.36 DoubleRepeatSlash

DoubleRepeatSlash objects are created by: Section 2.2.100 [Slash_repeat_engraver], page 267.

Standard settings:

`dot-negative-kern` (number):
`0.75`
The space to remove between a dot and a slash in percent repeat glyphs. Larger values bring the two elements closer together.

`font-encoding` (symbol):
`'fetaMusic`
The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`slash-negative-kern` (number):
`1.6`
The space to remove between slashes in percent repeat glyphs. Larger values bring the two elements closer together.

`slope` (number):
`1.0`
The slope of this object.

`stencil` (stencil):
`ly:percent-repeat-item-interface::beat-slash`
The symbol to print.

`thickness` (number):
`0.48`
Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.78 [percent-repeat-interface], page 444, Section 3.2.79 [percent-repeat-item-interface], page 445 and Section 3.2.86 [rhythmic-grob-interface], page 447.

3.1.37 DynamicLineSpanner

DynamicLineSpanner objects are created by: Section 2.2.31 [Dynamic_align_engraver], page 244 and Section 2.2.32 [Dynamic_engraver], page 245.

Standard settings:

`axes` (list):
`'(1)`
List of axis numbers. In the case of alignment grobs, this should contain only one number.

`direction` (direction):
`-1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`minimum-space` (dimension, in staff space):
`1.2`
Minimum distance that the victim should move (after padding).

`outside-staff-priority` (number):
`250`
If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.6`
Add this much extra space between objects that are next to each other.

`side-axis` (number):
`1`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`slur-padding` (number):
`0.3`
Extra distance between slur and script.

`staff-padding` (dimension, in staff space):
`0.1`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`
Hard coded extent in Y direction.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.25 [dynamic-interface], page 417, Section 3.2.26 [dynamic-line-spanner-interface], page 417, Section 3.2.42 [grob-interface], page 424, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.38 DynamicText

DynamicText objects are created by: Section 2.2.32 [Dynamic_engraver], page 245 and Section 2.2.70 [New_dynamic_engraver], page 257.

Standard settings:

`direction` (direction):
`ly:script-interface::calc-direction`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`
In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`font-encoding` (symbol):
`'fetaText`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`font-series` (symbol):
`'bold`

Select the series of a font. Choices include `medium`, `bold`, `bold-narrow`, etc.

`font-shape` (symbol):
`'italic`

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`outside-staff-priority` (number):
`250`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`right-padding` (dimension, in staff space):
`0.5`

Space to insert on the right side of an object (e.g., between note and its accidentals).

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`self-alignment-Y` (number):
`0`

Like `self-alignment-X` but for the Y axis.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`ly:self-alignment-interface::x-aligned-on-self`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:self-alignment-interface::y-aligned-on-self`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.25 [dynamic-interface], page 417, Section 3.2.27 [dynamic-text-interface], page 418, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.89 [script-interface], page 447, Section 3.2.90 [self-alignment-interface], page 448 and Section 3.2.115 [text-interface], page 464.

3.1.39 DynamicTextSpanner

DynamicTextSpanner objects are created by: Section 2.2.32 [Dynamic_engraver], page 245 and Section 2.2.70 [New_dynamic_engraver], page 257.

Standard settings:

`before-line-breaking` (boolean):
`dynamic-text-spanner::before-line-breaking`

Dummy property, used to trigger a callback function.

`bound-details` (list):
`'((right (attach-dir . -1) (Y . 0) (padding . 0.75)) (right-broken (attach-dir . 1) (padding . 0.0)) (left (attach-dir . -1) (Y . 0) (stencil-offset -0.75 . -0.5) (padding . 0.75)) (left-broken (attach-dir . 1)))`

An alist of properties for determining attachments of spanners to edges.

`dash-fraction` (number):
`0.2`

Size of the dashes, relative to `dash-period`. Should be between `0.0` (no line) and `1.0` (continuous line).

`dash-period` (number):
`3.0`

The length of one dash together with whitespace. If negative, no line is drawn at all.

`font-shape` (symbol):
`'italic`

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`font-size` (number):
`1`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`left-bound-info` (list):
`ly:line-spanner::calc-left-bound-info-and-text`

An alist of properties for determining attachments of spanners to edges.

`minimum-length` (dimension, in staff space):
`2.0`

Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`minimum-Y-extent` (pair of numbers):
`'(-1 . 1)`

Minimum size of an object in Y dimension, measured in `staff-space` units.

`right-bound-info` (list):
`ly:line-spanner::calc-right-bound-info`

An alist of properties for determining attachments of spanners to edges.

`springs-and-rods` (boolean):
`ly:spanner::set-spacing-rods`
Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:line-spanner::print`
The symbol to print.

`style` (symbol):
`'dashed-line`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

This object supports the following interface(s): Section 3.2.25 [dynamic-interface], page 417, Section 3.2.28 [dynamic-text-spanner-interface], page 418, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.57 [line-spanner-interface], page 435, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.115 [text-interface], page 464.

3.1.40 Episema

Episema objects are created by: Section 2.2.35 [Episema_engraver], page 245.

Standard settings:

`bound-details` (list):
`'((left (Y . 0) (padding . 0) (attach-dir . -1)) (right (Y . 0) (padding . 0) (attach-dir . 1)))`
An alist of properties for determining attachments of spanners to edges.

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`left-bound-info` (list):
`ly:line-spanner::calc-left-bound-info`
An alist of properties for determining attachments of spanners to edges.

`right-bound-info` (list):
`ly:line-spanner::calc-right-bound-info`
An alist of properties for determining attachments of spanners to edges.

`side-axis` (number):
`1`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`stencil` (stencil):
`ly:line-spanner::print`
The symbol to print.

`style` (symbol):
`'line`

This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.30 [episema-interface], page 419, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.57 [line-spanner-interface], page 435, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.41 Fingering

Fingering objects are created by: Section 2.2.39 [Fingering_engraver], page 247 and Section 2.2.71 [New_fingering_engraver], page 258.

Standard settings:

`avoid-slur` (symbol):
`'around`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`direction` (direction):
`ly:script-interface::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-encoding` (symbol):
`'fetaText`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`font-size` (number):
`-5`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`padding` (dimension, in staff space):
`0.5`

Add this much extra space between objects that are next to each other.

`script-priority` (number):
`100`

A sorting key that determines in what order a script is within a stack of scripts.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`self-alignment-Y` (number):
`0`

Like `self-alignment-X` but for the Y axis.

`slur-padding` (number):
`0.2`

Extra distance between slur and script.

`staff-padding` (dimension, in staff space):
`0.5`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`text` (markup):
`fingering::calc-text`

Text markup. See Section "Formatting text" in *Notation Reference*.

This object supports the following interface(s): Section 3.2.32 [finger-interface], page 419, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451, Section 3.2.115 [text-interface], page 464 and Section 3.2.116 [text-script-interface], page 465.

3.1.42 FootnoteItem

FootnoteItem objects are created by: Section 2.2.41 [Footnote_engraver], page 247.

Standard settings:

`annotation-balloon` (boolean)
Print the balloon around an annotation.

`annotation-line` (boolean):
`#t`

Print the line from an annotation to the grob that it annotates.

`break-visibility` (vector):
`inherit-y-parent-visibility`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`footnote-text` (markup):
`#<procedure #f (grob)>`

A footnote for the grob.

`stencil` (stencil):
`ly:balloon-interface::print`
The symbol to print.

`text` (markup):
`#<procedure #f (grob)>`
Text markup. See Section "Formatting text" in *Notation Reference*.

`X-offset` (number):
`#<procedure #f (grob)>`
The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

`Y-offset` (number):
`#<procedure #f (grob)>`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.8 [balloon-interface], page 408, Section 3.2.33 [font-interface], page 419, Section 3.2.34 [footnote-interface], page 421, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.115 [text-interface], page 464.

3.1.43 FootnoteSpanner

FootnoteSpanner objects are created by: Section 2.2.41 [Footnote_engraver], page 247.

Standard settings:

`annotation-balloon` (boolean)
Print the balloon around an annotation.

`annotation-line` (boolean):
`#t`
Print the line from an annotation to the grob that it annotates.

`footnote-text` (markup):
`#<procedure #f (grob)>`
A footnote for the grob.

`stencil` (stencil):
`ly:balloon-interface::print-spanner`
The symbol to print.

`text` (markup):
`#<procedure #f (grob)>`
Text markup. See Section "Formatting text" in *Notation Reference*.

`X-offset` (number):
`#<procedure #f (grob)>`
The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

`Y-offset` (number):
`#<procedure #f (grob)>`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.8 [balloon-interface], page 408, Section 3.2.33 [font-interface], page 419, Section 3.2.34 [footnote-interface], page 421, Section 3.2.35 [footnote-spanner-interface], page 421, Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.115 [text-interface], page 464.

3.1.44 FretBoard

FretBoard objects are created by: Section 2.2.43 [Fretboard_engraver], page 248.

Standard settings:

`after-line-breaking` (boolean):
`ly:chord-name::after-line-breaking`

Dummy property, used to trigger callback for `after-line-breaking`.

`extra-spacing-height` (pair of numbers):
`'(0.2 . -0.2)`

In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`fret-diagram-details` (list):
`'((finger-code . below-string))`

An alist of detailed grob properties for fret diagrams. Each alist entry consists of a `(property . value)` pair. The properties which can be included in `fret-diagram-details` include the following:

- `barre-type` – Type of barre indication used. Choices include `curved`, `straight`, and `none`. Default `curved`.
- `capo-thickness` – Thickness of capo indicator, in multiples of fret-space. Default value 0.5.
- `dot-color` – Color of dots. Options include `black` and `white`. Default `black`.
- `dot-label-font-mag` – Magnification for font used to label fret dots. Default value 1.
- `dot-position` – Location of dot in fret space. Default 0.6 for dots without labels, 0.95-`dot-radius` for dots with labels.
- `dot-radius` – Radius of dots, in terms of fret spaces. Default value 0.425 for labeled dots, 0.25 for unlabeled dots.
- `finger-code` – Code for the type of fingering indication used. Options include `none`, `in-dot`, and `below-string`. Default `none` for markup fret diagrams, `below-string` for `FretBoards` fret diagrams.
- `fret-count` – The number of frets. Default 4.
- `fret-label-custom-format` – The format string to be used label the lowest fret number, when `number-type` equals to `custom`. Default `"~a"`.
- `fret-label-font-mag` – The magnification of the font used to label the lowest fret number. Default 0.5.
- `fret-label-vertical-offset` – The offset of the fret label from the center of the fret in direction parallel to strings. Default 0.

- `label-dir` – Side to which the fret label is attached. `-1`, `#LEFT`, or `#DOWN` for left or down; `1`, `#RIGHT`, or `#UP` for right or up. Default `#RIGHT`.
- `mute-string` – Character string to be used to indicate muted string. Default `"x"`.
- `number-type` – Type of numbers to use in fret label. Choices include `roman-lower`, `roman-upper`, `arabic` and `custom`. In the later case, the format string is supplied by the `fret-label-custom-format` property. Default `roman-lower`.
- `open-string` – Character string to be used to indicate open string. Default `"o"`.
- `orientation` – Orientation of fret-diagram. Options include `normal`, `landscape`, and `opposing-landscape`. Default `normal`.
- `string-count` – The number of strings. Default 6.
- `string-label-font-mag` – The magnification of the font used to label fingerings at the string, rather than in the dot. Default value 0.6 for `normal` orientation, 0.5 for `landscape` and `opposing-landscape`.
- `string-thickness-factor` – Factor for changing thickness of each string in the fret diagram. Thickness of string k is given by `thickness` * (1+`string-thickness-factor`) ^ (k-1). Default 0.
- `top-fret-thickness` – The thickness of the top fret line, as a multiple of the standard thickness. Default value 3.
- `xo-font-magnification` – Magnification used for mute and open string indicators. Default value 0.5.
- `xo-padding` – Padding for open and mute indicators from top fret. Default value 0.25.

`stencil` (stencil):
`fret-board::calc-stencil`

The symbol to print.

This object supports the following interface(s): Section 3.2.18 [chord-name-interface], page 415, Section 3.2.33 [font-interface], page 419, Section 3.2.36 [fret-diagram-interface], page 421, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.86 [rhythmic-grob-interface], page 447.

3.1.45 Glissando

Glissando objects are created by: Section 2.2.44 [Glissando_engraver], page 249 and Section 2.2.72 [Note_head_line_engraver], page 258.

Standard settings:

`after-line-breaking` (boolean):
`ly:spanner::kill-zero-spanned-time`

Dummy property, used to trigger callback for `after-line-breaking`.

`bound-details` (list):
`'((right (attach-dir . 0) (padding . 1.5)) (left (attach-dir . 0) (padding . 1.5)))`

An alist of properties for determining attachments of spanners to edges.

`gap` (dimension, in staff space):
`0.5`
Size of a gap in a variable symbol.

`left-bound-info` (list):
`ly:line-spanner::calc-left-bound-info`
An alist of properties for determining attachments of spanners to edges.

`normalized-endpoints` (pair):
`ly:spanner::calc-normalized-endpoints`
Represents left and right placement over the total spanner, where the width of the spanner is normalized between 0 and 1.

`right-bound-info` (list):
`ly:line-spanner::calc-right-bound-info`
An alist of properties for determining attachments of spanners to edges.

`stencil` (stencil):
`ly:line-spanner::print`
The symbol to print.

`style` (symbol):
`'line`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`X-extent` (pair of numbers)
Hard coded extent in X direction.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

`zigzag-width` (dimension, in staff space):
`0.75`
The width of one zigzag squiggle. This number is adjusted slightly so that the glissando line can be constructed from a whole number of squiggles.

This object supports the following interface(s): Section 3.2.37 [glissando-interface], page 423, Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.57 [line-spanner-interface], page 435, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.124 [unbreakable-spanner-interface], page 470.

3.1.46 GraceSpacing

GraceSpacing objects are created by: Section 2.2.47 [Grace_spacing_engraver], page 250.

Standard settings:

`common-shortest-duration` (moment):
`grace-spacing::calc-shortest-duration`
The most common shortest note length. This is used in spacing. Enlarging this sets the score tighter.

`shortest-duration-space` (dimension, in staff space):
`1.6`
Start with this much space for the shortest duration. This is expressed in `spacing-increment` as unit. See also Section "spacing-spanner-interface" in *Internals Reference*.

`spacing-increment` (number):
`0.8`
Add this much space for a doubled duration. Typically, the width of a note head. See also Section "spacing-spanner-interface" in *Internals Reference*.

This object supports the following interface(s): Section 3.2.38 [grace-spacing-interface], page 423, Section 3.2.42 [grob-interface], page 424, Section 3.2.98 [spacing-options-interface], page 455 and Section 3.2.101 [spanner-interface], page 457.

3.1.47 GridLine

GridLine objects are created by: Section 2.2.48 [Grid_line_span_engraver], page 250.

Standard settings:

`layer` (integer):
`0`
An integer which determines the order of printing objects. Objects with the lowest value of layer are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a layer value of 1.

`self-alignment-X` (number):
`0`
Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`stencil` (stencil):
`ly:grid-line-interface::print`
The symbol to print.

`X-extent` (pair of numbers):
`ly:grid-line-interface::width`
Hard coded extent in X direction.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:self-alignment-interface::centered-on-x-parent>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) >) >`
The horizontal amount that this object is moved relative to its X-parent.

This object supports the following interface(s): Section 3.2.40 [grid-line-interface], page 424, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.90 [self-alignment-interface], page 448.

3.1.48 GridPoint

GridPoint objects are created by: Section 2.2.49 [Grid_point_engraver], page 250.

Standard settings:

`X-extent` (pair of numbers):
`'(0 . 0)`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`'(0 . 0)`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.41 [grid-point-interface], page 424, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.49 Hairpin

Hairpin objects are created by: Section 2.2.32 [Dynamic_engraver], page 245 and Section 2.2.70 [New_dynamic_engraver], page 257.

Standard settings:

`after-line-breaking` (boolean):
`ly:spanner::kill-zero-spanned-time`
Dummy property, used to trigger callback for `after-line-breaking`.

`bound-padding` (number):
`1.0`
The amount of padding to insert around spanner bounds.

`circled-tip` (boolean)
Put a circle at start/end of hairpins (al/del niente).

`grow-direction` (direction):
`hairpin::calc-grow-direction`
Crescendo or decrescendo?

`height` (dimension, in staff space):
`0.6666`
Height of an object in `staff-space` units.

`minimum-length` (dimension, in staff space):
`2.0`
Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`self-alignment-Y` (number):
`0`
Like `self-alignment-X` but for the Y axis.

`springs-and-rods` (boolean):
`ly:spanner::set-spacing-rods`
Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:hairpin::print`
The symbol to print.

`thickness` (number):
`1.0`
Line thickness, generally measured in `line-thickness`.

`to-barline` (boolean):
`#t`

If true, the spanner will stop at the bar line just before it would otherwise stop.

`Y-offset` (number):
`ly:self-alignment-interface::y-aligned-on-self`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.25 [dynamic-interface], page 417, Section 3.2.42 [grob-interface], page 424, Section 3.2.43 [hairpin-interface], page 428, Section 3.2.56 [line-interface], page 435, Section 3.2.90 [self-alignment-interface], page 448 and Section 3.2.101 [spanner-interface], page 457.

3.1.50 HorizontalBracket

HorizontalBracket objects are created by: Section 2.2.52 [Horizontal_bracket_engraver], page 251.

Standard settings:

`bracket-flare` (pair of numbers):
`'(0.5 . 0.5)`

A pair of numbers specifying how much edges of brackets should slant outward. Value `0.0` means straight edges.

`connect-to-neighbor` (pair):
`ly:tuplet-bracket::calc-connect-to-neighbors`

Pair of booleans, indicating whether this grob looks as a continued break.

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`padding` (dimension, in staff space):
`0.2`

Add this much extra space between objects that are next to each other.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`0.2`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:horizontal-bracket::print`

The symbol to print.

`thickness` (number):
`1.0`
Line thickness, generally measured in `line-thickness`.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.45 [horizontal-bracket-interface], page 429, Section 3.2.56 [line-interface], page 435, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.51 InstrumentName

InstrumentName objects are created by: Section 2.2.54 [Instrument_name_engraver], page 251.

Standard settings:

`direction` (direction):
`-1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`padding` (dimension, in staff space):
`0.3`
Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`
Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`self-alignment-Y` (number):
`0`
Like `self-alignment-X` but for the Y axis.

`stencil` (stencil):
`system-start-text::print`
The symbol to print.

`X-offset` (number):
`system-start-text::calc-x-offset`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`system-start-text::calc-y-offset`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.113 [system-start-text-interface], page 464.

3.1.52 InstrumentSwitch

InstrumentSwitch objects are created by: Section 2.2.55 [Instrument_switch_engraver], page 252.

Standard settings:

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`outside-staff-priority` (number):
`500`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.5`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`-1`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`0.5`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`ly:self-alignment-interface::x-aligned-on-self`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.115 [text-interface], page 464.

3.1.53 KeyCancellation

KeyCancellation objects are created by: Section 2.2.57 [Key_engraver], page 252.

Standard settings:

`break-align-symbol` (symbol):
`'key-cancellation`

This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#t #t #f)`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`extra-spacing-width` (pair of numbers):
`'(0.0 . 0.5)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`glyph-name-alist` (list):
`'((0 . accidentals.natural))`

An alist of key-string pairs.

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
`'((time-signature extra-space . 1.25) (staff-bar extra-space . 0.6) (key-signature extra-space . 0.5) (cue-clef extra-space . 0.5) (right-edge extra-space . 0.5) (first-note fixed-space . 2.5))`

A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
`ly:key-signature-interface::print`

The symbol to print.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.49 [key-cancellation-interface], page 433, Section 3.2.50 [key-signature-interface], page 433 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.54 KeySignature

KeySignature objects are created by: Section 2.2.57 [Key_engraver], page 252.

Standard settings:

`avoid-slur` (symbol):
`'inside`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`break-align-anchor` (number):
`ly:break-aligned-interface::calc-extent-aligned-anchor`

Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-symbol` (symbol):
`'key-signature`

This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#f #f #t)`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`extra-spacing-width` (pair of numbers):
`'(0.0 . 0.5)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`glyph-name-alist` (list):
`'((0 . accidentals.natural) (-1/2 . accidentals.flat) (1/2 . accidentals.sharp) (1 . accidentals.doublesharp) (-1 . accidentals.flatflat) (3/4 . accidentals.sharp.slashslash.stemstemstem) (1/4 . accidentals.sharp.slashslash.stem) (-1/4 . accidentals.mirroredflat) (-3/4 . accidentals.mirroredflat.flat))`

An alist of key-string pairs.

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
`'((time-signature extra-space . 1.15) (staff-bar extra-space . 1.1) (cue-clef extra-space . 0.5) (right-edge extra-space . 0.5) (first-note fixed-space . 2.5))`

A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
`ly:key-signature-interface::print`

The symbol to print.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.50 [key-signature-interface], page 433 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.55 LaissezVibrerTie

LaissezVibrerTie objects are created by: Section 2.2.59 [Laissez_vibrer_engraver], page 254.

Standard settings:

`control-points` (list):
`ly:semi-tie::calc-control-points`

List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`details` (list):
`'((ratio . 0.333) (height-limit . 1.0))`

Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction):
`ly:tie::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=1, `#DOWN`=-1, `#LEFT`=-1, `#RIGHT`=1, `#CENTER`=0.

`extra-spacing-height` (pair of numbers):
`'(-0.5 . 0.5)`

In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`head-direction` (direction):
`-1`
Are the note heads left or right in a semitie?

`stencil` (stencil):
`laissez-vibrer::print`
The symbol to print.

`thickness` (number):
`1.0`
Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.92 [semi-tie-interface], page 449.

3.1.56 LaissezVibrerTieColumn

LaissezVibrerTieColumn objects are created by: Section 2.2.59 [Laissez_vibrer_engraver], page 254.

Standard settings:

`head-direction` (direction):
`ly:semi-tie-column::calc-head-direction`
Are the note heads left or right in a semitie?

`X-extent` (pair of numbers)
Hard coded extent in X direction.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.91 [semi-tie-column-interface], page 449.

3.1.57 LedgerLineSpanner

LedgerLineSpanner objects are created by: Section 2.2.60 [Ledger_line_engraver], page 254.

Standard settings:

`layer` (integer):
`0`
An integer which determines the order of printing objects. Objects with the lowest value of layer are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a layer value of 1.

`length-fraction` (number):
`0.25`
Multiplier for lengths. Used for determining ledger lines and stem lengths.

`minimum-length-fraction` (number):
`0.25`
Minimum length of ledger line as fraction of note head size.

`springs-and-rods` (boolean):
`ly:ledger-line-spanner::set-spacing-rods`
Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:ledger-line-spanner::print`
The symbol to print.

`X-extent` (pair of numbers)
Hard coded extent in X direction.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.51 [ledger-line-spanner-interface], page 434 and Section 3.2.101 [spanner-interface], page 457.

3.1.58 LeftEdge

LeftEdge objects are created by: Section 2.2.13 [Break_align_engraver], page 238.

Standard settings:

`break-align-anchor` (number):
`ly:break-aligned-interface::calc-extent-aligned-anchor`
Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-symbol` (symbol):
`'left-edge`
This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
`#(#t #f #t)`
A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`extra-spacing-height` (pair of numbers):
`'(+inf.0 . -inf.0)`
In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`non-musical` (boolean):
`#t`
True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
`'((ambitus extra-space . 2.0) (breathing-sign minimum-space . 0.0) (cue-end-clef extra-space . 0.8) (clef extra-space . 0.8) (cue-clef extra-space . 0.8) (staff-bar extra-space . 0.0) (key-cancellation extra-space . 0.0) (key-signature extra-space . 0.8) (time-signature extra-space . 1.0) (custos extra-space . 0.0) (first-note fixed-space . 2.0) (right-edge extra-space . 0.0))`
A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`X-extent` (pair of numbers):
`'(0 . 0)`

Hard coded extent in X direction.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.42 [grob-interface], page 424 and Section 3.2.48 [item-interface], page 432.

3.1.59 LigatureBracket

LigatureBracket objects are created by: Section 2.2.61 [Ligature_bracket_engraver], page 254.

Standard settings:

`connect-to-neighbor` (pair):
`ly:tuplet-bracket::calc-connect-to-neighbors`

Pair of booleans, indicating whether this grob looks as a continued break.

`control-points` (list):
`ly:tuplet-bracket::calc-control-points`

List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`edge-height` (pair):
`'(0.7 . 0.7)`

A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`padding` (dimension, in staff space):
`2.0`

Add this much extra space between objects that are next to each other.

`positions` (pair of numbers):
`ly:tuplet-bracket::calc-positions`

Pair of staff coordinates `(`*`left . right`*`)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

`shorten-pair` (pair of numbers):
`'(-0.2 . -0.2)`

The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`staff-padding` (dimension, in staff space):
`0.25`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:tuplet-bracket::print`
The symbol to print.

`thickness` (number):
`1.6`
Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.122 [tuplet-bracket-interface], page 468.

3.1.60 LyricExtender

LyricExtender objects are created by: Section 2.2.36 [Extender_engraver], page 246.

Standard settings:

`minimum-length` (dimension, in staff space):
`1.5`
Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`stencil` (stencil):
`ly:lyric-extender::print`
The symbol to print.

`thickness` (number):
`0.8`
Line thickness, generally measured in `line-thickness`.

`Y-extent` (pair of numbers):
`'(0 . 0)`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.58 [lyric-extender-interface], page 436, Section 3.2.60 [lyric-interface], page 437 and Section 3.2.101 [spanner-interface], page 457.

3.1.61 LyricHyphen

LyricHyphen objects are created by: Section 2.2.53 [Hyphen_engraver], page 251.

Standard settings:

`after-line-breaking` (boolean):
`ly:spanner::kill-zero-spanned-time`
Dummy property, used to trigger callback for `after-line-breaking`.

`dash-period` (number):
`10.0`
The length of one dash together with whitespace. If negative, no line is drawn at all.

`height` (dimension, in staff space):
`0.42`

Height of an object in `staff-space` units.

`length` (dimension, in staff space):
`0.66`

User override for the stem length of unbeamed stems.

`minimum-distance` (dimension, in staff space):
`0.1`

Minimum distance between rest and notes or beam.

`minimum-length` (dimension, in staff space):
`0.3`

Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`padding` (dimension, in staff space):
`0.07`

Add this much extra space between objects that are next to each other.

`springs-and-rods` (boolean):
`ly:lyric-hyphen::set-spacing-rods`

Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:lyric-hyphen::print`

The symbol to print.

`thickness` (number):
`1.3`

Line thickness, generally measured in `line-thickness`.

`Y-extent` (pair of numbers):
`'(0 . 0)`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.59 [lyric-hyphen-interface], page 437, Section 3.2.60 [lyric-interface], page 437 and Section 3.2.101 [spanner-interface], page 457.

3.1.62 LyricSpace

LyricSpace objects are created by: Section 2.2.53 [Hyphen_engraver], page 251.

Standard settings:

`minimum-distance` (dimension, in staff space):
`0.45`

Minimum distance between rest and notes or beam.

`padding` (dimension, in staff space):
`0.0`

Add this much extra space between objects that are next to each other.

`springs-and-rods` (boolean):
`ly:lyric-hyphen::set-spacing-rods`
Dummy variable for triggering spacing routines.

`X-extent` (pair of numbers)
Hard coded extent in X direction.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.59 [lyric-hyphen-interface], page 437 and Section 3.2.101 [spanner-interface], page 457.

3.1.63 LyricText

LyricText objects are created by: Section 2.2.62 [Lyric_engraver], page 254.

Standard settings:

`extra-spacing-height` (pair of numbers):
`'(0.2 . -0.2)`
In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`extra-spacing-width` (pair of numbers):
`'(0.0 . 0.0)`
In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`font-series` (symbol):
`'medium`
Select the series of a font. Choices include `medium`, `bold`, `bold-narrow`, etc.

`font-size` (number):
`1.0`
The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`self-alignment-X` (number):
`0`
Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`stencil` (stencil):
`lyric-text::print`
The symbol to print.

`text` (markup):
`#<procedure #f (grob)>`
Text markup. See Section "Formatting text" in *Notation Reference*.

`word-space` (dimension, in staff space):
`0.6`
Space to insert between words in texts.

`X-offset` (number):
`ly:self-alignment-interface::aligned-on-x-parent`
The horizontal amount that this object is moved relative to its X-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.61 [lyric-syllable-interface], page 437, Section 3.2.86 [rhythmic-grob-interface], page 447, Section 3.2.90 [self-alignment-interface], page 448 and Section 3.2.115 [text-interface], page 464.

3.1.64 MeasureGrouping

MeasureGrouping objects are created by: Section 2.2.65 [Measure_grouping_engraver], page 255.

Standard settings:

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`height` (dimension, in staff space):
`2.0`
Height of an object in `staff-space` units.

`padding` (dimension, in staff space):
`2`
Add this much extra space between objects that are next to each other.

`side-axis` (number):
`1`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`3`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:measure-grouping::print`
The symbol to print.

`thickness` (number):
`1`
Line thickness, generally measured in `line-thickness`.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.63 [measure-grouping-interface], page 437, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.65 MelodyItem

MelodyItem objects are created by: Section 2.2.66 [Melody_engraver], page 256.

Standard settings:

`neutral-direction` (direction):
`-1`
Which direction to take in the center of the staff.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.64 [melody-spanner-interface], page 438.

3.1.66 MensuralLigature

MensuralLigature objects are created by: Section 2.2.67 [Mensural_ligature_engraver], page 256.

Standard settings:

`stencil` (stencil):
`ly:mensural-ligature::print`
The symbol to print.

`thickness` (number):
`1.4`
Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.65 [mensural-ligature-interface], page 438 and Section 3.2.101 [spanner-interface], page 457.

3.1.67 MetronomeMark

MetronomeMark objects are created by: Section 2.2.68 [Metronome_mark_engraver], page 256.

Standard settings:

`after-line-breaking` (boolean):
`ly:side-position-interface::move-to-extremal-staff`
Dummy property, used to trigger callback for `after-line-breaking`.

`break-align-symbols` (list):
`'(time-signature)`
A list of symbols that determine which break-aligned grobs to align this to. If the grob selected by the first symbol in the list is invisible due to break-visibility, we will align to the next grob (and so on). Choices are `left-edge`, `ambitus`, `breathing-sign`, `clef`, `staff-bar`, `key-cancellation`, `key-signature`, `time-signature`, and `custos`.

`break-visibility` (vector):
`#(#f #t #t)`
A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`non-break-align-symbols` (list):
`'(multi-measure-rest-interface)`

A list of symbols that determine which NON-break-aligned interfaces to align this to.

`outside-staff-priority` (number):
`1000`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.8`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`-1`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:break-alignable-interface::self-align-callback>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) >) >`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.14 [break-alignable-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424,

Section 3.2.48 [item-interface], page 432, Section 3.2.66 [metronome-mark-interface], page 439, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.115 [text-interface], page 464.

3.1.68 MultiMeasureRest

MultiMeasureRest objects are created by: Section 2.2.69 [Multi_measure_rest_engraver], page 257.

Standard settings:

`expand-limit` (integer):
`10`
Maximum number of measures expanded in church rests.

`hair-thickness` (number):
`2.0`
Thickness of the thin line in a bar line.

`padding` (dimension, in staff space):
`1`
Add this much extra space between objects that are next to each other.

`spacing-pair` (pair):
`'(break-alignment . break-alignment)`
A pair of alignment symbols which set an object's spacing relative to its left and right `BreakAlignment`s.
For example, a `MultiMeasureRest` will ignore prefatory items at its bounds (i.e., clefs, key signatures and time signatures) using the following override:

```
\override MultiMeasureRest #'spacing-pair = #'(staff-bar . staff-bar)
```

`springs-and-rods` (boolean):
`ly:multi-measure-rest::set-spacing-rods`
Dummy variable for triggering spacing routines.

`staff-position` (number):
`0`
Vertical position, measured in half staff spaces, counted from the middle line.

`stencil` (stencil):
`ly:multi-measure-rest::print`
The symbol to print.

`thick-thickness` (number):
`6.6`
Bar line thickness, measured in `line-thickness`.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.67 [multi-measure-interface], page 439, Section 3.2.68 [multi-measure-rest-interface], page 439, Section 3.2.85 [rest-interface], page 446, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.69 MultiMeasureRestNumber

MultiMeasureRestNumber objects are created by: Section 2.2.69 [Multi_measure_rest_engraver], page 257.

Standard settings:

`bound-padding` (number):
`2.0`

The amount of padding to insert around spanner bounds.

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`font-encoding` (symbol):
`'fetaText`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`padding` (dimension, in staff space):
`0.4`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`springs-and-rods` (boolean):
`ly:multi-measure-rest::set-text-rods`

Dummy variable for triggering spacing routines.

`staff-padding` (dimension, in staff space):
`0.4`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-centered-on-y-parent>) >) >`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.67 [multi-measure-interface], page 439, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.115 [text-interface], page 464.

3.1.70 MultiMeasureRestText

MultiMeasureRestText objects are created by: Section 2.2.69 [Multi_measure_rest_engraver], page 257.

Standard settings:

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`outside-staff-priority` (number):
`450`
If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.2`
Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`
Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`staff-padding` (dimension, in staff space):
`0.25`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`
The symbol to print.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-centered-on-y-parent>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) >) >`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.67 [multi-measure-interface], page 439, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.115 [text-interface], page 464.

3.1.71 NonMusicalPaperColumn

NonMusicalPaperColumn objects are created by: Section 2.2.80 [Paper_column_engraver], page 261.

Standard settings:

`allow-loose-spacing` (boolean):
`#t`

If set, column can be detached from main spacing.

`axes` (list):
`'(0)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`before-line-breaking` (boolean):
`ly:paper-column::before-line-breaking`

Dummy property, used to trigger a callback function.

`full-measure-extra-space` (number):
`1.0`

Extra space that is allocated at the beginning of a measure with only one note. This property is read from the NonMusicalPaperColumn that begins the measure.

`horizontal-skylines` (pair of skylines):
`ly:separation-item::calc-skylines`

Two skylines, one to the left and one to the right of this grob.

`keep-inside-line` (boolean):
`#t`

If set, this column cannot have objects sticking into the margin.

`line-break-permission` (symbol):
`'allow`

Instructs the line breaker on whether to put a line break at this column. Can be `force` or `allow`.

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`page-break-permission` (symbol):
`'allow`

Instructs the page breaker on whether to put a page break at this column. Can be `force` or `allow`.

`skyline-vertical-padding` (number):
`0.6`

The amount by which the left and right skylines of a column are padded vertically, beyond the `Y-extents` and `extra-spacing-heights` of the constituent grobs in the column. Increase this to prevent interleaving of grobs from adjacent columns.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.76 [paper-column-interface], page 443, Section 3.2.93 [separation-item-interface], page 450 and Section 3.2.96 [spaceable-grob-interface], page 454.

3.1.72 NoteCollision

NoteCollision objects are created by: Section 2.2.19 [Collision_engraver], page 240.

Standard settings:

`axes` (list):
`'(0 1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`prefer-dotted-right` (boolean):
`#t`

For note collisions, prefer to shift dotted up-note to the right, rather than shifting just the dot.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.69 [note-collision-interface], page 440.

3.1.73 NoteColumn

NoteColumn objects are created by: Section 2.2.94 [Rhythmic_column_engraver], page 265.

Standard settings:

`axes` (list):
`'(0 1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`horizontal-skylines` (pair of skylines):
`ly:separation-item::calc-skylines`

Two skylines, one to the left and one to the right of this grob.

`skyline-vertical-padding` (number):
`0.15`

The amount by which the left and right skylines of a column are padded vertically, beyond the `Y-extent`s and `extra-spacing-height`s of the constituent grobs in the column. Increase this to prevent interleaving of grobs from adjacent columns.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.70 [note-column-interface], page 440 and Section 3.2.93 [separation-item-interface], page 450.

3.1.74 NoteHead

NoteHead objects are created by: Section 2.2.20 [Completion_heads_engraver], page 240, Section 2.2.30 [Drum_notes_engraver], page 244 and Section 2.2.73 [Note_heads_engraver], page 259.

Standard settings:

`duration-log` (integer):
`note-head::calc-duration-log`

The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

`extra-spacing-height` (pair of numbers):
`ly:note-head::include-ledger-line-height`

In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`glyph-name` (string):
`note-head::calc-glyph-name`

The glyph name within the font.

`stem-attachment` (pair of numbers):
`ly:note-head::calc-stem-attachment`

An `(x . y)` pair where the stem attaches to the notehead.

`stencil` (stencil):
`ly:note-head::print`
The symbol to print.

`X-offset` (number):
`ly:note-head::stem-x-shift`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.39 [gregorian-ligature-interface], page 423, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.52 [ledgered-interface], page 434, Section 3.2.54 [ligature-head-interface], page 435, Section 3.2.65 [mensural-ligature-interface], page 438, Section 3.2.71 [note-head-interface], page 441, Section 3.2.86 [rhythmic-grob-interface], page 447, Section 3.2.87 [rhythmic-head-interface], page 447, Section 3.2.105 [staff-symbol-referencer-interface], page 459 and Section 3.2.125 [vaticana-ligature-interface], page 470.

3.1.75 NoteName

NoteName objects are created by: Section 2.2.74 [Note_name_engraver], page 259.

Standard settings:

`stencil` (stencil):
`ly:text-interface::print`
The symbol to print.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.72 [note-name-interface], page 441 and Section 3.2.115 [text-interface], page 464.

3.1.76 NoteSpacing

NoteSpacing objects are created by: Section 2.2.76 [Note_spacing_engraver], page 259.

Standard settings:

`knee-spacing-correction` (number):
`1.0`
Factor for the optical correction amount for kneed beams. Set between `0` for no correction and `1` for full correction.

`same-direction-correction` (number):
`0.25`
Optical correction amount for stems that are placed in tight configurations. This amount is used for stems with the same direction to compensate for note head to stem distance.

`space-to-barline` (boolean):
`#t`
If set, the distance between a note and the following non-musical column will be measured to the bar line instead of to the beginning of the non-musical column. If there is a clef change followed by a bar line, for example, this means that we will try to space the non-musical column as though the clef is not there.

`stem-spacing-correction` (number):
`0.5`
Optical correction amount for stems that are placed in tight configurations. For opposite directions, this amount is the correction for two normal sized stems that overlap completely.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.73 [note-spacing-interface], page 441 and Section 3.2.97 [spacing-interface], page 455.

3.1.77 OctavateEight

OctavateEight objects are created by: Section 2.2.17 [Clef_engraver], page 239 and Section 2.2.23 [Cue_clef_engraver], page 241.

Standard settings:

`break-visibility` (vector):
`inherit-x-parent-visibility`
A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`font-shape` (symbol):
`'italic`
Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`font-size` (number):
`-4`
The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`self-alignment-X` (number):
`0`
Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`staff-padding` (dimension, in staff space):
`0.2`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`
The symbol to print.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::centered-on-x-parent>) >) >`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.115 [text-interface], page 464.

3.1.78 OttavaBracket

OttavaBracket objects are created by: Section 2.2.77 [Ottava_spanner_engraver], page 260.

Standard settings:

`dash-fraction` (number):
`0.3`

Size of the dashes, relative to `dash-period`. Should be between `0.0` (no line) and `1.0` (continuous line).

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`edge-height` (pair):
`'(0 . 1.2)`

A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`font-shape` (symbol):
`'italic`

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`minimum-length` (dimension, in staff space):
`1.0`

Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`outside-staff-priority` (number):
`400`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.5`

Add this much extra space between objects that are next to each other.

`shorten-pair` (pair of numbers):
`'(0.0 . -0.6)`

The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`staff-padding` (dimension, in staff space):
`1.0`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:ottava-bracket::print`

The symbol to print.

`style` (symbol):
`'dashed-line`

This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.45 [horizontal-bracket-interface], page 429, Section 3.2.56 [line-interface], page 435, Section 3.2.75 [ottava-bracket-interface], page 442, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.115 [text-interface], page 464.

3.1.79 PaperColumn

PaperColumn objects are created by: Section 2.2.80 [Paper_column_engraver], page 261.

Standard settings:

`allow-loose-spacing` (boolean):
`#t`

If set, column can be detached from main spacing.

`axes` (list):
`'(0)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`before-line-breaking` (boolean):
`ly:paper-column::before-line-breaking`

Dummy property, used to trigger a callback function.

`horizontal-skylines` (pair of skylines):
`ly:separation-item::calc-skylines`

Two skylines, one to the left and one to the right of this grob.

`keep-inside-line` (boolean):
`#t`

If set, this column cannot have objects sticking into the margin.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.76 [paper-column-interface], page 443, Section 3.2.93 [separation-item-interface], page 450 and Section 3.2.96 [spaceable-grob-interface], page 454.

3.1.80 ParenthesesItem

ParenthesesItem objects are created by: Section 2.2.81 [Parenthesis_engraver], page 261.

Standard settings:

`font-size` (number):
`-6`
The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`padding` (dimension, in staff space):
`0.2`
Add this much extra space between objects that are next to each other.

`stencil` (stencil):
`parentheses-item::print`
The symbol to print.

`stencils` (list):
`parentheses-item::calc-parenthesis-stencils`
Multiple stencils, used as intermediate value.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.77 [parentheses-interface], page 444.

3.1.81 PercentRepeat

PercentRepeat objects are created by: Section 2.2.83 [Percent_repeat_engraver], page 262.

Standard settings:

`dot-negative-kern` (number):
`0.75`
The space to remove between a dot and a slash in percent repeat glyphs. Larger values bring the two elements closer together.

`font-encoding` (symbol):
`'fetaMusic`
The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`slope` (number):
`1.0`
The slope of this object.

`spacing-pair` (pair):
`'(break-alignment . staff-bar)`
A pair of alignment symbols which set an object's spacing relative to its left and right `BreakAlignment`s.

For example, a `MultiMeasureRest` will ignore prefatory items at its bounds (i.e., clefs, key signatures and time signatures) using the following override:

```
\override MultiMeasureRest #'spacing-pair = #'(staff-bar . staff-bar)
```

`springs-and-rods` (boolean):
`ly:multi-measure-rest::set-spacing-rods`

Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:multi-measure-rest::percent`

The symbol to print.

`thickness` (number):
`0.48`

Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.68 [multi-measure-rest-interface], page 439, Section 3.2.78 [percent-repeat-interface], page 444 and Section 3.2.101 [spanner-interface], page 457.

3.1.82 PercentRepeatCounter

PercentRepeatCounter objects are created by: Section 2.2.83 [Percent_repeat_engraver], page 262.

Standard settings:

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-encoding` (symbol):
`'fetaText`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`font-size` (number):
`-2`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`padding` (dimension, in staff space):
`0.2`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`staff-padding` (dimension, in staff space):
`0.25`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-centered-on-y-parent>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) >) >`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.78 [percent-repeat-interface], page 444, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.115 [text-interface], page 464.

3.1.83 PhrasingSlur

PhrasingSlur objects are created by: Section 2.2.84 [Phrasing_slur_engraver], page 262.

Standard settings:

`control-points` (list):
`ly:slur::calc-control-points`

List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`details` (list):
`'((region-size . 4) (head-encompass-penalty . 1000.0) (stem-encompass-penalty . 30.0) (closeness-factor . 10) (edge-attraction-factor . 4) (same-slope-penalty . 20) (steeper-slope-factor . 50) (non-horizontal-penalty . 15) (max-slope . 1.1) (max-slope-factor . 10) (free-head-distance . 0.3) (free-slur-distance . 0.8) (extra-object-collision-penalty . 50) (accidental-collision . 3) (extra-encompass-free-distance . 0.3) (extra-encompass-collision-distance . 0.8) (head-slur-distance-max-ratio . 3) (head-slur-distance-factor . 10) (absolute-closeness-measure . 0.3) (edge-slope-exponent . 1.7))`

Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction):
`ly:slur::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`height-limit` (dimension, in staff space):
`2.0`

Maximum slur height: The longer the slur, the closer it is to this height.

`minimum-length` (dimension, in staff space):
`1.5`

Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`ratio` (number):
`0.333`

Parameter for slur shape. The higher this number, the quicker the slur attains its `height-limit`.

`spanner-id` (string):
`""`

An identifier to distinguish concurrent spanners.

`springs-and-rods` (boolean):
`ly:spanner::set-spacing-rods`

Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:slur::print`

The symbol to print.

`thickness` (number):
`1.1`

Line thickness, generally measured in `line-thickness`.

`Y-extent` (pair of numbers):
`ly:slur::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.95 [slur-interface], page 452 and Section 3.2.101 [spanner-interface], page 457.

3.1.84 PianoPedalBracket

PianoPedalBracket objects are created by: Section 2.2.86 [Piano_pedal_engraver], page 263.

Standard settings:

`bound-padding` (number):
`1.0`
The amount of padding to insert around spanner bounds.

`bracket-flare` (pair of numbers):
`'(0.5 . 0.5)`
A pair of numbers specifying how much edges of brackets should slant outward. Value `0.0` means straight edges.

`direction` (direction):
`-1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`edge-height` (pair):
`'(1.0 . 1.0)`
A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`shorten-pair` (pair of numbers):
`'(0.0 . 0.0)`
The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`stencil` (stencil):
`ly:piano-pedal-bracket::print`
The symbol to print.

`style` (symbol):
`'line`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`thickness` (number):
`1.0`
Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.80 [piano-pedal-bracket-interface], page 445, Section 3.2.81 [piano-pedal-interface], page 446 and Section 3.2.101 [spanner-interface], page 457.

3.1.85 RehearsalMark

RehearsalMark objects are created by: Section 2.2.64 [Mark_engraver], page 255.

Standard settings:

`after-line-breaking` (boolean):
`ly:side-position-interface::move-to-extremal-staff`
Dummy property, used to trigger callback for `after-line-breaking`.

`baseline-skip` (dimension, in staff space):
`2`
Distance between base lines of multiple lines of text.

`break-align-symbols` (list):
`'(staff-bar clef)`

A list of symbols that determine which break-aligned grobs to align this to. If the grob selected by the first symbol in the list is invisible due to break-visibility, we will align to the next grob (and so on). Choices are `left-edge`, `ambitus`, `breathing-sign`, `clef`, `staff-bar`, `key-cancellation`, `key-signature`, `time-signature`, and `custos`.

`break-visibility` (vector):
`#(#f #t #t)`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`font-size` (number):
`2`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`non-musical` (boolean):
`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`outside-staff-priority` (number):
`1500`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.8`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`stencil` (stencil):
`ly:text-interface::print`
The symbol to print.

`X-offset` (number):
`#<simple-closure (#<primitive-generic +> #<simple-closure (#<primitive-procedure ly:break-alignable-interface::self-align-callback>) > #<simple-closure (#<primitive-procedure ly:self-alignment-interface::x-aligned-on-self>) >) >`
The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.14 [break-alignable-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.62 [mark-interface], page 437, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.115 [text-interface], page 464.

3.1.86 RepeatSlash

RepeatSlash objects are created by: Section 2.2.100 [Slash_repeat_engraver], page 267.

Standard settings:

`slash-negative-kern` (number):
`0.85`
The space to remove between slashes in percent repeat glyphs. Larger values bring the two elements closer together.

`slope` (number):
`1.7`
The slope of this object.

`stencil` (stencil):
`ly:percent-repeat-item-interface::beat-slash`
The symbol to print.

`thickness` (number):
`0.48`
Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.78 [percent-repeat-interface], page 444, Section 3.2.79 [percent-repeat-item-interface], page 445 and Section 3.2.86 [rhythmic-grob-interface], page 447.

3.1.87 RepeatTie

RepeatTie objects are created by: Section 2.2.91 [Repeat_tie_engraver], page 265.

Standard settings:

`control-points` (list):
`ly:semi-tie::calc-control-points`
List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`details` (list):
`'((ratio . 0.333) (height-limit . 1.0))`

Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction):
`ly:tie::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`extra-spacing-height` (pair of numbers):
`'(-0.5 . 0.5)`

In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`head-direction` (direction):
`1`

Are the note heads left or right in a semitie?

`stencil` (stencil):
`ly:tie::print`

The symbol to print.

`thickness` (number):
`1.0`

Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.92 [semi-tie-interface], page 449.

3.1.88 RepeatTieColumn

RepeatTieColumn objects are created by: Section 2.2.91 [Repeat_tie_engraver], page 265.

Standard settings:

`direction` (direction):
`ly:tie::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`head-direction` (direction):
`ly:semi-tie-column::calc-head-direction`

Are the note heads left or right in a semitie?

`X-extent` (pair of numbers)
Hard coded extent in X direction.

`Y-extent` (pair of numbers)
: Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.91 [semi-tie-column-interface], page 449.

3.1.89 Rest

Rest objects are created by: Section 2.2.21 [Completion_rest_engraver], page 241 and Section 2.2.93 [Rest_engraver], page 265.

Standard settings:

`duration-log` (integer):
: `stem::calc-duration-log`

  The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

`minimum-distance` (dimension, in staff space):
: `0.25`

  Minimum distance between rest and notes or beam.

`stencil` (stencil):
: `ly:rest::print`

  The symbol to print.

`X-extent` (pair of numbers):
: `ly:rest::width`

  Hard coded extent in X direction.

`Y-extent` (pair of numbers):
: `ly:rest::height`

  Hard coded extent in Y direction.

`Y-offset` (number):
: `ly:rest::y-offset-callback`

  The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.85 [rest-interface], page 446, Section 3.2.86 [rhythmic-grob-interface], page 447, Section 3.2.87 [rhythmic-head-interface], page 447 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.90 RestCollision

RestCollision objects are created by: Section 2.2.92 [Rest_collision_engraver], page 265.

Standard settings:

`minimum-distance` (dimension, in staff space):
: `0.75`

  Minimum distance between rest and notes or beam.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.84 [rest-collision-interface], page 446.

3.1.91 Script

Script objects are created by: Section 2.2.30 [Drum_notes_engraver], page 244, Section 2.2.71 [New_fingering_engraver], page 258 and Section 2.2.97 [Script_engraver], page 266.

Standard settings:

`add-stem-support` (boolean):
`#t`

If set, the `Stem` object is included in this script's support.

`direction` (direction):
`ly:script-interface::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-encoding` (symbol):
`'fetaMusic`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`0.25`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:script-interface::print`

The symbol to print.

`X-offset` (number):
`script-interface::calc-x-offset`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.89 [script-interface], page 447 and Section 3.2.94 [side-position-interface], page 451.

3.1.92 ScriptColumn

ScriptColumn objects are created by: Section 2.2.96 [Script_column_engraver], page 266.

Standard settings:

`before-line-breaking` (boolean):
`ly:script-column::before-line-breaking`

Dummy property, used to trigger a callback function.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.88 [script-column-interface], page 447.

3.1.93 ScriptRow

ScriptRow objects are created by: Section 2.2.98 [Script_row_engraver], page 266.

Standard settings:

`before-line-breaking` (boolean):
`ly:script-column::row-before-line-breaking`

Dummy property, used to trigger a callback function.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.88 [script-column-interface], page 447.

3.1.94 Slur

Slur objects are created by: Section 2.2.101 [Slur_engraver], page 267.

Standard settings:

`avoid-slur` (symbol):
`'inside`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`control-points` (list):
`ly:slur::calc-control-points`

List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`details` (list):
`'((region-size . 4) (head-encompass-penalty . 1000.0) (stem-encompass-penalty . 30.0) (closeness-factor . 10) (edge-attraction-factor . 4) (same-slope-penalty . 20) (steeper-slope-factor . 50) (non-horizontal-penalty . 15) (max-slope . 1.1) (max-slope-factor . 10) (free-head-distance . 0.3) (free-slur-distance . 0.8) (extra-object-collision-penalty . 50) (accidental-collision . 3) (extra-encompass-free-distance . 0.3) (extra-encompass-collision-distance . 0.8) (head-slur-distance-max-ratio . 3) (head-slur-distance-factor . 10) (absolute-closeness-measure . 0.3) (edge-slope-exponent . 1.7))`

Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction):
`ly:slur::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`height-limit` (dimension, in staff space):
`2.0`

Maximum slur height: The longer the slur, the closer it is to this height.

`line-thickness` (number):
`0.8`

The thickness of the tie or slur contour.

`minimum-length` (dimension, in staff space):
`1.5`

Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`ratio` (number):
`0.25`

Parameter for slur shape. The higher this number, the quicker the slur attains its `height-limit`.

`spanner-id` (string):
`""`

An identifier to distinguish concurrent spanners.

`springs-and-rods` (boolean):
`ly:spanner::set-spacing-rods`

Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:slur::print`

The symbol to print.

`thickness` (number):
`1.2`

Line thickness, generally measured in `line-thickness`.

`Y-extent` (pair of numbers):
`ly:slur::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.95 [slur-interface], page 452 and Section 3.2.101 [spanner-interface], page 457.

3.1.95 SostenutoPedal

SostenutoPedal objects are created by: Section 2.2.86 [Piano_pedal_engraver], page 263.

Standard settings:

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`font-shape` (symbol):
`'italic`

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`padding` (dimension, in staff space):
`0.0`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`ly:self-alignment-interface::x-aligned-on-self`

The horizontal amount that this object is moved relative to its X-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.82 [piano-pedal-script-interface], page 446, Section 3.2.90 [self-alignment-interface], page 448 and Section 3.2.115 [text-interface], page 464.

3.1.96 SostenutoPedalLineSpanner

SostenutoPedalLineSpanner objects are created by: Section 2.2.85 [Piano_pedal_align_engraver], page 263.

Standard settings:

`axes` (list):
`'(1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`minimum-space` (dimension, in staff space):
`1.0`
Minimum distance that the victim should move (after padding).

`outside-staff-priority` (number):
`1000`
If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`1.2`
Add this much extra space between objects that are next to each other.

`side-axis` (number):
`1`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`1.0`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`
Hard coded extent in Y direction.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.81 [piano-pedal-interface], page 446, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.97 SpacingSpanner

SpacingSpanner objects are created by: Section 2.2.103 [Spacing_engraver], page 268.

Standard settings:

`average-spacing-wishes` (boolean):
`#t`
If set, the spacing wishes are averaged over staves.

`base-shortest-duration` (moment):
`#<Mom 3/16>`

Spacing is based on the shortest notes in a piece. Normally, pieces are spaced as if notes at least as short as this are present.

`common-shortest-duration` (moment):
`ly:spacing-spanner::calc-common-shortest-duration`

The most common shortest note length. This is used in spacing. Enlarging this sets the score tighter.

`shortest-duration-space` (dimension, in staff space):
`2.0`

Start with this much space for the shortest duration. This is expressed in `spacing-increment` as unit. See also Section "spacing-spanner-interface" in *Internals Reference*.

`spacing-increment` (number):
`1.2`

Add this much space for a doubled duration. Typically, the width of a note head. See also Section "spacing-spanner-interface" in *Internals Reference*.

`springs-and-rods` (boolean):
`ly:spacing-spanner::set-springs`

Dummy variable for triggering spacing routines.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.98 [spacing-options-interface], page 455, Section 3.2.99 [spacing-spanner-interface], page 455 and Section 3.2.101 [spanner-interface], page 457.

3.1.98 SpanBar

SpanBar objects are created by: Section 2.2.105 [Span_bar_engraver], page 268.

Standard settings:

`allow-span-bar` (boolean):
`#t`

If false, no inter-staff bar line will be created below this bar line.

`before-line-breaking` (boolean):
`ly:span-bar::before-line-breaking`

Dummy property, used to trigger a callback function.

`break-align-symbol` (symbol):
`'staff-bar`

This key is used for aligning and spacing breakable items.

`glyph-name` (string):
`ly:span-bar::calc-glyph-name`

The glyph name within the font.

`hair-thickness` (number):
`1.6`

Thickness of the thin line in a bar line.

`kern` (dimension, in staff space):
`3.0`
Amount of extra white space to add. For bar lines, this is the amount of space after a thick line.

`layer` (integer):
`0`
An integer which determines the order of printing objects. Objects with the lowest value of layer are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a layer value of 1.

`non-musical` (boolean):
`#t`
True if the grob belongs to a `NonMusicalPaperColumn`.

`stencil` (stencil):
`ly:span-bar::print`
The symbol to print.

`thick-thickness` (number):
`6.0`
Bar line thickness, measured in `line-thickness`.

`thin-kern` (number):
`3.0`
The space after a hair-line in a bar line.

`X-extent` (pair of numbers):
`ly:span-bar::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.9 [bar-line-interface], page 409, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.100 [span-bar-interface], page 456.

3.1.99 StaffGrouper

StaffGrouper objects are not created by any engraver.

Standard settings:

`staff-staff-spacing` (list):
`'((basic-distance . 9) (minimum-distance . 7) (padding . 1) (stretchability . 5))`
When applied to a staff-group's `StaffGrouper` grob, this spacing alist controls the distance between consecutive staves within the staff-group. When applied to a staff's `VerticalAxisGroup` grob, it controls the distance between the staff and the nearest staff below it in the same system, replacing any settings inherited from the `StaffGrouper` grob of the containing staff-group, if there is one. This property remains in effect even when non-staff lines appear between staves. The alist can contain the following keys:

- `basic-distance` – the vertical distance, measured in staff-spaces, between the reference points of the two items when no collisions would result, and no stretching or compressing is in effect.
- `minimum-distance` – the smallest allowable vertical distance, measured in staff-spaces, between the reference points of the two items, when compressing is in effect.
- `padding` – the minimum required amount of unobstructed vertical whitespace between the bounding boxes (or skylines) of the two items, measured in staff-spaces.
- `stretchability` – a unitless measure of the dimension's relative propensity to stretch. If zero, the distance will not stretch (unless collisions would result).

`staffgroup-staff-spacing` (list):

`'((basic-distance . 10.5) (minimum-distance . 8) (padding . 1) (stretchability . 9))`

The spacing alist controlling the distance between the last staff of the current staff-group and the staff just below it in the same system, even if one or more non-staff lines exist between the two staves. If the `staff-staff-spacing` property of the staff's `VerticalAxisGroup` grob is set, that is used instead. See `staff-staff-spacing` for a description of the alist structure.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.102 [staff-grouper-interface], page 458.

3.1.100 StaffSpacing

StaffSpacing objects are created by: Section 2.2.99 [Separating_line_group_engraver], page 266.

Standard settings:

`non-musical` (boolean):

`#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`stem-spacing-correction` (number):

`0.4`

Optical correction amount for stems that are placed in tight configurations. For opposite directions, this amount is the correction for two normal sized stems that overlap completely.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.97 [spacing-interface], page 455 and Section 3.2.103 [staff-spacing-interface], page 458.

3.1.101 StaffSymbol

StaffSymbol objects are created by: Section 2.2.109 [Staff_symbol_engraver], page 269 and Section 2.2.115 [Tab_staff_symbol_engraver], page 271.

Standard settings:

`layer` (integer):

`0`

An integer which determines the order of printing objects. Objects with the lowest value of layer are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a layer value of 1.

`ledger-line-thickness` (pair of numbers):
`'(1.0 . 0.1)`

The thickness of ledger lines. It is the sum of 2 numbers: The first is the factor for line thickness, and the second for staff space. Both contributions are added.

`line-count` (integer):
`5`

The number of staff lines.

`stencil` (stencil):
`ly:staff-symbol::print`

The symbol to print.

`Y-extent` (pair of numbers):
`ly:staff-symbol::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.104 [staff-symbol-interface], page 459.

3.1.102 StanzaNumber

StanzaNumber objects are created by: Section 2.2.111 [Stanza_number_engraver], page 269.

Standard settings:

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-series` (symbol):
`'bold`

Select the series of a font. Choices include `medium`, `bold`, `bold-narrow`, etc.

`padding` (dimension, in staff space):
`1.0`

Add this much extra space between objects that are next to each other.

`side-axis` (number):
`0`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`

The horizontal amount that this object is moved relative to its X-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.94 [side-position-interface], page 451, Section 3.2.106 [stanza-number-interface], page 459 and Section 3.2.115 [text-interface], page 464.

3.1.103 Stem

Stem objects are created by: Section 2.2.112 [Stem_engraver], page 270.

Standard settings:

`beamlet-default-length` (pair):
`'(1.1 . 1.1)`

A pair of numbers. The first number specifies the default length of a beamlet that sticks out of the left hand side of this stem; the second number specifies the default length of the beamlet to the right. The actual length of a beamlet is determined by taking either the default length or the length specified by `beamlet-max-length-proportion`, whichever is smaller.

`beamlet-max-length-proportion` (pair):
`'(0.75 . 0.75)`

The maximum length of a beamlet, as a proportion of the distance between two adjacent stems.

`default-direction` (direction):
`ly:stem::calc-default-direction`

Direction determined by note head positions.

`details` (list):
`'((lengths 3.5 3.5 3.5 4.25 5.0 6.0) (beamed-lengths 3.26 3.5 3.6) (beamed-minimum-free-lengths 1.83 1.5 1.25) (beamed-extreme-minimum-free-lengths 2.0 1.25) (stem-shorten 1.0 0.5))`

Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction):
`ly:stem::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`duration-log` (integer):
`stem::calc-duration-log`

The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

`flag` (stencil):
`ly:stem::calc-flag`
A function returning the full flag stencil for the `Stem`, which is passed to the function as the only argument. The default ly:stem::calc-stencil function uses the `flag-style` property to determine the correct glyph for the flag. By providing your own function, you can create arbitrary flags.

`length` (dimension, in staff space):
`ly:stem::calc-length`
User override for the stem length of unbeamed stems.

`neutral-direction` (direction):
`-1`
Which direction to take in the center of the staff.

`stem-end-position` (number):
`ly:stem::calc-stem-end-position`
Where does the stem end (the end is opposite to the support-head)?

`stencil` (stencil):
`ly:stem::print`
The symbol to print.

`thickness` (number):
`1.3`
Line thickness, generally measured in `line-thickness`.

`X-extent` (pair of numbers):
`ly:stem::width`
Hard coded extent in X direction.

`X-offset` (number):
`ly:stem::offset-callback`
The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers):
`ly:stem::height`
Hard coded extent in Y direction.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.107 [stem-interface], page 459.

3.1.104 StemTremolo

StemTremolo objects are created by: Section 2.2.112 [Stem_engraver], page 270.

Standard settings:

`beam-thickness` (dimension, in staff space):
`0.48`
Beam thickness, measured in `staff-space` units.

`beam-width` (dimension, in staff space):
`ly:stem-tremolo::calc-width`
Width of the tremolo sign.

`slope` (number):
`ly:stem-tremolo::calc-slope`
The slope of this object.

`stencil` (stencil):
`ly:stem-tremolo::print`
The symbol to print.

`style` (symbol):
`ly:stem-tremolo::calc-style`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`X-extent` (pair of numbers):
`ly:stem-tremolo::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:stem-tremolo::height`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.108 [stem-tremolo-interface], page 462.

3.1.105 StringNumber

StringNumber objects are created by: Section 2.2.71 [New_fingering_engraver], page 258.

Standard settings:

`avoid-slur` (symbol):
`'around`
Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`font-encoding` (symbol):
`'fetaText`
The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`font-size` (number):
`-5`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`padding` (dimension, in staff space):
`0.5`

Add this much extra space between objects that are next to each other.

`script-priority` (number):
`100`

A sorting key that determines in what order a script is within a stack of scripts.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`self-alignment-Y` (number):
`0`

Like `self-alignment-X` but for the Y axis.

`staff-padding` (dimension, in staff space):
`0.5`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`print-circled-text-callback`

The symbol to print.

`text` (markup):
`string-number::calc-text`

Text markup. See Section "Formatting text" in *Notation Reference*.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451, Section 3.2.109 [string-number-interface], page 462, Section 3.2.115 [text-interface], page 464 and Section 3.2.116 [text-script-interface], page 465.

3.1.106 StrokeFinger

StrokeFinger objects are created by: Section 2.2.71 [New_fingering_engraver], page 258.

Standard settings:

`digit-names` (vector):
`#(p i m a x)`

Names for string finger digits.

`font-shape` (symbol):
`'italic`

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`font-size` (number):
`-4`
The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`padding` (dimension, in staff space):
`0.5`
Add this much extra space between objects that are next to each other.

`script-priority` (number):
`100`
A sorting key that determines in what order a script is within a stack of scripts.

`self-alignment-X` (number):
`0`
Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`self-alignment-Y` (number):
`0`
Like `self-alignment-X` but for the Y axis.

`staff-padding` (dimension, in staff space):
`0.5`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`
The symbol to print.

`text` (markup):
`stroke-finger::calc-text`
Text markup. See Section "Formatting text" in *Notation Reference*.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451, Section 3.2.110 [stroke-finger-interface], page 462, Section 3.2.115 [text-interface], page 464 and Section 3.2.116 [text-script-interface], page 465.

3.1.107 SustainPedal

SustainPedal objects are created by: Section 2.2.86 [Piano_pedal_engraver], page 263.

Standard settings:

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`padding` (dimension, in staff space):
`0.0`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`stencil` (stencil):
`ly:sustain-pedal::print`

The symbol to print.

`X-offset` (number):
`ly:self-alignment-interface::x-aligned-on-self`

The horizontal amount that this object is moved relative to its X-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.81 [piano-pedal-interface], page 446, Section 3.2.82 [piano-pedal-script-interface], page 446, Section 3.2.90 [self-alignment-interface], page 448 and Section 3.2.115 [text-interface], page 464.

3.1.108 SustainPedalLineSpanner

SustainPedalLineSpanner objects are created by: Section 2.2.85 [Piano_pedal_align_engraver], page 263.

Standard settings:

`axes` (list):
`'(1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`minimum-space` (dimension, in staff space):
`1.0`

Minimum distance that the victim should move (after padding).

`outside-staff-priority` (number):
`1000`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`1.2`
Add this much extra space between objects that are next to each other.

`side-axis` (number):
`1`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`1.2`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`
Hard coded extent in Y direction.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.81 [piano-pedal-interface], page 446, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.109 System

System objects are not created by any engraver.

Standard settings:

`axes` (list):
`'(0 1)`
List of axis numbers. In the case of alignment grobs, this should contain only one number.

`skyline-horizontal-padding` (number):
`0.5`
For determining the vertical distance between two staves, it is possible to have a configuration which would result in a tight interleaving of grobs from the top staff and the bottom staff. The larger this parameter is, the farther apart the staves are placed in such a configuration.

`vertical-skylines` (pair of skylines):
`ly:axis-group-interface::calc-skylines`
Two skylines, one above and one below this grob.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:system::height`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.111 [system-interface], page 463.

3.1.110 SystemStartBar

SystemStartBar objects are created by: Section 2.2.113 [System_start_delimiter_engraver], page 270.

Standard settings:

`collapse-height` (dimension, in staff space):
`5.0`
Minimum height of system start delimiter. If equal or smaller, the bracket/brace/line is removed.

`direction` (direction):
`-1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`padding` (dimension, in staff space):
`-0.1`
Add this much extra space between objects that are next to each other.

`stencil` (stencil):
`ly:system-start-delimiter::print`
The symbol to print.

`style` (symbol):
`'bar-line`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`thickness` (number):
`1.6`
Line thickness, generally measured in `line-thickness`.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`
The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.112 [system-start-delimiter-interface], page 463.

3.1.111 SystemStartBrace

SystemStartBrace objects are created by: Section 2.2.113 [System_start_delimiter_engraver], page 270.

Standard settings:

`collapse-height` (dimension, in staff space):
`5.0`

Minimum height of system start delimiter. If equal or smaller, the bracket/brace/line is removed.

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-encoding` (symbol):
`'fetaBraces`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`padding` (dimension, in staff space):
`0.3`

Add this much extra space between objects that are next to each other.

`stencil` (stencil):
`ly:system-start-delimiter::print`

The symbol to print.

`style` (symbol):
`'brace`

This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`

The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.112 [system-start-delimiter-interface], page 463.

3.1.112 SystemStartBracket

SystemStartBracket objects are created by: Section 2.2.113 [System_start_delimiter_engraver], page 270.

Standard settings:

`collapse-height` (dimension, in staff space):
`5.0`

Minimum height of system start delimiter. If equal or smaller, the bracket/brace/line is removed.

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`padding` (dimension, in staff space):
`0.8`

Add this much extra space between objects that are next to each other.

`stencil` (stencil):
`ly:system-start-delimiter::print`

The symbol to print.

`style` (symbol):
`'bracket`

This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`thickness` (number):
`0.45`

Line thickness, generally measured in `line-thickness`.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`

The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.112 [system-start-delimiter-interface], page 463.

3.1.113 SystemStartSquare

SystemStartSquare objects are created by: Section 2.2.113 [System_start_delimiter_engraver], page 270.

Standard settings:

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`stencil` (stencil):
`ly:system-start-delimiter::print`
The symbol to print.

`style` (symbol):
`'line-bracket`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`thickness` (number):
`1.0`
Line thickness, generally measured in `line-thickness`.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`
The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.112 [system-start-delimiter-interface], page 463.

3.1.114 TabNoteHead

TabNoteHead objects are created by: Section 2.2.114 [Tab_note_heads_engraver], page 270.

Standard settings:

`details` (list):
`'((cautionary-properties (angularity . 0.4) (half-thickness . 0.075) (padding . 0) (procedure . #<procedure parenthesize-stencil (stencil half-thickness width angularity padding)>) (width . 0.25)) (head-offset . 3/5) (harmonic-properties (angularity . 2) (half-thickness . 0.075) (padding . 0) (procedure . #<procedure parenthesize-stencil (stencil half-thickness width angularity padding)>) (width . 0.25)) (repeat-tied-properties (note-head-visible . #t) (parenthesize . #t)) (tied-properties (break-visibility . #(#f #f #t)) (parenthesize . #t)))`
Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction):
`0`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`duration-log` (integer):
`note-head::calc-duration-log`

The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

`font-series` (symbol):
`'bold`

Select the series of a font. Choices include `medium`, `bold`, `bold-narrow`, etc.

`font-size` (number):
`-2`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`stem-attachment` (pair of numbers):
`'(0.0 . 1.35)`

An `(x . y)` pair where the stem attaches to the notehead.

`stencil` (stencil):
`tab-note-head::print`

The symbol to print.

`whiteout` (boolean):
`#t`

If true, the grob is printed over a white background to white-out underlying material, if the grob is visible. Usually #f by default.

`X-offset` (number):
`ly:self-alignment-interface::x-aligned-on-self`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.71 [note-head-interface], page 441, Section 3.2.86 [rhythmic-grob-interface], page 447, Section 3.2.87 [rhythmic-head-interface], page 447, Section 3.2.105 [staff-symbol-referencer-interface], page 459, Section 3.2.114 [tab-note-head-interface], page 464 and Section 3.2.115 [text-interface], page 464.

3.1.115 TextScript

TextScript objects are created by: Section 2.2.118 [Text_engraver], page 272.

Standard settings:

`avoid-slur` (symbol):
`'around`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`outside-staff-priority` (number):
`450`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.5`

Add this much extra space between objects that are next to each other.

`script-priority` (number):
`200`

A sorting key that determines in what order a script is within a stack of scripts.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`slur-padding` (number):
`0.5`

Extra distance between slur and script.

`staff-padding` (dimension, in staff space):
`0.5`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`ly:self-alignment-interface::x-aligned-on-self`

The horizontal amount that this object is moved relative to its X-parent.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.47 [instrument-specific-markup-interface], page 430, Section 3.2.48 [item-interface], page 432, Section 3.2.90 [self-alignment-interface], page 448, Section 3.2.94 [side-position-interface], page 451, Section 3.2.115 [text-interface], page 464 and Section 3.2.116 [text-script-interface], page 465.

3.1.116 TextSpanner

TextSpanner objects are created by: Section 2.2.119 [Text_spanner_engraver], page 272.

Standard settings:

`bound-details` (list):
`'((left (Y . 0) (padding . 0.25) (attach-dir . -1)) (left-broken (end-on-note . #t)) (right (Y . 0) (padding . 0.25)))`

An alist of properties for determining attachments of spanners to edges.

`dash-fraction` (number):
`0.2`

Size of the dashes, relative to `dash-period`. Should be between `0.0` (no line) and `1.0` (continuous line).

`dash-period` (number):
`3.0`

The length of one dash together with whitespace. If negative, no line is drawn at all.

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-shape` (symbol):
`'italic`

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`left-bound-info` (list):
`ly:line-spanner::calc-left-bound-info`

An alist of properties for determining attachments of spanners to edges.

`outside-staff-priority` (number):
`350`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`right-bound-info` (list):
`ly:line-spanner::calc-right-bound-info`

An alist of properties for determining attachments of spanners to edges.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`0.8`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:line-spanner::print`

The symbol to print.

`style` (symbol):
`'dashed-line`

This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.57 [line-spanner-interface], page 435, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.117 Tie

Tie objects are created by: Section 2.2.20 [Completion_heads_engraver], page 240 and Section 2.2.120 [Tie_engraver], page 272.

Standard settings:

`avoid-slur` (symbol):
`'inside`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`control-points` (list):
`ly:tie::calc-control-points`

List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`details` (list):
`'((ratio . 0.333) (center-staff-line-clearance . 0.6) (tip-staff-line-clearance . 0.45) (note-head-gap . 0.2) (stem-gap . 0.35) (height-limit . 1.0) (horizontal-distance-penalty-factor . 10) (same-dir-as-stem-penalty . 8) (min-length-penalty-factor . 26) (tie-tie-collision-distance . 0.45) (tie-tie-collision-penalty . 25.0) (intra-space-threshold . 1.25) (outer-tie-vertical-distance-symmetry-penalty-factor . 10) (outer-tie-length-symmetry-penalty-factor`

```
. 10) (vertical-distance-penalty-factor . 7) (outer-
tie-vertical-gap . 0.25) (multi-tie-region-size . 3)
(single-tie-region-size . 4) (between-length-limit . 1.0))
```

Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction):
`ly:tie::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-size` (number):
`-6`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`line-thickness` (number):
`0.8`

The thickness of the tie or slur contour.

`neutral-direction` (direction):
`1`

Which direction to take in the center of the staff.

`springs-and-rods` (boolean):
`ly:spanner::set-spacing-rods`

Dummy variable for triggering spacing routines.

`stencil` (stencil):
`ly:tie::print`

The symbol to print.

`thickness` (number):
`1.2`

Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.118 [tie-interface], page 466.

3.1.118 TieColumn

TieColumn objects are created by: Section 2.2.20 [Completion_heads_engraver], page 240 and Section 2.2.120 [Tie_engraver], page 272.

Standard settings:

`before-line-breaking` (boolean):
`ly:tie-column::before-line-breaking`

Dummy property, used to trigger a callback function.

`X-extent` (pair of numbers)
Hard coded extent in X direction.

`Y-extent` (pair of numbers)
: Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.117 [tie-column-interface], page 466.

3.1.119 TimeSignature

TimeSignature objects are created by: Section 2.2.122 [Time_signature_engraver], page 273.

Standard settings:

`avoid-slur` (symbol):
: `'inside`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`break-align-anchor` (number):
: `ly:break-aligned-interface::calc-extent-aligned-anchor`

Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-anchor-alignment` (number):
: `-1`

Read by `ly:break-aligned-interface::calc-extent-aligned-anchor` for aligning an anchor to a grob's extent.

`break-align-symbol` (symbol):
: `'time-signature`

This key is used for aligning and spacing breakable items.

`break-visibility` (vector):
: `#(#t #t #t)`

A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`extra-spacing-height` (pair of numbers):
: `'(-1.0 . 1.0)`

In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`non-musical` (boolean):
: `#t`

True if the grob belongs to a `NonMusicalPaperColumn`.

`space-alist` (list):
: `'((cue-clef extra-space . 1.5) (first-note fixed-space . 2.0) (right-edge extra-space . 0.5) (staff-bar minimum-space . 2.0))`

A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(break-align-symbol type . distance)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`stencil` (stencil):
`ly:time-signature::print`
The symbol to print.

`style` (symbol):
`'C`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

This object supports the following interface(s): Section 3.2.15 [break-aligned-interface], page 413, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432 and Section 3.2.119 [time-signature-interface], page 467.

3.1.120 TrillPitchAccidental

TrillPitchAccidental objects are created by: Section 2.2.89 [Pitched_trill_engraver], page 264.

Standard settings:

`direction` (direction):
`-1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-size` (number):
`-4`
The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`glyph-name-alist` (list):
```
'((0 . accidentals.natural) (-1/2 . accidentals.flat) (1/2
. accidentals.sharp) (1 . accidentals.doublesharp) (-1 .
accidentals.flatflat) (3/4 . accidentals.sharp.slashslash.stemstemstem)
(1/4 . accidentals.sharp.slashslash.stem)
(-1/4 . accidentals.mirroredflat) (-3/4 .
accidentals.mirroredflat.flat))
```
An alist of key-string pairs.

`padding` (dimension, in staff space):
`0.2`
Add this much extra space between objects that are next to each other.

`side-axis` (number):
`0`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`stencil` (stencil):
`ly:accidental-interface::print`
The symbol to print.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`
The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers):
`ly:accidental-interface::height`
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.1 [accidental-interface], page 403, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.46 [inline-accidental-interface], page 430, Section 3.2.48 [item-interface], page 432, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.120 [trill-pitch-accidental-interface], page 467.

3.1.121 TrillPitchGroup

TrillPitchGroup objects are created by: Section 2.2.89 [Pitched_trill_engraver], page 264.

Standard settings:

`axes` (list):
`'(0)`
List of axis numbers. In the case of alignment grobs, this should contain only one number.

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`font-size` (number):
`-4`
The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`padding` (dimension, in staff space):
`0.3`
Add this much extra space between objects that are next to each other.

`side-axis` (number):
`0`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`stencil` (stencil):
`parenthesize-elements`
The symbol to print.

`stencils` (list):
`parentheses-item::calc-parenthesis-stencils`
Multiple stencils, used as intermediate value.

`X-offset` (number):
`ly:side-position-interface::x-aligned-side`

The horizontal amount that this object is moved relative to its X-parent.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.71 [note-head-interface], page 441, Section 3.2.77 [parentheses-interface], page 444 and Section 3.2.94 [side-position-interface], page 451.

3.1.122 TrillPitchHead

TrillPitchHead objects are created by: Section 2.2.89 [Pitched_trill_engraver], page 264.

Standard settings:

`duration-log` (integer):
`2`

The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

`font-size` (number):
`-4`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`stencil` (stencil):
`ly:note-head::print`

The symbol to print.

`Y-offset` (number):
`ly:staff-symbol-referencer::callback`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.52 [ledgered-interface], page 434, Section 3.2.83 [pitched-trill-interface], page 446, Section 3.2.87 [rhythmic-head-interface], page 447 and Section 3.2.105 [staff-symbol-referencer-interface], page 459.

3.1.123 TrillSpanner

TrillSpanner objects are created by: Section 2.2.126 [Trill_spanner_engraver], page 274.

Standard settings:

`after-line-breaking` (boolean):
`ly:spanner::kill-zero-spanned-time`

Dummy property, used to trigger callback for `after-line-breaking`.

`bound-details` (list):
`'((left (text #<procedure musicglyph-markup (layout props glyph-name)> scripts.trill) (Y . 0) (stencil-offset -0.5 . -1) (padding . 0.5) (attach-dir . 0)) (left-broken (end-on-note . #t)) (right (Y . 0)))`

An alist of properties for determining attachments of spanners to edges.

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`left-bound-info` (list):
`ly:line-spanner::calc-left-bound-info`

An alist of properties for determining attachments of spanners to edges.

`outside-staff-priority` (number):
`50`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`0.5`

Add this much extra space between objects that are next to each other.

`right-bound-info` (list):
`ly:line-spanner::calc-right-bound-info`

An alist of properties for determining attachments of spanners to edges.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`1.0`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:line-spanner::print`

The symbol to print.

`style` (symbol):
`'trill`

This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.57 [line-spanner-interface], page 435, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.121 [trill-spanner-interface], page 468.

3.1.124 TupletBracket

TupletBracket objects are created by: Section 2.2.127 [Tuplet_engraver], page 275.

Standard settings:

`connect-to-neighbor` (pair):
`ly:tuplet-bracket::calc-connect-to-neighbors`

Pair of booleans, indicating whether this grob looks as a continued break.

`control-points` (list):
`ly:tuplet-bracket::calc-control-points`

List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`direction` (direction):
`ly:tuplet-bracket::calc-direction`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`edge-height` (pair):
`'(0.7 . 0.7)`

A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`full-length-to-extent` (boolean):
`#t`

Run to the extent of the column for a full-length tuplet bracket.

`padding` (dimension, in staff space):
`1.1`

Add this much extra space between objects that are next to each other.

`positions` (pair of numbers):
`ly:tuplet-bracket::calc-positions`

Pair of staff coordinates `(`*`left . right`*`)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

`shorten-pair` (pair of numbers):
`'(-0.2 . -0.2)`

The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`staff-padding` (dimension, in staff space):
`0.25`

Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`stencil` (stencil):
`ly:tuplet-bracket::print`

The symbol to print.

`thickness` (number):
`1.6`

Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.122 [tuplet-bracket-interface], page 468.

3.1.125 TupletNumber

TupletNumber objects are created by: Section 2.2.127 [Tuplet_engraver], page 275.

Standard settings:

`avoid-slur` (symbol):
`'inside`

Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`font-shape` (symbol):
`'italic`

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`font-size` (number):
`-2`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`stencil` (stencil):
`ly:tuplet-number::print`

The symbol to print.

`text` (markup):
`tuplet-number::calc-denominator-text`

Text markup. See Section "Formatting text" in *Notation Reference*.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457, Section 3.2.115 [text-interface], page 464 and Section 3.2.123 [tuplet-number-interface], page 469.

3.1.126 UnaCordaPedal

UnaCordaPedal objects are created by: Section 2.2.86 [Piano_pedal_engraver], page 263.

Standard settings:

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`extra-spacing-width` (pair of numbers):
`'(+inf.0 . -inf.0)`

In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`font-shape` (symbol):
`'italic`

Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`padding` (dimension, in staff space):
`0.0`

Add this much extra space between objects that are next to each other.

`self-alignment-X` (number):
`0`

Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`stencil` (stencil):
`ly:text-interface::print`

The symbol to print.

`X-offset` (number):
`ly:self-alignment-interface::x-aligned-on-self`

The horizontal amount that this object is moved relative to its X-parent.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.48 [item-interface], page 432, Section 3.2.82 [piano-pedal-script-interface], page 446, Section 3.2.90 [self-alignment-interface], page 448 and Section 3.2.115 [text-interface], page 464.

3.1.127 UnaCordaPedalLineSpanner

UnaCordaPedalLineSpanner objects are created by: Section 2.2.85 [Piano_pedal_align_engraver], page 263.

Standard settings:

`axes` (list):
`'(1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`direction` (direction):
`-1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`minimum-space` (dimension, in staff space):
`1.0`
Minimum distance that the victim should move (after padding).

`outside-staff-priority` (number):
`1000`
If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`1.2`
Add this much extra space between objects that are next to each other.

`side-axis` (number):
`1`
If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`staff-padding` (dimension, in staff space):
`1.2`
Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`
Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`
Hard coded extent in Y direction.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`
The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.81 [piano-pedal-interface], page 446, Section 3.2.94 [side-position-interface], page 451 and Section 3.2.101 [spanner-interface], page 457.

3.1.128 VaticanaLigature

VaticanaLigature objects are created by: Section 2.2.129 [Vaticana_ligature_engraver], page 275.

Standard settings:

`stencil` (stencil):
`ly:vaticana-ligature::print`
The symbol to print.

`thickness` (number):
`0.6`

Line thickness, generally measured in `line-thickness`.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.125 [vaticana-ligature-interface], page 470.

3.1.129 VerticalAlignment

VerticalAlignment objects are created by: Section 2.2.130 [Vertical_align_engraver], page 276.

Standard settings:

`axes` (list):
`'(1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`stacking-dir` (direction):
`-1`

Stack objects in which direction?

`vertical-skylines` (pair of skylines):
`ly:axis-group-interface::combine-skylines`

Two skylines, one above and one below this grob.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`

Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.4 [align-interface], page 405, Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424 and Section 3.2.101 [spanner-interface], page 457.

3.1.130 VerticalAxisGroup

VerticalAxisGroup objects are created by: Section 2.2.5 [Axis_group_engraver], page 235 and Section 2.2.51 [Hara_kiri_engraver], page 251.

Standard settings:

`axes` (list):
`'(1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`default-staff-staff-spacing` (list):
`'((basic-distance . 9) (minimum-distance . 8) (padding . 1))`

The settings to use for `staff-staff-spacing` when it is unset, for ungrouped staves and for grouped staves that do not have the relevant `StaffGrouper` property set (`staff-staff-spacing` or `staffgroup-staff-spacing`).

`nonstaff-unrelatedstaff-spacing` (list):
`'((padding . 0.5))`

The spacing alist controlling the distance between the current non-staff line and the nearest staff in the opposite direction from `staff-affinity`, if there are no other non-staff lines between the two, and `staff-affinity` is either `UP` or `DOWN`. See `staff-staff-spacing` for a description of the alist structure.

`staff-staff-spacing` (list):
`ly:axis-group-interface::calc-staff-staff-spacing`

When applied to a staff-group's `StaffGrouper` grob, this spacing alist controls the distance between consecutive staves within the staff-group. When applied to a staff's `VerticalAxisGroup` grob, it controls the distance between the staff and the nearest staff below it in the same system, replacing any settings inherited from the `StaffGrouper` grob of the containing staff-group, if there is one. This property remains in effect even when non-staff lines appear between staves. The alist can contain the following keys:

- `basic-distance` – the vertical distance, measured in staff-spaces, between the reference points of the two items when no collisions would result, and no stretching or compressing is in effect.
- `minimum-distance` – the smallest allowable vertical distance, measured in staff-spaces, between the reference points of the two items, when compressing is in effect.
- `padding` – the minimum required amount of unobstructed vertical whitespace between the bounding boxes (or skylines) of the two items, measured in staff-spaces.
- `stretchability` – a unitless measure of the dimension's relative propensity to stretch. If zero, the distance will not stretch (unless collisions would result).

`stencil` (stencil):
`ly:axis-group-interface::print`

The symbol to print.

`vertical-skylines` (pair of skylines):
`ly:hara-kiri-group-spanner::calc-skylines`

Two skylines, one above and one below this grob.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:hara-kiri-group-spanner::y-extent`

Hard coded extent in Y direction.

`Y-offset` (number):
`ly:hara-kiri-group-spanner::force-hara-kiri-callback`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.44 [hara-kiri-group-spanner-interface], page 428 and Section 3.2.101 [spanner-interface], page 457.

3.1.131 VoiceFollower

VoiceFollower objects are created by: Section 2.2.72 [Note_head_line_engraver], page 258.

Standard settings:

`after-line-breaking` (boolean):
`ly:spanner::kill-zero-spanned-time`
Dummy property, used to trigger callback for `after-line-breaking`.

`bound-details` (list):
`'((right (attach-dir . 0) (padding . 1.5)) (left (attach-dir . 0) (padding . 1.5)))`
An alist of properties for determining attachments of spanners to edges.

`gap` (dimension, in staff space):
`0.5`
Size of a gap in a variable symbol.

`left-bound-info` (list):
`ly:line-spanner::calc-left-bound-info`
An alist of properties for determining attachments of spanners to edges.

`non-musical` (boolean):
`#t`
True if the grob belongs to a `NonMusicalPaperColumn`.

`right-bound-info` (list):
`ly:line-spanner::calc-right-bound-info`
An alist of properties for determining attachments of spanners to edges.

`stencil` (stencil):
`ly:line-spanner::print`
The symbol to print.

`style` (symbol):
`'line`
This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`X-extent` (pair of numbers)
Hard coded extent in X direction.

`Y-extent` (pair of numbers)
Hard coded extent in Y direction.

This object supports the following interface(s): Section 3.2.42 [grob-interface], page 424, Section 3.2.56 [line-interface], page 435, Section 3.2.57 [line-spanner-interface], page 435 and Section 3.2.101 [spanner-interface], page 457.

3.1.132 VoltaBracket

VoltaBracket objects are created by: Section 2.2.131 [Volta_engraver], page 276.

Standard settings:

`direction` (direction):
`1`
If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object.

Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`edge-height` (pair):
`'(2.0 . 2.0)`

A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`font-encoding` (symbol):
`'fetaText`

The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`font-size` (number):
`-4`

The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`stencil` (stencil):
`ly:volta-bracket-interface::print`

The symbol to print.

`thickness` (number):
`1.6`

Line thickness, generally measured in `line-thickness`.

`word-space` (dimension, in staff space):
`0.6`

Space to insert between words in texts.

This object supports the following interface(s): Section 3.2.33 [font-interface], page 419, Section 3.2.42 [grob-interface], page 424, Section 3.2.45 [horizontal-bracket-interface], page 429, Section 3.2.56 [line-interface], page 435, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457, Section 3.2.115 [text-interface], page 464, Section 3.2.126 [volta-bracket-interface], page 470 and Section 3.2.127 [volta-interface], page 471.

3.1.133 VoltaBracketSpanner

VoltaBracketSpanner objects are created by: Section 2.2.131 [Volta_engraver], page 276.

Standard settings:

`after-line-breaking` (boolean):
`ly:side-position-interface::move-to-extremal-staff`

Dummy property, used to trigger callback for `after-line-breaking`.

`axes` (list):
`'(1)`

List of axis numbers. In the case of alignment grobs, this should contain only one number.

`direction` (direction):
`1`

If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`no-alignment` (boolean):
`#t`

If set, don't place this grob in a `VerticalAlignment`; rather, place it using its own `Y-offset` callback.

`outside-staff-priority` (number):
`600`

If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`padding` (dimension, in staff space):
`1`

Add this much extra space between objects that are next to each other.

`side-axis` (number):
`1`

If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`X-extent` (pair of numbers):
`ly:axis-group-interface::width`

Hard coded extent in X direction.

`Y-extent` (pair of numbers):
`ly:axis-group-interface::height`

Hard coded extent in Y direction.

`Y-offset` (number):
`ly:side-position-interface::y-aligned-side`

The vertical amount that this object is moved relative to its Y-parent.

This object supports the following interface(s): Section 3.2.7 [axis-group-interface], page 406, Section 3.2.42 [grob-interface], page 424, Section 3.2.94 [side-position-interface], page 451, Section 3.2.101 [spanner-interface], page 457 and Section 3.2.127 [volta-interface], page 471.

3.2 Graphical Object Interfaces

3.2.1 accidental-interface

A single accidental.

User settable properties:

`alteration` (number)
Alteration numbers for accidental.

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`glyph-name-alist` (list)
: An alist of key-string pairs.

`hide-tied-accidental-after-break` (boolean)
: If set, an accidental that appears on a tied note after a line break will not be displayed.

`parenthesized` (boolean)
: Parenthesize this grob.

`restore-first` (boolean)
: Print a natural before the accidental.

Internal properties:

`forced` (boolean)
: Manually forced accidental.

`tie` (graphical (layout) object)
: A pointer to a `Tie` object.

This grob interface is used in the following graphical object(s): Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.6 [AmbitusAccidental], page 293 and Section 3.1.120 [TrillPitchAccidental], page 391.

3.2.2 accidental-placement-interface

Resolve accidental collisions.

User settable properties:

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`right-padding` (dimension, in staff space)
: Space to insert on the right side of an object (e.g., between note and its accidentals).

`script-priority` (number)
: A sorting key that determines in what order a script is within a stack of scripts.

Internal properties:

`accidental-grobs` (list)
: An alist with (*`notename . groblist`*) entries.

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

This grob interface is used in the following graphical object(s): Section 3.1.3 [AccidentalPlacement], page 290.

3.2.3 accidental-suggestion-interface

An accidental, printed as a suggestion (typically: vertically over a note).

This grob interface is used in the following graphical object(s): Section 3.1.4 [AccidentalSuggestion], page 291.

3.2.4 align-interface

Order grobs from top to bottom, left to right, right to left or bottom to top. For vertical alignments of staves, the `break-system-details` of the left Section "NonMusicalPaperColumn" in *Internals Reference* may be set to tune vertical spacing.

User settable properties:

`align-dir` (direction)
: Which side to align? `-1`: left side, `0`: around center of width, `1`: right side.

`axes` (list)
: List of axis numbers. In the case of alignment grobs, this should contain only one number.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`stacking-dir` (direction)
: Stack objects in which direction?

Internal properties:

`elements` (array of grobs)
: An array of grobs; the type is depending on the grob where this is set in.

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

This grob interface is used in the following graphical object(s): Section 3.1.14 [BassFigureAlignment], page 300 and Section 3.1.129 [VerticalAlignment], page 399.

3.2.5 ambitus-interface

The line between note heads for a pitch range.

User settable properties:

`gap` (dimension, in staff space)
: Size of a gap in a variable symbol.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`note-heads` (array of grobs)
: An array of note head grobs.

This grob interface is used in the following graphical object(s): Section 3.1.5 [Ambitus], page 292, Section 3.1.7 [AmbitusLine], page 294 and Section 3.1.8 [AmbitusNoteHead], page 294.

3.2.6 arpeggio-interface

Functions and settings for drawing an arpeggio symbol.

User settable properties:

`arpeggio-direction` (direction)
: If set, put an arrow on the arpeggio squiggly line.

`positions` (pair of numbers)
: Pair of staff coordinates `(left . right)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

`script-priority` (number)
: A sorting key that determines in what order a script is within a stack of scripts.

`dash-definition` (pair)
: List of `dash-elements` defining the dash structure. Each `dash-element` has a starting t value, an ending t-value, a `dash-fraction`, and a `dash-period`.

Internal properties:

`stems` (array of grobs)
: An array of stem objects.

This grob interface is used in the following graphical object(s): Section 3.1.9 [Arpeggio], page 295.

3.2.7 axis-group-interface

An object that groups other layout objects.

User settable properties:

`axes` (list)
: List of axis numbers. In the case of alignment grobs, this should contain only one number.

`default-staff-staff-spacing` (list)
: The settings to use for `staff-staff-spacing` when it is unset, for ungrouped staves and for grouped staves that do not have the relevant `StaffGrouper` property set (`staff-staff-spacing` or `staffgroup-staff-spacing`).

`max-stretch` (number)
: The maximum amount that this `VerticalAxisGroup` can be vertically stretched (for example, in order to better fill a page).

`no-alignment` (boolean)
: If set, don't place this grob in a `VerticalAlignment`; rather, place it using its own `Y-offset` callback.

`nonstaff-nonstaff-spacing` (list)
: The spacing alist controlling the distance between the current non-staff line and the next non-staff line in the direction of `staff-affinity`, if both are on the same side of the related staff, and `staff-affinity` is either `UP` or `DOWN`. See `staff-staff-spacing` for a description of the alist structure.

`nonstaff-relatedstaff-spacing` (list)
: The spacing alist controlling the distance between the current non-staff line and the nearest staff in the direction of `staff-affinity`, if there are no non-staff lines between the two, and `staff-affinity` is either `UP` or `DOWN`. If `staff-affinity` is `CENTER`, then `nonstaff-relatedstaff-spacing` is used for the nearest staves on *both* sides, even if other non-staff lines appear between the current one and either of the staves. See `staff-staff-spacing` for a description of the alist structure.

`nonstaff-unrelatedstaff-spacing` (list)
: The spacing alist controlling the distance between the current non-staff line and the nearest staff in the opposite direction from `staff-affinity`, if there are no other non-staff lines between the two, and `staff-affinity` is either `UP` or `DOWN`. See `staff-staff-spacing` for a description of the alist structure.

`staff-affinity` (direction)
: The direction of the staff to use for spacing the current non-staff line. Choices are `UP`, `DOWN`, and `CENTER`. If `CENTER`, the non-staff line will be placed equidistant between the two nearest staves on either side, unless collisions or other spacing constraints prevent this. Setting `staff-affinity` for a staff causes it to be treated as a non-staff line. Setting `staff-affinity` to `#f` causes a non-staff line to be treated as a staff.

`staff-staff-spacing` (list)
: When applied to a staff-group's `StaffGrouper` grob, this spacing alist controls the distance between consecutive staves within the staff-group. When applied to a staff's `VerticalAxisGroup` grob, it controls the distance between the staff and the nearest staff below it in the same system, replacing any settings inherited from the `StaffGrouper` grob of the containing staff-group, if there is one. This property remains in effect even when non-staff lines appear between staves. The alist can contain the following keys:

  - `basic-distance` – the vertical distance, measured in staff-spaces, between the reference points of the two items when no collisions would result, and no stretching or compressing is in effect.
  - `minimum-distance` – the smallest allowable vertical distance, measured in staff-spaces, between the reference points of the two items, when compressing is in effect.
  - `padding` – the minimum required amount of unobstructed vertical whitespace between the bounding boxes (or skylines) of the two items, measured in staff-spaces.
  - `stretchability` – a unitless measure of the dimension's relative propensity to stretch. If zero, the distance will not stretch (unless collisions would result).

`vertical-skylines` (pair of skylines)
: Two skylines, one above and one below this grob.

Internal properties:

`adjacent-pure-heights` (pair)
: A pair of vectors. Used by a `VerticalAxisGroup` to cache the `Y-extent`s of different column ranges.

`elements` (array of grobs)
: An array of grobs; the type is depending on the grob where this is set in.

`pure-relevant-grobs` (array of grobs)
: All the grobs (items and spanners) that are relevant for finding the `pure-Y-extent`

`pure-relevant-items` (array of grobs)
: A subset of elements that are relevant for finding the `pure-Y-extent`.

`pure-relevant-spanners` (array of grobs)
: A subset of elements that are relevant for finding the `pure-Y-extent`.

`pure-Y-common` (graphical (layout) object)
: A cache of the `common_refpoint_of_array` of the `elements` grob set.

`staff-grouper` (graphical (layout) object)
: The staff grouper we belong to.

`system-Y-offset` (number)
: The Y-offset (relative to the bottom of the top-margin of the page) of the system to which this staff belongs.

`X-common` (graphical (layout) object)
: Common reference point for axis group.

`Y-common` (graphical (layout) object)
: See `X-common`.

This grob interface is used in the following graphical object(s): Section 3.1.5 [Ambitus], page 292, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.21 [BreakAlignGroup], page 304, Section 3.1.22 [BreakAlignment], page 305, Section 3.1.32 [DotColumn], page 314, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.71 [NonMusicalPaperColumn], page 349, Section 3.1.72 [NoteCollision], page 350, Section 3.1.73 [NoteColumn], page 350, Section 3.1.79 [PaperColumn], page 355, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.109 [System], page 380, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397, Section 3.1.129 [VerticalAlignment], page 399, Section 3.1.130 [VerticalAxisGroup], page 399 and Section 3.1.133 [VoltaBracketSpanner], page 402.

3.2.8 balloon-interface

A collection of routines to put text balloons around an object.

User settable properties:

`annotation-balloon` (boolean)
: Print the balloon around an annotation.

`annotation-line` (boolean)
: Print the line from an annotation to the grob that it annotates.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`text` (markup)
: Text markup. See Section "Formatting text" in *Notation Reference*.

Internal properties:

`spanner-placement` (direction)
: The place of an annotation on a spanner. LEFT is for the first spanner, and RIGHT is for the last. CENTER will place it on the broken spanner that falls closest to the center of the length of the entire spanner, although this behavior is unpredictable in situations with lots of rhythmic diversity. For predictable results, use LEFT and RIGHT.

This grob interface is used in the following graphical object(s): Section 3.1.10 [BalloonTextItem], page 296, Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

3.2.9 bar-line-interface

Bar line.

Print a special bar symbol. It replaces the regular bar symbol with a special symbol. The argument *bartype* is a string which specifies the kind of bar line to print. Options are `|`, `:|`, `|:`, `:|:`, `:|.|:`, `:|.:`, `.`, `||`, `|.`, `.|`, `.|.`, `|.|`, `:`, `dashed`, `'` and `S`.

These produce, respectively, a normal bar line, a right repeat, a left repeat, a thick double repeat, a thin-thick-thin double repeat, a thin-thick double repeat, a thick bar, a double bar, a start bar, an end bar, a thick double bar, a thin-thick-thin bar, a dotted bar, a dashed bar, a tick as bar line and a segno bar.

In addition, there is an option `||:` which is equivalent to `|:` except at line breaks, where it produces a double bar (`||`) at the end of the line and a repeat sign (`|:`) at the beginning of the new line.

For segno, `S` produces a segno sign except at line breaks, where it produces a double bar (`||`) at the end of the line and a segno sign at the beginning of the new line. `|S` is equivalent to `S` but produces a simple bar line (`|`) instead of a double bar line (`||`) at line breaks. `S|` produces the segno sign at line breaks and starts the following line without special bar lines.

`S|:` and `:|S` are used for repeat/segno combinations that are separated at line breaks. Alternatively, `.S|:` and `:|S.` may be used which combine repeat signs and segno at the same line in case of a line break. `:|S|:` is a combination of a left repeat (`:|`), a segno (`S`) and a right repeat `|:` which splits before the segno at line breaks; `:|S.|:` splits after the segno sign.

If *bartype* is set to `empty` then nothing is printed, but a line break is allowed at that spot.

`gap` is used for the gaps in dashed bar lines.

User settable properties:

`allow-span-bar` (boolean)
: If false, no inter-staff bar line will be created below this bar line.

`gap` (dimension, in staff space)
: Size of a gap in a variable symbol.

`kern` (dimension, in staff space)
: Amount of extra white space to add. For bar lines, this is the amount of space after a thick line.

`thin-kern` (number)
: The space after a hair-line in a bar line.

`hair-thickness` (number)
: Thickness of the thin line in a bar line.

`thick-thickness` (number)
: Bar line thickness, measured in `line-thickness`.

`glyph` (string)
: A string determining what 'style' of glyph is typeset. Valid choices depend on the function that is reading this property.

`glyph-name` (string)
: The glyph name within the font.

Internal properties:

`bar-extent` (pair of numbers)
: The Y-extent of the actual bar line. This may differ from `Y-extent` because it does not include the dots in a repeat bar line.

This grob interface is used in the following graphical object(s): Section 3.1.11 [BarLine], page 297 and Section 3.1.98 [SpanBar], page 370.

3.2.10 bass-figure-alignment-interface

Align a bass figure.

This grob interface is used in the following graphical object(s): Section 3.1.14 [BassFigure-Alignment], page 300.

3.2.11 bass-figure-interface

A bass figure text.

User settable properties:

`implicit` (boolean)
: Is this an implicit bass figure?

This grob interface is used in the following graphical object(s): Section 3.1.13 [BassFigure], page 300.

3.2.12 beam-interface

A beam.

The `beam-thickness` property is the weight of beams, measured in staffspace. The `direction` property is not user-serviceable. Use the `direction` property of `Stem` instead.

The following properties may be set in the `details` list.

`stem-length-demerit-factor`
: Demerit factor used for inappropriate stem lengths.

`secondary-beam-demerit`
: Demerit used in quanting calculations for multiple beams.

`region-size`
: Size of region for checking quant scores.

`beam-eps` Epsilon for beam quant code to check for presence in gap.

`stem-length-limit-penalty`
: Penalty for differences in stem lengths on a beam.

`damping-direction-penalty`
: Demerit penalty applied when beam direction is different from damping direction.

`hint-direction-penalty`
: Demerit penalty applied when beam direction is different from damping direction, but damping slope is <= `round-to-zero-slope`.

`musical-direction-factor`
: Demerit scaling factor for difference between beam slope and music slope.

`ideal-slope-factor`
: Demerit scaling factor for difference between beam slope and damping slope.

`round-to-zero-slope`
: Damping slope which is considered zero for purposes of calculating direction penalties.

User settable properties:

`annotation` (string)
: Annotate a grob for debug purposes.

`auto-knee-gap` (dimension, in staff space)
: If a gap is found between note heads where a horizontal beam fits that is larger than this number, make a kneed beam.

`beamed-stem-shorten` (list)
: How much to shorten beamed stems, when their direction is forced. It is a list, since the value is different depending on the number of flags and beams.

`beaming` (pair)
: Pair of number lists. Each number list specifies which beams to make. `0` is the central beam, `1` is the next beam toward the note, etc. This information is used to determine how to connect the beaming patterns from stem to stem inside a beam.

`beam-thickness` (dimension, in staff space)
: Beam thickness, measured in `staff-space` units.

`break-overshoot` (pair of numbers)
: How much does a broken spanner stick out of its bounds?

`clip-edges` (boolean)
: Allow outward pointing beamlets at the edges of beams?

`concaveness` (number)
: A beam is concave if its inner stems are closer to the beam than the two outside stems. This number is a measure of the closeness of the inner stems. It is used for damping the slope of the beam.

`collision-interfaces` (list)
: A list of interfaces for which automatic beam-collision resolution is run.

`collision-voice-only` (boolean)
: Does automatic beam collsion apply only to the voice in which the beam was created?

`damping` (number)
: Amount of beam slope damping.

`details` (list)
: Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`gap` (dimension, in staff space)
: Size of a gap in a variable symbol.

`gap-count` (integer)
: Number of gapped beams for tremolo.

`grow-direction` (direction)
: Crescendo or decrescendo?

`inspect-quants` (pair of numbers)
: If debugging is set, set beam and slur quants to this position, and print the respective scores.

`knee` (boolean)
: Is this beam kneed?

`length-fraction` (number)
: Multiplier for lengths. Used for determining ledger lines and stem lengths.

`neutral-direction` (direction)
: Which direction to take in the center of the staff.

`positions` (pair of numbers)
: Pair of staff coordinates `(`*`left . right`*`)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

Internal properties:

`covered-grobs` (array of grobs)
: Grobs that could potentially collide with a beam.

`least-squares-dy` (number)
: The ideal beam slope, without damping.

`normal-stems` (array of grobs)
: An array of visible stems.

`quantized-positions` (pair of numbers)
: The beam positions after quanting.

`shorten` (dimension, in staff space)
: The amount of space that a stem is shortened. Internally used to distribute beam shortening over stems.

`stems` (array of grobs)
: An array of stem objects.

This grob interface is used in the following graphical object(s): Section 3.1.19 [Beam], page 302.

3.2.13 bend-after-interface

A doit or drop.

User settable properties:

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`delta-position` (number)
: The vertical position difference.

This grob interface is used in the following graphical object(s): Section 3.1.20 [BendAfter], page 304.

3.2.14 break-alignable-interface

Object that is aligned on a break alignment.

User settable properties:

`break-align-symbols` (list)
: A list of symbols that determine which break-aligned grobs to align this to. If the grob selected by the first symbol in the list is invisible due to break-visibility, we will align to the next grob (and so on). Choices are `left-edge`, `ambitus`, `breathing-sign`, `clef`, `staff-bar`, `key-cancellation`, `key-signature`, `time-signature`, and `custos`.

`non-break-align-symbols` (list)
: A list of symbols that determine which NON-break-aligned interfaces to align this to.

This grob interface is used in the following graphical object(s): Section 3.1.12 [BarNumber], page 298, Section 3.1.67 [MetronomeMark], page 344 and Section 3.1.85 [RehearsalMark], page 360.

3.2.15 break-aligned-interface

Items that are aligned in prefatory matter.

The spacing of these items is controlled by the `space-alist` property. It contains a list `break-align-symbols` with a specification of the associated space. The space specification can be

`(minimum-space . spc))`
: Pad space until the distance is *spc*.

`(fixed-space . spc)`
: Set a fixed space.

`(semi-fixed-space . spc)`
: Set a space. Half of it is fixed and half is stretchable. (does not work at start of line. fixme)

`(extra-space . spc)`
: Add *spc* amount of space.

Special keys for the alist are `first-note` and `next-note`, signifying the first note on a line, and the next note halfway a line.

Rules for this spacing are much more complicated than this. See [Wanske] page 126–134, [Ross] page 143–147.

User settable properties:

`break-align-anchor` (number)
: Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-anchor-alignment` (number)
: Read by `ly:break-aligned-interface::calc-extent-aligned-anchor` for aligning an anchor to a grob's extent.

`break-align-symbol` (symbol)
: This key is used for aligning and spacing breakable items.

`space-alist` (list)
: A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

This grob interface is used in the following graphical object(s): Section 3.1.5 [Ambitus], page 292, Section 3.1.6 [AmbitusAccidental], page 293, Section 3.1.11 [BarLine], page 297, Section 3.1.21 [BreakAlignGroup], page 304, Section 3.1.23 [BreathingSign], page 306, Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.31 [Custos], page 313, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.58 [LeftEdge], page 338 and Section 3.1.119 [TimeSignature], page 390.

3.2.16 break-alignment-interface

The object that performs break alignment. See Section 3.2.15 [break-aligned-interface], page 413.

User settable properties:

`break-align-orders` (vector)
: Defines the order in which prefatory matter (clefs, key signatures) appears. The format is a vector of length 3, where each element is one order for end-of-line, middle of line, and start-of-line, respectively. An order is a list of symbols.

  For example, clefs are put after key signatures by setting

```
\override Score.BreakAlignment #'break-align-orders =
  #(make-vector 3 '(span-bar
                    breathing-sign
                    staff-bar
                    key
```

```
clef
time-signature))
```

Internal properties:

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

This grob interface is used in the following graphical object(s): Section 3.1.22 [BreakAlignment], page 305.

3.2.17 breathing-sign-interface

A breathing sign.

User settable properties:

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

This grob interface is used in the following graphical object(s): Section 3.1.23 [BreathingSign], page 306.

3.2.18 chord-name-interface

A chord label (name or fretboard).

Internal properties:

`begin-of-line-visible` (boolean)
: Set to make `ChordName` or `FretBoard` be visible only at beginning of line or at chord changes.

This grob interface is used in the following graphical object(s): Section 3.1.24 [ChordName], page 307 and Section 3.1.44 [FretBoard], page 326.

3.2.19 clef-interface

A clef sign.

User settable properties:

`full-size-change` (boolean)
: Don't make a change clef smaller.

`glyph` (string)
: A string determining what 'style' of glyph is typeset. Valid choices depend on the function that is reading this property.

`glyph-name` (string)
: The glyph name within the font.

`non-default` (boolean)
: Set for manually specified clefs.

This grob interface is used in the following graphical object(s): Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311 and Section 3.1.30 [CueEndClef], page 312.

3.2.20 cluster-beacon-interface

A place holder for the cluster spanner to determine the vertical extents of a cluster spanner at this X position.

User settable properties:

`positions` (pair of numbers)
: Pair of staff coordinates `(left . right)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

This grob interface is used in the following graphical object(s): Section 3.1.27 [ClusterSpannerBeacon], page 309.

3.2.21 cluster-interface

A graphically drawn musical cluster.

`padding` adds to the vertical extent of the shape (top and bottom).

The property `style` controls the shape of cluster segments. Valid values include `leftsided-stairs`, `rightsided-stairs`, `centered-stairs`, and `ramp`.

User settable properties:

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

Internal properties:

`columns` (array of grobs)
: An array of grobs, typically containing `PaperColumn` or `NoteColumn` objects.

This grob interface is used in the following graphical object(s): Section 3.1.26 [ClusterSpanner], page 309.

3.2.22 custos-interface

A custos object. `style` can have four valid values: `mensural`, `vaticana`, `medicaea`, and `hufnagel`. `mensural` is the default style.

User settable properties:

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`neutral-position` (number)
: Position (in half staff spaces) where to flip the direction of custos stem.

`neutral-direction` (direction)
: Which direction to take in the center of the staff.

This grob interface is used in the following graphical object(s): Section 3.1.31 [Custos], page 313.

3.2.23 dot-column-interface

Group dot objects so they form a column, and position dots so they do not clash with staff lines.

User settable properties:

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

Internal properties:

`dots` (array of grobs)
: Multiple `Dots` objects.

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

This grob interface is used in the following graphical object(s): Section 3.1.32 [DotColumn], page 314.

3.2.24 dots-interface

The dots to go with a notehead or rest. `direction` sets the preferred direction to move in case of staff line collisions. `style` defaults to undefined, which is normal 19th/20th century traditional style. Set `style` to `vaticana` for ancient type dots.

User settable properties:

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`dot-count` (integer)
: The number of dots.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

This grob interface is used in the following graphical object(s): Section 3.1.33 [Dots], page 315.

3.2.25 dynamic-interface

Any kind of loudness sign.

This grob interface is used in the following graphical object(s): Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321 and Section 3.1.49 [Hairpin], page 330.

3.2.26 dynamic-line-spanner-interface

Dynamic line spanner.

User settable properties:

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

This grob interface is used in the following graphical object(s): Section 3.1.37 [DynamicLineSpanner], page 318.

3.2.27 dynamic-text-interface

An absolute text dynamic.

User settable properties:

`right-padding` (dimension, in staff space)
: Space to insert on the right side of an object (e.g., between note and its accidentals).

This grob interface is used in the following graphical object(s): Section 3.1.38 [DynamicText], page 319.

3.2.28 dynamic-text-spanner-interface

Dynamic text spanner.

User settable properties:

`text` (markup)
: Text markup. See Section “Formatting text” in *Notation Reference*.

This grob interface is used in the following graphical object(s): Section 3.1.39 [DynamicTextSpanner], page 321.

3.2.29 enclosing-bracket-interface

Brackets alongside bass figures.

User settable properties:

`bracket-flare` (pair of numbers)
: A pair of numbers specifying how much edges of brackets should slant outward. Value `0.0` means straight edges.

`edge-height` (pair)
: A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`shorten-pair` (pair of numbers)
: The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`elements` (array of grobs)
: An array of grobs; the type is depending on the grob where this is set in.

This grob interface is used in the following graphical object(s): Section 3.1.16 [BassFigureBracket], page 301.

3.2.30 episema-interface

An episema line.

This grob interface is used in the following graphical object(s): Section 3.1.40 [Episema], page 322.

3.2.31 figured-bass-continuation-interface

Simple extender line between bounds.

User settable properties:

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

Internal properties:

`figures` (array of grobs)
: Figured bass objects for continuation line.

This grob interface is used in the following graphical object(s): Section 3.1.17 [BassFigureContinuation], page 301.

3.2.32 finger-interface

A fingering instruction.

This grob interface is used in the following graphical object(s): Section 3.1.41 [Fingering], page 323.

3.2.33 font-interface

Any symbol that is typeset through fixed sets of glyphs, (i.e., fonts).

User settable properties:

`font-encoding` (symbol)
: The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`font-family` (symbol)
: The font family is the broadest category for selecting text fonts. Options include: `sans`, `roman`.

`font-name` (string)
: Specifies a file name (without extension) of the font to load. This setting overrides selection using `font-family`, `font-series` and `font-shape`.

`font-series` (symbol)
: Select the series of a font. Choices include `medium`, `bold`, `bold-narrow`, etc.

`font-shape` (symbol)
: Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`font-size` (number)
: The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

Internal properties:

`font` (font metric)
: A cached font metric object.

This grob interface is used in the following graphical object(s): Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.6 [AmbitusAccidental], page 293, Section 3.1.7 [AmbitusLine], page 294, Section 3.1.8 [AmbitusNoteHead], page 294, Section 3.1.9 [Arpeggio], page 295, Section 3.1.10 [BalloonTextItem], page 296, Section 3.1.11 [BarLine], page 297, Section 3.1.12 [BarNumber], page 298, Section 3.1.13 [BassFigure], page 300, Section 3.1.19 [Beam], page 302, Section 3.1.23 [BreathingSign], page 306, Section 3.1.24 [ChordName], page 307, Section 3.1.25 [Clef], page 307, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.31 [Custos], page 313, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.40 [Episema], page 322, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.44 [FretBoard], page 326, Section 3.1.51 [InstrumentName], page 332, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.61 [LyricHyphen], page 340, Section 3.1.63 [LyricText], page 342, Section 3.1.66 [MensuralLigature], page 344, Section 3.1.67 [MetronomeMark], page 344, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.71 [NonMusicalPaperColumn], page 349, Section 3.1.74 [NoteHead], page 351, Section 3.1.75 [NoteName], page 352, Section 3.1.77 [OctavateEight], page 353, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.79 [PaperColumn], page 355, Section 3.1.80 [ParenthesesItem], page 356, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.85 [RehearsalMark], page 360, Section 3.1.89 [Rest], page 364, Section 3.1.91 [Script], page 365, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.98 [SpanBar], page 370, Section 3.1.102 [StanzaNumber], page 373, Section 3.1.103 [Stem], page 374, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.107 [SustainPedal], page 378, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383, Section 3.1.114 [TabNoteHead], page 384, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.119 [TimeSignature], page 390, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.125 [TupletNum-

ber], page 396, Section 3.1.126 [UnaCordaPedal], page 396, Section 3.1.128 [VaticanaLigature], page 398 and Section 3.1.132 [VoltaBracket], page 401.

3.2.34 footnote-interface

Make a footnote.

User settable properties:

`footnote-text` (markup)
A footnote for the grob.

This grob interface is used in the following graphical object(s): Section 3.1.42 [FootnoteItem], page 324 and Section 3.1.43 [FootnoteSpanner], page 325.

3.2.35 footnote-spanner-interface

Make a footnote spanner.

User settable properties:

`footnote-text` (markup)
A footnote for the grob.

Internal properties:

`spanner-placement` (direction)
The place of an annotation on a spanner. LEFT is for the first spanner, and RIGHT is for the last. CENTER will place it on the broken spanner that falls closest to the center of the length of the entire spanner, although this behavior is unpredictable in situations with lots of rhythmic diversity. For predictable results, use LEFT and RIGHT.

This grob interface is used in the following graphical object(s): Section 3.1.43 [FootnoteSpanner], page 325.

3.2.36 fret-diagram-interface

A fret diagram

User settable properties:

`align-dir` (direction)
Which side to align? `-1`: left side, `0`: around center of width, `1`: right side.

`fret-diagram-details` (list)
An alist of detailed grob properties for fret diagrams. Each alist entry consists of a `(`*`property . value`*`)` pair. The properties which can be included in `fret-diagram-details` include the following:

- `barre-type` – Type of barre indication used. Choices include `curved`, `straight`, and `none`. Default `curved`.
- `capo-thickness` – Thickness of capo indicator, in multiples of fret-space. Default value 0.5.
- `dot-color` – Color of dots. Options include `black` and `white`. Default `black`.
- `dot-label-font-mag` – Magnification for font used to label fret dots. Default value 1.

- `dot-position` – Location of dot in fret space. Default 0.6 for dots without labels, 0.95-`dot-radius` for dots with labels.
- `dot-radius` – Radius of dots, in terms of fret spaces. Default value 0.425 for labeled dots, 0.25 for unlabeled dots.
- `finger-code` – Code for the type of fingering indication used. Options include `none`, `in-dot`, and `below-string`. Default `none` for markup fret diagrams, `below-string` for `FretBoards` fret diagrams.
- `fret-count` – The number of frets. Default 4.
- `fret-label-custom-format` – The format string to be used label the lowest fret number, when `number-type` equals to `custom`. Default `"~a"`.
- `fret-label-font-mag` – The magnification of the font used to label the lowest fret number. Default 0.5.
- `fret-label-vertical-offset` – The offset of the fret label from the center of the fret in direction parallel to strings. Default 0.
- `label-dir` – Side to which the fret label is attached. `-1`, `#LEFT`, or `#DOWN` for left or down; `1`, `#RIGHT`, or `#UP` for right or up. Default `#RIGHT`.
- `mute-string` – Character string to be used to indicate muted string. Default `"x"`.
- `number-type` – Type of numbers to use in fret label. Choices include `roman-lower`, `roman-upper`, `arabic` and `custom`. In the later case, the format string is supplied by the `fret-label-custom-format` property. Default `roman-lower`.
- `open-string` – Character string to be used to indicate open string. Default `"o"`.
- `orientation` – Orientation of fret-diagram. Options include `normal`, `landscape`, and `opposing-landscape`. Default `normal`.
- `string-count` – The number of strings. Default 6.
- `string-label-font-mag` – The magnification of the font used to label fingerings at the string, rather than in the dot. Default value 0.6 for `normal` orientation, 0.5 for `landscape` and `opposing-landscape`.
- `string-thickness-factor` – Factor for changing thickness of each string in the fret diagram. Thickness of string k is given by `thickness` * (1+`string-thickness-factor`) ^ (k-1). Default 0.
- `top-fret-thickness` – The thickness of the top fret line, as a multiple of the standard thickness. Default value 3.
- `xo-font-magnification` – Magnification used for mute and open string indicators. Default value 0.5.
- `xo-padding` – Padding for open and mute indicators from top fret. Default value 0.25.

`size` (number)
: Size of object, relative to standard size.

`dot-placement-list` (list)
: List consisting of `(`*`description string-number fret-number finger-number`*`)` entries used to define fret diagrams.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

This grob interface is used in the following graphical object(s): Section 3.1.44 [FretBoard], page 326.

3.2.37 glissando-interface

A glissando.

Internal properties:

`glissando-index` (integer)
: The index of a glissando in its note column.

This grob interface is used in the following graphical object(s): Section 3.1.45 [Glissando], page 327.

3.2.38 grace-spacing-interface

Keep track of durations in a run of grace notes.

User settable properties:

`common-shortest-duration` (moment)
: The most common shortest note length. This is used in spacing. Enlarging this sets the score tighter.

Internal properties:

`columns` (array of grobs)
: An array of grobs, typically containing `PaperColumn` or `NoteColumn` objects.

This grob interface is used in the following graphical object(s): Section 3.1.46 [GraceSpacing], page 328.

3.2.39 gregorian-ligature-interface

A gregorian ligature.

Internal properties:

`virga` (boolean)
: Is this neume a virga?

`stropha` (boolean)
: Is this neume a stropha?

`inclinatum` (boolean)
: Is this neume an inclinatum?

`auctum` (boolean)
: Is this neume liquescentically augmented?

`descendens` (boolean)
: Is this neume of descendent type?

`ascendens` (boolean)
: Is this neume of ascending type?

`oriscus` (boolean)
: Is this neume an oriscus?

`quilisma` (boolean)
: Is this neume a quilisma?

`deminutum` (boolean)
: Is this neume deminished?

`cavum` (boolean)
: Is this neume outlined?

`linea` (boolean)
: Attach vertical lines to this neume?

`pes-or-flexa` (boolean)
: Shall this neume be joined with the previous head?

`context-info` (integer)
: Within a ligature, the final glyph or shape of a head may be affected by the left and/or right neighbour head. `context-info` holds for each head such information about the left and right neighbour, encoded as a bit mask.

`prefix-set` (number)
: A bit mask that holds all Gregorian head prefixes, such as `\virga` or `\quilisma`.

This grob interface is used in the following graphical object(s): Section 3.1.74 [NoteHead], page 351.

3.2.40 grid-line-interface

A line that is spanned between grid-points.

User settable properties:

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`elements` (array of grobs)
: An array of grobs; the type is depending on the grob where this is set in.

This grob interface is used in the following graphical object(s): Section 3.1.47 [GridLine], page 329.

3.2.41 grid-point-interface

A spanning point for grid lines.

This grob interface is used in the following graphical object(s): Section 3.1.48 [GridPoint], page 329.

3.2.42 grob-interface

A grob represents a piece of music notation.

All grobs have an X and Y position on the page. These X and Y positions are stored in a relative format, thus they can easily be combined by stacking them, hanging one grob to the side of another, or coupling them into grouping objects.

Each grob has a reference point (a.k.a. parent): The position of a grob is stored relative to that reference point. For example, the X reference point of a staccato dot usually is the note head that it applies to. When the note head is moved, the staccato dot moves along automatically.

A grob is often associated with a symbol, but some grobs do not print any symbols. They take care of grouping objects. For example, there is a separate grob that stacks staves vertically. The Section 3.1.72 [NoteCollision], page 350 object is also an abstract grob: It only moves around chords, but doesn't print anything.

Grobs have properties (Scheme variables) that can be read and set. Two types of them exist: immutable and mutable. Immutable variables define the default style and behavior. They are shared between many objects. They can be changed using `\override` and `\revert`. Mutable properties are variables that are specific to one grob. Typically, lists of other objects, or results from computations are stored in mutable properties. In particular, every call to `ly:grob-set-property!` (or its C++ equivalent) sets a mutable property.

The properties `after-line-breaking` and `before-line-breaking` are dummies that are not user-serviceable.

User settable properties:

`X-extent` (pair of numbers)
: Hard coded extent in X direction.

`X-offset` (number)
: The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers)
: Hard coded extent in Y direction.

`Y-offset` (number)
: The vertical amount that this object is moved relative to its Y-parent.

`after-line-breaking` (boolean)
: Dummy property, used to trigger callback for `after-line-breaking`.

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`before-line-breaking` (boolean)
: Dummy property, used to trigger a callback function.

`color` (color)
: The color of this grob.

`extra-X-extent` (pair of numbers)
: A grob is enlarged in X dimension by this much.

`extra-Y-extent` (pair of numbers)
: A grob is enlarged in Y dimension by this much.

`extra-offset` (pair of numbers)
: A pair representing an offset. This offset is added just before outputting the symbol, so the typesetting engine is completely oblivious to it. The values are measured in `staff-space` units of the staff's `StaffSymbol`.

`layer` (integer)
: An integer which determines the order of printing objects. Objects with the lowest value of layer are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a layer value of 1.

`minimum-X-extent` (pair of numbers)
: Minimum size of an object in X dimension, measured in `staff-space` units.

`minimum-Y-extent` (pair of numbers)
: Minimum size of an object in Y dimension, measured in `staff-space` units.

`outside-staff-horizontal-padding` (number)
: By default, an outside-staff-object can be placed so that is it very close to another grob horizontally. If this property is set, the outside-staff-object is raised so that it is not so close to its neighbor.

`outside-staff-padding` (number)
: The padding to place between this grob and the staff when spacing according to `outside-staff-priority`.

`outside-staff-priority` (number)
: If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`rotation` (list)
: Number of degrees to rotate this object, and what point to rotate around. For example, `#'(45 0 0)` rotates by 45 degrees around the center of this object.

`springs-and-rods` (boolean)
: Dummy variable for triggering spacing routines.

`stencil` (stencil)
: The symbol to print.

`transparent` (boolean)
: This makes the grob invisible.

`whiteout` (boolean)
: If true, the grob is printed over a white background to white-out underlying material, if the grob is visible. Usually #f by default.

Internal properties:

`axis-group-parent-X` (graphical (layout) object)
: Containing X axis group.

`axis-group-parent-Y` (graphical (layout) object)
: Containing Y axis group.

`cause` (any type)
: Any kind of causation objects (i.e., music, or perhaps translator) that was the cause for this grob.

`cross-staff` (boolean)
: For a beam or a stem, this is true if we depend on inter-staff spacing.

`interfaces` (list)
: A list of symbols indicating the interfaces supported by this object. It is initialized from the `meta` field.

`meta` (list)
: Provide meta information. It is an alist with the entries `name` and `interfaces`.

`pure-Y-offset-in-progress` (boolean)
: A debugging aid for catching cyclic dependencies.

`staff-symbol` (graphical (layout) object)
: The staff symbol grob that we are in.

This grob interface is used in the following graphical object(s): Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290, Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.5 [Ambitus], page 292, Section 3.1.6 [AmbitusAccidental], page 293, Section 3.1.7 [AmbitusLine], page 294, Section 3.1.8 [AmbitusNoteHead], page 294, Section 3.1.9 [Arpeggio], page 295, Section 3.1.10 [BalloonTextItem], page 296, Section 3.1.11 [BarLine], page 297, Section 3.1.12 [BarNumber], page 298, Section 3.1.13 [BassFigure], page 300, Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.16 [BassFigureBracket], page 301, Section 3.1.17 [BassFigureContinuation], page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.21 [BreakAlignGroup], page 304, Section 3.1.22 [BreakAlignment], page 305, Section 3.1.23 [BreathingSign], page 306, Section 3.1.24 [ChordName], page 307, Section 3.1.25 [Clef], page 307, Section 3.1.26 [ClusterSpanner], page 309, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.31 [Custos], page 313, Section 3.1.32 [DotColumn], page 314, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.40 [Episema], page 322, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.44 [FretBoard], page 326, Section 3.1.45 [Glissando], page 327, Section 3.1.46 [GraceSpacing], page 328, Section 3.1.47 [GridLine], page 329, Section 3.1.48 [GridPoint], page 329, Section 3.1.49 [Hairpin], page 330, Section 3.1.50 [HorizontalBracket], page 331, Section 3.1.51 [InstrumentName], page 332, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.58 [LeftEdge], page 338, Section 3.1.59 [LigatureBracket], page 339, Section 3.1.60 [LyricExtender], page 340, Section 3.1.61 [LyricHyphen], page 340, Section 3.1.62 [LyricSpace], page 341, Section 3.1.63 [LyricText], page 342, Section 3.1.64 [MeasureGrouping], page 343, Section 3.1.65 [MelodyItem], page 344, Section 3.1.66 [MensuralLigature], page 344, Section 3.1.67 [MetronomeMark], page 344, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.71 [NonMusicalPaperColumn], page 349, Section 3.1.72 [NoteCollision], page 350, Section 3.1.73 [NoteColumn], page 350, Section 3.1.74 [NoteHead], page 351, Section 3.1.75 [NoteName], page 352, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.77 [OctavateEight], page 353, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.79 [PaperColumn], page 355, Section 3.1.80 [ParenthesesItem], page 356, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83

[PhrasingSlur], page 358, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.85 [RehearsalMark], page 360, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.90 [RestCollision], page 364, Section 3.1.91 [Script], page 365, Section 3.1.92 [ScriptColumn], page 365, Section 3.1.93 [ScriptRow], page 366, Section 3.1.94 [Slur], page 366, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.97 [SpacingSpanner], page 369, Section 3.1.98 [SpanBar], page 370, Section 3.1.99 [StaffGrouper], page 371, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.102 [StanzaNumber], page 373, Section 3.1.103 [Stem], page 374, Section 3.1.104 [StemTremolo], page 375, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.107 [SustainPedal], page 378, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.109 [System], page 380, Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383, Section 3.1.114 [TabNoteHead], page 384, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.119 [TimeSignature], page 390, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.125 [TupletNumber], page 396, Section 3.1.126 [UnaCordaPedal], page 396, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397, Section 3.1.128 [VaticanaLigature], page 398, Section 3.1.129 [VerticalAlignment], page 399, Section 3.1.130 [VerticalAxisGroup], page 399, Section 3.1.131 [VoiceFollower], page 401, Section 3.1.132 [VoltaBracket], page 401 and Section 3.1.133 [VoltaBracketSpanner], page 402.

3.2.43 hairpin-interface

A hairpin crescendo or decrescendo.

User settable properties:

`circled-tip` (boolean)
: Put a circle at start/end of hairpins (al/del niente).

`bound-padding` (number)
: The amount of padding to insert around spanner bounds.

`grow-direction` (direction)
: Crescendo or decrescendo?

`height` (dimension, in staff space)
: Height of an object in `staff-space` units.

Internal properties:

`adjacent-spanners` (array of grobs)
: An array of directly neighboring dynamic spanners.

This grob interface is used in the following graphical object(s): Section 3.1.49 [Hairpin], page 330.

3.2.44 hara-kiri-group-spanner-interface

A group spanner that keeps track of interesting items. If it doesn't contain any after line breaking, it removes itself and all its children.

User settable properties:

`remove-empty` (boolean)
: If set, remove group if it contains no interesting items.

`remove-first` (boolean)
: Remove the first staff of an orchestral score?

Internal properties:

`items-worth-living` (array of grobs)
: An array of interesting items. If empty in a particular staff, then that staff is erased.

`important-column-ranks` (vector)
: A cache of columns that contain `items-worth-living` data.

`keep-alive-with` (array of grobs)
: An array of other `VerticalAxisGroup`s. If any of them are alive, then we will stay alive.

This grob interface is used in the following graphical object(s): Section 3.1.130 [VerticalAxisGroup], page 399.

3.2.45 horizontal-bracket-interface

A horizontal bracket encompassing notes.

User settable properties:

`bracket-flare` (pair of numbers)
: A pair of numbers specifying how much edges of brackets should slant outward. Value `0.0` means straight edges.

`edge-height` (pair)
: A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`shorten-pair` (pair of numbers)
: The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`connect-to-neighbor` (pair)
: Pair of booleans, indicating whether this grob looks as a continued break.

Internal properties:

`columns` (array of grobs)
: An array of grobs, typically containing `PaperColumn` or `NoteColumn` objects.

This grob interface is used in the following graphical object(s): Section 3.1.50 [HorizontalBracket], page 331, Section 3.1.78 [OttavaBracket], page 354 and Section 3.1.132 [VoltaBracket], page 401.

3.2.46 inline-accidental-interface

An inlined accidental (i.e. normal accidentals, cautionary accidentals).

This grob interface is used in the following graphical object(s): Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289 and Section 3.1.120 [TrillPitchAccidental], page 391.

3.2.47 instrument-specific-markup-interface

Instrument-specific markup (like fret boards or harp pedal diagrams).

User settable properties:

`fret-diagram-details` (list)
: An alist of detailed grob properties for fret diagrams. Each alist entry consists of a `(property . value)` pair. The properties which can be included in `fret-diagram-details` include the following:

  - `barre-type` – Type of barre indication used. Choices include `curved`, `straight`, and `none`. Default `curved`.
  - `capo-thickness` – Thickness of capo indicator, in multiples of fret-space. Default value 0.5.
  - `dot-color` – Color of dots. Options include `black` and `white`. Default `black`.
  - `dot-label-font-mag` – Magnification for font used to label fret dots. Default value 1.
  - `dot-position` – Location of dot in fret space. Default 0.6 for dots without labels, 0.95-`dot-radius` for dots with labels.
  - `dot-radius` – Radius of dots, in terms of fret spaces. Default value 0.425 for labeled dots, 0.25 for unlabeled dots.
  - `finger-code` – Code for the type of fingering indication used. Options include `none`, `in-dot`, and `below-string`. Default `none` for markup fret diagrams, `below-string` for `FretBoards` fret diagrams.
  - `fret-count` – The number of frets. Default 4.
  - `fret-label-custom-format` – The format string to be used label the lowest fret number, when `number-type` equals to `custom`. Default `"~a"`.
  - `fret-label-font-mag` – The magnification of the font used to label the lowest fret number. Default 0.5.
  - `fret-label-vertical-offset` – The offset of the fret label from the center of the fret in direction parallel to strings. Default 0.
  - `label-dir` – Side to which the fret label is attached. `-1`, `#LEFT`, or `#DOWN` for left or down; `1`, `#RIGHT`, or `#UP` for right or up. Default `#RIGHT`.
  - `mute-string` – Character string to be used to indicate muted string. Default `"x"`.
  - `number-type` – Type of numbers to use in fret label. Choices include `roman-lower`, `roman-upper`, `arabic` and `custom`. In the later case, the format string is supplied by the `fret-label-custom-format` property. Default `roman-lower`.

- `open-string` – Character string to be used to indicate open string. Default `"o"`.
- `orientation` – Orientation of fret-diagram. Options include `normal`, `landscape`, and `opposing-landscape`. Default `normal`.
- `string-count` – The number of strings. Default 6.
- `string-label-font-mag` – The magnification of the font used to label fingerings at the string, rather than in the dot. Default value 0.6 for `normal` orientation, 0.5 for `landscape` and `opposing-landscape`.
- `string-thickness-factor` – Factor for changing thickness of each string in the fret diagram. Thickness of string *k* is given by `thickness` * (1+`string-thickness-factor`) ^ (*k*-1). Default 0.
- `top-fret-thickness` – The thickness of the top fret line, as a multiple of the standard thickness. Default value 3.
- `xo-font-magnification` – Magnification used for mute and open string indicators. Default value 0.5.
- `xo-padding` – Padding for open and mute indicators from top fret. Default value 0.25.

`graphical` (boolean)
: Display in graphical (vs. text) form.

`harp-pedal-details` (list)
: An alist of detailed grob properties for harp pedal diagrams. Each alist entry consists of a (*`property . value`*) pair. The properties which can be included in harp-pedal-details include the following:

  - `box-offset` – Vertical shift of the center of flat/sharp pedal boxes above/below the horizontal line. Default value 0.8.
  - `box-width` – Width of each pedal box. Default value 0.4.
  - `box-height` – Height of each pedal box. Default value 1.0.
  - `space-before-divider` – Space between boxes before the first divider (so that the diagram can be made symmetric). Default value 0.8.
  - `space-after-divider` – Space between boxes after the first divider. Default value 0.8.
  - `circle-thickness` – Thickness (in unit of the line-thickness) of the ellipse around circled pedals. Default value 0.5.
  - `circle-x-padding` – Padding in X direction of the ellipse around circled pedals. Default value 0.15.
  - `circle-y-padding` – Padding in Y direction of the ellipse around circled pedals. Default value 0.2.

`size` (number)
: Size of object, relative to standard size.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

This grob interface is used in the following graphical object(s): Section 3.1.115 [TextScript], page 385.

3.2.48 item-interface

Grobs can be distinguished in their role in the horizontal spacing. Many grobs define constraints on the spacing by their sizes, for example, note heads, clefs, stems, and all other symbols with a fixed shape. These grobs form a subtype called `Item`.

Some items need special treatment for line breaking. For example, a clef is normally only printed at the start of a line (i.e., after a line break). To model this, 'breakable' items (clef, key signature, bar lines, etc.) are copied twice. Then we have three versions of each breakable item: one version if there is no line break, one version that is printed before the line break (at the end of a system), and one version that is printed after the line break.

Whether these versions are visible and take up space is determined by the outcome of the `break-visibility` grob property, which is a function taking a direction (`-1`, `0` or `1`) as an argument. It returns a cons of booleans, signifying whether this grob should be transparent and have no extent.

The following variables for `break-visibility` are predefined:

grob will show:	before break	no break	after break
all-invisible	no	no	no
begin-of-line-visible	no	no	yes
end-of-line-visible	yes	no	no
all-visible	yes	yes	yes
begin-of-line-invisible	yes	yes	no
end-of-line-invisible	no	yes	yes
center-invisible	yes	no	yes

User settable properties:

`break-visibility` (vector)
: A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`extra-spacing-height` (pair of numbers)
: In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`extra-spacing-width` (pair of numbers)
: In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`non-musical` (boolean)
: True if the grob belongs to a `NonMusicalPaperColumn`.

This grob interface is used in the following graphical object(s): Section 3.1.1 [Accidental], page 289, Section 3.1.2 [AccidentalCautionary], page 289, Section 3.1.3 [AccidentalPlacement], page 290, Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.5 [Ambitus], page 292, Section 3.1.6 [AmbitusAccidental], page 293, Section 3.1.7 [AmbitusLine], page 294, Section 3.1.8 [AmbitusNoteHead], page 294, Section 3.1.9 [Arpeggio], page 295, Section 3.1.10 [BalloonTextItem], page 296, Section 3.1.11 [BarLine], page 297, Section 3.1.12 [BarNumber], page 298, Section 3.1.13 [BassFigure], page 300, Section 3.1.16 [BassFigure-

Bracket], page 301, Section 3.1.21 [BreakAlignGroup], page 304, Section 3.1.22 [BreakAlignment], page 305, Section 3.1.23 [BreathingSign], page 306, Section 3.1.24 [ChordName], page 307, Section 3.1.25 [Clef], page 307, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.31 [Custos], page 313, Section 3.1.32 [DotColumn], page 314, Section 3.1.33 [Dots], page 315, Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.38 [DynamicText], page 319, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.44 [FretBoard], page 326, Section 3.1.47 [GridLine], page 329, Section 3.1.48 [GridPoint], page 329, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.55 [LaissezVibrerTie], page 336, Section 3.1.56 [LaissezVibrerTieColumn], page 337, Section 3.1.58 [LeftEdge], page 338, Section 3.1.63 [LyricText], page 342, Section 3.1.65 [MelodyItem], page 344, Section 3.1.67 [MetronomeMark], page 344, Section 3.1.71 [NonMusicalPaperColumn], page 349, Section 3.1.72 [NoteCollision], page 350, Section 3.1.73 [NoteColumn], page 350, Section 3.1.74 [NoteHead], page 351, Section 3.1.75 [NoteName], page 352, Section 3.1.76 [NoteSpacing], page 352, Section 3.1.77 [OctavateEight], page 353, Section 3.1.79 [PaperColumn], page 355, Section 3.1.80 [ParenthesesItem], page 356, Section 3.1.85 [RehearsalMark], page 360, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.87 [RepeatTie], page 362, Section 3.1.88 [RepeatTieColumn], page 363, Section 3.1.89 [Rest], page 364, Section 3.1.90 [RestCollision], page 364, Section 3.1.91 [Script], page 365, Section 3.1.92 [ScriptColumn], page 365, Section 3.1.93 [ScriptRow], page 366, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.98 [SpanBar], page 370, Section 3.1.100 [StaffSpacing], page 372, Section 3.1.102 [StanzaNumber], page 373, Section 3.1.103 [Stem], page 374, Section 3.1.104 [StemTremolo], page 375, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.107 [SustainPedal], page 378, Section 3.1.114 [TabNoteHead], page 384, Section 3.1.115 [TextScript], page 385, Section 3.1.119 [TimeSignature], page 390, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.122 [TrillPitchHead], page 393 and Section 3.1.126 [UnaCordaPedal], page 396.

3.2.49 key-cancellation-interface

A key cancellation.

This grob interface is used in the following graphical object(s): Section 3.1.53 [KeyCancellation], page 334.

3.2.50 key-signature-interface

A group of accidentals, to be printed as signature sign.

User settable properties:

`alteration-alist` (list)
: List of (*`pitch . accidental`*) pairs for key signature.

`c0-position` (integer)
: An integer indicating the position of middle C.

`glyph-name-alist` (list)
: An alist of key-string pairs.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`padding-pairs` (list)
: An alist mapping (*`name . name`*) to distances.

This grob interface is used in the following graphical object(s): Section 3.1.53 [KeyCancellation], page 334 and Section 3.1.54 [KeySignature], page 335.

3.2.51 ledger-line-spanner-interface

This spanner draws the ledger lines of a staff. This is a separate grob because it has to process all potential collisions between all note heads.

User settable properties:

`gap` (dimension, in staff space)
: Size of a gap in a variable symbol.

`length-fraction` (number)
: Multiplier for lengths. Used for determining ledger lines and stem lengths.

`minimum-length-fraction` (number)
: Minimum length of ledger line as fraction of note head size.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`note-heads` (array of grobs)
: An array of note head grobs.

This grob interface is used in the following graphical object(s): Section 3.1.57 [LedgerLineSpanner], page 337.

3.2.52 ledgered-interface

Objects that need ledger lines, typically note heads. See also Section 3.2.51 [ledger-line-spanner-interface], page 434.

User settable properties:

`no-ledgers` (boolean)
: If set, don't draw ledger lines on this object.

This grob interface is used in the following graphical object(s): Section 3.1.8 [AmbitusNoteHead], page 294, Section 3.1.74 [NoteHead], page 351 and Section 3.1.122 [TrillPitchHead], page 393.

3.2.53 ligature-bracket-interface

A bracket indicating a ligature in the original edition.

User settable properties:

`width` (dimension, in staff space)
: The width of a grob measured in staff space.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

`height` (dimension, in staff space)
: Height of an object in `staff-space` units.

This grob interface is not used in any graphical object.

3.2.54 ligature-head-interface

A note head that can become part of a ligature.

This grob interface is used in the following graphical object(s): Section 3.1.74 [NoteHead], page 351.

3.2.55 ligature-interface

A ligature.

This grob interface is not used in any graphical object.

3.2.56 line-interface

Generic line objects. Any object using lines supports this. The property `style` can be `line`, `dashed-line`, `trill`, `dotted-line`, `zigzag` or `none` (a transparent line).

For `dashed-line`, the length of the dashes is tuned with `dash-fraction`. If the latter is set to 0, a dotted line is produced.

User settable properties:

`arrow-length` (number)
: Arrow length.

`arrow-width` (number)
: Arrow width.

`dash-fraction` (number)
: Size of the dashes, relative to `dash-period`. Should be between `0.0` (no line) and `1.0` (continuous line).

`dash-period` (number)
: The length of one dash together with whitespace. If negative, no line is drawn at all.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

`zigzag-length` (dimension, in staff space)
: The length of the lines of a zigzag, relative to `zigzag-width`. A value of `1` gives 60-degree zigzags.

`zigzag-width` (dimension, in staff space)
: The width of one zigzag squiggle. This number is adjusted slightly so that the glissando line can be constructed from a whole number of squiggles.

This grob interface is used in the following graphical object(s): Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.40 [Episema], page 322, Section 3.1.45 [Glissando], page 327, Section 3.1.49 [Hairpin], page 330, Section 3.1.50 [HorizontalBracket], page 331, Section 3.1.59 [LigatureBracket], page 339, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.116 [TextSpanner], page 387, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.131 [VoiceFollower], page 401 and Section 3.1.132 [VoltaBracket], page 401.

3.2.57 line-spanner-interface

Generic line drawn between two objects, e.g., for use with glissandi.

User settable properties:

`bound-details` (list)
: An alist of properties for determining attachments of spanners to edges.

`extra-dy` (number)
: Slope glissandi this much extra.

`gap` (dimension, in staff space)
: Size of a gap in a variable symbol.

`left-bound-info` (list)
: An alist of properties for determining attachments of spanners to edges.

`right-bound-info` (list)
: An alist of properties for determining attachments of spanners to edges.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

`to-barline` (boolean)
: If true, the spanner will stop at the bar line just before it would otherwise stop.

Internal properties:

`note-columns` (array of grobs)
: An array of `NoteColumn` grobs.

This grob interface is used in the following graphical object(s): Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.40 [Episema], page 322, Section 3.1.45 [Glissando], page 327, Section 3.1.116 [TextSpanner], page 387, Section 3.1.123 [TrillSpanner], page 393 and Section 3.1.131 [VoiceFollower], page 401.

3.2.58 lyric-extender-interface

The extender is a simple line at the baseline of the lyric that helps show the length of a melisma (a tied or slurred note).

User settable properties:

`left-padding` (dimension, in staff space)
: The amount of space that is put left to an object (e.g., a lyric extender).

`next` (graphical (layout) object)
: Object that is next relation (e.g., the lyric syllable following an extender).

`right-padding` (dimension, in staff space)
: Space to insert on the right side of an object (e.g., between note and its accidentals).

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`heads` (array of grobs)
: An array of note heads.

This grob interface is used in the following graphical object(s): Section 3.1.60 [LyricExtender], page 340.

3.2.59 lyric-hyphen-interface

A centered hyphen is simply a line between lyrics used to divide syllables.

User settable properties:

`dash-period` (number)
: The length of one dash together with whitespace. If negative, no line is drawn at all.

`height` (dimension, in staff space)
: Height of an object in `staff-space` units.

`length` (dimension, in staff space)
: User override for the stem length of unbeamed stems.

`minimum-distance` (dimension, in staff space)
: Minimum distance between rest and notes or beam.

`minimum-length` (dimension, in staff space)
: Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

This grob interface is used in the following graphical object(s): Section 3.1.61 [LyricHyphen], page 340 and Section 3.1.62 [LyricSpace], page 341.

3.2.60 lyric-interface

Any object that is related to lyrics.

This grob interface is used in the following graphical object(s): Section 3.1.60 [LyricExtender], page 340 and Section 3.1.61 [LyricHyphen], page 340.

3.2.61 lyric-syllable-interface

A single piece of lyrics.

This grob interface is used in the following graphical object(s): Section 3.1.63 [LyricText], page 342.

3.2.62 mark-interface

A rehearsal mark.

This grob interface is used in the following graphical object(s): Section 3.1.85 [RehearsalMark], page 360.

3.2.63 measure-grouping-interface

This object indicates groups of beats. Valid choices for `style` are `bracket` and `triangle`.

User settable properties:

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`height` (dimension, in staff space)
: Height of an object in `staff-space` units.

This grob interface is used in the following graphical object(s): Section 3.1.64 [Measure-Grouping], page 343.

3.2.64 melody-spanner-interface

Context dependent typesetting decisions.

User settable properties:

`neutral-direction` (direction)
: Which direction to take in the center of the staff.

Internal properties:

`stems` (array of grobs)
: An array of stem objects.

This grob interface is used in the following graphical object(s): Section 3.1.65 [MelodyItem], page 344.

3.2.65 mensural-ligature-interface

A mensural ligature.

User settable properties:

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`delta-position` (number)
: The vertical position difference.

`ligature-flexa` (boolean)
: request joining note to the previous one in a flexa.

`head-width` (dimension, in staff space)
: The width of this ligature head.

`add-join` (boolean)
: Is this ligature head-joined with the next one by a vertical line?

`flexa-interval` (integer)
: The interval spanned by the two notes of a flexa shape (1 is a second, 7 is an octave).

`primitive` (integer)
: A pointer to a ligature primitive, i.e., an item similar to a note head that is part of a ligature.

This grob interface is used in the following graphical object(s): Section 3.1.66 [MensuralLigature], page 344 and Section 3.1.74 [NoteHead], page 351.

3.2.66 metronome-mark-interface

A metronome mark.

This grob interface is used in the following graphical object(s): Section 3.1.67 [MetronomeMark], page 344.

3.2.67 multi-measure-interface

Multi measure rest, and the text or number that is printed over it.

User settable properties:

`bound-padding` (number)
: The amount of padding to insert around spanner bounds.

This grob interface is used in the following graphical object(s): Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347 and Section 3.1.70 [MultiMeasureRestText], page 348.

3.2.68 multi-measure-rest-interface

A rest that spans a whole number of measures.

User settable properties:

`bound-padding` (number)
: The amount of padding to insert around spanner bounds.

`expand-limit` (integer)
: Maximum number of measures expanded in church rests.

`hair-thickness` (number)
: Thickness of the thin line in a bar line.

`measure-count` (integer)
: The number of measures for a multi-measure rest.

`minimum-length` (dimension, in staff space)
: Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`spacing-pair` (pair)
: A pair of alignment symbols which set an object's spacing relative to its left and right `BreakAlignment`s.

  For example, a `MultiMeasureRest` will ignore prefatory items at its bounds (i.e., clefs, key signatures and time signatures) using the following override:

```
\override MultiMeasureRest #'spacing-pair = #'(staff-bar . staff-bar)
```

`thick-thickness` (number)
: Bar line thickness, measured in `line-thickness`.

Internal properties:

`use-breve-rest` (boolean)
: Use breve rests for measures longer than a whole rest.

This grob interface is used in the following graphical object(s): Section 3.1.68 [MultiMeasureRest], page 346 and Section 3.1.81 [PercentRepeat], page 356.

3.2.69 note-collision-interface

An object that handles collisions between notes with different stem directions and horizontal shifts. Most of the interesting properties are to be set in Section 3.2.70 [note-column-interface], page 440: these are `force-hshift` and `horizontal-shift`.

User settable properties:

`merge-differently-dotted` (boolean)
: Merge note heads in collisions, even if they have a different number of dots. This is normal notation for some types of polyphonic music.

  `merge-differently-dotted` only applies to opposing stem directions (i.e., voice 1 & 2).

`merge-differently-headed` (boolean)
: Merge note heads in collisions, even if they have different note heads. The smaller of the two heads is rendered invisible. This is used in polyphonic guitar notation. The value of this setting is used by Section "note-collision-interface" in *Internals Reference*.

  `merge-differently-headed` only applies to opposing stem directions (i.e., voice 1 & 2).

`prefer-dotted-right` (boolean)
: For note collisions, prefer to shift dotted up-note to the right, rather than shifting just the dot.

Internal properties:

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

This grob interface is used in the following graphical object(s): Section 3.1.72 [NoteCollision], page 350.

3.2.70 note-column-interface

Stem and noteheads combined.

User settable properties:

`force-hshift` (number)
: This specifies a manual shift for notes in collisions. The unit is the note head width of the first voice note. This is used by Section "note-collision-interface" in *Internals Reference*.

`horizontal-shift` (integer)
: An integer that identifies ranking of `NoteColumn`s for horizontal shifting. This is used by Section "note-collision-interface" in *Internals Reference*.

`ignore-collision` (boolean)
: If set, don't do note collision resolution on this `NoteColumn`.

Internal properties:

`arpeggio` (graphical (layout) object)
: A pointer to an `Arpeggio` object.

`note-heads` (array of grobs)
: An array of note head grobs.

`rest` (graphical (layout) object)
: A pointer to a `Rest` object.

`rest-collision` (graphical (layout) object)
: A rest collision that a rest is in.

`stem` (graphical (layout) object)
: A pointer to a `Stem` object.

This grob interface is used in the following graphical object(s): Section 3.1.73 [NoteColumn], page 350.

3.2.71 note-head-interface

A note head. There are many possible values for `style`. For a complete list, see Section "Note head styles" in *Notation Reference*.

User settable properties:

`note-names` (vector)
: Vector of strings containing names for easy-notation note heads.

`glyph-name` (string)
: The glyph name within the font.

`stem-attachment` (pair of numbers)
: An `(x . y)` pair where the stem attaches to the notehead.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

Internal properties:

`accidental-grob` (graphical (layout) object)
: The accidental for this note.

This grob interface is used in the following graphical object(s): Section 3.1.8 [AmbitusNoteHead], page 294, Section 3.1.74 [NoteHead], page 351, Section 3.1.114 [TabNoteHead], page 384 and Section 3.1.121 [TrillPitchGroup], page 392.

3.2.72 note-name-interface

Note names.

This grob interface is used in the following graphical object(s): Section 3.1.75 [NoteName], page 352.

3.2.73 note-spacing-interface

This object calculates spacing wishes for individual voices.

User settable properties:

`knee-spacing-correction` (number)
: Factor for the optical correction amount for kneed beams. Set between `0` for no correction and `1` for full correction.

`same-direction-correction` (number)
: Optical correction amount for stems that are placed in tight configurations. This amount is used for stems with the same direction to compensate for note head to stem distance.

`stem-spacing-correction` (number)
: Optical correction amount for stems that are placed in tight configurations. For opposite directions, this amount is the correction for two normal sized stems that overlap completely.

`space-to-barline` (boolean)
: If set, the distance between a note and the following non-musical column will be measured to the bar line instead of to the beginning of the non-musical column. If there is a clef change followed by a bar line, for example, this means that we will try to space the non-musical column as though the clef is not there.

Internal properties:

`left-items` (array of grobs)
: DOCME

`right-items` (array of grobs)
: DOCME

This grob interface is used in the following graphical object(s): Section 3.1.76 [NoteSpacing], page 352.

3.2.74 only-prebreak-interface

Kill this grob after the line breaking process.

This grob interface is not used in any graphical object.

3.2.75 ottava-bracket-interface

An ottava bracket.

User settable properties:

`edge-height` (pair)
: A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`bracket-flare` (pair of numbers)
: A pair of numbers specifying how much edges of brackets should slant outward. Value `0.0` means straight edges.

`shorten-pair` (pair of numbers)
: The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`minimum-length` (dimension, in staff space)
: Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

This grob interface is used in the following graphical object(s): Section 3.1.78 [OttavaBracket], page 354.

3.2.76 paper-column-interface

`Paper_column` objects form the top-most X parents for items. There are two types of columns: musical and non-musical, to which musical and non-musical objects are attached respectively. The spacing engine determines the X positions of these objects.

They are numbered, the first (leftmost) is column 0. Numbering happens before line breaking, and columns are not renumbered after line breaking. Since many columns go unused, you should only use the rank field to get ordering information. Two adjacent columns may have non-adjacent numbers.

User settable properties:

`between-cols` (pair)
: Where to attach a loose column to.

`full-measure-extra-space` (number)
: Extra space that is allocated at the beginning of a measure with only one note. This property is read from the NonMusicalPaperColumn that begins the measure.

`labels` (list)
: List of labels (symbols) placed on a column.

`line-break-system-details` (list)
: An alist of properties to use if this column is the start of a system.

`line-break-penalty` (number)
: Penalty for a line break at this column. This affects the choices of the line breaker; it avoids a line break at a column with a positive penalty and prefers a line break at a column with a negative penalty.

`line-break-permission` (symbol)
: Instructs the line breaker on whether to put a line break at this column. Can be `force` or `allow`.

`page-break-penalty` (number)
: Penalty for page break at this column. This affects the choices of the page breaker; it avoids a page break at a column with a positive penalty and prefers a page break at a column with a negative penalty.

`page-break-permission` (symbol)
: Instructs the page breaker on whether to put a page break at this column. Can be `force` or `allow`.

`page-turn-penalty` (number)
: Penalty for a page turn at this column. This affects the choices of the page breaker; it avoids a page turn at a column with a positive penalty and prefers a page turn at a column with a negative penalty.

`page-turn-permission` (symbol)
: Instructs the page breaker on whether to put a page turn at this column. Can be `force` or `allow`.

`rhythmic-location` (rhythmic location)
: Where (bar number, measure position) in the score.

`shortest-playing-duration` (moment)
: The duration of the shortest note playing here.

`shortest-starter-duration` (moment)
: The duration of the shortest note that starts here.

`used` (boolean)
: If set, this spacing column is kept in the spacing problem.

`when` (moment)
: Global time step associated with this column happen?

Internal properties:

`bounded-by-me` (array of grobs)
: An array of spanners that have this column as start/begin point. Only columns that have grobs or act as bounds are spaced.

`grace-spacing` (graphical (layout) object)
: A run of grace notes.

`maybe-loose` (boolean)
: Used to mark a breakable column that is loose if and only if it is in the middle of a line.

`spacing` (graphical (layout) object)
: The spacing spanner governing this section.

This grob interface is used in the following graphical object(s): Section 3.1.71 [NonMusicalPaperColumn], page 349 and Section 3.1.79 [PaperColumn], page 355.

3.2.77 parentheses-interface

Parentheses for other objects.

User settable properties:

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`stencils` (list)
: Multiple stencils, used as intermediate value.

This grob interface is used in the following graphical object(s): Section 3.1.80 [ParenthesesItem], page 356 and Section 3.1.121 [TrillPitchGroup], page 392.

3.2.78 percent-repeat-interface

Beat, Double and single measure repeats.

User settable properties:

`dot-negative-kern` (number)
: The space to remove between a dot and a slash in percent repeat glyphs. Larger values bring the two elements closer together.

`slash-negative-kern` (number)
: The space to remove between slashes in percent repeat glyphs. Larger values bring the two elements closer together.

`slope` (number)
: The slope of this object.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

This grob interface is used in the following graphical object(s): Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357 and Section 3.1.86 [RepeatSlash], page 362.

3.2.79 percent-repeat-item-interface

Repeats that look like percent signs.

User settable properties:

`dot-negative-kern` (number)
: The space to remove between a dot and a slash in percent repeat glyphs. Larger values bring the two elements closer together.

`slash-negative-kern` (number)
: The space to remove between slashes in percent repeat glyphs. Larger values bring the two elements closer together.

`slope` (number)
: The slope of this object.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

This grob interface is used in the following graphical object(s): Section 3.1.34 [DoublePercentRepeat], page 315, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.36 [DoubleRepeatSlash], page 317 and Section 3.1.86 [RepeatSlash], page 362.

3.2.80 piano-pedal-bracket-interface

The bracket of the piano pedal. It can be tuned through the regular bracket properties.

User settable properties:

`bound-padding` (number)
: The amount of padding to insert around spanner bounds.

`edge-height` (pair)
: A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`shorten-pair` (pair of numbers)
: The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`bracket-flare` (pair of numbers)
: A pair of numbers specifying how much edges of brackets should slant outward. Value `0.0` means straight edges.

Internal properties:

`pedal-text` (graphical (layout) object)
: A pointer to the text of a mixed-style piano pedal.

This grob interface is used in the following graphical object(s): Section 3.1.84 [PianoPedalBracket], page 359.

3.2.81 piano-pedal-interface

A piano pedal sign.

This grob interface is used in the following graphical object(s): Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.107 [SustainPedal], page 378, Section 3.1.108 [SustainPedalLineSpanner], page 379 and Section 3.1.127 [UnaCordaPedalLineSpanner], page 397.

3.2.82 piano-pedal-script-interface

A piano pedal sign, fixed size.

This grob interface is used in the following graphical object(s): Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.107 [SustainPedal], page 378 and Section 3.1.126 [UnaCordaPedal], page 396.

3.2.83 pitched-trill-interface

A note head to indicate trill pitches.

Internal properties:

`accidental-grob` (graphical (layout) object)
: The accidental for this note.

This grob interface is used in the following graphical object(s): Section 3.1.122 [TrillPitchHead], page 393.

3.2.84 rest-collision-interface

Move ordinary rests (not multi-measure nor pitched rests) to avoid conflicts.

User settable properties:

`minimum-distance` (dimension, in staff space)
: Minimum distance between rest and notes or beam.

Internal properties:

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

`elements` (array of grobs)
: An array of grobs; the type is depending on the grob where this is set in.

This grob interface is used in the following graphical object(s): Section 3.1.90 [RestCollision], page 364.

3.2.85 rest-interface

A rest symbol. The property `style` can be `default`, `mensural`, `neomensural` or `classical`.

User settable properties:

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`minimum-distance` (dimension, in staff space)
: Minimum distance between rest and notes or beam.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

This grob interface is used in the following graphical object(s): Section 3.1.68 [MultiMeasureRest], page 346 and Section 3.1.89 [Rest], page 364.

3.2.86 rhythmic-grob-interface

Any object with a duration. Used to determine which grobs are interesting enough to maintain a hara-kiri staff.

This grob interface is used in the following graphical object(s): Section 3.1.13 [BassFigure], page 300, Section 3.1.24 [ChordName], page 307, Section 3.1.27 [ClusterSpannerBeacon], page 309, Section 3.1.36 [DoubleRepeatSlash], page 317, Section 3.1.44 [FretBoard], page 326, Section 3.1.63 [LyricText], page 342, Section 3.1.74 [NoteHead], page 351, Section 3.1.86 [RepeatSlash], page 362, Section 3.1.89 [Rest], page 364 and Section 3.1.114 [TabNoteHead], page 384.

3.2.87 rhythmic-head-interface

Note head or rest.

User settable properties:

`duration-log` (integer)
: The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

Internal properties:

`dot` (graphical (layout) object)
: A reference to a `Dots` object.

`stem` (graphical (layout) object)
: A pointer to a `Stem` object.

This grob interface is used in the following graphical object(s): Section 3.1.8 [AmbitusNoteHead], page 294, Section 3.1.74 [NoteHead], page 351, Section 3.1.89 [Rest], page 364, Section 3.1.114 [TabNoteHead], page 384 and Section 3.1.122 [TrillPitchHead], page 393.

3.2.88 script-column-interface

An interface that sorts scripts according to their `script-priority` and `outside-staff-priority`.

This grob interface is used in the following graphical object(s): Section 3.1.92 [ScriptColumn], page 365 and Section 3.1.93 [ScriptRow], page 366.

3.2.89 script-interface

An object that is put above or below a note.

User settable properties:

`add-stem-support` (boolean)
: If set, the `Stem` object is included in this script's support.

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`script-priority` (number)
: A sorting key that determines in what order a script is within a stack of scripts.

`side-relative-direction` (direction)
: Multiply direction of `direction-source` with this to get the direction of this object.

`slur-padding` (number)
: Extra distance between slur and script.

`toward-stem-shift` (number)
: Amount by which scripts are shifted toward the stem if their direction coincides with the stem direction. `0.0` means keep the default position (centered on the note head), `1.0` means centered on the stem. Interpolated values are possible.

Internal properties:

`direction-source` (graphical (layout) object)
: In case `side-relative-direction` is set, which grob to get the direction from.

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

`script-stencil` (pair)
: A pair `(`*`type . arg`*`)` which acts as an index for looking up a `Stencil` object.

`slur` (graphical (layout) object)
: A pointer to a `Slur` object.

This grob interface is used in the following graphical object(s): Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.38 [DynamicText], page 319 and Section 3.1.91 [Script], page 365.

3.2.90 self-alignment-interface

Position this object on itself and/or on its parent. To this end, the following functions are provided:

`Self_alignment_interface::[xy]_aligned_on_self`
: Align self on reference point, using `self-alignment-X` and `self-alignment-Y`.

`Self_alignment_interface::aligned_on_[xy]_parent`
`Self_alignment_interface::centered_on_[xy]_parent`
: Shift the object so its own reference point is centered on the extent of the parent

User settable properties:

`self-alignment-X` (number)
: Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`self-alignment-Y` (number)
: Like `self-alignment-X` but for the Y axis.

This grob interface is used in the following graphical object(s): Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.12 [BarNumber], page 298, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.38 [DynamicText], page 319, Section 3.1.41 [Fingering], page 323, Section 3.1.47 [GridLine], page 329, Section 3.1.49 [Hairpin], page 330, Section 3.1.51 [InstrumentName], page 332, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.63 [LyricText], page 342, Section 3.1.67 [MetronomeMark], page 344, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.77 [OctavateEight], page 353, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.85 [RehearsalMark], page 360, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.107 [SustainPedal], page 378, Section 3.1.115 [TextScript], page 385 and Section 3.1.126 [UnaCordaPedal], page 396.

3.2.91 semi-tie-column-interface

The interface for a column of l.v. (laissez vibrer) ties.

User settable properties:

`head-direction` (direction)
: Are the note heads left or right in a semitie?

`tie-configuration` (list)
: List of `(`*`position . dir`*`)` pairs, indicating the desired tie configuration, where *position* is the offset from the center of the staff in staff space and *dir* indicates the direction of the tie (`1`=>up, `-1`=>down, `0`=>center). A non-pair entry in the list causes the corresponding tie to be formatted automatically.

Internal properties:

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

This grob interface is used in the following graphical object(s): Section 3.1.56 [LaissezVibrerTieColumn], page 337 and Section 3.1.88 [RepeatTieColumn], page 363.

3.2.92 semi-tie-interface

A tie which is only on one side connected to a note head.

User settable properties:

`control-points` (list)
: List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`details` (list)
: Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`head-direction` (direction)
: Are the note heads left or right in a semitie?

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`note-head` (graphical (layout) object)
: A single note head.

This grob interface is used in the following graphical object(s): Section 3.1.55 [LaissezVibrerTie], page 336 and Section 3.1.87 [RepeatTie], page 362.

3.2.93 separation-item-interface

Item that computes widths to generate spacing rods.

User settable properties:

`X-extent` (pair of numbers)
: Hard coded extent in X direction.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`horizontal-skylines` (pair of skylines)
: Two skylines, one to the left and one to the right of this grob.

`skyline-vertical-padding` (number)
: The amount by which the left and right skylines of a column are padded vertically, beyond the `Y-extent`s and `extra-spacing-height`s of the constituent grobs in the column. Increase this to prevent interleaving of grobs from adjacent columns.

Internal properties:

`conditional-elements` (array of grobs)
: Internal use only.

`elements` (array of grobs)
: An array of grobs; the type is depending on the grob where this is set in.

This grob interface is used in the following graphical object(s): Section 3.1.71 [NonMusicalPaperColumn], page 349, Section 3.1.73 [NoteColumn], page 350 and Section 3.1.79 [PaperColumn], page 355.

3.2.94 side-position-interface

Position a victim object (this one) next to other objects (the support). The property `direction` signifies where to put the victim object relative to the support (left or right, up or down?)

The routine also takes the size of the staff into account if `staff-padding` is set. If undefined, the staff symbol is ignored.

User settable properties:

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`minimum-space` (dimension, in staff space)
: Minimum distance that the victim should move (after padding).

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`side-axis` (number)
: If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`slur-padding` (number)
: Extra distance between slur and script.

`staff-padding` (dimension, in staff space)
: Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

Internal properties:

`quantize-position` (boolean)
: If set, a vertical alignment is aligned to be within staff spaces.

`side-support-elements` (array of grobs)
: The side support, an array of grobs.

This grob interface is used in the following graphical object(s): Section 3.1.4 [AccidentalSuggestion], page 291, Section 3.1.6 [AmbitusAccidental], page 293, Section 3.1.9 [Arpeggio], page 295, Section 3.1.12 [BarNumber], page 298, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.40 [Episema], page 322, Section 3.1.41 [Fingering], page 323, Section 3.1.50 [HorizontalBracket], page 331, Section 3.1.51 [InstrumentName], page 332, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.64 [MeasureGrouping], page 343, Section 3.1.67 [MetronomeMark], page 344, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.77 [OctavateEight], page 353, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.85 [RehearsalMark], page 360, Section 3.1.91 [Script], page 365, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.102 [StanzaNumber], page 373, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.110 [SystemStartBar],

page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383, Section 3.1.115 [TextScript], page 385, Section 3.1.116 [TextSpanner], page 387, Section 3.1.120 [TrillPitchAccidental], page 391, Section 3.1.121 [TrillPitchGroup], page 392, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397, Section 3.1.132 [VoltaBracket], page 401 and Section 3.1.133 [VoltaBracketSpanner], page 402.

3.2.95 slur-interface

A slur. The following properties may be set in the `details` list.

`region-size`
: Size of region (in staff spaces) for determining potential endpoints in the Y direction.

`head-encompass-penalty`
: Demerit to apply when note heads collide with a slur.

`stem-encompass-penalty`
: Demerit to apply when stems collide with a slur.

`closeness-factor`
: Additional demerit used when scoring encompasses.

`edge-attraction-factor`
: Factor used to calculate the demerit for distances between slur endpoints and their corresponding base attachments.

`same-slope-penalty`
: Demerit for slurs with attachment points that are horizontally aligned.

`steeper-slope-factor`
: Factor used to calculate demerit only if this slur is not broken.

`non-horizontal-penalty`
: Demerit for slurs with attachment points that are not horizontally aligned.

`max-slope`
: The maximum slope allowed for this slur.

`max-slope-factor`
: Factor that calculates demerit based on the max slope.

`free-head-distance`
: The amount of vertical free space that must exist between a slur and note heads.

`absolute-closeness-measure`
: Factor to calculate demerit for variance between a note head and slur.

`extra-object-collision-penalty`
: Factor to calculate demerit for extra objects that the slur encompasses, including accidentals, fingerings, and tuplet numbers.

`accidental-collision`
: Factor to calculate demerit for `Accidental` objects that the slur encompasses. This property value replaces the value of `extra-object-collision-penalty`.

`extra-encompass-free-distance`
: The amount of vertical free space that must exist between a slur and various objects it encompasses, including accidentals, fingerings, and tuplet numbers.

`extra-encompass-collision-distance`
: This detail is currently unused.

`head-slur-distance-factor`
: Factor to calculate demerit for variance between a note head and slur.

`head-slur-distance-max-ratio`
: The maximum value for the ratio of distance between a note head and slur.

`free-slur-distance`
: The amount of vertical free space that must exist between adjacent slurs. This subproperty only works for `PhrasingSlur`.

`edge-slope-exponent`
: Factor used to calculate the demerit for the slope of a slur near its endpoints; a larger value yields a larger demerit.

User settable properties:

`annotation` (string)
: Annotate a grob for debug purposes.

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`control-points` (list)
: List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`dash-definition` (pair)
: List of `dash-elements` defining the dash structure. Each `dash-element` has a starting t value, an ending t-value, a `dash-fraction`, and a `dash-period`.

`details` (list)
: Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP`=`1`, `#DOWN`=`-1`, `#LEFT`=`-1`, `#RIGHT`=`1`, `#CENTER`=`0`.

`eccentricity` (number)
: How asymmetrical to make a slur. Positive means move the center to the right.

`height-limit` (dimension, in staff space)
: Maximum slur height: The longer the slur, the closer it is to this height.

`inspect-quants` (pair of numbers)
: If debugging is set, set beam and slur quants to this position, and print the respective scores.

`inspect-index` (integer)
: If debugging is set, set beam and slur configuration to this index, and print the respective scores.

`line-thickness` (number)
: The thickness of the tie or slur contour.

`positions` (pair of numbers)
: Pair of staff coordinates `(left . right)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

`ratio` (number)
: Parameter for slur shape. The higher this number, the quicker the slur attains its `height-limit`.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`encompass-objects` (array of grobs)
: Objects that a slur should avoid in addition to notes and stems.

`note-columns` (array of grobs)
: An array of `NoteColumn` grobs.

This grob interface is used in the following graphical object(s): Section 3.1.83 [PhrasingSlur], page 358 and Section 3.1.94 [Slur], page 366.

3.2.96 spaceable-grob-interface

A layout object that takes part in the spacing problem.

User settable properties:

`allow-loose-spacing` (boolean)
: If set, column can be detached from main spacing.

`keep-inside-line` (boolean)
: If set, this column cannot have objects sticking into the margin.

`measure-length` (moment)
: Length of a measure. Used in some spacing situations.

Internal properties:

`ideal-distances` (list)
: `(obj . (dist . strength))` pairs.

`left-neighbor` (graphical (layout) object)
: The right-most column that has a spacing-wish for this column.

`minimum-distances` (list)
: A list of rods that have the format `(obj . dist)`.

`right-neighbor` (graphical (layout) object)
: See `left-neighbor`.

`spacing-wishes` (array of grobs)
: An array of note spacing or staff spacing objects.

This grob interface is used in the following graphical object(s): Section 3.1.71 [NonMusicalPaperColumn], page 349 and Section 3.1.79 [PaperColumn], page 355.

3.2.97 spacing-interface

This object calculates the desired and minimum distances between two columns.

Internal properties:

`left-items` (array of grobs)
DOCME

`right-items` (array of grobs)
DOCME

This grob interface is used in the following graphical object(s): Section 3.1.76 [NoteSpacing], page 352 and Section 3.1.100 [StaffSpacing], page 372.

3.2.98 spacing-options-interface

Supports setting of spacing variables.

User settable properties:

`spacing-increment` (number)
Add this much space for a doubled duration. Typically, the width of a note head. See also Section "spacing-spanner-interface" in *Internals Reference*.

`shortest-duration-space` (dimension, in staff space)
Start with this much space for the shortest duration. This is expressed in `spacing-increment` as unit. See also Section "spacing-spanner-interface" in *Internals Reference*.

This grob interface is used in the following graphical object(s): Section 3.1.46 [GraceSpacing], page 328 and Section 3.1.97 [SpacingSpanner], page 369.

3.2.99 spacing-spanner-interface

The space taken by a note is dependent on its duration. Doubling a duration adds `spacing-increment` to the space. The most common shortest note gets `shortest-duration-space`. Notes that are even shorter are spaced proportonial to their duration.

Typically, the increment is the width of a black note head. In a piece with lots of 8th notes, and some 16th notes, the eighth note gets a 2 note heads width (i.e., the space following a note is a 1 note head width). A 16th note is followed by 0.5 note head width. The quarter note is followed by 3 NHW, the half by 4 NHW, etc.

User settable properties:

`average-spacing-wishes` (boolean)
If set, the spacing wishes are averaged over staves.

`base-shortest-duration` (moment)
Spacing is based on the shortest notes in a piece. Normally, pieces are spaced as if notes at least as short as this are present.

`common-shortest-duration` (moment)
The most common shortest note length. This is used in spacing. Enlarging this sets the score tighter.

`packed-spacing` (boolean)
: If set, the notes are spaced as tightly as possible.

`shortest-duration-space` (dimension, in staff space)
: Start with this much space for the shortest duration. This is expressed in `spacing-increment` as unit. See also Section "spacing-spanner-interface" in *Internals Reference*.

`spacing-increment` (number)
: Add this much space for a doubled duration. Typically, the width of a note head. See also Section "spacing-spanner-interface" in *Internals Reference*.

`strict-grace-spacing` (boolean)
: If set, main notes are spaced normally, then grace notes are put left of the musical columns for the main notes.

`strict-note-spacing` (boolean)
: If set, unbroken columns with non-musical material (clefs, bar lines, etc.) are not spaced separately, but put before musical columns.

`uniform-stretching` (boolean)
: If set, items stretch proportionally to their durations. This looks better in complex polyphonic patterns.

This grob interface is used in the following graphical object(s): Section 3.1.97 [SpacingSpanner], page 369.

3.2.100 span-bar-interface

A bar line that is spanned between other barlines. This interface is used for bar lines that connect different staves.

User settable properties:

`glyph-name` (string)
: The glyph name within the font.

Internal properties:

`elements` (array of grobs)
: An array of grobs; the type is depending on the grob where this is set in.

`pure-Y-common` (graphical (layout) object)
: A cache of the `common_refpoint_of_array` of the `elements` grob set.

`pure-relevant-grobs` (array of grobs)
: All the grobs (items and spanners) that are relevant for finding the `pure-Y-extent`

`pure-relevant-items` (array of grobs)
: A subset of elements that are relevant for finding the `pure-Y-extent`.

`pure-relevant-spanners` (array of grobs)
: A subset of elements that are relevant for finding the `pure-Y-extent`.

This grob interface is used in the following graphical object(s): Section 3.1.98 [SpanBar], page 370.

3.2.101 spanner-interface

Some objects are horizontally spanned between objects. For example, slurs, beams, ties, etc. These grobs form a subtype called `Spanner`. All spanners have two span points (these must be `Item` objects), one on the left and one on the right. The left bound is also the X reference point of the spanner.

User settable properties:

`normalized-endpoints` (pair)
: Represents left and right placement over the total spanner, where the width of the spanner is normalized between 0 and 1.

`minimum-length` (dimension, in staff space)
: Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`spanner-id` (string)
: An identifier to distinguish concurrent spanners.

`to-barline` (boolean)
: If true, the spanner will stop at the bar line just before it would otherwise stop.

This grob interface is used in the following graphical object(s): Section 3.1.14 [BassFigureAlignment], page 300, Section 3.1.15 [BassFigureAlignmentPositioning], page 300, Section 3.1.17 [BassFigureContinuation], page 301, Section 3.1.18 [BassFigureLine], page 302, Section 3.1.19 [Beam], page 302, Section 3.1.20 [BendAfter], page 304, Section 3.1.26 [ClusterSpanner], page 309, Section 3.1.37 [DynamicLineSpanner], page 318, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.40 [Episema], page 322, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.45 [Glissando], page 327, Section 3.1.46 [GraceSpacing], page 328, Section 3.1.49 [Hairpin], page 330, Section 3.1.50 [HorizontalBracket], page 331, Section 3.1.51 [InstrumentName], page 332, Section 3.1.57 [LedgerLineSpanner], page 337, Section 3.1.59 [LigatureBracket], page 339, Section 3.1.60 [LyricExtender], page 340, Section 3.1.61 [LyricHyphen], page 340, Section 3.1.62 [LyricSpace], page 341, Section 3.1.64 [MeasureGrouping], page 343, Section 3.1.66 [MensuralLigature], page 344, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.81 [PercentRepeat], page 356, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.83 [PhrasingSlur], page 358, Section 3.1.84 [PianoPedalBracket], page 359, Section 3.1.94 [Slur], page 366, Section 3.1.96 [SostenutoPedalLineSpanner], page 368, Section 3.1.97 [SpacingSpanner], page 369, Section 3.1.99 [StaffGrouper], page 371, Section 3.1.101 [StaffSymbol], page 372, Section 3.1.108 [SustainPedalLineSpanner], page 379, Section 3.1.109 [System], page 380, Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382, Section 3.1.113 [SystemStartSquare], page 383, Section 3.1.116 [TextSpanner], page 387, Section 3.1.117 [Tie], page 388, Section 3.1.118 [TieColumn], page 389, Section 3.1.123 [TrillSpanner], page 393, Section 3.1.124 [TupletBracket], page 395, Section 3.1.125 [TupletNumber], page 396, Section 3.1.127 [UnaCordaPedalLineSpanner], page 397, Section 3.1.128 [VaticanaLigature], page 398, Section 3.1.129 [VerticalAlignment], page 399, Section 3.1.130 [VerticalAxisGroup], page 399, Section 3.1.131 [VoiceFollower], page 401, Section 3.1.132 [VoltaBracket], page 401 and Section 3.1.133 [VoltaBracketSpanner], page 402.

3.2.102 staff-grouper-interface

A grob that collects staves together.

User settable properties:

`staff-staff-spacing` (list)
: When applied to a staff-group's `StaffGrouper` grob, this spacing alist controls the distance between consecutive staves within the staff-group. When applied to a staff's `VerticalAxisGroup` grob, it controls the distance between the staff and the nearest staff below it in the same system, replacing any settings inherited from the `StaffGrouper` grob of the containing staff-group, if there is one. This property remains in effect even when non-staff lines appear between staves. The alist can contain the following keys:

  - `basic-distance` – the vertical distance, measured in staff-spaces, between the reference points of the two items when no collisions would result, and no stretching or compressing is in effect.
  - `minimum-distance` – the smallest allowable vertical distance, measured in staff-spaces, between the reference points of the two items, when compressing is in effect.
  - `padding` – the minimum required amount of unobstructed vertical whitespace between the bounding boxes (or skylines) of the two items, measured in staff-spaces.
  - `stretchability` – a unitless measure of the dimension's relative propensity to stretch. If zero, the distance will not stretch (unless collisions would result).

`staffgroup-staff-spacing` (list)
: The spacing alist controlling the distance between the last staff of the current staff-group and the staff just below it in the same system, even if one or more non-staff lines exist between the two staves. If the `staff-staff-spacing` property of the staff's `VerticalAxisGroup` grob is set, that is used instead. See `staff-staff-spacing` for a description of the alist structure.

This grob interface is used in the following graphical object(s): Section 3.1.99 [StaffGrouper], page 371.

3.2.103 staff-spacing-interface

This object calculates spacing details from a breakable symbol (left) to another object. For example, it takes care of optical spacing from a bar line to a note.

User settable properties:

`stem-spacing-correction` (number)
: Optical correction amount for stems that are placed in tight configurations. For opposite directions, this amount is the correction for two normal sized stems that overlap completely.

This grob interface is used in the following graphical object(s): Section 3.1.100 [StaffSpacing], page 372.

3.2.104 staff-symbol-interface

This spanner draws the lines of a staff. A staff symbol defines a vertical unit, the *staff space*. Quantities that go by a half staff space are called *positions*. The center (i.e., middle line or space) is position 0. The length of the symbol may be set by hand through the `width` property.

User settable properties:

`ledger-line-thickness` (pair of numbers)
: The thickness of ledger lines. It is the sum of 2 numbers: The first is the factor for line thickness, and the second for staff space. Both contributions are added.

`line-count` (integer)
: The number of staff lines.

`line-positions` (list)
: Vertical positions of staff lines.

`staff-space` (dimension, in staff space)
: Amount of space between staff lines, expressed in global `staff-space`.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

`width` (dimension, in staff space)
: The width of a grob measured in staff space.

This grob interface is used in the following graphical object(s): Section 3.1.101 [StaffSymbol], page 372.

3.2.105 staff-symbol-referencer-interface

An object whose Y position is meant relative to a staff symbol. These usually have `Staff_symbol_referencer::callback` in their `Y-offset-callbacks`.

User settable properties:

`staff-position` (number)
: Vertical position, measured in half staff spaces, counted from the middle line.

This grob interface is used in the following graphical object(s): Section 3.1.8 [Ambitus-NoteHead], page 294, Section 3.1.9 [Arpeggio], page 295, Section 3.1.19 [Beam], page 302, Section 3.1.25 [Clef], page 307, Section 3.1.29 [CueClef], page 311, Section 3.1.30 [CueEndClef], page 312, Section 3.1.31 [Custos], page 313, Section 3.1.33 [Dots], page 315, Section 3.1.53 [KeyCancellation], page 334, Section 3.1.54 [KeySignature], page 335, Section 3.1.68 [MultiMeasureRest], page 346, Section 3.1.74 [NoteHead], page 351, Section 3.1.89 [Rest], page 364, Section 3.1.114 [TabNoteHead], page 384 and Section 3.1.122 [TrillPitchHead], page 393.

3.2.106 stanza-number-interface

A stanza number, to be put in from of a lyrics line.

This grob interface is used in the following graphical object(s): Section 3.1.102 [StanzaNumber], page 373.

3.2.107 stem-interface

The stem represents the graphical stem. In addition, it internally connects note heads, beams, and tremolos. Rests and whole notes have invisible stems.

The following properties may be set in the `details` list.

`beamed-lengths`
: List of stem lengths given beam multiplicity.

`beamed-minimum-free-lengths`
: List of normal minimum free stem lengths (chord to beams) given beam multiplicity.

`beamed-extreme-minimum-free-lengths`
: List of extreme minimum free stem lengths (chord to beams) given beam multiplicity.

`lengths` Default stem lengths. The list gives a length for each flag count.

`stem-shorten`
: How much a stem in a forced direction should be shortened. The list gives an amount depending on the number of flags and beams.

User settable properties:

`avoid-note-head` (boolean)
: If set, the stem of a chord does not pass through all note heads, but starts at the last note head.

`beaming` (pair)
: Pair of number lists. Each number list specifies which beams to make. `0` is the central beam, `1` is the next beam toward the note, etc. This information is used to determine how to connect the beaming patterns from stem to stem inside a beam.

`beamlet-default-length` (pair)
: A pair of numbers. The first number specifies the default length of a beamlet that sticks out of the left hand side of this stem; the second number specifies the default length of the beamlet to the right. The actual length of a beamlet is determined by taking either the default length or the length specified by `beamlet-max-length-proportion`, whichever is smaller.

`beamlet-max-length-proportion` (pair)
: The maximum length of a beamlet, as a proportion of the distance between two adjacent stems.

`default-direction` (direction)
: Direction determined by note head positions.

`details` (list)
: Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`duration-log` (integer)
: The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

`flag` (stencil)
: A function returning the full flag stencil for the `Stem`, which is passed to the function as the only argument. The default ly:stem::calc-stencil function uses the `flag-style` property to determine the correct glyph for the flag. By providing your own function, you can create arbitrary flags.

`flag-style` (symbol)
: A symbol determining what style of flag glyph is typeset on a `Stem`. Valid options include `'()` for standard flags, `'mensural` and `'no-flag`, which switches off the flag.

`french-beaming` (boolean)
: Use French beaming style for this stem. The stem stops at the innermost beams.

`length` (dimension, in staff space)
: User override for the stem length of unbeamed stems.

`length-fraction` (number)
: Multiplier for lengths. Used for determining ledger lines and stem lengths.

`max-beam-connect` (integer)
: Maximum number of beams to connect to beams from this stem. Further beams are typeset as beamlets.

`neutral-direction` (direction)
: Which direction to take in the center of the staff.

`no-stem-extend` (boolean)
: If set, notes with ledger lines do not get stems extending to the middle staff line.

`stem-end-position` (number)
: Where does the stem end (the end is opposite to the support-head)?

`stemlet-length` (number)
: How long should be a stem over a rest?

`stroke-style` (string)
: Set to `"grace"` to turn stroke through flag on.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`beam` (graphical (layout) object)
: A pointer to the beam, if applicable.

`note-heads` (array of grobs)
: An array of note head grobs.

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

`rests` (array of grobs)
: An array of rest objects.

`stem-info` (pair)
: A cache of stem parameters.

`tremolo-flag` (graphical (layout) object)
: The tremolo object on a stem.

This grob interface is used in the following graphical object(s): Section 3.1.103 [Stem], page 374.

3.2.108 stem-tremolo-interface

A beam slashing a stem to indicate a tremolo. The property `style` can be `default` or `rectangle`.

User settable properties:

`beam-thickness` (dimension, in staff space)
: Beam thickness, measured in `staff-space` units.

`beam-width` (dimension, in staff space)
: Width of the tremolo sign.

`flag-count` (number)
: The number of tremolo beams.

`length-fraction` (number)
: Multiplier for lengths. Used for determining ledger lines and stem lengths.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`slope` (number)
: The slope of this object.

Internal properties:

`stem` (graphical (layout) object)
: A pointer to a `Stem` object.

This grob interface is used in the following graphical object(s): Section 3.1.104 [StemTremolo], page 375.

3.2.109 string-number-interface

A string number instruction.

This grob interface is used in the following graphical object(s): Section 3.1.105 [StringNumber], page 376.

3.2.110 stroke-finger-interface

A right hand finger instruction.

User settable properties:

`digit-names` (vector)
: Names for string finger digits.

This grob interface is used in the following graphical object(s): Section 3.1.106 [StrokeFinger], page 377.

3.2.111 system-interface

This is the top-level object: Each object in a score ultimately has a `System` object as its X and Y parent.

User settable properties:

`labels` (list)
: List of labels (symbols) placed on a column.

`skyline-horizontal-padding` (number)
: For determining the vertical distance between two staves, it is possible to have a configuration which would result in a tight interleaving of grobs from the top staff and the bottom staff. The larger this parameter is, the farther apart the staves are placed in such a configuration.

Internal properties:

`all-elements` (array of grobs)
: An array of all grobs in this line. Its function is to protect objects from being garbage collected.

`columns` (array of grobs)
: An array of grobs, typically containing `PaperColumn` or `NoteColumn` objects.

`pure-Y-extent` (pair of numbers)
: The estimated height of a system.

This grob interface is used in the following graphical object(s): Section 3.1.109 [System], page 380.

3.2.112 system-start-delimiter-interface

The brace, bracket or bar in front of the system. The following values for `style` are recognized:

`bracket` A thick bracket, normally used to group similar instruments in a score. Default for `StaffGroup`. `SystemStartBracket` uses this style.

`brace` A 'piano style' brace normally used for an instrument that uses two staves. The default style for `GrandStaff`. `SystemStartBrace` uses this style.

`bar-line` A simple line between the staves in a score. Default for staves enclosed in `<<` and `>>`. `SystemStartBar` uses this style.

`line-bracket`
: A simple square, normally used for subgrouping instruments in a score. `SystemStartSquare` uses this style.

See also '`input/regression/system-start-nesting.ly`'.

User settable properties:

`collapse-height` (dimension, in staff space)
: Minimum height of system start delimiter. If equal or smaller, the bracket/brace/line is removed.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

This grob interface is used in the following graphical object(s): Section 3.1.110 [SystemStartBar], page 381, Section 3.1.111 [SystemStartBrace], page 382, Section 3.1.112 [SystemStartBracket], page 382 and Section 3.1.113 [SystemStartSquare], page 383.

3.2.113 system-start-text-interface

Text in front of the system.

User settable properties:

`long-text` (markup)
: Text markup. See Section "Formatting text" in *Notation Reference*.

`self-alignment-X` (number)
: Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`self-alignment-Y` (number)
: Like `self-alignment-X` but for the Y axis.

`text` (markup)
: Text markup. See Section "Formatting text" in *Notation Reference*.

This grob interface is used in the following graphical object(s): Section 3.1.51 [InstrumentName], page 332.

3.2.114 tab-note-head-interface

A note head in tablature.

User settable properties:

`details` (list)
: Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

Internal properties:

`display-cautionary` (boolean)
: Should the grob be displayed as a cautionary grob?

`span-start` (boolean)
: Is the note head at the start of a spanner?

This grob interface is used in the following graphical object(s): Section 3.1.114 [TabNoteHead], page 384.

3.2.115 text-interface

A Scheme markup text, see Section "Formatting text" in *Notation Reference* and Section "New markup command definition" in *Extending*.

There are two important commands: `ly:text-interface::print`, which is a grob callback, and `ly:text-interface::interpret-markup`.

User settable properties:

`baseline-skip` (dimension, in staff space)
: Distance between base lines of multiple lines of text.

`text` (markup)
: Text markup. See Section "Formatting text" in *Notation Reference*.

`word-space` (dimension, in staff space)
: Space to insert between words in texts.

`text-direction` (direction)
: This controls the ordering of the words. The default `RIGHT` is for roman text. Arabic or Hebrew should use `LEFT`.

This grob interface is used in the following graphical object(s): Section 3.1.10 [BalloonTextItem], page 296, Section 3.1.12 [BarNumber], page 298, Section 3.1.13 [BassFigure], page 300, Section 3.1.23 [BreathingSign], page 306, Section 3.1.24 [ChordName], page 307, Section 3.1.28 [CombineTextScript], page 309, Section 3.1.35 [DoublePercentRepeatCounter], page 316, Section 3.1.38 [DynamicText], page 319, Section 3.1.39 [DynamicTextSpanner], page 321, Section 3.1.41 [Fingering], page 323, Section 3.1.42 [FootnoteItem], page 324, Section 3.1.43 [FootnoteSpanner], page 325, Section 3.1.52 [InstrumentSwitch], page 333, Section 3.1.63 [LyricText], page 342, Section 3.1.67 [MetronomeMark], page 344, Section 3.1.69 [MultiMeasureRestNumber], page 347, Section 3.1.70 [MultiMeasureRestText], page 348, Section 3.1.75 [NoteName], page 352, Section 3.1.77 [OctavateEight], page 353, Section 3.1.78 [OttavaBracket], page 354, Section 3.1.82 [PercentRepeatCounter], page 357, Section 3.1.85 [RehearsalMark], page 360, Section 3.1.95 [SostenutoPedal], page 367, Section 3.1.102 [StanzaNumber], page 373, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377, Section 3.1.107 [SustainPedal], page 378, Section 3.1.114 [TabNoteHead], page 384, Section 3.1.115 [TextScript], page 385, Section 3.1.125 [TupletNumber], page 396, Section 3.1.126 [UnaCordaPedal], page 396 and Section 3.1.132 [VoltaBracket], page 401.

3.2.116 text-script-interface

An object that is put above or below a note.

User settable properties:

`add-stem-support` (boolean)
: If set, the `Stem` object is included in this script's support.

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`script-priority` (number)
: A sorting key that determines in what order a script is within a stack of scripts.

Internal properties:

`slur` (graphical (layout) object)
: A pointer to a `Slur` object.

This grob interface is used in the following graphical object(s): Section 3.1.28 [CombineTextScript], page 309, Section 3.1.41 [Fingering], page 323, Section 3.1.105 [StringNumber], page 376, Section 3.1.106 [StrokeFinger], page 377 and Section 3.1.115 [TextScript], page 385.

3.2.117 tie-column-interface

Object that sets directions of multiple ties in a tied chord.

User settable properties:

`tie-configuration` (list)
: List of `(`*`position . dir`*`)` pairs, indicating the desired tie configuration, where *position* is the offset from the center of the staff in staff space and *dir* indicates the direction of the tie (`1`=>up, `-1`=>down, `0`=>center). A non-pair entry in the list causes the corresponding tie to be formatted automatically.

Internal properties:

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

This grob interface is used in the following graphical object(s): Section 3.1.118 [TieColumn], page 389.

3.2.118 tie-interface

A horizontal curve connecting two noteheads.

User settable properties:

`annotation` (string)
: Annotate a grob for debug purposes.

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`control-points` (list)
: List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`dash-definition` (pair)
: List of `dash-elements` defining the dash structure. Each `dash-element` has a starting t value, an ending t-value, a `dash-fraction`, and a `dash-period`.

`details` (list)
: Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`head-direction` (direction)
: Are the note heads left or right in a semitie?

`line-thickness` (number)
: The thickness of the tie or slur contour.

`neutral-direction` (direction)
: Which direction to take in the center of the staff.

`staff-position` (number)
: Vertical position, measured in half staff spaces, counted from the middle line.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

This grob interface is used in the following graphical object(s): Section 3.1.117 [Tie], page 388.

3.2.119 time-signature-interface

A time signature, in different styles. The following values for `style` are are recognized:

`C` 4/4 and 2/2 are typeset as C and struck C, respectively. All other time signatures are written with two digits. The value `default` is equivalent to `C`.

`neomensural`
: 2/2, 3/2, 2/4, 3/4, 4/4, 6/4, 9/4, 4/8, 6/8, and 9/8 are typeset with neo-mensural style mensuration marks. All other time signatures are written with two digits.

`mensural` 2/2, 3/2, 2/4, 3/4, 4/4, 6/4, 9/4, 4/8, 6/8, and 9/8 are typeset with mensural style mensuration marks. All other time signatures are written with two digits.

`single-digit`
: All time signatures are typeset with a single digit, e.g., 3/2 is written as 3.

`numbered` All time signatures are typeset with two digits.

User settable properties:

`fraction` (pair of numbers)
: Numerator and denominator of a time signature object.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

This grob interface is used in the following graphical object(s): Section 3.1.119 [TimeSignature], page 390.

3.2.120 trill-pitch-accidental-interface

An accidental for trill pitch.

This grob interface is used in the following graphical object(s): Section 3.1.120 [TrillPitchAccidental], page 391.

3.2.121 trill-spanner-interface

A trill spanner.

This grob interface is used in the following graphical object(s): Section 3.1.123 [TrillSpanner], page 393.

3.2.122 tuplet-bracket-interface

A bracket with a number in the middle, used for tuplets. When the bracket spans a line break, the value of `break-overshoot` determines how far it extends beyond the staff. At a line break, the markups in the `edge-text` are printed at the edges.

User settable properties:

`bracket-flare` (pair of numbers)
: A pair of numbers specifying how much edges of brackets should slant outward. Value `0.0` means straight edges.

`bracket-visibility` (boolean or symbol)
: This controls the visibility of the tuplet bracket. Setting it to false prevents printing of the bracket. Setting the property to `if-no-beam` makes it print only if there is no beam associated with this tuplet bracket.

`break-overshoot` (pair of numbers)
: How much does a broken spanner stick out of its bounds?

`connect-to-neighbor` (pair)
: Pair of booleans, indicating whether this grob looks as a continued break.

`control-points` (list)
: List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`edge-height` (pair)
: A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`edge-text` (pair)
: A pair specifying the texts to be set at the edges: `(`*`left-text . right-text`*`)`.

`full-length-padding` (number)
: How much padding to use at the right side of a full-length tuplet bracket.

`full-length-to-extent` (boolean)
: Run to the extent of the column for a full-length tuplet bracket.

`gap` (dimension, in staff space)
: Size of a gap in a variable symbol.

`positions` (pair of numbers)
: Pair of staff coordinates `(left . right)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`shorten-pair` (pair of numbers)
: The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`staff-padding` (dimension, in staff space)
: Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`note-columns` (array of grobs)
: An array of `NoteColumn` grobs.

`tuplet-number` (graphical (layout) object)
: The number for a bracket.

`tuplets` (array of grobs)
: An array of smaller tuplet brackets.

This grob interface is used in the following graphical object(s): Section 3.1.59 [LigatureBracket], page 339 and Section 3.1.124 [TupletBracket], page 395.

3.2.123 tuplet-number-interface

The number for a bracket.

User settable properties:

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

Internal properties:

`bracket` (graphical (layout) object)
: The bracket for a number.

This grob interface is used in the following graphical object(s): Section 3.1.125 [TupletNumber], page 396.

3.2.124 unbreakable-spanner-interface

A spanner that should not be broken across line breaks. Override with `breakable=##t`.

User settable properties:

`breakable` (boolean)
: Allow breaks here.

This grob interface is used in the following graphical object(s): Section 3.1.19 [Beam], page 302 and Section 3.1.45 [Glissando], page 327.

3.2.125 vaticana-ligature-interface

A vaticana style Gregorian ligature.

User settable properties:

`glyph-name` (string)
: The glyph name within the font.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

Internal properties:

`flexa-height` (dimension, in staff space)
: The height of a flexa shape in a ligature grob (in `staff-space` units).

`flexa-width` (dimension, in staff space)
: The width of a flexa shape in a ligature grob in (in `staff-space` units).

`add-cauda` (boolean)
: Does this flexa require an additional cauda on the left side?

`add-stem` (boolean)
: Is this ligature head a virga and therefore needs an additional stem on the right side?

`add-join` (boolean)
: Is this ligature head-joined with the next one by a vertical line?

`delta-position` (number)
: The vertical position difference.

`x-offset` (dimension, in staff space)
: Extra horizontal offset for ligature heads.

This grob interface is used in the following graphical object(s): Section 3.1.74 [NoteHead], page 351 and Section 3.1.128 [VaticanaLigature], page 398.

3.2.126 volta-bracket-interface

Volta bracket with number.

User settable properties:

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

`height` (dimension, in staff space)
: Height of an object in `staff-space` units.

Internal properties:

`bars` (array of grobs)
: An array of bar line pointers.

This grob interface is used in the following graphical object(s): Section 3.1.132 [VoltaBracket], page 401.

3.2.127 volta-interface

A volta repeat.

This grob interface is used in the following graphical object(s): Section 3.1.132 [VoltaBracket], page 401 and Section 3.1.133 [VoltaBracketSpanner], page 402.

3.3 User backend properties

`add-stem-support` (boolean)
: If set, the `Stem` object is included in this script's support.

`after-line-breaking` (boolean)
: Dummy property, used to trigger callback for `after-line-breaking`.

`align-dir` (direction)
: Which side to align? `-1`: left side, `0`: around center of width, `1`: right side.

`allow-loose-spacing` (boolean)
: If set, column can be detached from main spacing.

`allow-span-bar` (boolean)
: If false, no inter-staff bar line will be created below this bar line.

`alteration` (number)
: Alteration numbers for accidental.

`alteration-alist` (list)
: List of `(`*`pitch . accidental`*`)` pairs for key signature.

`annotation` (string)
: Annotate a grob for debug purposes.

`annotation-balloon` (boolean)
: Print the balloon around an annotation.

`annotation-line` (boolean)
: Print the line from an annotation to the grob that it annotates.

`arpeggio-direction` (direction)
: If set, put an arrow on the arpeggio squiggly line.

`arrow-length` (number)
: Arrow length.

`arrow-width` (number)
: Arrow width.

`auto-knee-gap` (dimension, in staff space)
: If a gap is found between note heads where a horizontal beam fits that is larger than this number, make a kneed beam.

`average-spacing-wishes` (boolean)
: If set, the spacing wishes are averaged over staves.

`avoid-note-head` (boolean)
: If set, the stem of a chord does not pass through all note heads, but starts at the last note head.

`avoid-slur` (symbol)
: Method of handling slur collisions. Choices are `inside`, `outside`, `around`, and `ignore`. `inside` adjusts the slur if needed to keep the grob inside the slur. `outside` moves the grob vertically to the outside of the slur. `around` moves the grob vertically to the outside of the slur only if there is a collision. `ignore` does not move either. In grobs whose notational significance depends on vertical position (such as accidentals, clefs, etc.), `outside` and `around` behave like `ignore`.

`axes` (list)
: List of axis numbers. In the case of alignment grobs, this should contain only one number.

`base-shortest-duration` (moment)
: Spacing is based on the shortest notes in a piece. Normally, pieces are spaced as if notes at least as short as this are present.

`baseline-skip` (dimension, in staff space)
: Distance between base lines of multiple lines of text.

`beam-thickness` (dimension, in staff space)
: Beam thickness, measured in `staff-space` units.

`beam-width` (dimension, in staff space)
: Width of the tremolo sign.

`beamed-stem-shorten` (list)
: How much to shorten beamed stems, when their direction is forced. It is a list, since the value is different depending on the number of flags and beams.

`beaming` (pair)
: Pair of number lists. Each number list specifies which beams to make. `0` is the central beam, `1` is the next beam toward the note, etc. This information is used to determine how to connect the beaming patterns from stem to stem inside a beam.

`beamlet-default-length` (pair)
: A pair of numbers. The first number specifies the default length of a beamlet that sticks out of the left hand side of this stem; the second number specifies the default length of the beamlet to the right. The actual length of a beamlet is determined by taking either the default length or the length specified by `beamlet-max-length-proportion`, whichever is smaller.

`beamlet-max-length-proportion` (pair)
: The maximum length of a beamlet, as a proportion of the distance between two adjacent stems.

`before-line-breaking` (boolean)
: Dummy property, used to trigger a callback function.

`between-cols` (pair)
: Where to attach a loose column to.

`bound-details` (list)
: An alist of properties for determining attachments of spanners to edges.

`bound-padding` (number)
: The amount of padding to insert around spanner bounds.

`bracket-flare` (pair of numbers)
: A pair of numbers specifying how much edges of brackets should slant outward. Value `0.0` means straight edges.

`bracket-visibility` (boolean or symbol)
: This controls the visibility of the tuplet bracket. Setting it to false prevents printing of the bracket. Setting the property to `if-no-beam` makes it print only if there is no beam associated with this tuplet bracket.

`break-align-anchor` (number)
: Grobs aligned to this break-align grob will have their X-offsets shifted by this number. In bar lines, for example, this is used to position grobs relative to the (visual) center of the bar line.

`break-align-anchor-alignment` (number)
: Read by `ly:break-aligned-interface::calc-extent-aligned-anchor` for aligning an anchor to a grob's extent.

`break-align-orders` (vector)
: Defines the order in which prefatory matter (clefs, key signatures) appears. The format is a vector of length 3, where each element is one order for end-of-line, middle of line, and start-of-line, respectively. An order is a list of symbols.

  For example, clefs are put after key signatures by setting

```
\override Score.BreakAlignment #'break-align-orders =
  #(make-vector 3 '(span-bar
                    breathing-sign
                    staff-bar
                    key
                    clef
                    time-signature))
```

`break-align-symbol` (symbol)
: This key is used for aligning and spacing breakable items.

`break-align-symbols` (list)
: A list of symbols that determine which break-aligned grobs to align this to. If the grob selected by the first symbol in the list is invisible due to break-visibility, we will align to the next grob (and so on). Choices are `left-edge`, `ambitus`, `breathing-sign`, `clef`, `staff-bar`, `key-cancellation`, `key-signature`, `time-signature`, and `custos`.

`break-overshoot` (pair of numbers)
: How much does a broken spanner stick out of its bounds?

`break-visibility` (vector)
: A vector of 3 booleans, `#(`*`end-of-line unbroken begin-of-line`*`)`. `#t` means visible, `#f` means killed.

`breakable` (boolean)
: Allow breaks here.

`c0-position` (integer)
: An integer indicating the position of middle C.

`circled-tip` (boolean)
: Put a circle at start/end of hairpins (al/del niente).

`clip-edges` (boolean)
: Allow outward pointing beamlets at the edges of beams?

`collapse-height` (dimension, in staff space)
: Minimum height of system start delimiter. If equal or smaller, the bracket/brace/line is removed.

`collision-interfaces` (list)
: A list of interfaces for which automatic beam-collision resolution is run.

`collision-voice-only` (boolean)
: Does automatic beam collsion apply only to the voice in which the beam was created?

`color` (color)
: The color of this grob.

`common-shortest-duration` (moment)
: The most common shortest note length. This is used in spacing. Enlarging this sets the score tighter.

`concaveness` (number)
: A beam is concave if its inner stems are closer to the beam than the two outside stems. This number is a measure of the closeness of the inner stems. It is used for damping the slope of the beam.

`connect-to-neighbor` (pair)
: Pair of booleans, indicating whether this grob looks as a continued break.

`control-points` (list)
: List of offsets (number pairs) that form control points for the tie, slur, or bracket shape. For Béziers, this should list the control points of a third-order Bézier curve.

`damping` (number)
: Amount of beam slope damping.

`dash-definition` (pair)
: List of `dash-elements` defining the dash structure. Each `dash-element` has a starting t value, an ending t-value, a `dash-fraction`, and a `dash-period`.

`dash-fraction` (number)
: Size of the dashes, relative to `dash-period`. Should be between `0.0` (no line) and `1.0` (continuous line).

`dash-period` (number)
: The length of one dash together with whitespace. If negative, no line is drawn at all.

`default-direction` (direction)
: Direction determined by note head positions.

`default-staff-staff-spacing` (list)
: The settings to use for `staff-staff-spacing` when it is unset, for ungrouped staves and for grouped staves that do not have the relevant `StaffGrouper` property set (`staff-staff-spacing` or `staffgroup-staff-spacing`).

`details` (list)
: Alist of parameters for detailed grob behavior. More information on the allowed parameters for a grob can be found by looking at the top of the Internals Reference page for each interface having a `details` property.

`digit-names` (vector)
: Names for string finger digits.

`direction` (direction)
: If `side-axis` is `0` (or `#X`), then this property determines whether the object is placed `#LEFT`, `#CENTER` or `#RIGHT` with respect to the other object. Otherwise, it determines whether the object is placed `#UP`, `#CENTER` or `#DOWN`. Numerical values may also be used: `#UP=1`, `#DOWN=-1`, `#LEFT=-1`, `#RIGHT=1`, `#CENTER=0`.

`dot-count` (integer)
: The number of dots.

`dot-negative-kern` (number)
: The space to remove between a dot and a slash in percent repeat glyphs. Larger values bring the two elements closer together.

`dot-placement-list` (list)
: List consisting of `(`*`description string-number fret-number finger-number`*`)` entries used to define fret diagrams.

`duration-log` (integer)
: The 2-log of the note head duration, i.e., `0` = whole note, `1` = half note, etc.

`eccentricity` (number)
: How asymmetrical to make a slur. Positive means move the center to the right.

`edge-height` (pair)
: A pair of numbers specifying the heights of the vertical edges: `(`*`left-height . right-height`*`)`.

`edge-text` (pair)
: A pair specifying the texts to be set at the edges: `(`*`left-text . right-text`*`)`.

`expand-limit` (integer)
: Maximum number of measures expanded in church rests.

`extra-dy` (number)
: Slope glissandi this much extra.

`extra-offset` (pair of numbers)
: A pair representing an offset. This offset is added just before outputting the symbol, so the typesetting engine is completely oblivious to it. The values are measured in `staff-space` units of the staff's `StaffSymbol`.

`extra-spacing-height` (pair of numbers)
: In the horizontal spacing problem, we increase the height of each item by this amount (by adding the 'car' to the bottom of the item and adding the 'cdr' to the top of the item). In order to make a grob infinitely high (to prevent the horizontal spacing problem from placing any other grobs above or below this grob), set this to `(-inf.0 . +inf.0)`.

`extra-spacing-width` (pair of numbers)
: In the horizontal spacing problem, we pad each item by this amount (by adding the 'car' on the left side of the item and adding the 'cdr' on the right side of the item). In order to make a grob take up no horizontal space at all, set this to `(+inf.0 . -inf.0)`.

`extra-X-extent` (pair of numbers)
: A grob is enlarged in X dimension by this much.

`extra-Y-extent` (pair of numbers)
: A grob is enlarged in Y dimension by this much.

`flag` (stencil)
: A function returning the full flag stencil for the `Stem`, which is passed to the function as the only argument. The default ly:stem::calc-stencil function uses the `flag-style` property to determine the correct glyph for the flag. By providing your own function, you can create arbitrary flags.

`flag-count` (number)
: The number of tremolo beams.

`flag-style` (symbol)
: A symbol determining what style of flag glyph is typeset on a `Stem`. Valid options include `'()` for standard flags, `'mensural` and `'no-flag`, which switches off the flag.

`font-encoding` (symbol)
: The font encoding is the broadest category for selecting a font. Currently, only lilypond's system fonts (Emmentaler) are using this property. Available values are `fetaMusic` (Emmentaler), `fetaBraces`, `fetaText` (Emmentaler).

`font-family` (symbol)
: The font family is the broadest category for selecting text fonts. Options include: `sans`, `roman`.

`font-name` (string)
: Specifies a file name (without extension) of the font to load. This setting overrides selection using `font-family`, `font-series` and `font-shape`.

`font-series` (symbol)
: Select the series of a font. Choices include `medium`, `bold`, `bold-narrow`, etc.

`font-shape` (symbol)
: Select the shape of a font. Choices include `upright`, `italic`, `caps`.

`font-size` (number)
: The font size, compared to the 'normal' size. `0` is style-sheet's normal size, `-1` is smaller, `+1` is bigger. Each step of 1 is approximately 12% larger; 6 steps are exactly a factor 2 larger. Fractional values are allowed.

`footnote-text` (markup)
: A footnote for the grob.

`force-hshift` (number)
: This specifies a manual shift for notes in collisions. The unit is the note head width of the first voice note. This is used by Section "note-collision-interface" in *Internals Reference*.

`fraction` (pair of numbers)
: Numerator and denominator of a time signature object.

`french-beaming` (boolean)
: Use French beaming style for this stem. The stem stops at the innermost beams.

`fret-diagram-details` (list)
: An alist of detailed grob properties for fret diagrams. Each alist entry consists of a `(`*`property . value`*`)` pair. The properties which can be included in `fret-diagram-details` include the following:

  - `barre-type` – Type of barre indication used. Choices include `curved`, `straight`, and `none`. Default `curved`.

- `capo-thickness` – Thickness of capo indicator, in multiples of fret-space. Default value 0.5.
- `dot-color` – Color of dots. Options include `black` and `white`. Default `black`.
- `dot-label-font-mag` – Magnification for font used to label fret dots. Default value 1.
- `dot-position` – Location of dot in fret space. Default 0.6 for dots without labels, 0.95-`dot-radius` for dots with labels.
- `dot-radius` – Radius of dots, in terms of fret spaces. Default value 0.425 for labeled dots, 0.25 for unlabeled dots.
- `finger-code` – Code for the type of fingering indication used. Options include `none`, `in-dot`, and `below-string`. Default `none` for markup fret diagrams, `below-string` for `FretBoards` fret diagrams.
- `fret-count` – The number of frets. Default 4.
- `fret-label-custom-format` – The format string to be used label the lowest fret number, when `number-type` equals to `custom`. Default `"~a"`.
- `fret-label-font-mag` – The magnification of the font used to label the lowest fret number. Default 0.5.
- `fret-label-vertical-offset` – The offset of the fret label from the center of the fret in direction parallel to strings. Default 0.
- `label-dir` – Side to which the fret label is attached. `-1`, `#LEFT`, or `#DOWN` for left or down; `1`, `#RIGHT`, or `#UP` for right or up. Default `#RIGHT`.
- `mute-string` – Character string to be used to indicate muted string. Default `"x"`.
- `number-type` – Type of numbers to use in fret label. Choices include `roman-lower`, `roman-upper`, `arabic` and `custom`. In the later case, the format string is supplied by the `fret-label-custom-format` property. Default `roman-lower`.
- `open-string` – Character string to be used to indicate open string. Default `"o"`.
- `orientation` – Orientation of fret-diagram. Options include `normal`, `landscape`, and `opposing-landscape`. Default `normal`.
- `string-count` – The number of strings. Default 6.
- `string-label-font-mag` – The magnification of the font used to label fingerings at the string, rather than in the dot. Default value 0.6 for `normal` orientation, 0.5 for `landscape` and `opposing-landscape`.
- `string-thickness-factor` – Factor for changing thickness of each string in the fret diagram. Thickness of string k is given by `thickness` * (1+`string-thickness-factor`) ^ (k-1). Default 0.
- `top-fret-thickness` – The thickness of the top fret line, as a multiple of the standard thickness. Default value 3.
- `xo-font-magnification` – Magnification used for mute and open string indicators. Default value 0.5.
- `xo-padding` – Padding for open and mute indicators from top fret. Default value 0.25.

`full-length-padding` (number)
: How much padding to use at the right side of a full-length tuplet bracket.

`full-length-to-extent` (boolean)
: Run to the extent of the column for a full-length tuplet bracket.

`full-measure-extra-space` (number)
: Extra space that is allocated at the beginning of a measure with only one note. This property is read from the NonMusicalPaperColumn that begins the measure.

`full-size-change` (boolean)
: Don't make a change clef smaller.

`gap` (dimension, in staff space)
: Size of a gap in a variable symbol.

`gap-count` (integer)
: Number of gapped beams for tremolo.

`glyph` (string)
: A string determining what 'style' of glyph is typeset. Valid choices depend on the function that is reading this property.

`glyph-name` (string)
: The glyph name within the font.

`glyph-name-alist` (list)
: An alist of key-string pairs.

`graphical` (boolean)
: Display in graphical (vs. text) form.

`grow-direction` (direction)
: Crescendo or decrescendo?

`hair-thickness` (number)
: Thickness of the thin line in a bar line.

`harp-pedal-details` (list)
: An alist of detailed grob properties for harp pedal diagrams. Each alist entry consists of a `(property . value)` pair. The properties which can be included in harp-pedal-details include the following:

  - `box-offset` – Vertical shift of the center of flat/sharp pedal boxes above/below the horizontal line. Default value 0.8.
  - `box-width` – Width of each pedal box. Default value 0.4.
  - `box-height` – Height of each pedal box. Default value 1.0.
  - `space-before-divider` – Space between boxes before the first divider (so that the diagram can be made symmetric). Default value 0.8.
  - `space-after-divider` – Space between boxes after the first divider. Default value 0.8.
  - `circle-thickness` – Thickness (in unit of the line-thickness) of the ellipse around circled pedals. Default value 0.5.
  - `circle-x-padding` – Padding in X direction of the ellipse around circled pedals. Default value 0.15.
  - `circle-y-padding` – Padding in Y direction of the ellipse around circled pedals. Default value 0.2.

`head-direction` (direction)
: Are the note heads left or right in a semitie?

`height` (dimension, in staff space)
: Height of an object in `staff-space` units.

`height-limit` (dimension, in staff space)
: Maximum slur height: The longer the slur, the closer it is to this height.

`hide-tied-accidental-after-break` (boolean)
: If set, an accidental that appears on a tied note after a line break will not be displayed.

`horizontal-shift` (integer)
: An integer that identifies ranking of `NoteColumn`s for horizontal shifting. This is used by Section "note-collision-interface" in *Internals Reference*.

`horizontal-skylines` (pair of skylines)
: Two skylines, one to the left and one to the right of this grob.

`ignore-collision` (boolean)
: If set, don't do note collision resolution on this `NoteColumn`.

`implicit` (boolean)
: Is this an implicit bass figure?

`inspect-index` (integer)
: If debugging is set, set beam and slur configuration to this index, and print the respective scores.

`inspect-quants` (pair of numbers)
: If debugging is set, set beam and slur quants to this position, and print the respective scores.

`keep-inside-line` (boolean)
: If set, this column cannot have objects sticking into the margin.

`kern` (dimension, in staff space)
: Amount of extra white space to add. For bar lines, this is the amount of space after a thick line.

`knee` (boolean)
: Is this beam kneed?

`knee-spacing-correction` (number)
: Factor for the optical correction amount for kneed beams. Set between `0` for no correction and `1` for full correction.

`labels` (list)
: List of labels (symbols) placed on a column.

`layer` (integer)
: An integer which determines the order of printing objects. Objects with the lowest value of layer are drawn first, then objects with progressively higher values are drawn, so objects with higher values overwrite objects with lower values. By default most objects are assigned a layer value of 1.

`ledger-line-thickness` (pair of numbers)
: The thickness of ledger lines. It is the sum of 2 numbers: The first is the factor for line thickness, and the second for staff space. Both contributions are added.

`left-bound-info` (list)
: An alist of properties for determining attachments of spanners to edges.

`left-padding` (dimension, in staff space)
: The amount of space that is put left to an object (e.g., a lyric extender).

`length` (dimension, in staff space)
: User override for the stem length of unbeamed stems.

`length-fraction` (number)
: Multiplier for lengths. Used for determining ledger lines and stem lengths.

`line-break-penalty` (number)
: Penalty for a line break at this column. This affects the choices of the line breaker; it avoids a line break at a column with a positive penalty and prefers a line break at a column with a negative penalty.

`line-break-permission` (symbol)
: Instructs the line breaker on whether to put a line break at this column. Can be `force` or `allow`.

`line-break-system-details` (list)
: An alist of properties to use if this column is the start of a system.

`line-count` (integer)
: The number of staff lines.

`line-positions` (list)
: Vertical positions of staff lines.

`line-thickness` (number)
: The thickness of the tie or slur contour.

`long-text` (markup)
: Text markup. See Section "Formatting text" in *Notation Reference*.

`max-beam-connect` (integer)
: Maximum number of beams to connect to beams from this stem. Further beams are typeset as beamlets.

`max-stretch` (number)
: The maximum amount that this `VerticalAxisGroup` can be vertically stretched (for example, in order to better fill a page).

`measure-count` (integer)
: The number of measures for a multi-measure rest.

`measure-length` (moment)
: Length of a measure. Used in some spacing situations.

`merge-differently-dotted` (boolean)
: Merge note heads in collisions, even if they have a different number of dots. This is normal notation for some types of polyphonic music.

  `merge-differently-dotted` only applies to opposing stem directions (i.e., voice 1 & 2).

`merge-differently-headed` (boolean)
: Merge note heads in collisions, even if they have different note heads. The smaller of the two heads is rendered invisible. This is used in polyphonic guitar notation. The value of this setting is used by Section "note-collision-interface" in *Internals Reference*.

  `merge-differently-headed` only applies to opposing stem directions (i.e., voice 1 & 2).

`minimum-distance` (dimension, in staff space)
: Minimum distance between rest and notes or beam.

`minimum-length` (dimension, in staff space)
: Try to make a spanner at least this long, normally in the horizontal direction. This requires an appropriate callback for the `springs-and-rods` property. If added to a `Tie`, this sets the minimum distance between noteheads.

`minimum-length-fraction` (number)
: Minimum length of ledger line as fraction of note head size.

`minimum-space` (dimension, in staff space)
: Minimum distance that the victim should move (after padding).

`minimum-X-extent` (pair of numbers)
: Minimum size of an object in X dimension, measured in `staff-space` units.

`minimum-Y-extent` (pair of numbers)
: Minimum size of an object in Y dimension, measured in `staff-space` units.

`neutral-direction` (direction)
: Which direction to take in the center of the staff.

`neutral-position` (number)
: Position (in half staff spaces) where to flip the direction of custos stem.

`next` (graphical (layout) object)
: Object that is next relation (e.g., the lyric syllable following an extender).

`no-alignment` (boolean)
: If set, don't place this grob in a `VerticalAlignment`; rather, place it using its own `Y-offset` callback.

`no-ledgers` (boolean)
: If set, don't draw ledger lines on this object.

`no-stem-extend` (boolean)
: If set, notes with ledger lines do not get stems extending to the middle staff line.

`non-break-align-symbols` (list)
: A list of symbols that determine which NON-break-aligned interfaces to align this to.

`non-default` (boolean)
: Set for manually specified clefs.

`non-musical` (boolean)
: True if the grob belongs to a `NonMusicalPaperColumn`.

`nonstaff-nonstaff-spacing` (list)
: The spacing alist controlling the distance between the current non-staff line and the next non-staff line in the direction of `staff-affinity`, if both are on the same side of the related staff, and `staff-affinity` is either `UP` or `DOWN`. See `staff-staff-spacing` for a description of the alist structure.

`nonstaff-relatedstaff-spacing` (list)
: The spacing alist controlling the distance between the current non-staff line and the nearest staff in the direction of `staff-affinity`, if there are no non-staff lines between the two, and `staff-affinity` is either `UP` or `DOWN`. If `staff-affinity` is `CENTER`, then `nonstaff-relatedstaff-spacing` is used for the nearest staves on *both* sides, even if other non-staff lines appear between the current one and either of the staves. See `staff-staff-spacing` for a description of the alist structure.

`nonstaff-unrelatedstaff-spacing` (list)
: The spacing alist controlling the distance between the current non-staff line and the nearest staff in the opposite direction from `staff-affinity`, if there are no other non-staff lines between the two, and `staff-affinity` is either `UP` or `DOWN`. See `staff-staff-spacing` for a description of the alist structure.

`normalized-endpoints` (pair)
: Represents left and right placement over the total spanner, where the width of the spanner is normalized between 0 and 1.

`note-names` (vector)
: Vector of strings containing names for easy-notation note heads.

`outside-staff-horizontal-padding` (number)
: By default, an outside-staff-object can be placed so that is it very close to another grob horizontally. If this property is set, the outside-staff-object is raised so that it is not so close to its neighbor.

`outside-staff-padding` (number)
: The padding to place between this grob and the staff when spacing according to `outside-staff-priority`.

`outside-staff-priority` (number)
: If set, the grob is positioned outside the staff in such a way as to avoid all collisions. In case of a potential collision, the grob with the smaller `outside-staff-priority` is closer to the staff.

`packed-spacing` (boolean)
: If set, the notes are spaced as tightly as possible.

`padding` (dimension, in staff space)
: Add this much extra space between objects that are next to each other.

`padding-pairs` (list)
: An alist mapping `(`*`name . name`*`)` to distances.

`page-break-penalty` (number)
: Penalty for page break at this column. This affects the choices of the page breaker; it avoids a page break at a column with a positive penalty and prefers a page break at a column with a negative penalty.

`page-break-permission` (symbol)
: Instructs the page breaker on whether to put a page break at this column. Can be `force` or `allow`.

`page-turn-penalty` (number)
: Penalty for a page turn at this column. This affects the choices of the page breaker; it avoids a page turn at a column with a positive penalty and prefers a page turn at a column with a negative penalty.

`page-turn-permission` (symbol)
: Instructs the page breaker on whether to put a page turn at this column. Can be `force` or `allow`.

`parenthesized` (boolean)
: Parenthesize this grob.

`positions` (pair of numbers)
: Pair of staff coordinates `(`*`left . right`*`)`, where both *left* and *right* are in `staff-space` units of the current staff. For slurs, this value selects which slur candidate to use; if extreme positions are requested, the closest one is taken.

`prefer-dotted-right` (boolean)
: For note collisions, prefer to shift dotted up-note to the right, rather than shifting just the dot.

`ratio` (number)
: Parameter for slur shape. The higher this number, the quicker the slur attains its `height-limit`.

`remove-empty` (boolean)
: If set, remove group if it contains no interesting items.

`remove-first` (boolean)
: Remove the first staff of an orchestral score?

`restore-first` (boolean)
: Print a natural before the accidental.

`rhythmic-location` (rhythmic location)
: Where (bar number, measure position) in the score.

`right-bound-info` (list)
: An alist of properties for determining attachments of spanners to edges.

`right-padding` (dimension, in staff space)
: Space to insert on the right side of an object (e.g., between note and its accidentals).

`rotation` (list)
: Number of degrees to rotate this object, and what point to rotate around. For example, `#'(45 0 0)` rotates by 45 degrees around the center of this object.

`same-direction-correction` (number)
: Optical correction amount for stems that are placed in tight configurations. This amount is used for stems with the same direction to compensate for note head to stem distance.

`script-priority` (number)
: A sorting key that determines in what order a script is within a stack of scripts.

`self-alignment-X` (number)
: Specify alignment of an object. The value `-1` means left aligned, `0` centered, and `1` right-aligned in X direction. Other numerical values may also be specified.

`self-alignment-Y` (number)
: Like `self-alignment-X` but for the Y axis.

`shorten-pair` (pair of numbers)
: The lengths to shorten a text-spanner on both sides, for example a pedal bracket. Positive values shorten the text-spanner, while negative values lengthen it.

`shortest-duration-space` (dimension, in staff space)
: Start with this much space for the shortest duration. This is expressed in `spacing-increment` as unit. See also Section "spacing-spanner-interface" in *Internals Reference*.

`shortest-playing-duration` (moment)
: The duration of the shortest note playing here.

`shortest-starter-duration` (moment)
: The duration of the shortest note that starts here.

`side-axis` (number)
: If the value is `#X` (or equivalently `0`), the object is placed horizontally next to the other object. If the value is `#Y` or `1`, it is placed vertically.

`side-relative-direction` (direction)
: Multiply direction of `direction-source` with this to get the direction of this object.

`size` (number)
: Size of object, relative to standard size.

`skyline-horizontal-padding` (number)
: For determining the vertical distance between two staves, it is possible to have a configuration which would result in a tight interleaving of grobs from the top staff and the bottom staff. The larger this parameter is, the farther apart the staves are placed in such a configuration.

`skyline-vertical-padding` (number)
: The amount by which the left and right skylines of a column are padded vertically, beyond the `Y-extent`s and `extra-spacing-height`s of the constituent grobs in the column. Increase this to prevent interleaving of grobs from adjacent columns.

`slash-negative-kern` (number)
: The space to remove between slashes in percent repeat glyphs. Larger values bring the two elements closer together.

`slope` (number)
: The slope of this object.

`slur-padding` (number)
: Extra distance between slur and script.

`space-alist` (list)
: A table that specifies distances between prefatory items, like clef and time-signature. The format is an alist of spacing tuples: `(`*`break-align-symbol type . distance`*`)`, where *type* can be the symbols `minimum-space` or `extra-space`.

`space-to-barline` (boolean)
: If set, the distance between a note and the following non-musical column will be measured to the bar line instead of to the beginning of the non-musical column. If there is a clef change followed by a bar line, for example, this means that we will try to space the non-musical column as though the clef is not there.

`spacing-increment` (number)
: Add this much space for a doubled duration. Typically, the width of a note head. See also Section “spacing-spanner-interface” in *Internals Reference*.

`spacing-pair` (pair)
: A pair of alignment symbols which set an object's spacing relative to its left and right `BreakAlignment`s.

  For example, a `MultiMeasureRest` will ignore prefatory items at its bounds (i.e., clefs, key signatures and time signatures) using the following override:

```
\override MultiMeasureRest #'spacing-pair = #'(staff-bar . staff-bar)
```

`spanner-id` (string)
: An identifier to distinguish concurrent spanners.

`springs-and-rods` (boolean)
: Dummy variable for triggering spacing routines.

`stacking-dir` (direction)
: Stack objects in which direction?

`staff-affinity` (direction)
: The direction of the staff to use for spacing the current non-staff line. Choices are `UP`, `DOWN`, and `CENTER`. If `CENTER`, the non-staff line will be placed equidistant between the two nearest staves on either side, unless collisions or other spacing constraints prevent this. Setting `staff-affinity` for a staff causes it to be treated as a non-staff line. Setting `staff-affinity` to `#f` causes a non-staff line to be treated as a staff.

`staff-padding` (dimension, in staff space)
: Maintain this much space between reference points and the staff. Its effect is to align objects of differing sizes (like the dynamics **p** and **f**) on their baselines.

`staff-position` (number)
: Vertical position, measured in half staff spaces, counted from the middle line.

`staff-space` (dimension, in staff space)
: Amount of space between staff lines, expressed in global `staff-space`.

`staff-staff-spacing` (list)
: When applied to a staff-group's `StaffGrouper` grob, this spacing alist controls the distance between consecutive staves within the staff-group. When applied to a staff's `VerticalAxisGroup` grob, it controls the distance between the staff and the nearest staff below it in the same system, replacing any settings inherited from the `StaffGrouper` grob of the containing staff-group, if there is one. This property remains in effect even when non-staff lines appear between staves. The alist can contain the following keys:

  - `basic-distance` – the vertical distance, measured in staff-spaces, between the reference points of the two items when no collisions would result, and no stretching or compressing is in effect.
  - `minimum-distance` – the smallest allowable vertical distance, measured in staff-spaces, between the reference points of the two items, when compressing is in effect.
  - `padding` – the minimum required amount of unobstructed vertical whitespace between the bounding boxes (or skylines) of the two items, measured in staff-spaces.
  - `stretchability` – a unitless measure of the dimension's relative propensity to stretch. If zero, the distance will not stretch (unless collisions would result).

`staffgroup-staff-spacing` (list)
: The spacing alist controlling the distance between the last staff of the current staff-group and the staff just below it in the same system, even if one or more non-staff lines exist between the two staves. If the `staff-staff-spacing` property of the staff's `VerticalAxisGroup` grob is set, that is used instead. See `staff-staff-spacing` for a description of the alist structure.

`stem-attachment` (pair of numbers)
: An `(x . y)` pair where the stem attaches to the notehead.

`stem-end-position` (number)
: Where does the stem end (the end is opposite to the support-head)?

`stem-spacing-correction` (number)
: Optical correction amount for stems that are placed in tight configurations. For opposite directions, this amount is the correction for two normal sized stems that overlap completely.

`stemlet-length` (number)
: How long should be a stem over a rest?

`stencil` (stencil)
: The symbol to print.

`stencils` (list)
: Multiple stencils, used as intermediate value.

`strict-grace-spacing` (boolean)
: If set, main notes are spaced normally, then grace notes are put left of the musical columns for the main notes.

`strict-note-spacing` (boolean)
: If set, unbroken columns with non-musical material (clefs, bar lines, etc.) are not spaced separately, but put before musical columns.

`stroke-style` (string)
: Set to `"grace"` to turn stroke through flag on.

`style` (symbol)
: This setting determines in what style a grob is typeset. Valid choices depend on the `stencil` callback reading this property.

`text` (markup)
: Text markup. See Section "Formatting text" in *Notation Reference*.

`text-direction` (direction)
: This controls the ordering of the words. The default `RIGHT` is for roman text. Arabic or Hebrew should use `LEFT`.

`thick-thickness` (number)
: Bar line thickness, measured in `line-thickness`.

`thickness` (number)
: Line thickness, generally measured in `line-thickness`.

`thin-kern` (number)
: The space after a hair-line in a bar line.

`tie-configuration` (list)
: List of `(`*`position . dir`*`)` pairs, indicating the desired tie configuration, where *position* is the offset from the center of the staff in staff space and *dir* indicates the direction of the tie (`1`=>up, `-1`=>down, `0`=>center). A non-pair entry in the list causes the corresponding tie to be formatted automatically.

`to-barline` (boolean)
: If true, the spanner will stop at the bar line just before it would otherwise stop.

`toward-stem-shift` (number)
: Amount by which scripts are shifted toward the stem if their direction coincides with the stem direction. `0.0` means keep the default position (centered on the note head), `1.0` means centered on the stem. Interpolated values are possible.

`transparent` (boolean)
: This makes the grob invisible.

`uniform-stretching` (boolean)
: If set, items stretch proportionally to their durations. This looks better in complex polyphonic patterns.

`used` (boolean)
: If set, this spacing column is kept in the spacing problem.

`vertical-skylines` (pair of skylines)
: Two skylines, one above and one below this grob.

`when` (moment)
: Global time step associated with this column happen?

`whiteout` (boolean)
: If true, the grob is printed over a white background to white-out underlying material, if the grob is visible. Usually #f by default.

`width` (dimension, in staff space)
: The width of a grob measured in staff space.

`word-space` (dimension, in staff space)
: Space to insert between words in texts.

`X-extent` (pair of numbers)
: Hard coded extent in X direction.

`X-offset` (number)
: The horizontal amount that this object is moved relative to its X-parent.

`Y-extent` (pair of numbers)
: Hard coded extent in Y direction.

`Y-offset` (number)
: The vertical amount that this object is moved relative to its Y-parent.

`zigzag-length` (dimension, in staff space)
: The length of the lines of a zigzag, relative to `zigzag-width`. A value of `1` gives 60-degree zigzags.

`zigzag-width` (dimension, in staff space)
: The width of one zigzag squiggle. This number is adjusted slightly so that the glissando line can be constructed from a whole number of squiggles.

3.4 Internal backend properties

`accidental-grob` (graphical (layout) object)
: The accidental for this note.

`accidental-grobs` (list)
: An alist with `(`*`notename . groblist`*`)` entries.

`add-cauda` (boolean)
: Does this flexa require an additional cauda on the left side?

`add-join` (boolean)
: Is this ligature head-joined with the next one by a vertical line?

`add-stem` (boolean)
: Is this ligature head a virga and therefore needs an additional stem on the right side?

`adjacent-pure-heights` (pair)
: A pair of vectors. Used by a `VerticalAxisGroup` to cache the `Y-extent`s of different column ranges.

`adjacent-spanners` (array of grobs)
: An array of directly neighboring dynamic spanners.

`all-elements` (array of grobs)
: An array of all grobs in this line. Its function is to protect objects from being garbage collected.

`arpeggio` (graphical (layout) object)
: A pointer to an `Arpeggio` object.

`ascendens` (boolean)
: Is this neume of ascending type?

`auctum` (boolean)
: Is this neume liquescentically augmented?

`axis-group-parent-X` (graphical (layout) object)
: Containing X axis group.

`axis-group-parent-Y` (graphical (layout) object)
: Containing Y axis group.

`bar-extent` (pair of numbers)
: The Y-extent of the actual bar line. This may differ from `Y-extent` because it does not include the dots in a repeat bar line.

`bars` (array of grobs)
: An array of bar line pointers.

`beam` (graphical (layout) object)
: A pointer to the beam, if applicable.

`begin-of-line-visible` (boolean)
: Set to make `ChordName` or `FretBoard` be visible only at beginning of line or at chord changes.

`bounded-by-me` (array of grobs)
: An array of spanners that have this column as start/begin point. Only columns that have grobs or act as bounds are spaced.

`bracket` (graphical (layout) object)
: The bracket for a number.

`cause` (any type)
: Any kind of causation objects (i.e., music, or perhaps translator) that was the cause for this grob.

`cavum` (boolean)
: Is this neume outlined?

`columns` (array of grobs)
: An array of grobs, typically containing `PaperColumn` or `NoteColumn` objects.

`conditional-elements` (array of grobs)
: Internal use only.

`context-info` (integer)
: Within a ligature, the final glyph or shape of a head may be affected by the left and/or right neighbour head. `context-info` holds for each head such information about the left and right neighbour, encoded as a bit mask.

`covered-grobs` (array of grobs)
: Grobs that could potentially collide with a beam.

`cross-staff` (boolean)
: For a beam or a stem, this is true if we depend on inter-staff spacing.

`delta-position` (number)
: The vertical position difference.

`deminutum` (boolean)
: Is this neume deminished?

`descendens` (boolean)
: Is this neume of descendent type?

`direction-source` (graphical (layout) object)
: In case `side-relative-direction` is set, which grob to get the direction from.

`display-cautionary` (boolean)
: Should the grob be displayed as a cautionary grob?

`dot` (graphical (layout) object)
: A reference to a `Dots` object.

`dots` (array of grobs)
: Multiple `Dots` objects.

`elements` (array of grobs)
: An array of grobs; the type is depending on the grob where this is set in.

`encompass-objects` (array of grobs)
: Objects that a slur should avoid in addition to notes and stems.

`figures` (array of grobs)
: Figured bass objects for continuation line.

`flexa-height` (dimension, in staff space)
: The height of a flexa shape in a ligature grob (in `staff-space` units).

`flexa-interval` (integer)
: The interval spanned by the two notes of a flexa shape (1 is a second, 7 is an octave).

`flexa-width` (dimension, in staff space)
: The width of a flexa shape in a ligature grob in (in `staff-space` units).

`font` (font metric)
: A cached font metric object.

`forced` (boolean)
: Manually forced accidental.

`glissando-index` (integer)
: The index of a glissando in its note column.

`grace-spacing` (graphical (layout) object)
: A run of grace notes.

`head-width` (dimension, in staff space)
: The width of this ligature head.

`heads` (array of grobs)
: An array of note heads.

`ideal-distances` (list)
: (*obj* . (*dist* . *strength*)) pairs.

`important-column-ranks` (vector)
A cache of columns that contain `items-worth-living` data.

`inclinatum` (boolean)
Is this neume an inclinatum?

`interfaces` (list)
A list of symbols indicating the interfaces supported by this object. It is initialized from the `meta` field.

`items-worth-living` (array of grobs)
An array of interesting items. If empty in a particular staff, then that staff is erased.

`keep-alive-with` (array of grobs)
An array of other `VerticalAxisGroup`s. If any of them are alive, then we will stay alive.

`least-squares-dy` (number)
The ideal beam slope, without damping.

`left-items` (array of grobs)
DOCME

`left-neighbor` (graphical (layout) object)
The right-most column that has a spacing-wish for this column.

`ligature-flexa` (boolean)
request joining note to the previous one in a flexa.

`linea` (boolean)
Attach vertical lines to this neume?

`maybe-loose` (boolean)
Used to mark a breakable column that is loose if and only if it is in the middle of a line.

`meta` (list) Provide meta information. It is an alist with the entries `name` and `interfaces`.

`minimum-distances` (list)
A list of rods that have the format `(obj . dist)`.

`normal-stems` (array of grobs)
An array of visible stems.

`note-columns` (array of grobs)
An array of `NoteColumn` grobs.

`note-head` (graphical (layout) object)
A single note head.

`note-heads` (array of grobs)
An array of note head grobs.

`oriscus` (boolean)
Is this neume an oriscus?

`pedal-text` (graphical (layout) object)
A pointer to the text of a mixed-style piano pedal.

`pes-or-flexa` (boolean)
Shall this neume be joined with the previous head?

`positioning-done` (boolean)
: Used to signal that a positioning element did its job. This ensures that a positioning is only done once.

`prefix-set` (number)
: A bit mask that holds all Gregorian head prefixes, such as `\virga` or `\quilisma`.

`primitive` (integer)
: A pointer to a ligature primitive, i.e., an item similar to a note head that is part of a ligature.

`pure-relevant-grobs` (array of grobs)
: All the grobs (items and spanners) that are relevant for finding the `pure-Y-extent`

`pure-relevant-items` (array of grobs)
: A subset of elements that are relevant for finding the `pure-Y-extent`.

`pure-relevant-spanners` (array of grobs)
: A subset of elements that are relevant for finding the `pure-Y-extent`.

`pure-Y-common` (graphical (layout) object)
: A cache of the `common_refpoint_of_array` of the `elements` grob set.

`pure-Y-extent` (pair of numbers)
: The estimated height of a system.

`pure-Y-offset-in-progress` (boolean)
: A debugging aid for catching cyclic dependencies.

`quantize-position` (boolean)
: If set, a vertical alignment is aligned to be within staff spaces.

`quantized-positions` (pair of numbers)
: The beam positions after quanting.

`quilisma` (boolean)
: Is this neume a quilisma?

`rest` (graphical (layout) object)
: A pointer to a `Rest` object.

`rest-collision` (graphical (layout) object)
: A rest collision that a rest is in.

`rests` (array of grobs)
: An array of rest objects.

`right-items` (array of grobs)
: DOCME

`right-neighbor` (graphical (layout) object)
: See `left-neighbor`.

`script-stencil` (pair)
: A pair `(`*`type . arg`*`)` which acts as an index for looking up a `Stencil` object.

`shorten` (dimension, in staff space)
: The amount of space that a stem is shortened. Internally used to distribute beam shortening over stems.

`side-support-elements` (array of grobs)
: The side support, an array of grobs.

`slur` (graphical (layout) object)
: A pointer to a `Slur` object.

`spacing` (graphical (layout) object)
: The spacing spanner governing this section.

`spacing-wishes` (array of grobs)
: An array of note spacing or staff spacing objects.

`span-start` (boolean)
: Is the note head at the start of a spanner?

`spanner-placement` (direction)
: The place of an annotation on a spanner. LEFT is for the first spanner, and RIGHT is for the last. CENTER will place it on the broken spanner that falls closest to the center of the length of the entire spanner, although this behavior is unpredictable in situations with lots of rhythmic diversity. For predictable results, use LEFT and RIGHT.

`staff-grouper` (graphical (layout) object)
: The staff grouper we belong to.

`staff-symbol` (graphical (layout) object)
: The staff symbol grob that we are in.

`stem` (graphical (layout) object)
: A pointer to a `Stem` object.

`stem-info` (pair)
: A cache of stem parameters.

`stems` (array of grobs)
: An array of stem objects.

`stropha` (boolean)
: Is this neume a stropha?

`system-Y-offset` (number)
: The Y-offset (relative to the bottom of the top-margin of the page) of the system to which this staff belongs.

`tie` (graphical (layout) object)
: A pointer to a `Tie` object.

`tremolo-flag` (graphical (layout) object)
: The tremolo object on a stem.

`tuplet-number` (graphical (layout) object)
: The number for a bracket.

`tuplets` (array of grobs)
: An array of smaller tuplet brackets.

`use-breve-rest` (boolean)
: Use breve rests for measures longer than a whole rest.

`virga` (boolean)
: Is this neume a virga?

`X-common` (graphical (layout) object)
: Common reference point for axis group.

`x-offset` (dimension, in staff space)
: Extra horizontal offset for ligature heads.

`Y-common` (graphical (layout) object)
: See `X-common`.

4 Scheme functions

`ly:add-context-mod` *contextmods modification* [Function]
Adds the given context *modification* to the list *contextmods* of context modifications.

`ly:add-file-name-alist` *alist* [Function]
Add mappings for error messages from *alist*.

`ly:add-interface` *iface desc props* [Function]
Add a new grob interface. *iface* is the interface name, *desc* is the interface description, and *props* is the list of user-settable properties for the interface.

`ly:add-listener` *list disp cl* [Function]
Add the listener *list* to the dispatcher *disp*. Whenever *disp* hears an event of class *cl*, it is forwarded to *list*.

`ly:add-option` *sym val description* [Function]
Add a program option *sym*. *val* is the default value and *description* is a string description.

`ly:all-grob-interfaces` [Function]
Return the hash table with all grob interface descriptions.

`ly:all-options` [Function]
Get all option settings in an alist.

`ly:all-stencil-expressions` [Function]
Return all symbols recognized as stencil expressions.

`ly:assoc-get` *key alist default-value strict-checking* [Function]
Return value if *key* in *alist*, else *default-value* (or `#f` if not specified). If *strict-checking* is set to `#t` and *key* is not in *alist*, a programming_error is output.

`ly:axis-group-interface::add-element` *grob grob-element* [Function]
Set *grob* the parent of *grob-element* on all axes of *grob*.

`ly:beam-score-count` [Function]
count number of beam scores.

`ly:book-add-bookpart!` *book-smob book-part* [Function]
Add *book-part* to *book-smob* book part list.

`ly:book-add-score!` *book-smob score* [Function]
Add *score* to *book-smob* score list.

`ly:book-book-parts` *book* [Function]
Return book parts in *book*.

`ly:book-header` *book* [Function]
Return header in *book*.

`ly:book-paper` *book* [Function]
Return paper in *book*.

`ly:book-process` *book-smob default-paper default-layout output* [Function]
Print book. *output* is passed to the backend unchanged. For example, it may be a string (for file based outputs) or a socket (for network based output).

`ly:book-process-to-systems` *book-smob default-paper default-layout output* [Function]
Print book. *output* is passed to the backend unchanged. For example, it may be a string (for file based outputs) or a socket (for network based output).

`ly:book-scores` *book* [Function]
Return scores in *book*.

`ly:box?` *x* [Function]
Is *x* a `Box` object?

`ly:bp` *num* [Function]
num bigpoints (1/72th inch).

`ly:bracket` *a iv t p* [Function]
Make a bracket in direction *a*. The extent of the bracket is given by *iv*. The wings protrude by an amount of *p*, which may be negative. The thickness is given by *t*.

`ly:broadcast` *disp ev* [Function]
Send the stream event *ev* to the dispatcher *disp*.

`ly:camel-case->lisp-identifier` *name-sym* [Function]
Convert `FooBar_Bla` to `foo-bar-bla` style symbol.

`ly:chain-assoc-get` *key achain default-value strict-checking* [Function]
Return value for *key* from a list of alists *achain*. If no entry is found, return *default-value* or `#f` if *default-value* is not specified. With *strict-checking* set to `#t`, a programming_error is output in such cases.

`ly:cm` *num* [Function]
num cm.

`ly:command-line-code` [Function]
The Scheme code specified on command-line with '`-e`'.

`ly:command-line-options` [Function]
The Scheme options specified on command-line with '`-d`'.

`ly:command-line-verbose?` [Function]
Was `be_verbose_global` set?

`ly:connect-dispatchers` *to from* [Function]
Make the dispatcher *to* listen to events from *from*.

`ly:context?` *x* [Function]
Is *x* a `Context` object?

`ly:context-current-moment` *context* [Function]
Return the current moment of *context*.

`ly:context-event-source` *context* [Function]
Return `event-source` of context *context*.

`ly:context-events-below` *context* [Function]
Return a `stream-distributor` that distributes all events from *context* and all its subcontexts.

`ly:context-find` *context name* [Function]
Find a parent of *context* that has name or alias *name*. Return `#f` if not found.

`ly:context-grob-definition` *context name* [Function]
Return the definition of *name* (a symbol) within *context* as an alist.

`ly:context-id` *context* [Function]
Return the ID string of *context*, i.e., for `\context Voice = "one" ...` return the string `one`.

`ly:context-name` *context* [Function]
Return the name of *context*, i.e., for `\context Voice = "one" ...` return the symbol `Voice`.

`ly:context-now` *context* [Function]
Return `now-moment` of context *context*.

`ly:context-parent` *context* [Function]
Return the parent of *context*, `#f` if none.

`ly:context-property` *context sym def* [Function]
Return the value for property *sym* in *context*. If *def* is given, and property value is `'()`, return *def*.

`ly:context-property-where-defined` *context name* [Function]
Return the context above *context* where *name* is defined.

`ly:context-pushpop-property` *context grob eltprop val* [Function]
Do a single `\override` or `\revert` operation in *context*. The grob definition *grob* is extended with *eltprop* (if *val* is specified) or reverted (if unspecified).

`ly:context-set-property!` *context name val* [Function]
Set value of property *name* in context *context* to *val*.

`ly:context-unset-property` *context name* [Function]
Unset value of property *name* in context *context*.

`ly:default-scale` [Function]
Get the global default scale.

`ly:dimension?` *d* [Function]
Return *d* as a number. Used to distinguish length variables from normal numbers.

`ly:dir?` *s* [Function]
Is *s* a direction? Valid directions are `-1`, `0`, or `1`, where `-1` represents left or down, `1` represents right or up, and `0` represents a neutral direction.

`ly:dispatcher?` *x* [Function]
Is *x* a `Dispatcher` object?

`ly:duration?` *x* [Function]
Is *x* a `Duration` object?

`ly:duration<?` *p1 p2* [Function]
Is *p1* shorter than *p2*?

`ly:duration->string` *dur* [Function]
Convert *dur* to a string.

`ly:duration-dot-count` *dur* [Function]
Extract the dot count from *dur*.

`ly:duration-factor` *dur* [Function]
Extract the compression factor from *dur*. Return it as a pair.

`ly:duration-length` *dur* [Function]
The length of the duration as a `moment`.

`ly:duration-log` *dur* [Function]
Extract the duration log from *dur*.

`ly:effective-prefix` [Function]
Return effective prefix.

`ly:encode-string-for-pdf` *str* [Function]
Encode the given string to either Latin1 (which is a subset of the PDFDocEncoding) or if that's not possible to full UTF-16BE with Byte-Order-Mark (BOM).

`ly:engraver-announce-end-grob` *engraver grob cause* [Function]
Announce the end of a grob (i.e., the end of a spanner) originating from given *engraver* instance, with *grob* being a grob. *cause* should either be another grob or a music event.

`ly:engraver-make-grob` *engraver grob-name cause* [Function]
Create a grob originating from given *engraver* instance, with given *grob-name*, a symbol. *cause* should either be another grob or a music event.

`ly:error` *str rest* [Function]
A Scheme callable function to issue the error *str*. The error is formatted with `format` and *rest*.

`ly:eval-simple-closure` *delayed closure scm-start scm-end* [Function]
Evaluate a simple *closure* with the given *delayed* argument. If *scm-start* and *scm-end* are defined, evaluate it purely with those start and end points.

`ly:event-deep-copy` *m* [Function]
Copy *m* and all sub expressions of *m*.

`ly:event-property` *sev sym* [Function]
Get the property *sym* of stream event *mus*. If *sym* is undefined, return `'()`.

`ly:event-set-property!` *ev sym val* [Function]
Set property *sym* in event *ev* to *val*.

`ly:expand-environment` *str* [Function]
Expand `$VAR` and `${VAR}` in *str*.

`ly:export` *arg* [Function]
Export a Scheme object to the parser so it is treated as an identifier.

`ly:find-file` *name* [Function]
Return the absolute file name of *name*, or `#f` if not found.

`ly:font-config-add-directory` *dir* [Function]
Add directory *dir* to FontConfig.

`ly:font-config-add-font` *font* [Function]
Add font *font* to FontConfig.

`ly:font-config-display-fonts` [Function]
Dump a list of all fonts visible to FontConfig.

`ly:font-config-get-font-file` *name* [Function]
Get the file for font *name*.

`ly:font-design-size` *font* [Function]
Given the font metric *font*, return the design size, relative to the current output-scale.

`ly:font-file-name` *font* [Function]
Given the font metric *font*, return the corresponding file name.

`ly:font-get-glyph` *font name* [Function]
Return a stencil from *font* for the glyph named *name*. If the glyph is not available, return an empty stencil.

Note that this command can only be used to access glyphs from fonts loaded with `ly:system-font-load`; currently, this means either the Emmentaler or Emmentaler-Brace fonts, corresponding to the font encodings `fetaMusic` and `fetaBraces`, respectively.

`ly:font-glyph-name-to-charcode` *font name* [Function]
Return the character code for glyph *name* in *font*.

Note that this command can only be used to access glyphs from fonts loaded with `ly:system-font-load`; currently, this means either the Emmentaler or Emmentaler-Brace fonts, corresponding to the font encodings `fetaMusic` and `fetaBraces`, respectively.

`ly:font-glyph-name-to-index` *font name* [Function]
Return the index for *name* in *font*.

Note that this command can only be used to access glyphs from fonts loaded with `ly:system-font-load`; currently, this means either the Emmentaler or Emmentaler-Brace fonts, corresponding to the font encodings `fetaMusic` and `fetaBraces`, respectively.

`ly:font-index-to-charcode` *font index* [Function]
Return the character code for *index* in *font*.

Note that this command can only be used to access glyphs from fonts loaded with `ly:system-font-load`; currently, this means either the Emmentaler or Emmentaler-Brace fonts, corresponding to the font encodings `fetaMusic` and `fetaBraces`, respectively.

`ly:font-magnification` *font* [Function]
Given the font metric *font*, return the magnification, relative to the current output-scale.

`ly:font-metric?` *x* [Function]
Is *x* a `Font_metric` object?

`ly:font-name` *font* [Function]
Given the font metric *font*, return the corresponding name.

`ly:font-sub-fonts` *font* [Function]
Given the font metric *font* of an OpenType font, return the names of the subfonts within *font*.

`ly:format` *str rest* [Function]
LilyPond specific format, supporting `~a` and `~[0-9]f`. Basic support for `~s` is also provided.

`ly:format-output` *context* [Function]
Given a global context in its final state, process it and return the `Music_output` object in its final state.

`ly:get-all-function-documentation` [Function]
Get a hash table with all LilyPond Scheme extension functions.

`ly:get-all-translators` [Function]
Return a list of all translator objects that may be instantiated.

`ly:get-context-mods` *contextmod* [Function]
Returns the list of context modifications stored in *contextmod*.

`ly:get-listened-event-classes` [Function]
Return a list of all event classes that some translator listens to.

`ly:get-option` *var* [Function]
Get a global option setting.

`ly:gettext` *original* [Function]
A Scheme wrapper function for `gettext`.

`ly:grob?` *x* [Function]
Is *x* a `Grob` object?

`ly:grob-alist-chain` *grob global* [Function]
Get an alist chain for grob *grob*, with *global* as the global default. If unspecified, `font-defaults` from the layout block is taken.

`ly:grob-array?` *x* [Function]
Is *x* a `Grob_array` object?

`ly:grob-array->list` *grob-arr* [Function]
Return the elements of *grob-arr* as a Scheme list.

`ly:grob-array-length` *grob-arr* [Function]
Return the length of *grob-arr*.

`ly:grob-array-ref` *grob-arr index* [Function]
Retrieve the *index*th element of *grob-arr*.

`ly:grob-basic-properties` *grob* [Function]
Get the immutable properties of *grob*.

`ly:grob-chain-callback` *grob proc sym* [Function]
Find the callback that is stored as property *sym* of grob *grob* and chain *proc* to the head of this, meaning that it is called using *grob* and the previous callback's result.

`ly:grob-common-refpoint` *grob other axis* [Function]
Find the common refpoint of *grob* and *other* for *axis*.

`ly:grob-common-refpoint-of-array` *grob others axis* [Function]
Find the common refpoint of *grob* and *others* (a grob-array) for *axis*.

`ly:grob-default-font` *grob* [Function]
Return the default font for grob *grob*.

`ly:grob-extent` *grob refp axis* [Function]
Get the extent in *axis* direction of *grob* relative to the grob *refp*.

`ly:grob-interfaces` *grob* [Function]
Return the interfaces list of grob *grob*.

`ly:grob-layout` *grob* [Function]
Get `\layout` definition from grob *grob*.

`ly:grob-object` *grob sym* [Function]
Return the value of a pointer in grob *grob* of property *sym*. It returns `'()` (end-of-list) if *sym* is undefined in *grob*.

`ly:grob-original` *grob* [Function]
Return the unbroken original grob of *grob*.

`ly:grob-parent` *grob axis* [Function]
Get the parent of *grob*. *axis* is 0 for the X-axis, 1 for the Y-axis.

`ly:grob-pq<?` *a b* [Function]
Compare two grob priority queue entries. This is an internal function.

`ly:grob-properties` *grob* [Function]
Get the mutable properties of *grob*.

`ly:grob-property` *grob sym val* [Function]
Return the value for property *sym* of *grob*. If no value is found, return *val* or `'()` if *val* is not specified.

`ly:grob-property-data` *grob sym* [Function]
Return the value for property *sym* of *grob*, but do not process callbacks.

`ly:grob-relative-coordinate` *grob refp axis* [Function]
Get the coordinate in *axis* direction of *grob* relative to the grob *refp*.

`ly:grob-robust-relative-extent` *grob refp axis* [Function]
Get the extent in *axis* direction of *grob* relative to the grob *refp*, or `(0,0)` if empty.

`ly:grob-script-priority-less` *a b* [Function]
Compare two grobs by script priority. For internal use.

`ly:grob-set-nested-property!` *grob symlist val* [Function]
Set nested property *symlist* in grob *grob* to value *val*.

`ly:grob-set-object!` *grob sym val* [Function]
Set *sym* in grob *grob* to value *val*.

`ly:grob-set-parent!` *grob axis parent-grob* [Function]
Set *parent-grob* the parent of grob *grob* in axis *axis*.

`ly:grob-set-property!` *grob sym val* [Function]
Set *sym* in grob *grob* to value *val*.

`ly:grob-staff-position` *sg* [Function]
Return the Y-position of *sg* relative to the staff.

`ly:grob-suicide!` *grob* [Function]
Kill *grob*.

`ly:grob-system` *grob* [Function]
Return the system grob of *grob*.

`ly:grob-translate-axis!` *grob d a* [Function]
Translate *grob* on axis *a* over distance *d*.

`ly:gulp-file` *name size* [Function]
Read *size* characters from the file *name*, and return its contents in a string. If *size* is undefined, the entire file is read. The file is looked up using the search path.

`ly:hash-table-keys` *tab* [Function]
Return a list of keys in *tab*.

`ly:inch` *num* [Function]
num inches.

`ly:input-both-locations` *sip* [Function]
Return input location in *sip* as `(file-name first-line first-column last-line last-column)`.

`ly:input-file-line-char-column` *sip* [Function]
Return input location in *sip* as `(file-name line char column)`.

`ly:input-location?` *x* [Function]
Is *x* an `input-location`?

`ly:input-message` *sip msg rest* [Function]
Print *msg* as a GNU compliant error message, pointing to the location in *sip*. *msg* is interpreted similar to `format`'s argument, using *rest*.

`ly:interpret-music-expression` *mus ctx* [Function]
Interpret the music expression *mus* in the global context *ctx*. The context is returned in its final state.

`ly:interpret-stencil-expression` *expr func arg1 offset* [Function]
Parse *expr*, feed bits to *func* with first arg *arg1* having offset *offset*.

`ly:intlog2` *d* [Function]
The 2-logarithm of $1/d$.

`ly:is-listened-event-class` *sym* [Function]
Is *sym* a listened event class?

`ly:item?` *g* [Function]
Is *g* an `Item` object?

`ly:item-break-dir` *it* [Function]
The break status direction of item *it*. `-1` means end of line, `0` unbroken, and `1` beginning of line.

`ly:iterator?` *x* [Function]
Is *x* a `Music_iterator` object?

`ly:lexer-keywords` *lexer* [Function]
Return a list of `(KEY . CODE)` pairs, signifying the LilyPond reserved words list.

`ly:lily-lexer?` *x* [Function]
Is *x* a `Lily_lexer` object?

`ly:lily-parser?` *x* [Function]
Is *x* a `Lily_parser` object?

`ly:listener?` *x* [Function]
Is *x* a `Listener` object?

`ly:make-book` *paper header scores* [Function]
Make a `\book` of *paper* and *header* (which may be `#f` as well) containing `\scores`.

`ly:make-book-part` *scores* [Function]
Make a `\bookpart` containing `\scores`.

`ly:make-dispatcher` [Function]
Return a newly created dispatcher.

`ly:make-duration` *length dotcount num den* [Function]
length is the negative logarithm (base 2) of the duration: 1 is a half note, 2 is a quarter note, 3 is an eighth note, etc. The number of dots after the note is given by the optional argument *dotcount*.

The duration factor is optionally given by *num* and *den*.

A duration is a musical duration, i.e., a length of time described by a power of two (whole, half, quarter, etc.) and a number of augmentation dots.

`ly:make-global-context` *output-def* [Function]
Set up a global interpretation context, using the output block *output-def*. The context is returned.

`ly:make-global-translator` *global* [Function]
Create a translator group and connect it to the global context *global*. The translator group is returned.

`ly:make-listener` *callback* [Function]
Create a listener. Any time the listener hears an object, it will call *callback* with that object.
callback should take exactly one argument.

`ly:make-moment` *n d gn gd* [Function]
Create the rational number with main timing n/d, and optional grace timing gn/gd.

A *moment* is a point in musical time. It consists of a pair of rationals (m, g), where m is the timing for the main notes, and g the timing for grace notes. In absence of grace notes, g is zero.

`ly:make-music` *props* [Function]
Make a C++ `Music` object and initialize it with *props*.

This function is for internal use and is only called by `make-music`, which is the preferred interface for creating music objects.

`ly:make-music-function` *signature func* [Function]
Make a function to process music, to be used for the parser. *func* is the function, and *signature* describes its arguments. *signature* is a list containing either `ly:music?` predicates or other type predicates.

`ly:make-output-def` [Function]
Make an output definition.

`ly:make-page-label-marker` *label* [Function]
Return page marker with label *label*.

`ly:make-page-permission-marker` *symbol permission* [Function]
Return page marker with page breaking and turning permissions.

`ly:make-pango-description-string` *chain size* [Function]
Make a `PangoFontDescription` string for the property alist *chain* at size *size*.

`ly:make-paper-outputter` *port format* [Function]
Create an outputter that evaluates within `output-`*format*, writing to *port*.

`ly:make-pitch` *octave note alter* [Function]
octave is specified by an integer, zero for the octave containing middle C. *note* is a number indexing the global default scale, with 0 corresponding to pitch C and 6 usually corresponding to pitch B. *alter* is a rational number of 200-cent whole tones for alteration.

`ly:make-prob` *type init rest* [Function]
Create a `Prob` object.

`ly:make-scale` *steps* [Function]
Create a scale. The argument is a vector of rational numbers, each of which represents the number of 200 cent tones of a pitch above the tonic.

`ly:make-score` *music* [Function]
Return score with *music* encapsulated in it.

`ly:make-simple-closure` *expr* [Function]
Make a simple closure. *expr* should be form of `(func a1 a2 ...)`, and will be invoked as `(func delayed-arg a1 a2 ...)`.

`ly:make-stencil` *expr xext yext* [Function]
Stencils are device independent output expressions. They carry two pieces of information:

1. A specification of how to print this object. This specification is processed by the output backends, for example '`scm/output-ps.scm`'.
2. The vertical and horizontal extents of the object, given as pairs. If an extent is unspecified (or if you use `(1000 . -1000)` as its value), it is taken to be empty.

`ly:make-stream-event` *cl proplist* [Function]
Create a stream event of class *cl* with the given mutable property list.

`ly:message` *str rest* [Function]
A Scheme callable function to issue the message *str*. The message is formatted with `format` and *rest*.

`ly:minimal-breaking` *pb* [Function]
Break (pages and lines) the `Paper_book` object *pb* without looking for optimal spacing: stack as many lines on a page before moving to the next one.

`ly:mm` *num* [Function]
num mm.

`ly:module->alist` *mod* [Function]
Dump the contents of module *mod* as an alist.

`ly:module-copy` *dest src* [Function]
Copy all bindings from module *src* into *dest*.

`ly:modules-lookup` *modules sym def* [Function]
Look up *sym* in the list *modules*, returning the first occurence. If not found, return *def* or `#f` if *def* isn't specified.

`ly:moment?` *x* [Function]
Is *x* a `Moment` object?

`ly:moment<?` *a b* [Function]
Compare two moments.

`ly:moment-add` *a b* [Function]
Add two moments.

`ly:moment-div` *a b* [Function]
Divide two moments.

`ly:moment-grace-denominator` *mom* [Function]
Extract denominator from grace timing.

`ly:moment-grace-numerator` *mom* [Function]
Extract numerator from grace timing.

`ly:moment-main-denominator` *mom* [Function]
Extract denominator from main timing.

`ly:moment-main-numerator` *mom* [Function]
Extract numerator from main timing.

`ly:moment-mod` *a b* [Function]
Modulo of two moments.

`ly:moment-mul` *a b* [Function]
Multiply two moments.

`ly:moment-sub` *a b* [Function]
Subtract two moments.

`ly:music?` *obj* [Function]
Is *obj* a music object?

`ly:music-compress` *m factor* [Function]
Compress music object *m* by moment *factor*.

`ly:music-deep-copy` *m* [Function]
Copy *m* and all sub expressions of *m*.

`ly:music-duration-compress` *mus fact* [Function]
Compress *mus* by factor *fact*, which is a `Moment`.

`ly:music-duration-length` *mus* [Function]
Extract the duration field from *mus* and return the length.

`ly:music-function?` *x* [Function]
Is *x* a `music-function`?

`ly:music-function-extract` *x* [Function]
Return the Scheme function inside *x*.

`ly:music-length` *mus* [Function]
Get the length of music expression *mus* and return it as a `Moment` object.

`ly:music-list?` *lst* [Function]
Is *lst* a list of music objects?

`ly:music-mutable-properties` *mus* [Function]
Return an alist containing the mutable properties of *mus*. The immutable properties are not available, since they are constant and initialized by the `make-music` function.

`ly:music-output?` *x* [Function]
Is *x* a `Music_output` object?

`ly:music-property` *mus sym val* [Function]
Return the value for property *sym* of music expression *mus*. If no value is found, return *val* or `'()` if *val* is not specified.

`ly:music-set-property!` *mus sym val* [Function]
Set property *sym* in music expression *mus* to *val*.

`ly:music-transpose` *m p* [Function]
Transpose *m* such that central C is mapped to *p*. Return *m*.

`ly:note-column-accidentals` *note-column* [Function]
Return the `AccidentalPlacement` grob from *note-column* if any, or `SCM_EOL` otherwise.

`ly:note-column-dot-column` *note-column* [Function]
Return the `DotColumn` grob from *note-column* if any, or `SCM_EOL` otherwise.

`ly:note-head::stem-attachment` *font-metric glyph-name* [Function]
Get attachment in *font-metric* for attaching a stem to notehead *glyph-name*.

`ly:number->string` *s* [Function]
Convert *s* to a string without generating many decimals.

`ly:optimal-breaking` *pb* [Function]
Optimally break (pages and lines) the `Paper_book` object *pb* to minimize badness in bother vertical and horizontal spacing.

`ly:option-usage` [Function]
Print `ly:set-option` usage.

`ly:otf->cff` *otf-file-name* [Function]
Convert the contents of an OTF file to a CFF file, returning it as a string.

`ly:otf-font?` *font* [Function]
Is *font* an OpenType font?

`ly:otf-font-glyph-info` *font glyph* [Function]
Given the font metric *font* of an OpenType font, return the information about named glyph *glyph* (a string).

`ly:otf-font-table-data` *font tag* [Function]
Extract a table *tag* from *font*. Return empty string for non-existent *tag*.

`ly:otf-glyph-count` *font* [Function]
Return the number of glyphs in *font*.

`ly:otf-glyph-list` *font* [Function]
Return a list of glyph names for *font*.

`ly:output-def?` *def* [Function]
Is *def* an output definition?

`ly:output-def-clone` *def* [Function]
Clone output definition *def*.

`ly:output-def-lookup` *def sym val* [Function]
Return the value of *sym* in output definition *def* (e.g., `\paper`). If no value is found, return *val* or `'()` if *val* is undefined.

`ly:output-def-parent` *def* [Function]
Return the parent output definition of *def*.

`ly:output-def-scope` *def* [Function]
Return the variable scope inside *def*.

`ly:output-def-set-variable!` *def sym val* [Function]
Set an output definition *def* variable *sym* to *val*.

`ly:output-description` *output-def* [Function]
Return the description of translators in *output-def*.

`ly:output-formats` [Function]
Formats passed to '`--format`' as a list of strings, used for the output.

`ly:outputter-close` *outputter* [Function]
Close port of *outputter*.

`ly:outputter-dump-stencil` *outputter stencil* [Function]
Dump stencil *expr* onto *outputter*.

`ly:outputter-dump-string` *outputter str* [Function]
Dump *str* onto *outputter*.

`ly:outputter-module` *outputter* [Function]
Return output module of *outputter*.

`ly:outputter-output-scheme` *outputter expr* [Function]
Eval *expr* in module of *outputter*.

`ly:outputter-port` *outputter* [Function]
Return output port for *outputter*.

`ly:page-marker?` *x* [Function]
Is *x* a `Page_marker` object?

`ly:page-turn-breaking` *pb* [Function]
Optimally break (pages and lines) the `Paper_book` object *pb* such that page turns only happen in specified places, returning its pages.

`ly:pango-font?` *f* [Function]
Is *f* a pango font?

`ly:pango-font-physical-fonts` *f* [Function]
Return alist of `(ps-name file-name font-index)` lists for Pango font *f*.

`ly:paper-book?` *x* [Function]
Is *x* a `Paper_book` object?

`ly:paper-book-header` *pb* [Function]
Return the header definition (`\header`) in `Paper_book` object *pb*.

`ly:paper-book-pages` *pb* [Function]
Return pages in `Paper_book` object *pb*.

`ly:paper-book-paper` *pb* [Function]
Return the paper output definition (`\paper`) in `Paper_book` object *pb*.

`ly:paper-book-performances` *pb* [Function]
Return performances in `Paper_book` object *pb*.

`ly:paper-book-scopes` *pb* [Function]
Return scopes in `Paper_book` object *pb*.

`ly:paper-book-systems` *pb* [Function]
Return systems in `Paper_book` object *pb*.

`ly:paper-fonts` *def* [Function]
Return a list containing the fonts from output definition *def* (e.g., `\paper`).

`ly:paper-get-font` *def chain* [Function]
Find a font metric in output definition *def* satisfying the font-qualifiers in alist chain *chain*, and return it. (An alist chain is a list of alists, containing grob properties.)

`ly:paper-get-number` *def sym* [Function]
Return the value of variable *sym* in output definition *def* as a double.

`ly:paper-outputscale` *def* [Function]
Return the output-scale for output definition *def*.

`ly:paper-score-paper-systems` *paper-score* [Function]
Return vector of `paper_system` objects from *paper-score*.

`ly:paper-system?` *obj* [Function]
Is *obj* a C++ `Prob` object of type `paper-system`?

`ly:paper-system-minimum-distance` *sys1 sys2* [Function]
Measure the minimum distance between these two paper-systems, using their stored skylines if possible and falling back to their extents otherwise.

`ly:parse-file` *name* [Function]
Parse a single `.ly` file. Upon failure, throw `ly-file-failed` key.

`ly:parser-clear-error` *parser* [Function]
Clear the error flag for the parser.

`ly:parser-clone` *parser-smob* [Function]
Return a clone of *parser-smob*.

`ly:parser-define!` *parser-smob symbol val* [Function]
Bind *symbol* to *val* in *parser-smob*'s module.

`ly:parser-error` *parser msg input* [Function]
Display an error message and make the parser fail.

`ly:parser-has-error?` *parser* [Function]
Does *parser* have an error flag?

`ly:parser-include-string` *parser-smob ly-code* [Function]
Include the string *ly-code* into the input stream for *parser-smob*.

`ly:parser-lexer` *parser-smob* [Function]
Return the lexer for *parser-smob*.

`ly:parser-lookup` *parser-smob symbol* [Function]
Look up *symbol* in *parser-smob*'s module. Return `'()` if not defined.

`ly:parser-output-name` *parser* [Function]
Return the base name of the output file.

`ly:parser-parse-string` *parser-smob ly-code* [Function]
Parse the string *ly-code* with *parser-smob*. Upon failure, throw `ly-file-failed` key.

`ly:parser-set-note-names` *parser names* [Function]
Replace current note names in *parser*. *names* is an alist of symbols. This only has effect if the current mode is notes.

`ly:parser-set-repetition-function` *parser fun* [Function]
Replace the current repetition function in *parser*. *fun* is the new repetition function.

`ly:parser-set-repetition-symbol` *parser sym* [Function]
Replace the current repetition symbol in *parser*. *sym* is the new repetition symbol.

`ly:performance-write` *performance filename* [Function]
Write *performance* to *filename*.

`ly:pfb->pfa` *pfb-file-name* [Function]
Convert the contents of a Type 1 font in PFB format to PFA format.

`ly:pitch?` *x* [Function]
Is *x* a `Pitch` object?

`ly:pitch<?` *p1 p2* [Function]
Is *p1* lexicographically smaller than *p2*?

`ly:pitch-alteration` *pp* [Function]
Extract the alteration from pitch *pp*.

`ly:pitch-diff` *pitch root* [Function]
Return pitch *delta* such that *pitch* transposed by *delta* equals *root*.

`ly:pitch-negate` *p* [Function]
Negate *p*.

`ly:pitch-notename` *pp* [Function]
Extract the note name from pitch *pp*.

`ly:pitch-octave` *pp* [Function]
Extract the octave from pitch *pp*.

`ly:pitch-quartertones` *pp* [Function]
Calculate the number of quarter tones of *pp* from middle C.

`ly:pitch-semitones` *pp* [Function]
Calculate the number of semitones of *pp* from middle C.

`ly:pitch-steps` *p* [Function]
Number of steps counted from middle C of the pitch *p*.

`ly:pitch-transpose` *p delta* [Function]
Transpose *p* by the amount *delta*, where *delta* is relative to middle C.

`ly:pointer-group-interface::add-grob` *grob sym grob-element* [Function]
Add *grob-element* to *grob*'s *sym* grob array.

`ly:position-on-line?` *sg spos* [Function]
Return whether *spos* is on a line of the staff associated with the grob *sg* (even on an extender line).

`ly:prob?` *x* [Function]
Is *x* a `Prob` object?

`ly:prob-immutable-properties` *prob* [Function]
Retrieve an alist of immutable properties.

`ly:prob-mutable-properties` *prob* [Function]
Retrieve an alist of mutable properties.

`ly:prob-property` *prob sym val* [Function]
Return the value for property *sym* of Prob object *prob*. If no value is found, return *val* or `'()` if *val* is not specified.

`ly:prob-property?` *obj sym* [Function]
Is boolean prop *sym* of *sym* set?

`ly:prob-set-property!` *obj sym value* [Function]
Set property *sym* of *obj* to *value*.

`ly:prob-type?` *obj type* [Function]
Is *obj* the specified prob-type?

`ly:programming-error` *str rest* [Function]
A Scheme callable function to issue the internal warning *str*. The message is formatted with `format` and *rest*.

`ly:progress` *str rest* [Function]
A Scheme callable function to print progress *str*. The message is formatted with `format` and *rest*.

`ly:property-lookup-stats` *sym* [Function]
Return hash table with a property access corresponding to *sym*. Choices are `prob`, `grob`, and `context`.

`ly:protects` [Function]
Return hash of protected objects.

`ly:pt` *num* [Function]
num printer points.

`ly:register-stencil-expression` *symbol* [Function]
Add *symbol* as head of a stencil expression.

`ly:relative-group-extent` *elements common axis* [Function]
Determine the extent of *elements* relative to *common* in the *axis* direction.

`ly:reset-all-fonts` [Function]
Forget all about previously loaded fonts.

`ly:round-filled-box` *xext yext blot* [Function]
Make a `Stencil` object that prints a black box of dimensions *xext*, *yext* and roundness *blot*.

`ly:round-filled-polygon` *points blot* [Function]
Make a `Stencil` object that prints a black polygon with corners at the points defined by *points* (list of coordinate pairs) and roundness *blot*.

`ly:run-translator` *mus output-def* [Function]
Process *mus* according to *output-def*. An interpretation context is set up, and *mus* is interpreted with it. The context is returned in its final state.

Optionally, this routine takes an object-key to to uniquely identify the score block containing it.

`ly:score?` *x* [Function]
Is *x* a `Score` object?

`ly:score-add-output-def!` *score def* [Function]
Add an output definition *def* to *score*.

`ly:score-embedded-format` *score layout* [Function]
Run *score* through *layout* (an output definition) scaled to correct output-scale already, returning a list of layout-lines.

`ly:score-error?` *score* [Function]
Was there an error in the score?

`ly:score-header` *score* [Function]
Return score header.

`ly:score-music` *score* [Function]
Return score music.

`ly:score-output-defs` *score* [Function]
All output definitions in a score.

`ly:score-set-header!` *score module* [Function]
Set the score header.

`ly:set-default-scale` *scale* [Function]
Set the global default scale. This determines the tuning of pitches with no accidentals or key signatures. The first pitch is C. Alterations are calculated relative to this scale. The number of pitches in this scale determines the number of scale steps that make up an octave. Usually the 7-note major scale.

`ly:set-grob-creation-callback` *cb* [Function]
Specify a procedure that will be called every time a new grob is created. The callback will receive as arguments the grob that was created, the name of the C++ source file that caused the grob to be created, and the corresponding line number in the C++ source file.

`ly:set-grob-modification-callback` *cb* [Function]
Specify a procedure that will be called every time LilyPond modifies a grob property. The callback will receive as arguments the grob that is being modified, the name of the C++ file in which the modification was requested, the line number in the C++ file in which the modification was requested, the name of the function in which the modification was requested, the property to be changed, and the new value for the property.

`ly:set-middle-C!` *context* [Function]
Set the `middleCPosition` variable in *context* based on the variables `middleCClefPosition` and middleCOffset.

`ly:set-option` *var val* [Function]
Set a program option.

`ly:set-property-cache-callback` *cb* [Function]
Specify a procedure that will be called whenever lilypond calculates a callback function and caches the result. The callback will receive as arguments the grob whose property it is, the name of the property, the name of the callback that calculated the property, and the new (cached) value of the property.

`ly:simple-closure?` *clos* [Function]
Is *clos* a simple closure?

`ly:skyline?` *x* [Function]
Is *x* a `Skyline` object?

`ly:skyline-pair?` *x* [Function]
Is *x* a `Skyline_pair` object?

`ly:slur-score-count` [Function]
count number of slur scores.

`ly:smob-protects` [Function]
Return LilyPond's internal smob protection list.

`ly:solve-spring-rod-problem` *springs rods length ragged* [Function]
Solve a spring and rod problem for *count* objects, that are connected by *count*-1 *springs*, and an arbitrary number of *rods*. *count* is implicitly given by *springs* and *rods*. The *springs* argument has the format `(ideal, inverse_hook)` and *rods* is of the form `(idx1, idx2, distance)`.

length is a number, *ragged* a boolean.

The function returns a list containing the force (positive for stretching, negative for compressing and `#f` for non-satisfied constraints) followed by *spring-count*+1 positions of the objects.

`ly:source-file?` *x* [Function]
Is *x* a `Source_file` object?

`ly:spanner?` *g* [Function]
Is *g* a spanner object?

`ly:spanner-bound` *spanner dir* [Function]
Get one of the bounds of *spanner*. *dir* is `-1` for left, and `1` for right.

`ly:spanner-broken-into` *spanner* [Function]
Return broken-into list for *spanner*.

`ly:spanner-set-bound!` *spanner dir item* [Function]
Set grob *item* as bound in direction *dir* for *spanner*.

`ly:spawn` *command rest* [Function]
Simple interface to g_spawn_sync *str*. The error is formatted with `format` and *rest*.

`ly:staff-symbol-line-thickness` *grob* [Function]
Returns the `line-thickness` of the staff associated with *grob*.

`ly:staff-symbol-staff-space` *grob* [Function]
Returns the `staff-space` of the staff associated with *grob*.

`ly:start-environment` [Function]
Return the environment (a list of strings) that was in effect at program start.

`ly:stderr-redirect` *file-name mode* [Function]
Redirect stderr to *file-name*, opened with *mode*.

`ly:stencil?` *x* [Function]
Is *x* a `Stencil` object?

`ly:stencil-add` *args* [Function]
Combine stencils. Takes any number of arguments.

`ly:stencil-aligned-to` *stil axis dir* [Function]
Align *stil* using its own extents. *dir* is a number. `-1` and `1` are left and right, respectively. Other values are interpolated (so `0` means the center).

`ly:stencil-combine-at-edge` *first axis direction second padding minimum* [Function]
Construct a stencil by putting *second* next to *first*. *axis* can be 0 (x-axis) or 1 (y-axis). *direction* can be -1 (left or down) or 1 (right or up). The stencils are juxtaposed with *padding* as extra space. If this puts the reference points closer than *minimum*, they are moved by the latter amount. *first* and *second* may also be `'()` or `#f`.

`ly:stencil-empty?` *stil* [Function]
Return whether *stil* is empty.

`ly:stencil-expr` *stil* [Function]
Return the expression of *stil*.

`ly:stencil-extent` *stil axis* [Function]
Return a pair of numbers signifying the extent of *stil* in *axis* direction (`0` or `1` for x and y axis, respectively).

`ly:stencil-fonts` *s* [Function]
Analyze *s*, and return a list of fonts used in *s*.

`ly:stencil-in-color` *stc r g b* [Function]
Put *stc* in a different color.

`ly:stencil-rotate` *stil angle x y* [Function]
Return a stencil *stil* rotated *angle* degrees around the relative offset (*x*, *y*). E.g. an offset of (-1, 1) will rotate the stencil around the left upper corner.

`ly:stencil-rotate-absolute` *stil angle x y* [Function]
Return a stencil *stil* rotated *angle* degrees around point (*x*, *y*), given in absolute coordinates.

`ly:stencil-scale` *stil x y* [Function]
Scale *stil* using the horizontal and vertical scaling factors *x* and *y*.

`ly:stencil-translate` *stil offset* [Function]
Return a *stil*, but translated by *offset* (a pair of numbers).

`ly:stencil-translate-axis` *stil amount axis* [Function]
Return a copy of *stil* but translated by *amount* in *axis* direction.

`ly:stream-event?` *obj* [Function]
Is *obj* a `Stream_event` object?

`ly:string-percent-encode` *str* [Function]
Encode all characters in string *str* with hexadecimal percent escape sequences, with the following exceptions: characters `-`, `.`, `/`, and `_`; and characters in ranges `0-9`, `A-Z`, and `a-z`.

`ly:string-substitute` *a b s* [Function]
Replace string *a* by string *b* in string *s*.

`ly:success` *str rest* [Function]
A Scheme callable function to issue a success message *str*. The message is formatted with `format` and *rest*.

`ly:system-font-load` *name* [Function]
Load the OpenType system font '*name*`.otf`'. Fonts loaded with this command must contain three additional SFNT font tables called `LILC`, `LILF`, and `LILY`, needed for typesetting musical elements. Currently, only the Emmentaler and the Emmentaler-Brace fonts fulfill these requirements.

Note that only `ly:font-get-glyph` and derived code (like `\lookup`) can access glyphs from the system fonts; text strings are handled exclusively via the Pango interface.

`ly:text-interface::interpret-markup` [Function]
Convert a text markup into a stencil. Takes three arguments, *layout*, *props*, and *markup*.

layout is a `\layout` block; it may be obtained from a grob with `ly:grob-layout`. *props* is an alist chain, i.e. a list of alists. This is typically obtained with `(ly:grob-alist-chain grob (ly:output-def-lookup layout 'text-font-defaults))`. *markup* is the markup text to be processed.

`ly:translator?` *x* [Function]
Is *x* a `Translator` object?

`ly:translator-context` *trans* [Function]
Return the context of the translator object *trans*.

`ly:translator-description` *me* [Function]
Return an alist of properties of translator *me*.

`ly:translator-group?` *x* [Function]
Is *x* a `Translator_group` object?

`ly:translator-name` *trans* [Function]
Return the type name of the translator object *trans*. The name is a symbol.

`ly:transpose-key-alist` *l pit* [Function]
Make a new key alist of *l* transposed by pitch *pit*.

`ly:truncate-list!` *lst i* [Function]
Take at most the first *i* of list *lst*.

`ly:ttf->pfa` *ttf-file-name idx* [Function]
Convert the contents of a TrueType font file to PostScript Type 42 font, returning it as a string. The optional *idx* argument is useful for TrueType collections (TTC) only; it specifies the font index within the TTC. The default value of *idx* is 0.

`ly:ttf-ps-name` *ttf-file-name idx* [Function]
Extract the PostScript name from a TrueType font. The optional *idx* argument is useful for TrueType collections (TTC) only; it specifies the font index within the TTC. The default value of *idx* is 0.

`ly:unit` [Function]
Return the unit used for lengths as a string.

`ly:usage` [Function]
Print usage message.

`ly:version` [Function]
Return the current lilypond version as a list, e.g., `(1 3 127 uu1)`.

`ly:warning` *str rest* [Function]
A Scheme callable function to issue the warning *str*. The message is formatted with `format` and *rest*.

`ly:wide-char->utf-8` *wc* [Function]
Encode the Unicode codepoint *wc*, an integer, as UTF-8.

Appendix A Indices

A.1 Concept index

(Index is nonexistent)

A.2 Function index

ly:add-context-mod ... 494
ly:add-file-name-alist ... 494
ly:add-interface ... 494
ly:add-listener ... 494
ly:add-option ... 494
ly:all-grob-interfaces ... 494
ly:all-options ... 494
ly:all-stencil-expressions ... 494
ly:assoc-get ... 494
ly:axis-group-interface::add-element ... 494
ly:beam-score-count ... 494
ly:book-add-bookpart! ... 494
ly:book-add-score! ... 494
ly:book-book-parts ... 494
ly:book-header ... 494
ly:book-paper ... 494
ly:book-process ... 494
ly:book-process-to-systems ... 495
ly:book-scores ... 495
ly:box? ... 495
ly:bp ... 495
ly:bracket ... 495
ly:broadcast ... 495
ly:camel-case->lisp-identifier ... 495
ly:chain-assoc-get ... 495
ly:cm ... 495
ly:command-line-code ... 495
ly:command-line-options ... 495
ly:command-line-verbose? ... 495
ly:connect-dispatchers ... 495
ly:context-current-moment ... 495
ly:context-event-source ... 495
ly:context-events-below ... 495
ly:context-find ... 496
ly:context-grob-definition ... 496
ly:context-id ... 496
ly:context-name ... 496
ly:context-now ... 496
ly:context-parent ... 496
ly:context-property ... 496
ly:context-property-where-defined ... 496
ly:context-pushpop-property ... 496
ly:context-set-property! ... 496
ly:context-unset-property ... 496
ly:context? ... 495
ly:default-scale ... 496
ly:dimension? ... 496
ly:dir? ... 496
ly:dispatcher? ... 496
ly:duration->string ... 496
ly:duration-dot-count ... 497
ly:duration-factor ... 497
ly:duration-length ... 497
ly:duration-log ... 497
ly:duration<? ... 496
ly:duration? ... 496
ly:effective-prefix ... 497
ly:encode-string-for-pdf ... 497
ly:engraver-announce-end-grob ... 497
ly:engraver-make-grob ... 497
ly:error ... 497
ly:eval-simple-closure ... 497
ly:event-deep-copy ... 497
ly:event-property ... 497
ly:event-set-property! ... 497
ly:expand-environment ... 497
ly:export ... 497
ly:find-file ... 497
ly:font-config-add-directory ... 497
ly:font-config-add-font ... 497
ly:font-config-display-fonts ... 498
ly:font-config-get-font-file ... 498
ly:font-design-size ... 498
ly:font-file-name ... 498
ly:font-get-glyph ... 498
ly:font-glyph-name-to-charcode ... 498
ly:font-glyph-name-to-index ... 498
ly:font-index-to-charcode ... 498
ly:font-magnification ... 498
ly:font-metric? ... 498
ly:font-name ... 498
ly:font-sub-fonts ... 498
ly:format ... 498
ly:format-output ... 498
ly:get-all-function-documentation ... 499
ly:get-all-translators ... 499
ly:get-context-mods ... 499
ly:get-listened-event-classes ... 499
ly:get-option ... 499
ly:gettext ... 499
ly:grob-alist-chain ... 499
ly:grob-array->list ... 499
ly:grob-array-length ... 499
ly:grob-array-ref ... 499
ly:grob-array? ... 499
ly:grob-basic-properties ... 499
ly:grob-chain-callback ... 499
ly:grob-common-refpoint ... 499
ly:grob-common-refpoint-of-array ... 499
ly:grob-default-font ... 499
ly:grob-extent ... 499
ly:grob-interfaces ... 499
ly:grob-layout ... 500
ly:grob-object ... 500

ly:grob-original 500
ly:grob-parent 500
ly:grob-pq<? 500
ly:grob-properties 500
ly:grob-property 500
ly:grob-property-data 500
ly:grob-relative-coordinate 500
ly:grob-robust-relative-extent 500
ly:grob-script-priority-less 500
ly:grob-set-nested-property! 500
ly:grob-set-object! 500
ly:grob-set-parent! 500
ly:grob-set-property! 500
ly:grob-staff-position 500
ly:grob-suicide! 500
ly:grob-system 500
ly:grob-translate-axis! 500
ly:grob? 499
ly:gulp-file 501
ly:hash-table-keys 501
ly:inch 501
ly:input-both-locations 501
ly:input-file-line-char-column 501
ly:input-location? 501
ly:input-message 501
ly:interpret-music-expression 501
ly:interpret-stencil-expression 501
ly:intlog2 501
ly:is-listened-event-class 501
ly:item-break-dir 501
ly:item? 501
ly:iterator? 501
ly:lexer-keywords 501
ly:lily-lexer? 501
ly:lily-parser? 501
ly:listener? 501
ly:make-book 502
ly:make-book-part 502
ly:make-dispatcher 502
ly:make-duration 502
ly:make-global-context 502
ly:make-global-translator 502
ly:make-listener 502
ly:make-moment 502
ly:make-music 502
ly:make-music-function 502
ly:make-output-def 502
ly:make-page-label-marker 502
ly:make-page-permission-marker 502
ly:make-pango-description-string 502
ly:make-paper-outputter 503
ly:make-pitch 503
ly:make-prob 503
ly:make-scale 503
ly:make-score 503
ly:make-simple-closure 503
ly:make-stencil 503
ly:make-stream-event 503
ly:message 503
ly:minimal-breaking 503
ly:mm 503
ly:module->alist 503
ly:module-copy 503
ly:modules-lookup 503
ly:moment-add 504
ly:moment-div 504
ly:moment-grace-denominator 504
ly:moment-grace-numerator 504
ly:moment-main-denominator 504
ly:moment-main-numerator 504
ly:moment-mod 504
ly:moment-mul 504
ly:moment-sub 504
ly:moment<? 504
ly:moment? 503
ly:music-compress 504
ly:music-deep-copy 504
ly:music-duration-compress 504
ly:music-duration-length 504
ly:music-function-extract 504
ly:music-function? 504
ly:music-length 504
ly:music-list? 504
ly:music-mutable-properties 505
ly:music-output? 505
ly:music-property 505
ly:music-set-property! 505
ly:music-transpose 505
ly:music? 504
ly:note-column-accidentals 505
ly:note-column-dot-column 505
ly:note-head::stem-attachment 505
ly:number->string 505
ly:optimal-breaking 505
ly:option-usage 505
ly:otf->cff 505
ly:otf-font-glyph-info 505
ly:otf-font-table-data 505
ly:otf-font? 505
ly:otf-glyph-count 505
ly:otf-glyph-list 505
ly:output-def-clone 506
ly:output-def-lookup 506
ly:output-def-parent 506
ly:output-def-scope 506
ly:output-def-set-variable! 506
ly:output-def? 505
ly:output-description 506
ly:output-formats 506
ly:outputter-close 506
ly:outputter-dump-stencil 506
ly:outputter-dump-string 506
ly:outputter-module 506
ly:outputter-output-scheme 506
ly:outputter-port 506
ly:page-marker? 506
ly:page-turn-breaking 506
ly:pango-font-physical-fonts 506
ly:pango-font? 506
ly:paper-book-header 506
ly:paper-book-pages 507
ly:paper-book-paper 507
ly:paper-book-performances 507
ly:paper-book-scopes 507
ly:paper-book-systems 507
ly:paper-book? 506
ly:paper-fonts 507
ly:paper-get-font 507
ly:paper-get-number 507
ly:paper-outputscale 507

ly:paper-score-paper-systems 507
ly:paper-system-minimum-distance 507
ly:paper-system? 507
ly:parse-file 507
ly:parser-clear-error 507
ly:parser-clone 507
ly:parser-define! 507
ly:parser-error 507
ly:parser-has-error? 507
ly:parser-include-string 507
ly:parser-lexer 508
ly:parser-lookup 508
ly:parser-output-name 508
ly:parser-parse-string 508
ly:parser-set-note-names 508
ly:parser-set-repetition-function 508
ly:parser-set-repetition-symbol 508
ly:performance-write 508
ly:pfb->pfa 508
ly:pitch-alteration 508
ly:pitch-diff 508
ly:pitch-negate 508
ly:pitch-notename 508
ly:pitch-octave 508
ly:pitch-quartertones 508
ly:pitch-semitones 508
ly:pitch-steps 508
ly:pitch-transpose 509
ly:pitch<? 508
ly:pitch? 508
ly:pointer-group-interface::add-grob 509
ly:position-on-line? 509
ly:prob-immutable-properties 509
ly:prob-mutable-properties 509
ly:prob-property 509
ly:prob-property? 509
ly:prob-set-property! 509
ly:prob-type? 509
ly:prob? 509
ly:programming-error 509
ly:progress 509
ly:property-lookup-stats 509
ly:protects 509
ly:pt 509
ly:register-stencil-expression 509
ly:relative-group-extent 509
ly:reset-all-fonts 509
ly:round-filled-box 510
ly:round-filled-polygon 510
ly:run-translator 510
ly:score-add-output-def! 510
ly:score-embedded-format 510
ly:score-error? 510
ly:score-header 510
ly:score-music 510
ly:score-output-defs 510
ly:score-set-header! 510
ly:score? 510
ly:set-default-scale 510
ly:set-grob-creation-callback 510
ly:set-grob-modification-callback 510
ly:set-middle-C! 511
ly:set-option 511
ly:set-property-cache-callback 511
ly:simple-closure? 511
ly:skyline-pair? 511
ly:skyline? 511
ly:slur-score-count 511
ly:smob-protects 511
ly:solve-spring-rod-problem 511
ly:source-file? 511
ly:spanner-bound 511
ly:spanner-broken-into 511
ly:spanner-set-bound! 511
ly:spanner? 511
ly:spawn 511
ly:staff-symbol-line-thickness 512
ly:staff-symbol-staff-space 512
ly:start-environment 512
ly:stderr-redirect 512
ly:stencil-add 512
ly:stencil-aligned-to 512
ly:stencil-combine-at-edge 512
ly:stencil-empty? 512
ly:stencil-expr 512
ly:stencil-extent 512
ly:stencil-fonts 512
ly:stencil-in-color 512
ly:stencil-rotate 512
ly:stencil-rotate-absolute 512
ly:stencil-scale 512
ly:stencil-translate 512
ly:stencil-translate-axis 513
ly:stencil? 512
ly:stream-event? 513
ly:string-percent-encode 513
ly:string-substitute 513
ly:success 513
ly:system-font-load 513
ly:text-interface::interpret-markup 513
ly:translator-context 513
ly:translator-description 513
ly:translator-group? 513
ly:translator-name 513
ly:translator? 513
ly:transpose-key-alist 513
ly:truncate-list! 513
ly:ttf->pfa 513
ly:ttf-ps-name 514
ly:unit 514
ly:usage 514
ly:version 514
ly:warning 514
ly:wide-char->utf-8 514